

Measurement Results

1-7810/19-03-06_log1_conducted

[Test logging](#)

This addendum is electronically signed and valid without handwritten signature.
For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorized:

Mihail Dorongovskij
Lab Manager
Radio Communications & EMC

Table of Content

IUT Summary	3
1. FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE coded S8	4
2. FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE coded S8	7
3. FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE coded S8	10
4. FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE coded S8	13
5. FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE coded S8	15
6. FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE coded S8	17
7. FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE coded S8	19
8. FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE coded S8	21
9. FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE coded S8	23
10. FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE coded S8	25
11. FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE coded S8	28
12. FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE coded S8	31
13. FCC Part 15.247 TX Spurious Conducted ~ BT LE coded S8	34
14. FCC Part 15.247 TX Spurious Conducted ~ BT LE coded S8	36
15. FCC Part 15.247 TX Spurious Conducted ~ BT LE coded S8	38
16. FCC Part 15.247 Restricted Band Edge Conducted Peak DTS Video Avg ~ BT LE coded S8	40
17. FCC Part 15.247 Restricted Band Edge Conducted Peak DTS Video Avg ~ BT LE coded S8	42

IUT Summary

IUT DEFINITION & Common settings	
Manufacturer	ABITRON
Type	CMB-1
Serial No. Setup No.	B00007 1.0
SW Version HW Version	NI NI
Comment 1 2	Power setting 6 dBm
Tlow Tmid Thigh [°C]	-40 20 85
Vlow Vmid Vhigh [V] @Imax [A]	3.1 3.6 5.5 @1
Auto Control enabled Power Supply Climatic Box	No No
Antenna Gain [dBi]	0
Additional Path Loss [dB]	0.5

IUT Common Settings BT Low Energy	
Intermodulation Value N	3
Image Freq. Low Mid High [MHz]	0 0 0
Power Class	2
1 Mbps supported	False TXpayload 255 RXpayload 255
2 Mbps supported	False TXpayload 255 RXpayload 255
Longrange S8 supported	True TXpayload 255 RXpayload 255
Longrange S2 supported	False TXpayload 255 RXpayload 255
Signaling Settings	None
Signaling RF Settings	None
User Interaction	Yes
Switch Matrix & Pathcompensation enabled	Yes

1. FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE coded S8

Test References	
TC Start	03.03.2020 10:51:14
System Version	1.0.0.33
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.1 RBW $\geq$ DTS Bandwidth
Class / TC Version	TC_VM_FCC15247_Maximum_Peak_Conducted_Output_Power_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Conducted DTS - BT LE coded S8
Add. Information	


Test Parameter	
Technology to test	BT LE coded S8
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2402
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60

Test at TX 2402 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	RESET OK

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	9.27 10.31 15				
Start [MHz] Stop [MHz]	2401.000 2403.000				
RBW [MHz] VBW [MHz]	0.100000 0.300000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE				


DTS Bandwidth					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	---	---	754	kHz	INFO



Plot_FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE coded S8 DTS BW_03032020_105141.png

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.27 10.31 20				
Start [MHz] Stop [MHz]	2401.000 2403.000				
RBW [MHz] VBW [MHz]	2.000000 5.000000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	50 200 1001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	30.00	4.35	dBm	PASS
Peak Power	---	1000	2.722701	mW	PASS
Frequency at Peak	---	---	2401.736	MHz	INFO



Plot_FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE coded S8_03032020_105157.png

TEST FINISHED

General Verdict

03.03.2020 10:51:57 / RT: 43 s

PASS

2. FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE coded S8

Test References	
TC Start	03.03.2020 11:43:03
System Version	1.0.0.33
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.1 RBW $\geq$ DTS Bandwidth
Class / TC Version	TC_VM_FCC15247_Maximum_Peak_Conducted_Output_Power_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Conducted DTS - BT LE coded S8
Add. Information	


Test Parameter	
Technology to test	BT LE coded S8
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2402
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60

Test at TX 2440 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	RESET OK


READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	9.10 10.4 15				
Start [MHz] Stop [MHz]	2439.000 2441.000				
RBW [MHz] VBW [MHz]	0.100000 0.300000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE				

DTS Bandwidth					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	---	---	686	kHz	INFO



READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.10 10.4 20				
Start [MHz] Stop [MHz]	2439.000 2441.000				
RBW [MHz] VBW [MHz]	1.000000 5.000000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	50 200 1001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	30.00	4.13	dBm	PASS
Peak Power	---	1000	2.588213	mW	PASS
Frequency at Peak	---	---	2439.752	MHz	INFO



Plot_FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE coded S8_03032020_114347.png

TEST FINISHED		
General Verdict	03.03.2020 11:43:47 / RT: 44 s	PASS

3. FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE coded S8

Test References	
TC Start	03.03.2020 12:49:25
System Version	1.0.0.33
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.3.1.1 RBW $\geq$ DTS Bandwidth
Class / TC Version	TC_VM_FCC15247_Maximum_Peak_Conducted_Output_Power_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Maximum Peak Output Power Conducted DTS - BT LE coded S8
Add. Information	


Test Parameter	
Technology to test	BT LE coded S8
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2402
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60

Test at TX 2480 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	RESET OK

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	9.45 10.45 15				
Start [MHz] Stop [MHz]	2479.000 2481.000				
RBW [MHz] VBW [MHz]	0.100000 0.300000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE				


DTS Bandwidth					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	---	---	736	kHz	INFO



Plot_FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE coded S8 DTS BW_03032020_124952.png

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.45 10.45 20				
Start [MHz] Stop [MHz]	2479.000 2481.000				
RBW [MHz] VBW [MHz]	1.000000 5.000000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	50 200 1001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	30.00	4.52	dBm	PASS
Peak Power	---	1000	2.831392	mW	PASS
Frequency at Peak	---	---	2480.266	MHz	INFO



Plot_FCC Part 15.247 Maximum Peak Conducted Output Power DTS ~ BT LE coded S8_03032020_125008.png

TEST FINISHED

General Verdict

03.03.2020 12:50:08 / RT: 43 s

PASS

4. FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE coded S8

Test References	
TC Start	03.03.2020 10:52:01
System Version	1.0.0.33
Test Specification	FCC Part 15.247
Test Method	99
Class / TC Version	TC_VM_FCC15247_Bandwidth_6dB_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Bandwidth 6dB DTS - BT LE coded S8
Add. Information	


Test Parameter	
Technology to test	BT LE coded S8
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2402
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60

Test at TX 2402 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	RESET OK

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	9.30 10.31 15				
Start [MHz] Stop [MHz]	2401.000 2403.000				
RBW [MHz] VBW [MHz]	0.100000 0.300000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	747	kHz	PASS



Plot_FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE coded S8_03032020_105229.png

TEST FINISHED		
General Verdict	03.03.2020 10:52:29 / RT: 28 s	PASS

5. FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE coded S8

Test References	
TC Start	03.03.2020 11:43:51
System Version	1.0.0.33
Test Specification	FCC Part 15.247
Test Method	99
Class / TC Version	TC_VM_FCC15247_Bandwidth_6dB_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Bandwidth 6dB DTS - BT LE coded S8
Add. Information	


Test Parameter	
Technology to test	BT LE coded S8
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2402
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60

Test at TX 2440 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	RESET OK

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	9.07 10.4 15				
Start [MHz] Stop [MHz]	2439.000 2441.000				
RBW [MHz] VBW [MHz]	0.100000 0.300000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	688	kHz	PASS



TEST FINISHED		
General Verdict	03.03.2020 11:44:19 / RT: 28 s	PASS

6. FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE coded S8

Test References	
TC Start	03.03.2020 12:50:13
System Version	1.0.0.33
Test Specification	FCC Part 15.247
Test Method	99
Class / TC Version	TC_VM_FCC15247_Bandwidth_6dB_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Bandwidth 6dB DTS - BT LE coded S8
Add. Information	


Test Parameter	
Technology to test	BT LE coded S8
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2402
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60

Test at TX 2480 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	RESET OK

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	9.49 10.45 15				
Start [MHz] Stop [MHz]	2479.000 2481.000				
RBW [MHz] VBW [MHz]	0.100000 0.300000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	50 200 10001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
DTS Bandwidth (6dB)	500	---	731	kHz	PASS



Plot_FCC Part 15.247 Bandwidth 6dB DTS ~ BT LE coded S8_03032020_125040.png

TEST FINISHED		
General Verdict	03.03.2020 12:50:41 / RT: 28 s	PASS

7. FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE coded S8

Test References	
TC Start	03.03.2020 10:52:34
System Version	1.0.0.33
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
Class / TC Version	TC_VM_FCC15247_Peak_Power_Spectral_Density_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - BT LE coded S8
Add. Information	


Test Parameter	
Technology to test	BT LE coded S8
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2402
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60

Test at TX 2402 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	RESET OK

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			9.29 10.31 15		
Start [MHz] Stop [MHz]			2401.250 2402.750		
RBW [MHz] VBW [MHz]			0.003000 0.010000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			1000 20 1001 SWE		

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-1.7	dBm/3KHz	PASS



Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE coded S8_03032020_105310.png

TEST FINISHED		
General Verdict	03.03.2020 10:53:11 / RT: 37 s	PASS

8. FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE coded S8

Test References	
TC Start	03.03.2020 11:44:23
System Version	1.0.0.33
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
Class / TC Version	TC_VM_FCC15247_Peak_Power_Spectral_Density_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - BT LE coded S8
Add. Information	


Test Parameter	
Technology to test	BT LE coded S8
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2402
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60

Test at TX 2440 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	RESET OK

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	9.11 10.4 15				
Start [MHz] Stop [MHz]	2439.250 2440.750				
RBW [MHz] VBW [MHz]	0.003000 0.010000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-2.25	dBm/3KHz	PASS



Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE coded S8_03032020_114500.png

TEST FINISHED		
General Verdict	03.03.2020 11:45:00 / RT: 37 s	PASS

9. FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE coded S8

Test References	
TC Start	03.03.2020 12:50:45
System Version	1.0.0.33
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - Chapter 8.4 DTS maximum power spectral density level in the fundamental emission
Class / TC Version	TC_VM_FCC15247_Peak_Power_Spectral_Density_DTS_V01 Version: 0.0.1
My Description	FCC 15.247 Peak Power Spectral Density DTS - BT LE coded S8
Add. Information	


Test Parameter	
Technology to test	BT LE coded S8
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2402
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60

Test at TX 2480 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	RESET OK

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	9.47 10.45 15				
Start [MHz] Stop [MHz]	2479.250 2480.750				
RBW [MHz] VBW [MHz]	0.003000 0.010000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	1000 20 1001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Peak power Density	---	8	-1.61	dBm/3KHz	PASS



Plot_FCC Part 15.247 Peak Power Spectral Density DTS ~ BT LE coded S8_03032020_125122.png

TEST FINISHED		
General Verdict	03.03.2020 12:51:22 / RT: 37 s	PASS

10. FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE coded S8

Test References	
TC Start	03.03.2020 10:53:15
System Version	1.0.0.33
Test Specification	FCC Part 15.247
Test Method	
Class / TC Version	TC_VM_FCC15247_Bandwidth_99PCT_20dB_DTS_FHSS_V01 Version: 0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - BT LE coded S8
Add. Information	



Test Parameter	
Technology to test	BT LE coded S8
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2402
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60

Test at TX 2402 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	RESET OK

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			9.30 10.31 15		
Start [MHz] Stop [MHz]			2401.000 2403.000		
RBW [MHz] VBW [MHz]			0.020000 0.050000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			50 200 10001 SWE		

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	1086	kHz	INFO
T1 99%	2400.000000	---	2401.4563	MHz	PASS
T2 99%	---	2483.500000	2402.5419	MHz	PASS



RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	1146	kHz	INFO
T1 20DB	2400.000000	---	2401.4258	MHz	PASS



T2 20dB

2483.500000

2402.5722

MHz

PASS



TEST FINISHED

General Verdict

03.03.2020 10:53:56 / RT: 41 s

PASS

11. FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE coded S8

Test References	
TC Start	03.03.2020 11:45:04
System Version	1.0.0.33
Test Specification	FCC Part 15.247
Test Method	
Class / TC Version	TC_VM_FCC15247_Bandwidth_99PCT_20dB_DTS_FHSS_V01 Version: 0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - BT LE coded S8
Add. Information	



Test Parameter	
Technology to test	BT LE coded S8
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2402
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60

Test at TX 2440 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	RESET OK

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			9.08 10.4 15		
Start [MHz] Stop [MHz]			2439.000 2441.000		
RBW [MHz] VBW [MHz]			0.020000 0.050000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			50 200 10001 SWE		

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	1058	kHz	INFO
T1 99%	2400.000000	---	2439.4699	MHz	PASS
T2 99%	---	2483.500000	2440.5277	MHz	PASS



RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	1106	kHz	INFO
T1 20DB	2400.000000	---	2439.4488	MHz	PASS


T2 20dB

2483.500000


2440.5548

MHz

PASS



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE coded S8 20dB_03032020_114542.png



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE coded S8_03032020_114545.png

TEST FINISHED

General Verdict

03.03.2020 11:45:46 / RT: 41 s

PASS

12. FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE coded S8

Test References	
TC Start	03.03.2020 12:51:26
System Version	1.0.0.33
Test Specification	FCC Part 15.247
Test Method	
Class / TC Version	TC_VM_FCC15247_Bandwidth_99PCT_20dB_DTS_FHSS_V01 Version: 0.0.2
My Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - BT LE coded S8
Add. Information	



Test Parameter	
Technology to test	BT LE coded S8
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2402
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60

Test at TX 2480 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	RESET OK

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			9.51 10.45 15		
Start [MHz] Stop [MHz]			2479.000 2481.000		
RBW [MHz] VBW [MHz]			0.020000 0.050000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			50 200 10001 SWE		

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	1082	kHz	INFO
T1 99%	2400.000000	---	2479.4565	MHz	PASS
T2 99%	---	2483.500000	2480.5383	MHz	PASS



RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 20dB	---	---	1145	kHz	INFO
T1 20DB	2400.000000	---	2479.4254	MHz	PASS


T2 20dB

2483.500000


2480.5704

MHz

PASS



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE coded S8_03032020_125203.png



Plot_FCC Part 15.247 Bandwidth 99PCT-20dB ~ BT LE coded S8_03032020_125207.png

TEST FINISHED

General Verdict

03.03.2020 12:52:08 / RT: 41 s

PASS

13. FCC Part 15.247 TX Spurious Conducted ~ BT LE coded S8

Test References	
TC Start	03.03.2020 10:54:01
System Version	1.0.0.33
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
Class / TC Version	TC_VM_FCC15247_TX_Emissions_Conducted_V01 Version: 0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - BT LE coded S8
Add. Information	



Test Parameter	
Technology to test	BT LE coded S8
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2402
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60

Test at TX 2402 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	RESET OK

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	9.58 0 25				
Start [MHz] Stop [MHz]	24530.000 25030.000				
RBW [MHz] VBW [MHz]	0.100000 0.300000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2401.83 MHz	---	---	0.64	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 16793.667 MHz	0	---	18.94	dB	INFO



TEST FINISHED		
General Verdict	03.03.2020 10:58:55 / RT: 294 s	PASS

14. FCC Part 15.247 TX Spurious Conducted ~ BT LE coded S8

Test References	
TC Start	03.03.2020 11:45:50
System Version	1.0.0.33
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
Class / TC Version	TC_VM_FCC15247_TX_Emissions_Conducted_V01 Version: 0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - BT LE coded S8
Add. Information	


Test Parameter	
Technology to test	BT LE coded S8
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2402
Frequency mid to test	True Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60

Test at TX 2440 MHz


DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	RESET OK

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]			9.32 0 25		
Start [MHz] Stop [MHz]			24530.000 25030.000		
RBW [MHz] VBW [MHz]			0.100000 0.300000		
Detector TraceMode			POS MAXH		
Sweep: Time [ms] Count Points per Section Type			500 8 3001 SWE		

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2440.00 MHz	---	---	0.89	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 17299.667 MHz	0	---	19.04	dB	INFO



Plot_FCC Part 15.247 TX Spurious Conducted ~ BT LE coded S8 2440_03032020_115040.png



Plot_FCC Part 15.247 TX Spurious Conducted ~ BT LE coded S8 2440_03032020_115043.png

TEST FINISHED		
General Verdict	03.03.2020 11:50:44 / RT: 293 s	PASS

15. FCC Part 15.247 TX Spurious Conducted ~ BT LE coded S8

Test References	
TC Start	03.03.2020 12:52:12
System Version	1.0.0.33
Test Specification	FCC Part 15.247
Test Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable.
Class / TC Version	TC_VM_FCC15247_TX_Emissions_Conducted_V01 Version: 0.0.1
My Description	FCC 15.247 TX Emissions Conducted DTS - BT LE coded S8
Add. Information	



Test Parameter	
Technology to test	BT LE coded S8
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2402
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60

Test at TX 2480 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	RESET OK

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	9.69 0 25				
Start [MHz] Stop [MHz]	24530.000 25030.000				
RBW [MHz] VBW [MHz]	0.100000 0.300000				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	500 8 3001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Reference @ 2480.33 MHz	---	---	0.91	dBm	INFO
No peaks detected	---	---			PASS
Lowest margin to limit 15301.667 MHz	0	---	18.98	dB	INFO



TEST FINISHED		
General Verdict	03.03.2020 12:57:06 / RT: 294 s	PASS

16. FCC Part 15.247 Restricted Band Edge Conducted Peak DTS Video Avg ~ BT LE coded S8

Test References	
TC Start	03.03.2020 10:58:59
System Version	1.0.0.33
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - 8.7.3 Integration Method; ANSI C63.10-2013 11.13.3.2 Peak Detection
Class / TC Version	TC_VM_FCC15247_Restricted_Band_Edge_Conducted_Peak_V01 Version: 0.0.1
My Description	FCC 15.247 Restricted Band Edge Conducted Peak DTS - BT LE coded S8
Add. Information	


Test Parameter	
Technology to test	BT LE coded S8
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	True Freq [MHz] 2402
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	False Freq [MHz] 2480
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60

Test at TX 2402 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	RESET OK

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	9.31 10.31 15				
Start [MHz] Stop [MHz]	2388.000 2390.000				
RBW [MHz] VBW [MHz]	0.100000 0.000200				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	78 300 1001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Band Power without Antenna Gain	---	-41.23	-61.64	dBm	Information
Band Power incl. Antenna Gain	---	-41.23	-61.64	dBm	PASS



TEST FINISHED		
General Verdict	03.03.2020 10:59:42 / RT: 43 s	PASS

17. FCC Part 15.247 Restricted Band Edge Conducted Peak DTS Video Avg ~ BT LE coded S8

Test References	
TC Start	03.03.2020 12:57:10
System Version	1.0.0.33
Test Specification	FCC Part 15.247
Test Method	DTS: KDB 558074 D01 V05 - 8.7.3 Integration Method; ANSI C63.10-2013 11.13.3.2 Peak Detection
Class / TC Version	TC_VM_FCC15247_Restricted_Band_Edge_Conducted_Peak_V01 Version: 0.0.1
My Description	FCC 15.247 Restricted Band Edge Conducted Peak DTS - BT LE coded S8
Add. Information	


Test Parameter	
Technology to test	BT LE coded S8
Antenna Port used	1
Temperature	mid
Voltage	mid
Frequency low to test	False Freq [MHz] 2402
Frequency mid to test	False Freq [MHz] 2440
Frequency high to test	True Freq [MHz] 2480
Switched Path	IUT - SignalingUnit - SpectrumAnalyzer
Devices in use	SA: Rohde&Schwarz,FSV-30,1321.3008K30/103170,3.60

Test at TX 2480 MHz

DTM Connection check					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Connection result	---	---	---	---	RESET OK

READ SA SETTINGS:					
RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	9.43 10.45 15				
Start [MHz] Stop [MHz]	2483.500 2485.500				
RBW [MHz] VBW [MHz]	0.100000 0.000200				
Detector TraceMode	POS MAXH				
Sweep: Time [ms] Count Points per Section Type	78 300 1001 SWE				

RESULT					
Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Band Power without Antenna Gain	---	-41.23	-58.25	dBm	Information
Band Power incl. Antenna Gain	---	-41.23	-58.25	dBm	PASS



TEST FINISHED		
General Verdict	03.03.2020 12:57:54 / RT: 43 s	PASS

- END OF DOCUMENT -