



MEASUREMENT REPORT

FCC PART 15.247 WLAN 802.11b/g/n

FCC ID: 2AC9MDSL2401HNT1C

APPLICANT: Wuxi Mitrastar Technology Co., Ltd

Application Type: Certification

Product: BHS VDSL VoIP

Model No.: DSL-2401HNU-T1C, DSL-2401HN-T1C

Trademark: MitraStar

FCC Classification: Digital Transmission System (DTS)

FCC Rule Part(s): Part 15.247

Test Procedure(s): ANSI C63.10-2013, KDB 558074 D01v03r02,
KDB 662911 D01v02r01

Test Date: Apr. 09 ~ 12, 2015

Reviewed By : Robin Wu
(Robin Wu)

Approved By : Marlin Chen
(Marlin Chen)



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 558074 D01v03r02. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date
1504RSU00101	Rev. 01	Initial report	04-21-2015
1504RSU00101	Rev. 02	Corrected the direction gain	04-22-2015

CONTENTS

Description	Page
§2.1033 General Information.....	5
1. INTRODUCTION	6
1.1. Scope	6
1.2. MRT Test Location.....	6
2. PRODUCT INFORMATION.....	7
2.1. Equipment Description	7
2.2. Applicable Standards	7
2.3. Working Frequencies	8
2.4. Description of Available Antennas	8
2.5. Description of Antenna RF Port	9
2.6. Test Mode	9
2.7. Test Software	9
2.8. Device Capabilities	10
2.9. Test Configuration.....	11
2.10. EMI Suppression Device(s)/Modifications.....	11
2.11. Labeling Requirements	11
3. DESCRIPTION of TEST	12
3.1. Evaluation Procedure.....	12
3.2. AC Line Conducted Emissions.....	12
3.3. Radiated Emissions	13
4. ANTENNA REQUIREMENTS	14
5. TEST EQUIPMENT CALIBRATION DATE	15
6. MEASUREMENT UNCERTAINTY	16
7. TEST RESULT	17
7.1. Summary	17
7.2. 6dB Bandwidth Measurement	18
7.2.1. Test Limit	18
7.2.2. Test Procedure used	18
7.2.3. Test Setting	18
7.2.4. Test Setup	18
7.2.5. Test Result	19
7.3. Output Power Measurement	31

7.3.1.	Test Limit	31
7.3.2.	Test Procedure Used.....	31
7.3.3.	Test Setting	31
7.3.4.	Test Setup	31
7.3.5.	Test Result of Output Power	32
7.4.	Power Spectral Density Measurement	35
7.4.1.	Test Limit	35
7.4.2.	Test Procedure Used.....	35
7.4.3.	Test Setting	35
7.4.4.	Test Setup	36
7.4.5.	Test Result	37
7.5.	Conducted Band Edge and Out-of-Band Emissions	48
7.5.1.	Test Limit	48
7.5.2.	Test Procedure Used.....	48
7.5.3.	Test Setting	48
7.5.4.	Test Setup	49
7.5.5.	Test Result	50
7.6.	Radiated Spurious Emission Measurement	72
7.6.1.	Test Limit	72
7.6.2.	Test Procedure Used.....	72
7.6.3.	Test Setting	72
7.6.4.	Test Setup	74
7.6.5.	Test Result	76
7.7.	Radiated Restricted Band Edge Measurement.....	106
7.7.1.	Test Result	106
7.8.	AC Conducted Emissions Measurement	170
7.8.1.	Test Limit	170
7.8.2.	Test Setup	170
7.8.3.	Test Result	171
8.	CONCLUSION	173

§2.1033 General Information

Applicant:	Wuxi Mitrastar Technology Co., Ltd
Applicant Address:	60#-E Minshan Road, High and New Technology Industrial Development Zone, Wuxi, Jiangsu Province, China
Manufacturer:	Wuxi Mitrastar Technology Co., Ltd
Manufacturer Address:	60#-E Minshan Road, High and New Technology Industrial Development Zone, Wuxi, Jiangsu Province, China
Test Site:	MRT Technology (Suzhou) Co., Ltd
Test Site Address:	D8 Building, Youxin Industrial Park, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
MRT Registration No.:	809388
FCC Rule Part(s):	Part 15.247
Model No.:	DSL-2401HNU-T1C, DSL-2401HN-T1C
FCC ID:	2AC9MDSL2401HNT1C
Test Device Serial No.:	N/A ☐ Production ☒ Pre-Production ☐ Engineering
FCC Classification:	Digital Transmission System (DTS)

Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Tian'edang Rd., Suzhou, China.

- MRT facility is a FCC registered (MRT Reg. No. 809388) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules.
- MRT facility is an IC registered (MRT Reg. No. 11384A-1) test laboratory with the site description on file at Industry Canada.
- MRT facility is a VCCI registered (R-4179, G-814, C-4664, T-2206) test laboratory with the site description on file at VCCI Council.
- MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (A2LA) under the American Association for Laboratory Accreditation Program (A2LA Cert. No. 3628.01) in EMC, Telecommunications and Radio testing for FCC, Industry Canada, EU and TELEC Rules.



1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taihu Lake. These measurement tests were conducted at the MRT Technology (Suzhou) Co., Ltd. Facility located at D8 Building, Youxin Industrial Park, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on September 30, 2013.



2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name	BHS VDSL VoIP
Model No.	DSL-2401HNU-T1C, DSL-2401HN-T1C
Frequency Range	802.11b/g/n-HT20: 2412 ~ 2462 MHz 802.11n-HT40: 2422 ~ 2452 MHz
Maximum Output Power	802.11b: 19.45dBm 802.11g: 17.87dBm 802.11n-HT20: 20.35dBm 802.11n-HT40: 19.90dBm
Type of Modulation	802.11b: DSSS 802.11g/n: OFDM

Note: There are different of USB Port between models, and evaluated the different models in “FCC DoC report”

2.2. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.207
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
- ANSI C63.10-2013

Note:

1. All the test items were verified and recorded according to the standards and without any deviation during the test.
2. FCC permits the use of the 1.5 meter table as an alternative in ANSI C63.10-2013 through inquiry tracking number 198796.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B recorded in a separate report.

2.3. Working Frequencies

Channel List for 802.11b/g/n-HT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz	N/A	N/A

Channel List for 802.11n-HT40

Channel	Frequency	Channel	Frequency	Channel	Frequency
03	2422 MHz	04	2427 MHz	05	2432 MHz
06	2437 MHz	07	2442 MHz	08	2447 MHz
09	2452 MHz	N/A	N/A	N/A	N/A


2.4. Description of Available Antennas

Antenna Type	Frequency Band (GHz)	T _x Paths	Max Peak Gain (dBi)	Directional Gain (dBi)
PCB Antenna	2.4	2	Ant 0: 3.5 Ant 1: 3.7	3.6

Note: Directional gain = $10 \log[(10^{G1/10} + 10^{G2/10} + \dots + 10^{GN/10})/N_{ANT}]$ dBi [Note the “20”s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]

2.5. Description of Antenna RF Port

RF Port				
Test Mode	Software Control Port			
2.4GHz T _x	Ant 1	Ant 2	--	--



2.6. Test Mode

Test Mode	Mode 1: Transmit by 802.11b
	Mode 2: Transmit by 802.11g
	Mode 3: Transmit by 802.11n-HT20
	Mode 4: Transmit by 802.11n-HT40

2.7. Test Software

The test utility software used during testing was “serial port instructions”, power parameter values are written in test software.


2.8. Device Capabilities

This device contains the following capabilities:

2.4GHz WLAN (DTS).

Note: 2.4GHz WLAN (DTS) operation is possible in 20MHz, and 40MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section 6.0 b) of KDB 558074 D01v03r02. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Test Mode	Duty Cycle
802.11b	97.3%
802.11g	90.7%
802.11n-HT20	86.5%
802.11n-HT40	78.7%



2.9. Test Configuration

The **BHS VDSL VoIP FCC ID: 2AC9MDSL2401HNT1C** was tested per the guidance of KDB 558074 D01v03r02. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.10. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.11. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase.

However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(a)(5).

Please see attachment for FCC ID label and label location.

3. DESCRIPTION of TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance provided in KDB 558074 D01v03r02 were used in the measurement of the **BHS VDSL VoIP FCC ID: 2AC9MDSL2401HNT1C**.

Deviation from measurement procedure.....None

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

Line conducted emissions test results are shown in Section 7.8.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of **BHS VDSL VoIP** is **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The **BHS VDSL VoIP FCC ID: 2AC9MDSL2401HNT1C** unit complies with the requirement of §15.203.

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions

Instrument	Manufacturer	Type No.	Serial No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR7	101209	1 year	2015/11/07
Two-Line V-Network	R&S	ENV216	101683	1 year	2015/11/07
Two-Line V-Network	R&S	ENV216	101684	1 year	2015/11/07
Temperature/ Meter Humidity	Anymetre	TH101B	SR2-01	1 year	2015/11/14

Radiated Emission

Instrument	Manufacturer	Type No.	Serial No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Agilent	E4447A	MY45300136	1 year	2015/10/09
EMI Test Receiver	R&S	ESR7	101209	1 year	2015/11/07
Preamplifier	MRT	AP18G40	S-001	1 year	2015/10/06
Preamplifier	Agilent	83017A	MY53270040	1 year	2015/12/13
Loop Antenna	Schwarzbeck	FMZB1519	1519-041	1 year	2015/11/08
TRILOG Antenna	Schwarzbeck	VULB9162	9162-047	1 year	2015/11/08
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1167	1 year	2015/11/08
Broadband Horn Antenna	Schwarzbeck	BBHA9170	9170-549	1 year	2016/01/05
Temperature/Humidity Meter	Anymetre	TH101B	AC1-01	1 year	2015/11/14

Conducted Test Equipment

Instrument	Manufacturer	Type No.	Serial No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Agilent	N9020A	MY52090106	1 year	2015/04/23
USB Wideband Power Sensor	Boonton	55006	8911	1 year	2015/10/15
Temperature/Humidity Meter	Anymetre	TH101B	TR3-01	1 year	2015/11/14

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 150kHz~30MHz: 3.46dB
Radiated Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 9kHz ~ 1GHz: 4.18dB 1GHz ~ 25GHz: 4.76dB

7. TEST RESULT

7.1. Summary

Product Name: BHS VDSL VoIP
FCC ID: 2AC9MDSL2401HNT1C
FCC Classification: Digital Transmission System (DTS)
Data Rate(s) Tested: 1Mbps ~ 11Mbps (b); 6Mbps ~ 54Mbps (g);
6.5/7.2Mbps ~ 130/144.4Mbps (n-HT20);
13.5/15Mbps ~ 270/300Mbps (n-HT40).

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	6dB Bandwidth	$\geq 500\text{kHz}$	Conducted	Pass	Section 7.2
15.247(b)(3)	Output Power	$\leq 30\text{dBm}$		Pass	Section 7.3
15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$		Pass	Section 7.4
15.247(d)	Band Edge / Out-of-Band Emissions	$\geq 30\text{dBc(Average)}$		Pass	Section 7.5
15.205 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	Radiated	Pass	Section 7.6 & 7.7
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	Line Conducted	Pass	Section 7.8

Notes:

- 1) All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.

7.2. 6dB Bandwidth Measurement

7.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


7.2.2. Test Procedure used

KDB 558074 D01v03r02 - Section 8.2 Option 2

7.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. Allow the trace was allowed to stabilize

7.2.4. Test Setup




7.2.5. Test Result

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
Ant 1						
802.11b	1	01	2412	9.60	≥ 0.5	Pass
802.11b	1	06	2437	10.04	≥ 0.5	Pass
802.11b	1	11	2462	9.58	≥ 0.5	Pass
802.11g	6	01	2412	15.07	≥ 0.5	Pass
802.11g	6	06	2437	15.12	≥ 0.5	Pass
802.11g	6	11	2462	15.13	≥ 0.5	Pass
802.11n-HT20	6.5	01	2412	15.12	≥ 0.5	Pass
802.11n-HT20	6.5	06	2437	15.11	≥ 0.5	Pass
802.11n-HT20	6.5	11	2462	15.11	≥ 0.5	Pass
802.11n-HT40	13.5	03	2422	35.10	≥ 0.5	Pass
802.11n-HT40	13.5	06	2437	33.87	≥ 0.5	Pass
802.11n-HT40	13.5	09	2452	35.09	≥ 0.5	Pass
Ant 2						
802.11n-HT20	6.5	01	2412	15.12	≥ 0.5	Pass
802.11n-HT20	6.5	06	2437	15.12	≥ 0.5	Pass
802.11n-HT20	6.5	11	2462	15.12	≥ 0.5	Pass
802.11n-HT40	13.5	03	2422	35.11	≥ 0.5	Pass
802.11n-HT40	13.5	06	2437	35.09	≥ 0.5	Pass
802.11n-HT40	13.5	09	2452	35.11	≥ 0.5	Pass


Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
Ant 1 / Ant 1 + 2						
802.11n-HT20	13.0	01	2412	15.11	≥0.5	Pass
802.11n-HT20	13.0	06	2437	15.12	≥0.5	Pass
802.11n-HT20	13.0	11	2462	15.12	≥0.5	Pass
802.11n-HT40	27.0	03	2422	35.07	≥0.5	Pass
802.11n-HT40	27.0	06	2437	32.61	≥0.5	Pass
802.11n-HT40	27.0	09	2452	32.62	≥0.5	Pass
Ant 2 / Ant 1 + 2						
802.11n-HT20	13.0	01	2412	15.12	≥0.5	Pass
802.11n-HT20	13.0	06	2437	15.13	≥0.5	Pass
802.11n-HT20	13.0	11	2462	15.12	≥0.5	Pass
802.11n-HT40	27.0	03	2422	35.10	≥0.5	Pass
802.11n-HT40	27.0	06	2437	35.07	≥0.5	Pass
802.11n-HT40	27.0	09	2452	35.10	≥0.5	Pass

802.11b 6dB Bandwidth - Ant 1


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11g 6dB Bandwidth - Ant 1


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT20 6dB Bandwidth - Ant 1


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT40 6dB Bandwidth - Ant 1


Channel 03 (2422MHz)



Channel 06 (2437MHz)




Channel 09 (2452MHz)




802.11n-HT20 6dB Bandwidth - Ant 2


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT40 6dB Bandwidth - Ant 2


Channel 03 (2422MHz)



Channel 06 (2437MHz)




Channel 09 (2452MHz)




802.11n-HT20 6dB Bandwidth - Ant 1 / Ant 1 + 2


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT40 6dB Bandwidth - Ant 1 / Ant 1 + 2


Channel 03 (2422MHz)



Channel 06 (2437MHz)




Channel 09 (2452MHz)




802.11n-HT20 6dB Bandwidth - Ant 2 / Ant 1 + 2


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT40 6dB Bandwidth - Ant 2 / Ant 1 + 2


Channel 03 (2422MHz)



Channel 06 (2437MHz)



Channel 09 (2452MHz)



7.3. Output Power Measurement

7.3.1. Test Limit

The maximum out power shall be less 1 Watt (30dBm).

7.3.2. Test Procedure Used


KDB 558074 D01v03r02 - Section 9.2.3.2 AVGPM-G Average Power Method

7.3.3. Test Setting

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

7.3.4. Test Setup



7.3.5. Test Result of Output Power

Power output test was verified over all data rates of each mode shown as below, and then choose the maximum power output (yellow marker) for final test of each channel.

MCS Index for 802.11n	N _{TX}	Data Rate (Mbps)					
		802.11b	802.11g	20MHz Bandwidth		40MHz Bandwidth	
				800ns GI	400ns GI	800ns GI	400ns GI
0	1	1	6	6.5	7.2	13.5	15.0
1	1	2	9	13.0	14.4	27.0	30.0
2	1	5.5	12	19.5	21.7	40.5	45.0
3	1	11	18	26.0	28.9	54.0	60.0
4	1	--	24	39.0	43.3	81.0	90.0
5	1	--	36	52.0	57.8	108.0	120.0
6	1	--	48	58.5	65.0	121.5	135.0
7	1	--	54	65.0	72.2	135.0	150.0
8	2	--	--	13.0	14.4	27.0	30.0
9	2	--	--	26.0	28.9	54.0	60.0
10	2	--	--	39.0	43.3	81.0	90.0
11	2	--	--	52.0	57.8	108.0	120.0
12	2	--	--	78.0	86.7	162.0	180.0
13	2	--	--	104.0	115.6	216.0	240.0
14	2	--	--	117.0	130.0	243.0	270.0
15	2	--	--	130.0	144.0	270.0	300.0

Output power at various data rates for Ant 1:

Test Mode	Bandwidth (MHz)	Channel No.	Frequency (MHz)	Data Rate (Mbps)	Average Power (dBm)
802.11b	20	6	2437	1	19.45
				5.5	19.02
				11	18.48
802.11g	20	6	2437	6	17.87
				24	17.28
				54	16.74
802.11n	20	6	2437	6.5	17.72
				52	17.02
				130	16.35
802.11n	40	6	2437	13.5	17.40
				108	16.87
				270	16.27

Test Result of Average Output Power

Test Mode	Data Rate (Mbps)	Channel No.	Freq. (MHz)	Ant 1 Average Power (dBm)	Ant 2 Average Power (dBm)	Total Average Power (dBm)	Limit (dBm)	Result
Ant 1								
11b	1	1	2412	19.45	--	19.45	≤30.0	Pass
11b	1	6	2437	19.45	--	19.45	≤30.0	Pass
11b	1	11	2462	19.43	--	19.43	≤30.0	Pass
11g	6	1	2412	14.88	--	14.88	≤30.0	Pass
11g	6	6	2437	17.87	--	17.87	≤30.0	Pass
11g	6	11	2462	14.73	--	14.73	≤30.0	Pass
11n-HT20	6.5	1	2412	12.77	--	12.77	≤30.0	Pass
11n-HT20	6.5	6	2437	17.72	--	17.72	≤30.0	Pass
11n-HT20	6.5	11	2462	12.62	--	12.62	≤30.0	Pass
11n-HT40	13.5	3	2422	11.42	--	11.42	≤30.0	Pass
11n-HT40	13.5	6	2437	17.40	--	17.40	≤30.0	Pass
11n-HT40	13.5	9	2452	11.47	--	11.47	≤30.0	Pass
Ant 2								
11n-HT20	6.5	1	2412	--	12.67	12.67	≤30.0	Pass
11n-HT20	6.5	6	2437	--	17.62	17.62	≤30.0	Pass
11n-HT20	6.5	11	2462	--	12.77	12.77	≤30.0	Pass
11n-HT40	13.5	3	2422	--	11.55	11.55	≤30.0	Pass
11n-HT40	13.5	6	2437	--	17.49	17.49	≤30.0	Pass
11n-HT40	13.5	9	2452	--	11.51	11.51	≤30.0	Pass
Ant 1 + 2								
11n-HT20	13.0	1	2412	12.41	12.58	15.51	≤30.0	Pass
11n-HT20	13.0	6	2437	17.21	17.46	20.35	≤30.0	Pass
11n-HT20	13.0	11	2462	11.98	12.55	15.28	≤30.0	Pass
11n-HT40	27.0	3	2422	10.83	11.10	13.98	≤30.0	Pass
11n-HT40	27.0	6	2437	16.72	17.06	19.90	≤30.0	Pass
11n-HT40	27.0	9	2452	10.48	11.00	13.76	≤30.0	Pass

Note: Total Average Power (dBm) = $10 \cdot \log\{10^{(\text{Ant 1 Average Power} / 10)} + 10^{(\text{Ant 2 Average Power} / 10)}\}$ (dBm).

7.4. Power Spectral Density Measurement

7.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.


7.4.2. Test Procedure Used

KDB 558074 D01v03r02 - Section 10.5 Method AVGPSD

7.4.3. Test Setting

1. Measure the duty cycle (x) of the transmitter output signal
2. Set instrument center frequency to DTS channel center frequency.
3. Set span to at least 1.5 times the OBW.
4. RBW = 10kHz
5. VBW = 30kHz
6. Detector = RMS
7. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
8. Sweep time = auto couple
9. Don't use sweep triggering. Allow sweep to "free run".
10. Employ trace averaging (RMS) mode over a minimum of 100 traces.
11. Use the peak marker function to determine the maximum amplitude level.
12. Add $10 \log (1/x)$, where x is the duty cycle measured in step (a, to the measured PSD to compute the average PSD during the actual transmission time.
13. Add Constant Factor = $10 \cdot \log(3\text{kHz} / 10\text{kHz}) = -5.23$

7.4.4. Test Setup




7.4.5. Test Result

Test Mode	Data Rate (Mbps)	Channel No.	Freq. (MHz)	Ant 1 AVGPSPD (dBm / 10kHz)	Ant 2 AVGPSPD (dBm / 10kHz)	Duty Cycle (%)	Constant Factor	Total AVGPSPD (dBm / 3kHz)	Limit (dBm / 3kHz)	Result
Ant 1										
11b	1	1	2412	-7.43	--	97.3	-5.23	-12.54	≤8.0	Pass
11b	1	6	2437	-6.83	--	97.3	-5.23	-11.94	≤8.0	Pass
11b	1	11	2462	-6.94	--	97.3	-5.23	-12.05	≤8.0	Pass
11g	6	1	2412	-12.94	--	90.7	-5.23	-17.75	≤8.0	Pass
11g	6	6	2437	-9.88	--	90.7	-5.23	-14.69	≤8.0	Pass
11g	6	11	2462	-13.16	--	90.7	-5.23	-17.97	≤8.0	Pass
11n-HT20	6.5	1	2412	-16.18	--	86.5	-5.23	-20.78	≤8.0	Pass
11n-HT20	6.5	6	2437	-10.23	--	86.5	-5.23	-14.83	≤8.0	Pass
11n-HT20	6.5	11	2462	-15.01	--	86.5	-5.23	-19.61	≤8.0	Pass
11n-HT40	13.5	3	2422	-19.32	--	78.7	-5.23	-23.51	≤8.0	Pass
11n-HT40	13.5	6	2437	-13.21	--	78.7	-5.23	-17.40	≤8.0	Pass
11n-HT40	13.5	9	2452	-19.32	--	78.7	-5.23	-23.51	≤8.0	Pass
Ant 2										
11n-HT20	6.5	1	2412	--	-15.14	86.5	-5.23	-19.74	≤8.0	Pass
11n-HT20	6.5	6	2437	--	-10.07	86.5	-5.23	-14.67	≤8.0	Pass
11n-HT20	6.5	11	2462	--	-15.24	86.5	-5.23	-19.84	≤8.0	Pass
11n-HT40	13.5	3	2422	--	-13.47	78.7	-5.23	-17.66	≤8.0	Pass
11n-HT40	13.5	6	2437	--	-13.06	78.7	-5.23	-17.25	≤8.0	Pass
11n-HT40	13.5	9	2452	--	-19.17	78.7	-5.23	-23.36	≤8.0	Pass
Ant 1 + 2										
11n-HT20	13.0	1	2412	-15.57	-14.96	86.5	-5.23	-16.84	≤8.0	Pass
11n-HT20	13.0	6	2437	-10.62	-9.96	86.5	-5.23	-11.87	≤8.0	Pass
11n-HT20	13.0	11	2462	-15.71	-14.82	86.5	-5.23	-16.83	≤8.0	Pass
11n-HT40	27.0	3	2422	-18.75	-19.28	78.7	-5.23	-20.19	≤8.0	Pass
11n-HT40	27.0	6	2437	-13.16	-12.81	78.7	-5.23	-14.16	≤8.0	Pass
11n-HT40	27.0	9	2452	-19.24	-18.72	78.7	-5.23	-20.15	≤8.0	Pass


Note: When EUT duty cycle < 98%, the total AVGPSPD = $10 \cdot \log\{10^{(\text{Ant 1 AVGPSPD}/10)} + 10^{(\text{Ant 2 AVGPSPD}/10)}\} + 10 \cdot \log(1/\text{duty cycle}) + \text{Constant Factor}$.

802.11b AVGPDS - Ant 1


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11g AVGPDS - Ant 1


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT20 AVGPSPD - Ant 1


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT40 AVGPSD - Ant 1


Channel 03 (2422MHz)



Channel 06 (2437MHz)




Channel 09 (2452MHz)




802.11n-HT20 AVGPSD - Ant 2


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT40 AVGPDS - Ant 2


Channel 03 (2422MHz)



Channel 06 (2437MHz)




Channel 09 (2452MHz)




802.11n-HT20 AVGPDS - Ant 1 / Ant 1 + 2


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT40 AVGPSD - Ant 1 / Ant 1 + 2


Channel 03 (2422MHz)



Channel 06 (2437MHz)




Channel 09 (2452MHz)




802.11n-HT20 AVGPSD - Ant 2 / Ant 1 + 2


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT40 AVGPDS - Ant 2 / Ant 1 + 2


Channel 03 (2422MHz)



Channel 06 (2437MHz)



Channel 09 (2452MHz)



7.5. Conducted Band Edge and Out-of-Band Emissions

7.5.1. Test Limit

The limit for out-of-band spurious emissions at the band edge is 30dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure.

7.5.2. Test Procedure Used

KDB 558074 D01v03r02 - Section 11.2 & Section 11.3

7.5.3. Test Settling


1. Reference level measurement

- (a) Set instrument center frequency to DTS channel center frequency
- (b) Set the span to ≥ 1.5 times the DTS bandwidth
- (c) Set the RBW = 100 kHz
- (d) Set the VBW $\geq 3 \times$ RBW
- (e) Detector = peak
- (f) Sweep time = auto couple
- (g) Trace mode = max hold
- (h) Allow trace to fully stabilize

2. Emission level measurement

- (a) Set the center frequency and span to encompass frequency range to be measured
- (b) RBW = 100kHz
- (c) VBW = 300kHz
- (d) Detector = Peak
- (e) Trace mode = max hold
- (f) Sweep time = auto couple
- (g) The trace was allowed to stabilize

7.5.4. Test Setup




7.5.5. Test Result

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	Limit	Result
Ant 1					
802.11b	1	01	2412	30dBc	Pass
802.11b	1	06	2437	30dBc	Pass
802.11b	1	11	2462	30dBc	Pass
802.11g	6	01	2412	30dBc	Pass
802.11g	6	06	2437	30dBc	Pass
802.11g	6	11	2462	30dBc	Pass
802.11n-HT20	6.5	01	2412	30dBc	Pass
802.11n-HT20	6.5	06	2437	30dBc	Pass
802.11n-HT20	6.5	11	2462	30dBc	Pass
802.11n-HT40	13.5	03	2422	30dBc	Pass
802.11n-HT40	13.5	06	2437	30dBc	Pass
802.11n-HT40	13.5	09	2452	30dBc	Pass
Ant 2					
802.11n-HT20	6.5	01	2412	30dBc	Pass
802.11n-HT20	6.5	06	2437	30dBc	Pass
802.11n-HT20	6.5	11	2462	30dBc	Pass
802.11n-HT40	13.5	03	2422	30dBc	Pass
802.11n-HT40	13.5	06	2437	30dBc	Pass
802.11n-HT40	13.5	09	2452	30dBc	Pass

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	Limit	Result
Ant 1 / Ant 1 + 2					
802.11n-HT20	13.0	01	2412	30dBc	Pass
802.11n-HT20	13.0	06	2437	30dBc	Pass
802.11n-HT20	13.0	11	2462	30dBc	Pass
802.11n-HT40	27.0	03	2422	30dBc	Pass
802.11n-HT40	27.0	06	2437	30dBc	Pass
802.11n-HT40	27.0	09	2452	30dBc	Pass
Ant 2 / Ant 1 + 2					
802.11n-HT20	13.0	01	2412	30dBc	Pass
802.11n-HT20	13.0	06	2437	30dBc	Pass
802.11n-HT20	13.0	11	2462	30dBc	Pass
802.11n-HT40	27.0	03	2422	30dBc	Pass
802.11n-HT40	27.0	06	2437	30dBc	Pass
802.11n-HT40	27.0	09	2452	30dBc	Pass


802.11b Out-of-Band Emissions - Ant 1

100kHz PSD reference Level




Channel 01 (2412MHz)

Low Band Edge




Spurious Emission




Channel 06 (2437MHz)

Spurious Emission




Channel 11 (2462MHz)

High Band Edge




Spurious Emission




802.11g Out-of-Band Emissions - Ant 1

100kHz PSD reference Level




Channel 01 (2412MHz)

Low Band Edge




Spurious Emission




Channel 06 (2437MHz)

Spurious Emission




Channel 11 (2462MHz)

High Band Edge




Spurious Emission




802.11n-HT20 Out-of-Band Emissions - Ant 1

100kHz PSD reference Level




Channel 01 (2412MHz)

Low Band Edge




Spurious Emission




Channel 06 (2437MHz)

Spurious Emission




Channel 11 (2462MHz)

High Band Edge




Spurious Emission




802.11n-HT40 Out-of-Band Emissions - Ant 1

100kHz PSD reference Level




Channel 03 (2422MHz)

Low Band Edge




Spurious Emission




Channel 06 (2437MHz)

Spurious Emission




Channel 9 (2452MHz)

High Band Edge




Spurious Emission




802.11n-HT20 Out-of-Band Emissions - Ant 2

100kHz PSD reference Level




Channel 01 (2412MHz)

Low Band Edge




Spurious Emission




Channel 06 (2437MHz)

Spurious Emission




Channel 11 (2462MHz)

High Band Edge




Spurious Emission




802.11n-HT40 Out-of-Band Emissions - Ant 2

100kHz PSD reference Level




Channel 03 (2422MHz)

Low Band Edge




Spurious Emission




Channel 06 (2437MHz)

Spurious Emission




Channel 9 (2452MHz)

High Band Edge




Spurious Emission




802.11n-HT20 Out-of-Band Emissions - Ant 1 / Ant 1 + 2

100kHz PSD reference Level




Channel 01 (2412MHz)

Low Band Edge




Spurious Emission




Channel 06 (2437MHz)

Spurious Emission




Channel 11 (2462MHz)

High Band Edge




Spurious Emission




802.11n-HT40 Out-of-Band Emissions - Ant 1 / Ant 1 + 2

100kHz PSD reference Level




Channel 03 (2422MHz)

Low Band Edge




Spurious Emission




Channel 06 (2437MHz)

Spurious Emission




Channel 9 (2452MHz)

High Band Edge




Spurious Emission




802.11n-HT20 Out-of-Band Emissions - Ant 2 / Ant 1 + 2

100kHz PSD reference Level




Channel 01 (2412MHz)

Low Band Edge




Spurious Emission




Channel 06 (2437MHz)

Spurious Emission




Channel 11 (2462MHz)

High Band Edge




Spurious Emission




802.11n-HT40 Out-of-Band Emissions - Ant 2 / Ant 1 + 2

100kHz PSD reference Level




Channel 03 (2422MHz)

Low Band Edge




Spurious Emission




Channel 06 (2437MHz)

Spurious Emission




Channel 9 (2452MHz)

High Band Edge



Spurious Emission



7.6. Radiated Spurious Emission Measurement

7.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [V/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

7.6.2. Test Procedure Used

KDB 558074 D01v03r02 - Section 12.2.3 (quasi-peak measurements)

KDB 558074 D01v03r02 - Section 12.2.4 (peak power measurements)

KDB 558074 D01v03r02 - Section 12.2.5 (average power measurements)

7.6.3. Test Setting

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in Table 1
3. VBW = 3MHz
4. Detector = peak

5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Table 1 - RBW as a function of frequency


Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000 MHz	1 MHz

Average Field Strength Measurements


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW $\geq 1/T$
4. De As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces

7.6.4. Test Setup


9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:



1GHz ~ 18GHz Test Setup:



18GHz ~25GHz Test Setup:



7.6.5. Test Result

Test Mode:	802.11b - Ant 1	Test Site:	AC1
Test Channel:	01	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3201.5	43.6	-1.6	42.0	90.2	-48.2	Peak	Horizontal
*	4425.5	37.3	1.5	38.8	90.2	-51.4	Peak	Horizontal
	4825.0	49.2	2.7	51.9	74.0	-22.1	Peak	Horizontal
	10928.0	36.5	13.0	49.5	74.0	-24.5	Peak	Horizontal
*	3499.0	43.5	-1.1	42.4	90.2	-47.8	Peak	Vertical
*	4468.0	37.1	1.6	38.7	90.2	-51.5	Peak	Vertical
	5003.5	41.8	3.0	44.8	74.0	-29.2	Peak	Vertical
	11081.0	36.8	12.9	49.7	74.0	-24.3	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (110.2dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11b - Ant 1	Test Site:	AC1
Test Channel:	06	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3397.0	45.8	-1.7	44.1	90.4	-46.3	Peak	Horizontal
*	4485.0	37.5	1.6	39.1	90.4	-51.3	Peak	Horizontal
	4876.0	47.6	2.7	50.3	74.0	-23.7	Peak	Horizontal
	7307.0	42.2	8.0	50.2	74.0	-23.8	Peak	Horizontal
*	3524.5	39.9	-1.0	38.9	90.4	-51.5	Peak	Vertical
*	4476.5	37.3	1.6	38.9	90.4	-51.5	Peak	Vertical
	4986.5	42.5	3.0	45.5	74.0	-28.5	Peak	Vertical
	7307.0	41.9	8.0	49.9	74.0	-24.1	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (110.4dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11b - Ant 1	Test Site:	AC1
Test Channel:	11	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3448.0	43.9	-1.4	42.5	89.9	-47.4	Peak	Horizontal
*	4442.5	36.8	1.5	38.3	89.9	-51.6	Peak	Horizontal
	4927.0	47.5	2.8	50.3	74.0	-23.7	Peak	Horizontal
	7383.5	43.8	7.9	51.7	74.0	-22.3	Peak	Horizontal
*	3448.0	42.1	-1.4	40.7	89.9	-49.2	Peak	Vertical
*	4408.5	39.0	1.4	40.4	89.9	-49.5	Peak	Vertical
	4986.5	42.0	3.0	45.0	74.0	-29.0	Peak	Vertical
	7383.5	42.4	7.9	50.3	74.0	-23.7	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (109.9dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11g - Ant 1	Test Site:	AC1
Test Channel:	01	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3397.0	42.2	-1.7	40.5	90.0	-49.5	Peak	Horizontal
*	4485.0	36.9	1.6	38.5	90.0	-51.5	Peak	Horizontal
	4825.0	41.8	2.7	44.5	74.0	-29.5	Peak	Horizontal
	7485.5	39.5	8.2	47.7	74.0	-26.3	Peak	Horizontal
*	3499.0	40.2	-1.1	39.1	90.0	-50.9	Peak	Vertical
*	4485.0	37.4	1.6	39.0	90.0	-51.0	Peak	Vertical
	4995.0	41.7	3.0	44.7	74.0	-29.3	Peak	Vertical
	7468.5	39.6	8.1	47.7	74.0	-26.3	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (110.0dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11g - Ant 1	Test Site:	AC1
Test Channel:	06	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3397.0	41.7	-1.7	40.0	88.2	-48.2	Peak	Horizontal
*	4425.5	37.5	1.5	39.0	88.2	-49.2	Peak	Horizontal
	4876.0	44.0	2.7	46.7	74.0	-27.3	Peak	Horizontal
	7315.5	44.4	8.0	52.4	74.0	-21.6	Peak	Horizontal
*	3499.0	40.3	-1.1	39.2	88.2	-49.0	Peak	Vertical
*	4459.5	37.0	1.5	38.5	88.2	-49.7	Peak	Vertical
	4978.0	41.6	3.0	44.6	74.0	-29.4	Peak	Vertical
	7307.0	42.3	8.0	50.3	74.0	-23.7	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (108.2dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11g - Ant 1	Test Site:	AC1
Test Channel:	11	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3397.0	42.5	-1.7	40.8	89.1	-48.3	Peak	Horizontal
*	4451.0	36.8	1.5	38.3	89.1	-50.8	Peak	Horizontal
	4918.5	40.9	2.8	43.7	74.0	-30.3	Peak	Horizontal
	7494.0	39.9	8.2	48.1	74.0	-25.9	Peak	Horizontal
*	3499.0	40.2	-1.1	39.1	89.1	-50.0	Peak	Vertical
*	4434.0	36.9	1.5	38.4	89.1	-50.7	Peak	Vertical
	4995.0	41.6	3.0	44.6	74.0	-29.4	Peak	Vertical
	7468.5	39.9	8.1	48.0	74.0	-26.0	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (109.1dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11n-HT20 - Ant 1	Test Site:	AC1
Test Channel:	01	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3448.0	42.0	-1.4	40.6	86.8	-46.2	Peak	Horizontal
*	4442.5	36.6	1.5	38.1	86.8	-48.7	Peak	Horizontal
	4825.0	43.4	2.7	46.1	74.0	-27.9	Peak	Horizontal
	11140.5	36.2	12.6	48.8	74.0	-25.2	Peak	Horizontal
*	3592.5	40.6	-0.7	39.9	86.8	-46.9	Peak	Vertical
*	4442.5	37.3	1.5	38.8	86.8	-48.0	Peak	Vertical
	4825.0	42.6	2.7	45.3	74.0	-28.7	Peak	Vertical
	10936.5	36.8	13.0	49.8	74.0	-24.2	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (106.8dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11n-HT20 - Ant 1	Test Site:	AC1
Test Channel:	06	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3397.0	41.2	-1.7	39.5	96.8	-57.3	Peak	Horizontal
*	4442.5	37.0	1.5	38.5	96.8	-58.3	Peak	Horizontal
	4876.0	43.3	2.7	46.0	74.0	-28.0	Peak	Horizontal
	7315.5	42.0	8.0	50.0	74.0	-24.0	Peak	Horizontal
*	3397.0	40.2	-1.7	38.5	96.8	-58.3	Peak	Vertical
*	4425.5	37.0	1.5	38.5	96.8	-58.3	Peak	Vertical
	4876.0	40.5	2.7	43.2	74.0	-30.8	Peak	Vertical
	7307.0	41.3	8.0	49.3	74.0	-24.7	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (116.8dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11n-HT20 - Ant 1	Test Site:	AC1
Test Channel:	11	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3439.5	41.5	-1.5	40.0	87.2	-47.2	Peak	Horizontal
*	4425.5	36.4	1.5	37.9	87.2	-49.3	Peak	Horizontal
	4995.0	41.5	3.0	44.5	74.0	-29.5	Peak	Horizontal
	7485.5	39.0	8.2	47.2	74.0	-26.8	Peak	Horizontal
*	3558.5	40.0	-0.8	39.2	87.2	-48.0	Peak	Vertical
*	4459.5	36.6	1.5	38.1	87.2	-49.1	Peak	Vertical
	4995.0	41.2	3.0	44.2	74.0	-29.8	Peak	Vertical
	7468.5	39.1	8.1	47.2	74.0	-26.8	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (107.2dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11n-HT40 - Ant 1	Test Site:	AC1
Test Channel:	03	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3397.0	42.3	-1.7	40.6	83.9	-43.3	Peak	Horizontal
*	4425.5	36.6	1.5	38.1	83.9	-45.8	Peak	Horizontal
	4995.0	41.5	3.0	44.5	74.0	-29.5	Peak	Horizontal
	7266.0	36.4	7.9	44.3	74.0	-29.7	Peak	Horizontal
*	3499.0	42.1	-1.1	41.0	83.9	-42.9	Peak	Vertical
*	4442.5	36.3	1.5	37.8	83.9	-46.1	Peak	Vertical
	4986.5	40.7	3.0	43.7	74.0	-30.3	Peak	Vertical
	7468.5	39.9	8.1	48.0	74.0	-26.0	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (103.9dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11n-HT40 - Ant 1	Test Site:	AC1
Test Channel:	06	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3397.0	42.6	-1.7	40.9	93.6	-52.7	Peak	Horizontal
*	4442.5	36.8	1.5	38.3	93.6	-55.3	Peak	Horizontal
	4986.5	41.0	3.0	44.0	74.0	-30.0	Peak	Horizontal
	7298.5	39.2	8.0	47.2	74.0	-26.8	Peak	Horizontal
*	3499.0	40.1	-1.1	39.0	93.6	-54.6	Peak	Vertical
*	4425.5	37.0	1.5	38.5	93.6	-55.1	Peak	Vertical
	4995.0	41.0	3.0	44.0	74.0	-30.0	Peak	Vertical
	7502.5	39.7	8.3	48.0	74.0	-26.0	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (113.6dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11n-HT40 - Ant 1	Test Site:	AC1
Test Channel:	09	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3397.0	45.6	-1.7	43.9	80.0	-36.1	Peak	Horizontal
*	4476.5	36.6	1.6	38.2	80.0	-41.8	Peak	Horizontal
	4986.5	41.5	3.0	44.5	74.0	-29.5	Peak	Horizontal
	7468.5	39.0	8.1	47.1	74.0	-26.9	Peak	Horizontal
*	3397.0	40.7	-1.7	39.0	80.0	-41.0	Peak	Vertical
*	4459.5	36.3	1.5	37.8	80.0	-42.2	Peak	Vertical
	4986.5	41.1	3.0	44.1	74.0	-29.9	Peak	Vertical
	7485.5	38.9	8.2	47.1	74.0	-26.9	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (100.0dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11n-HT20 - Ant 2	Test Site:	AC1
Test Channel:	01	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3397.0	44.1	-1.7	42.4	87.2	-44.8	Peak	Horizontal
*	4425.5	36.5	1.5	38.0	87.2	-49.2	Peak	Horizontal
	4995.0	41.5	3.0	44.5	74.0	-29.5	Peak	Horizontal
	7468.5	38.8	8.1	46.9	74.0	-27.1	Peak	Horizontal
*	3499.0	40.9	-1.1	39.8	87.2	-47.4	Peak	Vertical
*	4442.5	36.7	1.5	38.2	87.2	-49.0	Peak	Vertical
	4986.5	40.5	3.0	43.5	74.0	-30.5	Peak	Vertical
	7468.5	38.8	8.1	46.9	74.0	-27.1	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (107.2dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11n-HT20 - Ant 2	Test Site:	AC1
Test Channel:	06	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3397.0	42.0	-1.7	40.3	99.4	-59.1	Peak	Horizontal
*	5496.5	37.7	3.5	41.2	99.4	-58.2	Peak	Horizontal
	7315.5	43.4	8.0	51.4	74.0	-22.6	Peak	Horizontal
	12194.5	29.0	11.7	40.7	54.0	-13.3	Average	Horizontal
	12194.5	44.1	11.7	55.8	74.0	-18.2	Peak	Horizontal
*	3499.0	40.9	-1.1	39.8	99.4	-59.6	Peak	Vertical
*	5794.0	36.6	4.0	40.6	99.4	-58.8	Peak	Vertical
	7307.0	43.5	8.0	51.5	74.0	-22.5	Peak	Vertical
	12186.0	42.7	11.7	54.4	74.0	-19.6	Peak	Vertical
	12186.2	28.9	11.7	40.6	54.0	-13.4	Average	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (119.4dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11n-HT20 - Ant 2	Test Site:	AC1
Test Channel:	11	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3201.5	42.9	-1.6	41.3	87.7	-46.4	Peak	Horizontal
*	4485.0	37.6	1.6	39.2	87.7	-48.5	Peak	Horizontal
	4986.5	41.9	3.0	44.9	74.0	-29.1	Peak	Horizontal
	7468.5	38.1	8.1	46.2	74.0	-27.8	Peak	Horizontal
*	3499.0	40.1	-1.1	39.0	87.7	-48.7	Peak	Vertical
*	4425.5	36.6	1.5	38.1	87.7	-49.6	Peak	Vertical
	4995.0	41.2	3.0	44.2	74.0	-29.8	Peak	Vertical
	7468.5	38.9	8.1	47.0	74.0	-27.0	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (107.7dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11n-HT40 - Ant 2	Test Site:	AC1
Test Channel:	03	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3201.5	46.0	-1.6	44.4	84.8	-40.4	Peak	Horizontal
*	4442.5	37.2	1.5	38.7	84.8	-46.1	Peak	Horizontal
	4995.0	41.4	3.0	44.4	74.0	-29.6	Peak	Horizontal
	7502.5	38.1	8.3	46.4	74.0	-27.6	Peak	Horizontal
*	3363.0	37.9	-1.8	36.1	84.8	-48.7	Peak	Vertical
*	4476.5	35.6	1.6	37.2	84.8	-47.6	Peak	Vertical
	4995.0	39.9	3.0	42.9	74.0	-31.1	Peak	Vertical
	7477.0	38.6	8.2	46.8	74.0	-27.2	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (104.8dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11n-HT40 - Ant 2	Test Site:	AC1
Test Channel:	06	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3397.0	41.6	-1.7	39.9	98.7	-58.8	Peak	Horizontal
*	4434.0	37.5	1.5	39.0	98.7	-59.7	Peak	Horizontal
	4884.5	47.4	2.7	50.1	74.0	-23.9	Peak	Horizontal
	12203.0	40.8	11.7	52.5	74.0	-21.5	Peak	Horizontal
*	3397.0	42.4	-1.7	40.7	98.7	-58.0	Peak	Vertical
*	4442.5	36.3	1.5	37.8	98.7	-60.9	Peak	Vertical
	4876.0	41.4	2.7	44.1	74.0	-29.9	Peak	Vertical
	12194.5	40.1	11.7	51.8	74.0	-22.2	Peak	Vertical

Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (118.7dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11n-HT40 - Ant 2	Test Site:	AC1
Test Channel:	09	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3176.0	40.2	-1.6	38.6	85.1	-46.5	Peak	Horizontal
*	3397.0	44.7	-1.7	43.0	85.1	-42.1	Peak	Horizontal
	3796.5	43.8	-0.2	43.6	74.0	-30.4	Peak	Horizontal
	4986.5	41.3	3.0	44.3	74.0	-29.7	Peak	Horizontal
*	3448.0	42.9	-1.4	41.5	85.1	-43.6	Peak	Vertical
*	4459.5	35.8	1.5	37.3	85.1	-47.8	Peak	Vertical
	4995.0	40.0	3.0	43.0	74.0	-31.0	Peak	Vertical
	7485.5	38.9	8.2	47.1	74.0	-26.9	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (105.1dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11n-HT20 - Ant 1 + 2	Test Site:	AC1
Test Channel:	01	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3422.5	41.8	-1.6	40.2	91.1	-50.9	Peak	Horizontal
*	4476.5	37.3	1.6	38.9	91.1	-52.2	Peak	Horizontal
	4816.5	42.8	2.7	45.5	74.0	-28.5	Peak	Horizontal
	7494.0	38.9	8.2	47.1	74.0	-26.9	Peak	Horizontal
*	3499.0	39.8	-1.1	38.7	91.1	-52.4	Peak	Vertical
*	4442.5	37.2	1.5	38.7	91.1	-52.4	Peak	Vertical
	4995.0	40.5	3.0	43.5	74.0	-30.5	Peak	Vertical
	7468.5	38.6	8.1	46.7	74.0	-27.3	Peak	Vertical

Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (111.1dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11n-HT20 - Ant 1 + 2	Test Site:	AC1
Test Channel:	06	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3397.0	41.4	-1.7	39.7	104.2	-64.5	Peak	Horizontal
*	4434.0	37.1	1.5	38.6	104.2	-65.6	Peak	Horizontal
	4816.5	43.6	2.7	46.3	74.0	-27.7	Peak	Horizontal
	7502.5	38.7	8.3	47.0	74.0	-27.0	Peak	Horizontal
*	3473.5	39.7	-1.3	38.4	104.2	-65.8	Peak	Vertical
*	4485.0	37.0	1.6	38.6	104.2	-65.6	Peak	Vertical
	7307.0	46.7	8.0	54.7	74.0	-19.3	Peak	Vertical
	7307.2	31.5	8.0	39.5	54.0	-14.5	Average	Vertical
	12185.9	29.5	11.7	41.2	54.0	-12.8	Average	Vertical
	12186.0	43.8	11.7	55.5	74.0	-18.5	Peak	Vertical

Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (124.2dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11n-HT20 - Ant 1 + 2	Test Site:	AC1
Test Channel:	11	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3303.5	43.2	-1.8	41.4	91.3	-49.9	Peak	Horizontal
*	4442.5	36.3	1.5	37.8	91.3	-53.5	Peak	Horizontal
	4927.0	49.1	2.8	51.9	74.0	-22.1	Peak	Horizontal
	7392.0	39.2	7.9	47.1	74.0	-26.9	Peak	Horizontal
*	3499.0	39.7	-1.1	38.6	91.3	-52.7	Peak	Vertical
*	4459.5	36.0	1.5	37.5	91.3	-53.8	Peak	Vertical
	4995.0	40.9	3.0	43.9	74.0	-30.1	Peak	Vertical
	7375.0	38.7	7.9	46.6	74.0	-27.4	Peak	Vertical

Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (111.3dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11n-HT40 - Ant 1 + 2	Test Site:	AC1
Test Channel:	03	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3397.0	43.8	-1.7	42.1	86.9	-44.8	Peak	Horizontal
*	4459.5	37.0	1.5	38.5	86.9	-48.4	Peak	Horizontal
	5003.5	42.2	3.0	45.2	74.0	-28.8	Peak	Horizontal
	7477.0	38.6	8.2	46.8	74.0	-27.2	Peak	Horizontal
*	3499.0	40.7	-1.1	39.6	86.9	-47.3	Peak	Vertical
*	4408.5	36.1	1.4	37.5	86.9	-49.4	Peak	Vertical
	4995.0	40.5	3.0	43.5	74.0	-30.5	Peak	Vertical
	7494.0	38.7	8.2	46.9	74.0	-27.1	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (106.9dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11n-HT40 - Ant 1 + 2	Test Site:	AC1
Test Channel:	06	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3397.0	41.5	-1.7	39.8	98.5	-58.7	Peak	Horizontal
*	4468.0	35.8	1.6	37.4	98.5	-61.1	Peak	Horizontal
	7324.0	43.8	8.0	51.8	74.0	-22.2	Peak	Horizontal
	12194.5	41.2	11.7	52.9	74.0	-21.1	Peak	Horizontal
*	3533.0	39.4	-1.0	38.4	98.5	-60.1	Peak	Vertical
*	4459.5	35.9	1.5	37.4	98.5	-61.1	Peak	Vertical
	7315.5	42.7	8.0	50.7	74.0	-23.3	Peak	Vertical
	12186.0	39.0	11.7	50.7	74.0	-23.3	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (118.5dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	802.11n-HT40 - Ant 1 + 2	Test Site:	AC1
Test Channel:	09	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
*	3397.0	41.3	-1.7	39.6	87.5	-47.9	Peak	Horizontal
*	4459.5	36.5	1.5	38.0	87.5	-49.5	Peak	Horizontal
	5003.5	42.5	3.0	45.5	74.0	-28.5	Peak	Horizontal
	7485.5	38.1	8.2	46.3	74.0	-27.7	Peak	Horizontal
*	3575.5	39.6	-0.8	38.8	87.5	-48.7	Peak	Vertical
*	4493.5	36.5	1.6	38.1	87.5	-49.4	Peak	Vertical
	4995.0	41.6	3.0	44.6	74.0	-29.4	Peak	Vertical
	7477.0	37.9	8.2	46.1	74.0	-27.9	Peak	Vertical


Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (107.5dBμV/m).

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

The worst case of Radiated Emission below 1GHz:

Site: AC1	Time: 2015/04/09 - 15:34
Limit: FCC_Part15.209_RE(3m)	Engineer: Milo Li
Probe: VULB9162_0.03-8GHz	Polarity: Horizontal
EUT: BHS VDSL VoIP	Power: AC 120V/60Hz
Note: There is the worst case within frequency range 30MHz~1GHz.	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			139.520	24.796	15.300	-18.704	43.500	9.496	QP
2			151.503	24.096	14.600	-19.404	43.500	9.496	QP
3			200.280	25.630	13.400	-17.870	43.500	12.230	QP
4			384.890	38.518	22.190	-7.482	46.000	16.328	QP
5		*	600.120	39.423	19.460	-6.577	46.000	19.963	QP
6			737.420	33.414	11.450	-12.586	46.000	21.964	QP

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)