



SAR Test exclusion documentation according to FCC KDB 447498

Report identification number: 1-0590/20-01-14 Exclusion (FCC)

contains the module with the following certification numbers	
FCC ID	2ACAH-AUMRIT

This report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:

cn=Alexander Hnatovskiy, o=CTC advanced
GmbH, ou=HNA-161129,
email=Alexander.Hnatovskiy@ctcadvanced.c
om, c=DE
2020.12.10 12:55:43 +01'00'

Alexander Hnatovskiy
Lab Manager
Radio Communications & EMC

cn=Marco Scigliano, o=CTC advanced
GmbH, ou=SCI-161125,
email=marco.scigliano@ctcadvanced.co
m, c=DE
2020.12.10 12:22:18 +01'00'

Marco Scigliano
Testing Manager
Radio Communications & EMC

EUT technologies:

Technologies:	Max. rated power: (AVG)	Max. gain:	Min. pathloss:
Bluetooth LE	Measured: -1.7 dBm	0.6 dBi	0 dB (if applicable)
NFMI 3.8 MHz)*	--	--	--

)* exempt from routine evaluation CFR47 § 2.1093

SAR test exclusion according to KDB447498 (General RF Exposure Guidance v06)

Equation from Chapter 4.3.1: Standalone SAR test exclusion considerations page 11 and ff.

(1) Standalone SAR test exclusion for 100 MHz to 6 GHz at test separation distances $\leq 50\text{mm}$

$$(\text{Threshold}_{1\text{-g};10\text{-g}}) \times d_{\text{separation}} / f^{0.5}$$

where

Threshold_{1-g;10-g} is 3 for 1-g; 7.5 for 10-g

d_{separation} is the min. test separation distance; 5mm is used if the distance is less

f is the RF channel transmit frequency

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

frequency [MHz]	d _{separation} [mm]	Threshold _{1-g}	Powerlimit [mW]	P _{max-declared}		Exclusion
				[dBm]	[mW]	
2450.00	5	3	9.58	-1.10	0.78	yes

The limit above is defined for body worn application and therefore cover all use cases.