



## FCC 47 CFR PART 15 SUBPART C

for

**Stealth Intelligent WiFi Router**

**Model: IR300/VF35A**

**Brand: VOLANS**

**Test Report Number:**  
**C140611Z01-RP1**

**Issued Date: July 11, 2014**

Issued for

**Chengdu Volans Technology, Inc.**  
**7-8F, Building G4, No.1800, Mid Yizhou Ave, Hi-tech Zone,**  
**Chengdu, P.R.China 610041**

Issued by:

**Compliance Certification Services (Shenzhen) Inc.**  
No.10-1 Mingkeda Logistics park, No.18, Huanguan South Rd.,  
Guan Lan Town, Baoan District, Shenzhen, China  
TEL: 86-755-28055000  
FAX: 86-755-28055221



**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST or any government agencies. The test results in the report only apply to the tested sample.



Revision History

| Rev. | Issue Date    | Revisions     | Effect Page | Revised By   |
|------|---------------|---------------|-------------|--------------|
| 00   | July 11, 2014 | Initial Issue | ALL         | Sabrina Wang |
|      |               |               |             |              |
|      |               |               |             |              |
|      |               |               |             |              |



TABLE OF CONTENTS

|                                                       |           |
|-------------------------------------------------------|-----------|
| <b>1 TEST CERTIFICATION .....</b>                     | <b>4</b>  |
| <b>2 TEST RESULT SUMMARY .....</b>                    | <b>5</b>  |
| <b>3 EUT DESCRIPTION .....</b>                        | <b>6</b>  |
| <b>4 TEST METHODOLOGY .....</b>                       | <b>7</b>  |
| 4.1. DESCRIPTION OF TEST MODES .....                  | 7         |
| <b>5 SETUP OF EQUIPMENT UNDER TEST .....</b>          | <b>8</b>  |
| 5.1. DESCRIPTION OF SUPPORT UNITS .....               | 8         |
| 5.2. CONFIGURATION OF SYSTEM UNDER TEST .....         | 8         |
| <b>6 FACILITIES AND ACCREDITATIONS .....</b>          | <b>9</b>  |
| 6.1. FACILITIES .....                                 | 9         |
| 6.2. ACCREDITATIONS .....                             | 9         |
| 6.3. MEASUREMENT UNCERTAINTY .....                    | 9         |
| <b>7 FCC PART 15.247 REQUIREMENTS .....</b>           | <b>10</b> |
| 7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT ..... | 10        |
| 7.2. SPURIOUS EMISSIONS MEASUREMENT .....             | 15        |
| 7.3. 6dB BANDWIDTH MEASUREMENT .....                  | 65        |
| 7.4. PEAK OUTPUT POWER .....                          | 79        |
| 7.5. BAND EDGES MEASUREMENT .....                     | 83        |
| 7.6. PEAK POWER SPECTRAL DENSITY MEASUREMENT .....    | 109       |

**1 TEST CERTIFICATION**

|                     |                                                                                                                               |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------|
| <b>Product</b>      | Stealth Intelligent WiFi Router                                                                                               |
| <b>Model</b>        | IR300/VF35A                                                                                                                   |
| <b>Brand</b>        | VOLANS                                                                                                                        |
| <b>Tested</b>       | June 11~July 11, 2014                                                                                                         |
| <b>Applicant</b>    | <b>Chengdu Volans Technology, Inc.</b><br>7-8F, Building G4, No.1800, Mid Yizhou Ave, Hi-tech Zone, Chengdu, P.R.China 610041 |
| <b>Manufacturer</b> | <b>Chengdu Volans Technology, Inc.</b><br>7-8F, Building G4, No.1800, Mid Yizhou Ave, Hi-tech Zone, Chengdu, P.R.China 610041 |

| <b>APPLICABLE STANDARDS</b> |                                |                              |                                                                         |
|-----------------------------|--------------------------------|------------------------------|-------------------------------------------------------------------------|
| <b>Standard</b>             | <b>Test Type</b>               | <b>Standard</b>              | <b>Test Type</b>                                                        |
| 15.207(a)                   | Power Line Conducted Emissions | 15.247(d)<br>15.209(a)       | ● Spurious Emissions<br>● Conducted Measurement<br>● Radiated Emissions |
| 15.247(a)(2)                | 6dB Bandwidth Measurement      | 15.247(b)(3)<br>15.247(b)(4) | Peak Power Measurement                                                  |
| 15.247(d)                   | Band Edges Measurement         | 15.247(e)                    | Peak Power Spectral Density                                             |

**We hereby certify that:**

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in **ANSI C63.4: 2009** and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

**Approved by:****Reviewed by:**

**Sunday Hu**  
Supervisor of EMC Dept.  
Compliance Certification Service Inc.

**Ruby Zhang**  
Supervisor of Report Dept.  
Compliance Certification Service Inc.

**2 TEST RESULT SUMMARY**

| <b>APPLICABLE STANDARDS</b>  |                                                                         |               |                                |
|------------------------------|-------------------------------------------------------------------------|---------------|--------------------------------|
| <b>Standard</b>              | <b>Test Type</b>                                                        | <b>Result</b> | <b>Remark</b>                  |
| 15.247(a)(2)                 | 6dB Bandwidth Measurement                                               | Pass          | Meet the requirement of limit. |
| 15.247(b)(3)<br>15.247(b)(4) | Peak Power Measurement                                                  | Pass          | Meet the requirement of limit. |
| 15.247(d)                    | Band Edges Measurement                                                  | Pass          | Meet the requirement of limit. |
| 15.247(e)                    | Peak Power Spectral Density                                             | Pass          | Meet the requirement of limit. |
| 15.247(d)<br>15.209(a)       | ● Spurious Emissions<br>● Conducted Measurement<br>● Radiated Emissions | Pass          | Meet the requirement of limit. |
| 15.207(a)                    | Power line Conducted Emissions                                          | Pass          | Meet the requirement of limit. |

Note: 1. The statements of test result on the above are decided by the request of test standard only; the measurement uncertainties are not factored into this compliance determination.

2. The information of measurement uncertainty is available upon the customer's request.



### 3 EUT DESCRIPTION

|                                         |                                                                                                                                                                                                                                                                                                                                      |
|-----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product</b>                          | Stealth Intelligent WiFi Router                                                                                                                                                                                                                                                                                                      |
| <b>Model Number</b>                     | IR300/VF35A                                                                                                                                                                                                                                                                                                                          |
| <b>Brand</b>                            | VOLANS                                                                                                                                                                                                                                                                                                                               |
| <b>Model Discrepancy</b>                | N/A                                                                                                                                                                                                                                                                                                                                  |
| <b>Identify Number</b>                  | C140611Z01-RP1                                                                                                                                                                                                                                                                                                                       |
| <b>Power Supply</b>                     | DC12V supply by the adapter                                                                                                                                                                                                                                                                                                          |
| <b>Adapter Manufacturer / Model No.</b> | Shenzhen Gongjin Electronics Co., Ltd. / S12B22-120A100-04<br>I/P: AC100-240V ~ 50/60Hz, 0.5A max<br>O/P: DC12V, 1A<br>DC Output Cable: Unshielded, 1.90m                                                                                                                                                                            |
| <b>Transmit Power</b>                   | IEEE 802.11b mode: 26.59dBm (Antenna 0)<br>IEEE 802.11b mode: 25.67dBm (Antenna 1)<br>IEEE 802.11g mode: 23.17dBm (Antenna 0)<br>IEEE 802.11g mode: 22.71dBm (Antenna 1)<br>IEEE 802.11n HT20 MHz mode: 22.90dBm(Combine with Antenna 0 and Antenna 1)<br>IEEE 802.11n HT40 MHz mode: 22.81dBm(Combine with Antenna 0 and Antenna 1) |
| <b>Modulation Technique</b>             | IEEE 802.11b mode: DSSS(CCK,QPSK, BPSK)<br>IEEE 802.11g mode: OFDM (BPSK/QPSK/16QAM/64QAM)<br>IEEE 802.11n HT20 MHz mode: OFDM (BPSK/QPSK/16QAM/64QAM)<br>IEEE 802.11n HT40 MHz mode: OFDM (BPSK/QPSK/16QAM/64QAM)                                                                                                                   |
| <b>Transmit Data Rate</b>               | IEEE 802.11b: 11Mbps(CCK) with fall back rates of 5.5/2/1Mbps<br>IEEE 802.11g: 54Mbps with fall back rates of 48/36/24/18/12/9 /6Mbps<br>IEEE 802.11n HT20: 130Mbps with fall back rates of 130/117/104/78/52/39/26/13Mbps<br>IEEE 802.11n HT40: 270Mbps with fall back rates of 270/243/216/162/108/81/54/27Mbps                    |
| <b>Number of Channels</b>               | IEEE 802.11b mode: 11 Channels<br>IEEE 802.11g mode: 11 Channels<br>IEEE 802.11n HT20 MHz mode: 11 Channels<br>IEEE 802.11n HT40 MHz mode: 7 Channels                                                                                                                                                                                |
| <b>Antenna Specification</b>            | Dipole Antenna 0 with 5.0dBi gain (Max)<br>Dipole Antenna 1 with 5.0dBi gain (Max)                                                                                                                                                                                                                                                   |
| <b>Channels Spacing</b>                 | IEEE 802.11b/g ,802.11n HT20/HT40 : 5MHz                                                                                                                                                                                                                                                                                             |
| <b>Temperature Range</b>                | 0°C ~ +40°C                                                                                                                                                                                                                                                                                                                          |

**Note:** 1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.

2. This submittal(s) (test report) is intended for FCC ID: 2ACBQIR300 filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



## 4 TEST METHODOLOGY

### 4.1. DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

| Test Item          | Test mode                                                                                   | Worse mode    |
|--------------------|---------------------------------------------------------------------------------------------|---------------|
| Conducted Emission | <b>Mode 1:</b> LAN 10Mbps 100% with adapter<br><b>Mode 2:</b> LAN 100Mbps 100% with adapter | <b>Mode 2</b> |
| Radiated Emission  | <b>Mode 1:</b> TX                                                                           | <b>Mode 1</b> |

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only, and power line conducted emission below 30MHz, which worst case was in normal link mode.

IEEE802.11b mode: Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 1Mbps data rate were chosen for full testing.

IEEE802.11g mode: Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6Mbps data rate were chosen for full testing.

IEEE 802.11n HT20 MHz mode: Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 13Mbps data rate were chosen for full testing.

IEEE 802.11n HT40 MHz mode: Channel Low (2422MHz), Channel Mid (2437MHz) and Channel High (2452MHz) with 27Mbps data rate were chosen for full testing.



## **5 SETUP OF EQUIPMENT UNDER TEST**

### **5.1. DESCRIPTION OF SUPPORT UNITS**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| No. | Equipment       | Model No. | Serial No. | FCC ID | Brand     | Data Cable          | Power Cord          |
|-----|-----------------|-----------|------------|--------|-----------|---------------------|---------------------|
| 1   | Notebook 1#     | E335      | R9-WN1EF   | DoC    | Think pad | Unshielded<br>1.70m | Unshielded<br>1.80m |
| 2   | Notebook 2#     | E335      | R9-WN0KH   | DoC    | Think pad | Unshielded<br>1.70m | Unshielded<br>1.80m |
| 3   | RJ45<br>Cable*3 | N/A       | N/A        | N/A    | N/A       | Unshielded<br>1.20m | N/A                 |

**Note:**

Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

### **5.2. CONFIGURATION OF SYSTEM UNDER TEST**

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.



## 6 FACILITIES AND ACCREDITATIONS

### 6.1. FACILITIES

All measurement facilities used to collect the measurement data are located at **No.10-1 Mingkeda Logistics park, No.18, Huanguan South Rd., Guan Lan Town, Baoan District, Shenzhen, China**

The sites are constructed in conformance with the requirements of ANSI C63.4, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

### 6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

|              |             |
|--------------|-------------|
| <b>USA</b>   | <b>A2LA</b> |
| <b>China</b> | <b>CNAS</b> |

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

|               |                                           |
|---------------|-------------------------------------------|
| <b>USA</b>    | <b>FCC</b>                                |
| <b>Japan</b>  | <b>VCCI(C-3478, R-3135, T-652, G-624)</b> |
| <b>Canada</b> | <b>INDUSTRY CANADA</b>                    |
| <b>Taiwan</b> | <b>BSMI</b>                               |

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsrf.com>

### 6.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| <b>Parameter</b>                                         | <b>Uncertainty</b> |
|----------------------------------------------------------|--------------------|
| Radiated Emission, 30 to 200 MHz<br>Test Site : 966(2)   | +/-3.6880dB        |
| Radiated Emission, 200 to 1000 MHz<br>Test Site : 966(2) | +/-3.6695dB        |
| Radiated Emission, 1 to 8 GHz                            | +/-5.1782dB        |
| Radiated Emission, 8 to 18 GHz                           | +/-5.2173dB        |
| Conducted Emissions                                      | +/-3.6836dB        |
| Band Width                                               | 178kHz             |
| Peak Output Power MU                                     | +/-1.906dB         |
| Band Edge MU                                             | +/-0.182dB         |
| Channel Separation MU                                    | 416.178Hz          |
| Duty Cycle MU                                            | 0.054ms            |
| Frequency Stability MU                                   | 226Hz              |

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

The measured result is above (below) the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance (non-compliance) is more probable than non-compliance) with the specification limit.



## 7 FCC PART 15.247 REQUIREMENTS

### 7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT

#### 7.1.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

| Frequency Range (MHz) | Limits (dB $\mu$ V) |           |
|-----------------------|---------------------|-----------|
|                       | Quasi-peak          | Average   |
| 0.15 to 0.50          | 66 to 56*           | 56 to 46* |
| 0.50 to 5             | 56                  | 46        |
| 5 to 30               | 60                  | 50        |

**NOTE:**

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 7.1.2. TEST INSTRUMENTS

| Conducted Emission Test Site |               |                    |               |                  |                 |
|------------------------------|---------------|--------------------|---------------|------------------|-----------------|
| Name of Equipment            | Manufacturer  | Model Number       | Serial Number | Last Calibration | Due Calibration |
| EMI TEST RECEIVER            | ROHDE&SCHWARZ | ESCI               | 100783        | 03/09/2014       | 03/08/2015      |
| LISN(EUT)                    | ROHDE&SCHWARZ | ENV216             | 101543-WX     | 04/20/2014       | 04/19/2015      |
| LISN                         | EMCO          | 3825/2             | 8901-1459     | 03/09/2014       | 03/08/2015      |
| Temp. / Humidity Meter       | VICTOR        | HTC-1              | N/A           | 03/17/2014       | 03/17/2015      |
| Test S/W                     | FARAD         | EZ-EMC/ CCS-3A1-CE |               |                  |                 |

**NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. N.C.R = No Calibration Request.




## 7.1.3. TEST PROCEDURES (please refer to measurement standard)

- The EUT and Support equipment, if needed, was placed on a non-conducted table, which is 0.8m above the ground plane and 0.4m away from the conducted wall.
- The test equipment EUT installed received AC main power, through a Line Impedance Stabilization Network (LISN), which supplied power source and was grounded to the ground plane. All support equipment power received from a second LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- The EUT test program was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The frequency range from 150 kHz to 30 MHz was searched. The test data of the worst-case condition(s) was recorded. Emission levels under limit 20dB were not recorded.



#### 7.1.4. TEST SETUP



For the actual test configuration, please refer to the related item - Photographs of the Test Configuration.

#### 7.1.5. DATA SAMPLE


| Frequency (MHz) | QuasiPeak Reading (dBuV) | Average Reading (dBuV) | Correction Factor (dB) | QuasiPeak Result (dBuV) | Average Result (dBuV) | QuasiPeak Limit (dBuV) | Average Limit (dBuV) | QuasiPeak Margin (dB) | Average Margin (dB) | Remark (Pass/Fail) |
|-----------------|--------------------------|------------------------|------------------------|-------------------------|-----------------------|------------------------|----------------------|-----------------------|---------------------|--------------------|
| X.XXXX          | 32.69                    | 25.65                  | 11.52                  | 44.21                   | 37.17                 | 65.78                  | 55.79                | -21.57                | -18.62              | Pass               |

Factor = Insertion loss of LISN + Cable Loss  
Result = Quasi-peak Reading/ Average Reading + Factor  
Limit = Limit stated in standard  
Margin = Result (dBuV) – Limit (dBuV)



## 7.1.6. TEST RESULTS

|                          |              |           |        |
|--------------------------|--------------|-----------|--------|
| Model No.                | IR300        | RBW,VBW   | 9 kHz  |
| Environmental Conditions | 22°C, 45% RH | Test Mode | Mode 2 |
| Tested by                | Mack Li      | Line      | L1     |




| Frequency (MHz) | QuasiPeak Reading (dBuV) | Average Reading (dBuV) | Correction Factor (dB) | QuasiPeak Result (dBuV) | Average Result (dBuV) | QuasiPeak Limit (dBuV) | Average Limit (dBuV) | QuasiPeak Margin (dB) | Average Margin (dB) | Remark (Pass/Fail) | Line (L1/L2) |
|-----------------|--------------------------|------------------------|------------------------|-------------------------|-----------------------|------------------------|----------------------|-----------------------|---------------------|--------------------|--------------|
| 0.1500          | 39.09                    | 29.56                  | 9.58                   | 48.67                   | 39.14                 | 65.99                  | 56.00                | -17.32                | -16.86              | Pass               | L1           |
| 0.1980          | 37.16                    | 19.62                  | 9.69                   | 46.85                   | 29.31                 | 63.69                  | 53.69                | -16.84                | -24.38              | Pass               | L1           |
| 0.4220          | 38.04                    | 28.30                  | 9.68                   | 47.72                   | 37.98                 | 57.41                  | 47.41                | -9.69                 | -9.43               | Pass               | L1           |
| 1.3660          | 33.22                    | 17.23                  | 9.72                   | 42.94                   | 26.95                 | 56.00                  | 46.00                | -13.06                | -19.05              | Pass               | L1           |
| 3.5300          | 31.45                    | 12.29                  | 9.71                   | 41.16                   | 22.00                 | 56.00                  | 46.00                | -14.84                | -24.00              | Pass               | L1           |
| 13.7700         | 33.38                    | 18.44                  | 9.90                   | 43.28                   | 28.34                 | 60.00                  | 50.00                | -16.72                | -21.66              | Pass               | L1           |

**REMARKS:** L1 = Line One (Live Line)



|                          |              |           |        |
|--------------------------|--------------|-----------|--------|
| Model No.                | IR300        | RBW,VBW   | 9 kHz  |
| Environmental Conditions | 22°C, 45% RH | Test Mode | Mode 2 |
| Tested by                | Mack Li      | Line      | L1     |



| Frequency (MHz) | QuasiPeak Reading (dBuV) | Average Reading (dBuV) | Correction Factor (dB) | QuasiPeak Result (dBuV) | Average Result (dBuV) | QuasiPeak Limit (dBuV) | Average Limit (dBuV) | QuasiPeak Margin (dB) | Average Margin (dB) | Remark (Pass/Fail) | Line (L1/L2) |
|-----------------|--------------------------|------------------------|------------------------|-------------------------|-----------------------|------------------------|----------------------|-----------------------|---------------------|--------------------|--------------|
| 0.1500          | 37.88                    | 28.56                  | 9.78                   | 47.66                   | 38.34                 | 65.99                  | 56.00                | -18.33                | -17.66              | Pass               | L2           |
| 0.4220          | 36.80                    | 27.86                  | 9.71                   | 46.51                   | 37.57                 | 57.41                  | 47.41                | -10.90                | -9.84               | Pass               | L2           |
| 0.8460          | 31.99                    | 14.97                  | 9.75                   | 41.74                   | 24.72                 | 56.00                  | 46.00                | -14.26                | -21.28              | Pass               | L2           |
| 1.2660          | 31.66                    | 12.92                  | 9.79                   | 41.45                   | 22.71                 | 56.00                  | 46.00                | -14.55                | -23.29              | Pass               | L2           |
| 3.3220          | 30.45                    | 12.77                  | 9.75                   | 40.20                   | 22.52                 | 56.00                  | 46.00                | -15.80                | -23.48              | Pass               | L2           |
| 11.8260         | 32.86                    | 16.60                  | 9.81                   | 42.67                   | 26.41                 | 60.00                  | 50.00                | -17.33                | -23.59              | Pass               | L2           |

**REMARKS:** L2 = Line Two (Neutral Line)



## **7.2. SPURIOUS EMISSIONS MEASUREMENT**

### **7.2.1. CONDUCTED EMISSIONS MEASUREMENT**

#### **7.2.1.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT**

§15.247(d) specifies that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3) requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3) requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

#### **7.2.1.2. TEST INSTRUMENTS**

| <b>Name of Equipment</b> | <b>Manufacturer</b> | <b>Model</b> | <b>Serial Number</b> | <b>Last Calibration</b> | <b>Due Calibration</b> |
|--------------------------|---------------------|--------------|----------------------|-------------------------|------------------------|
| Spectrum Analyzer        | R&S                 | FSU          | 200409               | 09/23/2013              | 09/22/2014             |
| Spectrum Analyzer        | Agilent             | E4446A       | US44300399           | 03/01/2014              | 03/01/2015             |

#### **7.2.1.3. TEST PROCEDURE** (please refer to measurement standard)

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.




#### 7.2.1.4. TEST RESULTS


##### Test Plot


##### IEEE 802.11b mode (Antenna 0)

##### CH Low (30MHz ~26.5GHz)




##### CH Low (2.31GHz ~2.43GHz)








### CH High (30MHz ~26.5GHz)




### CH High (2.45GHz ~2.5GHz)







**IEEE 802.11b mode (Antenna 1)**

**CH Low (30MHz ~26.5GHz)**




**CH Low (2.31GHz ~2.43GHz)**








## CH High (30MHz ~26.5GHz)




## CH High (2.45GHz ~2.5GHz)






IEEE 802.11g mode (Antenna 0)

CH Low (30MHz ~26.5GHz)



Date: 8.JUL.2014 13:58:08


CH Low (2.31GHz ~2.43GHz)



Date: 8.JUL.2014 13:57:25




CH Mid (30MHz ~26.5GHz)




Date: 8.JUL.2014 13:55:50

**CH High (30MHz ~26.5GHz)**



Date: 8.JUL.2014 13:54:28

## CH High (2.45GHz ~2.5GHz)




Date: 8.JUL.2014 13:53:28




IEEE 802.11g mode (Antenna 1)

CH Low (30MHz ~26.5GHz)




Date: 8.JUL.2014 11:21:55

CH Low (2.31GHz ~2.43GHz)




Date: 8.JUL.2014 11:19:46






### CH High (30MHz ~26.5GHz)



Date: 8.JUL.2014 11:26:07

### CH High (2.45GHz ~2.5GHz)




Date: 8.JUL.2014 11:25:07




**IEEE 802.11n HT20 MHz mode (Antenna 0)**

**CH Low (30MHz ~26.5GHz)**



Date: 8.JUL.2014 14:00:37


**CH Low (2.31GHz ~2.43GHz)**



Date: 8.JUL.2014 13:59:24




CH Mid (30MHz ~26.5GHz)



Date: 8.JUL.2014 14:01:51




## CH High (30MHz ~26.5GHz)



Date: 8.JUL.2014 14:03:26

## CH High (2.45GHz ~2.5GHz)




Date: 8.JUL.2014 14:02:37




**IEEE 802.11n HT20 MHz mode (Antenna 1)**

**CH Low (30MHz ~26.5GHz)**




Date: 8.JUL.2014 11:40:01

**CH Low (2.31GHz ~2.43GHz)**




Date: 8.JUL.2014 11:37:32






### CH High (30MHz ~26.5GHz)



Date: 8.JUL.2014 11:35:46

### CH High (2.45GHz ~2.5GHz)




Date: 8.JUL.2014 11:34:54




**IEEE 802.11n HT40 MHz mode (Antenna 0)**

**CH Low (30MHz ~26.5GHz)**



Date: 8.JUL.2014 14:05:46


**CH Low (2.31GHz ~2.45GHz)**



Date: 8.JUL.2014 14:04:50




CH Mid (30MHz ~26.5GHz)



Date: 8.JUL.2014 14:06:57




### CH High (30MHz ~26.5GHz)



Date: 8.JUL.2014 14:08:22

### CH High (2.43GHz ~2.5GHz)




Date: 8.JUL.2014 14:07:43




**IEEE 802.11n HT40 MHz mode (Antenna 1)**

**CH Low (30MHz ~26.5GHz)**



Date: 8.JUL.2014 14:17:13


**CH Low (2.31GHz ~2.45GHz)**



Date: 8.JUL.2014 14:16:34




CH Mid (30MHz ~26.5GHz)



Date: 8.JUL.2014 14:13:12




### CH High (30MHz ~26.5GHz)



Date: 8.JUL.2014 14:15:18

### CH High (2.43GHz ~2.5GHz)



Date: 8.JUL.2014 14:11:49

**7.2.2. RADIATED EMISSIONS MEASUREMENT****7.2.2.1. LIMITS OF RADIATED EMISSIONS MEASUREMENT**

According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength (mV/m) | Measurement Distance (m) |
|-----------------|-----------------------|--------------------------|
| 0.009-0.490     | 2400/F(kHz)           | 300                      |
| 0.490-1.705     | 24000/F(kHz)          | 30                       |
| 1.705-30.0      | 30                    | 30                       |
| 30-88           | 100*                  | 3                        |
| 88-216          | 150*                  | 3                        |
| 216-960         | 200*                  | 3                        |
| Above 960       | 500                   | 3                        |

**Remark:** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

1. In the emission table above, the tighter limit applies at the band edges.

| Frequency (MHz) | Field Strength (μV/m at 3-meter) | Field Strength (dBμV/m at 3-meter) |
|-----------------|----------------------------------|------------------------------------|
| 30-88           | 100                              | 40                                 |
| 88-216          | 150                              | 43.5                               |
| 216-960         | 200                              | 46                                 |
| Above 960       | 500                              | 54                                 |

**NOTE:**(1) The lower limit shall apply at the transition frequencies.

(2) Emission level (dBμV/m) = 20 log Emission level (μV/m).

**7.2.2.2. TEST INSTRUMENTS**

| <b>Radiated Emission Test Site 966 (2)</b> |                     |                     |                      |                         |                        |
|--------------------------------------------|---------------------|---------------------|----------------------|-------------------------|------------------------|
| <b>Name of Equipment</b>                   | <b>Manufacturer</b> | <b>Model Number</b> | <b>Serial Number</b> | <b>Last Calibration</b> | <b>Due Calibration</b> |
| PSA Series Spectrum Analyzer               | Agilent             | E4446A              | US44300399           | 03/01/2014              | 03/01/2015             |
| EMI TEST RECEIVER                          | ROHDE&SCHWARZ       | ESCI                | 100783               | 03/09/2014              | 03/08/2015             |
| Amplifier                                  | MITEQ               | AM-1604-3000        | 1123808              | 03/18/2014              | 03/18/2015             |
| High Noise Amplifier                       | Agilent             | 8449B               | 3008A01838           | 03/18/2014              | 03/18/2015             |
| Board-Band Horn Antenna                    | Schwarzbeck         | BBHA 9170           | 9170-497             | 07/10/2014              | 07/09/2015             |
| Bilog Antenna                              | SCHAFFNER           | CBL6143             | 5082                 | 03/01/2014              | 03/01/2015             |
| Horn Antenna                               | SCHWARZBECK         | BBHA9120            | D286                 | 03/01/2014              | 03/01/2015             |
| Loop Antenna                               | COM-POWER           | AL-130              | 121044               | 09/27/2013              | 09/26/2014             |
| Turn Table                                 | N/A                 | N/A                 | N/A                  | N.C.R                   | N.C.R                  |
| Controller                                 | Sunol Sciences      | SC104V              | 022310-1             | N.C.R                   | N.C.R                  |
| Controller                                 | CT                  | N/A                 | N/A                  | N.C.R                   | N.C.R                  |
| Temp. / Humidity Meter                     | Anymetre            | JR913               | N/A                  | 02/28/2014              | 02/28/2015             |
| Antenna Tower                              | SUNOL               | TLT2                | N/A                  | N.C.R                   | N.C.R                  |
| Test S/W                                   | FARAD               | LZ-RF / CCS-SZ-3A2  |                      |                         |                        |

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The FCC Site Registration number is 101879.
3. N.C.R = No Calibration Required.




**7.2.2.3. TEST PROCEDURE** (please refer to measurement standard)

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:
  - Below 1GHz:
    - RBW=100kHz / VBW=300kHz / Sweep=AUTO
  - Above 1GHz:
    - (a) PEAK: RBW=1MHz,VBW=3MHz / Sweep=AUTO
    - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.




#### 7.2.2.4. TEST SETUP

##### Below 30MHz




##### Below 1 GHz





**Above 1 GHz**



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

**7.2.2.5. DATA SAPLE****Below 1GHz**

| Frequency (MHz) | Reading (dBuV) | Correct Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|-----------------------|-----------------|----------------|-------------|--------------------|--------|
| XXX.XXXX        | 36.37          | -12.20                | 24.17           | 40.00          | -15.83      | V                  | QP     |

Frequency (MHz) = Emission frequency in MHz  
 Reading (dBuV) = Uncorrected Analyzer / Receiver reading  
 Correct Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain  
 Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)  
 Limit (dBuV/m) = Limit stated in standard  
 Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)  
 Q.P. = Quasi-peak Reading

**Above 1GHz**

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| XXXX.XXXX       | 62.09          | -11.42                   | 50.67           | 74.00          | -23.33      | V                  | Peak   |
| XXXX.XXXX       | 49.78          | -11.42                   | 38.36           | 54.00          | -15.64      | V                  | AVG    |

Frequency (MHz) = Emission frequency in MHz  
 Reading (dBuV) = Uncorrected Analyzer / Receiver reading  
 Correction Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain  
 Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)  
 Limit (dBuV/m) = Limit stated in standard  
 Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)  
 Peak = Peak Reading  
 AVG = Average Reading

**Calculation Formula**

Margin (dB) = Result (dBuV/m) – Limits (dBuV/m)  
 Result (dBuV/m) = Reading (dBuV) + Correction Factor

**7.2.2.6. TEST RESULTS****Below 1 GHz****Test Mode:** TX**Tested by:** Mack Li**Ambient temperature:** 24°C**Relative humidity:** 52% RH**Date:** July 3, 2013

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| 106.6300        | 48.77          | -8.30                    | 40.47           | 43.50          | -3.03       | V                  | QP     |
| 142.5200        | 42.05          | -3.45                    | 38.60           | 43.50          | -4.90       | V                  | QP     |
| 174.5300        | 44.89          | -5.84                    | 39.05           | 43.50          | -4.45       | V                  | QP     |
| 237.5800        | 37.49          | -2.24                    | 35.25           | 46.00          | -10.75      | V                  | QP     |
| 600.3600        | 42.31          | -1.26                    | 41.05           | 46.00          | -4.95       | V                  | QP     |
| 799.2100        | 36.25          | -0.77                    | 35.48           | 46.00          | -10.52      | V                  | QP     |
|                 |                |                          |                 |                |             |                    |        |
| 109.5400        | 47.94          | -12.16                   | 35.78           | 43.50          | -7.72       | H                  | QP     |
| 199.7500        | 49.28          | -9.27                    | 40.01           | 43.50          | -3.49       | H                  | QP     |
| 243.4000        | 42.92          | -2.07                    | 40.85           | 46.00          | -5.15       | H                  | QP     |
| 386.9600        | 45.50          | -5.72                    | 39.78           | 46.00          | -6.22       | H                  | QP     |
| 600.3600        | 41.31          | -0.33                    | 40.98           | 46.00          | -5.02       | H                  | QP     |
| 750.7100        | 41.73          | -4.70                    | 37.03           | 46.00          | -8.97       | H                  | QP     |

**\*\*Remark:** No emission found between lowest internal used/generated frequency to 30MHz.**Notes:**

1. Radiated emissions measured in frequency range from 9kHz to 1GHz were made with an instrument using Quasi-peak detector mode.
2. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
3. The IF bandwidth of Receiver between 30MHz to 1GHz was 120kHz.
4. Frequency (MHz). = Emission frequency in MHz  
 Reading (dBuV/m) = Receiver reading  
 Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain  
 Limit (dBuV/m) = Limit stated in standard  
 Margin (dB) = Measured (dBuV/m) – Limits (dBuV/m)  
 Antenna Pole (H/V) = Current carrying line of reading

**Above 1 GHz****Antenna 0****Test Mode:** TX / IEEE 802.11b(CH Low)**Tested by:** Mack Li**Ambient temperature:** 24°C **Relative humidity:** 52% RH**Date:** June 29, 2014

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| 3043.000        | 44.79          | -3.72                    | 41.07           | 74.00          | -32.93      | V                  | peak   |
| 3628.000        | 43.42          | -2.42                    | 41.00           | 74.00          | -33.00      | V                  | peak   |
| 4825.000        | 50.71          | 1.78                     | 52.49           | 74.00          | -21.51      | V                  | peak   |
| 4825.000        | 48.37          | 1.78                     | 50.15           | 54.00          | -3.85       | V                  | AVG    |
| 5347.000        | 40.82          | 2.54                     | 43.36           | 74.00          | -30.64      | V                  | peak   |
| 6085.000        | 40.07          | 3.76                     | 43.83           | 74.00          | -30.17      | V                  | peak   |
| 6949.000        | 41.94          | 7.48                     | 49.42           | 74.00          | -24.58      | V                  | peak   |
|                 |                |                          |                 |                |             |                    |        |
| 3376.000        | 44.31          | -3.12                    | 41.19           | 74.00          | -32.81      | H                  | Peak   |
| 4204.000        | 42.47          | -0.44                    | 42.03           | 74.00          | -31.97      | H                  | Peak   |
| 4825.000        | 46.04          | 1.78                     | 47.82           | 74.00          | -26.18      | H                  | Peak   |
| 5752.000        | 41.31          | 2.97                     | 44.28           | 74.00          | -29.72      | H                  | peak   |
| 6580.000        | 40.16          | 5.89                     | 46.05           | 74.00          | -27.95      | H                  | peak   |
| 6958.000        | 41.21          | 7.52                     | 48.73           | 74.00          | -25.27      | H                  | peak   |

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Test Mode:** TX / IEEE 802.11b (CH Mid)**Tested by:** Mack Li**Ambient temperature:** 24°C**Relative humidity:** 52% RH**Date:** June 29, 2014

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| 3223.000        | 43.45          | -3.39                    | 40.06           | 74.00          | -33.94      | V                  | Peak   |
| 3871.000        | 42.84          | -1.52                    | 41.32           | 74.00          | -32.68      | V                  | Peak   |
| 4870.000        | 48.48          | 1.97                     | 50.45           | 74.00          | -23.55      | V                  | Peak   |
| 5842.000        | 40.61          | 3.12                     | 43.73           | 74.00          | -30.27      | V                  | Peak   |
| 6724.000        | 40.17          | 6.51                     | 46.68           | 74.00          | -27.32      | V                  | Peak   |
| 7669.000        | 40.16          | 9.00                     | 49.16           | 74.00          | -24.84      | V                  | Peak   |
|                 |                |                          |                 |                |             |                    |        |
| 4033.000        | 42.69          | -0.94                    | 41.75           | 74.00          | -32.25      | H                  | Peak   |
| 4870.000        | 44.89          | 1.97                     | 46.86           | 74.00          | -27.14      | H                  | Peak   |
| 5644.000        | 40.91          | 2.79                     | 43.70           | 74.00          | -30.30      | H                  | Peak   |
| 6166.000        | 41.34          | 4.11                     | 45.45           | 74.00          | -28.55      | H                  | Peak   |
| 6904.000        | 40.74          | 7.29                     | 48.03           | 74.00          | -25.97      | H                  | Peak   |
| 7543.000        | 40.81          | 8.76                     | 49.57           | 74.00          | -24.43      | H                  | Peak   |

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



**Test Mode:** TX / IEEE 802.11b (CH High)

**Tested by:** Mack Li

**Ambient temperature:** 24°C

**Relative humidity:** 52% RH

**Date:** June 29, 2014

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| 3727.000        | 42.44          | -2.05                    | 40.39           | 74.00          | -33.61      | V                  | Peak   |
| 4303.000        | 42.64          | -0.15                    | 42.49           | 74.00          | -31.51      | V                  | Peak   |
| 4924.000        | 46.63          | 2.19                     | 48.82           | 74.00          | -25.18      | V                  | Peak   |
| 5905.000        | 40.36          | 3.23                     | 43.59           | 74.00          | -30.41      | V                  | Peak   |
| 6562.000        | 39.93          | 5.81                     | 45.74           | 74.00          | -28.26      | V                  | Peak   |
| 7669.000        | 40.93          | 9.00                     | 49.93           | 74.00          | -24.07      | V                  | Peak   |
|                 |                |                          |                 |                |             |                    |        |
| 3979.000        | 41.73          | -1.12                    | 40.61           | 74.00          | -33.39      | H                  | Peak   |
| 4924.000        | 42.77          | 2.19                     | 44.96           | 74.00          | -29.04      | H                  | Peak   |
| 5905.000        | 41.28          | 3.23                     | 44.51           | 74.00          | -29.49      | H                  | Peak   |
| 7030.000        | 41.42          | 7.76                     | 49.18           | 74.00          | -24.82      | H                  | Peak   |
| 7597.000        | 40.75          | 8.86                     | 49.61           | 74.00          | -24.39      | H                  | Peak   |
| 8362.000        | 40.50          | 9.45                     | 49.95           | 74.00          | -24.05      | H                  | Peak   |

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Antenna 1****Test Mode:** TX / IEEE 802.11b(CH Low)**Tested by:** Mack Li**Ambient temperature:** 24°C**Relative humidity:** 52% RH**Date:** June 29, 2014

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| 3574.000        | 42.91          | -2.62                    | 40.29           | 74.00          | -33.71      | V                  | peak   |
| 4267.000        | 41.42          | -0.26                    | 41.16           | 74.00          | -32.84      | V                  | peak   |
| 4825.000        | 48.88          | 1.78                     | 50.66           | 74.00          | -23.34      | V                  | peak   |
| 5752.000        | 41.51          | 2.97                     | 44.48           | 74.00          | -29.52      | V                  | peak   |
| 6769.000        | 40.73          | 6.70                     | 47.43           | 74.00          | -26.57      | V                  | peak   |
| 7741.000        | 40.81          | 9.14                     | 49.95           | 74.00          | -24.05      | V                  | peak   |
|                 |                |                          |                 |                |             |                    |        |
| 3304.000        | 43.23          | -3.25                    | 39.98           | 74.00          | -34.02      | H                  | Peak   |
| 3907.000        | 42.23          | -1.38                    | 40.85           | 74.00          | -33.15      | H                  | Peak   |
| 4825.000        | 43.35          | 1.78                     | 45.13           | 74.00          | -28.87      | H                  | Peak   |
| 5824.000        | 40.56          | 3.09                     | 43.65           | 74.00          | -30.35      | H                  | peak   |
| 6715.000        | 39.93          | 6.47                     | 46.40           | 74.00          | -27.60      | H                  | peak   |
| 7516.000        | 39.45          | 8.71                     | 48.16           | 74.00          | -25.84      | H                  | peak   |

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Test Mode:** TX / IEEE 802.11b (CH Mid)**Tested by:** Mack Li**Ambient temperature:** 24°C**Relative humidity:** 52% RH**Date:** June 29, 2014

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| 3268.000        | 43.87          | -3.31                    | 40.56           | 74.00          | -33.44      | V                  | Peak   |
| 3961.000        | 42.30          | -1.18                    | 41.12           | 74.00          | -32.88      | V                  | Peak   |
| 4870.000        | 46.85          | 1.97                     | 48.82           | 74.00          | -25.18      | V                  | Peak   |
| 6202.000        | 39.82          | 4.26                     | 44.08           | 74.00          | -29.92      | V                  | Peak   |
| 6967.000        | 41.00          | 7.56                     | 48.56           | 74.00          | -25.44      | V                  | Peak   |
| 7732.000        | 40.25          | 9.13                     | 49.38           | 74.00          | -24.62      | V                  | Peak   |
|                 |                |                          |                 |                |             |                    |        |
| 3214.000        | 43.52          | -3.41                    | 40.11           | 74.00          | -33.89      | H                  | Peak   |
| 3970.000        | 41.90          | -1.15                    | 40.75           | 74.00          | -33.25      | H                  | Peak   |
| 4870.000        | 43.26          | 1.97                     | 45.23           | 74.00          | -28.77      | H                  | Peak   |
| 5338.000        | 40.99          | 2.54                     | 43.53           | 74.00          | -30.47      | H                  | Peak   |
| 6553.000        | 39.26          | 5.77                     | 45.03           | 74.00          | -28.97      | H                  | Peak   |
| 7471.000        | 39.87          | 8.62                     | 48.49           | 74.00          | -25.51      | H                  | Peak   |

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Test Mode:** TX / IEEE 802.11b (CH High)**Tested by:** Mack Li**Ambient temperature:** 24°C**Relative humidity:** 52% RH**Date:** June 29, 2014

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| 3448.000        | 43.84          | -2.98                    | 40.86           | 74.00          | -33.14      | V                  | Peak   |
| 4033.000        | 42.48          | -0.94                    | 41.54           | 74.00          | -32.46      | V                  | Peak   |
| 4924.000        | 45.53          | 2.19                     | 47.72           | 74.00          | -26.28      | V                  | Peak   |
| 5419.000        | 41.28          | 2.54                     | 43.82           | 74.00          | -30.18      | V                  | Peak   |
| 6364.000        | 39.92          | 4.96                     | 44.88           | 74.00          | -29.12      | V                  | Peak   |
| 6931.000        | 40.24          | 7.40                     | 47.64           | 74.00          | -26.36      | V                  | Peak   |
|                 |                |                          |                 |                |             |                    |        |
| 4303.000        | 42.63          | -0.15                    | 42.48           | 74.00          | -31.52      | H                  | Peak   |
| 4924.000        | 42.16          | 2.19                     | 44.35           | 74.00          | -29.65      | H                  | Peak   |
| 5464.000        | 40.92          | 2.55                     | 43.47           | 74.00          | -30.53      | H                  | Peak   |
| 6220.000        | 40.30          | 4.34                     | 44.64           | 74.00          | -29.36      | H                  | Peak   |
| 7003.000        | 41.21          | 7.71                     | 48.92           | 74.00          | -25.08      | H                  | Peak   |
| 7768.000        | 40.17          | 9.20                     | 49.37           | 74.00          | -24.63      | H                  | Peak   |

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Antenna 0****Test Mode:** TX / IEEE 802.11g(CH Low)**Tested by:** Mack Li**Ambient temperature:** 24°C**Relative humidity:** 52% RH**Date:** June 29, 2014

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| 3763.9000       | 43.23          | -1.91                    | 41.32           | 74.00          | -32.68      | V                  | Peak   |
| 4646.8000       | 41.89          | 1.04                     | 42.93           | 74.00          | -31.07      | V                  | Peak   |
| 5173.3000       | 40.93          | 2.52                     | 43.45           | 74.00          | -30.55      | V                  | Peak   |
| 6218.2000       | 41.10          | 4.33                     | 45.43           | 74.00          | -28.57      | V                  | Peak   |
| 6892.3000       | 39.72          | 7.24                     | 46.96           | 74.00          | -27.04      | V                  | Peak   |
| 7707.7000       | 39.71          | 9.08                     | 48.79           | 74.00          | -25.21      | V                  | Peak   |
|                 |                |                          |                 |                |             |                    |        |
| 2989.9000       | 44.52          | -3.85                    | 40.67           | 74.00          | -33.33      | H                  | Peak   |
| 4276.0000       | 42.70          | -0.23                    | 42.47           | 74.00          | -31.53      | H                  | Peak   |
| 4932.1000       | 41.12          | 2.23                     | 43.35           | 74.00          | -30.65      | H                  | Peak   |
| 5921.2000       | 39.98          | 3.26                     | 43.24           | 74.00          | -30.76      | H                  | Peak   |
| 7119.1000       | 40.76          | 7.93                     | 48.69           | 74.00          | -25.31      | H                  | Peak   |
| 8019.1000       | 39.81          | 9.64                     | 49.45           | 74.00          | -24.55      | H                  | Peak   |

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Test Mode: TX / IEEE 802.11g (CH Mid)

Tested by: Mack Li

Ambient temperature: 24°C Relative humidity: 52% RH

Date: June 29, 2014

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| 3168.1000       | 44.52          | -3.49                    | 41.03           | 74.00          | -32.97      | V                  | Peak   |
| 4188.7000       | 41.63          | -0.49                    | 41.14           | 74.00          | -32.86      | V                  | Peak   |
| 4801.6000       | 41.38          | 1.68                     | 43.06           | 74.00          | -30.94      | V                  | Peak   |
| 5688.1000       | 41.25          | 2.87                     | 44.12           | 74.00          | -29.88      | V                  | Peak   |
| 6570.1000       | 39.70          | 5.85                     | 45.55           | 74.00          | -28.45      | V                  | Peak   |
| 7712.2000       | 40.40          | 9.09                     | 49.49           | 74.00          | -24.51      | V                  | Peak   |
|                 |                |                          |                 |                |             |                    |        |
| 3859.3000       | 43.44          | -1.56                    | 41.88           | 74.00          | -32.12      | H                  | Peak   |
| 4908.7000       | 41.10          | 2.13                     | 43.23           | 74.00          | -30.77      | H                  | Peak   |
| 5742.1000       | 40.72          | 2.96                     | 43.68           | 74.00          | -30.32      | H                  | Peak   |
| 6596.2000       | 39.79          | 5.96                     | 45.75           | 74.00          | -28.25      | H                  | Peak   |
| 7438.6000       | 40.18          | 8.56                     | 48.74           | 74.00          | -25.26      | H                  | Peak   |
| 8221.6000       | 40.58          | 9.53                     | 50.11           | 74.00          | -23.89      | H                  | Peak   |

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Test Mode:** TX / IEEE 802.11g (CH High)**Tested by:** Mack Li**Ambient temperature:** 24°C **Relative humidity:** 52% RH**Date:** June 29, 2014

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| 3207.7000       | 44.25          | -3.42                    | 40.83           | 74.00          | -33.17      | V                  | Peak   |
| 4042.9000       | 42.68          | -0.91                    | 41.77           | 74.00          | -32.23      | V                  | Peak   |
| 5039.2000       | 41.55          | 2.51                     | 44.06           | 74.00          | -29.94      | V                  | Peak   |
| 5714.2000       | 40.30          | 2.91                     | 43.21           | 74.00          | -30.79      | V                  | Peak   |
| 6769.9000       | 39.65          | 6.71                     | 46.36           | 74.00          | -27.64      | V                  | Peak   |
| 7288.3000       | 40.39          | 8.26                     | 48.65           | 74.00          | -25.35      | V                  | Peak   |
|                 |                |                          |                 |                |             |                    |        |
| 3865.6000       | 43.11          | -1.54                    | 41.57           | 74.00          | -32.43      | H                  | Peak   |
| 4836.7000       | 41.74          | 1.83                     | 43.57           | 74.00          | -30.43      | H                  | Peak   |
| 5307.4000       | 41.36          | 2.53                     | 43.89           | 74.00          | -30.11      | H                  | Peak   |
| 6152.5000       | 40.43          | 4.05                     | 44.48           | 74.00          | -29.52      | H                  | Peak   |
| 7090.3000       | 39.69          | 7.88                     | 47.57           | 74.00          | -26.43      | H                  | Peak   |
| 8103.7000       | 39.96          | 9.59                     | 49.55           | 74.00          | -24.45      | H                  | Peak   |

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Antenna 1****Test Mode:** TX / IEEE 802.11g(CH Low)**Tested by:** Mack Li**Ambient temperature:** 24°C**Relative humidity:** 52% RH**Date:** June 29, 2014

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| 3205.0000       | 44.30          | -3.43                    | 40.87           | 74.00          | -33.13      | V                  | Peak   |
| 3768.4000       | 43.03          | -1.90                    | 41.13           | 74.00          | -32.87      | V                  | Peak   |
| 4813.3000       | 42.99          | 1.73                     | 44.72           | 74.00          | -29.28      | V                  | Peak   |
| 5750.2000       | 40.97          | 2.97                     | 43.94           | 74.00          | -30.06      | V                  | Peak   |
| 6412.6000       | 40.62          | 5.17                     | 45.79           | 74.00          | -28.21      | V                  | Peak   |
| 7246.0000       | 40.91          | 8.18                     | 49.09           | 74.00          | -24.91      | V                  | Peak   |
|                 |                |                          |                 |                |             |                    |        |
| 3631.6000       | 42.88          | -2.40                    | 40.48           | 74.00          | -33.52      | H                  | Peak   |
| 4734.1000       | 41.89          | 1.40                     | 43.29           | 74.00          | -30.71      | H                  | Peak   |
| 5140.9000       | 41.67          | 2.52                     | 44.19           | 74.00          | -29.81      | H                  | Peak   |
| 6376.6000       | 40.13          | 5.01                     | 45.14           | 74.00          | -28.86      | H                  | Peak   |
| 7311.7000       | 40.26          | 8.31                     | 48.57           | 74.00          | -25.43      | H                  | Peak   |
| 8224.3000       | 39.96          | 9.53                     | 49.49           | 74.00          | -24.51      | H                  | Peak   |

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



**Test Mode:** TX / IEEE 802.11g (CH Mid)

**Tested by:** Mack Li

**Ambient temperature:** 24°C **Relative humidity:** 52% RH

**Date:** June 29, 2014

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| 3730.6000       | 44.62          | -2.04                    | 42.58           | 74.00          | -31.42      | V                  | Peak   |
| 5059.9000       | 41.86          | 2.51                     | 44.37           | 74.00          | -29.63      | V                  | Peak   |
| 5808.7000       | 41.32          | 3.07                     | 44.39           | 74.00          | -29.61      | V                  | Peak   |
| 6589.9000       | 41.16          | 5.93                     | 47.09           | 74.00          | -26.91      | V                  | Peak   |
| 7022.8000       | 40.32          | 7.74                     | 48.06           | 74.00          | -25.94      | V                  | Peak   |
| 7967.8000       | 40.91          | 9.59                     | 50.50           | 74.00          | -23.50      | V                  | Peak   |
|                 |                |                          |                 |                |             |                    |        |
| 4034.8000       | 43.63          | -0.94                    | 42.69           | 74.00          | -31.31      | H                  | Peak   |
| 5132.8000       | 40.92          | 2.52                     | 43.44           | 74.00          | -30.56      | H                  | Peak   |
| 5778.1000       | 40.95          | 3.02                     | 43.97           | 74.00          | -30.03      | H                  | Peak   |
| 6309.1000       | 40.69          | 4.72                     | 45.41           | 74.00          | -28.59      | H                  | Peak   |
| 7369.3000       | 39.77          | 8.42                     | 48.19           | 74.00          | -25.81      | H                  | Peak   |
| 7920.1000       | 40.43          | 9.49                     | 49.92           | 74.00          | -24.08      | H                  | Peak   |

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



**Test Mode:** TX / IEEE 802.11g (CH High)

**Tested by:** Mack Li

**Ambient temperature:** 24°C

**Relative humidity:** 52% RH

**Date:** June 29, 2014

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| 3438.1000       | 43.18          | -3.00                    | 40.18           | 74.00          | -33.82      | V                  | Peak   |
| 3865.6000       | 43.12          | -1.54                    | 41.58           | 74.00          | -32.42      | V                  | Peak   |
| 5025.7000       | 40.90          | 2.51                     | 43.41           | 74.00          | -30.59      | V                  | Peak   |
| 6173.2000       | 40.52          | 4.14                     | 44.66           | 74.00          | -29.34      | V                  | Peak   |
| 7207.3000       | 39.35          | 8.10                     | 47.45           | 74.00          | -26.55      | V                  | Peak   |
| 7999.3000       | 40.41          | 9.65                     | 50.06           | 74.00          | -23.94      | V                  | Peak   |
|                 |                |                          |                 |                |             |                    |        |
| 3700.0000       | 42.73          | -2.15                    | 40.58           | 74.00          | -33.42      | H                  | Peak   |
| 4965.4000       | 41.55          | 2.37                     | 43.92           | 74.00          | -30.08      | H                  | Peak   |
| 5428.9000       | 41.03          | 2.54                     | 43.57           | 74.00          | -30.43      | H                  | Peak   |
| 6619.6000       | 40.73          | 6.06                     | 46.79           | 74.00          | -27.21      | H                  | Peak   |
| 7390.0000       | 40.20          | 8.46                     | 48.66           | 74.00          | -25.34      | H                  | Peak   |
| 7964.2000       | 39.69          | 9.58                     | 49.27           | 74.00          | -24.73      | H                  | Peak   |

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



## Combine with Antenna 0 and Antenna 1

**Test Mode:** TX / IEEE 802.11n HT20 MHz (CH Low)

**Tested by:** Mack Li

**Ambient temperature:** 24°C      **Relative humidity:** 52% RH

**Date:** June 29, 2014

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| 3440.8000       | 43.47          | -3.00                    | 40.47           | 74.00          | -33.53      | V                  | Peak   |
| 3833.2000       | 43.26          | -1.66                    | 41.60           | 74.00          | -32.40      | V                  | Peak   |
| 5133.7000       | 41.82          | 2.52                     | 44.34           | 74.00          | -29.66      | V                  | Peak   |
| 5876.2000       | 40.20          | 3.18                     | 43.38           | 74.00          | -30.62      | V                  | Peak   |
| 7069.6000       | 40.69          | 7.84                     | 48.53           | 74.00          | -25.47      | V                  | Peak   |
| 7993.0000       | 40.39          | 9.64                     | 50.03           | 74.00          | -23.97      | V                  | Peak   |
|                 |                |                          |                 |                |             |                    |        |
| 3862.0000       | 42.86          | -1.55                    | 41.31           | 74.00          | -32.69      | H                  | Peak   |
| 4792.6000       | 41.49          | 1.65                     | 43.14           | 74.00          | -30.86      | H                  | Peak   |
| 5834.8000       | 40.65          | 3.11                     | 43.76           | 74.00          | -30.24      | H                  | Peak   |
| 6911.2000       | 39.31          | 7.32                     | 46.63           | 74.00          | -27.37      | H                  | Peak   |
| 7606.0000       | 40.01          | 8.88                     | 48.89           | 74.00          | -25.11      | H                  | Peak   |
| 8239.6000       | 39.79          | 9.52                     | 49.31           | 74.00          | -24.69      | H                  | Peak   |

### REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Test Mode:** TX / IEEE 802.11n HT20 MHz (CH Mid)**Tested by:** Mack Li**Ambient temperature:** 24°C **Relative humidity:** 52% RH**Date:** June 29, 2014

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| 3860.2000       | 43.58          | -1.56                    | 42.02           | 74.00          | -31.98      | V                  | Peak   |
| 4961.8000       | 41.19          | 2.35                     | 43.54           | 74.00          | -30.46      | V                  | Peak   |
| 6033.7000       | 40.00          | 3.54                     | 43.54           | 74.00          | -30.46      | V                  | Peak   |
| 6811.3000       | 39.61          | 6.89                     | 46.50           | 74.00          | -27.50      | V                  | Peak   |
| 7593.4000       | 39.64          | 8.86                     | 48.50           | 74.00          | -25.50      | V                  | Peak   |
| 8019.1000       | 40.36          | 9.64                     | 50.00           | 74.00          | -24.00      | V                  | Peak   |
|                 |                |                          |                 |                |             |                    |        |
| 3214.0000       | 44.54          | -3.41                    | 41.13           | 74.00          | -32.87      | H                  | Peak   |
| 4201.3000       | 41.71          | -0.45                    | 41.26           | 74.00          | -32.74      | H                  | Peak   |
| 4843.0000       | 41.75          | 1.86                     | 43.61           | 74.00          | -30.39      | H                  | Peak   |
| 5544.1000       | 40.93          | 2.62                     | 43.55           | 74.00          | -30.45      | H                  | Peak   |
| 6490.9000       | 40.21          | 5.51                     | 45.72           | 74.00          | -28.28      | H                  | Peak   |
| 7431.4000       | 39.65          | 8.54                     | 48.19           | 74.00          | -25.81      | H                  | Peak   |

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



**Test Mode:** TX / EEE 802.11n HT20 MHz (CH High)

**Tested by:** Mack Li

**Ambient temperature:** 24°C

**Relative humidity:** 52% RH

**Date:** June 29, 2014

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| 3765.7000       | 43.38          | -1.91                    | 41.47           | 74.00          | -32.53      | V                  | Peak   |
| 5005.0000       | 41.05          | 2.51                     | 43.56           | 74.00          | -30.44      | V                  | Peak   |
| 5553.1000       | 40.56          | 2.64                     | 43.20           | 74.00          | -30.80      | V                  | Peak   |
| 6198.4000       | 39.95          | 4.25                     | 44.20           | 74.00          | -29.80      | V                  | Peak   |
| 7067.8000       | 39.61          | 7.83                     | 47.44           | 74.00          | -26.56      | V                  | Peak   |
| 7631.2000       | 40.24          | 8.93                     | 49.17           | 74.00          | -24.83      | V                  | Peak   |
|                 |                |                          |                 |                |             |                    |        |
| 3741.4000       | 43.50          | -2.00                    | 41.50           | 74.00          | -32.50      | H                  | Peak   |
| 4304.8000       | 42.99          | -0.14                    | 42.85           | 74.00          | -31.15      | H                  | Peak   |
| 5072.5000       | 42.54          | 2.52                     | 45.06           | 74.00          | -28.94      | H                  | Peak   |
| 6245.2000       | 39.89          | 4.45                     | 44.34           | 74.00          | -29.66      | H                  | Peak   |
| 7246.0000       | 40.34          | 8.18                     | 48.52           | 74.00          | -25.48      | H                  | Peak   |
| 7557.4000       | 40.24          | 8.79                     | 49.03           | 74.00          | -24.97      | H                  | Peak   |

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



## Combine with Antenna 0 and Antenna 1

Test Mode: TX/ IEEE 802.11n HT40 MHz (CH Low)

Tested by: Mack Li

Ambient temperature: 24°C

Relative humidity: 52% RH

Date: June 29, 2014

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| 3307.6000       | 43.67          | -3.24                    | 40.43           | 74.00          | -33.57      | V                  | Peak   |
| 4593.7000       | 41.74          | 0.82                     | 42.56           | 74.00          | -31.44      | V                  | Peak   |
| 5712.4000       | 41.26          | 2.91                     | 44.17           | 74.00          | -29.83      | V                  | Peak   |
| 6423.4000       | 40.17          | 5.21                     | 45.38           | 74.00          | -28.62      | V                  | Peak   |
| 6990.4000       | 40.19          | 7.66                     | 47.85           | 74.00          | -26.15      | V                  | Peak   |
| 7998.4000       | 40.69          | 9.65                     | 50.34           | 74.00          | -23.66      | V                  | Peak   |
|                 |                |                          |                 |                |             |                    |        |
| 3449.8000       | 43.35          | -2.98                    | 40.37           | 74.00          | -33.63      | H                  | Peak   |
| 4395.7000       | 41.21          | 0.12                     | 41.33           | 74.00          | -32.67      | H                  | Peak   |
| 5029.3000       | 41.74          | 2.51                     | 44.25           | 74.00          | -29.75      | H                  | Peak   |
| 5953.6000       | 40.75          | 3.31                     | 44.06           | 74.00          | -29.94      | H                  | Peak   |
| 6578.2000       | 39.71          | 5.88                     | 45.59           | 74.00          | -28.41      | H                  | Peak   |
| 7930.9000       | 40.93          | 9.52                     | 50.45           | 74.00          | -23.55      | H                  | Peak   |

### REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



**Test Mode:** TX / IEEE 802.11n HT40 MHz (CH Mid)

**Tested by:** Mack Li

**Ambient temperature:** 24°C

**Relative humidity:** 52% RH

**Date:** June 29, 2014

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| 3111.4000       | 44.39          | -3.60                    | 40.79           | 74.00          | -33.21      | V                  | Peak   |
| 4323.7000       | 42.00          | -0.09                    | 41.91           | 74.00          | -32.09      | V                  | Peak   |
| 4876.3000       | 43.12          | 2.00                     | 45.12           | 74.00          | -28.88      | V                  | Peak   |
| 6179.5000       | 39.76          | 4.16                     | 43.92           | 74.00          | -30.08      | V                  | Peak   |
| 7140.7000       | 39.51          | 7.97                     | 47.48           | 74.00          | -26.52      | V                  | Peak   |
| 7690.6000       | 40.36          | 9.05                     | 49.41           | 74.00          | -24.59      | V                  | Peak   |
|                 |                |                          |                 |                |             |                    |        |
| 4243.6000       | 42.08          | -0.32                    | 41.76           | 74.00          | -32.24      | H                  | Peak   |
| 5074.3000       | 41.62          | 2.52                     | 44.14           | 74.00          | -29.86      | H                  | Peak   |
| 5718.7000       | 40.32          | 2.92                     | 43.24           | 74.00          | -30.76      | H                  | Peak   |
| 6625.0000       | 40.57          | 6.08                     | 46.65           | 74.00          | -27.35      | H                  | Peak   |
| 7419.7000       | 39.95          | 8.52                     | 48.47           | 74.00          | -25.53      | H                  | Peak   |
| 7786.9000       | 40.91          | 9.23                     | 50.14           | 74.00          | -23.86      | H                  | Peak   |

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Test Mode:** TX/ IEEE 802.11n HT40 MHz (CH High)**Tested by:** Mack Li**Ambient temperature:** 24°C **Relative humidity:** 52% RH**Date:** June 29, 2014

| Frequency (MHz) | Reading (dBuV) | Correction Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Pole (V/H) | Remark |
|-----------------|----------------|--------------------------|-----------------|----------------|-------------|--------------------|--------|
| 3552.4000       | 43.60          | -2.70                    | 40.90           | 74.00          | -33.10      | V                  | Peak   |
| 4297.6000       | 42.69          | -0.17                    | 42.52           | 74.00          | -31.48      | V                  | Peak   |
| 4905.1000       | 41.72          | 2.12                     | 43.84           | 74.00          | -30.16      | V                  | Peak   |
| 5676.4000       | 41.23          | 2.85                     | 44.08           | 74.00          | -29.92      | V                  | Peak   |
| 6614.2000       | 40.13          | 6.04                     | 46.17           | 74.00          | -27.83      | V                  | Peak   |
| 7369.3000       | 40.05          | 8.42                     | 48.47           | 74.00          | -25.53      | V                  | Peak   |
|                 |                |                          |                 |                |             |                    |        |
| 3763.9000       | 43.70          | -1.91                    | 41.79           | 74.00          | -32.21      | H                  | Peak   |
| 5175.1000       | 41.32          | 2.52                     | 43.84           | 74.00          | -30.16      | H                  | Peak   |
| 6254.2000       | 40.86          | 4.49                     | 45.35           | 74.00          | -28.65      | H                  | Peak   |
| 7184.8000       | 40.85          | 8.06                     | 48.91           | 74.00          | -25.09      | H                  | Peak   |
| 7989.4000       | 39.78          | 9.63                     | 49.41           | 74.00          | -24.59      | H                  | Peak   |
| 8611.3000       | 40.15          | 9.31                     | 49.46           | 74.00          | -24.54      | H                  | Peak   |

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



### 7.3. 6dB BANDWIDTH MEASUREMENT

#### 7.3.1. LIMITS

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

#### 7.3.2. TEST INSTRUMENTS


| Name of Equipment | Manufacturer | Model  | Serial Number | Last Calibration | Calibration Due |
|-------------------|--------------|--------|---------------|------------------|-----------------|
| Spectrum Analyzer | Agilent      | N9010A | MY52221469    | 10/25/2013       | 10/24/2014      |

#### 7.3.3. TEST PROCEDURES (please refer to measurement standard)

##### 8.1 Option 1:

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### 7.3.4. TEST SETUP



**7.3.5. TEST RESULTS***No non-compliance noted***Test Data****Test Mode: IEEE 802.11b Mode**

| Channel | Frequency (MHz) | Bandwidth (kHz)<br>Antenna 0 | Bandwidth (kHz)<br>Antenna 1 | Limit (kHz) | Test Result |
|---------|-----------------|------------------------------|------------------------------|-------------|-------------|
| Low     | 2412            | 10120                        | 10120                        | >500        | PASS        |
| Mid     | 2437            | 10110                        | 10110                        |             | PASS        |
| High    | 2462            | 10120                        | 10120                        |             | PASS        |

**Test Mode: IEEE 802.11g Mode**

| Channel | Frequency (MHz) | Bandwidth (kHz)<br>Antenna 0 | Bandwidth (kHz)<br>Antenna 1 | Limit (kHz) | Test Result |
|---------|-----------------|------------------------------|------------------------------|-------------|-------------|
| Low     | 2412            | 16590                        | 16550                        | >500        | PASS        |
| Mid     | 2437            | 16580                        | 16580                        |             | PASS        |
| High    | 2462            | 16590                        | 16580                        |             | PASS        |

**Test Mode: IEEE 802.11n HT20 MHz Mode**

| Channel | Frequency (MHz) | Bandwidth (kHz)<br>Antenna 0 | Bandwidth (kHz)<br>Antenna 1 | Limit (kHz) | Test Result |
|---------|-----------------|------------------------------|------------------------------|-------------|-------------|
| Low     | 2412            | 17810                        | 17820                        | >500        | PASS        |
| Mid     | 2437            | 17790                        | 17800                        |             | PASS        |
| High    | 2462            | 17780                        | 17800                        |             | PASS        |

**Test Mode: IEEE 802.11n HT40 MHz Mode**


| Channel | Frequency (MHz) | Bandwidth (kHz)<br>Antenna 0 | Bandwidth (kHz)<br>Antenna 1 | Limit (kHz) | Test Result |
|---------|-----------------|------------------------------|------------------------------|-------------|-------------|
| Low     | 2422            | 36540                        | 36580                        | >500        | PASS        |
| Mid     | 2437            | 36590                        | 36590                        |             | PASS        |
| High    | 2452            | 36540                        | 36590                        |             | PASS        |




### Test Plot

#### IEEE 802.11b mode (Antenna 0)

#### 6dB Bandwidth (CH Low)




#### 6dB Bandwidth (CH Mid)






### 6dB Bandwidth (CH High)




### IEEE 802.11b mode (Antenna 1)

### 6dB Bandwidth (CH Low)






### 6dB Bandwidth (CH Low)




### 6dB Bandwidth (CH Mid)






## IEEE 802.11g mode (Antenna 0)

### 6dB Bandwidth (CH Low)




### 6dB Bandwidth (CH Mid)






### 6dB Bandwidth (CH High)




### IEEE 802.11g mode (Antenna 1)

### 6dB Bandwidth (CH Low)






### 6dB Bandwidth (CH Low)




### 6dB Bandwidth (CH Mid)






## IEEE 802.11n HT20 MHz mode (Antenna 0)

### 6dB Bandwidth (CH Low)




### 6dB Bandwidth (CH Mid)






### 6dB Bandwidth (CH High)




### IEEE 802.11n HT20 MHz mode (Antenna 1)

#### 6dB Bandwidth (CH Low)






### 6dB Bandwidth (CH Mid)




### 6dB Bandwidth (CH High)






IEEE 802.11n HT40 MHz mode (Antenna 0)

6dB Bandwidth (CH Low)




6dB Bandwidth (CH Mid)






### 6dB Bandwidth (CH High)




### IEEE 802.11n HT40 MHz mode (Antenna 1)

### 6dB Bandwidth (CH Low)






### 6dB Bandwidth (CH Mid)



### 6dB Bandwidth (CH High)





## **7.4. PEAK OUTPUT POWER**

### **7.4.1. LIMITS**

The maximum peak output power of the intentional radiator shall not exceed the following:

1. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 Watt.
2. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **7.4.2. TEST INSTRUMENTS**

| <b>Name of Equipment</b> | <b>Manufacturer</b> | <b>Model</b> | <b>Serial Number</b> | <b>Last Calibration</b> | <b>Calibration Due</b> |
|--------------------------|---------------------|--------------|----------------------|-------------------------|------------------------|
| Spectrum Analyzer        | Agilent             | E4446A       | US44300399           | 03/01/2014              | 03/01/2015             |
| Power Meter              | Anritsu             | ML2495A      | 1204003              | 03/01/2014              | 03/01/2015             |
| Power Sensor             | Anritsu             | MA2411B      | 1126150              | 03/01/2014              | 03/01/2015             |

### **7.4.3. TEST PROCEDURES** (please refer to measurement standard)

#### **9.1.1 RBW $\geq$ DTS bandwidth**

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the *DTS bandwidth*.

- a) Set the RBW  $\geq$  *DTS bandwidth*.
- b) Set VBW  $\geq$  3 RBW.
- c) Set span  $\geq$  3 x RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.



### 9.1.2 Integrated band power method

This procedure may be used when the maximum available RBW of the measurement instrument is less than the *DTS bandwidth*.

- a) Set the RBW = 1 MHz.
- b) Set the VBW  $\geq 3$  RBW
- c) Set the span  $\geq 1.5 \times$  DTS bandwidth.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select peak detector). If the instrument does not have a band power function, sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS bandwidth.

### 9.1.3 PKPM1 Peak power meter method

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

### 7.4.4. TEST SETUP

