

FCC RF Test Report


APPLICANT : AMobile Intelligent Corp
EQUIPMENT : AMobile 5" RISC-based Panel PC
BRAND NAME : AMobile
MODEL NAME : IOT-500
FCC ID : 2ACC5-HM500
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter (PCB)

The product was received on Jan. 11, 2016 and testing was completed on Mar. 04, 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	6
1.5 Modification of EUT	6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	7
1.7 Testing Location	8
1.8 Applicable Standards	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System	10
2.3 Support Unit used in test configuration	10
2.4 Measurement Results Explanation Example	10
3 CONDUCTED TEST RESULT	11
3.1 Measuring Instruments.....	11
3.2 Test Setup	11
3.3 Test Result of Conducted Test.....	11
3.4 Conducted Output Power and ERP/EIRP	12
3.5 Peak-to-Average Ratio	13
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	14
3.7 Conducted Band Edge	15
3.8 Conducted Spurious Emission	16
3.9 Frequency Stability	17
4 RADIATED TEST ITEMS	18
4.1 Measuring Instruments.....	18
4.2 Test Setup	18
4.3 Test Result of Radiated Test.....	18
4.4 Field Strength of Spurious Radiation Measurement	19
5 LIST OF MEASURING EQUIPMENT	20
6 UNCERTAINTY OF EVALUATION	21
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG611103	Rev. 01	Initial issue of report	Mar. 08, 2016

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049 §22.917(b) §24.238(b)	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235		Within Authorized Band		
4.4	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 19.63 dB at 3756.000 MHz

1 General Description

1.1 Applicant

AMobile Intelligent Corp

18F. -1, No.150, Jian 1st Rd., Zhong He Dist., New Taipei City 235, Taiwan

1.2 Manufacturer

AMobile Intelligent Corp

18F. -1, No.150, Jian 1st Rd., Zhong He Dist., New Taipei City 235, Taiwan

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	AMobile 5" RISC-based Panel PC
Brand Name	AMobile
Model Name	IOT-500
FCC ID	2ACC5-HM500
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth v4.1 EDR/LE
HW Version	1.0
SW Version	V01.01.00.R277
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM/GPRS/EDGE: 850: 824.2 MHz ~ 848.8 MHz 1900: 1850.2 MHz ~ 1909.8MHz WCDMA: Band V: 826.4 MHz ~ 846.6 MHz Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM/GPRS/EDGE: 850: 869.2 MHz ~ 893.8 MHz 1900: 1930.2 MHz ~ 1989.8 MHz WCDMA: Band V: 871.4 MHz ~ 891.6 MHz Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM/GPRS/EDGE: 850: 31.54 dBm 1900: 28.37 dBm WCDMA: Band V: 23.80 dBm Band II: 22.25 dBm
Antenna Type	Dipole Antenna
Antenna Gain	Cellular Band: 2.43 dBi PCS Band: 1.61 dBi
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GPRS class 8	GMSK	1.5205	0.0072 ppm	248KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.3350	0.0120 ppm	249KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.2559	0.0060 ppm	4M16F9W
Part 24	GSM1900 GPRS class 8	GMSK	0.9954	0.0074 ppm	247KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.3606	0.0069 ppm	248KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.2432	0.0059 ppm	4M16F9W

1.7 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No.
	TH03-HY

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No.
	03CH11-HY

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-D-2010
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GPRS class 8 Link + DC 12V ■ EDGE class 8 Link + DC 12V ■ GPRS class 8 Link + DC 24V	■ GPRS class 8 Link ■ EDGE class 8 Link
GSM 1900	■ GPRS class 8 Link + DC 12V ■ EDGE class 8 Link + DC 12V	■ GPRS class 8 Link ■ EDGE class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link + DC 12V	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link + DC 12V ■ RMC 12.2Kbps Link + DC 24V	■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	Topward	3303D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.2 dB and a 10dB attenuator.

Example :

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$


3 Conducted Test Result

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. Set EUT to transmit at maximum output power.
4. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.
Record the maximum PAPR level associated with a probability of 0.1%.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13dBm.

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13dBm.

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Jun. 24, 2015	Mar. 02, 2016 ~ Mar. 03, 2016	Jun. 23, 2016	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SU-641	92013721	-30℃ ~70℃	Nov. 20, 2015	Mar. 02, 2016 ~ Mar. 03, 2016	Nov. 19, 2016	Conducted (TH03-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL883644	Voltage:0~20V;Current:0~5A	Nov. 26, 2015	Mar. 02, 2016 ~ Mar. 03, 2016	Nov. 25, 2016	Conducted (TH03-HY)
System Simulator	Agilent	E5515C	MY50266977	N/A	May 14, 2015	Mar. 02, 2016 ~ Mar. 03, 2016	May 13, 2016	Conducted (TH03-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Nov. 20, 2015	Mar. 03, 2016 ~ Mar. 04, 2016	Nov. 19, 2016	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D	35414	30MHz~1GHz	Nov. 17, 2015	Mar. 03, 2016 ~ Mar. 04, 2016	Nov. 16, 2016	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1326	1GHz ~ 18GHz	Oct. 08, 2015	Mar. 03, 2016 ~ Mar. 04, 2016	Oct. 07, 2016	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Nov. 19, 2015	Mar. 03, 2016 ~ Mar. 04, 2016	Nov. 18, 2016	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz ~ 44GHZ	Sep. 24, 2015	Mar. 03, 2016 ~ Mar. 04, 2016	Sep. 23, 2016	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-450 0-B	N/A	1~4m	N/A	Mar. 03, 2016 ~ Mar. 04, 2016	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0-360 degree	N/A	Mar. 03, 2016 ~ Mar. 04, 2016	N/A	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA917025 1	18GHz- 40GHz	Oct. 12, 2015	Mar. 03, 2016 ~ Mar. 04, 2016	Oct. 11, 2016	Radiation (03CH11-HY)



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.90
---	------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GPRS class 8	31.46	31.54	31.47	28.22	28.06	28.37
GPRS class 10	30.79	30.78	30.84	27.48	27.33	27.68
GPRS class 11	29.06	29.09	29.06	25.76	25.55	25.95
GPRS class 12	28.03	28.06	27.99	24.72	24.52	24.93
EGPRS class 8	24.97	24.90	24.78	23.83	23.87	23.96
EGPRS class 10	23.96	23.77	23.67	22.68	22.71	22.64
EGPRS class 11	21.88	21.64	21.52	20.35	20.23	20.27
EGPRS class 12	20.78	20.59	20.50	19.12	19.08	19.14

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6
RMC 12.2K	23.80	22.49	22.78	21.75	21.23	22.25
HSDPA Subtest-1	22.79	21.52	21.79	19.71	19.24	20.38
HSDPA Subtest-2	22.78	21.49	21.77	19.70	19.25	20.38
HSDPA Subtest-3	22.32	21.01	21.33	19.71	19.24	20.39
HSDPA Subtest-4	22.30	20.99	21.31	19.70	19.28	20.40
HSUPA Subtest-1	20.86	19.46	19.81	18.68	18.30	19.43
HSUPA Subtest-2	20.86	19.50	19.80	18.68	18.33	19.48
HSUPA Subtest-3	21.81	20.45	20.78	19.65	19.30	20.40
HSUPA Subtest-4	20.40	19.04	19.31	17.82	17.81	18.90
HSUPA Subtest-5	22.74	21.37	21.70	20.10	19.75	20.85



A1. GSM

Peak-to-Average Ratio

Mode	GSM850		Limit: 13dB
Mod.	GPRS class 8	EDGE class 8	Result
Lowest CH	0.20	3.28	PASS
Middle CH	0.24	3.36	
Highest CH	0.24	3.24	

Mode	GSM1900		Limit: 13dB
Mod.	GPRS class 8	EDGE class 8	Result
Lowest CH	0.20	3.52	PASS
Middle CH	0.20	3.64	
Highest CH	0.24	3.64	



GSM850 (GPRS class 8)		GSM850 (EDGE class 8)	
Lowest Channel		Lowest Channel	
Ref: 35 dBm Att: 30 dB AGT: 3.125 ms RSW: 10 MHz Offset: 16.3 dB 100% 10% 1% .1% .01% Center: 824.2 MHz 2 dB/ Mean Pwr: + 20 dB Trace 1 Mean 30.82 dBm Peak 31.09 dBm Crest 0.27 dB 10 % 0.16 dB 1 % 0.20 dB .1 % 0.20 dB .01 % 0.20 dB		Ref: 35 dBm Att: 30 dB AGT: 3.125 ms RSW: 10 MHz Offset: 16.3 dB 100% 10% 1% .1% .01% Center: 824.2 MHz 2 dB/ Mean Pwr: + 20 dB Trace 1 Mean 24.54 dBm Peak 27.91 dBm Crest 3.38 dB 10 % 2.56 dB 1 % 3.16 dB .1 % 3.28 dB .01 % 3.32 dB	
Date: 3.MAR.2016 09:55:36		Date: 3.MAR.2016 10:19:28	
Middle Channel		Middle Channel	
Ref: 35 dBm Att: 30 dB AGT: 3.125 ms RSW: 10 MHz Offset: 16.3 dB 100% 10% 1% .1% .01% Center: 835.4 MHz 2 dB/ Mean Pwr: + 20 dB Trace 1 Mean 30.93 dBm Peak 31.16 dBm Crest 0.23 dB 10 % 0.16 dB 1 % 0.20 dB .1 % 0.24 dB .01 % 0.24 dB		Ref: 35 dBm Att: 30 dB AGT: 3.125 ms RSW: 10 MHz Offset: 16.3 dB 100% 10% 1% .1% .01% Center: 835.4 MHz 2 dB/ Mean Pwr: + 20 dB Trace 1 Mean 24.06 dBm Peak 27.49 dBm Crest 3.43 dB 10 % 2.64 dB 1 % 3.20 dB .1 % 3.36 dB .01 % 3.44 dB	
Date: 3.MAR.2016 09:56:25		Date: 3.MAR.2016 10:19:53	
Highest Channel		Highest Channel	
Ref: 35 dBm Att: 30 dB AGT: 3.125 ms RSW: 10 MHz Offset: 16.3 dB 100% 10% 1% .1% .01% Center: 848.8 MHz 2 dB/ Mean Pwr: + 20 dB Trace 1 Mean 31.42 dBm Peak 31.65 dBm Crest 0.23 dB 10 % 0.16 dB 1 % 0.20 dB .1 % 0.24 dB .01 % 0.24 dB		Ref: 35 dBm Att: 30 dB AGT: 3.125 ms RSW: 10 MHz Offset: 16.3 dB 100% 10% 1% .1% .01% Center: 848.8 MHz 2 dB/ Mean Pwr: + 20 dB Trace 1 Mean 24.30 dBm Peak 27.63 dBm Crest 3.33 dB 10 % 2.52 dB 1 % 3.12 dB .1 % 3.24 dB .01 % 3.32 dB	
Date: 3.MAR.2016 09:56:45		Date: 3.MAR.2016 10:20:17	




GSM1900 (GPRS class 8)		GSM1900 (EDGE class 8)	
Lowest Channel		Lowest Channel	

**26dB Bandwidth**


Mode	GSM850	
Mod.	GPRS class 8	EDGE class 8
Lowest CH	0.298	0.307
Middle CH	0.314	0.309
Highest CH	0.307	0.298

Mode	GSM1900	
Mod.	GPRS class 8	EDGE class 8
Lowest CH	0.315	0.298
Middle CH	0.307	0.303
Highest CH	0.302	0.304



GSM1900 (GPRS class 8)


Lowest Channel



Date: 3.MAR.2016 10:35:50


GSM1900 (EDGE class 8)

Lowest Channel




Date: 3.MAR.2016 11:12:32

Middle Channel




Date: 3.MAR.2016 10:36:23

Middle Channel




Date: 3.MAR.2016 11:13:10

Highest Channel



Date: 3.MAR.2016 10:36:56

Highest Channel



Date: 3.MAR.2016 11:13:55


**Occupied Bandwidth**

Mode	GSM850	
Mod.	GPRS class 8	EDGE class 8
Lowest CH	0.248	0.248
Middle CH	0.247	0.249
Highest CH	0.246	0.249

Mode	GSM1900	
Mod.	GPRS class 8	EDGE class 8
Lowest CH	0.245	0.248
Middle CH	0.247	0.241
Highest CH	0.246	0.245

GSM850 (GPRS class 8)


Lowest Channel



Date: 3.MAR.2016 09:41:02


GSM850 (EDGE class 8)

Lowest Channel




Date: 3.MAR.2016 10:10:20

Middle Channel




Date: 3.MAR.2016 09:41:41

Middle Channel




Date: 3.MAR.2016 10:10:55

Highest Channel




Date: 3.MAR.2016 09:42:57

Highest Channel



Date: 3-MAR-2016 10:11:44






Conducted Band Edge


GSM850 (GPRS class 8)

Lowest Band Edge



Date: 3.MAR.2016 09:45:26


Highest Band Edge



Date: 3.MAR.2016 09:47:54


GSM850 (EDGE class 8)

Lowest Band Edge



Date: 3.MAR.2016 10:13:37

Highest Band Edge




Date: 3.MAR.2016 10:15:28




GSM1900 (GPRS class 8)

Lowest Band Edge



Date: 3.MAR.2016 10:43:25


Highest Band Edge



Date: 3.MAR.2016 10:45:03


GSM1900 (EDGE class 8)

Lowest Band Edge



Date: 3.MAR.2016 11:24:16

Highest Band Edge




Date: 3.MAR.2016 11:25:54

Conducted Spurious Emission

GSM850 (GPRS class 8)	GSM850 (EDGE class 8)
Lowest Channel	Lowest Channel
<	

GSM1900 (GPRS class 8)


Lowest Channel



Date: 3.MAR.2016 10:46:11


GSM1900 (EDGE class 8)

Lowest Channel




Date: 3.MAR.2016 11:17:49

Middle Channel




Date: 3.MAR.2016 10:47:04

Middle Channel




Date: 3.MAR.2016 11:18:42

Highest Channel



Date: 3.MAR.2016 10:47:56

Highest Channel



Date: 3.MAR.2016 11:19:34

Frequency Stability

Test Conditions	Middle Channel	GSM850 (GPRS class 8)	GSM850 (EDGE class 8)	Limit
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		2.5ppm
50	Normal Voltage	0.0024	0.0120	PASS
40	Normal Voltage	0.0036	0.0036	
30	Normal Voltage	0.0036	0.0012	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0012	0.0012	
0	Normal Voltage	0.0024	0.0036	
-10	Normal Voltage	0.0012	0.0060	
-20	Normal Voltage	0.0000	0.0108	
-30	Normal Voltage	0.0048	0.0084	
20	Maximum Voltage	0.0024	0.0024	
20	Normal Voltage	0.0012	0.0108	
20	Battery End Point	0.0072	0.0072	

Note:

1. Normal Voltage = 12.0V. ; Battery End Point (BEP) = 12.0 V. ; Maximum Voltage =24.0 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Test Conditions	Middle Channel	GSM1900 (GPRS class 8)	GSM1900 (EDGE class 8)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0011	0.0011	PASS
40	Normal Voltage	0.0021	0.0053	
30	Normal Voltage	0.0005	0.0016	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0005	0.0027	
0	Normal Voltage	0.0032	0.0048	
-10	Normal Voltage	0.0016	0.0032	
-20	Normal Voltage	0.0027	0.0011	
-30	Normal Voltage	0.0048	0.0027	
20	Maximum Voltage	0.0074	0.0069	
20	Normal Voltage	0.0043	0.0021	
20	Battery End Point	0.0069	0.0037	

Note:







1. Normal Voltage = 12.0V. ; Battery End Point (BEP) = 12.0 V. ; Maximum Voltage =24.0 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



A2. WCDMA

Peak-to-Average Ratio

Mode	WCDMA Band V	WCDMA Band II	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	3.08	3.16	PASS
Middle CH	3.00	2.84	
Highest CH	3.00	2.72	

WCDMA Band V (RMC 12.2Kbps)	WCDMA Band II (RMC 12.2Kbps)
Lowest Channel	Lowest Channel
 Ref: 30 dBm, Att: 30 dB, AGT: 3.125 ms, RBW: 10 MHz Center: 826.4 MHz, 2 dB/ Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean: 20.35 dBm Peak: 23.83 dBm Crest: 3.48 dB 10 %: 1.80 dB 1 %: 2.64 dB .1 %: 3.08 dB .01 %: 3.28 dB Date: 3.MAR.2016 13:38:17	 Ref: 30 dBm, Att: 30 dB, AGT: 3.125 ms, RBW: 10 MHz Center: 1.8524 GHz, 2 dB/ Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean: 19.62 dBm Peak: 23.06 dBm Crest: 3.44 dB 10 %: 1.84 dB 1 %: 2.72 dB .1 %: 3.16 dB .01 %: 3.36 dB Date: 3.MAR.2016 11:53:18
Middle Channel	Middle Channel
 Ref: 30 dBm, Att: 30 dB, AGT: 3.125 ms, RBW: 10 MHz Center: 836.4 MHz, 2 dB/ Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean: 20.83 dBm Peak: 24.11 dBm Crest: 3.28 dB 10 %: 1.76 dB 1 %: 2.60 dB .1 %: 3.00 dB .01 %: 3.20 dB Date: 3.MAR.2016 13:38:30	 Ref: 30 dBm, Att: 30 dB, AGT: 3.125 ms, RBW: 10 MHz Center: 1.88 GHz, 2 dB/ Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean: 20.09 dBm Peak: 23.20 dBm Crest: 3.11 dB 10 %: 1.72 dB 1 %: 2.44 dB .1 %: 2.84 dB .01 %: 3.00 dB Date: 3.MAR.2016 11:53:28
Highest Channel	Highest Channel
 Ref: 30 dBm, Att: 30 dB, AGT: 3.125 ms, RBW: 10 MHz Center: 846.6 MHz, 2 dB/ Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean: 20.67 dBm Peak: 24.04 dBm Crest: 3.37 dB 10 %: 1.72 dB 1 %: 2.56 dB .1 %: 3.00 dB .01 %: 3.20 dB Date: 3.MAR.2016 13:38:48	 Ref: 30 dBm, Att: 30 dB, AGT: 3.125 ms, RBW: 10 MHz Center: 1.9076 GHz, 2 dB/ Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean: 19.82 dBm Peak: 22.77 dBm Crest: 2.96 dB 10 %: 1.68 dB 1 %: 2.36 dB .1 %: 2.72 dB .01 %: 2.88 dB Date: 3.MAR.2016 11:53:38

**26dB Bandwidth**


Mode	WCDMA Band V	WCDMA Band II
Mod.	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.67	4.67
Middle CH	4.70	4.68
Highest CH	4.69	4.71



WCDMA Band V (RMC 12.2Kbps)	WCDMA Band II (RMC 12.2Kbps)
Lowest Channel	Lowest Channel
Date: 3.MAR.2016 13:29:26	Date: 3.MAR.2016 11:41:29
Middle Channel	Middle Channel
Date: 3.MAR.2016 13:29:55	Date: 3.MAR.2016 11:41:57
Highest Channel	Highest Channel
Date: 3.MAR.2016 13:30:23	Date: 3.MAR.2016 11:42:25

**Occupied Bandwidth**

Mode	WCDMA Band V	WCDMA Band II
Mod.	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.16	4.15
Middle CH	4.16	4.16
Highest CH	4.14	4.15






Conducted Band Edge


WCDMA Band V (RMC 12.2Kbps)

Lowest Band Edge



Date: 3.MAR.2016 13:44:40

Highest Band Edge




Date: 3.MAR.2016 13:47:22




WCDMA Band II (RMC 12.2Kbps)

Lowest Band Edge



Date: 3.MAR.2016 11:46:45

Highest Band Edge




Date: 3.MAR.2016 11:49:27

Conducted Spurious Emission

WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 3.MAR.2016 13:36:09


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 3.MAR.2016 11:51:15

Middle Channel




Date: 3.MAR.2016 13:36:54

Middle Channel




Date: 3.MAR.2016 11:52:00

Highest Channel



Date: 3.MAR.2016 13:37:39

Highest Channel



Date: 3.MAR.2016 11:52:45

Frequency Stability

Test Conditions	Middle Channel	WCDMA Band V (RMC 12.2Kbps)	Limit
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	2.5ppm
50	Normal Voltage	0.0036	PASS
40	Normal Voltage	0.0060	
30	Normal Voltage	0.0024	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0012	
0	Normal Voltage	0.0024	
-10	Normal Voltage	0.0048	
-20	Normal Voltage	0.0000	
-30	Normal Voltage	0.0012	
20	Maximum Voltage	0.0024	
20	Normal Voltage	0.0012	
20	Battery End Point	0.0060	

Note:

1. Normal Voltage = 12.0V. ; Battery End Point (BEP) = 12.0 V. ; Maximum Voltage =24.0 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



Test Conditions	Middle Channel	WCDMA Band II (RMC 12.2Kbps)	Limit
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Note 2.
			Result
50	Normal Voltage	0.0043	PASS
40	Normal Voltage	0.0021	
30	Normal Voltage	0.0027	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0005	
0	Normal Voltage	0.0021	
-10	Normal Voltage	0.0037	
-20	Normal Voltage	0.0021	
-30	Normal Voltage	0.0059	
20	Maximum Voltage	0.0016	
20	Normal Voltage	0.0037	
20	Battery End Point	0.0021	

Note:

1. Normal Voltage = 12.0V. ; Battery End Point (BEP) = 12.0 V. ; Maximum Voltage =24.0 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Appendix B. Test Results of Radiated Test

ERP/EIRP

Cellular Band ($G_T - L_C = 2.43\text{dB}$)									
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	31.46	31.54	31.47	24.97	24.9	24.78	23.8	22.49	22.78
Conducted Power (Watts)	1.40	1.43	1.42	0.31	0.31	0.30	0.24	0.18	0.19
ERP(dBm)	31.74	31.82	31.75	25.25	25.18	25.06	24.08	22.77	23.06
ERP(Watts)	1.4928	1.5205	1.4962	0.3350	0.3296	0.3206	0.2559	0.1892	0.2023

PCS Band ($G_T - L_C = 1.61\text{dB}$)									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	28.22	28.06	28.37	23.83	23.87	23.96	21.75	21.23	22.25
Conducted Power (Watts)	0.66	0.64	0.69	0.24	0.24	0.25	0.15	0.13	0.17
EIRP(dBm)	29.83	29.67	29.98	25.44	25.48	25.57	23.36	22.84	23.86
EIRP(Watts)	0.9616	0.9268	0.9954	0.3499	0.3532	0.3606	0.2168	0.1923	0.2432

Note: maximum burst average power for GSM, and maximum average power for WCDMA.

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB



Radiated Spurious Emission

<DC 12V>

GSM850 (GPRS class 8)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-51.96	-13	-38.96	-56.71	-53.72	0.98	4.89	H
	2472	-52.45	-13	-39.45	-61.85	-54.33	1.28	5.32	H
	3296	-59.17	-13	-46.17	-71.78	-62.58	1.54	7.10	H
	4120	-59.47	-13	-46.47	-75.14	-64.11	1.83	8.62	H
	5768	-56.72	-13	-43.72	-77.07	-61.6	2.78	9.81	H
	1648	-53.82	-13	-40.82	-57.09	-55.58	0.98	4.89	V
	2472	-43.94	-13	-30.94	-54.34	-45.82	1.28	5.32	V
	3296	-56.37	-13	-43.37	-67.87	-59.78	1.54	7.10	V
	4120	-59.48	-13	-46.48	-75.08	-64.12	1.83	8.62	V
	5768	-55.47	-13	-42.47	-74.73	-60.35	2.78	9.81	V
Middle	1672	-53.63	-13	-40.63	-58.2	-55.31	0.99	4.82	H
	2512	-52.80	-13	-39.80	-62.36	-54.77	1.29	5.41	H
	3344	-58.12	-13	-45.12	-70.29	-61.73	1.56	7.31	H
	4184	-59.68	-13	-46.68	-75.43	-64.3	1.87	8.64	H
	5856	-58.02	-13	-45.02	-78.76	-62.88	2.83	9.84	H
	1672	-53.44	-13	-40.44	-56.46	-55.12	0.99	4.82	V
	2512	-43.40	-13	-30.40	-53.63	-45.37	1.29	5.41	V
	3344	-57.42	-13	-44.42	-68.77	-61.03	1.56	7.31	V
	4184	-58.36	-13	-45.36	-74.15	-62.98	1.87	8.64	V
	5856	-55.52	-13	-42.52	-75.63	-60.38	2.83	9.84	V
Highest	1696	-56.21	-13	-43.21	-60.92	-57.81	1.00	4.75	H
	2544	-53.53	-13	-40.53	-63.13	-55.51	1.30	5.44	H
	3392	-59.22	-13	-46.22	-71.5	-63.02	1.57	7.52	H
	4248	-59.32	-13	-46.32	-75.28	-63.92	1.90	8.65	H
	5944	-56.84	-13	-43.84	-77.99	-61.69	2.88	9.88	H
	1696	-57.30	-13	-44.30	-61.08	-58.9	1.00	4.75	V
	2544	-51.18	-13	-38.18	-61.41	-53.16	1.30	5.44	V
	3392	-57.36	-13	-44.36	-69.16	-61.16	1.57	7.52	V
	4248	-59.45	-13	-46.45	-75.19	-64.05	1.90	8.65	V
	5944	-55.84	-13	-42.84	-76.66	-60.69	2.88	9.88	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM850 (EDGE class 8)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-53.52	-13	-40.52	-58.21	-55.28	0.98	4.89	H
	2472	-48.18	-13	-35.18	-58.32	-50.06	1.28	5.32	H
	3296	-56.70	-13	-43.70	-69.27	-60.11	1.54	7.10	H
	4120	-60.79	-13	-47.79	-75.68	-65.43	1.83	8.62	H
	1648	-53.53	-13	-40.53	-57.2	-55.29	0.98	4.89	V
	2472	-44.25	-13	-31.25	-54.61	-46.13	1.28	5.32	V
	3296	-55.03	-13	-42.03	-67.32	-58.44	1.54	7.10	V
	4120	-59.27	-13	-46.27	-74.72	-63.91	1.83	8.62	V
Middle	1672	-53.60	-13	-40.60	-58.42	-55.28	0.99	4.82	H
	2512	-49.07	-13	-36.07	-59.26	-51.04	1.29	5.41	H
	3344	-59.76	-13	-46.76	-71.95	-63.37	1.56	7.31	H
	4184	-60.49	-13	-47.49	-75.92	-65.11	1.87	8.64	H
	1672	-53.61	-13	-40.61	-56.09	-55.29	0.99	4.82	V
	2512	-47.09	-13	-34.09	-57.27	-49.06	1.29	5.41	V
	3344	-57.23	-13	-44.23	-68.65	-60.84	1.56	7.31	V
	4184	-59.71	-13	-46.71	-75	-64.33	1.87	8.64	V
Highest	1696	-53.68	-13	-40.68	-58.6	-55.28	1.00	4.75	H
	2544	-52.73	-13	-39.73	-62.3	-54.71	1.30	5.44	H
	3392	-58.39	-13	-45.39	-71.19	-62.19	1.57	7.52	H
	4248	-58.88	-13	-45.88	-74.94	-63.48	1.90	8.65	H
	1696	-55.51	-13	-42.51	-59.02	-57.11	1.00	4.75	V
	2544	-50.24	-13	-37.24	-60.58	-54.37	1.30	5.44	V
	3392	-57.07	-13	-44.07	-69.15	-63.02	1.57	7.52	V
	4248	-57.17	-13	-44.17	-72.94	-63.92	1.90	8.65	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM1900 (GPRS class 8)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700	-53.62	-13	-40.62	-68.05	-60.19	1.67	8.24	H
	5548	-43.15	-13	-30.15	-63.78	-50.22	2.65	9.72	H
	7403	-52.04	-13	-39.04	-78.35	-61.19	2.46	11.61	H
	3700	-55.84	-13	-42.84	-70.29	-62.41	1.67	8.24	V
	5548	-49.02	-13	-36.02	-68.02	-56.09	2.65	9.72	V
	7403	-53.51	-13	-40.51	-77.37	-62.66	2.46	11.61	V
Middle	3763	-52.18	-13	-39.18	-67.02	-58.81	1.69	8.32	H
	5639	-42.11	-13	-29.11	-62.31	-49.16	2.71	9.76	H
	7522	-51.18	-13	-38.18	-76.8	-60.57	2.42	11.81	H
	3763	-54.39	-13	-41.39	-68.55	-61.02	1.69	8.32	V
	5639	-46.21	-13	-33.21	-64.94	-53.26	2.71	9.76	V
	7522	-53.32	-13	-40.32	-77.22	-62.71	2.42	11.81	V
Highest	3819	-52.56	-13	-39.56	-67.44	-59.24	1.70	8.38	H
	5730	-42.08	-13	-29.08	-62.15	-49.11	2.76	9.79	H
	7641	-50.58	-13	-37.58	-75.63	-60.08	2.38	11.88	H
	3819	-59.47	-13	-46.47	-73.97	-66.15	1.70	8.38	V
	5730	-50.41	-13	-37.41	-69.56	-57.44	2.76	9.79	V
	7641	-54.31	-13	-41.31	-78.42	-63.81	2.38	11.88	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM1900 (EDGE class 8)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700	-52.77	-13	-39.77	-67.48	-59.34	1.67	8.24	H
	5548	-42.04	-13	-29.04	-62.53	-49.11	2.65	9.72	H
	7403	-52.66	-13	-39.66	-77.82	-61.81	2.46	11.61	H
	3700	-56.68	-13	-43.68	-70.55	-63.25	1.67	8.24	V
	5548	-48.04	-13	-35.04	-67.19	-55.11	2.65	9.72	V
	7403	-52.28	-13	-39.28	-76.38	-61.43	2.46	11.61	V
Middle	3763	-50.71	-13	-37.71	-65.66	-57.34	1.69	8.32	H
	5639	-41.10	-13	-28.10	-61.88	-48.15	2.71	9.76	H
	7522	-51.94	-13	-38.94	-76.95	-61.33	2.42	11.81	H
	3763	-54.61	-13	-41.61	-68.92	-61.24	1.69	8.32	V
	5639	-47.14	-13	-34.14	-66.12	-54.19	2.71	9.76	V
	7522	-53.65	-13	-40.65	-77.18	-63.04	2.42	11.81	V
Highest	3819	-54.75	-13	-41.75	-69.27	-61.43	1.70	8.38	H
	5730	-41.08	-13	-28.08	-61.99	-48.11	2.76	9.79	H
	7641	-48.56	-13	-35.56	-73.34	-58.06	2.38	11.88	H
	3819	-56.03	-13	-43.03	-70.66	-62.71	1.70	8.38	V
	5730	-46.82	-13	-33.82	-65.89	-53.85	2.76	9.79	V
	7641	-53.46	-13	-40.46	-77.22	-62.96	2.38	11.88	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band V (RMC 12.2Kbps)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-58.68	-13	-45.68	-62.91	-60.44	0.98	4.89	H
	2480	-63.31	-13	-50.31	-73.37	-65.22	1.28	5.34	H
	3296	-63.67	-13	-50.67	-76.5	-67.08	1.54	7.10	H
	1648	-62.19	-13	-49.19	-66.12	-63.95	0.98	4.89	V
	2480	-63.81	-13	-50.81	-73.94	-65.72	1.28	5.34	V
	3296	-65.40	-13	-52.40	-76.6	-68.81	1.54	7.10	V
Middle	1672	-58.51	-13	-45.51	-63.37	-60.19	0.99	4.82	H
	2504	-65.32	-13	-52.32	-74.61	-67.28	1.29	5.40	H
	3344	-63.40	-13	-50.40	-75.62	-67.01	1.56	7.31	H
	1672	-62.31	-13	-49.31	-65.46	-63.99	0.99	4.82	V
	2504	-64.58	-13	-51.58	-74.44	-66.54	1.29	5.40	V
	3344	-64.44	-13	-51.44	-75.5	-68.05	1.56	7.31	V
Highest	1696	-58.52	-13	-45.52	-63.44	-60.12	1.00	4.75	H
	2544	-65.55	-13	-52.55	-75.42	-67.53	1.30	5.44	H
	3392	-61.48	-13	-48.48	-73.91	-65.28	1.57	7.52	H
	1696	-61.62	-13	-48.62	-65.46	-63.22	1.00	4.75	V
	2544	-63.20	-13	-50.20	-74.01	-65.18	1.30	5.44	V
	3392	-62.63	-13	-49.63	-74.26	-66.43	1.57	7.52	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band II (RMC 12.2Kbps)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3707	-34.73	-13	-21.73	-48.85	-41.31	1.67	8.25	H
	5555	-55.04	-13	-42.04	-76.02	-62.11	2.66	9.72	H
	7410	-51.92	-13	-38.92	-76.67	-61.08	2.46	11.62	H
	3707	-39.00	-13	-26.00	-53.4	-45.58	1.67	8.25	V
	5555	-54.86	-13	-41.86	-72.75	-61.93	2.66	9.72	V
	7410	-53.91	-13	-40.91	-77.83	-63.07	2.46	11.62	V
Middle	3756	-32.63	-13	-19.63	-47.67	-39.25	1.68	8.31	H
	5646	-54.13	-13	-41.13	-74.29	-61.18	2.71	9.76	H
	7515	-51.99	-13	-38.99	-76.17	-61.37	2.42	11.81	H
	3756	-40.47	-13	-27.47	-55.26	-47.09	1.68	8.31	V
	5646	-53.28	-13	-40.28	-71.72	-60.33	2.71	9.76	V
	7515	-51.56	-13	-38.56	-75.66	-60.94	2.42	11.81	V
Highest	3812	-38.61	-13	-25.61	-53.3	-45.28	1.70	8.37	H
	5730	-54.37	-13	-41.37	-74.32	-61.4	2.76	9.79	H
	7627	-47.60	-13	-34.60	-72.44	-57.09	2.39	11.88	H
	3812	-44.69	-13	-31.69	-58.34	-51.36	1.70	8.37	V
	5730	-52.08	-13	-39.08	-71.97	-59.11	2.76	9.79	V
	7627	-48.57	-13	-35.57	-72.51	-58.06	2.39	11.88	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



<DC 24V>

GSM850 (GPRS class 8)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-53.32	-13	-40.32	-57.97	-55.08	0.98	4.89	H
	2472	-49.61	-13	-36.61	-59.29	-51.49	1.28	5.32	H
	3296	-58.40	-13	-45.40	-70.88	-61.81	1.54	7.10	H
	4120	-59.71	-13	-46.71	-75.01	-64.35	1.83	8.62	H
	5768	-56.96	-13	-43.96	-76.88	-61.84	2.78	9.81	H
	1648	-53.53	-13	-40.53	-57.2	-55.29	0.98	4.89	V
	2472	-45.20	-13	-32.20	-55.6	-47.08	1.28	5.32	V
	3296	-54.93	-13	-41.93	-65.71	-58.34	1.54	7.10	V
	4120	-59.55	-13	-46.55	-74.98	-64.19	1.83	8.62	V
	5768	-55.56	-13	-42.56	-74.52	-60.44	2.78	9.81	V
Middle	1672	-53.68	-13	-40.68	-58.01	-55.36	0.99	4.82	H
	2512	-54.11	-13	-41.11	-64.12	-56.08	1.29	5.41	H
	3344	-59.10	-13	-46.10	-71.78	-62.71	1.56	7.31	H
	4184	-60.20	-13	-47.20	-75.76	-64.82	1.87	8.64	H
	5856	-57.03	-13	-44.03	-77.96	-61.89	2.83	9.84	H
	1672	-54.13	-13	-41.13	-57.03	-55.81	0.99	4.82	V
	2512	-46.12	-13	-33.12	-56.48	-48.09	1.29	5.41	V
	3344	-56.92	-13	-43.92	-67.9	-60.53	1.56	7.31	V
	4184	-58.32	-13	-45.32	-74.69	-62.94	1.87	8.64	V
	5856	-55.21	-13	-42.21	-75.24	-60.07	2.83	9.84	V
Highest	1696	-57.65	-13	-44.65	-62.2	-59.25	1.00	4.75	H
	2544	-58.50	-13	-45.50	-67.99	-60.48	1.30	5.44	H
	3392	-59.71	-13	-46.71	-71.73	-63.51	1.57	7.52	H
	4248	-59.49	-13	-46.49	-74.97	-64.09	1.90	8.65	H
	5944	-56.12	-13	-43.12	-77.88	-60.97	2.88	9.88	H
	1696	-57.86	-13	-44.86	-61.43	-59.46	1.00	4.75	V
	2544	-51.73	-13	-38.73	-62	-53.71	1.30	5.44	V
	3392	-55.24	-13	-42.24	-66.82	-59.04	1.57	7.52	V
	4248	-59.28	-13	-46.28	-74.92	-63.88	1.90	8.65	V
	5944	-55.07	-13	-42.07	-76.3	-59.92	2.88	9.88	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band II (RMC 12.2Kbps)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3707	-44.26	-13	-31.26	-58.75	-50.84	1.67	8.25	H
	5555	-55.90	-13	-42.90	-75.23	-62.97	2.66	9.72	H
	7410	-49.85	-13	-36.85	-74.75	-59.01	2.46	11.62	H
	3707	-48.46	-13	-35.46	-63.31	-55.04	1.67	8.25	V
	5555	-54.87	-13	-41.87	-72.62	-61.94	2.66	9.72	V
	7410	-52.08	-13	-39.08	-76.71	-61.24	2.46	11.62	V
Middle	3756	-45.29	-13	-32.29	-59.87	-51.91	1.68	8.31	H
	5646	-54.04	-13	-41.04	-74.18	-61.09	2.71	9.76	H
	7515	-49.88	-13	-36.88	-74.11	-59.26	2.42	11.81	H
	3756	-47.81	-13	-34.81	-62.34	-54.43	1.68	8.31	V
	5646	-52.44	-13	-39.44	-71.21	-59.49	2.71	9.76	V
	7515	-50.79	-13	-37.79	-74.84	-60.17	2.42	11.81	V
Highest	3812	-44.73	-13	-31.73	-59.08	-51.4	1.70	8.37	H
	5730	-54.05	-13	-41.05	-74.4	-61.08	2.76	9.79	H
	7627	-49.94	-13	-36.94	-74.38	-59.43	2.39	11.88	H
	3812	-46.79	-13	-33.79	-60.33	-53.46	1.70	8.37	V
	5730	-52.18	-13	-39.18	-71.46	-59.21	2.76	9.79	V
	7627	-51.82	-13	-38.82	-75.26	-61.31	2.39	11.88	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.