



REPORT No. : SZ15080082S01

FCC SAR TEST REPORT

APPLICANT : TCL Communication Ltd.
PRODUCT NAME : Car Wifi Hotspot
MODEL NAME : Y856UB
TRADE NAME : ALCATEL ONETOUCH
BRAND NAME : ALCATEL ONETOUCH
FCC ID : 2ACCJB028
STANDARD(S) : 47CFR 2.1093
IEEE 1528-2013
ISSUE DATE : 2015-11-10



SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB GROUP

FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , Guangdong Province, P. R. China

Tel: 86-755-36698555
Http://www.morlab.com

Fax: 86-755-36698525
E-mail: service@morlab.cn



DIRECTORY

TEST REPORT DECLARATION	5
1. TECHNICAL INFORMATION	6
1.1 IDENTIFICATION OF APPLICANT	6
1.2 IDENTIFICATION OF MANUFACTURER	6
1.3 EQUIPMENT UNDER TEST (EUT)	6
1.3.1 PHOTOGRAPHS OF THE EUT	6
1.3.2 IDENTIFICATION OF ALL USED EUT	7
1.4 APPLIED REFERENCE DOCUMENTS	7
2. SPECIFIC ABSORPTION RATE (SAR)	9
2.1 INTRODUCTION	9
2.2 SAR DEFINITION	9
3. SAR MEASUREMENT SETUP	10
3.1 THE MEASUREMENT SYSTEM	10
3.2 PROBE	10
3.3 PROBE CALIBRATION PROCESS	12
3.3.1 DOSIMETRIC ASSESSMENT PROCEDURE	12
3.3.2 FREE SPACE ASSESSMENT PROCEDURE	12
3.3.3 TEMPERATURE ASSESSMENT PROCEDURE	12
3.4 PHANTOM	13
3.5 DEVICE HOLDER	13
4. TISSUE SIMULATING LIQUIDS	14
5. UNCERTAINTY ASSESSMENT	16
5.1 UNCERTAINTY EVALUATION FOR EUT SAR TEST	16
5.2 UNCERTAINTY FOR SYSTEM PERFORMANCE CHECK	17



6. SAR MEASUREMENT EVALUATION	19
6.1 SYSTEM SETUP	19
6.2 VALIDATION RESULTS	20
7. OPERATIONAL CONDITIONS DURING TEST	21
7.1 BODY-WORN CONFIGURATIONS	21
7.2 MEASUREMENT PROCEDURE	21
7.3 DESCRIPTION OF INTERPOLATION/EXTRAPOLATION SCHEME	22
8. HOTSPOT MODE EVALUATION PROCEDURE	23
9. INFORMATION RELATED TO LTE TEST PARAMETER(PER 941225 D05V02R03)	24
10. SAR EVALUATION PROCEDURES&POWER MEASUREMENT FOR LTE	27
11. MEASUREMENT OF CONDUCTED OUTPUT POWER	44
12. TEST RESULTS LIST	47
13. REPEATED SAR MEASUREMENT	59
14 MULTIPLE TRANSMITTERS EVALUATION	60
15. ANNEX A GENERAL INFORMATION	64
16. ANNEX B PHOTOGRAPHS OF THE EUT	64
17. ANNEX C PLOTS OF SAR TEST RESULTS	64
18. ANNEX D SYSTEM PERFORMANCE CHECK DATA	64
15. ANNEX A GENERAL INFORMATION	65



REPORT No. : SZ15080082S01

Change History		
Issue	Date	Reason for change
1.0	2015-11-10	First edition



REPORT No. : SZ15080082S01

TEST REPORT DECLARATION

Applicant	TCL Communication Ltd.		
Applicant Address	5F, C-Tower, No.232, Liangjing Road, Zhangjiang High-tech Park, Pudong, Shanghai, China		
Manufacturer	TCL Mobile Communication Co. Ltd. Huizhou		
Manufacturer Address	70 Huifeng 4rd., ZhongKai High-Technology Development District, Huizhou, Guangdong, PRC. 516006		
Product Name	Car Wifi Hotspot		
Model Name	Y856UB		
Brand Name	ALCATEL ONETOUCH		
HW Version	03		
SW Version	Y856_00_03.28_07		
Test Standards	47CFR 2.1093; IEEE 1528-2013		
Test Date	2015-10-16 to 2015-10-17		
The Highest Reported 1g-SAR(W/kg)	Body	1.349W/Kg	Limit(W/kg): 1.6W/kg
	Simultaneous	1.483W/Kg	

Tested by : Liu Jun

Liu Jun

Reviewed by : Zhu Zhan

Zhu Zhan

Approved by : Zeng Dexin

Zeng Dexin



1. TECHNICAL INFORMATION

Note: the Following data is based on the information by the applicant.

1.1 Identification of Applicant

Company Name:	TCL Communication Ltd.
Address:	5F, C-Tower, No.232, Liangjing Road, Zhangjiang High-tech Park, Pudong, Shanghai, China

1.2 Identification of Manufacturer

Company Name:	TCL Mobile Communication Co. Ltd. Huizhou
Address:	70 Huifeng 4rd., ZhongKai High-Technology Development District, Huizhou, Guangdong, PRC. 516006

1.3 Equipment Under Test (EUT)

Model Name:	Y856UB
Trade Name:	ALCATEL ONETOUCH
Brand Name:	ALCATEL ONETOUCH
Hardware Version:	03
Software Version:	Y856_00_03.28_07
Tx Frequency Bands:	CDMA BC0: 824-849MHz; CDMA BC1: 1850-1910MHz; CDMA BC10: 817.25-819.75MHz; 817.9-819.75MHz; FDD-LTE Band 25: 1850-1915MHz; FDD-LTE Band 26: 824-849 MHz; TDD-LTE Band 41: 2496-2690MHz; WiFi 802.11b/g/n20/n40; WiFi 802.11n MIMO 2x2
Uplink Modulations:	CDMA: CDMA LTE: QPSK/16QAM; WIFI 802.11b: DSSS; WIFI 802.11g: OFDM; WIFI 802.11n20: OFDM; WIFI 802.11n40: OFDM;
DTM:	Not support
Antenna type:	Fixed Internal Antenna
Development Stage:	Identical prototype

1.3.1 Photographs of the EUT

Please refer to the External Photos for the Photos of the EUT



1.3.2 Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the Following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
1#	03	Y856_00_03.28_07

1.4 Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1	47 CFR§2.1093	Radiofrequency Radiation Exposure Evaluation: Portable Devices
2	IEEE 1528-2013	IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
3	KDB 447498 D01v05r02	General RF Exposure Guidance
4	KDB 248227 D01v02	SAR Measurement Procedures for 802.11 a/b/g Transmitters
5	KDB 941225 D01v03	SAR Measurement Procedures for 3G Devices
6	KDB 941225 D02v02r02	HSPA and 1x Advanced
7	KDB 941225 D03v01	SAR Test Reduction GSM GPRS EDGE
8	KDB 941225 D04v01	SAR for GSM E GPRS Dual Xfer Mode
9	KDB941225 D05v02r03	SAR for LTE Devices
10	KDB941225 D06v01r01	Hotspot Mode SAR
11	KDB 865664 D01v01r04	SAR Measurement 100 MHz to 6 GHz
12	KDB 865664 D02v01r01	SAR Reporting



1.5 Device Category and SAR Limits

Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

Note: This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.



2. SPECIFIC ABSORPTION RATE (SAR)

2.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are Middle than the limits for general population/uncontrolled.

2.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density. (p). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by,

$$SAR = C \left(\frac{\delta T}{\delta t} \right)$$

Where C is the specific head capacity, δT is the temperature rise and δt the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where σ is the conductivity of the tissue, ρ is the mass density of the tissue and $|E|$ is the rms electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

3. SAR MEASUREMENT SETUP

3.1 The Measurement System

Comosar is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The Comosar system consists of the Following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The Following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 10g mass.

3.2 Probe


For the measurements the Specific Dosimetric E-Field Probe SN 37/08 EP80 with Following specifications is used

- Dynamic range: 0.01-100 W/kg
- Tip Diameter: 6.5 mm

- Distance between probe tip and sensor center: 2.5mm
- Distance between sensor center and the inner phantom surface: 4 mm
(repeatability better than +/- 1mm)
- Probe linearity: <0.25 dB
- Axial Isotropy: <0.25 dB
- Spherical Isotropy: <0.25 dB
- Calibration range: 835to 2500MHz for head & body simulating liquid.

Angle between probe axis (evaluation axis) and surface normal line: less than 30°

Probe calibration is realized, in compliance with CENELEC EN 62209 and IEEE 1528 std, with CALISAR, Antenna proprietary calibration system. The calibration is performed with the EN 622091 annex technique using reference guide at the five frequencies.



$$SAR = \frac{4(P_{fw} - P_{bw})}{ab\delta} \cos^2\left(\pi \frac{y}{a}\right) c \quad (2z/\delta)$$

Where :

P_{fw} = Forward Power

P_{bw} = Backward Power

a and b = Waveguide dimensions

l = Skin depth



Keithley configuration:

Rate = Medium; Filter =ON; RDGS=10; FILTER TYPE =MOVING AVERAGE; RANGE AUTO

After each calibration, a SAR measurement is performed on a validation dipole and compared with a NPL calibrated probe, to verify it.

The calibration factors, CF(N), for the 3 sensors corresponding to dipole 1, dipole 2 and dipole 3 are:

$$CF(N)=SAR(N)/Vlin(N) \quad (N=1,2,3)$$

The linearised output voltage Vlin(N) is obtained from the displayed output voltage V(N) using

$$Vlin(N)=V(N)*(1+V(N)/DCP(N)) \quad (N=1,2,3)$$

Where DCP is the diode compression point in mV.

3.3 Probe Calibration Process

3.3.1 Dosimetric Assessment Procedure

Each E-Probe/Probe Amplifier combination has unique calibration parameters. SATIMO Probe calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm^2) using an with CALISAR, Antenna proprietary calibration system.

3.3.2 Free Space Assessment Procedure

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/cm^2 .

3.3.3 Temperature Assessment Procedure

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulating head tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

Where:

δt = exposure time (30 seconds),



$$SAR = C \left(\frac{\delta T}{\delta t} \right)$$

C = heat capacity of tissue (brain or muscle),

δT = temperature increase due to RF exposure.

SAR is proportional to $\Delta T/\Delta t$, the initial rate of tissue heating, before thermal diffusion takes place.

The electric field in the simulated tissue can be used to estimate SAR by equating the thermally derived SAR to that with the E- field component.

Where:

$$SAR = \frac{\sigma |E|^2}{\rho}$$

σ = simulated tissue conductivity,


ρ = Tissue density (1.25 g/cm³ for brain tissue)

3.4 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.

3.5 Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is Middle than 1°.



Device holder

System Material	Permittivity	Loss Tangent
Delrin	3.7	0.005



4. TISSUE SIMULATING LIQUIDS

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in below table.

The following table gives the recipes for tissue simulating liquids

Frequency Band (MHz)	750	835		1750	1900		2450	2600
Tissue Type	Body	Head	Body	Body	Head	Body	Body	Body
Ingredients (% by weight)								
Deionised Water	50.00	50.36	50.20	68.80	54.90	40.40	73.20	68.1
Salt(NaCl)	0.80	1.25	0.90	0.20	0.18	0.50	0.10	0.10
Sugar	48.80	0.00	48.50	0.00	0.00	58.00	0.00	0.00
Tween 20	0.00	48.39	0.00	0.00	0.00	0.00	0.00	0.00
HEC	0.20	0.00	0.20	0.00	0.00	1.00	0.00	0.00
Bactericide	0.20	0.00	0.20	0.00	0.00	0.10	0.00	0.00
Triton X-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
DGBE	0.00	0.00	0.00	31.00	44.92	0.00	26.70	31.8
Diethylenglycol monohexylether	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Target dielectric parameters								
Dielectric Constant	55.50	41.50	56.10	53.40	39.90	53.30	52.70	52.5
Conductivity (S/m)	0.96	0.90	0.95	1.49	1.42	1.52	1.95	2.16

Note: Please refer to the validation results for dielectric parameters of each frequency band.

The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using an Agilent 85033E Dielectric Probe Kit and an Agilent Network Analyzer.



Table 1: Dielectric Performance of Tissue Simulating Liquid

Temperature: 22.0~23.8°C, humidity: 54~60%.						
Date	Freq.(MHz)	Liquid Parameters	Meas.	Target	Delta(%)	Limit±(%)
2015/11/04	Body 835	Relative Permittivity(ϵ_r):	55.69	56.10	-0.73	5
		Conductivity(σ):	0.97	0.95	2.11	5
2015/11/04	Body 1900	Relative Permittivity(ϵ_r):	53.10	53.3	-0.38	5
		Conductivity(σ):	1.53	1.52	0.66	5
2015/11/05	Body 2450	Relative Permittivity(ϵ_r):	52.52	52.70	-0.34	5
		Conductivity(σ):	1.94	1.95	-0.51	5
2015/11/05	Body 2600	Relative Permittivity(ϵ_r):	52.45	52.50	-0.10	5
		Conductivity(σ):	2.10	2.16	-2.78	5



5. UNCERTAINTY ASSESSMENT

The Following table includes the uncertainty table of the IEEE 1528. The values are determined by Antennessa.

5.1 UNCERTAINTY EVALUATION FOR EUT SAR TEST

a	b	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/ e	k
Uncertainty Component	Sec.	Tol (+-%)	Prob Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi
Measurement System									
Probe calibration	E.2.1	4.76	N	1	1	1	4.76	4.7	∞
Axial Isotropy	E.2.2	2.5	R	$\sqrt{3}$	0.7	0.7	1.01	1.0	∞
Hemispherical Isotropy	E.2.2	4.0	R	$\sqrt{3}$	0.7	0.7	1.62	1.6	∞
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	1	1	0.58	0.5	∞
Linearity	E.2.4	5.0	R	$\sqrt{3}$	1	1	2.89	2.8	∞
System detection limits	E.2.5	1.0	R	$\sqrt{3}$	1	1	0.58	0.5	∞
Readout Electronics	E.2.6	0.02	N	1	1	1	0.02	0.0	∞
Reponse Time	E.2.7	3.0	R	$\sqrt{3}$	1	1	1.73	1.7	∞
Integration Time	E.2.8	2.0	R	$\sqrt{3}$	1	1	1.15	1.1	∞
RF ambient Conditions	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.7	∞
Probe positioner Mechanical Tolerance	E.6.2	2.0	R	$\sqrt{3}$	1	1	1.15	1.1 5	∞
Probe positioning with respect to Phantom Shell	E.6.3	0.05	R	$\sqrt{3}$	1	1	0.03	0.0 3	∞
Extrapolation, interpolation and integration Algoritms for Max. SAR Evaluation	E.5.2	5.0	R	$\sqrt{3}$	1	1	2.89	2.8 9	∞
Test sample Related									
Test sample positioning	E.4.2. 1	0.03	N	1	1	1	0.03	0.0 3	N- 1
Device Holder Uncertainty	E.4.1.	5.00	N	1	1	1	5.00	5.0	N-



	1							0	1
Output power Power drift - SAR drift measurement	6.6.2	4.04	R	$\sqrt{3}$	1	1	2.33	2.3 3	∞
Phantom and Tissue Parameters									
Phantom Uncertainty (Shape and thickness tolerances)	E.3.1	0.05	R	$\sqrt{3}$	1	1	0.03	0.0 3	∞
Liquid conductivity - deviation from target value	E.3.2	4.57	R	$\sqrt{3}$	0.64	0.43	1.69	1.1 3	∞
Liquid conductivity - measurement uncertainty	E.3.3	5.00	N	1	0.64	0.43	3.20	2.1 5	M
Liquid permittivity - deviation from target value	E.3.2	3.69	R	$\sqrt{3}$	0.6	0.49	1.28	1.0 4	∞
Liquid permittivity - measurement uncertainty	E.3.3	10.0 0	N	1	0.6	0.49	6.00	4.9 0	M
Combined Standard Uncertainty			RSS				11.55	10. 67	
Expanded Uncertainty (95% Confidence interval)			K=2				23.11	21. 33	

5.2 UNCERTAINTY FOR SYSTEM PERFORMANCE CHECK

a	b	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/ e	k
Uncertainty Component	Sec.	Tol (+-%)	Prob Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi
Measurement System									
Probe calibration	E.2.1	4.76	N	1	1	1	4.76	4.7	∞
Axial Isotropy	E.2.2	2.5	R	$\sqrt{3}$	0.7	0.7	1.01	1.0	∞
Hemispherical Isotropy	E.2.2	4.0	R	$\sqrt{3}$	0.7	0.7	1.62	1.6	∞
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	1	1	0.58	0.5	∞
Linearity	E.2.4	5.0	R	$\sqrt{3}$	1	1	2.89	2.8	∞
System detection limits	E.2.5	1.0	R	$\sqrt{3}$	1	1	0.58	0.5	∞
Readout Electronics	E.2.6	0.02	N	1	1	1	0.02	0.0	∞




Reponse Time	E.2.7	3.0	R	$\sqrt{3}$	1	1	1.73	1.7	∞
Integration Time	E.2.8	2.0	R	$\sqrt{3}$	1	1	1.15	1.1	∞
RF ambient Conditions	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.7	∞
Probe positioner Mechanical Tolerance	E.6.2	2.0	R	$\sqrt{3}$	1	1	1.15	1.1 5	∞
Probe positioning with respect to Phantom Shell	E.6.3	0.05	R	$\sqrt{3}$	1	1	0.03	0.0 3	∞
Extrapolation, interpolation and integration Algoritms for Max. SAR Evaluation	E.5.2	5.0	R	$\sqrt{3}$	1	1	2.89	2.8 9	∞
Dipole									
Dipole axis to liquid Distance	8,E.4. 2	1.00	N	$\sqrt{3}$	1	1	0.58	0.5 8	∞
Input power and SAR drift measurement	8,6.6. 2	4.04	R	$\sqrt{3}$	1	1	2.33	2.3 3	∞
Phantom and Tissue Parameters									
Phantom Uncertainty (Shape and thickness tolerances)	E.3.1	0.05	R	$\sqrt{3}$	1	1	0.03	0.0 3	∞
Liquid conductivity - deviation from target value	E.3.2	4.57	R	$\sqrt{3}$	0.64	0.43	1.69	1.1 3	∞
Liquid conductivity - measurement uncertainty	E.3.3	5.00	N	$\sqrt{3}$	0.64	0.43	1.85	1.2 4	M
Liquid permittivity - deviation from target value	E.3.2	3.69	R	$\sqrt{3}$	0.6	0.49	1.28	1.0 4	∞
Liquid permittivity - measurement uncertainty	E.3.3	10.0 0	N	$\sqrt{3}$	0.6	0.49	3.46	2.8 3	M
Combined Standard Uncertainty			RSS				8.83	8.3 7	
Expanded Uncertainty (95% Confidence interval)			K=2				17.66	16. 73	

6. SAR MEASUREMENT EVALUATION

6.1 System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave which comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below



The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The power meter PM1 measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to



6 GHz) at the dipole connector and the power meter PM2 is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter PM2.

6.2 Validation Results

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

Frequency	835MHz(B)	1900MHz(B)	2450MHz(B)	2600MHz(B)
Target value 1W (1g)	10.04 W/Kg	42.36W/Kg	56.13 W/Kg	57.73 W/Kg
Test value 1g (100 mW input power)	0.992 W/Kg (11.04)	4.348 W/Kg (11.04)	5.443 W/Kg (11.05)	5.487 W/Kg (11.05)
Normalized to 1W value(1g)	9.92 W/Kg	43.48 W/Kg	54.43 W/Kg	54.87 W/Kg

Note: System checks the specific test data please see Annex D

7. OPERATIONAL CONDITIONS DURING TEST

7.1 Body-worn Configurations

The body-worn configurations shall be tested with the supplied accessories (belt-clips, holsters, etc.) attached to the device in normal use configuration.

For body-worn and other configurations a flat phantom shall be used which is comprised of material with electrical properties similar to the corresponding tissues.




Illustration for Body Worn Position

7.2 Measurement procedure

The Following steps are used for each test position

1. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface.
2. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
3. Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
4. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.



7.3 Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimize measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1mm step.


The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

8. HOTSPOT MODE EVALUATION PROCEDURE

The SAR evaluation procedures for Portable Devices with Wireless Router function is according to KDB 941225 D06 Hot Spot SAR v01r01.

SAR must be tested for all surfaces and edges (side) with a transmitting antenna with in 2.5 cm from that surface or edge, at a test separation distance of 10 mm, in the wireless mode that support wireless routing.

Edge configurations:



Assessment		Hotspot side for SAR				
		Test distance: 15mm				
Antennas	Back	Front	Edge A	Edge B	Edge C	Edge D
CDMA/LTE	Yes	Yes	Yes	Yes	No	Yes
WLAN(ANT 1)	Yes	Yes	No	Yes	No	Yes
WLAN(ANT 2)	Yes	Yes	No	Yes	No	Yes



9. Information Related to LTE Test parameter(Per 941225 D05v02r03)

1	Identify the operating frequency range of each LTE transmission FCC band used by the device	Band 25 Tx:1850-1910 MHz Rx:1930-1995 MHz Band 26 Tx: 814 - 849MHz Rx: 859 - 894MHz Band 41 Tx:2496-2690 MHz Rx: 2496-2690 MHz							
2	Identify the high, middle and low (L, M, H) channel numbers and frequencies tested in each LTE frequency band	Band25	Channel Bandwidth						
			20Mhz	15MHz	10MHz	5MHz	3MHz	1.4MHz	
			Low	20050/ 1720	20025/ 1717.5	20000/ 1715	19975/ 1712.5	19965/ 1711.5	19957/ 1710.7
			Middle	20175/ 1732.5	20175/ 1732.5	20175/ 1732.5	20175/ 1732.5	20175/ 1732.5	20175/ 1732.5
		High	20300/ 1745	20325/ 1747.5	20350/ 1750	20375/ 1752.5	20384/ 1753.5	20392/ 1754.2	
			Band26	Channel Bandwidth					
				20Mhz	15MHz	10MHz	5MHz	3MHz	1.4MHz
				Low	20850/2 510	20825/ 2507.2	20800/ 2505	20775/ 2502.5	/
		Middle		21100/2 535	21100/ 2535	21100/ 2535	21100/2 535	/	/
			High	21350/2 560	21375/ 2562.5	21400/ 2565	21425/ 2567.5	/	/
3	Specify the UE category and uplink modulations used	The UE Category is 4 and the uplink modulations used are QPSK and 16QAM.							
4	Descriptions of the LTE transmitter and antenna implementation & identify whether it is a standalone transmitter operating independently of other wireless transmitters in the device or sharing hardware components and/or antenna(s) with other transmitters etc.	The module has a primary antenna for all LTE&UMTS bands, a Wi-Fi Tx/Rx antenna.							
5	Identify the LTE Band	Mobile Hotspot Mode will be tested according to Section 9 of this							



	Voice/data requirements in each operating mode and exposure condition with respect to head and body test configurations, antenna locations, handset flip-cover or slide positions, antenna diversity conditions, etc.	report.																																						
6	Identify if Maximum Power Reduction (MPR) is optional or mandatory, i.e. built-in by design: only mandatory MPR may be considered during SAR testing, when the maximum output power is permanently limited by the MPR implemented within the UE; and only for the applicable RB (resource block) configurations specified in LTE standards b) A-MPR (additional MPR) must be disabled.	As per 3GPP TS 36.101 v11.0.0 (2012-03) Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3 <table><tr><th rowspan="2">Modulation</th><th colspan="6">Channel bandwidth / Transmission bandwidth (N_{RB})</th><th rowspan="2">MPR (dB)</th></tr><tr><th>1.4 MHz</th><th>3.0 MHz</th><th>5 MHz</th><th>10 MHz</th><th>15 MHz</th><th>20 MHz</th></tr><tr><td>QPSK</td><td>> 5</td><td>> 4</td><td>> 8</td><td>> 12</td><td>> 16</td><td>> 18</td><td>≤ 1</td></tr><tr><td>16 QAM</td><td>≤ 5</td><td>≤ 4</td><td>≤ 8</td><td>≤ 12</td><td>≤ 16</td><td>≤ 18</td><td>≤ 1</td></tr><tr><td>16 QAM</td><td>> 5</td><td>> 4</td><td>> 8</td><td>> 12</td><td>> 16</td><td>> 18</td><td>≤ 2</td></tr></table> A-MPR is supported by design, but disable for SAR testing.	Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)																																	
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																		
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1																																	
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																	
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2																																	
7	Include the maximum average conducted output power measured on the required test channels for each channel bandwidth and UL modulation used in each frequency band: a) with 1 RB allocated at the low, centred, high end of a channel b) using 50% RB allocation low, centered, high end within a channel c) using 100% RB allocation	This is included in the section 11 of this report.																																						



8	Include the maximum average conducted output power measured for the other wireless mode and frequency bands	This is included in the section 13 of this report.
10	Identify the simultaneous transmission conditions for the voice and data configurations supported by all wireless modes, device configurations and frequency bands, for the head and body exposure conditions and device operating configurations (handset flip or cover positions, antenna diversity conditions etc.)	
11	When power reduction is applied to certain wireless modes to satisfy SAR compliance for simultaneous transmission conditions, other equipment certification or operating requirements, include the maximum average conducted output power measured in each power reduction mode applicable to the simultaneous voice/data transmission configurations for such wireless configurations and frequency bands; and also include details of the power reduction implementation and measurement setup	Not applicable.



10. SAR EVALUATION PROCEDURES&POWER MEASUREMENT FOR LTE

“1. QPSK with 1 RB allocation

Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and *required test channel* combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each *required test channel*. When the *reported SAR* is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and *required test channels* is not required for 1 RB allocation; otherwise, SAR is required for the remaining *required test channels* and only for the RB offset configuration with the highest output power for that channel.6 When the *reported SAR* of a *required test channel* is > 1.45 W/kg, SAR is required for all three RB offset configurations for that *required test channel*.

2. QPSK with 50% RB allocation

The procedures required for 1 RB allocation in 1. are applied to measure the SAR for QPSK with 50% RB allocation.

3. QPSK with 100% RB allocation

For QPSK with 100% RB allocation, SAR is not required when the highest maximum output

power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB

allocations and the highest *reported SAR* for 1 RB and 50% RB allocation in 1. and 2. are ≤ 0.8

W/kg. Otherwise, SAR is measured for the highest output power channel and if the *reported SAR*

is > 1.45 W/kg, the remaining *required test channels* must also be tested.

Higher order modulations

For each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in

sections 1. and 2.and 3. to determine the QAM configurations that may need SAR measurement.

For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> \frac{1}{2}$ dB higher than the same configuration in QPSK or when the *reported SAR* for the QPSK configuration is > 1.45 W/kg.

4. Other channel bandwidth standalone SAR test requirements

For the other channel bandwidths used by the device in a frequency band, apply all the procedures required for the largest channel bandwidth in section 5.2 to determine the channels and RB configurations that need SAR testing and only measure SAR when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is $> \frac{1}{2}$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the *reported SAR* of a configuration for the largest channel bandwidth is > 1.45 W/kg.



The equivalent channel configuration for the RB allocation, RB offset and modulation etc. Is determined for the smaller channel bandwidth according to the same number of RB allocated in The largest channel bandwidth. For example, 50 RB in 10 MHz channel bandwidth does not apply to 5MHz channel bandwidth; therefore, this cannot be tested in the smaller channel bandwidth. However, 50% RB allocation in 10 MHz channel bandwidth is equivalent to 100% RB allocation in 5 MHz channel bandwidth; therefore, these are the equivalent configurations to be compared to determine the specific channel and configuration in the smaller channel bandwidth that need SAR testing.”



REPORT No. : SZ15080082S01

LTE BAND 25

Band Width	Channel	Freq.(MHZ)	Modulation	RB Configuration		Average Power (dBm)
				RB Size	RB Offset	
20MHz	L 26140	1860	QPSK	1	0	21.03
				1	49	23.16
				1	99	23.50
				50	0	22.12
				50	25	22.31
				50	49	22.60
				100	0	22.54
			16-QAM	1	0	20.10
				1	49	22.35
				1	99	22.94
				50	0	20.86
				50	25	21.20
				50	49	21.16
				100	0	21.49
	M 26365	1882.5	QPSK	1	0	23.59
				1	49	23.46
				1	99	23.46
				50	0	22.39
				50	25	22.52
				50	49	22.57
				100	0	22.62
			16-QAM	1	0	22.74
				1	49	22.79
				1	99	22.53
				50	0	21.52
				50	25	21.38
				50	49	21.77
				100	0	21.60
	H 26590	1905	QPSK	1	0	23.02
				1	49	23.45
				1	99	21.37
				50	0	22.43
				50	25	22.13
				50	49	22.33
				100	0	22.39
			16-QAM	1	0	22.60
				1	49	22.52
				1	99	20.96
				50	0	20.12
				50	25	20.94
				50	49	21.06
				100	0	21.41



LTE BAND 25 (Continue)

Band Width	Channel	Freq.(MHZ)	Modulation	RB Configuration		Average Power (dBm)
				RB Size	RB Offset	
15MHz	L 26115	1857.5	QPSK	1	0	21.20
				1	37	23.16
				1	74	23.40
				36	0	21.90
				36	18	22.21
				36	35	22.51
				75	0	22.47
			16-QAM	1	0	20.33
				1	37	22.26
				1	74	22.57
				36	0	21.11
				36	18	21.35
				36	35	21.08
				75	0	21.60
	M 26365	1882.5	QPSK	1	0	23.33
				1	37	23.59
				1	74	23.22
				36	0	22.50
				36	18	22.38
				36	35	22.52
				75	0	22.62
			16-QAM	1	0	22.76
				1	37	22.81
				1	74	22.74
				36	0	21.62
				36	18	21.35
				36	35	21.73
				75	0	21.61
	H 26615	1907.5	QPSK	1	0	23.35
				1	37	23.65
				1	74	21.68
				36	0	22.41
				36	18	22.10
				36	35	22.44
				75	0	22.32
			16-QAM	1	0	22.80
				1	37	22.42
				1	74	20.94
				36	0	21.56
				36	18	21.33
				36	35	21.03
				75	0	22.36



LTE BAND 25 (Continue)

Band Width	Channel	Freq.(MHZ)	Modulation	RB Configuration		Average Power (dBm)
				RB Size	RB Offset	
10MHz	L 26090	1855	QPSK	1	0	21.49
				1	24	22.08
				1	49	22.56
				25	0	21.84
				25	12	21.66
				25	24	22.36
				50	0	22.10
			16-QAM	1	0	20.64
				1	24	21.52
				1	49	21.86
				25	0	20.93
				25	12	20.51
				25	24	20.76
				50	0	21.20
	M 26365	1882.5	QPSK	1	0	23.64
				1	24	23.39
				1	49	23.44
				25	0	22.57
				25	12	22.62
				25	24	22.59
				50	0	22.58
			16-QAM	1	0	22.90
				1	24	22.45
				1	49	22.78
				25	0	21.62
				25	12	21.71
				25	24	21.55
				50	0	21.51
	H 26640	1910	QPSK	1	0	23.24
				1	24	23.16
				1	49	21.91
				25	0	22.39
				25	12	22.06
				25	24	22.36
				50	0	22.35
			16-QAM	1	0	22.43
				1	24	22.10
				1	49	20.78
				25	0	21.32
				25	12	21.09
				25	24	21.16
				50	0	22.05



REPORT No. : SZ15080082S01

LTE BAND 25 (Continue)

Band Width	Channel	Freq.(MHZ)	Modulation	RB Configuration		Average Power
				RB Size	RB Offset	(dBm)
5MHz	L 26065	1852.5	QPSK	1	0	21.76
				1	12	22.15
				1	24	22.03
				12	0	21.79
				12	6	21.86
				12	11	21.95
			25	0	21.83	
			16-QAM	1	0	21.15
				1	12	21.23
				1	24	21.51
				12	0	20.76
				12	6	20.64
	12	11		20.49		
	25	0	20.91			
	M 26365	1882.5	QPSK	1	0	23.44
				1	12	23.36
				1	24	23.41
				12	0	22.59
				12	6	22.33
				12	11	22.46
			25	0	22.60	
			16-QAM	1	0	22.33
				1	12	22.11
				1	24	22.16
				12	0	21.59
				12	6	21.63
	12	11		21.47		
	25	0	21.57			
	H 26665	1912.5	QPSK	1	0	22.69
				1	12	22.32
				1	24	21.87
				12	0	22.43
				12	6	22.02
				12	11	22.21
			25	0	22.38	
			16-QAM	1	0	22.10
1				12	21.22	
1				24	21.36	
12				0	21.06	
12				6	21.10	
12	11	21.03				
25	0	21.54				



REPORT No. : SZ15080082S01

LTE BAND 25 (Continue)

Band Width	Channel	Freq.(MHZ)	Modulation	RB Configuration		Average Power (dBm)
				RB Size	RB Offset	
3MHz	L 26055	1851.5	QPSK	1	0	21.77
				1	7	21.94
				1	14	21.89
				8	0	21.11
				8	4	21.23
				8	7	21.52
				15	0	21.91
			16-QAM	1	0	20.95
				1	7	21.20
				1	14	21.17
				8	0	20.89
				8	4	20.96
				8	7	21.10
				15	0	21.09
	M 26365	1882.5	QPSK	1	0	23.62
				1	7	23.30
				1	14	23.44
				8	0	22.41
				8	4	22.06
				8	7	22.13
				15	0	22.63
			16-QAM	1	0	22.65
				1	7	22.76
				1	14	22.50
				8	0	21.43
				8	4	21.26
				8	7	21.82
				15	0	21.58
	H 26675	1913.5	QPSK	1	0	22.54
				1	7	22.44
				1	14	22.14
				8	0	21.62
				8	4	21.38
				8	7	21.42
				15	0	22.37
			16-QAM	1	0	21.44
				1	7	21.32
				1	14	21.10
				8	0	21.03
				8	4	21.41
				8	7	21.00
				15	0	21.57



REPORT No. : SZ15080082S01

LTE BAND 25 (Continue)

Band Width	Channel	Freq.(MHZ)	Modulation	RB Configuration		Average Power (dBm)
				RB Size	RB Offset	
1.4MHz	L 26047	1850.7	QPSK	1	0	21.98
				1	2	22.01
				1	5	21.95
				3	0	21.98
				3	1	21.56
				3	2	21.95
			16-QAM	6	0	21.92
				1	0	21.10
				1	2	21.22
				1	5	21.16
				3	0	21.20
				3	1	21.13
	M 26365	1882.5	QPSK	3	2	21.11
				6	0	21.06
				1	0	23.74
				1	2	23.35
				1	5	23.35
				3	0	23.47
			16-QAM	3	1	23.34
				3	2	23.41
				6	0	22.64
				1	0	22.40
				1	2	22.35
				1	5	22.36
	H 26683	1914.3	QPSK	3	0	21.86
				3	2	21.91
				3	5	21.46
				6	0	21.61
			16-QAM	1	0	22.42
				1	2	22.47
				1	5	22.30
				3	0	22.43
				3	1	22.52
				3	2	22.32
				6	0	22.38
			16-QAM	1	0	21.25
				1	2	21.31
				1	5	21.26
				3	0	21.06
				3	1	21.43
				3	2	21.58
				6	0	21.59



REPORT No. : SZ15080082S01

LTE BAND 26

Band Width	Channel	Freq.(MHZ)	Modulation	RB Configuration		Average Power (dBm)
				RB Size	RB Offset	
15MHz	L 26865	831.5	QPSK	1	0	23.25
				1	37	22.71
				1	74	22.72
				36	0	21.94
				36	18	21.56
				36	35	21.82
				75	0	22.05
			16-QAM	1	0	22.37
				1	37	22.06
				1	74	22.11
				36	0	21.53
				36	18	21.46
				36	35	21.32
				75	0	21.00
	M 26915	836.5	QPSK	1	0	22.75
				1	37	22.68
				1	74	22.67
				36	0	21.91
				36	18	21.53
				36	35	21.81
				75	0	21.97
			16-QAM	1	0	22.43
				1	37	22.12
				1	74	22.04
				36	0	21.26
				36	18	21.33
				36	35	21.14
				75	0	20.86
	H 26965	841.5	QPSK	1	0	23.12
				1	37	23.03
				1	74	22.99
				36	0	22.11
				36	18	22.09
				36	35	22.10
				75	0	22.21
			16-QAM	1	0	21.82
				1	37	21.65
				1	74	21.60
				36	0	21.06
				36	18	21.13
				36	35	21.09
				75	0	21.16



REPORT No. : SZ15080082S01

LTE BAND 26 (Continue)

Band Width	Channel	Freq.(MHZ)	Modulation	RB Configuration		Average Power (dBm)
				RB Size	RB Offset	
10MHz	L 26840	829	QPSK	1	0	23.27
				1	24	23.56
				1	49	23.29
				25	0	22.15
				25	12	22.49
				25	24	22.21
				50	0	22.28
			16-QAM	1	0	22.37
				1	24	22.59
				1	49	22.48
				25	0	21.41
				25	12	21.28
				25	24	21.52
				50	0	21.31
	M 26915	836.5	QPSK	1	0	22.72
				1	24	22.86
				1	49	23.00
				25	0	22.06
				25	12	22.15
				25	24	22.18
				50	0	22.26
			16-QAM	1	0	22.53
				1	24	22.41
				1	49	22.59
				25	0	21.13
				25	12	21.33
				25	24	21.09
				50	0	21.23
	H 26990	844	QPSK	1	0	21.29
				1	24	22.53
				1	49	22.88
				25	0	22.12
				25	12	22.20
				25	24	22.03
				50	0	22.13
			16-QAM	1	0	21.85
				1	24	21.78
				1	49	21.67
				25	0	21.03
				25	12	21.18
				25	24	21.12
				50	0	21.06



REPORT No. : SZ15080082S01

LTE BAND 26 (Continue)

Band Width	Channel	Freq.(MHZ)	Modulation	RB Configuration		Average Power
				RB Size	RB Offset	(dBm)
5MHz	L 26815	826.5	QPSK	1	0	23.19
				1	12	23.42
				1	24	23.32
				12	0	22.52
				12	6	22.66
				12	11	22.18
			25	0	22.29	
			16-QAM	1	0	22.53
				1	12	22.43
				1	24	22.27
				12	0	21.56
				12	6	21.77
	12	11		21.33		
	25	0	21.11			
	M 26915	836.5	QPSK	1	0	23.11
				1	12	23.06
				1	24	23.13
				12	0	22.34
				12	6	22.18
				12	11	22.44
			25	0	22.19	
			16-QAM	1	0	22.42
				1	12	22.60
				1	24	22.13
				12	0	21.38
				12	6	21.44
	12	11		21.25		
	25	0	21.34			
	H 27015	846.5	QPSK	1	0	22.95
				1	12	22.88
1				24	22.97	
12				0	22.03	
12				6	22.11	
12				11	22.06	
25			0	22.02		
16-QAM			1	0	22.54	
			1	12	22.52	
			1	24	22.15	
			12	0	21.42	
			12	6	21.29	
	12	11	21.33			
25	0	21.06				



REPORT No. : SZ15080082S01

TE BAND 26 (Continue)

Band Width	Channel	Freq.(MHZ)	Modulation	RB Configuration		Average Power (dBm)
				RB Size	RB Offset	
3MHz	L 26805	825.5	QPSK	1	0	23.35
				1	7	23.44
				1	14	23.37
				8	0	22.16
				8	4	22.52
				8	7	22.28
				15	0	22.32
			16-QAM	1	0	22.63
				1	7	22.53
				1	14	22.18
				8	0	21.25
				8	4	21.08
				8	7	21.33
				15	0	21.12
	M 26915	836.5	QPSK	1	0	23.26
				1	7	23.11
				1	14	23.03
				8	0	22.16
				8	4	22.34
				8	7	22.19
				15	0	22.24
			16-QAM	1	0	22.76
				1	7	22.34
				1	14	22.08
				8	0	21.16
				8	4	21.43
				8	7	21.38
				15	0	21.25
	H 27025	847.5	QPSK	1	0	22.90
				1	7	23.06
				1	14	22.96
				8	0	22.10
				8	4	21.96
				8	7	22.21
				15	0	22.02
			16-QAM	1	0	21.69
				1	7	21.88
				1	14	21.66
				8	0	21.12
				8	4	21.25
				8	7	21.36
				15	0	21.03



REPORT No. : SZ15080082S01

LTE BAND 26 (Continue)

Band Width	Channel	Freq.(MHZ)	Modulation	RB Configuration		Average Power (dBm)
				RB Size	RB Offset	
1.4MHz	L 26797	824.7	QPSK	1	0	23.28
				1	2	23.15
				1	5	23.23
				3	0	23.20
				3	1	23.05
				3	2	22.86
			16-QAM	6	0	22.32
				1	0	22.54
				1	2	22.42
				1	5	22.33
				3	0	21.71
				3	1	21.86
	M 26915	836.5	QPSK	3	2	21.52
				6	0	21.45
				1	0	23.27
				1	2	23.42
				1	5	23.62
				3	0	23.25
			16-QAM	3	1	23.41
				3	2	23.26
				6	0	22.29
				1	0	22.53
				1	2	22.44
				1	5	22.61
	H 27033	848.3	QPSK	3	0	22.06
				3	2	22.42
				3	5	22.13
				6	0	21.24
			16-QAM	1	0	22.89
				1	2	22.91
				1	5	22.99
				3	0	22.95
				3	1	22.88
				3	2	23.01
				6	0	22.10
			16-QAM	1	0	21.62
				1	2	21.70
				1	5	21.54
				3	0	21.52
				3	1	21.69
				3	2	21.24
				6	0	21.10



REPORT No. : SZ15080082S01

LTE BAND 41

Band Width	Channel	Freq.(MHZ)	Modulation	RB Configuration		Average Power (dBm)
				RB Size	RB Offset	
20MHz	L 39750	2506	QPSK	1	0	22.05
				1	49	22.82
				1	99	22.84
				50	0	21.69
				50	25	21.53
				50	49	21.80
				100	0	21.72
			16-QAM	1	0	21.66
				1	49	21.92
				1	99	21.48
				50	0	20.75
				50	25	20.69
				50	49	20.51
				100	0	20.63
	M 40620	2593	QPSK	1	0	22.84
				1	49	22.45
				1	99	22.29
				50	0	21.45
				50	25	21.34
				50	49	21.53
				100	0	21.46
			16-QAM	1	0	21.26
				1	49	21.40
				1	99	21.33
				50	0	20.58
				50	25	20.42
				50	49	20.64
				100	0	20.33
	H 41490	2680	QPSK	1	0	22.19
				1	49	21.93
				1	99	22.30
				50	0	20.85
				50	25	20.66
				50	49	20.76
				100	0	20.75
			16-QAM	1	0	20.52
				1	49	20.83
				1	99	20.71
				50	0	19.81
				50	25	20.16
				50	49	19.92
				100	0	19.77



REPORT No. : SZ15080082S01

LTE BAND 41 (Continue)

Band Width	Channel	Freq.(MHZ)	Modulation	RB Configuration		Average Power (dBm)
				RB Size	RB Offset	
15MHz	L 39725	2503.5	QPSK	1	0	22.62
				1	37	22.52
				1	74	22.61
				36	0	21.65
				36	18	21.72
				36	35	21.67
				75	0	21.70
			16-QAM	1	0	21.53
				1	37	21.43
				1	74	21.60
				36	0	20.71
				36	18	20.52
				36	35	20.39
				75	0	20.51
	M 40620	2593	QPSK	1	0	22.51
				1	37	22.37
				1	74	22.40
				36	0	21.47
				36	18	21.38
				36	35	21.44
				75	0	21.52
			16-QAM	1	0	21.42
				1	37	21.59
				1	74	21.32
				36	0	20.56
				36	18	20.71
				36	35	20.28
				75	0	20.37
	H 41515	2682.5	QPSK	1	0	22.22
				1	37	21.87
				1	74	22.35
				36	0	20.84
				36	18	20.53
				36	35	20.79
				75	0	20.92
			16-QAM	1	0	20.88
				1	37	20.67
				1	74	20.82
				36	0	19.93
				36	18	19.75
				36	35	19.66
				75	0	19.84



LTE BAND 41 (Continue)

Band Width	Channel	Freq.(MHZ)	Modulation	RB Configuration		Average Power
				RB Size	RB Offset	(dBm)
10MHz	L 39700	2501	QPSK	1	0	22.72
				1	24	22.62
				1	49	22.68
				25	0	21.53
				25	12	21.43
				25	24	21.66
				50	0	21.71
			16-QAM	1	0	21.34
				1	24	21.52
				1	49	21.44
				25	0	20.85
				25	12	20.42
				25	24	20.62
				50	0	20.32
	M 40620	2593	QPSK	1	0	22.41
				1	24	22.36
				1	49	22.29
				25	0	21.53
				25	12	21.38
				25	24	21.16
				50	0	21.46
			16-QAM	1	0	21.62
				1	24	21.43
				1	49	21.71
				25	0	20.37
				25	12	20.59
				25	24	20.25
				50	0	20.36
	H 41540	2685	QPSK	1	0	22.16
				1	24	22.07
1				49	22.31	
25				0	20.75	
25				12	21.06	
25				24	20.95	
50				0	20.66	
16-QAM			1	0	20.73	
			1	24	20.86	
			1	49	20.39	
			25	0	19.96	
			25	12	20.04	
			25	24	19.86	
			50	0	19.77	



REPORT No. : SZ15080082S01

LTE BAND 41 (Continue)

Band Width	Channel	Freq.(MHZ)	Modulation	RB Configuration		Average Power (dBm)
				RB Size	RB Offset	
5MHz	L 39675	2498.5	QPSK	1	0	22.41
				1	12	22.32
				1	24	22.51
				12	0	21.43
				12	6	21.38
				12	11	21.16
				25	0	21.56
			16-QAM	1	0	21.38
				1	12	21.42
				1	24	21.26
				12	0	20.48
				12	6	20.39
				12	11	20.75
				25	0	20.61
	M 40620	2593	QPSK	1	0	22.42
				1	12	22.38
				1	24	22.24
				12	0	21.52
				12	6	21.39
				12	11	21.08
				25	0	21.33
			16-QAM	1	0	21.37
				1	12	21.26
				1	24	21.69
				12	0	20.42
				12	6	20.83
				12	11	20.63
				25	0	20.29
	H 41565	2687.5	QPSK	1	0	22.16
				1	12	21.93
				1	24	22.42
				12	0	20.91
				12	6	20.73
				12	11	20.62
				25	0	20.71
			16-QAM	1	0	20.69
				1	12	20.74
				1	24	20.59
				12	0	19.86
				12	6	19.66
				12	11	19.92
				25	0	19.57



11. MEASUREMENT OF CONDUCTED OUTPUT POWER

1. CDMA 1xRTT Conducted power

Band	Channel	Frequency (MHz)	Output Power
CDMA BC 0	1013	824.7	28.75
	384	836.52	28.76
	777	848.31	28.56
EVDO 0 BC 0	1013	824.7	26.78
	384	836.52	26.94
	777	848.31	26.97
EVDO A BC 0	1013	824.7	28.14
	384	836.52	28.61
	777	848.31	28.26
CDMA BC 1	25	1851.25	26.81
	600	1880.0	26.84
	1175	1908.75	26.89
EVDO 0 BC 1	25	1851.25	26.71
	600	1880.0	26.71
	1175	1908.75	26.96
EVDO A BC 1	25	1851.25	26.54
	600	1880.0	26.52
	1175	1908.75	26.79
CDMA BC 10 Subclass 2	450	817.25	28.34
	500	818.50	28.62
	550	819.75	28.31
EVDO 0 BC 10 Subclass 2	450	817.25	28.60
	500	818.50	28.58
	550	819.75	28.32
EVDO A BC 10 Subclass 2	450	817.25	28.31
	500	818.50	28.60
	550	819.75	28.57



Band	Channel	Frequency (MHz)	Output Power
CDMA BC 10 Subclass 3	650	822.25	28.64
	660	822.50	28.67
	670	822.75	28.57
EVDO 0 BC 10 Subclass 3	650	822.25	28.72
	660	822.50	28.66
	670	822.75	28.59
EVDO A BC 10 Subclass 3	650	822.25	28.62
	660	822.50	28.62
	670	822.75	28.64

2. Wifi average output power(ATN1)

Band	Channel	Frequency (MHz)	Output Power(dBm)		
			802.11b	802.11g	802.11n 20
Wifi	1	2412	14.08	12.34	9.50
	6	2437	13.59	11.94	9.21
	11	2462	16.19	14.13	11.55

Band	Channel	Frequency (MHz)	Output Power(dBm)
			802.11n40
Wifi	3	2422	9.12
	6	2437	9.31
	9	2452	9.97



3. Wifi average output power(ANT2)

Band	Channel	Frequency (MHz)	Output Power(dBm)		
			802.11b	802.11g	802.11n20
Wifi	1	2412	14.03	11.91	9.42
	6	2437	13.51	11.46	9.21
	11	2462	14.56	11.88	9.64

Band	Channel	Frequency (MHz)	Output Power(dBm)
			802.11n40
Wifi	3	2422	7.59
	6	2437	8.08
	9	2452	8.22

4. Wifi MIMO 2x2 average output power

Band	Channel	Frequency (MHz)	Output Power(dBm)
			MIMO 2x2 802.11n20
Wifi	1	2422	12.47
	6	2437	12.22
	11	2452	13.71

Band	Channel	Frequency (MHz)	Output Power(dBm)
			MIMO 2x2 802.11n40
Wifi	3	2422	11.43
	6	2437	11.54
	9	2452	12.19



12. TEST RESULTS LIST

Summary of Measurement Results (CDMA BC0 Band)

Temperature: 21.0~23.8°C, humidity: 54~60%.

Phantom Configurations	Device Test Positions	Device Test channel	SAR(W/Kg), 1g Peak	Scaling Factor	Scaled SAR (W/Kg), 1g	Plot No.
CDMA Body (15mm Separation)	Back upward	1013	0.910	1.059	0.964	
		384	0.959	1.057	1.014	
		777	0.836	1.081	0.904	
	Face upward	1013	0.847	1.059	0.897	
		384	0.807	1.057	0.853	
		777	0.789	1.081	0.853	
	Edge A	384	0.320	1.081	0.346	
	Edge B		0.211		0.228	
	Edge D		0.149		0.161	
EVDO 0 Body (15mm Separation)	Back upward	1013	0.843	1.052	0.887	
		384	0.859	1.014	0.871	
		777	0.789	1.007	0.795	
	Face upward	384	0.707	1.014	0.717	
	Edge A		0.248		0.251	
	Edge B		0.205		0.208	
	Edge D		0.229		0.232	



Summary of Measurement Results (CDMA BC1 Band)

Temperature: 21.0~23.8°C, humidity: 54~60%.

Phantom Configurations	Device Test Positions	Device Test channel	SAR(W/Kg), 1g Peak	Scaling Factor	Scaled SAR (W/Kg), 1g	Plot No.
CDMA Body (15mm Separation)	Back upward	25	1.063	1.045	1.136	
		600	1.038	1.037	1.154	
		1175	1.192	1.026	1.223	
	Face upward	25	1.274	1.045	1.331	
		600	1.268	1.037	1.314	
		1175	1.315	1.026	1.349	
	Edge A	1175	0.413	1.026	0.424	
	Edge B		0.159		0.163	
	Edge D		0.141		0.145	
EVDO 0 Body (15mm Separation)	Back upward	25	0.927	1.069	0.991	
		600	1.148	1.069	1.227	
		1175	1.013	1.009	1.022	
	Face upward	25	0.844	1.069	0.902	
		600	1.053	1.069	1.126	
		1175	0.968	1.009	0.977	
	Edge A	1175	0.344	1.009	0.347	
	Edge B		0.128		0.129	
	Edge D		0.101		0.102	



Summary of Measurement Results (CDMA BC10 Subclass 3 Band)

Temperature: 21.0~23.8°C, humidity: 54~60%.

Phantom Configurations	Device Test Positions	Device Test channel	SAR(W/Kg), 1g Peak	Scaling Factor	Scaled SAR (W/Kg), 1g	Plot No.
CDMA Body (15mm Separation)	Back upward	650	1.083	1.086	1.176	
		660	1.148	1.079	1.239	
		670	1.013	1.104	1.118	
	Face upward	650	0.844	1.086	0.917	
		660	1.049	1.079	1.132	
		670	0.956	1.104	1.055	
	Edge A	660	0.355	1.079	0.383	
	Edge B		0.279	1.079	0.301	
	Edge D		0.137	1.079	0.148	
EVDO 0 Body (15mm Separation)	Back upward	650	1.090	1.067	1.163	
		660	0.989	1.081	1.069	
		670	1.008	1.099	1.108	
	Face upward	650	0.941	1.067	1.004	
		660	0.874	1.081	0.945	
		670	0.856	1.099	0.941	
	Edge A	650	0.284	1.081	0.307	
	Edge B		0.201	1.081	0.217	
	Edge D		0.224	1.081	0.242	



Note:

1. The test distance separation refer to User Manual.
2. When the 1-g SAR for the mid-band channel or the channel with the highest output power satisfy the following conditions, testing of the other channels in the band is not required. (Per KDB 447498 D01 General RF Exposure Guidance v05r02)
 - $\leq 0.8 \text{ W/kg}$ and transmission band $\leq 100 \text{ MHz}$
 - $\leq 0.6 \text{ W/kg}$ and, $100 \text{ MHz} < \text{transmission bandwidth} \leq 200 \text{ MHz}$
 - $\leq 0.4 \text{ W/kg}$ and transmission band $> 200 \text{ MHz}$
3. IEEE Std 1528-2013 require the middle channel to be tested first. This generally applies to wireless devices that are designed to operate in technologies with tight tolerances for maximum output power variations across channels in the band. When the maximum output power variation across the required test channels is $> \frac{1}{2} \text{ dB}$, instead of the middle channel, the highest output power channel must be used.
4. Per KDB 447498, when the SAR procedures require multiple channels to be tested and the 1-g SAR for the highest output channel is less than 0.8 W/kg and peak SAR is less than 1.6 W/kg , where the transmission band corresponding to all channels is $\leq 100 \text{ MHz}$, testing for the other channels is not required.



Summary of Measurement Results (LTE Band 25 bandwidth 20MHz with QPSK 1RB)

Temperature: 21.0~23.8°C, humidity: 54~60%.						
Phantom Configurations	Device Test Positions	Device Test channel	SAR(W/Kg), 1g Peak	Scaling Factor	Scaled SAR (W/Kg), 1g	Plot No.
Body (15mm Separation)	Back upward	26140	1.034	1.000	1.034	
		26365	1.143	1.002	1.145	
		26590	1.028	1.012	1.040	
	Face upward	26140	0.958	1.000	0.958	
		26365	0.967	1.002	0.969	
		26590	0.917	1.012	0.928	
	Edge A	26140	0.489	1.000	0.489	
	Edge B	26140	0.247	1.000	0.247	
	Edge D	26140	0.168	1.000	0.168	

Summary of Measurement Results (LTE Band 25 bandwidth 20MHz with QPSK 50RB)

Temperature: 21.0~23.8°C, humidity: 54~60%.						
Phantom Configurations	Device Test Positions	Device Test channel	SAR(W/Kg), 1g Peak	Scaling Factor	Scaled SAR (W/Kg), 1g	Plot No.
Body (15mm Separation)	Back upward	26140	0.727	1.096	0.797	
	Face upward		0.708		0.776	
	Edge A		0.354		0.388	
	Edge B		0.249		0.273	
	Edge D		0.184		0.202	



REPORT No. : SZ15080082S01

Summary of Measurement Results (LTE Band 25 bandwidth 20MHz with QPSK 50RB)

Temperature: 21.0~23.8°C, humidity: 54~60%.						
Phantom Configurations	Device Test Positions	Device Test channel	SAR(W/Kg), 1g Peak	Scaling Factor	Scaled SAR (W/Kg), 1g	Plot No.
Body (15mm Separation)	Back upward	26365	0.714	1.026	0.733	
	Face upward		0.698		0.716	

Additional LTE test requirement for 16QAM

Not required.

Additional LTE test requirement for other bandwidth

Not required.



Summary of Measurement Results (LTE Band 26 bandwidth 15MHz with QPSK 1RB)

Temperature: 21.0~23.8°C, humidity: 54~60%.						
Phantom Configurations	Device Test Positions	Device Test channel	SAR(W/Kg), 1g Peak	Scaling Factor	Scaled SAR (W/Kg), 1g	Plot No.
Body (15mm Separation)	Back upward	26865	0.708	1.059	0.750	6
	Face upward		0.640		0.678	
	Edge A		0.259		0.274	
	Edge B		0.206		0.218	
	Edge D		0.191		0.202	

Summary of Measurement Results (LTE Band 26 bandwidth 15MHz with QPSK 36RB)

Temperature: 21.0~23.8°C, humidity: 54~60%.						
Phantom Configurations	Device Test Positions	Device Test channel	SAR(W/Kg), 1g Peak	Scaling Factor	Scaled SAR (W/Kg), 1g	Plot No.
Body (15mm Separation)	Back upward	26865	0.628	1.094	0.687	
	Face upward		0.607		0.664	
	Edge A		0.227		0.248	
	Edge B		0.201		0.220	
	Edge D		0.164		0.179	

Additional LTE test requirement for 16QAM

Not required.

Additional LTE test requirement for other bandwidth

Not required.

Additional LTE test requirement for 20MHz with QPSK 100RB

Not required.



Summary of Measurement Results (LTE Band 41 bandwidth 20MHz with QPSK 1RB)

Temperature: 21.0~23.8°C, humidity: 54~60%.						
Phantom Configurations	Device Test Positions	Device Test channel	SAR(W/Kg), 1g Peak	Scaling Factor	Scaled SAR (W/Kg), 1g	Plot No.
Body (15mm Separation)	Back upward	40620	0.342	1.038	0.355	
	Face upward		0.413		0.429	
	Edge A		0.434		0.450	
	Edge B		0.258		0.268	
	Edge D		0.231		0.240	

Summary of Measurement Results (LTE Band 41 bandwidth 20MHz with QPSK 50RB)

Temperature: 21.0~23.8°C, humidity: 54~60%.						
Phantom Configurations	Device Test Positions	Device Test channel	SAR(W/Kg), 1g Peak	Scaling Factor	Scaled SAR (W/Kg), 1g	Plot No.
Body (15mm Separation)	Back upward	39750	0.289	1.047	0.303	
	Face upward		0.384		0.402	
	Edge A		0.401		0.420	
	Edge B		0.234		0.245	
	Edge D		0.218		0.228	

Additional LTE test requirement for 16QAM

Not required.

Additional LTE test requirement for other bandwidth

Not required.

Additional LTE test requirement for 20MHz with QPSK 100RB

Not required.



Note :

1. IEEE Std 1528-2013 require the middle channel to be tested first. This generally applies to wireless devices that are designed to operate in technologies with tight tolerances for maximum output power variations across channels in the band. When the maximum output power variation across the required test channels is $> 1/2$ dB, instead of the middle channel, the highest output power channel must be used.
2. Per KDB 447498, when the SAR procedures require multiple channels to be tested and the 1-g SAR for the highest output channel is less than 0.8 W/kg and peak SAR is less than 1.6W/kg, where the transmission band corresponding to all channels is ≤ 100 MHz, testing for the other channels is not required.
3. The WCDMA mode is test with 12.2kbps RMC and TPC set to all "1", if maximum SAR for 12.2kbps RMC is $\leq 75\%$ of the SAR limit (i.e. 1.2W/Kg 1g) and maximum average output of each RF channel with HSDPA/HSUPA active is less than 1/4 dB higher than that measured without HSDPA/HSUPA using 12.2kbps RMC, according to KDB 941225D01v02, SAR is not required for this handset with HSPA capabilities. This module supports 3GPP release R7 HSPA+ using QPSK only without 16QAM in the uplink. So PBA is not required for HSPA+.



REPORT No. : SZ15080082S01

Summary of Measurement Results (WLAN 802.11b Band ANT 1)

Temperature: 21.0~23.8°C, humidity: 54~60%.								
Phantom Configurations	Device Test Positions	Device Test channel	SAR(W/Kg), 1g Peak	Duty Cycle	Scaling Factor (Duty Cycle)	Scaling Factor (Power)	Scaled SAR (W/Kg), 1g	Plot No.
Body (15mm Separation)	Back upward	11	0.238	99.4%	1.006	1.074	0.257	9
	Front upward		0.134				0.145	
	Edge B		0.124				0.134	
	Edge D		0.109				0.118	

Summary of Measurement Results (WLAN 802.11b Band ANT 2)

Temperature: 21.0~23.8°C, humidity: 54~60%.								
Phantom Configurations	Device Test Positions	Device Test channel	SAR(W/Kg), 1g Peak	Duty Cycle	Scaling Factor (Duty Cycle)	Scaling Factor (Power)	Scaled SAR (W/Kg), 1g	Plot No.
Body (15mm Separation)	Back upward	11	0.201	99.4%	1.006	1.107	0.224	
	Front upward		0.104				0.116	
	Edge B		0.108				0.120	
	Edge D		0.094				0.105	

Summary of Measurement Results (WLAN 802.11n20 MIMO 2x2)

Temperature: 21.0~23.8°C, humidity: 54~60%.								
Phantom Configurations	Device Test Positions	Device Test channel	SAR(W/Kg), 1g Peak	Duty Cycle	Scaling Factor (Duty Cycle)	Scaling Factor (Power)	Scaled SAR (W/Kg), 1g	Plot No.
Body (15mm Separation)	Back upward	11	0.228	99.4%	1.006	1.069	0.245	
	Front upward		0.161				0.173	
	Edge B		0.121				0.130	



REPORT No. : SZ15080082S01

Notes:

1. The EUT has two WLAN Tx antennas, but only 802.11n support MIMO 2x2
2. SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:
3. When the reported SAR of the highest measured maximum output power channel for the exposure configuration is



6. Scaling Factor calculation

Band	Tune-up power tolerance(dBm)	SAR test channel Power (dBm)	Scaling Factor
CDMA BC0	Max output power =28(+1/-2)	28.75	1.059
		28.76	1.057
		28.66	1.081
EVDO 0 BC 0	Max output power =26(+1/-2)	26.78	1.052
		26.94	1.014
		26.97	1.007
CDMA BC1	Max output power =26(+1/-2)	26.71	1.069
		26.54	1.112
		26.89	1.026
EVDO 0 BC 1	Max output power =26(+1/-2)	26.71	1.069
		26.71	1.069
		26.96	1.009
CDMA BC10 Subclass 3	Max output power =28/(+1/-2)	28.64	1.086
		28.67	1.079
		28.57	1.104
EVDO 0 BC 10 Subclass 3	Max output power =28(+1/-2)	28.72	1.067
		28.66	1.081
		28.59	1.099
LTE BAND25 (QPSK)	Max output power =23+-0.5(1RB)	23.50	1.000
		23.49	1.002
		23.45	1.012
	Max output power =22.5+-0.5(50RB)	22.60	1.096
LTE BAND26 (QPSK)	Max output power =22+-0.5(100RB)	22.39	1.026
	Max output power =23.5+-0.5(1RB)	23.75	1.059
	Max output power =22+-0.5(25RB)	22.11	1.094
LTE BAND41 (QPSK)	Max output power =22+-0.5(1RB)	22.84	1.038
	Max output power =21.5+-0.5(50RB)	21.80	1.047
802.11b ANT1	Max output power =16+-0.5	16.19	1.074
802.11b ANT2	Max output power =14.5+-0.5	14.56	1.107
802.11n20 MIMO 2x2	Max output power =13.5+-0.5	13.71	1.069



13. REPEATED SAR MEASUREMENT

In accordance with published RF Exposure KDB procedure 865664 D01 SAR measurement 100 MHz to 6 GHz. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

Band	Test Position	Test Channel	Meas.SAR(W/kg)		Largest to Smallest SAR Ratio
			Original	Repeated	
CDMA BC0	Back upward	384	0.959	0.963	1.004
	Face upward		0.807	0.814	1.008
EVDO BC0	Back upward		0.859	0.842	1.020
CDMA BC1	Back upward	1175	1.192	1.189	1.003
	Face upward		1.315	1.298	1.013
CDMA BC 1 repeated	Face upward		1.298	1.308	1.008
EVDO BC1	Back upward		1.013	1.020	1.007
	Face upward		0.969	0.973	1.004
CDMA BC10	Back upward	660	1.148	1.140	1.007
	Face upward		1.049	1.041	1.008
EVDO BC10	Back upward	650	0.989	0.980	1.009
	Face upward		0.941	0.948	1.007
LTE Band 25	Back upward	26365	1.143	1.150	1.006
	Face upward		0.969	0.960	1.009



14 MULTIPLE TRANSMITTERS EVALUATION

Stand-alone SAR

Test distance: 10			
Band	Highest power(mW) per tune up	1-g SAR test threshold	Test required?
WIFI(802.11b)	16.19	[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • $[\sqrt{f}(\text{GHz})] \leq 3.0$ for 1-g SAR	Yes
WIFI(MIMO2x2)	13.71		Yes

Simultaneous SAR

#	Simultaneous transmission conditions			Sum of WWAN& WLAN
	WWAN		WLAN	
	LTE Data	CDMA	802.11b/g/n	
1	x		x	x
2		x	x	x
3		X	x	x
4	x		X	x

Note:

1. When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the Wi-Fi transmitter and another WWAN transmitter. Both transmitter often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.
2. The hotspot SAR result may overlap with the body-worn accessory SAR requirements, per KDB 941225 D06, the more conservative configurations can be considered, thus excluding some unnecessary body-worn accessory SAR tests.
3. GSM supports voice and data transmission, though not simultaneously. WCDMA supports voice and data transmission simultaneously.



4. Simultaneous Transmission SAR evaluation is not required for BT and WiFi, because the software mechanism have been incorporated to guarantee that the WLAN and Bluetooth transmitters would not simultaneously operate.

5. Per KDB 447498D01v05r01, Simultaneous Transmission SAR Evaluation procedures is as followed:

Step 1: If sum of 1 g SAR < 1.6 W/kg, Simultaneous SAR measurement is not required.

Step 2: If sum of 1 g SAR > 1.6 W/kg, ratio of SAR to peak separation distance for pair of transmitters calculated.

Step 3: If the ratio of SAR to peak separation distance is ≤ 0.04 , Simultaneous SAR measurement is not required.

Step 4: If the ratio of SAR to peak separation distance is > 0.04 , Simultaneous SAR measurement is required and simultaneous transmission SAR value is calculated.

(The ratio is determined by: $(SAR1 + SAR2) \wedge 1.5/Ri \leq 0.04$,

Ri is the separation distance between the peak SAR locations for the antenna pair in mm)

6. Sum of the SAR for CDMA BC0+WiFi

RF Exposure condition	Test position	Simultaneous Transmission Scenario		Max Σ 1-g SAR(W/Kg)	SPLSR (Yes/ No)
		CDMA	WiFi		
Body	Back upward	1.014	0.238	1.252	No
	Face upward	0.897	0.134	1.031	No
	Edge A	0.346	/	0.346	No
	Edge B	0.228	0.124	0.352	No
	Edge C	/	/	/	No
	Edge D	0.161	0.109	0.270	No



7. Sum of the SAR for CDMA BC1+Wi-Fi

RF Exposure condition	Test position	Simultaneous Transmission Scenario		Max Σ 1-g SAR(W/Kg)	SPLSR (Yes/ No)
		GPRS1900	WiFi		
Body	Back upward	1.223	0.238	1.461	No
	Face upward	1.349	0.134	1.483	No
	Edge A	0.424	/	0.424	No
	Edge B	0.163	0.124	0.287	No
	Edge C	/	/	/	No
	Edge D	0.145	0.109	0.254	No

8. Sum of the SAR for CDMA BC10+Wi-Fi

RF Exposure condition	Test position	Simultaneous Transmission Scenario		Max Σ 1-g SAR(W/Kg)	SPLSR (Yes/ No)
		WCDMA850	WiFi		
Body	Back upward	1.239	0.238	1.477	No
	Face upward	1.132	0.134	1.266	No
	Edge A	0.383	/	0.383	No
	Edge B	0.301	0.124	0.425	No
	Edge C	/	/	/	No
	Edge D	0.148	0.109	0.257	No

9. Sum of the SAR for LTE Band 25+Wi-Fi

RF Exposure condition	Test position	Simultaneous Transmission Scenario		Max Σ 1-g SAR(W/Kg)	SPLSR (Yes/ No)
		LTE Band 2	WiFi		
Body	Back upward	1.145	0.238	1.383	No
	Face upward	0.969	0.134	1.103	No
	Edge A	0.489	/	0.489	No
	Edge B	0.247	0.124	0.371	No
	Edge C	/	/	/	No
	Edge D	0.168	0.109	0.277	No



10. Sum of the SAR for LTE Band 26+Wi-Fi

RF Exposure condition	Test position	Simultaneous Transmission Scenario		Max Σ 1-g SAR(W/Kg)	SPLSR (Yes/ No)
		LTE Band 26	WiFi		
Body	Back upward	0.750	0.238	0.988	No
	Face upward	0.678	0.134	0.812	No
	Edge A	0.274	/	0.274	No
	Edge B	0.218	0.124	0.342	No
	Edge C	/	/	/	No
	Edge D	0.202	0.109	0.311	No

11. Sum of the SAR for LTE Band 41+Wi-Fi

RF Exposure condition	Test position	Simultaneous Transmission Scenario		Max Σ 1-g SAR(W/Kg)	SPLSR (Yes/ No)
		LTE Band 41	WiFi		
Body	Back upward	0.355	0.238	0.593	No
	Face upward	0.429	0.134	0.563	No
	Edge A	0.450	/	0.450	No
	Edge B	0.268	0.124	0.392	No
	Edge C	/	/	/	No
	Edge D	0.240	0.109	0.349	No

Note:

The Sum of the SAR is not greater than 1.6W/Kg SPLSR assessment is not required.



REPORT No. : SZ15080082S01

15. ANNEX A GENERAL INFORMATION

16. ANNEX B PHOTOGRAPHS OF THE EUT

17. ANNEX C PLOTS OF SAR TEST RESULTS

18. ANNEX D SYSTEM PERFORMANCE CHECK DATA



REPORT No. : SZ15080082S01

15. ANNEX A GENERAL INFORMATION

1. Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

**3. List of Test Equipments**

No.	Instrument	Type	Cal. Date	Cal. Due
1	PC	Dell (Pentium IV 2.4GHz, SN:X10-23533)	(n.a)	(n.a)
2	Network Emulator	Aglient (8960, SN:10752)	2015-2-21	1year
3	Network Analyzer	Agilent(E5071B ,SN:MY42404762)	2015-9-26	1year
4	Voltmeter	Keithley (2000, SN:1000572)	2015-9-24	1year
5	Signal Generator	Rohde&Schwarz (SMP_02)	2015-9-24	1year
6	Power Amplifier	PRANA (Ap32 SV125AZ)	2015-9-24	1year
7	Power Meter	Agilent (E4416A, SN:MY45102093)	2015-5-07	1year
8	Power Sensor	Agilent (N8482A, SN:MY41091706)	2015-5-07	1year
9	Directional coupler	Giga-tronics(SN:1829112)	2015-9-24	1year
10	Probe	Satimo (SN:SN 37/08 EP80)	2015-8-17	1year
11	Dielectric Probe Kit	Agilent (85033E)	2015-9-24	1year
12	Phantom	Satimo (SN:SN_36_08_SAM62)	2015-9-24	1year
13	Liquid	Satimo(Last Calibration: 2015-10-16 to 2015-10-17)	N/A	N/A
14	Dipole 835MHz	Satimo (SN 20/08 DIPC 99)	2014-9-22	3year
15	Dipole 1750MHz	Satimo (SN 30/13 DIP1G750-260)	2014-9-22	3year
16	Dipole 1900MHz	Satimo (SN 30/13 DIP1G900-261)	2014-9-22	3year
17	Dipole 2450MHz	Satimo (SN 30/13 DIP2G450-263)	2014-9-22	3year
18	Dipole 2600MHz	Satimo (SN 30/13 DIP2G600-265)	2014-9-22	3year

***** END OF REPORT *****