Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

e) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

©Copyright. All rights reserved by CTTL.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.8
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2450 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	**Permittivity**	**Conductivity**
Nominal Head TSL parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	37.9 ± 6 %	1.88 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm^3 (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	13.5 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	**52.5 W/kg ± 17.0 % (k=2)**

SAR averaged over 10 cm^3 (10 g) of Head TSL	condition	
SAR measured	250 mW input power	6.24 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	**24.5 W/kg ± 16.5 % (k=2)**

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	**Permittivity**	**Conductivity**
Nominal Body TSL parameters	22.0 °C	52.7	1.95 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	52.4 ± 6 %	2.03 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm^3 (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	13.3 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	**52.1 W/kg ± 17.0 % (k=2)**

SAR averaged over 10 cm^3 (10 g) of Body TSL	condition	
SAR measured	250 mW input power	6.16 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	**24.4 W/kg ± 16.5 % (k=2)**

©Copyright. All rights reserved by CTTL.

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	49.8 Ω + 4.4 jΩ
Return Loss	- 27.2 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	52.3 Ω + 1.5 jΩ
Return Loss	- 31.4 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.162 ns

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.
No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	November 10, 2009

©Copyright. All rights reserved by CTTL.

DASY5 Validation Report for Head TSL

Date: 24.07.2015

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:853

Communication System: UID 0 - CW; Frequency: 2450 MHz
Medium parameters used: f = 2450 MHz; σ = 1.88 S/m; ε_r = 37.9; ρ = 1000 kg/m^3
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.54, 4.54, 4.54); Calibrated: 30.12.2014;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 18.08.2014
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 100.4 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 27.9 W/kg
SAR(1 g) = 13.5 W/kg; SAR(10 g) = 6.24 W/kg
Maximum value of SAR (measured) = 17.7 W/kg



0 dB = 17.7 W/kg = 12.48 dBW/kg

©Copyright. All rights reserved by CTTL.

Impedance Measurement Plot for Head TSL



©Copyright. All rights reserved by CTTL.

DASY5 Validation Report for Body TSL

Date: 24.07.2015

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:853

Communication System: UID 0 - CW; Frequency: 2450 MHz
Medium parameters used: f = 2450 MHz; σ = 2.03 S/m; ε_r = 52.4; ρ = 1000 kg/m^3
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.32, 4.32, 4.32); Calibrated: 30.12.2014;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 18.08.2014
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 95.79 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 27.5 W/kg
SAR(1 g) = 13.3 W/kg; SAR(10 g) = 6.16 W/kg
Maximum value of SAR (measured) = 17.6 W/kg



0 dB = 17.6 W/kg = 12.46 dBW/kg

©Copyright. All rights reserved by CTTL.

Impedance Measurement Plot for Body TSL



©Copyright. All rights reserved by CTTL.

ANNEX I SPOT CHECK TEST

As the test lab for 4060S from TCL Communication Ltd, we, CTTL (Shouxiang), declare on our sole responsibility that, according to "Declaration of changes" provided by applicant, only the Spot check test should be performed. The test results are as below.

I.1 Conducted power of selected case

Table I.1-1: The conducted power results for GSM850/1900

GSM 850MHz	Conducted Power (dBm)		
	Channel 251(848.8MHz)	Channel 190(836.6MHz)	Channel 128(824.2MHz)
	\	32.05	\
GSM 1900MHz	Conducted Power (dBm)		
	Channel 810(1909.8MHz)	Channel 661(1880MHz)	Channel 512(1850.2MHz)
	29.45	\	\

Table I.1-2: The conducted power results for GPRS

GSM 850 GPRS (GMSK)	Measured Power (dBm)		
	251	190	128
2 Txslots	30.43	\	\
PCS1900 GPRS (GMSK)	Measured Power (dBm)		
	810	661	512
3 Txslots	26.45	\	\

Table I.1-3: The conducted Power for WCDMA

Item	**band**	**FDDV result**		
	ARFCN	**4233 (846.6MHz)**	**4182 (836.4MHz)**	**4132 (826.4MHz)**
WCDMA	****	\	23.82	23.94
Item	**band**	**FDDII result AP OFF**		
	ARFCN	**9538 (1907.6MHz)**	**9400 (1880MHz)**	**9262 (1852.4MHz)**
WCDMA	****	24.00	\	23.90
Item	**band**	**FDDII result AP ON**		
	ARFCN	**9538 (1907.6MHz)**	**9400 (1880MHz)**	**9262 (1852.4MHz)**
WCDMA	****	22.44	\	\
Item	**band**	**FDDIV result**		
	ARFCN	**1513 (1752.6MHz)**	**1412 (1732.4MHz)**	**1312 (1712.4MHz)**
WCDMA	****	23.91	\	23.93

Table I.1-4: The conducted Power for LTE

LTE Band2 20MHz 1RB-Middle (50) AP OFF	1900 (19100)	23.98
LTE Band2 20MHz 1RB-Low (50) AP ON	1900 (19100)	22.43
LTE Band4 20MHz 1RB-Middle (50)	1745 (20300)	24.21
	1720 (20050)	23.84
LTE Band5 10MHz 1RB-Middle (24)	836.5(20525)	24.17
LTE Band12 10MHz 1RB-Middle (24)	707.5(23095)	23.53
	704(23060)	23.70

Table I.1-5: The conducted Power for WLAN

Mode	Channel\data rate	1Mbps
802.11b	11	18
	6	17.65

©Copyright. All rights reserved by CTTL.

I.2 Measurement results

Table I.2-1: SAR Values (GSM 850 MHz Band - Head)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
836.6	190	Left	Touch	Fig.1	32.05	33.5	0.263	**0.37**	0.340	**0.47**	0.10

Table I.2-2: SAR Values (GSM 850 MHz Band - Body)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C											
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
848.8	251	GPRS (2)	Rear	Fig.2	30.43	30.5	0.505	**0.51**	0.662	**0.67**	-0.10

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table I.2-3: SAR Values (GSM 1900 MHz Band - Head)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1909.8	810	Left	Touch	Fig.3	29.45	30.5	0.182	**0.23**	0.303	**0.39**	0.07

Table I.2-4: SAR Values (GSM 1900 MHz Band - Body)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C											
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1909.8	810	GPRS (3)	Bottom	Fig.4	26.45	27	0.492	**0.56**	0.924	**1.05**	-0.06

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table I.2-5: SAR Values (WCDMA 850 MHz Band - Head)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
826.4	4132	Left	Touch	Fig.5	23.94	24	0.229	**0.23**	0.299	**0.30**	0.03

Table I.2-6: SAR Values (WCDMA 850 MHz Band - Body)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
836.4	4182	Rear	Fig.6	23.82	24	0.320	**0.33**	0.419	**0.44**	0.08

Note1: The distance between the EUT and the phantom bottom is 10mm.

©Copyright. All rights reserved by CTTL.

Table I.2-7: SAR Values (WCDMA 1700 MHz Band - Head)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1752.6	1513	Left	Touch	Fig.7	23.91	24	0.438	**0.45**	0.703	**0.72**	0.09

Table I.2-8: SAR Values (WCDMA 1700 MHz Band - Body)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1712.4	1312	Rear	Fig.8	23.93	24	0.598	**0.61**	0.925	**0.94**	-0.10

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table I.2-9: SAR Values (WCDMA 1900 MHz Band - Head)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1852.4	9262	Left	Touch	Fig.9	23.9	24	0.395	**0.40**	0.644	**0.66**	0.02

Table I.2-10: SAR Values (WCDMA 1900 MHz Band - Body) – AP ON

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1907.6	9538	Bottom	Fig.10	22.44	22.5	0.539	**0.55**	0.998	**1.01**	-0.06

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table I.2-11: SAR Values (WCDMA 1900 MHz Band - Body) – AP OFF

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1907.6	9538	Rear	Fig.11	24	24	0.317	**0.32**	0.514	**0.51**	-0.10

Note1: The distance between the EUT and the phantom bottom is 15mm.

Table I.2-12: SAR Values (LTE Band2 - Head)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C												
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
1900	19100	1RB_Mid	Left	Touch	Fig.12	23.98	24.8	0.390	**0.47**	0.649	**0.78**	0.00

Note1: The LTE mode is QPSK_20MHz.

©Copyright. All rights reserved by CTTL.

Table I.2-13: SAR Values (LTE Band2 - Body) – AP ON

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C											
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1900	19100	1RB_Low	Bottom	Fig.13	22.43	23	0.503	**0.57**	0.925	**1.05**	0.09

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_20MHz.

Table I.2-14: SAR Values (LTE Band2 - Body) – AP OFF

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C											
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1900	19100	1RB_Mid	Rear	Fig.14	23.98	24.8	0.361	**0.44**	0.593	**0.72**	-0.07

Note1: The distance between the EUT and the phantom bottom is 15mm.

Note2: The LTE mode is QPSK_20MHz.

Table I.2-15: SAR Values (LTE Band4 - Head)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C												
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
1745	20300	1RB_Mid	Left	Touch	Fig.15	24.21	24.5	0.431	**0.46**	0.686	**0.73**	-0.01

Note1: The LTE mode is QPSK_20MHz.

Table I.2-16: SAR Values (LTE Band4 - Body)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C											
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1720	20050	1RB_Mid	Rear	Fig.16	23.84	24.5	0.605	**0.70**	0.934	**1.09**	-0.15

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_20MHz.

Table I.2-17: SAR Values (LTE Band5 - Head)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C												
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
836.5	20525	1RB_Mid	Left	Touch	Fig.17	24.17	24.5	0.232	**0.25**	0.310	**0.33**	0.01

Note1: The LTE mode is QPSK_10MHz.

©Copyright. All rights reserved by CTTL.

Table I.2-18: SAR Values (LTE Band5 - Body)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5°C											
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
836.5	20525	1RB_Mid	Rear	Fig.18	24.17	24.5	0.343	**0.37**	0.447	**0.48**	-0.02

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_10MHz.

Table I.2-19: SAR Values (LTE Band12 - Head)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5 °C												
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.											
707.5	23095	1RB_Mid	Left	Touch	Fig.19	23.53	24	0.199	**0.22**	0.259	**0.29**	-0.05

Note1: The LTE mode is QPSK_10MHz.

Table I.2-20: SAR Values (LTE Band12 - Body)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5 °C											
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
704	23060	1RB_Mid	Rear	Fig.20	23.7	24	0.287	**0.31**	0.376	**0.40**	0.08

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_10MHz.

I.3 WLAN Evaluation

Head Evaluation

Table I.3-1: SAR Values (WLAN - Head) – 802.11b 1Mbps (Full SAR)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5 °C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
2437	6	Right	Touch	Fig.19	17.65	18	0.410	**0.44**	0.885	**0.96**	0.07

Table I.3-2: SAR Values (WLAN - Head) – 802.11b 1Mbps (Scaled Reported SAR)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5 °C							
Frequency		Side	Test Position	Actual duty factor	maximum duty factor	Reported SAR (1g) (W/kg)	Scaled reported SAR (1g) (W/kg)
MHz	Ch.						
2437	6	Right	Touch	97.83%	100%	**0.96**	**0.98**

©Copyright. All rights reserved by CTTL.

Body Evaluation

Table I.3-3: SAR Values (WLAN - Head) – 802.11b 1Mbps (Full SAR)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5 °C										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
2462	11	Rear	Fig.20	18	18	0.131	**0.13**	0.269	**0.27**	-0.10

Table I.3-4: SAR Values (WLAN - Head) – 802.11b 1Mbps (Scaled Reported SAR)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5 °C						
Frequency		Test Position	Actual duty factor	maximum duty factor	Reported SAR (1g) (W/kg)	Scaled reported SAR (1g) (W/kg)
MHz	Ch.					
2462	11	Rear	97.83%	100%	**0.27**	**0.28**

I.4 Reported SAR Comparison

Exposure Configuration	Technology Band	Reported SAR 1g (W/Kg): spot check	Reported SAR 1g (W/Kg): original
Head (Separation Distance 0mm)	GSM 850	**0.47**	0.39
	PCS 1900	0.39	0.39
	UMTS FDD 2	0.66	0.76
	UMTS FDD 4	**0.72**	0.59
	UMTS FDD 5	0.30	0.44
	LTE Band 2	0.78	0.79
	LTE Band 4	0.73	0.74
	LTE Band 5	0.33	0.44
	LTE Band 12	0.29	0.33
	WLAN 2.4 GHz	0.98	1.25
Hotspot (Separation Distance 10mm)	GSM 850	0.67	0.79
	PCS 1900	1.05	1.18
	UMTS FDD 2	1.01	1.04
	UMTS FDD 4	0.94	1.14
	UMTS FDD 5	0.44	0.48
	LTE Band 2	1.05	1.27
	LTE Band 4	1.09	1.30
	LTE Band 5	0.48	0.52
	LTE Band 12	0.40	0.52
	WLAN 2.4 GHz	0.28	0.29
Body-worn (Data) (Separation Distance 15mm)	UMTS FDD 2	0.51	0.63
	LTE Band2	0.72	0.82

Note: The spot check results of Head for GSM850 and UMTS Band4 are larger than the original results, so these values replace the original results and others are quoted.

©Copyright. All rights reserved by CTTL.

850 Left Cheek Middle

Date: 2016-06-21
Electronics: DAE4 Sn777
Medium: Head 850 MHz
Medium parameters used (interpolated): f = 836.6 MHz; σ = 0.932 mho/m; εr = 42.77; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: GSM 850 Frequency: 836.6 MHz Duty Cycle: 1:8.3
Probe: EX3DV4 - SN3617 ConvF(9.56, 9.56, 9.56)

Area Scan (71x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.371 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 6.814 V/m; Power Drift = 0.10 dB
Peak SAR (extrapolated) = 0.429 W/kg
SAR(1 g) = 0.340 W/kg; SAR(10 g) = 0.263 W/kg
Maximum value of SAR (measured) = 0.352 W/kg



Fig.1 850MHz

©Copyright. All rights reserved by CTTL.

850 Body Rear High

Date: 2016-06-21
Electronics: DAE4 Sn777
Medium: Body 850 MHz
Medium parameters used (interpolated): f = 848.8 MHz; σ = 0.992 mho/m; εr = 57.317; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: GSM 850 GPRS Frequency: 848.8 MHz Duty Cycle: 1:4
Probe: EX3DV4 - SN3617 ConvF(9.71, 9.71, 9.71)

Area Scan (111x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.734 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 25.94 V/m; Power Drift = -0.10 dB
Peak SAR (extrapolated) = 0.832 W/kg
SAR(1 g) = 0.662 W/kg; SAR(10 g) = 0.505 W/kg
Maximum value of SAR (measured) = 0.694 W/kg



Fig.2 850 MHz

©Copyright. All rights reserved by CTTL.

1900 Left Cheek High

Date: 2016-06-23
Electronics: DAE4 Sn777
Medium: Head 1900 MHz
Medium parameters used: f = 1910 MHz; σ = 1.42 mho/m; εr = 40.636; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8.3
Probe: EX3DV4 - SN3617 ConvF(8.07, 8.07, 8.07)

Area Scan (71x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.378 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 3.458 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 0.474 W/kg
SAR(1 g) = 0.303 W/kg; SAR(10 g) = 0.182 W/kg
Maximum value of SAR (measured) = 0.364 W/kg



Fig.3 1900 MHz

©Copyright. All rights reserved by CTTL.

1900 Body Bottom High

Date: 2016-06-23
Electronics: DAE4 Sn777
Medium: Body 1900 MHz
Medium parameters used: f = 1910 MHz; σ = 1.584 mho/m; εr = 52.591; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: GSM 1900MHz GPRS Frequency: 1910 MHz Duty Cycle: 1:2.67
Probe: EX3DV4 - SN3617 ConvF(7.74, 7.74, 7.74)

Area Scan (111x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 1.11 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 26.11 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 1.56 W/kg
SAR(1 g) = 0.924 W/kg; SAR(10 g) = 0.492 W/kg
Maximum value of SAR (measured) = 1.15 W/kg



Fig.4 1900 MHz

©Copyright. All rights reserved by CTTL.

WCDMA 850 Left Cheek Low

Date: 2016-06-21
Electronics: DAE4 Sn777
Medium: Head 850 MHz
Medium parameters used (interpolated): f = 826.4 MHz; σ = 0.922 mho/m; εr = 42.958; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: WCDMA; Frequency: 826.4 MHz; Duty Cycle: 1:1
Probe: EX3DV4 - SN3617 ConvF(9.56, 9.56, 9.56)

Area Scan (71x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.320 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 7.973 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 0.378 W/kg
SAR(1 g) = 0.299 W/kg; SAR(10 g) = 0.229 W/kg
Maximum value of SAR (measured) = 0.309 W/kg



Fig.5 WCDMA 850

©Copyright. All rights reserved by CTTL.

WCDMA 850 Body Rear Middle

Date: 2016-06-21
Electronics: DAE4 Sn777
Medium: Body 850 MHz
Medium parameters used (interpolated): f = 836.4 MHz; σ = 0.981 mho/m; εr = 57.466; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: WCDMA; Frequency: 836.4 MHz; Duty Cycle: 1:1
Probe: EX3DV4 - SN3617 ConvF(9.71, 9.71, 9.71)

Area Scan (111x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.464 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 20.33 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 0.534 W/kg
SAR(1 g) = 0.419 W/kg; SAR(10 g) = 0.320 W/kg.
Maximum value of SAR (measured) = 0.438 W/kg



Fig.6 WCDMA 850

©Copyright. All rights reserved by CTTL.

WCDMA 1700 Left Cheek High

Date: 2016-06-22
Electronics: DAE4 Sn777
Medium: Head 1750 MHz
Medium parameters used (interpolated): f = 1752.6 MHz; σ = 1.386 mho/m; εr = 42.289; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: WCDMA 1700 Frequency: 1752.6 MHz Duty Cycle: 1:1
Probe: EX3DV4 - SN3617 ConvF(8.34, 8.34, 8.34)

Area Scan (71x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.793 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 7.198 V/m; Power Drift = 0.09 dB
Peak SAR (extrapolated) = 1.05 W/kg
SAR(1 g) = 0.703 W/kg; SAR(10 g) = 0.438 W/kg
Maximum value of SAR (measured) = 0.761 W/kg



Fig.7 1700MHz

©Copyright. All rights reserved by CTTL.

WCDMA 1700 Body Rear Low

Date: 2016-06-22
Electronics: DAE4 Sn777
Medium: Body 1750 MHz
Medium parameters used (interpolated): f = 1712.4 MHz; σ = 1.5 mho/m; εr = 55.734; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: WCDMA 1700 Frequency: 1712.4 MHz Duty Cycle: 1:1
Probe: EX3DV4 - SN3617 ConvF(7.96, 7.96, 7.96)

Area Scan (111x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 1.08 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 16.12 V/m; Power Drift = -0.10 dB
Peak SAR (extrapolated) = 1.39 W/kg
SAR(1 g) = 0.925 W/kg; SAR(10 g) = 0.598 W/kg
Maximum value of SAR (measured) = 0.972 W/kg



Fig.8 1700 MHz

©Copyright. All rights reserved by CTTL.

WCDMA 1900 Left Cheek Low

Date: 2016-06-23
Electronics: DAE4 Sn777
Medium: Head 1900 MHz
Medium parameters used (interpolated): f = 1852.4 MHz; σ = 1.377 mho/m; εr = 40.777; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: WCDMA 1900 Frequency: 1852.4 MHz Duty Cycle: 1:1
Probe: EX3DV4 - SN3617 ConvF(8.07, 8.07, 8.07)

Area Scan (71x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.781 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 5.969 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 0.984 W/kg
SAR(1 g) = 0.644 W/kg; SAR(10 g) = 0.395 W/kg
Maximum value of SAR (measured) = 0.756 W/kg



Fig.9 WCDMA1900

©Copyright. All rights reserved by CTTL.

WCDMA 1900 Body Bottom High – AP ON

Date: 2016-06-23
Electronics: DAE4 Sn777
Medium: Body 1900 MHz
Medium parameters used: f = 1907.6 MHz; σ = 1.58 mho/m; εr = 52.577; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: WCDMA 1900 Frequency: 1907.6 MHz Duty Cycle: 1:1
Probe: EX3DV4 - SN3617 ConvF(7.74, 7.74, 7.74)

Area Scan (111x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 1.20 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 25.89 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 1.66 W/kg
SAR(1 g) = 0.998 W/kg; SAR(10 g) = 0.539 W/kg
Maximum value of SAR (measured) = 1.23 W/kg



Fig.10 WCDMA1900

©Copyright. All rights reserved by CTTL.

WCDMA 1900 Body Rear High – AP OFF

Date: 2016-06-23
Electronics: DAE4 Sn777
Medium: Body 1900 MHz
Medium parameters used: f = 1907.6 MHz; σ = 1.58 mho/m; εr = 52.577; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: WCDMA 1900 Frequency: 1907.6 MHz Duty Cycle: 1:1
Probe: EX3DV4 - SN3617 ConvF(7.74, 7.74, 7.74)

Area Scan (111x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.592 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 9.694 V/m; Power Drift = -0.10 dB
Peak SAR (extrapolated) = 0.794 W/kg
SAR(1 g) = 0.514 W/kg; SAR(10 g) = 0.317 W/kg
Maximum value of SAR (measured) = 0.609 W/kg



Fig.11 WCDMA1900

©Copyright. All rights reserved by CTTL.

LTE Band2 Left Cheek High with QPSK_20M_1RB_Middle

Date: 2016-06-23
Electronics: DAE4 Sn777
Medium: Head 1900 MHz
Medium parameters used: f = 1900 MHz; σ = 1.409 mho/m; εr = 40.685; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: LTE Band2 Frequency: 1900 MHz Duty Cycle: 1:1
Probe: EX3DV4 - SN3617 ConvF(8.07, 8.07, 8.07)

Area Scan (71x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.803 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 5.869 V/m; Power Drift = 0.00 dB
Peak SAR (extrapolated) = 1.02 W/kg
SAR(1 g) = 0.649 W/kg; SAR(10 g) = 0.390 W/kg
Maximum value of SAR (measured) = 0.781 W/kg



Fig.12 LTE Band2

©Copyright. All rights reserved by CTTL.

LTE Band2 Body Bottom High with QPSK_20M_1RB_Low – AP ON

Date: 2016-06-23
Electronics: DAE4 Sn777
Medium: Body 1900 MHz
Medium parameters used: f = 1900 MHz; σ = 1.575 mho/m; εr = 52.618; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: LTE Band2 Frequency: 1900 MHz Duty Cycle: 1:1
Probe: EX3DV4 - SN3617 ConvF(7.74, 7.74, 7.74)

Area Scan (111x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 1.15 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 21.66 V/m; Power Drift = 0.09 dB
Peak SAR (extrapolated) = 1.54 W/kg
SAR(1 g) = 0.925 W/kg; SAR(10 g) = 0.503 W/kg
Maximum value of SAR (measured) = 1.13 W/kg



Fig.13 LTE Band2

©Copyright. All rights reserved by CTTL.

LTE Band2 Body Rear High with QPSK_20M_1RB_Middle – AP OFF

Date: 2016-06-23
Electronics: DAE4 Sn777
Medium: Body 1900 MHz
Medium parameters used: f = 1900 MHz; σ = 1.575 mho/m; εr = 52.618; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: LTE Band2 Frequency: 1900 MHz Duty Cycle: 1:1
Probe: EX3DV4 - SN3617 ConvF(7.74, 7.74, 7.74)

Area Scan (111x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.740 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 12.47 V/m; Power Drift = -0.07 dB
Peak SAR (extrapolated) = 0.916 W/kg
SAR(1 g) = 0.593 W/kg; SAR(10 g) = 0.361 W/kg
Maximum value of SAR (measured) = 0.701 W/kg



Fig.14 LTE Band2

©Copyright. All rights reserved by CTTL.

LTE Band4 Left Cheek High with QPSK_20M_1RB_Middle

Date: 2016-06-22
Electronics: DAE4 Sn777
Medium: Head 1750 MHz
Medium parameters used: f = 1745 MHz; σ = 1.354 mho/m; εr = 41.566; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: LTE Band4 Frequency: 1745 MHz Duty Cycle: 1:1
Probe: EX3DV4 - SN3617 ConvF(8.34, 8.34, 8.34)

Area Scan (71x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.846 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 6.832 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 1.02 W/kg
SAR(1 g) = 0.686 W/kg; SAR(10 g) = 0.431 W/kg
Maximum value of SAR (measured) = 0.796 W/kg



Fig.15 LTE Band4

©Copyright. All rights reserved by CTTL.

LTE Band4 Body Rear Low with QPSK_20M_1RB_Middle

Date: 2016-06-22
Electronics: DAE4 Sn777
Medium: Body 1750 MHz
Medium parameters used: f = 1720 MHz; σ = 1.509 mho/m; εr = 55.652; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: LTE Band4 Frequency: 1720 MHz Duty Cycle: 1:1
Probe: EX3DV4 - SN3617 ConvF(7.96, 7.96, 7.96)

Area Scan (111x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 1.20 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 18.80 V/m; Power Drift = -0.15 dB
Peak SAR (extrapolated) = 1.40 W/kg
SAR(1 g) = 0.934 W/kg; SAR(10 g) = 0.605 W/kg
Maximum value of SAR (measured) = 1.08 W/kg



Fig.16 LTE Band4

©Copyright. All rights reserved by CTTL.

LTE Band5 Left Cheek Middle with QPSK_10M_1RB_Middle

Date: 2016-06-21
Electronics: DAE4 Sn777
Medium: Head 850 MHz
Medium parameters used (interpolated): f = 836.5 MHz; σ = 0.933 mho/m; εr = 42.769; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: LTE Band5 Frequency: 836.5 MHz Duty Cycle: 1:1
Probe: EX3DV4 - SN3617 ConvF(9.56, 9.56, 9.56)

Area Scan (71x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.342 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 5.886 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 0.409 W/kg
SAR(1 g) = 0.310 W/kg; SAR(10 g) = 0.232 W/kg
Maximum value of SAR (measured) = 0.327 W/kg



Fig.17 LTE Band5

©Copyright. All rights reserved by CTTL.

LTE Band5 Body Rear Middle with QPSK_10M_1RB_Middle

Date: 2016-06-21
Electronics: DAE4 Sn777
Medium: Body 850 MHz
Medium parameters used (interpolated): f = 836.5 MHz; σ = 0.996 mho/m; εr = 57.285; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: LTE Band5 Frequency: 836.5 MHz Duty Cycle: 1:1
Probe: EX3DV4 - SN3617 ConvF(9.71, 9.71, 9.71)

Area Scan (111x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.468 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 21.03 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 0.558 W/kg
SAR(1 g) = 0.447 W/kg; SAR(10 g) = 0.343 W/kg
Maximum value of SAR (measured) = 0.465 W/kg



Fig.18 LTE Band5

©Copyright. All rights reserved by CTTL.

LTE Band12 Left Cheek Middle with QPSK_10M_1RB_Middle

Date: 2016-06-20
Electronics: DAE4 Sn777
Medium: Head 750 MHz
Medium parameters used (interpolated): f = 707.5 MHz; σ = 0.823 mho/m; εr = 44.191; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: LTE Band12 Frequency: 707.5 MHz Duty Cycle: 1:1
Probe: EX3DV4 - SN3617 ConvF(9.98, 9.98, 9.98)

Area Scan (71x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.294 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 6.242 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 0.331 W/kg
SAR(1 g) = 0.259 W/kg; SAR(10 g) = 0.199 W/kg
Maximum value of SAR (measured) = 0.271 W/kg



Fig.19 LTE Band12

©Copyright. All rights reserved by CTTL.

LTE Band12 Body Rear Low with QPSK_10M_1RB_Middle

Date: 2016-06-20
Electronics: DAE4 Sn777
Medium: Body 750 MHz
Medium parameters used (interpolated): f = 704 MHz; σ = 0.911 mho/m; εr = 57.736; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: LTE Band12 Frequency: 704 MHz Duty Cycle: 1:1
Probe: EX3DV4 - SN3617 ConvF(9.76, 9.76, 9.76)

Area Scan (111x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.433 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 18.35 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 0.484 W/kg
SAR(1 g) = 0.376 W/kg; SAR(10 g) = 0.287 W/kg
Maximum value of SAR (measured) = 0.392 W/kg



Fig.20 LTE Band12

©Copyright. All rights reserved by CTTL.

Wifi 802.11b Right Cheek Channel 6

Date: 2016-06-19
Electronics: DAE4 Sn777
Medium: Head 2450 MHz
Medium parameters used (interpolated): f = 2437 MHz; σ = 1.82 mho/m; ε_r = 40.295; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: WLan 2450 Frequency: 2437 MHz Duty Cycle: 1:1
Probe: EX3DV4 - SN3617 ConvF(7.24, 7.24, 7.24)

Area Scan (81x141x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 1.22 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 13.95 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 1.97 W/kg
SAR(1 g) = 0.885 W/kg; SAR(10 g) = 0.410 W/kg
Maximum value of SAR (measured) = 1.16 W/kg



Fig.21 2450 MHz

©Copyright. All rights reserved by CTTL.

Wifi 802.11b Body Rear Channel 11

Date: 2016-06-19
Electronics: DAE4 Sn777
Medium: Body 2450 MHz
Medium parameters used (interpolated): f = 2462 MHz; σ = 1.945 mho/m; ε_r = 54.513; ρ = 1000 kg/m^3
Ambient Temperature: 23.0^{o}C Liquid Temperature: 22.5^{o}C
Communication System: WLan 2450 Frequency: 2462 MHz Duty Cycle: 1:1
Probe: EX3DV4 - SN3617 ConvF(7.35, 7.35, 7.35)

Area Scan (141x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.347 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 6.278 V/m; Power Drift = -0.10 dB
Peak SAR (extrapolated) = 0.509 W/kg
SAR(1 g) = 0.269 W/kg; SAR(10 g) = 0.131 W/kg
Maximum value of SAR (measured) = 0.302 W/kg



Fig.22 2450 MHz

©Copyright. All rights reserved by CTTL.

ANNEX J Accreditation Certificate

China National Accreditation Service for Conformity Assessment

LABORATORY ACCREDITATION CERTIFICATE

(No. CNAS L0570)

Telecommunication Technology Labs,

Academy of Telecommunication Research, MIIT

No.52, Huayuan North Road, Haidian District, Beijing, China

No.51, Xueyuan Road, Haidian District, Beijing, China

to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories(CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing and calibration.

The scope of accreditation is detailed in the attached schedule bearing the same accreditation number as above. The schedule forms an integral part of this certificate.

Date of Issue: 2014-10-29

Date of Expiry: 2017-06-19

Date of Initial Accreditation: 1998-07-03

Signed on behalf of China National Accreditation Service for Conformity Assessment

China National Accreditation Service for Conformity Assessment (CNAS) is authorized by Certification and Accreditation Administration of the People's Republic of China (CNCA) to operate the national accreditation schemes for conformity assessment. CNAS is the signatory to International Laboratory Accreditation Cooperation Multilateral Recognition Arrangement (ILAC MRA) and Asia Pacific Laboratory Accreditation Cooperation Multilateral Recognition Arrangement (APLAC MRA).

No. CNAS AL 2

0011149

©Copyright. All rights reserved by CTTL.