



LTE band 26(814MHz~824MHz),5MHz(-26dBc)

Frequency(MHz)	Emission Bandwidth (-26dBc)(MHz)	
	QPSK	16QAM
819	4.884	4.819

LTE band 26 , 5MHz Bandwidth,MID,QPSK (-26dBc BW)




LTE band 26 , 5MHz Bandwidth,MID,16QAM (-26dBc BW)




LTE band 26(814MHz~824MHz),10MHz(-26dBc)

Frequency(MHz)	Emission Bandwidth (-26dBc)(MHz)	
	QPSK	16QAM
819	9.682	9.595

LTE band 26 , 10MHz Bandwidth,MID,QPSK (-26dBc BW)




LTE band 26 , 10MHz Bandwidth,MID,16QAM (-26dBc BW)




LTE band 41,5MHz(-26dBc)

Frequency(MHz)	Emission Bandwidth (-26dBc)(MHz)	
	QPSK	16QAM
2593	4.971	4.884

LTE band 41 , 5MHz Bandwidth,MID,QPSK (-26dBc BW)




LTE band 41 , 5MHz Bandwidth,MID,16QAM (-26dBc BW)




LTE band 41,10MHz(-26dBc)

Frequency(MHz)	Emission Bandwidth (-26dBc)(MHz)	
	QPSK	16QAM
2593	9.682	9.508

LTE band 41 , 10MHz Bandwidth,MID,QPSK (-26dBc BW)




LTE band 41 , 10MHz Bandwidth,MID,16QAM (-26dBc BW)




LTE band 41,15MHz(-26dBc)

Frequency(MHz)	Emission Bandwidth (-26dBc)(MHz)	
	QPSK	16QAM
2593	14.457	14.457

LTE band 41 , 15MHz Bandwidth,MID,QPSK (-26dBc BW)




LTE band 41 , 15MHz Bandwidth,MID,16QAM (-26dBc BW)




LTE band 41,20MHz(-26dBc)

Frequency(MHz)	Emission Bandwidth (-26dBc)(MHz)	
	QPSK	16QAM
2593	19.103	19.363

LTE band 41 , 20MHz Bandwidth,MID,QPSK (-26dBc BW)




LTE band 41 , 20MHz Bandwidth,MID,16QAM (-26dBc BW)




LTE band 66,1.4MHz(-26dBc)

Frequency(MHz)	Emission Bandwidth (-26dBc)(MHz)	
	QPSK	16QAM
1745	1.276	1.301

LTE band 66 , 1.4MHz Bandwidth,MID,QPSK (-26dBc BW)




LTE band 66 , 1.4MHz Bandwidth,MID,16QAM (-26dBc BW)




LTE band 66,3MHz(-26dBc)

Frequency(MHz)	Emission Bandwidth (-26dBc)(MHz)	
	QPSK	16QAM
1745	2.904	2.904

LTE band 66 , 3MHz Bandwidth,MID,QPSK (-26dBc BW)




LTE band 66 , 3MHz Bandwidth,MID,16QAM (-26dBc BW)




LTE band 66,5MHz(-26dBc)

Frequency(MHz)	Emission Bandwidth (-26dBc)(MHz)	
	QPSK	16QAM
1745	4.906	4.863

LTE band 66 , 5MHz Bandwidth,MID,QPSK (-26dBc BW)




LTE band 66 , 5MHz Bandwidth,MID,16QAM (-26dBc BW)




LTE band 66,10MHz(-26dBc)

Frequency(MHz)	Emission Bandwidth (-26dBc)(MHz)	
	QPSK	16QAM
1745	9.682	9.551

LTE band 66 , 10MHz Bandwidth,MID,QPSK (-26dBc BW)




LTE band 66 , 10MHz Bandwidth,MID,16QAM (-26dBc BW)




LTE band 66,15MHz(-26dBc)

Frequency(MHz)	Emission Bandwidth (-26dBc)(MHz)	
	QPSK	16QAM
1745	14.653	14.522

LTE band 66 , 15MHz Bandwidth,MID,QPSK (-26dBc BW)




LTE band 66 , 15MHz Bandwidth,MID,16QAM (-26dBc BW)




LTE band 66,20MHz(-26dBc)

Frequency(MHz)	Emission Bandwidth (-26dBc)(MHz)	
	QPSK	16QAM
1745	19.016	19.190

LTE band 66 , 20MHz Bandwidth,MID,QPSK (-26dBc BW)




LTE band 66 , 20MHz Bandwidth,MID,16QAM (-26dBc BW)




LTE band 71,5MHz(-26dBc)

Frequency(MHz)	Emission Bandwidth (-26dBc)(MHz)	
	QPSK	16QAM
680.5	4.906	4.841

LTE band 71 , 5MHz Bandwidth,MID,QPSK (-26dBc BW)




LTE band 71 , 5MHz Bandwidth,MID,16QAM (-26dBc BW)




LTE band 71,10MHz(-26dBc)

Frequency(MHz)	Emission Bandwidth (-26dBc)(MHz)	
	QPSK	16QAM
680.5	9.725	9.551

LTE band 71 , 10MHz Bandwidth,MID,QPSK (-26dBc BW)




LTE band 71 , 10MHz Bandwidth,MID,16QAM (-26dBc BW)




LTE band 71,15MHz(-26dBc)

Frequency(MHz)	Emission Bandwidth (-26dBc)(MHz)	
	QPSK	16QAM
680.5	14.653	14.522

LTE band 71 , 15MHz Bandwidth,MID,QPSK (-26dBc BW)




LTE band 71 , 15MHz Bandwidth,MID,16QAM (-26dBc BW)




LTE band 71,20MHz(-26dBc)

Frequency(MHz)	Emission Bandwidth (-26dBc)(MHz)	
	QPSK	16QAM
683	19.016	19.016

LTE band 71 , 20MHz Bandwidth,MID,QPSK (-26dBc BW)



LTE band 71 , 20MHz Bandwidth,MID,16QAM (-26dBc BW)



A.6 Band Edge Compliance

A.6.1 Measurement limit

Part 22.917, Part 24.238 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Part 27.53(m) specifies for mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Part 27.53(g) states for operations in the 600 MHz band and the 698–746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.


Part 90.691 states that out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows: For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz. For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

The spectrum analyzer readings are corrected by $[10 \log(1/\text{duty cycle})]$ for the non-continuous transmitting scenario.


A.6.2 Measurement result

LTE band 2


OBW: 1RB-LOW_offset




LOW BAND EDGE BLOCK-1RB-LOW_offset



OBW: 1RB-HIGH_offset



HIGH BAND EDGE BLOCK-1RB-HIGH_offset



Spectrum

Ref Level 26.00 dBm Offset 0.80 dB RBW 200 kHz
 Att 45 dB SWT 100 ms VBW 1 MHz Mode Auto Sweep
 SGL Count 100/100 TDF

1Rm AvgLog

20 dBm
 10 dBm
 0 dBm
 -10 dBm
 -20 dBm
 -30 dBm
 -40 dBm
 -50 dBm
 -60 dBm
 -70 dBm

CF 1.85 GHz 501 pts Span 20.0 MHz

M1[1] -40.45 dBm 1.8500000 GHz
 M1
 S2
 S1


mit1_for_trace1

Date: 8.JAN.2025 11:10:42


The screenshot displays a spectrum analyzer interface. The top section contains control parameters: **Ref Level** 26.00 dBm, **Offset** 0.80 dB, **RBW** 200 kHz, **Att** 45 dB, **SWT** 100 ms, **VBW** 1 MHz, and **Mode** Auto Sweep. Below these, **SLG Count** is 100/100 and **TDF** is selected. The main plot area shows a blue trace labeled "1Rm AvgLog". The y-axis represents power in dBm, ranging from -70 to 20. The x-axis represents frequency in GHz, with a center frequency (CF) of 1.91 GHz and a span of 20.0 MHz. A red vertical line marks a point at 501 pts. To the left of this point, the signal is at approximately 0 dBm. At the red line, the signal drops sharply to about -48.86 dBm. A label "M1[1]" is placed above the drop, and another "M1" is at the new level. A red horizontal line is labeled "limit1_for_trace1". The bottom status bar shows the date and time: "Date: 8.JAN.2025 11:19:37".

LTE band 4


OBW: 1RB-LOW_offset




LOW BAND EDGE BLOCK-1RB-LOW_offset




OBW: 1RB-HIGH_offset




HIGH BAND EDGE BLOCK-1RB-HIGH_offset



LOW BAND EDGE BLOCK-20MHz-100%RB




HIGH BAND EDGE BLOCK-20MHz-100%RB




LTE band 5


OBW: 1RB-LOW_offset




LOW BAND EDGE BLOCK-1RB-LOW_offset




OBW: 1RB-HIGH_offset




HIGH BAND EDGE BLOCK-1RB-HIGH_offset



LOW BAND EDGE BLOCK-10MHz-100%RB




HIGH BAND EDGE BLOCK-10MHz-100%RB



LTE band 7


OBW: 1RB-LOW_offset




LOW BAND EDGE BLOCK-1RB-LOW_offset




LOW BAND EDGE BLOCK-1RB-LOW_offset




Channel power




OBW: 1RB-HIGH_offset




HIGH BAND EDGE BLOCK-1RB-HIGH_offset




HIGH BAND EDGE BLOCK-1RB-HIGH_offset




LOW BAND EDGE BLOCK-20MHz-100%RB



LOW BAND EDGE BLOCK-20MHz-100%RB



HIGH BAND EDGE BLOCK-20MHz-100%RB




HIGH BAND EDGE BLOCK-20MHz-100%RB




LTE band 12


LOW BAND EDGE BLOCK-1RB-LOW_offset




HIGH BAND EDGE BLOCK-1RB-HIGH_offset



LOW BAND EDGE BLOCK-10MHz-100%RB




HIGH BAND EDGE BLOCK-10MHz-100%RB




LTE band 25


OBW: 1RB-LOW_offset




LOW BAND EDGE BLOCK-1RB-LOW_offset




OBW: 1RB-HIGH_offset




HIGH BAND EDGE BLOCK-1RB-HIGH_offset



LOW BAND EDGE BLOCK-20MHz-100%RB




HIGH BAND EDGE BLOCK-20MHz-100%RB




LTE band 26(824MHz~849MHz)


OBW: 1RB-LOW_offset




LOW BAND EDGE BLOCK-1RB-LOW_offset




OBW: 1RB-HIGH_offset



HIGH BAND EDGE BLOCK-1RB-HIGH_offset



LOW BAND EDGE BLOCK-15MHz-100%RB




HIGH BAND EDGE BLOCK-15MHz-100%RB




LTE band 26(814MHz~824MHz)


OBW: 1RB-LOW_offset




LOW BAND EDGE BLOCK-1RB-LOW_offset




LOW BAND EDGE BLOCK-1RB-LOW_offset




OBW: 1RB-HIGH_offset




HIGH BAND EDGE BLOCK-1RB-HIGH_offset




HIGH BAND EDGE BLOCK-1RB-HIGH_offset




LOW BAND EDGE BLOCK-10MHz-100%RB




LOW BAND EDGE BLOCK-10MHz-100%RB



HIGH BAND EDGE BLOCK-10MHz-100%RB




HIGH BAND EDGE BLOCK-10MHz-100%RB




LTE band 38


OBW: 1RB-LOW_offset




LOW BAND EDGE BLOCK-1RB-LOW_offset




LOW BAND EDGE BLOCK-1RB-LOW_offset




OBW: 1RB-HIGH_offset




HIGH BAND EDGE BLOCK-1RB-HIGH_offset




HIGH BAND EDGE BLOCK-1RB-HIGH_offset




LOW BAND EDGE BLOCK-20MHz-100%RB




LOW BAND EDGE BLOCK-20MHz-100%RB



HIGH BAND EDGE BLOCK-20MHz-100%RB




HIGH BAND EDGE BLOCK-20MHz-100%RB




LTE band 41


OBW: 1RB-LOW_offset




LOW BAND EDGE BLOCK-1RB-LOW_offset




LOW BAND EDGE BLOCK-1RB-LOW_offset




OBW: 1RB-HIGH_offset




HIGH BAND EDGE BLOCK-1RB-HIGH_offset




HIGH BAND EDGE BLOCK-1RB-HIGH_offset




LOW BAND EDGE BLOCK-20MHz-100%RB




LOW BAND EDGE BLOCK-20MHz-100%RB




Channel power



HIGH BAND EDGE BLOCK-20MHz-100%RB




HIGH BAND EDGE BLOCK-20MHz-100%RB




LTE band 66


OBW: 1RB-LOW_offset




LOW BAND EDGE BLOCK-1RB-LOW_offset




OBW: 1RB-HIGH_offset




HIGH BAND EDGE BLOCK-1RB-HIGH_offset



LOW BAND EDGE BLOCK-20MHz-100%RB




HIGH BAND EDGE BLOCK-20MHz-100%RB




LTE band 71


LOW BAND EDGE BLOCK-1RB-LOW_offset




HIGH BAND EDGE BLOCK-1RB-HIGH_offset



LOW BAND EDGE BLOCK-20MHz-100%RB



HIGH BAND EDGE BLOCK-20MHz-100%RB



A.7 Conducted Spurious Emission

A.7.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. In measuring unwanted emissions, the spectrum shall be investigated from 30 MHz or the lowest radio frequency signal generated in the equipment, whichever is lower, without going below 9 kHz, up to at least the frequency given below:
 - (a) If the equipment operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
 - (b) If the equipment operates at or above 10 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.
3. The number of sweep points of spectrum analyzer is greater than $2 \times \text{span/RBW}$.

A. 7.2 Measurement Limit

Part 22.917, Part 24.238 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Part 27.53(m) specifies for mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Part 27.53(g) states for operations in the 600 MHz band and the 698–746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.



Part 90.691 states that out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows: For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$

decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz. For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10\log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

A.7.3 Measurement result


LTE band 7

NOTE: peak above the limit line is the carrier frequency.





LTE band 12

NOTE: peak above the limit line is the carrier frequency.




LTE band 25

NOTE: peak above the limit line is the carrier frequency.




LTE band 26(824MHz~849MHz)

NOTE: peak above the limit line is the carrier frequency.





LTE band 26(814MHz~824MHz)

NOTE: peak above the limit line is the carrier frequency.





LTE band 41

NOTE: peak above the limit line is the carrier frequency.




LTE band 66

NOTE: peak above the limit line is the carrier frequency.



LTE band 71

NOTE: peak above the limit line is the carrier frequency.



A.8 Peak-to-Average Power Ratio

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB

- a) Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- b) Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Record the maximum PAPR level associated with a probability of 0.1%.

Measurement results

LTE Band 7, 20MHz

Frequency (MHz)	PAPR (dB)			
	QPSK	16QAM	64QAM	256QAM
2535	5.33	6.26	6.49	6.67

LTE Band 12, 10MHz

Frequency (MHz)	PAPR (dB)			
	QPSK	16QAM	64QAM	256QAM
707.5	5.42	6.32	6.61	6.72

LTE Band 25, 20MHz

Frequency (MHz)	PAPR (dB)			
	QPSK	16QAM	64QAM	256QAM
1882.5	5.45	6.20	6.52	6.58

LTE Band 41, 20MHz

Frequency (MHz)	PAPR (dB)			
	QPSK	16QAM	64QAM	256QAM
2593	4.93	5.77	6.29	6.72

LTE Band 66, 20MHz

Frequency (MHz)	PAPR (dB)			
	QPSK	16QAM	64QAM	256QAM
1745	4.78	5.68	6.20	6.61

LTE Band 71, 20MHz

Frequency (MHz)	PAPR (dB)			
	QPSK	16QAM	64QAM	256QAM
683	5.36	6.09	6.41	6.46

Annex B: Accreditation Certificate



Accredited Laboratory

A2LA has accredited

TELECOMMUNICATION TECHNOLOGY LABS, CAICT

Beijing, People's Republic of China

for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 *General requirements for the competence of testing and calibration laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



Presented this 23rd day of July 2024.



Mr. Trace McInturff, Vice President, Accreditation Services
For the Accreditation Council
Certificate Number 7049.01
Valid to July 31, 2026

For the tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.

END OF REPORT