

1. Effective (Isotropic) Radiated Power Output Data

1.1 Test Result

1.1.1 Band V_ERP

Band: V								
ENV	Mode		Frequency (MHz)	Conducted Power (dBm)	Gain (dBi)	ERP (dBm)		Verdict
	Network	Subset				Result	Limit	
NTNV	RMC	12.2kbps RMC	826.4	22.27	-4.29	15.83	<=38.45	Pass
			836.6	22.26	-4.29	15.82	<=38.45	Pass
			846.6	22.31	-4.29	15.87	<=38.45	Pass
	HSDPA	Subtest 1	826.4	22.05	-4.29	15.61	<=38.45	Pass
		Subtest 2	826.4	21.99	-4.29	15.55	<=38.45	Pass
		Subtest 3	826.4	22.01	-4.29	15.57	<=38.45	Pass
		Subtest 4	826.4	21.99	-4.29	15.55	<=38.45	Pass
		Subtest 1	836.6	22.15	-4.29	15.71	<=38.45	Pass
		Subtest 2	836.6	22.16	-4.29	15.72	<=38.45	Pass
		Subtest 3	836.6	22.18	-4.29	15.74	<=38.45	Pass
		Subtest 4	836.6	22.15	-4.29	15.71	<=38.45	Pass
		Subtest 1	846.6	22.00	-4.29	15.56	<=38.45	Pass
		Subtest 2	846.6	22.01	-4.29	15.57	<=38.45	Pass
		Subtest 3	846.6	22.02	-4.29	15.58	<=38.45	Pass
		Subtest 4	846.6	21.98	-4.29	15.54	<=38.45	Pass
	HSUPA	Subtest 1	826.4	21.04	-4.29	14.60	<=38.45	Pass
		Subtest 2	826.4	20.97	-4.29	14.53	<=38.45	Pass
		Subtest 3	826.4	19.39	-4.29	12.95	<=38.45	Pass
		Subtest 4	826.4	19.23	-4.29	12.79	<=38.45	Pass
		Subtest 5	826.4	20.98	-4.29	14.54	<=38.45	Pass
		Subtest 1	836.6	21.25	-4.29	14.81	<=38.45	Pass
		Subtest 2	836.6	19.17	-4.29	12.73	<=38.45	Pass
		Subtest 3	836.6	21.27	-4.29	14.83	<=38.45	Pass
		Subtest 4	836.6	21.12	-4.29	14.68	<=38.45	Pass
		Subtest 5	836.6	21.12	-4.29	14.68	<=38.45	Pass
		Subtest 1	846.6	19.66	-4.29	13.22	<=38.45	Pass
		Subtest 2	846.6	19.66	-4.29	13.22	<=38.45	Pass
		Subtest 3	846.6	19.62	-4.29	13.18	<=38.45	Pass
		Subtest 4	846.6	20.80	-4.29	14.36	<=38.45	Pass
		Subtest 5	846.6	19.43	-4.29	12.99	<=38.45	Pass

Note1: ERP=Conducted Power+Antenna Gain-2.15

---End---