SAR TEST REPORT

No. I15Z40216-SEM01

For

TCL Communication Ltd.

HSUPA/HSDPA/UMTS Triple band/GSM Quad band mobile phone

Model Name: 4009A

With

Hardware Version: PIO

Software Version: v4B2A

FCC ID: 2ACCJH017

Issued Date: 2015-2-28

TESTING
CNAS L0570

Note:

The test results in this test report relate only to the devices specified in this report.This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District, Beijing, P. R. China100191

Tel:+86(0)10-62304633-2512,Fax:+86(0)10-62304633-2504

Email:cttl_terminals@catr.cn, website:www.chinattl.com

©Copyright. All rights reserved by CTTL.

REPORT HISTORY

Report Number	Revision	Issue Date	Description
I15Z40216-SEM01	Rev.0	2015-2-9	Initial creation of test report
I15Z40216-SEM01	Rev.1	2015-2-13	Update the table 14.2 on page 34 and table 14.14 on page 40
I15Z40216-SEM01	Rev.2	2015-2-28	Update the table of content, update tables 8.1 and 8.2 on page 17, correct reported SAR comparison on page 154

©Copyright. All rights reserved by CTTL.

TABLE OF CONTENT

1 TEST LABORATORY 5

1.1 TESTING LOCATION 5
1.2 TESTING ENVIRONMENT 5
1.3 PROJECT DATA 5
1.4 SIGNATURE 5

2 STATEMENT OF COMPLIANCE 6

3 CLIENT INFORMATION 8

3.1 APPLICANT INFORMATION 8
3.2 MANUFACTURER INFORMATION 8

4 EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) 9

4.1 ABOUT EUT 9
4.2 INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST 9
4.3 INTERNAL IDENTIFICATION OF AE USED DURING THE TEST 10

5 TEST METHODOLOGY 10

5.1 APPLICABLE LIMIT REGULATIONS 10
5.2 APPLICABLE MEASUREMENT STANDARDS 10

6 SPECIFIC ABSORPTION RATE (SAR) 11

6.1 INTRODUCTION 11
6.2 SAR DEFINITION 11

7 TISSUE SIMULATING LIQUIDS 12

7.1 TARGETS FOR TISSUE SIMULATING LIQUID 12
7.2 DIELECTRIC PERFORMANCE 12

8 SYSTEM VERIFICATION 16

8.1 SYSTEM SETUP 16
8.2 SYSTEM VERIFICATION 17

9 MEASUREMENT PROCEDURES 18

9.1 TESTS TO BE PERFORMED 18
9.2 GENERAL MEASUREMENT PROCEDURE 19
9.3 WCDMA MEASUREMENT PROCEDURES FOR SAR 20
9.4 BLUETOOTH & WI-FI MEASUREMENT PROCEDURES FOR SAR 21
9.5 POWER DRIFT 21

10 AREA SCAN BASED 1-G SAR 22

10.1 REQUIREMENT OF KDB 22
10.2 FAST SAR ALGORITHMS 22

11 CONDUCTED OUTPUT POWER 23

©Copyright. All rights reserved by CTTL.

11.1 MANUFACTURING TOLERANCE 23
11.2 GSM MEASUREMENT RESULT 25
11.3 WCDMA MEASUREMENT RESULT 26
11.4 WI-FI AND BT MEASUREMENT RESULT 26

12 SIMULTANEOUS TX SAR CONSIDERATIONS 28

12.1 INTRODUCTION 28
12.2 TRANSMIT ANTENNA SEPARATION DISTANCES 28
12.3 SAR MEASUREMENT POSITIONS 28
12.4 STANDALONE SAR TEST EXCLUSION CONSIDERATIONS 29

13 EVALUATION OF SIMULTANEOUS 30

14 SAR TEST RESULT 31

14.1 THE EVALUATION OF MULTI-BATTERIES 32
14.2 SAR RESULTS FOR FAST SAR 33
14.2 SAR RESULTS FOR STANDARD PROCEDURE 38

15 SAR MEASUREMENT VARIABILITY 41

16 MEASUREMENT UNCERTAINTY 42

17 MAIN TEST INSTRUMENTS 44

ANNEX A GRAPH RESULTS 45

ANNEX B SYSTEM VERIFICATION RESULTS 65

ANNEX C SAR MEASUREMENT SETUP 76

ANNEX D POSITION OF THE WIRELESS DEVICE IN RELATION TO THE PHANTOM 82

ANNEX E EQUIVALENT MEDIA RECIPES 85

ANNEX F SYSTEM VALIDATION 86

ANNEX G PROBE CALIBRATION CERTIFICATE 88

ANNEX H DIPOLE CALIBRATION CERTIFICATE 110

ANNEX I SPOT CHECK TEST 150

ANNEX J ACCREDITATION CERTIFICATE 163

©Copyright. All rights reserved by CTTL.

1 Test Laboratory

1.1 Testing Location

Company Name:	CTTL(Shouxiang)
Address:	No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District, Beijing, P. R. China100191

1.2 Testing Environment

Temperature:	18°C~25 °C,
Relative humidity:	30%~ 70%
Ground system resistance:	< 0.5 Ω
Ambient noise & Reflection:	< 0.012 W/kg

1.3 Project Data

Project Leader:	Qi Dianyuan
Test Engineer:	Lin Xiaojun
Testing Start Date:	December 13, 2014
Testing End Date:	February 3, 2015

1.4 Signature

Lin Xiaojun

(Prepared this test report)



Qi Dianyuan

(Reviewed this test report)

Xiao Li

Deputy Director of the laboratory

(Approved this test report)

©Copyright. All rights reserved by CTTL.

2 Statement of Compliance

This EUT is a variant product and the report of original sample is No.I14N01488-SAR. According to the client request, we quote the test results of original sample from table 14.2 to 14.25. The results of spot check are presented in the annex I.

The maximum results of Specific Absorption Rate (SAR) found during testing for TCL Communication Ltd. HSUPA/HSDPA/UMTS Triple band/GSM Quad band mobile phone 4009A are as follows:

Table 2.1: Highest Reported SAR (1g)

Exposure Configuration	Technology Band	Highest Reported SAR 1g (W/Kg)	Equipment Class
Head (Separation Distance 0mm)	GSM 850	0.90	PCE
	PCS 1900	0.62	
	UMTS FDD 5	0.92	
	UMTS FDD 2	0.99	
	WLAN 2.4 GHz	0.41	DTS
Body-worn (Separation Distance 10mm)	GSM 850	1.09	PCE
	PCS 1900	0.67	
	UMTS FDD 5	1.23	
	UMTS FDD 2	**1.27**	
	WLAN 2.4 GHz	0.13	DTS

The SAR values found for the Mobile Phone are below the maximum recommended levels of 1.6 W/Kg as averaged over any 1g tissue according to the ANSI C95.1-1999.

For body worn operation, this device has been tested and meets FCC RF exposure guidelines when used with any accessory that contains no metal and which provides a minimum separation distance of 10 mm between this device and the body of the user. Use of other accessories may not ensure compliance with FCC RF exposure guidelines.

The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output.

The measurement together with the test system set-up is described in annex C of this test report. A detailed description of the equipment under test can be found in chapter 4 of this test report.
The highest reported SAR value is obtained at the case of **(Table 2.1),** and the values are**: 1.27W/kg (1g).**

©Copyright. All rights reserved by CTTL.

Table 2.2: The sum of reported SAR values for main antenna and WiFi

	Position	Main antenna	WiFi	Sum
Highest reported SAR value for Head	Left hand, Touch cheek	0.90	0.41	**1.31**
	Right hand, Touch cheek	0.99	0.20	**1.09**
Highest reported SAR value for Body	Rear	1.27	0.13	**1.40**

Table 2.3: The sum of reported SAR values for main antenna and Bluetooth

	Position	Main antenna	BT*	Sum
Highest reported SAR value for Head	Right hand, Touch cheek	0.99	0.33	**1.32**
Highest reported SAR value for Body	Rear	1.27	0.17	**1.44**

BT* - Estimated SAR for Bluetooth (see the table 13.3)

According to the above tables, the highest sum of reported SAR values is **1.44 W/kg (1g)**. The detail for simultaneous transmission consideration is described in chapter 13.

©Copyright. All rights reserved by CTTL.

3 Client Information

3.1 Applicant Information

Company Name:	TCL Communication Ltd.
Address /Post:	5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203
City:	Shanghai
Postal Code:	201203
Country:	P.R.China
Contact:	Gong Zhizhou
Email:	zhizhou.gong@tcl.com
Telephone:	0086-21-61460890
Fax:	0086-21-61460602

3.2 Manufacturer Information

Company Name:	TCL Communication Ltd.
Address /Post:	5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203
City:	Shanghai
Postal Code:	201203
Country:	P.R.China
Contact:	Gong Zhizhou
Email:	zhizhou.gong@tcl.com
Telephone:	0086-21-61460890
Fax:	0086-21-61460602

©Copyright. All rights reserved by CTTL.

4 Equipment Under Test (EUT) and Ancillary Equipment (AE)

4.1 About EUT

Description:	HSUPA/HSDPA/UMTS Triple band/GSM Quad band mobile phone
Model Name:	4009A
Operating mode(s):	GSM 850/900/1800/1900, WCDMA 850/1900/2100, BT, Wi-Fi
Tested Tx Frequency:	825 – 848.8 MHz (GSM 850)
	1850.2 – 1910 MHz (GSM 1900)
	826.4–846.6 MHz (WCDMA850 Band V)
	1852.4–1907.6 MHz (WCDMA1900 Band II)
	2412 – 2462 MHz (Wi-Fi 2.4G)
GPRS&EGPRS Multislot Class:	12
GPRS capability Class:	B
WCDMA Category:	HSDPA: 14
	HSUPA: 6
	HSPA+: 14
Release Version:	GSM: Rel5
	GPRS: Rel5
	UMTS: R7
Test device Production information:	Production unit
Device type:	Portable device
Antenna type:	Integrated antenna
Accessories/Body-worn configurations:	Headset
Hotspot mode:	Support simultaneous transmission of hotspot and voice(or data)
Form factor:	110.5 mm × 59.9 mm

4.2 Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	014282000000297	PIO	v4B2A
EUT2	014282000001139	PIO	v4B2A

*EUT ID: is used to identify the test sample in the lab internally.

Note: It is performed to test SAR with the EUT1 and conducted power with the EUT 2

Note2: The sample information of spot check is presented in the annex I.

©Copyright. All rights reserved by CTTL.

4.3 Internal Identification of AE used during the test

AE ID*	Description	Model	SN	Manufacturer
AE1	Battery	CAB31P0000C1	/	BYD
AE2	Battery	CAB31P0000CB	/	OCEANSUN
AE3	Battery	CAB1150000C1	/	BYD
AE4	Battery	CAB1150001CB	/	OCEANSUN
AE5	Battery	CAB1300015C2	/	SCUD
AE6	Headset	CCB3160A11C4	/	Meihao
AE7	Headset	CCB3160A11C6	/	Shenghua
AE8	Headset	CCB3160A15C4	/	Meihao
AE9	Headset	CCB3160A15C6	/	Shenghua

*AE ID: is used to identify the test sample in the lab internally.

Note:

AE6 and AE8 are the same, so they can use the same results.

AE7 and AE9 are the same, so they can use the same results.

5 TEST METHODOLOGY

5.1 Applicable Limit Regulations

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

It specifies the maximum exposure limit of **1.6 W/kg** as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

5.2 Applicable Measurement Standards

IEEE 1528–2013: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Experimental Techniques.

KDB447498 D01: General RF Exposure Guidance v05r02: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

KDB648474 D04 Handset SAR v01r02: SAR Evaluation Considerations for Wireless Handsets.

KDB941225 D06 Hotspot Mode SAR v01r01: SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities

KDB248227 D01 SAR meas for 802 11 a b g v01r02 : SAR measurement procedures for 802.112abg transmitters.

KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r03: SAR Measurement Requirements for 100 MHz to 6 GHz.

KDB 865664 D02 RF Exposure Reporting v01r01: RF Exposure Compliance Reporting and Documentation Considerations

©Copyright. All rights reserved by CTTL.

6 Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt}\left(\frac{dW}{dm}\right) = \frac{d}{dt}\left(\frac{dW}{\rho dv}\right)$$

SAR is expressed in units of Watts per kilogram (W/kg)
SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = c\left(\frac{\delta T}{\delta t}\right)$$

Where: C is the specific head capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

©Copyright. All rights reserved by CTTL.

7 Tissue Simulating Liquids

7.1 Targets for tissue simulating liquid

Table 7.1: Targets for tissue simulating liquid

Frequency (MHz)	Liquid Type	Conductivity (σ)	± 5% Range	Permittivity (ε)	± 5% Range
835	Head	0.90	0.86～0.95	41.5	39.4～43.6
835	Body	0.97	0.92～1.02	55.2	52.4～58.0
1900	Head	1.40	1.33～1.47	40.0	38.0～42.0
1900	Body	1.52	1.44～1.60	53.3	50.6～56.0
2450	Head	1.80	1.71～1.89	39.2	37.2～41.2
2450	Body	1.95	1.85～2.05	52.7	50.1～55.3

7.2 Dielectric Performance

Table 7.2: Dielectric Performance of Tissue Simulating Liquid

Measurement Date (yyyy-mm-dd)	Type	Frequency	Permittivity ε	Drift (%)	Conductivity σ (S/m)	Drift (%)
2014-12-13	Head	835 MHz	41.87	0.89%	0.94	4.44%
2014-12-13	Body	835 MHz	55.56	0.65%	0.97	0.00%
2014-12-14	Head	1900 MHz	41.06	2.65%	1.45	3.57%
2014-12-14	Body	1900 MHz	52.59	-1.33%	1.51	-0.66%
2014-12-19	Head	2450 MHz	39.38	0.46%	1.78	-1.11%
2014-12-17	Body	2450 MHz	52.59	-0.21%	1.95	0.00%
2015-02-02	Head	835 MHz	41.73	0.55	0.9	0.00
2015-02-02	Body	835 MHz	54.54	-1.20	0.982	1.24
2015-02-03	Head	1900 MHz	40.09	0.23	1.404	0.29
2015-02-03	Body	1900 MHz	54.21	1.71	1.498	-1.45

Note: The liquid temperature is 22.0 ^{o}C

©Copyright. All rights reserved by CTTL.



Picture 7-1: Liquid depth in the Head Phantom (835 MHz)



Picture 7-2: Liquid depth in the Flat Phantom (835 MHz)

©Copyright. All rights reserved by CTTL.



Picture 7-3: Liquid depth in the Head Phantom (1900 MHz)



Picture 7-4 Liquid depth in the Flat Phantom (1900MHz)

©Copyright. All rights reserved by CTTL.



Picture 7-5 Liquid depth in the Head Phantom (2450MHz)



Picture 7-6 Liquid depth in the Flat Phantom (2450MHz)

©Copyright. All rights reserved by CTTL.

8 System verification

8.1 System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



Picture 8.1 System Setup for System Evaluation



Picture 8.2 Photo of Dipole Setup

©Copyright. All rights reserved by CTTL.

8.2 System Verification

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device.

The system verification results are required that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR. The details are presented in annex B.

Table 8.1: System Verification of Head

Measurement Date (yyyy-mm-dd)	Frequency	Target value (W/kg)		Measured value (W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
2014-12-13	835 MHz	1.6	2.44	1.61	2.43	0.63%	-0.41%
2014-12-14	1900 MHz	5.19	9.86	5.25	9.89	1.16%	0.30%
2014-12-19	2450 MHz	6.14	13.2	6.12	13.1	-0.33%	-0.76%
2015-02-02	835 MHz	1.58	2.43	1.59	2.43	0.63%	0.00
2015-02-03	1900 MHz	5.25	10.1	5.14	9.77	-2.10%	-3.27%

Table 8.2: System Verification of Body

Measurement Date (yyyy-mm-dd)	Frequency	Target value (W/kg)		Measured value (W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
2014-12-13	835 MHz	1.59	2.43	1.58	2.42	-0.63%	-0.41%
2014-12-14	1900 MHz	5.40	10.0	5.43	10.2	0.56%	2.00%
2014-12-17	2450 MHz	6.01	13.0	5.99	12.98	-0.33%	-0.15%
2015-02-02	835 MHz	1.62	2.46	1.55	2.36	-4.32%	-4.07%
2015-02-03	1900 MHz	5.35	10.1	5.47	10.3	2.24%	1.98%

©Copyright. All rights reserved by CTTL.

9 Measurement Procedures

9.1 Tests to be performed

In order to determine the highest value of the peak spatial-average SAR of a handset, all device positions, configurations and operational modes shall be tested for each frequency band according to steps 1 to 3 below. A flowchart of the test process is shown in picture 9.1.

Step 1: The tests described in 9.2 shall be performed at the channel that is closest to the centre of the transmit frequency band (f_c) for:

a) all device positions (cheek and tilt, for both left and right sides of the SAM phantom, as described in annex D),
b) all configurations for each device position in a), e.g., antenna extended and retracted, and
c) all operational modes, e.g., analogue and digital, for each device position in a) and configuration in b) in each frequency band.

If more than three frequencies need to be tested according to 11.1 (i.e., N_c > 3), then all frequencies, configurations and modes shall be tested for all of the above test conditions.

Step 2: For the condition providing highest peak spatial-average SAR determined in Step 1, perform all tests described in 9.2 at all other test frequencies, i.e., lowest and highest frequencies. In addition, for all other conditions (device position, configuration and operational mode) where the peak spatial-average SAR value determined in Step 1 is within 3 dB of the applicable SAR limit, it is recommended that all other test frequencies shall be tested as well.

Step 3: Examine all data to determine the highest value of the peak spatial-average SAR found in Steps 1 to 2.

©Copyright. All rights reserved by CTTL.



Picture 9.1 Block diagram of the tests to be performed

9.2 General Measurement Procedure

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements and fully documented in SAR reports to qualify for TCB approval. Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2003. The results should be documented as part of the system validation records and may be requested to support test results

©Copyright. All rights reserved by CTTL.

when all the measurement parameters in the following table are not satisfied.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	½·δ·ln(2) ± 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: Δx_{Area}, Δy_{Area}			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom}, Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the *reported* SAR from the area scan based *1-g SAR estimation* procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

9.3 WCDMA Measurement Procedures for SAR

The following procedures are applicable to WCDMA handsets operating under 3GPP Release99, Release 5 and Release 6. The default test configuration is to measure SAR with an established radio link between the DUT and a communication test set using a 12.2kbps RMC (reference measurement channel) configured in Test Loop Mode 1. SAR is selectively confirmed for other physical channel configurations (DPCCH & $DPDCH_n$), HSDPA and HSPA (HSUPA/HSDPA) modes according to output power, exposure conditions and device operating capabilities. Both uplink and downlink should be configured with the same RMC or AMR, when required. SAR for Release 5 HSDPA and Release 6 HSPA are measured using the applicable FRC (fixed reference channel) and E-DCH reference channel configurations. Maximum output power is verified according to applicable versions of 3GPP TS 34.121 and SAR must be measured according to these maximum output conditions. When Maximum Power Reduction (MPR) is not implemented according to Cubic Metric (CM) requirements for Release 6 HSPA, the following procedures do not apply.

©Copyright. All rights reserved by CTTL.

For Release 5 HSDPA Data Devices:

Sub-test	β_c	β_d	β_d （SF）	β_c / β_d	β_{hs}	CM/dB
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15	15/15	64	12/15	24/25	1.0
3	15/15	8/15	64	15/8	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

For Release 6 HSPA Data Devices

Sub-test	β_c	β_d	β_d （SF）	β_c / β_d	β_{hs}	β_{ec}	β_{ed}	β_{ed} （SF）	β_{ed} （codes）	CM (dB)	MPR (dB)	AG Index	E-TFCI
1	11/15	15/15	64	11/15	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	12/15	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1}:47/15 β_{ed2}:47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	4/15	56/75	4	1	3.0	2.0	17	71
5	15/15	15/15	64	15/15	24/15	30/15	134/15	4	1	1.0	0.0	21	81

9.4 Bluetooth & Wi-Fi Measurement Procedures for SAR

Normal network operating configurations are not suitable for measuring the SAR of 802.11 transmitters in general. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure that the results are consistent and reliable.

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in a test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

9.5 Power Drift

To control the output power stability during the SAR test, DASY4 system calculates the power drift by measuring the E-field at the same location at the beginning and at the end of the measurement for each test position. These drift values can be found in Table 14.2 to Table 14.25 labeled as: (Power Drift [dB]). This ensures that the power drift during one measurement is within 5%.

©Copyright. All rights reserved by CTTL.

10 Area Scan Based 1-g SAR

10.1 Requirement of KDB

According to the KDB447498 D01 v05, when the implementation is based the specific polynomial fit algorithm as presented at the 29th Bioelectromagnetics Society meeting (2007) and the estimated 1-g SAR is ≤ 1.2 W/kg, a zoom scan measurement is not required provided it is also not needed for any other purpose; for example, if the peak SAR location required for simultaneous transmission SAR test exclusion can be determined accurately by the SAR system or manually to discriminate between distinctive peaks and scattered noisy SAR distributions from area scans.

There must not be any warning or alert messages due to various measurement concerns identified by the SAR system; for example, noise in measurements, peaks too close to scan boundary, peaks are too sharp, spatial resolution and uncertainty issues etc. The SAR system verification must also demonstrate that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR (See Annex B). When all the SAR results for each exposure condition in a frequency band and wireless mode are based on estimated 1-g SAR, the 1-g SAR for the highest SAR configuration must be determined by a zoom scan.

10.2 Fast SAR Algorithms

The approach is based on the area scan measurement applying a frequency dependent attenuation parameter. This attenuation parameter was empirically determined by analyzing a large number of phones. The MOTOROLA FAST SAR was developed and validated by the MOTOROLA Research Group in Ft. Lauderdale.

In the initial study, an approximation algorithm based on Linear fit was developed. The accuracy of the algorithm has been demonstrated across a broad frequency range (136-2450 MHz) and for both 1- and 10-g averaged SAR using a sample of 264 SAR measurements from 55 wireless handsets. For the sample size studied, the root-mean-squared errors of the algorithm are 1.2% and 5.8% for 1- and 10-g averaged SAR, respectively. The paper describing the algorithm in detail is expected to be published in August 2004 within the Special Issue of Transactions on MTT.

In the second step, the same research group optimized the fitting algorithm to an Polynomial fit whereby the frequency validity was extended to cover the range 30-6000MHz. Details of this study can be found in the BEMS 2007 Proceedings.

Both algorithms are implemented in DASY software.

©Copyright. All rights reserved by CTTL.

11 Conducted Output Power

11.1 Manufacturing tolerance

Table 11.1: GSM Speech

GSM 850			
Channel	Channel 251	Channel 190	Channel 128
Target (dBm)	32.3	32.3	32.3
Tolerance ±(dB)	1	1	1
GSM 1900			
Channel	Channel 810	Channel 661	Channel 512
Target (dBm)	29.3	29.3	29.3
Tolerance ±(dB)	1	1	1

Table 11.2: GPRS and EGPRS

GSM 850 GPRS&EGPRS (GMSK)				
Channel		**251**	**190**	**128**
1 Txslot	Target (dBm)	32.3	32.3	32.3
	Tolerance ±(dB)	1	1	1
2 Txslots	Target (dBm)	29.5	29.5	29.5
	Tolerance ±(dB)	1	1	1
3Txslots	Target (dBm)	27.5	27.5	27.5
	Tolerance ±(dB)	1	1	1
4 Txslots	Target (dBm)	26.5	26.5	26.5
	Tolerance ±(dB)	1	1	1
GSM 1900 GPRS&EGPRS (GMSK)				
Channel		**810**	**661**	**512**
1 Txslot	Target (dBm)	29.3	29.3	29.3
	Tolerance ±(dB)	1	1	1
2 Txslots	Target (dBm)	27	27	27
	Tolerance ±(dB)	1	1	1
3Txslots	Target (dBm)	25	25	25
	Tolerance ±(dB)	1	1	1
4 Txslots	Target (dBm)	24	24	24
	Tolerance ±(dB)	1	1	1

©Copyright. All rights reserved by CTTL.

Table 11.3: WCDMA

UMTS Band V		Conducted Power (dBm)		
		Channel 4233	Channel 4183	Channel 4132
CS	Target (dBm)	23	23	23
	Tolerance ±(dB)	1	1	1
HSUPA sub-test 1-2	Target (dBm)	20	20	20
	Tolerance ±(dB)	1	1	1
HSUPA sub-test 3	Target (dBm)	20.5	20.5	20.5
	Tolerance ±(dB)	1	1	1
HSUPA sub-test 4	Target (dBm)	20	20	20
	Tolerance ±(dB)	1	1	1
HSUPA sub-test 5	Target (dBm)	21.5	21.5	21.5
	Tolerance ±(dB)	1	1	1
UMTS Band II		Conducted Power (dBm)		
		Channel 9538	Channel 9400	Channel 9262
CS	Target (dBm)	23	23	23
	Tolerance ±(dB)	1	1	1
HSUPA sub-test 1-2	Target (dBm)	20	20	20
	Tolerance ±(dB)	1	1	1
HSUPA sub-test 3	Target (dBm)	20.5	20.5	20.5
	Tolerance ±(dB)	1	1	1
HSUPA sub-test 4	Target (dBm)	19.5	19.5	19.5
	Tolerance ±(dB)	1	1	1
HSUPA sub-test 5	Target (dBm)	21.5	21.5	21.5
	Tolerance ±(dB)	1	1	1

Table 11.4: Bluetooth

Mode	Target (dBm)	Tolerance ±(dB)
GFSK	8	1
EDR2M-4_DQPSK	7.5	1
EDR3M-8DPSK	7.5	1

Table 11.5: WiFi

Mode	Channel/Data rate	Target (dBm)	Tolerance ±(dB)
802.11 b (2.4GHz)	/	17.5	1
802.11 g (2.4GHz)	6-18Mbps	15	1
	24-36Mbps	14	1
	48-54Mbps	13	1
802.11 n (2.4GHz HT20)	MCS0-2	13	1
	MCS3-5	12.5	1
	MCS6-7	11.5	1
802.11 n (2.4GHz HT40)	MCS0-2	10.5	1
	MCS3-5	9	1
	MCS6-7	8	1

©Copyright. All rights reserved by CTTL.

11.2 GSM Measurement result

During the process of testing, the EUT was controlled via Agilent Digital Radio Communication tester (E5515C) to ensure the maximum power transmission and proper modulation. This result contains conducted output power for the EUT. In all cases, the measured peak output power should be greater and within 5% than EMI measurement.

Table 11.6: The conducted power measurement results for GSM850/1900

GSM 850MHz	Conducted Power (dBm)		
	Channel 251(848.8MHz)	Channel 190(836.6MHz)	Channel 128(824.2MHz)
	32.73	32.71	32.68
GSM 1900MHz	Conducted Power (dBm)		
	Channel 810(1909.8MHz)	Channel 661(1880MHz)	Channel 512(1850.2MHz)
	29.74	29.73	29.69

Table 11.7: The conducted power measurement results for GPRS and EGPRS

GSM 850 GPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	**190**	**128**		**251**	**190**	**128**
1 Txslot	32.71	32.69	32.68	-9.03dB	23.68	23.66	23.65
2 Txslots	29.78	29.75	29.72	-6.02dB	23.76	23.73	23.7
3Txslots	27.60	27.61	27.58	-4.26dB	23.34	23.35	23.32
4 Txslots	26.79	26.77	26.75	-3.01dB	**23.78**	**23.76**	**23.74**
PCS1900 GPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	**661**	**512**		**810**	**661**	**512**
1 Txslot	29.70	29.68	29.65	-9.03dB	20.67	20.65	20.62
2 Txslots	27.32	27.30	27.24	-6.02dB	21.30	21.28	21.22
3Txslots	25.33	25.32	25.23	-4.26dB	21.07	21.06	20.97
4 Txslots	24.32	24.31	24.25	-3.01dB	**21.31**	**21.30**	**21.24**

NOTES:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

According to the conducted power as above, the body measurements are performed with 4Txslots for GSM 850 and GSM 1900.

©Copyright. All rights reserved by CTTL.

11.3 WCDMA Measurement result

Table 11.8: The conducted Power for WCDMA850/1900

UMTS Band II		Conducted Power (dBm)		
		Ch 9888 (1977.6MHz)	**Ch 9750 (1950MHz)**	**Ch 9612 (1922.4MHz)**
RMC	12.2kbps RMC	23.39	23.27	23.31
HSUPA	Sub - Test 1	19.95	19.92	19.95
	Sub - Test 2	19.94	19.91	19.97
	Sub - Test 3	20.89	20.89	20.97
	Sub - Test 4	19.42	19.33	19.49
	Sub - Test 5	21.83	21.80	21.91
UMTS Band V		**Conducted Power (dBm)**		
		Ch 2863 (912.6MHz)	**Ch 2788 (897.4MHz)**	**Ch 2712 (882.4MHz)**
RMC	12.2kbps RMC	22.95	22.88	22.95
HSUPA	Sub Test - 1	20.11	20.10	20.25
	Sub Test - 2	20.17	20.10	20.26
	Sub Test - 3	21.12	21.07	21.26
	Sub Test - 4	19.59	19.54	19.8
	Sub Test - 5	22.14	22.04	22.24

11.4 Wi-Fi and BT Measurement result

The output power of BT antenna is as following:

Mode	Conducted Power (dBm)		
	Channel 0 (2402MHz)	Channel 39 (2441MHz)	Channel 78 (2480MHz)
GFSK	8.23	8.75	8.24
EDR2M-4_DQPSK	7.68	8.18	8.14
EDR3M-8DPSK	7.79	8.30	8.29
BLE	0.1	0.52	0.26

The average conducted power for Wi-Fi is as following:

802.11b（dBm）

Channel\data rate	1Mbps	2Mbps	5.5Mbps	11Mbps
1(2412MHz)	17.92	/	/	/
6(2437MHz)	17.99	/	/	/
11(2462MHz)	18.16	18.09	18.07	17.82

802.11g（dBm）

Channel\data rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
1(2412MHz)	14.66	/	/	/	/	/	/	/
6(2437MHz)	14.77	/	/	/	/	/	/	/
11(2462MHz)	15.06	14.95	14.81	14.28	14.03	13.61	13.04	12.87

©Copyright. All rights reserved by CTTL.

802.11n（dBm）- HT20 (2.4G)

Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
1(2412MHz)	13.67	/	/	/	/	/	/	/
6(2437MHz)	13.83	13.56	13.33	13.09	12.31	11.96	11.81	11.65
11(2462MHz)	13.78	/	/	/	/	/	/	/

802.11n（dBm）- HT40 (2.4G)

Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
3(2422MHz)	11.18	/	/	/	/	/	/	/
6(2437MHz)	11.29	10.81	10.13	9.68	9.15	8.69	8.37	8.18
9(2452MHz)	11.27	/	/	/	/	/	/	/

©Copyright. All rights reserved by CTTL.

12 Simultaneous TX SAR Considerations

12.1 Introduction

The following procedures adopted from “FCC SAR Considerations for Cell Phones with Multiple Transmitters” are applicable to handsets with built-in unlicensed transmitters such as 802.11 a/b/g and Bluetooth devices which may simultaneously transmit with the licensed transmitter.
For this device, the BT and Wi-Fi can transmit simultaneous with other transmitters.

12.2 Transmit Antenna Separation Distances



Picture 12.1 Antenna Locations

12.3 SAR Measurement Positions

According to the KDB941225 D06 Hot Spot SAR v01, the edges with less than 2.5 cm distance to the antennas need to be tested for SAR.

SAR measurement positions						
Mode	Front	Rear	Left edge	Right edge	Top edge	Bottom edge
Main antenna	Yes	Yes	Yes	Yes	No	Yes
WLAN	Yes	Yes	No	Yes	Yes	No

©Copyright. All rights reserved by CTTL.

12.4 Standalone SAR Test Exclusion Considerations

Standalone 1-g head or body SAR evaluation by measurement or numerical simulation is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied. The 1-g SAR test exclusion threshold for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] · [√f(GHz)] ≤ 3.0 for 1-g SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Table 12.1: Standalone SAR test exclusion considerations

Band/Mode	F(GHz)	Position	SAR test exclusion threshold (mW)	RF output power		SAR test exclusion
				dBm	mW	
Bluetooth	2.441	Head	9.60	8.75	7.50	Yes
		Body	19.20	8.75	7.50	Yes
2.4GHz WLAN 802.11 b	2.45	Head	9.58	18.16	65.46	No
		Body	19.17	18.16	65.46	No

©Copyright. All rights reserved by CTTL.

13 Evaluation of Simultaneous

Table 13.1: The sum of reported SAR values for main antenna and WiFi

	Position	Main antenna	WiFi	Sum
Highest reported SAR value for Head	Left hand, Touch cheek	0.90	0.41	**1.31**
	Right hand, Touch cheek	0.99	0.20	**1.09**
Highest reported SAR value for Body	Rear	1.27	0.13	**1.40**

Table 13.2: The sum of reported SAR values for main antenna and Bluetooth

	Position	Main antenna	BT*	Sum
Highest reported SAR value for Head	Right hand, Touch cheek	0.99	0.33	**1.32**
Highest reported SAR value for Body	Rear	1.27	0.17	**1.44**

BT* - Estimated SAR for Bluetooth (see the table 13.3)

Table 13.3: Estimated SAR for Bluetooth

Position	F (GHz)	Distance (mm)	Upper limit of power *		Estimated$_{1g}$ (W/kg)
			dBm	mW	
Head	2.441	5	9	7.94	0.33
Body	2.441	10	9	7.94	0.17

* - Maximum possible output power declared by manufacturer

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:
(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[√f(GHz)/x] W/kg for test separation distances ≤ 50 mm;
where x = 7.5 for 1-g SAR.
When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

Conclusion:
According to the above tables, the sum of reported SAR values is < 1.6W/kg. So the simultaneous transmission SAR with volume scans is not required.

©Copyright. All rights reserved by CTTL.

14 SAR Test Result

It is determined by user manual for the distance between the EUT and the phantom bottom.
The distance is 10mm and just applied to the condition of body worn accessory.
It is performed for all SAR measurements with area scan based 1-g SAR estimation (Fast SAR). A zoom scan measurement is added when the estimated 1-g SAR is the highest measured SAR in each exposure configuration, wireless mode and frequency band combination or > 1.2W/kg.
The calculated SAR is obtained by the following formula:

$$\text{Reported SAR} = \text{Measured SAR} \times 10^{(P_{Target} - P_{Measured})/10}$$

Where P_{Target} is the power of manufacturing upper limit;
$P_{Measured}$ is the measured power in chapter 11.

Table 14.1: Duty Cycle

Mode	Duty Cycle
Speech for GSM850/1900	1:8.3
GPRS&EGPRS for GSM850	1:2
GPRS&EGPRS for GSM1900	1:2
WCDMA850/1900 &WiFi	1:1

©Copyright. All rights reserved by CTTL.

14.1 The evaluation of multi-batteries

We'll perform the head measurement in all bands with the primary battery depending on the evaluation of multi-batteries and retest on highest value point with other batteries. Then, repeat the measurement in the Body test.

Table 14.2: The evaluation of multi-batteries for Head Test

Frequency		Mode/Band	Side	Test Position	Battery Type	SAR(1g)	Power
MHz	Ch.					(W/kg)	Drift(dB)
1907.6	9538	WCDMA1900	Right	Touch	CAB31P0000C1	0.864	-0.02
1907.6	9538	WCDMA1900	Right	Touch	CAB31P0000CB	0.652	0.07
1907.6	9538	WCDMA1900	Right	Touch	CAB1150000C1	0.788	-0.05
1907.6	9538	WCDMA1900	Right	Touch	CAB1150001CB	0.702	0.10
1907.6	9538	WCDMA1900	Right	Touch	CAB1300015C2	0.811	0.16

Note: According to the values in the above table, the battery, CAB31P0000C1, is the primary battery. We'll perform the head measurement with this battery and retest on highest value point with others.

Table 14.3: The evaluation of multi-batteries for Body Test

Frequency		Mode/Band	Test Position	Spacing (mm)	Battery Type	SAR(1g)	Power
MHz	Ch.					(W/kg)	Drift(dB)
848.8	251	WCDMA1900	Rear	10	CAB31P0000C1	1.100	0.05
848.8	251	WCDMA1900	Rear	10	CAB31P0000CB	0.931	0.15
848.8	251	WCDMA1900	Rear	10	CAB1150000C1	0.970	0.16
848.8	251	WCDMA1900	Rear	10	CAB1150001CB	0.971	0.15
848.8	251	WCDMA1900	Rear	10	CAB1300015C2	0.890	0.17

Note: According to the values in the above table, the battery, CAB31P0000C1, is the primary battery. We'll perform the Body measurement with this battery and retest on highest value point with others.

©Copyright. All rights reserved by CTTL.

14.2 SAR results for Fast SAR

Table 14.4: SAR Values (GSM 850 MHz Band - Head) – CAB31P0000C1

Ambient Temperature: 22.5 °C Liquid Temperature: 22.0 °C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
848.8	251	Left	Touch	Fig.1	32.73	33.3	0.576	**0.66**	0.793	**0.90**	0.11
836.6	190	Left	Touch	/	32.71	33.3	0.433	**0.50**	0.636	**0.73**	0.18
824.2	128	Left	Touch	/	32.68	33.3	0.329	**0.38**	0.482	**0.56**	-0.01
848.8	251	Left	Tilt	/	32.73	33.3	0.250	**0.29**	0.362	**0.41**	0.01
836.6	190	Left	Tilt	/	32.71	33.3	0.194	**0.22**	0.281	**0.32**	0.08
824.2	128	Left	Tilt	/	32.68	33.3	0.146	**0.17**	0.210	**0.24**	0.02
848.8	251	Right	Touch	/	32.73	33.3	0.535	**0.61**	0.790	**0.90**	0.09
836.6	190	Right	Touch	/	32.71	33.3	0.420	**0.48**	0.618	**0.71**	-0.07
824.2	128	Right	Touch	/	32.68	33.3	0.322	**0.37**	0.474	**0.55**	0.04
848.8	251	Right	Tilt	/	32.73	33.3	0.313	**0.36**	0.454	**0.52**	-0.15
836.6	190	Right	Tilt	/	32.71	33.3	0.260	**0.30**	0.376	**0.43**	0.03
824.2	128	Right	Tilt	/	32.68	33.3	0.210	**0.24**	0.302	**0.35**	0.03

Table 14.5: SAR Values (GSM 850 MHz Band - Body) – CAB31P0000C1

Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
836.6	190	Front	/	26.77	27.5	0.305	**0.36**	0.429	**0.51**	-0.04
848.8	251	Rear	Fig.2	26.79	27.5	0.639	**0.75**	0.924	**1.09**	0.18
836.6	190	Rear	/	26.77	27.5	0.489	**0.58**	0.710	**0.84**	-0.14
824.2	128	Rear	/	26.75	27.5	0.387	**0.46**	0.571	**0.68**	0.04
836.6	190	Left	/	26.77	27.5	0.230	**0.27**	0.337	**0.40**	-0.06
836.6	190	Right	/	26.77	27.5	0.241	**0.29**	0.364	**0.43**	0.16
836.6	190	Bottom	/	26.77	27.5	0.068	**0.08**	0.105	**0.12**	0.07
848.8	251	Rear EGPRS	/	26.29	27.5	0.534	**0.71**	0.776	**1.03**	0.13
848.8	251	RearHeadset1	/	32.73	33.3	0.570	**0.65**	0.841	**0.96**	0.10
848.8	251	RearHeadset2	/	32.73	33.3	0.544	**0.62**	0.782	**0.89**	0.05

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: Headset1 is CCB3160A11C4, Headset2 is CCB3160A11C6.

©Copyright. All rights reserved by CTTL.

Table 14.6: SAR Values (GSM 1900 MHz Band - Head) – CAB31P0000C1

Ambient Temperature: 22.4 °C Liquid Temperature: 21.9 °C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1909.8	810	Left	Touch	/	29.74	30.3	0.189	**0.22**	0.325	**0.37**	0.00
1880	661	Left	Touch	/	29.73	30.3	0.160	**0.18**	0.268	**0.31**	0.06
1850.2	512	Left	Touch	/	29.69	30.3	0.155	**0.18**	0.256	**0.29**	0.08
1909.8	810	Left	Tilt	/	29.74	30.3	0.095	**0.11**	0.172	**0.20**	-0.01
1880	661	Left	Tilt	/	29.73	30.3	0.079	**0.09**	0.144	**0.16**	0.03
1850.2	512	Left	Tilt	/	29.69	30.3	0.07	**0.08**	0.125	**0.14**	0.03
1909.8	810	Right	Touch	Fig.3	29.74	30.3	0.298	**0.34**	0.543	**0.62**	0.18
1880	661	Right	Touch	/	29.73	30.3	0.238	**0.27**	0.405	**0.46**	-0.05
1850.2	512	Right	Touch	/	29.69	30.3	0.223	**0.26**	0.377	**0.43**	0.07
1909.8	810	Right	Tilt	/	29.74	30.3	0.100	**0.11**	0.174	**0.20**	0.14
1880	661	Right	Tilt	/	29.73	30.3	0.082	**0.09**	0.135	**0.15**	-0.02
1850.2	512	Right	Tilt	/	29.69	30.3	0.076	**0.09**	0.125	**0.14**	0.03

Table 14.7: SAR Values (GSM 1900 MHz Band - Body) – CAB31P0000C1

Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1880	661	Front	/	24.31	25	0.221	**0.26**	0.363	**0.43**	0.02
1909.8	810	Rear	Fig.4	24.32	25	0.331	**0.39**	0.572	**0.67**	0.03
1880	661	Rear	/	24.31	25	0.314	**0.37**	0.561	**0.66**	0.11
1850.2	512	Rear	/	24.25	25	0.298	**0.35**	0.528	**0.63**	-0.00
1880	661	Left	/	24.31	25	0.064	**0.08**	0.109	**0.13**	0.12
1880	661	Right	/	24.31	25	0.052	**0.06**	0.091	**0.11**	0.15
1880	661	Bottom	/	24.31	25	0.168	**0.20**	0.294	**0.34**	0.18
1909.8	810	RearEGPRS	/	24.32	25	0.290	**0.34**	0.509	**0.60**	0.12
1909.8	810	RearHeadset1	/	29.74	30.3	0.310	**0.35**	0.568	**0.65**	0.19
1909.8	810	RearHeadset2	/	29.74	30.3	0.288	**0.33**	0.527	**0.60**	0.14

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: Headset1 is CCB3160A11C4, Headset2 is CCB3160A11C6.

©Copyright. All rights reserved by CTTL.

Table 14.8: SAR Values (WCDMA 850 MHz Band - Head) – CAB31P0000C1

Ambient Temperature: 22.5 °C Liquid Temperature: 22.0 °C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
846.6	4233	Left	Touch	Fig.5	22.95	24	0.534	**0.68**	0.720	**0.92**	-0.04
836.4	4182	Left	Touch	/	22.88	24	0.471	**0.61**	0.687	**0.89**	0.02
826.4	4132	Left	Touch	/	22.95	24	0.431	**0.55**	0.629	**0.80**	0.04
846.6	4233	Left	Tilt	/	22.95	24	0.244	**0.31**	0.354	**0.45**	0.09
836.4	4182	Left	Tilt	/	22.88	24	0.216	**0.28**	0.313	**0.41**	0.09
826.4	4132	Left	Tilt	/	22.95	24	0.200	**0.26**	0.290	**0.37**	0.06
846.6	4233	Right	Touch	/	22.95	24	0.490	**0.62**	0.709	**0.90**	0.09
836.4	4182	Right	Touch	/	22.88	24	0.449	**0.58**	0.649	**0.84**	0.19
826.4	4132	Right	Touch	/	22.95	24	0.420	**0.54**	0.606	**0.77**	0.16
846.6	4233	Right	Tilt	/	22.95	24	0.271	**0.35**	0.393	**0.50**	0.04
836.4	4182	Right	Tilt	/	22.88	24	0.246	**0.32**	0.356	**0.46**	0.05
826.4	4132	Right	Tilt	/	22.95	24	0.226	**0.29**	0.326	**0.42**	0.07

Table 14.9: SAR Values (WCDMA 850 MHz Band - Body) – CAB31P0000C1

Ambient Temperature: 22.5 °C Liquid Temperature: 22.0 °C										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
836.4	4182	Front	/	22.88	24	0.399	**0.52**	0.576	**0.75**	0.11
846.6	4233	Rear	Fig.6	22.95	24	0.697	**0.89**	0.967	**1.23**	0.10
836.4	4182	Rear	/	22.88	24	0.619	**0.80**	0.894	**1.16**	0.04
826.4	4132	Rear	/	22.95	24	0.600	**0.76**	0.866	**1.10**	-0.00
836.4	4182	Left	/	22.88	24	0.365	**0.47**	0.537	**0.70**	0.15
836.4	4182	Right	/	22.88	24	0.301	**0.39**	0.445	**0.58**	0.10
836.4	4182	Bottom	/	22.88	24	0.062	**0.08**	0.097	**0.13**	0.12
846.6	4233	RearHeadset1	/	22.95	24	0.540	**0.69**	0.778	**0.99**	0.08
846.6	4233	RearHeadset2	/	22.95	24	0.537	**0.68**	0.743	**0.95**	0.09

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: Headset1 is CCB3160A11C4, Headset2 is CCB3160A11C6.

©Copyright. All rights reserved by CTTL.

Table 14.10: SAR Values (WCDMA 1900 MHz Band - Head) – CAB31P0000C1

Ambient Temperature: 22.4 °C Liquid Temperature: 21.9 °C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1907.6	9538	Left	Touch	/	23.39	24	0.429	**0.49**	0.760	**0.87**	-0.05
1880	9400	Left	Touch	/	23.27	24	0.412	**0.49**	0.722	**0.85**	0.12
1852.4	9262	Left	Touch	/	23.31	24	0.388	**0.45**	0.673	**0.79**	0.03
1907.6	9538	Left	Tilt	/	23.39	24	0.231	**0.27**	0.424	**0.49**	0.01
1880	9400	Left	Tilt	/	23.27	24	0.209	**0.25**	0.382	**0.45**	0.05
1852.4	9262	Left	Tilt	/	23.31	24	0.189	**0.22**	0.341	**0.40**	0.06
1907.6	9538	Right	Touch	Fig.7	23.39	24	0.489	**0.56**	0.864	**0.99**	-0.02
1880	9400	Right	Touch	/	23.27	24	0.437	**0.52**	0.803	**0.95**	0.19
1852.4	9262	Right	Touch	/	23.31	24	0.424	**0.50**	0.783	**0.92**	0.04
1907.6	9538	Right	Tilt	/	23.39	24	0.151	**0.17**	0.259	**0.30**	0.13
1880	9400	Right	Tilt	/	23.27	24	0.144	**0.17**	0.246	**0.29**	0.00
1852.4	9262	Right	Tilt	/	23.31	24	0.128	**0.15**	0.221	**0.26**	0.07

Table 14.11: SAR Values (WCDMA 1900 MHz Band - Body) – CAB31P0000C1

Ambient Temperature: 22.4 °C Liquid Temperature: 21.9 °C										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1880	9400	Front	/	23.27	24	0.289	**0.34**	0.495	**0.59**	-0.11
1907.6	9538	Rear	Fig.8	23.39	24	0.645	**0.74**	1.100	**1.27**	0.05
1880	9400	Rear	/	23.27	24	0.541	**0.64**	0.940	**1.11**	-0.01
1852.4	9262	Rear	/	23.31	24	0.496	**0.58**	0.862	**1.01**	0.08
1880	9400	Left	/	23.27	24	0.174	**0.21**	0.305	**0.36**	0.12
1880	9400	Right	/	23.27	24	0.136	**0.16**	0.223	**0.26**	0.16
1880	9400	Bottom	/	23.27	24	0.290	**0.34**	0.503	**0.60**	0.17
1907.6	9538	RearHeadset1	/	23.39	24	0.488	**0.56**	0.847	**0.97**	0.09
1907.6	9538	RearHeadset2	/	23.39	24	0.492	**0.57**	0.856	**0.99**	0.15

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: Headset1 is CCB3160A11C4, Headset2 is CCB3160A11C6.

©Copyright. All rights reserved by CTTL.

Table 14.12: SAR Values (Wi-Fi 802.11b - Head) – CAB31P0000C1

Ambient Temperature: 22.6 °C Liquid Temperature: 22.1 °C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
2462	11	Left	Touch	/	17.57	18.5	0.147	**0.18**	0.323	**0.40**	0.17
2437	6	Left	Touch	/	17.57	18.5	0.143	**0.18**	0.314	**0.39**	0.12
2412	1	Left	Touch	Fig.9	17.57	18.5	0.152	**0.19**	0.332	**0.41**	0.19
2437	6	Left	Tilt	/	17.57	18.5	0.084	**0.10**	0.185	**0.23**	0.12
2437	6	Right	Touch	/	17.57	18.5	0.086	**0.11**	0.160	**0.20**	0.10
2437	6	Right	Tilt	/	17.57	18.5	0.060	**0.07**	0.110	**0.14**	0.10

Table 14.13: SAR Values (Wi-Fi 802.11b - Body) – CAB31P0000C1

Ambient Temperature: 22.6 °C Liquid Temperature: 22.1 °C										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
2437	6	Front	/	17.57	18.5	0.036	**0.04**	0.062	**0.08**	0.15
2462	11	Rear	Fig.10	16.21	18.5	0.037	**0.06**	0.078	**0.13**	0.06
2437	6	Rear	/	17.57	18.5	0.035	**0.04**	0.064	**0.08**	0.12
2412	1	Rear	/	16.49	18.5	0.037	**0.06**	0.064	**0.10**	0.09
2437	6	Left	/	17.57	18.5	0.007	**0.01**	0.014	**0.02**	0.17
2437	6	Top	/	17.57	18.5	0.032	**0.04**	0.062	**0.08**	0.10
2437	6	Bottom	/	17.57	18.5	0.024	**0.03**	0.047	**0.06**	0.19

Note1: The distance between the EUT and the phantom bottom is 10mm.

©Copyright. All rights reserved by CTTL.

Table 14.14: SAR Values (WCDMA 1900 MHz Band - Head) for other batteries

Ambient Temperature: 22.4 °C Liquid Temperature: 21.9 °C										
Frequency		Test Position	Battery Type	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1907.6	9538	Right Touch	CAB31P0000CB	23.39	24	0.384	**0.44**	0.652	**0.75**	0.07
1907.6	9538	Right Touch	CAB1150000C1	23.39	24	0.449	**0.52**	0.788	**0.91**	-0.05
1907.6	9538	Right Touch	CAB1150001CB	23.39	24	0.404	**0.46**	0.702	**0.81**	0.10
1907.6	9538	Right Touch	CAB1300015C2	23.39	24	0.46	**0.53**	0.811	**0.93**	0.16

Table 14.15: SAR Values (WCDMA 1900 MHz Band-Body) for other batteries

Ambient Temperature: 22.4 °C Liquid Temperature: 21.9 °C										
Frequency		Test Position	Battery Type	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1907.6	9538	Rear	CAB31P0000CB	23.39	24	0.521	**0.60**	0.931	**1.07**	0.15
1907.6	9538	Rear	CAB1150000C1	23.39	24	0.551	**0.63**	0.970	**1.12**	0.16
1907.6	9538	Rear	CAB1150001CB	23.39	24	0.550	**0.63**	0.971	**1.12**	0.15
1907.6	9538	Rear	CAB1300015C2	23.39	24	0.506	**0.58**	0.890	**1.02**	0.17

14.2 SAR results for Standard procedure

There is zoom scan measurement to be added for the highest measured SAR in each exposure configuration/band.

Table 14.16: SAR Values (GSM 850 MHz Band - Head) – CAB31P0000C1

Ambient Temperature: 22.5 °C Liquid Temperature: 22.0 °C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
848.8	251	Left	Touch	Fig.1	32.73	33.3	0.576	**0.66**	0.793	**0.90**	0.11

Table 14.17: SAR Values (GSM 850 MHz Band - Body) – CAB31P0000C1

Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
848.8	251	Rear	Fig.2	26.79	27.5	0.639	**0.75**	0.924	**1.09**	0.18

Note1: The distance between the EUT and the phantom bottom is 10mm.

©Copyright. All rights reserved by CTTL.

Table 14.18: SAR Values (GSM 1900 MHz Band - Head) – CAB31P0000C1

Ambient Temperature: 22.4 °C Liquid Temperature: 21.9 °C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1909.8	810	Right	Touch	Fig.3	29.74	30.3	0.298	**0.34**	0.543	**0.62**	0.18

Table 14.19: SAR Values (GSM 1900 MHz Band - Body) – CAB31P0000C1

Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1909.8	810	Rear	Fig.4	24.32	25	0.331	**0.39**	0.572	**0.67**	0.03

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.20: SAR Values (WCDMA 850 MHz Band - Head) – CAB31P0000C1

Ambient Temperature: 22.5 °C Liquid Temperature: 22.0 °C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
846.6	4233	Left	Touch	Fig.5	22.95	24	0.534	**0.68**	0.720	**0.92**	-0.04

Table 14.21: SAR Values (WCDMA 850 MHz Band - Body) – CAB31P0000C1

Ambient Temperature: 22.5 °C Liquid Temperature: 22.0 °C										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
846.6	4233	Rear	Fig.6	22.95	24	0.697	**0.89**	0.967	**1.23**	0.10

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.22: SAR Values (WCDMA 1900 MHz Band - Head) – CAB31P0000C1

Ambient Temperature: 22.4 °C Liquid Temperature: 21.9 °C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1907.6	9538	Right	Touch	Fig.7	23.39	24	0.489	**0.56**	0.864	**0.99**	-0.02

Table 14.23: SAR Values (WCDMA 1900 MHz Band - Body) – CAB31P0000C1

Ambient Temperature: 22.4 °C Liquid Temperature: 21.9 °C										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
1907.6	9538	Rear	Fig.8	23.39	24	0.645	**0.74**	1.100	**1.27**	0.05

Note1: The distance between the EUT and the phantom bottom is 10mm.

©Copyright. All rights reserved by CTTL.

Table 14.24: SAR Values (Wi-Fi 802.11b - Head) – CAB31P0000C1

Ambient Temperature: 22.6 °C Liquid Temperature: 22.1 °C											
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
2412	1	Left	Touch	/	17.57	18.5	0.152	**0.19**	0.332	**0.41**	0.19

Table 14.25: SAR Values (Wi-Fi 802.11b - Body) – CAB31P0000C1

Ambient Temperature: 22.6 °C Liquid Temperature: 22.1 °C										
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
2462	11	Rear	/	16.21	18.5	0.037	**0.06**	0.078	**0.13**	0.06

Note1: The distance between the EUT and the phantom bottom is 10mm.

©Copyright. All rights reserved by CTTL.

15 SAR Measurement Variability

SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium.

The following procedures are applied to determine if repeated measurements are required.

1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.

2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.

3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).

4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.

Table 15.1: SAR Measurement Variability for Body GSM 850 (1g)

Frequency		Test Position	Spacing (mm)	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
MHz	Ch.						
848.8	251	Rear	10	0.924	0.916	1.01	/

Table 15.2: SAR Measurement Variability for Body WCDMA 850 (1g)

Frequency		Test Position	Spacing (mm)	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
MHz	Ch.						
846.6	4233	Rear	10	0.967	0.960	1.01	/

Table 15.3: SAR Measurement Variability for Head WCDMA 1900 (1g)

Frequency		Test Position	Spacing (mm)	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
MHz	Ch.						
1907.6	9538	Right Touch	10	0.864	0.857	1.01	/

Table 15.4: SAR Measurement Variability for Body WCDMA 1900 (1g)

Frequency		Test Position	Spacing (mm)	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
MHz	Ch.						
1907.6	9538	Rear	10	1.100	0.998	1.10	/

©Copyright. All rights reserved by CTTL.

16 Measurement Uncertainty

16.1 Measurement Uncertainty for Normal SAR Tests (300MHz~3GHz)

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement system										
1	Probe calibration	B	5.5	N	1	1	1	5.5	5.5	∞
2	Isotropy	B	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
3	Boundary effect	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
4	Linearity	B	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
5	Detection limit	B	1.0	N	1	1	1	0.6	0.6	∞
6	Readout electronics	B	0.3	R	$\sqrt{3}$	1	1	0.3	0.3	∞
7	Response time	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
8	Integration time	B	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	∞
9	RF ambient conditions-noise	B	0	R	$\sqrt{3}$	1	1	0	0	∞
10	RF ambient conditions-reflection	B	0	R	$\sqrt{3}$	1	1	0	0	∞
11	Probe positioned mech. restrictions	B	0.4	R	$\sqrt{3}$	1	1	0.2	0.2	∞
12	Probe positioning with respect to phantom shell	B	2.9	R	$\sqrt{3}$	1	1	1.7	1.7	∞
13	Post-processing	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
Test sample related										
14	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	71
15	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
16	Drift of output power	B	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
Phantom and set-up										
17	Phantom uncertainty	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
18	Liquid conductivity (target)	B	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
19	Liquid conductivity (meas.)	A	2.06	N	1	0.64	0.43	1.32	0.89	43
20	Liquid permittivity (target)	B	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞
21	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	1.0	0.8	521
Combined standard uncertainty		$u_c^{'} = \sqrt{\sum_{i=1}^{21} c_i^2 u_i^2}$						9.25	9.12	257
Expanded uncertainty (confidence interval of 95 %)		$u_e = 2u_c$						18.5	18.2	

©Copyright. All rights reserved by CTTL.

16.3 Measurement Uncertainty for Fast SAR Tests (300MHz~3GHz)

No.	Error Description	Type	Uncertainty value	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. (1g)	Std. Unc. (10g)	Degree of freedom
Measurement system										
1	Probe calibration	B	5.5	N	1	1	1	5.5	5.5	∞
2	Isotropy	B	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
3	Boundary effect	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
4	Linearity	B	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
5	Detection limit	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
6	Readout electronics	B	0.3	R	$\sqrt{3}$	1	1	0.3	0.3	∞
7	Response time	B	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
8	Integration time	B	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	∞
9	RF ambient conditions-noise	B	0	R	$\sqrt{3}$	1	1	0	0	∞
10	RF ambient conditions-reflection	B	0	R	$\sqrt{3}$	1	1	0	0	∞
11	Probe positioned mech. Restrictions	B	0.4	R	$\sqrt{3}$	1	1	0.2	0.2	∞
12	Probe positioning with respect to phantom shell	B	2.9	R	$\sqrt{3}$	1	1	1.7	1.7	∞
13	Post-processing	B	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
14	Fast SAR z-Approximation	B	7.0	R	$\sqrt{3}$	1	1	4.0	4.0	∞
Test sample related										
15	Test sample positioning	A	3.3	N	1	1	1	3.3	3.3	71
16	Device holder uncertainty	A	3.4	N	1	1	1	3.4	3.4	5
17	Drift of output power	B	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
Phantom and set-up										
18	Phantom uncertainty	B	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
19	Liquid conductivity (target)	B	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
20	Liquid conductivity (meas.)	A	2.06	N	1	0.64	0.43	1.32	0.89	43
21	Liquid permittivity (target)	B	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞
22	Liquid permittivity (meas.)	A	1.6	N	1	0.6	0.49	1.0	0.8	521
Combined standard uncertainty		$u_c^{'} = \sqrt{\sum_{i=1}^{22} c_i^2 u_i^2}$						10.1	9.95	257
Expanded uncertainty (confidence interval of 95 %)		$u_e = 2u_c$						20.2	19.9	

©Copyright. All rights reserved by CTTL.

17 MAIN TEST INSTRUMENTS

Table 17.1: List of Main Instruments

No.	Name	Type	Serial Number	Calibration Date	Valid Period
01	Network analyzer	Agilent E5071C	MY46103759	December 27,2013	One year
02	Power meter	NRVD	101253	March 8,2014	One year
03	Power sensor	NRV-Z5	100333		
04	Signal Generator	E4438C	MY45095825	January 14, 2014	One year
05	Amplifier	VTL5400	0404	No Calibration Requested	
06	BTS	E5515C	GB47460133	September 4, 2014	One year
07	E-field Probe	SPEAG ES3DV3	3151	September 1, 2014	One year
08	DAE	SPEAG DAE4	786	November 20, 2014	One year
09	Dipole Validation Kit	SPEAG D835V2	4d057	November 4, 2014	One year
10	Dipole Validation Kit	SPEAG D1900V2	5d088	November 5, 2014	One year
11	Dipole Validation Kit	SPEAG D2450V2	873	November 3, 2014	One year
12	Network analyzer	E5071C	MY46110673	February15,2014	One year
13	Power meter	NRVD	102083	March 15,2014	One year
14	Power sensor	NRV-Z5	100542		
15	Signal Generator	E4438C	MY49070393	February08, 2014	One Year
16	Amplifier	60S1G4	0331848	No Calibration Requested	
17	BTS	E5515C	MY50263375	January30, 2015	One year
18	E-field Probe	SPEAG EX3DV4	3846	September24, 2014	One year
19	DAE	SPEAG DAE4	777	September17, 2014	One year
20	Dipole Validation Kit	SPEAG D835V2	4d069	August28, 2014	One year
21	Dipole Validation Kit	SPEAG D1900V2	5d101	July23, 2014	One year

END OF REPORT BODY

©Copyright. All rights reserved by CTTL.

ANNEX A Graph Results

850 Left Cheek High

Date: 2014-12-13
Electronics: DAE4 Sn786
Medium: Head 900 MHz
Medium parameters used (interpolated): f = 848.8 MHz; σ = 0.939 S/m; ε_r = 41.723; ρ = 1000 kg/m^3
Ambient Temperature:21.7^{o}C Liquid Temperature:21.2^{o}C
Communication System: GSM Frequency: 848.8 MHz Duty Cycle: 1:8.3
Probe: ES3DV3 - SN3151 ConvF(6.04, 6.04, 6.04);

Left Cheek High/Area Scan (81x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.841 W/kg

Left Cheek High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 10.043 V/m; Power Drift = 0.11 dB
Peak SAR (extrapolated) = 1.02 W/kg
SAR(1 g) = 0.793 W/kg; SAR(10 g) = 0.576 W/kg

Maximum value of SAR (measured) = 0.841 W/kg



Fig.1 850MHz CH251

©Copyright. All rights reserved by CTTL.



Fig. 1-1 Z-Scan at power reference point (850 MHz CH251)

©Copyright. All rights reserved by CTTL.

850 Body Rear High

Date: 2014-12-13
Electronics: DAE4 Sn786
Medium: Body 900 MHz
Medium parameters used (interpolated): f = 848.8 MHz; σ = 0.977 S/m; ε_r = 55.686; ρ = 1000 kg/m^3
Ambient Temperature:22.7^{o}C Liquid Temperature:22.2^{o}C
Communication System: 4 slot GPRS Frequency: 848.8 MHz Duty Cycle: 1:2
Probe: ES3DV3 - SN3151 ConvF(6.14, 6.14, 6.14);

Rear side High/Area Scan (51x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.02 W/kg

Rear side High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 23.694 V/m; Power Drift = 0.18 dB
Peak SAR (extrapolated) = 1.29 W/kg
SAR(1 g) = 0.924 W/kg; SAR(10 g) = 0.639 W/kg

Maximum value of SAR (measured) = 0.990 W/kg



Fig.2 850 MHz CH251

©Copyright. All rights reserved by CTTL.



Fig. 2-1 Z-Scan at power reference point (850 MHz CH251)

©Copyright. All rights reserved by CTTL.

GSM1900 Right Cheek High

Date: 2014-12-14
Electronics: DAE4 Sn786
Medium: 1900 Head
Medium parameters used: f = 1910 MHz; σ = 1.454 S/m; ε_r = 41.028; ρ = 1000 kg/m^3
Ambient Temperature:21.7^{o}C Liquid Temperature:21.2^{o}C
Communication System: GSM Frequency: 1910 MHz Duty Cycle: 1:8.3
Probe: ES3DV3 - SN3151 ConvF(5.16, 5.16, 5.16);

Right Cheek High/Area Scan (51x101x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.551 W/kg

Right Cheek High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 6.627 V/m; Power Drift = 0.19 dB
Peak SAR (extrapolated) = 0.924 W/kg
SAR(1 g) = 0.543 W/kg; SAR(10 g) = 0.298 W/kg
Maximum value of SAR (measured) = 0.591 W/kg



Fig.3 1900 MHz CH810

©Copyright. All rights reserved by CTTL.



Fig. 3-1 Z-Scan at power reference point (1900 MHz CH810)

©Copyright. All rights reserved by CTTL.

GSM1900 Body Rear High

Date: 2014-12-14

Electronics: DAE4 Sn786

Medium: Body 1900MHz

Medium parameters used: f = 1910 MHz; σ = 1.522 S/m; ε_r = 52.593; ρ = 1000 kg/m^3

Ambient Temperature:21.7^{o}C Liquid Temperature:21.2^{o}C

Communication System: 4 slot GPRS Frequency: 1909.8 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3151 ConvF(4.77, 4.77, 4.77);

Rear side High/Area Scan (81x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.649 W/kg

Rear side High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.754 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.954 W/kg

SAR(1 g) = 0.572 W/kg; SAR(10 g) = 0.331 W/kg

Maximum value of SAR (measured) = 0.616 W/kg



Fig.4 1900 MHz CH810

©Copyright. All rights reserved by CTTL.



Fig.4-1 Z-Scan at power reference point (1900 MHz CH810)

©Copyright. All rights reserved by CTTL.

WCDMA 850 Left Cheek High

Date: 2014-12-13
Electronics: DAE4 Sn786
Medium: Head 900 MHz
Medium parameters used (interpolated): f = 846.6 MHz; σ = 0.939 S/m; ε_r = 41.741; ρ = 1000 kg/m^3
Ambient Temperature:21.7^{o}C Liquid Temperature:21.2^{o}C
Communication System: WCDMA Frequency: 846.6 MHz Duty Cycle: 1:1
Probe: ES3DV3 - SN3151 ConvF(6.04, 6.04, 6.04);

Left Cheek High/Area Scan (51x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.777 W/kg

Left Cheek High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 11.222 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 0.902 W/kg
SAR(1 g) = 0.720 W/kg; SAR(10 g) = 0.534 W/kg

Maximum value of SAR (measured) = 0.760 W/kg



Fig.5 WCDMA 850 CH4233

©Copyright. All rights reserved by CTTL.



Fig. 5-1 Z-Scan at power reference point (WCDMA 850 CH4233)

©Copyright. All rights reserved by CTTL.

WCDMA 850 Body Rear High

Date: 2014-12-13
Electronics: DAE4 Sn786
Medium: Body 900
Medium parameters used (interpolated): f = 846.6 MHz; σ = 0.976 S/m; ε_r = 55.684; ρ = 1000 kg/m^3
Ambient Temperature:21.7^{o}C Liquid Temperature:21.2^{o}C
Communication System: WCDMA Frequency: 846.6 MHz Duty Cycle: 1:1
Probe: ES3DV3 - SN3151 ConvF(6.14, 6.14, 6.14);

Rear side High/Area Scan (51x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.00 W/kg

Rear side High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 29.111 V/m; Power Drift = 0.10 dB
Peak SAR (extrapolated) = 1.27 W/kg
SAR(1 g) = 0.967 W/kg; SAR(10 g) = 0.697 W/kg

Maximum value of SAR (measured) = 1.02 W/kg



Fig.6 WCDMA 850 CH4233

©Copyright. All rights reserved by CTTL.



Fig. 6-1 Z-Scan at power reference point (WCDMA850 CH4233)

©Copyright. All rights reserved by CTTL.

WCDMA 1900 Right Cheek High

Date: 2014-12-14
Electronics: DAE4 Sn786
Medium: Head 1900 MHz
Medium parameters used: f = 1908 MHz; σ = 1.454 S/m; ε_r = 41.033; ρ = 1000 kg/m^3
Ambient Temperature:21.7^{o}C Liquid Temperature:21.2^{o}C
Communication System: WCDMA Frequency: 1908 MHz Duty Cycle: 1:1
Probe: ES3DV3 - SN3151 ConvF(5.16, 5.16, 5.16);

Right Cheek High/Area Scan (51x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 0.985 W/kg

Right Cheek High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 7.807 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 1.43 W/kg
SAR(1 g) = 0.864 W/kg; SAR(10 g) = 0.489 W/kg
Maximum value of SAR (measured) = 0.967 W/kg



Fig.7 WCDMA1900 CH9538

©Copyright. All rights reserved by CTTL.



Fig. 7-1 Z-Scan at power reference point (WCDMA1900 CH9538)

©Copyright. All rights reserved by CTTL.

WCDMA 1900 Body Rear High

Date: 2014-12-14
Electronics: DAE4 Sn786
Medium: Body 1900MHz
Medium parameters used: f = 1908 MHz; σ = 1.520 S/m; ε_r = 52.572; ρ = 1000 kg/m^3
Ambient Temperature:21.7^{o}C Liquid Temperature:21.2^{o}C
Communication System: WCDMA Frequency: 1908 MHz Duty Cycle: 1:1
Probe: ES3DV3 - SN3151 ConvF(4.77, 4.77, 4.77);

Rear side High/Area Scan (51x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 1.29 W/kg

Rear side High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 11.477 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 1.82 W/kg
SAR(1 g) = 1.1 W/kg; SAR(10 g) = 0.645 W/kg
Maximum value of SAR (measured) = 1.18 W/kg



Fig.8 WCDMA1900 CH9538

©Copyright. All rights reserved by CTTL.



Fig. 8-1 Z-Scan at power reference point (WCDMA1900 CH9538)

©Copyright. All rights reserved by CTTL.

Wifi 802.11b left Cheek Channel 1

Date: 2014-12-19

Electronics: DAE4 Sn786

Medium: Head 2450 MHz

Medium parameters used: f = 2412 MHz; σ = 1.772 S/m; ε_r = 39.391; ρ = 1000 kg/m^3

Ambient Temperature:21.7^{o}C Liquid Temperature:21.2^{o}C

Communication System: WiFi Frequency: 2412 MHz Duty Cycle: 1:1

Probe: ES3DV3 - SN3151 ConvF(4.71, 4.71, 4.71);

left/Cheek Low/Area Scan (51x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.423 W/kg

left/Cheek Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.143 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.779 W/kg

SAR(1 g) = 0.332 W/kg; SAR(10 g) = 0.152 W/kg

Maximum value of SAR (measured) = 0.376 W/kg



Fig.9 2450 MHz CH1

©Copyright. All rights reserved by CTTL.



Fig. 9-1 Z-Scan at power reference point (2450 MHz CH1)

©Copyright. All rights reserved by CTTL.

Wifi 802.11b Body Rear Channel 11

Date: 2014-12-17

Electronics: DAE4 Sn786

Medium: Body 2450 MHz

Medium parameters used: f = 2462 MHz; σ = 1.953 S/m; ε_r = 52.567; ρ = 1000 kg/m^3

Ambient Temperature:21.7^{o}C Liquid Temperature:21.2^{o}C

Communication System: WiFi Frequency: 2462 MHz Duty Cycle: 1:1

Probe: ES3DV3 - SN3151 ConvF(4.42, 4.42, 4.42);

Rear side High/Area Scan (51x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.0776 W/kg

Rear side High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.981 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.165 W/kg

SAR(1 g) = 0.078 W/kg; SAR(10 g) = 0.037 W/kg

Maximum value of SAR (measured) = 0.0883 W/kg



Fig.10 2450 MHz CH11

©Copyright. All rights reserved by CTTL.



Fig. 10-1 Z-Scan at power reference point (2450 MHz CH11)

©Copyright. All rights reserved by CTTL.

ANNEX B System Verification Results

835MHz

Date: 2014-12-13
Electronics: DAE4 Sn786
Medium: Head 900 MHz
Medium parameters used: f = 835 MHz; σ = 0.938 S/m; ε_r = 41.87; ρ = 1000 kg/m^3
Ambient Temperature: 22.0^{o}C Liquid Temperature: 21.5^{o}C
Communication System: CW Frequency: 835 MHz Duty Cycle: 1:1
Probe: ES3DV3 - SN3151 ConvF(6.04, 6.04, 6.04);

System Validation /Area Scan (81x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Reference Value = 54.722 V/m; Power Drift = 0.02 dB
Fast SAR: SAR(1 g) = 2.42 W/kg; SAR(10 g) = 1.58 W/kg
Maximum value of SAR (interpolated) = 2.62 W/kg

System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 54.722 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 3.69 W/kg
SAR(1 g) = 2.43 W/kg; SAR(10 g) = 1.61 W/kg
Maximum value of SAR (measured) = 2.64 W/kg



0 dB = 2.64 W/kg = 1.84 dBW/kg

Fig.B.1 validation 835MHz 250mW

©Copyright. All rights reserved by CTTL.

835MHz

Date: 2014-12-13

Electronics: DAE4 Sn786

Medium: Body 900 MHz

Medium parameters used: f = 835 MHz; σ = 0.969 S/m; ε_r = 55.562; ρ = 1000 kg/m^3

Ambient Temperature: 22.5^{o}C Liquid Temperature: 22.0^{o}C

Communication System: CW Frequency: 835 MHz Duty Cycle: 1:1

Probe: ES3DV3 - SN3151 ConvF(6.14, 6.14, 6.14);

System Validation /Area Scan (81x171x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 53.566 V/m; Power Drift = -0.02 dB

Fast SAR: SAR(1 g) = 2.41 W/kg; SAR(10 g) = 1.56 W/kg

Maximum value of SAR (interpolated) = 2.61 W/kg

System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 53.566 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 3.58 W/kg

SAR(1 g) = 2.42 W/kg; SAR(10 g) = 1.58 W/kg

Maximum value of SAR (measured) = 2.61 W/kg



0 dB = 2.61 W/kg = 1.82 dBW/kg

Fig.B.2 validation 835MHz 250mW

©Copyright. All rights reserved by CTTL.

1900MHz

Date: 2014-12-14

Electronics: DAE4 Sn786

Medium: Head 1900 MHz

Medium parameters used: f = 1900 MHz; σ = 1.453 S/m; ε_r = 41.061; ρ = 1000 kg/m^3

Ambient Temperature: 22.5^{o}C Liquid Temperature: 22.0^{o}C

Communication System: CW Frequency: 1900 MHz Duty Cycle: 1:1

Probe: ES3DV3 - SN3151 ConvF(5.16, 5.16, 5.16);

System Validation /Area Scan (81x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 86.259 V/m; Power Drift = -0.09 dB

Fast SAR: SAR(1 g) = 9.88 W/kg; SAR(10 g) = 5.18 W/kg

Maximum value of SAR (interpolated) = 13.5 W/kg

System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 86.259 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 18.4 W/kg

SAR(1 g) = 9.89 W/kg; SAR(10 g) = 5.25 W/kg

Maximum value of SAR (measured) = 11.3 W/kg



0 dB = 11.3 W/kg = 13.49 dBW/kg

Fig.B.3 validation 1900MHz 250mW

©Copyright. All rights reserved by CTTL.

1900MHz

Date: 2014-12-14

Electronics: DAE4 Sn786

Medium: Body 1900 MHz

Medium parameters used: f = 1900 MHz; σ = 1.513 S/m; ε_r = 52.586; ρ = 1000 kg/m^3

Ambient Temperature: 22.3^{o}C Liquid Temperature: 21.8^{o}C

Communication System: CW Frequency: 1900 MHz Duty Cycle: 1:1

Probe: ES3DV3 - SN3151 ConvF(4.77, 4.77, 4.77);

System validation /Area Scan (81x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 60.339 V/m; Power Drift = 0.08 dB

Fast SAR: SAR(1 g) = 10.1 W/kg; SAR(10 g) = 5.40 W/kg

Maximum value of SAR (interpolated) = 13.5 W/kg

System validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 60.339 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 19.3 W/kg

SAR(1 g) = 10.2 W/kg; SAR(10 g) = 5.43 W/kg

Maximum value of SAR (measured) = 12.2 W/kg



0 dB = 12.4 W/kg = 16.60 dBW/kg

Fig.B.4 validation 1900MHz 250mW

©Copyright. All rights reserved by CTTL.

2450MHz

Date: 2014-12-19

Electronics: DAE4 Sn786

Medium: Head 2450 MHz

Medium parameters used: f = 2450 MHz; σ = 1.774 S/m; ε_r = 39.256; ρ = 1000 kg/m^3

Ambient Temperature: 22.6^{o}C Liquid Temperature: 22.1^{o}C

Communication System: CW Frequency: 2450 MHz Duty Cycle: 1:1

Probe: ES3DV3 - SN3151 ConvF(4.71, 4.71, 4.71);

System Validation/Area Scan (81x101x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 84.926 V/m; Power Drift = 0.04 dB

Fast SAR: SAR(1 g) = 13.05 W/kg; SAR(10 g) = 6.09 W/kg

Maximum value of SAR (interpolated) = 11.5 W/kg

system check 2450M /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 84.926 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 22.1 W/kg

SAR(1 g) = 13.1 W/kg; SAR(10 g) = 6.12 W/kg

Maximum value of SAR (measured) = 14.6 W/kg



0 dB = 14.6 W/kg = 28.84 dBW/kg

Fig.B.5 validation 2450MHz 250mW

©Copyright. All rights reserved by CTTL.

2450MHz

Date: 2014-12-17

Electronics: DAE4 Sn786

Medium: Body 2450 MHz

Medium parameters used: f = 2450 MHz; σ = 1.951 S/m; ε_r = 52.593; ρ = 1000 kg/m^3

Ambient Temperature: 22.5^{o}C Liquid Temperature: 22.0^{o}C

Communication System: CW Frequency: 2450 MHz Duty Cycle: 1:1

Probe: ES3DV3 - SN3151 ConvF(4.42, 4.42, 4.42);

System Validation/Area Scan (81x101x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Reference Value = 84.926 V/m; Power Drift = 0.05 dB

Fast SAR: SAR(1 g) = 12.95 W/kg; SAR(10 g) = 5.96 W/kg

Maximum value of SAR (interpolated) = 12.2 W/kg

system check 2450M /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 84.926 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 26.2 W/kg

SAR(1 g) = 12.98 W/kg; SAR(10 g) = 5.99 W/kg

Maximum value of SAR (measured) = 14.1 W/kg



0 dB = 14.2 W/kg = 27.70 dBW/kg

Fig.B.6 validation 2450MHz 250mW

©Copyright. All rights reserved by CTTL.

835MHz

Date: 2015-2-2
Electronics: DAE4 Sn777
Medium: Head 850 MHz
Medium parameters used: f = 835 MHz; σ = 0.9 S/m; ε_r = 41.73; ρ = 1000 kg/m^3
Ambient Temperature: 22.5^{o}C Liquid Temperature: 22.0^{o}C
Communication System: CW Frequency: 835 MHz Duty Cycle: 1:1
Probe: EX3DV4 - SN3846 ConvF(9.18, 9.18, 9.18)

System Validation/Area Scan (61x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Reference Value = 55.066 V/m; Power Drift = 0.03 dB
Fast SAR: SAR(1 g) = 2.47 W/kg; SAR(10 g) = 1.62 W/kg
Maximum value of SAR (interpolated) = 2.70 W/kg

System Validation/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 55.066 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 3.14 W/kg
SAR(1 g) = 2.43 W/kg; SAR(10 g) = 1.59 W/kg
Maximum value of SAR (measured) = 2.67 W/kg



0 dB = 2.67 W/kg = 4.27 dBW/kg

Fig.B.7 validation 835MHz 250mW

©Copyright. All rights reserved by CTTL.

835MHz

Date: 2015-2-2
Electronics: DAE4 Sn777
Medium: Body 850 MHz
Medium parameters used: f = 835 MHz; σ = 0.982 S/m; ε_r = 54.54; ρ = 1000 kg/m^3
Ambient Temperature: 22.5^{o}C Liquid Temperature: 22.0^{o}C
Communication System: CW Frequency: 835 MHz Duty Cycle: 1:1
Probe: EX3DV4 - SN3846 ConvF(9.09, 9.09, 9.09)

System Validation /Area Scan (61x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Reference Value = 52.308 V/m; Power Drift = -0.06 dB
Fast SAR: SAR(1 g) = 2.31 W/kg; SAR(10 g) = 1.52 W/kg
Maximum value of SAR (interpolated) = 2.57 W/kg

System Validation /Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 52.308 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 3.09 W/kg
SAR(1 g) = 2.36 W/kg; SAR(10 g) = 1.55 W/kg
Maximum value of SAR (measured) = 2.60 W/kg



0 dB = 2.60 W/kg = 4.15 dBW/kg

Fig.B.8 validation 835MHz 250mW

©Copyright. All rights reserved by CTTL.