

Fig.A.6.1.73 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, Center Frequency)



Fig.A.6.1.74 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 30 MHz-1 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.75 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 1 GHz-2.5 GHz)



Fig.A.6.1.76 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 2.5 GHz-7.5 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.77 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 7.5 GHz-10 GHz)



Fig.A.6.1.78 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 10 GHz-15 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.79 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 15 GHz-20 GHz)



Fig.A.6.1.80 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch3, 20 GHz-26 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.81 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, Center Frequency)



Fig.A.6.1.82 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 30 MHz-1 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.83 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 1 GHz-2.5 GHz)



Fig.A.6.1.84 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 2.5 GHz-7.5 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.85 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 7.5 GHz-10 GHz)



Fig.A.6.1.86 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 10 GHz-15 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.87 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 15 GHz-20 GHz)



Fig.A.6.1.88 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch6, 20 GHz-26 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.89 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, Center Frequency)



Fig.A.6.1.90 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 30 MHz-1 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.91 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 1 GHz-2.5 GHz)



Fig.A.6.1.92 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 2.5 GHz-7.5 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.93 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 7.5 GHz-10 GHz)



Fig.A.6.1.94 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 10 GHz-15 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.1.95 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 15 GHz-20 GHz)



Fig.A.6.1.96 Transmitter Spurious Emission - Conducted (802.11n-HT40, Ch9, 20 GHz-26 GHz)

©Copyright. All rights reserved by CTTL.

A.6.2 Transmitter Spurious Emission - Radiated

Method of Measurement: See ANSI C63.10-2013-clause 6.4 &6.5 & 6.6

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Frequency (MHz)	Field strength(μV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Test Condition

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/1MHz	15
4000-18000	1MHz/1MHz	40
18000-26500	1MHz/1MHz	20

EUT ID: EUT1

©Copyright. All rights reserved by CTTL.

Measurement Results:

802.11b mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11b	Power	2.38GHz ~2.45GHz	Fig.A.6.2.1	**P**
	1	1 GHz ~ 3 GHz	Fig.A.6.2.2	**P**
		3 GHz ~ 18 GHz	Fig.A.6.2.3	**P**
	6	9 kHz ~30 MHz	Fig.A.6.2.4	**P**
		30 MHz ~1 GHz	Fig.A.6.2.5	**P**
		1 GHz ~ 3 GHz	Fig.A.6.2.6	**P**
		3 GHz ~ 18 GHz	Fig.A.6.2.7	**P**
		18 GHz~ 26.5 GHz	Fig.A.6.2.8	**P**
	Power	2.45GHz ~2.5GHz	Fig.A.6.2.9	**P**
	11	1 GHz ~ 3 GHz	Fig.A.6.2.10	**P**
		3 GHz ~ 18 GHz	Fig.A.6.2.11	**P**

802.11g mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11g	Power	2.38GHz ~2.43GHz	Fig.A.6.2.12	**P**
	1	1 GHz ~ 3 GHz	Fig.A.6.2.13	**P**
		3 GHz ~ 18 GHz	Fig.A.6.2.14	**P**
	6	30 MHz ~1 GHz	Fig.A.6.2.15	**P**
		1 GHz ~ 3 GHz	Fig.A.6.2.16	**P**
		3 GHz ~ 18 GHz	Fig.A.6.2.17	**P**
		18 GHz~ 26.5 GHz	Fig.A.6.2.18	**P**
	Power	2.45GHz ~2.5GHz	Fig.A.6.2.19	**P**
	11	1 GHz ~ 3 GHz	Fig.A.6.2.20	**P**
		3 GHz ~ 18 GHz	Fig.A.6.2.21	**P**

802.11n-HT20 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT20)	Power	2.38GHz ~2.45GHz	Fig.A.6.2.22	**P**
	1	1 GHz ~ 3 GHz	Fig.A.6.2.23	**P**
		3 GHz ~ 18 GHz	Fig.A.6.2.24	**P**
	6	30 MHz ~1 GHz	Fig.A.6.2.25	**P**
		1 GHz ~ 3 GHz	Fig.A.6.2.26	**P**
		3 GHz ~ 18 GHz	Fig.A.6.2.27	**P**
		18 GHz~ 26.5 GHz	Fig.A.6.2.28	**P**
	Power	2.45GHz ~2.5GHz	Fig.A.6.2.29	**P**
	11	1 GHz ~ 3 GHz	Fig.A.6.2.30	**P**
		3 GHz ~ 18 GHz	Fig.A.6.2.31	**P**

©Copyright. All rights reserved by CTTL.

802.11n-HT40 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT40)	Power	2.38GHz ~2.45GHz	Fig.A.6.2.32	**P**
	3	1 GHz ~ 3 GHz	Fig.A.6.2.33	**P**
		3 GHz ~ 18 GHz	Fig.A.6.2.34	**P**
	6	30 MHz ~1 GHz	Fig.A.6.2.35	**P**
		1 GHz ~ 3 GHz	Fig.A.6.2.36	**P**
		3 GHz ~ 18 GHz	Fig.A.6.2.37	**P**
		18 GHz~ 26.5 GHz	Fig.A.6.2.38	**P**
	Power	2.45GHz ~2.5GHz	Fig.A.6.2.39	**P**
	9	1 GHz ~ 3 GHz	Fig.A.6.2.40	**P**
		3 GHz ~ 18 GHz	Fig.A.6.2.41	**P**

Conclusion: Pass

Note:

A "reference path loss" is established and the A_{Rpl} is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

Result=P_{Mea}+$A_{Rpl=}$ P_{Mea}+Cable Loss+Antenna Factor

802.11b

Ch1

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
2382.268	59.7	-26.9	32.4	54.208	V
17664.750	59.0	-13.0	41.2	30.805	H
17973.750	58.4	-13.5	41.0	30.862	V
17373.000	58.4	-13.9	41.2	31.123	V
17752.500	58.4	-13.0	41.0	30.405	H
17688.750	58.3	-13.0	41.2	30.105	V

Ch6

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
17274.000	58.7	-15.1	41.2	32.593	H
17592.000	58.4	-14.9	41.2	32.118	H
17652.000	58.1	-13.0	41.2	29.905	V
17692.500	58.0	-13.0	41.2	29.805	H
17561.250	58.0	-14.9	41.2	31.718	V
17247.000	57.9	-15.1	41.4	31.593	V

©Copyright. All rights reserved by CTTL.

Ch11

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
2483.840	59.8	-27.4	32.4	54.772	V
17683.500	58.9	-13.0	41.2	30.705	V
17681.250	58.7	-13.0	41.2	30.505	H
17673.750	58.4	-13.0	41.2	30.205	H
17682.750	58.1	-13.0	41.2	29.905	V
17257.500	58.1	-15.1	41.2	31.993	V

802.11g

Ch1

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
2389.884	62.3	-26.9	32.4	56.808	V
17633.250	59.0	-13.0	41.2	30.805	V
17592.750	58.4	-14.9	41.2	32.118	H
17646.000	58.3	-13.0	41.2	30.105	H
17586.750	58.0	-14.9	41.2	31.718	V
17796.000	57.8	-13.0	41.0	29.805	V

Ch6

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
17726.250	58.5	-13.0	41.2	30.305	H
17641.500	58.2	-13.0	41.2	30.005	V
17590.500	58.1	-14.9	41.2	31.818	H
17613.000	58.0	-14.9	41.2	31.718	V
17756.250	57.9	-13.0	41.0	29.905	H
17694.000	57.9	-13.0	41.2	29.705	V

Ch11

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
2483.680	64.6	-27.4	32.4	59.572	V
17562.000	58.5	-14.9	41.2	32.218	V
17692.500	58.3	-13.0	41.2	30.105	H
17246.250	58.2	-15.1	41.4	31.893	V
17180.250	58.0	-15.1	41.4	31.693	V
17907.000	58.0	-13.5	41.0	30.462	V

©Copyright. All rights reserved by CTTL.

802.11n-HT20

Ch1

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
2389.352	62.9	-26.9	32.4	57.408	H
17757.750	58.7	-13.0	41.0	30.705	H
17723.250	58.3	-13.0	41.2	30.105	V
17754.750	58.1	-13.0	41.0	30.105	V
17785.500	58.1	-13.0	41.0	30.105	H
17511.000	58.0	-14.9	41.2	31.718	H

Ch6

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
17724.750	59.4	-13.0	41.2	31.205	V
17619.000	58.6	-14.9	41.2	32.318	V
17637.000	58.1	-13.0	41.2	29.905	H
17689.500	58.1	-13.0	41.2	29.905	V
17308.500	58.1	-13.9	41.2	30.823	H
17679.750	58.1	-13.0	41.2	29.905	V

Ch11

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
2483.700	62.6	-27.4	32.4	57.572	V
17719.500	58.4	-13.0	41.2	30.205	V
17640.750	58.0	-13.0	41.2	29.805	H
17521.500	58.0	-14.9	41.2	31.718	H
17625.750	57.9	-14.9	41.2	31.618	H
17706.000	57.7	-13.0	41.2	29.505	H

©Copyright. All rights reserved by CTTL.

802.11n-HT40

Ch3

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
2389.576	64.7	-26.9	32.4	59.208	H
17651.250	59.4	-13.0	41.2	31.205	H
17728.500	58.9	-13.0	41.2	30.705	H
17163.750	58.0	-15.1	41.4	31.693	V
17637.750	58.0	-13.0	41.2	29.805	H
17594.250	58.0	-14.9	41.2	31.718	V

Ch6

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
17730.750	59.3	-13.0	41.2	31.105	H
17636.250	58.9	-13.0	41.2	30.705	V
17562.750	58.4	-14.9	41.2	32.118	H
17191.500	58.0	-15.1	41.4	31.693	H
17797.500	58.0	-13.0	41.0	30.005	V
17627.250	57.9	-14.9	41.2	31.618	H

Ch9

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
2483.700	62.6	-27.4	32.4	57.572	V
17799.750	58.6	-13.0	41.0	30.605	V
17628.750	58.3	-14.9	41.2	32.018	V
17610.750	58.2	-14.9	41.2	31.918	V
17628.000	58.1	-14.9	41.2	31.818	V
17620.500	58.1	-14.9	41.2	31.818	H

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.1 Transmitter Spurious Emission - Radiated (Power): 802.11b, ch1, 2.38 GHz – 2.45GHz



Fig.A.6.2.2 Transmitter Spurious Emission - Radiated (802.11b, Ch1, 1 GHz-3 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.3 Transmitter Spurious Emission - Radiated (802.11b, Ch1, 3 GHz-18 GHz)



Fig.A.6.2.4 Transmitter Spurious Emission - Radiated (802.11b, Ch6, 9kHz-30 MHz)

©Copyright. All rights reserved by CTTL.

RE 30MHz-1GHz



Fig.A.6.2.5 Transmitter Spurious Emission - Radiated (802.11b, Ch6, 30 MHz-1 GHz)

RE - 1GHz-3GHz



Fig.A.6.2.6 Transmitter Spurious Emission - Radiated (802.11b, Ch6, 1 GHz-3 GHz)

©Copyright. All rights reserved by CTTL.

RE - 3GHz-18GHz



Fig.A.6.2.7 Transmitter Spurious Emission - Radiated (802.11b, Ch6, 3 GHz-18 GHz)

Normal RE_18G-26.5GHz



Fig.A.6.2.8 Transmitter Spurious Emission - Radiated (802.11b, Ch6, 18GHz – 26.5GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.9 Transmitter Spurious Emission - Radiated (Power): 802.11b, ch11, 2.45 GHz - 2.50GHz



Fig.A.6.2.10 Transmitter Spurious Emission - Radiated (802.11b, Ch11, 1 GHz-3 GHz)

©Copyright. All rights reserved by CTTL.

RE - 3GHz-18GHz



Fig.A.6.2.11 Transmitter Spurious Emission - Radiated (802.11b, Ch11, 3 GHz-18 GHz)

RE - Power-2.38GHz-2.45GHz



Fig.A.6.2.12 Transmitter Spurious Emission - Radiated (Power): 802.11g, ch1, 2.38 GHz - 2.45GHz

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.13 Transmitter Spurious Emission - Radiated (802.11g, Ch1, 1 GHz-3 GHz)



Fig.A.6.2.14 Transmitter Spurious Emission - Radiated (802.11g, Ch1, 3 GHz-18 GHz)

©Copyright. All rights reserved by CTTL.

RE 30MHz-1GHz



Fig.A.6.2.15 Transmitter Spurious Emission - Radiated (802.11g, Ch6, 30 MHz-1 GHz)

RE - 1GHz-3GHz



Fig.A.6.2.16 Transmitter Spurious Emission - Radiated (802.11g, Ch6, 1 GHz-3 GHz)

©Copyright. All rights reserved by CTTL.

RE - 3GHz-18GHz



Fig.A.6.2.17 Transmitter Spurious Emission - Radiated (802.11g, Ch6, 3 GHz-18 GHz)

Normal RE_18G-26.5GHz



Fig.A.6.2.18 Transmitter Spurious Emission - Radiated (802.11g, Ch6, 18GHz – 26.5GHz)

©Copyright. All rights reserved by CTTL.

RE - Power-2.45GHz-2.5GHz



Fig.A.6.2.19 Transmitter Spurious Emission - Radiated (Power): 802.11g, ch11, 2.45 GHz - 2.50GHz

RE - 1GHz-3GHz



Fig.A.6.2.20 Transmitter Spurious Emission - Radiated (802.11g, Ch11, 1 GHz-3 GHz)

©Copyright. All rights reserved by CTTL.

RE - 3GHz-18GHz



Fig.A.6.2.21 Transmitter Spurious Emission - Radiated (802.11g, Ch11, 3 GHz-18 GHz)

RE - Power-2.38GHz-2.45GHz



Fig.A.6.2.22 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT20, ch1, 2.38 GHz - 2.45GHz

©Copyright. All rights reserved by CTTL.

RE - 1GHz-3GHz



Fig.A.6.2.23 Transmitter Spurious Emission - Radiated (802.11n-HT20, Ch1, 1 GHz-3 GHz)

RE - 3GHz-18GHz



Fig.A.6.2.24 Transmitter Spurious Emission - Radiated (802.11n-HT20, Ch1, 3 GHz-18 GHz)

©Copyright. All rights reserved by CTTL.

RE 30MHz-1GHz



Fig.A.6.2.25 Transmitter Spurious Emission - Radiated (802.11n-HT20, Ch6, 30 MHz-1 GHz)

RE - 1GHz-3GHz



Fig.A.6.2.26 Transmitter Spurious Emission - Radiated (802.11n-HT20, Ch6, 1 GHz-3 GHz)

©Copyright. All rights reserved by CTTL.

RE - 3GHz-18GHz



Fig.A.6.2.27 Transmitter Spurious Emission - Radiated (802.11n-HT20, Ch6, 3 GHz-18 GHz)

Normal RE_18G-26.5GHz



Fig.A.6.2.28 Transmitter Spurious Emission - Radiated (802.11n-HT20, Ch6, 18GHz – 26.5GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.29 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT20, ch11, 2.45 GHz - 2.50GHz



Fig.A.6.2.30 Transmitter Spurious Emission - Radiated (802.11n-HT20, Ch11, 1 GHz-3 GHz)

©Copyright. All rights reserved by CTTL.

RE - 3GHz-18GHz



Fig.A.6.2.31 Transmitter Spurious Emission - Radiated (802.11n-HT20, Ch11, 3 GHz-18 GHz)

RE - Power-2.38GHz-2.45GHz



Fig.A.6.2.32 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT40, ch3, 2.38 GHz - 2.45GHz

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.33 Transmitter Spurious Emission - Radiated (802.11n-HT40, ch3, 1 GHz-3 GHz)



Fig.A.6.2.34 Transmitter Spurious Emission - Radiated (802.11n-HT40, ch3, 3 GHz-18 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.35 Transmitter Spurious Emission - Radiated (802.11n-HT40, Ch6, 30 MHz-1 GHz)



Fig.A.6.2.36 Transmitter Spurious Emission - Radiated (802.11n-HT40, Ch6, 1 GHz-3 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.37 Transmitter Spurious Emission - Radiated (802.11n-HT40, Ch6, 3 GHz-18 GHz)



Fig.A.6.2.38 Transmitter Spurious Emission - Radiated (802.11n-HT40, Ch6, 18GHz – 26.5GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.39 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT40, ch9, 2.45 GHz - 2.50GHz



Fig.A.6.2.40 Transmitter Spurious Emission - Radiated (802.11n-HT40, ch9, 1 GHz-3 GHz)

©Copyright. All rights reserved by CTTL.

RE - 3GHz-18GHz



Fig.A.6.2.41 Transmitter Spurious Emission - Radiated (802.11n-HT40, ch9, 3 GHz-18 GHz)

©Copyright. All rights reserved by CTTL.

A.7. AC Power-line Conducted Emission

Method of Measurement: See ANSI C63.10-2013-clause 6.2

1 The one EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit is selected for the final measurement, while applying the appropriate modulating signal to the EUT.

2 If the EUT is relocated from an exploratory test site to a final test site, the highest emissions shall be remaximized at the final test location before final ac power-line conducted emission measurements are performed.

3 The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) is then performed for the full frequency range for which the EUT is being tested for compliance without further variation of the EUT arrangement, cable positions, or EUT mode of operation.

4 If the EUT is comprised of equipment units that have their own separate ac power connections, e.g., floor-standing equipment with independent power cords for each shelf that are able to connect directly to the ac power network, each current-carrying conductor of one unit is measured while the other units are connected to a second (or more) LISN(s). All units shall be separately measured. If a power strip is provided by the manufacturer, to supply all of the units making up the EUT, only the conductors in the power cord of the power strip shall be measured.

5 If the EUT uses a detachable antenna, these measurements shall be made with a suitable dummy load connected to the antenna output terminals; otherwise, the tests shall be made with the antenna connected and, if adjustable, fully extended. When measuring the ac conducted emissions from a device that operates between 150 kHz and 30 MHz a non-detachable antenna may be replaced with a dummy load for the measurements within the fundamental emission band of the transmitter, but only for those measurements.36 Record the six highest EUT emissions relative to the limit of each of the current-carrying conductors of the power cords of the equipment that comprises the EUT over the frequency range specified by the procuring or regulatory agency. Diagram or photograph the test setup that was used. See Clause 8 for full reporting requirements.

Test Condition:

Voltage（V）	Frequency（Hz）
120	60

©Copyright. All rights reserved by CTTL.

Measurement Result and limit:

WLAN (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	66 to 56	Fig.A.7.1	Fig.A.7.2	**P**
0.5 to 5	56			
5 to 30	60			
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.				

WLAN (Average Limit)

Frequency range (MHz)	Average Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	56 to 46	Fig.A.7.1	Fig.A.7.2	**P**
0.5 to 5	46			
5 to 30	50			
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.				

Conclusion: Pass

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.A.7.1 AC Powerline Conducted Emission-802.11b

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.600001	42.3	GND	N	10.3	13.7	56.0
0.663001	47.4	GND	N	10.3	8.6	56.0
2.112001	35.6	GND	N	10.3	20.4	56.0
14.127001	41.5	GND	N	10.6	18.5	60.0
14.608501	41.4	GND	N	10.6	18.6	60.0
16.260001	38.3	GND	N	10.6	21.7	60.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.600001	37.3	GND	L1	10.3	8.7	46.0
0.658501	42.0	GND	L1	10.3	4.0	46.0
1.257001	31.5	GND	L1	10.3	14.5	46.0
1.639501	31.2	GND	L1	10.4	14.8	46.0
2.031001	30.7	GND	L1	10.3	15.3	46.0
2.089501	31.0	GND	L1	10.3	15.0	46.0

©Copyright. All rights reserved by CTTL.



Fig.A.7.2 AC Powerline Conducted Emission-Idle

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.600001	44.2	GND	N	10.3	11.8	56.0
0.663001	46.6	GND	N	10.3	9.4	56.0
1.315501	38.1	GND	N	10.3	17.9	56.0
2.634001	38.1	GND	N	10.4	17.9	56.0
14.626501	43.0	GND	L1	10.6	17.0	60.0
14.932501	42.5	GND	L1	10.6	17.5	60.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.600001	37.1	GND	L1	10.3	8.9	46.0
0.658501	41.2	GND	L1	10.3	4.8	46.0
1.257001	31.4	GND	N	10.3	14.6	46.0
1.311001	28.5	GND	L1	10.3	17.5	46.0
1.639501	31.3	GND	L1	10.4	14.7	46.0
2.089501	30.6	GND	L1	10.3	15.4	46.0

©Copyright. All rights reserved by CTTL.