FCC PART 15C
TEST REPORT

BLUETOOTH LOW ENERGY (BLE) PART

No. I19Z61572-IOT02

for

TCL Communication Ltd.

UMTS/GSM mobile phone

Model Name: 3078A

FCC ID: 2ACCJH108

with

Hardware Version: PIO

Software Version: V1.0

Issued Date: 2019-9-11

TESTING
NVLAP LAB CODE 600118-0

Note:

The test results in this test report relate only to the devices specified in this report.This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No.52, HuayuanNorth Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512,Fax:+86(0)10-62304633-2504

Email:cttl_terminals@caict.ac.cn, website:www.caict.ac.cn

©Copyright. All rights reserved by CTTL.

REPORT HISTORY

Report Number	Revision	Description	Issue Date
I19Z61572-IOT02	Rev.0	1st edition	2019-9-11

©Copyright. All rights reserved by CTTL.

CONTENTS

1. TEST LABORATORY.....5

1.1. INTRODUCTION &ACCREDITATION.....5
1.2. TESTING LOCATION.....5
1.3. TESTING ENVIRONMENT.....6
1.4. PROJECT DATA.....6
1.5. SIGNATURE.....6

2. CLIENT INFORMATION.....7

2.1. APPLICANT INFORMATION.....7
2.2. MANUFACTURER INFORMATION.....7

3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE).....8

3.1. ABOUT EUT.....8
3.2. INTERNAL IDENTIFICATION OF EUT.....8
3.3. INTERNAL IDENTIFICATION OF AE.....8
3.4. NORMAL ACCESSORY SETTING.....8
3.5. GENERAL DESCRIPTION.....9

3.6. EUT SET-UPS.....9

4. REFERENCE DOCUMENTS.....10

4.1. DOCUMENTS SUPPLIED BY APPLICANT.....10
4.2. REFERENCE DOCUMENTS FOR TESTING.....10

5. TEST RESULTS.....11

5.1. SUMMARY OF TEST RESULTS.....11
5.2. STATEMENTS.....11
5.3. EXPLANATION OF RE-USE OF TEST DATA.....11

6. TEST FACILITIES UTILIZED.....12

7. MEASUREMENT UNCERTAINTY.....13

7.1. PEAK OUTPUT POWER - CONDUCTED.....13
7.2. FREQUENCY BAND EDGES.....13
7.3. TRANSMITTER SPURIOUS EMISSION - CONDUCTED.....13
7.4. TRANSMITTER SPURIOUS EMISSION - RADIATED.....13
7.5. 6DB BANDWIDTH.....13
7.6. MAXIMUM POWER SPECTRAL DENSITY LEVEL.....13
7.7. AC POWERLINE CONDUCTED EMISSION.....14

ANNEX A: DETAILED TEST RESULTS.....15

A.1. MEASUREMENT METHOD.....15
A.2. PEAK OUTPUT POWER - CONDUCTED.....16
A.3. FREQUENCY BAND EDGES - CONDUCTED.....17

©Copyright. All rights reserved by CTTL.

A.4. TRANSMITTER SPURIOUS EMISSION - CONDUCTED..... 19
A.5. TRANSMITTER SPURIOUS EMISSION - RADIATED..... 28
A.6. 6DB BANDWIDTH.....32
A.7. MAXIMUM POWER SPECTRAL DENSITY LEVEL..... 35
A.8. AC POWERLINE CONDUCTED EMISSION.....38

ANNEX E: ACCREDITATION CERTIFICATE.....43

©Copyright. All rights reserved by CTTL.

1. Test Laboratory

1.1. Introduction &Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP)with lab code600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

1.2. Testing Location

Conducted testing Location: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China100191

Radiated testing Location: CTTL(BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology Development Area, Beijing, P. R. China 100176

©Copyright. All rights reserved by CTTL.

1.3. Testing Environment

Normal Temperature: 15-35℃

Relative Humidity: 20-75%

1.4. Project data

Testing Start Date: 2019-8-1

Testing End Date: 2019-9-5

1.5. Signature

Wu Le

(Prepared this test report)

Sun Zhenyu

(Reviewed this test report)

Li Zhuofang

(Approved this test report)

©Copyright. All rights reserved by CTTL.

2. Client Information

2.1. Applicant Information

Company Name:	TCL Communication Ltd.
Address /Post:	7/F, Block F4, TCL Communication Technology Building, TCL International E City, Zhong Shan Yuan Road, Nanshan District, Shenzhen, Guangdong, P.R. China 518052
City:	Shenzhen
Postal Code:	518052
Country:	China
Telephone:	0086-755-36611722
Fax:	0086-755-36612000-81722

2.2. Manufacturer Information

Company Name:	TCL Communication Ltd.
Address /Post:	7/F, Block F4, TCL Communication Technology Building, TCL International E City, Zhong Shan Yuan Road, Nanshan District, Shenzhen, Guangdong, P.R. China 518052
City:	Shenzhen
Postal Code:	518052
Country:	China
Telephone:	0086-755-36611722
Fax:	0086-755-36612000-81722

©Copyright. All rights reserved by CTTL.

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	UMTS/GSM mobile phone
Model Name	3078A
FCC ID	2ACCJH108
Frequency Band	ISM 2400MHz~2483.5MHz
Type of Modulation(LE mode)	GFSK (Bluetooth Low Energy)
Number of Channels(LE mode)	40
Power Supply	3.8V DC by Battery

3.2. Internal Identification of EUT

EUT ID*	SN or IMEI	HW Version	SW Version
EUT2	/	PIO	V1.0
EUT3	358937100000356	PIO	V1.0

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE

AE ID*	Description	Note
AE1	Battery	inbuilt
AE3	Charger	CH004
AE4	Charger	CH001

AE1

Model	CAB1000012CA
Manufacturer	TIANMAO
Capacitance	1000mAh
Nominal voltage	4.2V

AE3

Model	CBA0066AGAC5
Manufacturer	PUAN
Length of cable	/

AE4

Model	CBA0066AGAC7
Manufacturer	CHENYANG
Length of cable	/

*AE ID: is used to identify the test sample in the lab internally.

3.4. Normal Accessory setting

Fully charged battery is used during the test.

©Copyright. All rights reserved by CTTL.

3.5. General Description

The Equipment Under Test (EUT) is a model of UMTS/GSM mobile phone with integrated antenna. It consists of normal options: lithium battery, charger. Manual and specifications of the EUT were provided to fulfill the test. Samples undergoing test were selected by the Client.

3.6. EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.3	EUT2+ AE1+ AE3	Charger
Set.4	EUT2+ AE1+ AE4	Charger

©Copyright. All rights reserved by CTTL.

4. Reference Documents

4.1. Documents supplied by applicant

EUT feature information is supplied by the client or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part15	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902–928MHz, 2400–2483.5 MHz, and 5725–5850 MHz.	2018
ANSI C63.10	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices	June,2013

©Copyright. All rights reserved by CTTL.

5. Test Results

5.1. Summary of Test Results

Abbreviations used in this clause:

P Pass, The EUT complies with the essential requirements in the standard.

F Fail, The EUT does not comply with the essential requirements in the standard

NA Not Applicable, The test was not applicable

NP Not Performed, The test was not performed by CTTL

R Re-use test data from basic model report.

SUMMARY OF MEASUREMENT RESULTS	Sub-clause	Verdict
6dB Bandwidth	15.247 (a)(2)	**R**
Peak Output Power - Conducted	15.247 (b)(1)	**P**
Maximum Power Spectral Density Level	15.247(e)	**R**
Transmitter Spurious Emission - Conducted	15.247 (d)	**R**
Transmitter Spurious Emission - Radiated	15.247, 15.205, 15.209	**R**
Frequency Band Edges	15.247 (d)	**R**
AC Powerline Conducted Emission	15.107, 15.207	**R**

Please refer to **ANNEX A** for detail.

The measurement is made according to ANSI C63.10.

5.2. Statements

CTTL has evaluated the test cases requested by the applicant /manufacturer as listed in section 5.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.2

5.3. Explanation of re-use of test data

The Equipment Under Test (EUT) model 3078A(FCC ID: 2ACCJH108) is a variant product of 3078G(FCC ID: 2ACCJH109), according to the declaration of changes provided by the applicant and FCC KDB publication 484596 D01, spot check measurements(Peak Output Power-Conducted) were performed on this device, other test results are derived from test report No. I19Z61432-IOT02. Please refer Annex A for detail spot check verification data and reference data. the spot check test results are consistent with basic model.

For detail differences between two models please refer the Declaration of Changes document.

©Copyright. All rights reserved by CTTL.

6. Test Facilities Utilized

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSQ26	200136	Rohde & Schwarz	1 year	2019-11-21
2	LISN	ENV216	101459	Rohde & Schwarz	1 year	2020-04-10
3	Test Receiver	ESCI	100344	Rohde & Schwarz	1 year	2020-02.14
4	Shielding Room	S81	/	ETS-Lindgren	/	/

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESU26	100376	Rohde & Schwarz	1 year	2019-11-27
2	BiLog Antenna	VULB9163	514	Schwarzbeck	1 yea	2020-02-03
3	Dual-Ridge Waveguide Horn Antenna	3117	00139065	ETS-Lindgren	1 year	2019-11-05
4	Dual-Ridge Waveguide Horn Antenna	3116	2663	ETS-Lindgren	1 year	2020-05-31
5	Vector Signal Analyzer	FSV	101047	Rohde & Schwarz	1 year	2020-06-16

©Copyright. All rights reserved by CTTL.

7. Measurement Uncertainty

7.1. Peak Output Power - Conducted

Measurement Uncertainty:

Measurement Uncertainty (k=2)	0.66dB

7.2. Frequency Band Edges

Measurement Uncertainty:

Measurement Uncertainty (k=2)	0.66dB

7.3. Transmitter Spurious Emission - Conducted

Measurement Uncertainty:

Frequency Range	Uncertainty (k=2)
30 MHz ~ 8 GHz	1.22dB
8 GHz ~ 12.75 GHz	1.51dB
12.7GHz ~ 26 GHz	1.51dB

7.4. Transmitter Spurious Emission - Radiated

Measurement Uncertainty:

Frequency Range	Uncertainty (k=2)
＜ 1 GHz	4.86dB
＞ 1 GHz	5.26dB

7.5. 6dB Bandwidth

Measurement Uncertainty:

Measurement Uncertainty (k=2)	61.936Hz

7.6. Maximum Power Spectral Density Level

Measurement Uncertainty:

Measurement Uncertainty (k=2)	0.66dB

©Copyright. All rights reserved by CTTL.

7.7. AC Powerline Conducted Emission

Measurement Uncertainty:

Measurement Uncertainty (k=2)	3.38dB

©Copyright. All rights reserved by CTTL.

ANNEX A: Detailed Test Results

A.1. Measurement Method

A.1.1. Conducted Measurements

The measurement is made according to ANSI C63.10.

1). Connect the EUT to the test system correctly.

2). Set the EUT to the required work mode (Transmitter, receiver or transmitter & receiver).

3). Set the EUT to the required channel.

4). Set the EUT hopping mode (hopping or hopping off).

5). Set the spectrum analyzer to start measurement.

6). Record the values. Vector Signal Analyzer



A.1.2. Radiated Emission Measurements

The measurement is made according to ANSI C63.10.

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 1MHz;



©Copyright. All rights reserved by CTTL.

A.2. Peak Output Power - Conducted

Method of Measurement: See ANSI C63.10-clause 11.9.1.1

a) Set the RBW = 1 MHz.
b) Set VBW = 3 MHz.
c) Set span = 3 MHz.
d) Sweep time = auto couple.
e) Detector = peak.
f) Trace mode = max hold.
g) Allow trace to fully stabilize.
h) Use peak marker function to determine the peak amplitude level.

Measurement Limit:

Standard	Limit (dBm)
FCC Part 15.247(b)(1)	< 30

Spot check Measurement Results:

For GFSK

Channel No.	Frequency (MHz)	Peak Conducted Output Power (dBm)	Conclusion
0	2402	-4.03	P
19	2440	-3.90	P
39	2480	-4.59	P

Conclusion: PASS

Reference Measurement Results from basic model:

For GFSK

Channel No.	Frequency (MHz)	Peak Conducted Output Power (dBm)	Conclusion
0	2402	-3.95	P
19	2440	-3.09	P
39	2480	-3.34	P

Conclusion: PASS

©Copyright. All rights reserved by CTTL.

A.3. Frequency Band Edges - Conducted

Method of Measurement: See ANSI C63.10-clause 6.10.4

Connect the spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described below.

a) Set Span = 8MHz
b) Sweep Time: Auto
c) Set the RBW= 100 kHz
c) Set the VBW= 300 kHz
d) Detector: Peak
e) Trace: Max hold

Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not an absolute field strength measurement; it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.

Measurement Limit:

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	< -20

Measurement Result:

For GFSK

Channel No.	Frequency (MHz)	Hopping	Band Edge Power (dBc)		Conclusion
0	2402	Hopping OFF	Fig.1	-53.65	P
39	2480	Hopping OFF	Fig.2	-53.66	P

Conclusion: PASS

©Copyright. All rights reserved by CTTL.

Test graphs as below



Fig.1. Frequency Band Edges: GFSK, 2402 MHz, Hopping Off



Fig.2. Frequency Band Edges: GFSK, 2480 MHz, Hopping Off

©Copyright. All rights reserved by CTTL.

A.4. Transmitter Spurious Emission - Conducted

Method of Measurement: See ANSI C63.10-clause 11.11.2 and clause 11.11.3

Measurement Procedure – Reference Level

1. Set the RBW = 100 kHz.
2. Set the VBW = 300 kHz.
3. Set the span to ≥1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum PSD level. Next, determine the power in 100 kHz band segments outside of the authorized frequency band using the following measurement:

Measurement Procedure - Unwanted Emissions

1. Set RBW = 100 kHz.
2. Set VBW = 300 kHz.
3. Set span to encompass the spectrum to be examined.
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified above.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100 kHz bandwidth

©Copyright. All rights reserved by CTTL.

Measurement Results:

For GFSK

Channel No.	Frequency (MHz)	Frequency Range	Test Results	Conclusion
0	2402	Center Frequency	Fig.3	P
		30 MHz ~ 1 GHz	Fig.4	P
		1 GHz ~ 3 GHz	Fig.5	P
		3 GHz ~ 10 GHz	Fig.6	P
		10GHz ~ 26 GHz	Fig.7	P
19	2440	Center Frequency	Fig.8	P
		30 MHz ~ 1 GHz	Fig.9	P
		1 GHz ~ 3 GHz	Fig.10	P
		3 GHz ~ 10 GHz	Fig.11	P
		10GHz ~ 26 GHz	Fig.12	P
39	2480	Center Frequency	Fig.13	P
		30 MHz ~ 1 GHz	Fig.14	P
		1 GHz ~ 3GHz	Fig.15	P
		3 GHz ~ 10 GHz	Fig.16	P
		10 GHz ~ 26 GHz	Fig.17	P

Conclusion: PASS

Test graphs as below

Fig.3. Transmitter Spurious Emission - Conducted: GFSK,2402MHz

©Copyright. All rights reserved by CTTL.



Fig.4. Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz, 30MHz - 1GHz



Fig.5. Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz,1GHz - 3GHz

©Copyright. All rights reserved by CTTL.



Fig.6. Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz,3GHz - 10GHz



Fig.7. Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz,10GHz - 26GHz

©Copyright. All rights reserved by CTTL.



Fig.8. Transmitter Spurious Emission - Conducted: GFSK, 2440MHz



Fig.9. Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 30MHz - 1GHz

©Copyright. All rights reserved by CTTL.



Fig.10. Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 1GHz – 3GHz



Fig.11. Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 3GHz – 10GHz

©Copyright. All rights reserved by CTTL.



Fig.12. Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 10GHz – 26GHz



Fig.13. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz

©Copyright. All rights reserved by CTTL.



Fig.14. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 30MHz - 1GHz



Fig.15. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 1GHz - 3GHz

©Copyright. All rights reserved by CTTL.



Fig.16. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 3GHz - 10GHz



Fig.17. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 10GHz - 26GHz

©Copyright. All rights reserved by CTTL.

A.5. Transmitter Spurious Emission - Radiated

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

The measurement is made according to ANSI C63.10

Limit in restricted band:

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Test Condition

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/1MHz	15
4000-18000	1MHz/1MHz	40
18000-26500	1MHz/1MHz	20

Measurement Results:

A "reference path loss" is established and the A_{Rpl} is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

Result=P_{Mea}+A_{Rpl}

For GFSK

Frequency	Frequency Range	Test Results	Conclusion
Power	2.38GHz~2.4GHz---L	Fig.18	P
Power	2.45GHz~2.5GHz---H	Fig.19	P

©Copyright. All rights reserved by CTTL.

GFSK 2402MHz–Average

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2386.500	46.44	2.9	32.0	11.62	54.0	7.6	H	155	8
2387.100	46.39	2.9	32.0	11.57	54.0	7.6	H	155	46
4804.500	33.10	-35.0	34.1	34.04	54.0	20.9	H	155	20
7206.000	39.34	-32.4	35.8	35.93	54.0	14.7	H	155	118
9607.500	40.93	-29.7	36.7	33.88	54.0	13.1	H	155	82
12010.500	42.32	-30.5	38.9	33.92	54.0	11.7	H	155	46

GFSK 2440MHz–Average

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2397.300	46.48	2.9	32.0	11.64	54.0	7.5	H	155	8
2408.000	46.51	2.9	32.0	11.67	54.0	7.5	H	155	56
4882.500	32.64	-35.5	34.1	34.09	54.0	21.4	H	155	139
7320.000	40.61	-31.4	35.8	36.19	54.0	13.4	H	155	108
9763.500	39.20	-31.4	36.9	33.69	54.0	14.8	H	155	78
12205.500	44.09	-28.9	39.0	33.97	54.0	9.9	H	155	36

GFSK 2480MHz–Average

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2483.500	46.65	2.9	32.0	11.72	54.0	7.4	H	155	268
2483.700	46.54	2.9	32.0	11.61	54.0	7.5	H	155	138
4960.500	33.62	-34.9	34.1	34.40	54.0	20.4	H	155	104
7440.000	39.70	-32.2	35.8	36.07	54.0	14.3	H	155	40
9919.500	41.21	-29.6	37.1	33.75	54.0	12.8	H	155	28
12400.500	43.37	-30.0	39.1	34.33	54.0	10.6	H	155	8

©Copyright. All rights reserved by CTTL.

GFSK 2402MHz–Peak

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2380.644	61.37	2.9	32.0	26.55	74.0	12.6	H	155	88
2388.554	60.50	2.9	32.0	25.68	74.0	13.5	H	155	132
4804.000	38.56	-35.0	34.1	39.50	74.0	35.4	H	155	0
7206.000	46.14	-32.4	35.8	42.73	74.0	27.9	V	155	66
9608.000	45.39	-29.7	36.7	38.32	74.0	28.6	V	155	44
12010.000	46.04	-30.5	38.9	37.63	74.0	28.0	H	155	242

GFSK 2440MHz–Peak

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2378.400	48.86	2.9	32.0	43.32	74.0	25.1	H	155	88
2512.400	49.09	3.0	32.0	43.62	74.0	24.9	H	155	66
4882.000	38.41	-35.5	34.1	39.86	74.0	35.6	H	155	110
7323.000	42.73	-31.3	35.8	38.24	74.0	31.3	V	155	0
9764.000	43.49	-31.4	36.9	37.98	74.0	30.5	H	155	22
12205.000	47.53	-28.8	39.0	37.39	74.0	26.5	H	155	44

GFSK 2480MHz–Peak

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)	Antenna Height (cm)	Turntable angle (deg)
2490.405	60.78	2.9	32.0	25.85	74.0	13.2	H	155	22
2498.080	60.48	2.9	32.0	25.54	74.0	13.5	H	155	22
4960.000	40.91	-34.9	34.1	41.70	74.0	33.1	H	155	88
7440.000	47.04	-32.2	35.8	43.42	74.0	27.0	V	155	110
9920.000	47.52	-29.7	37.1	40.07	74.0	26.5	V	155	44
12400.000	47.65	-30.0	39.1	38.63	74.0	26.4	H	155	0

Conclusion: PASS

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.18. Transmitter Spurious Emission - Radiated: GFSK, 2402MHz, 1 GHz - 3GHz



Fig.19. Transmitter Spurious Emission - Radiated: GFSK, 2402MHz, 3 GHz - 18 GHz

©Copyright. All rights reserved by CTTL.

A.6. 6dB Bandwidth

Method of Measurement:

The measurement is made according to ANSI C63.10 clause 11.8.1
1.Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) = 300 kHz.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a)(2)	>= 500KHz

Measurement Results:
For GFSK

Channel No.	Frequency (MHz)	6dB Bandwidth (kHz)		Conclusion
0	2402	Fig.20	691.00	P
19	2440	Fig.21	689.00	P
39	2480	Fig.22	697.00	P

Conclusion: PASS
Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.20. 6dB Bandwidth: GFSK, 2402 MHz



Fig.21. 6dB Bandwidth: GFSK, 2440 MHz

©Copyright. All rights reserved by CTTL.



Fig.22. 6dB Bandwidth: GFSK, 2480 MHz

©Copyright. All rights reserved by CTTL.

A.7. Maximum Power Spectral Density Level

Method of Measurement:

The measurement is made according to ANSI C63.10 clause 11.10.2

1. Set the RBW = 3 kHz.
2. Set the VBW = 10 kHz.
3. Set the span to 2 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(e)	<=8.0dBm/3kHz

Measurement Results:

For GFSK

Channel No.	Frequency (MHz)	Maximum Power Spectral Density Level(dBm/3kHz)		Conclusion
0	2402	Fig.23	-19.36	P
19	2440	Fig.24	-18.78	P
39	2480	Fig.25	-18.45	P

Test graphs as below:

©Copyright. All rights reserved by CTTL.



Fig.23. Maximum Power Spectral Density Level Function: GFSK, 2402 MHz



Fig.24. Maximum Power Spectral Density Level Function: GFSK, 2440 MHz

©Copyright. All rights reserved by CTTL.



Fig.25. Maximum Power Spectral Density Level Function: GFSK, 2480 MHz

©Copyright. All rights reserved by CTTL.

A.8. AC Powerline Conducted Emission

Method of Measurement: See ANSI C63.10-clause 6.2

1. the one EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit is selected for the final measurement, while applying the appropriate modulating signal to the EUT.
2. If the EUT is relocated from an exploratory test site to a final test site, the highest emissions shall be remaximized at the final test location before final ac power-line conducted emission measurements are performed.
3. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) is then performed for the full frequency range for which the EUT is being tested for compliance without further variation of the EUT arrangement, cable positions, or EUT mode of operation.
4. If the EUT is comprised of equipment units that have their own separate ac power connections, e.g., floor-standing equipment with independent power cords for each shelf that are able to connect directly to the ac power network, each current-carrying conductor of one unit is measured while the other units are connected to a second (or more) LISN(s). All units shall be separately measured. If a power strip is provided by the manufacturer, to supply all of the units making up the EUT, only the conductors in the power cord of the power strip shall be measured.
5. If the EUT uses a detachable antenna, these measurements shall be made with a suitable dummy load connected to the antenna output terminals; otherwise, the tests shall be made with the antenna connected and, if adjustable, fully extended. When measuring the ac conducted emissions from a device that operates between 150 kHz and 30 MHz a non-detachable antenna may be replaced with a dummy load for the measurements within the fundamental emission band of the transmitter, but only for those measurements.36 Record the six highest EUT emissions relative to the limit of each of the current-carrying conductors of the power cords of the equipment that comprises the EUT over the frequency range specified by the procuring or regulatory agency. Diagram or photograph the test setup that was used. See Clause 8 for full reporting requirements.

Test Condition

Voltage（V）	Frequency（Hz）
120	60

Measurement Result and limit:

Bluetooth (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Conclusion
0.15 to 0.5	66 to 56	P
0.5 to 5	56	
5 to 30	60	
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.		

©Copyright. All rights reserved by CTTL.

Bluetooth (Average Limit)

Frequency range (MHz)	Average Limit (dBμV)	Conclusion
0.15 to 0.5	56 to 46	P
0.5 to 5	46	
5 to 30	50	
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.		

The measurement is made according to ANSI C63.10

Conclusion: PASS

Test graphs as below:

©Copyright. All rights reserved by CTTL.

Set.3, Traffic:



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.172500	52.6	2000.0	9.000	On	L1	25.8	12.2	64.8
0.433500	49.0	2000.0	9.000	On	L1	19.8	8.2	57.2
1.234500	45.3	2000.0	9.000	On	L1	19.6	10.7	56.0
1.720500	46.5	2000.0	9.000	On	L1	19.6	9.5	56.0
2.746500	48.2	2000.0	9.000	On	L1	19.6	7.8	56.0
3.646500	47.5	2000.0	9.000	On	L1	19.6	8.5	56.0

Final Result 2

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.429000	37.9	2000.0	9.000	On	L1	19.8	9.4	47.3
0.447000	41.0	2000.0	9.000	On	L1	19.8	6.0	46.9
1.248000	31.8	2000.0	9.000	On	L1	19.6	14.2	46.0
1.878000	38.0	2000.0	9.000	On	L1	19.6	8.0	46.0
2.832000	39.0	2000.0	9.000	On	L1	19.6	7.0	46.0
3.741000	37.0	2000.0	9.000	On	L1	19.6	9.0	46.0

©Copyright. All rights reserved by CTTL.

Set.3, Idle:



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.429000	48.7	2000.0	9.000	On	L1	19.8	8.6	57.3
0.438000	50.3	2000.0	9.000	On	L1	19.8	6.8	57.1
0.829500	45.4	2000.0	9.000	On	L1	19.7	10.6	56.0
2.103000	46.1	2000.0	9.000	On	L1	19.6	9.9	56.0
3.237000	48.2	2000.0	9.000	On	L1	19.6	7.8	56.0
3.678000	47.5	2000.0	9.000	On	L1	19.6	8.5	56.0

Final Result 2

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.429000	39.3	2000.0	9.000	On	L1	19.8	8.0	47.3
0.438000	41.4	2000.0	9.000	On	L1	19.8	5.7	47.1
1.239000	37.0	2000.0	9.000	On	L1	19.6	9.0	46.0
2.103000	35.4	2000.0	9.000	On	L1	19.6	10.6	46.0
2.836500	38.6	2000.0	9.000	On	L1	19.6	7.4	46.0
3.678000	36.9	2000.0	9.000	On	L1	19.6	9.1	46.0

©Copyright. All rights reserved by CTTL.

Set.4, Traffic:



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.393000	42.8	2000.0	9.000	On	L1	19.8	15.2	58.0
0.433500	43.7	2000.0	9.000	On	L1	19.8	13.5	57.2
1.176000	44.4	2000.0	9.000	On	L1	19.7	11.6	56.0
2.031000	42.5	2000.0	9.000	On	L1	19.6	13.5	56.0
3.043500	44.6	2000.0	9.000	On	L1	19.6	11.4	56.0
3.975000	44.7	2000.0	9.000	On	L1	19.6	11.3	56.0

Final Result 2

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.393000	40.9	2000.0	9.000	On	N	19.8	7.1	48.0
0.433500	32.3	2000.0	9.000	On	N	19.8	14.9	47.2
0.784500	38.1	2000.0	9.000	On	N	19.7	7.9	46.0
1.612500	32.7	2000.0	9.000	On	L1	19.6	13.3	46.0
3.133500	35.5	2000.0	9.000	On	L1	19.6	10.5	46.0
4.024500	34.8	2000.0	9.000	On	L1	19.6	11.2	46.0

©Copyright. All rights reserved by CTTL.

ANNEX E: Accreditation Certificate

United States Department of Commerce
National Institute of Standards and Technology

NVLAP®

Certificate of Accreditation to ISO/IEC 17025:2005

NVLAP LAB CODE: 600118-0

Telecommunication Technology Labs, CAICT
Beijing
China

is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:

Electromagnetic Compatibility & Telecommunications

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).

2018-09-28 through 2019-09-30
Effective Dates

For the National Voluntary Laboratory Accreditation Program

*****END OF REPORT*****

©Copyright. All rights reserved by CTTL.