TEST REPORT

No. I22Z61676-WMD01

for

TCL Communication Ltd.

GSM/UMTS/LTE mobile phone

Model Name: T430W

FCC ID: 2ACCJH167

with

Hardware Version: 03

Software Version: UGS4

Issued Date: 2022-10-19

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: cttl_terminals@caict.ac.cn, website: www.caict.ac.cn

©Copyright. All rights reserved by CTTL.

REPORT HISTORY

Report Number	Revision	Description	Issue Date
I22Z61676-WMD01	Rev.0	1st edition	2022-10-02
I22Z61676-WMD01	Rev.1	2nd edition. Update the Output power in section 3.1.Update the PCS1900-EIRP in section A1.3.2.	2022-10-19

Note: the latest revision of the test report supersedes all previous version.

©Copyright. All rights reserved by CTTL.

CONTENTS

1. TEST LABORATORY 4
1.1. INTRODUCTION & ACCREDITATION 4
1.2. TESTING LOCATION 4
1.3. TESTING ENVIRONMENT 5
1.4. PROJECT DATA 5
1.5. SIGNATURE 5
2. CLIENT INFORMATION 6
2.1. APPLICANT INFORMATION 6
2.2. MANUFACTURER INFORMATION 6
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) 7
3.1. ABOUT EUT 7
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST 7
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST 7
4. REFERENCE DOCUMENTS 8
4.1. DOCUMENTS SUPPLIED BY APPLICANT 8
4.2. REFERENCE DOCUMENTS FOR TESTING 8
5. LABORATORY ENVIRONMENT 9
6. SUMMARY OF TEST RESULT 10
7. TEST EQUIPMENTS UTILIZED 11
ANNEX A: MEASUREMENT RESULTS 12
A.1 OUTPUT POWER 12
A.2 EMISSION LIMIT 17
A.3 FREQUENCY STABILITY 22
A.4 OCCUPIED BANDWIDTH 24
A.5 EMISSION BANDWIDTH 37
A.6 BAND EDGE COMPLIANCE 50
A.7 CONDUCTED SPURIOUS EMISSION 55
A.8 PEAK-TO-AVERAGE POWER RATIO 60
ANNEX B: ACCREDITATION CERTIFICATE 61

©Copyright. All rights reserved by CTTL.

1. Test Laboratory

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2017 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0 and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

1.2. Testing Location

Location 1: CTTL (huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191

Location 2: CTTL (BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology Development Area, Beijing, P. R. China 100176

©Copyright. All rights reserved by CTTL.

1.3. Testing Environment

Normal Temperature: 15-35℃

Relative Humidity: 20-75%

1.4. Project Data

Testing Start Date: 2022-08-31

Testing End Date: 2022-10-01

1.5. Signature

Dong Yuan

(Prepared this test report)

Zhou Yu

(Reviewed this test report)

Zhao Hui Lin

Deputy Director of the laboratory

(Approved this test report)

©Copyright. All rights reserved by CTTL.

2. Client Information

2.1. Applicant Information

Company Name:	TCL Communication Ltd.
Address /Post:	5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong
Contact:	Annie Jiang
Email:	nianxiang.jiang@tcl.com
Telephone:	+86 755 3661 1621
Fax:	+86 755 3661 2000-81722

2.2. Manufacturer Information

Company Name:	TCL Communication Ltd.
Address /Post:	5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong
Contact:	Annie Jiang
Email:	nianxiang.jiang@tcl.com
Telephone:	+86 755 3661 1621
Fax:	+86 755 3661 2000-81722

©Copyright. All rights reserved by CTTL.

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	GSM/UMTS/LTE mobile phone
Model Name	T430W
FCC ID	2ACCJH167
Antenna	Embedded
Output power	28.17dBm maximum ERP measured for PCS1900
Extreme vol. Limits	3.5VDC to 4.4VDC (nominal: 3.85VDC)
Extreme temp. Tolerance	-10°C to +55°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL.

3.2. Internal Identification of EUT used during the test

EUT ID*	IMEI	HW Version	SW Version	Date of receipt
UT29a	016298000000770	03	UGS4	2022-08-31
UT43a	016298000001299	03	UGS4	2022-08-31

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description
AE1	Battery
AE2	Battery

AE1

Model	TLi028C7
Manufacturer	NINGBO VEKEN BATTERY CO., LTD.
Capacitance	3000mAh

AE2

Model	TLi028C1
Manufacturer	Shenzhen BYD Lithium Battery Company Limited
Capacitance	3000mAh

*AE ID: is used to identify the test sample in the lab internally.

©Copyright. All rights reserved by CTTL.

4. Reference Documents

4.1. Documents supplied by applicant

EUT parameters are supplied by the customer, which are the bases of testing. CAICT is not responsible for the accuracy of customer supplied technical information that may affect the test results (for example, antenna gain and loss of customer supplied cable).

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-21 Edition
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	10-1-21 Edition
ANSI/TIA-603-E	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2016
ANSI C63.26	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services	2015
KDB 971168 D01	MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS	v03r01

©Copyright. All rights reserved by CTTL.

5. Laboratory Environment

Fully-anechoic chamber FAC-3 (9 meters×6.5 meters×4 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 ˚C, Max. = 35 ˚C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

©Copyright. All rights reserved by CTTL.

6. Summary Of Test Result

GSM850

Items	List	Clause in FCC rules	Verdict
1	Output Power	22.913	P
2	Emission Limit	2.1051/22.917	P
3	Frequency Stability	2.1055	P
4	Occupied Bandwidth	2.1049	P
5	Emission Bandwidth	22.917	P
6	Band Edge Compliance	22.917	P
7	Conducted Spurious Emission	22.917	P

PCS1900

Items	List	Clause in FCC rules	Verdict
1	Output Power	24.232	P
2	Emission Limit	2.1051/24.238	P
3	Frequency Stability	2.1055	P
4	Occupied Bandwidth	2.1049	P
5	Emission Bandwidth	24.238	P
6	Band Edge Compliance	24.238	P
7	Conducted Spurious Emission	24.238	P
8	Peak-to-Average Power Ratio	24.232	P

Terms used in Verdict column

P	Pass. The EUT complies with the essential requirements in the standard.
NP	Not Performed. The test was not performed by CTTL.
NA	Not Applicable. The test was not applicable.
BR	Re-use test data from basic model report.
F	Fail. The EUT does not comply with the essential requirements in the standard.

All the test results are based on normal power.

Explanation of worst-case configuration

The worst-case scenario for all measurements is based on the conducted output power measurement investigation results unless otherwise stated. The test results shown in the following sections represent the worst case emission.

©Copyright. All rights reserved by CTTL.

7. Test Equipments Utilized

Description	Type	Series Number	Manufacture	Cal Due Date	Calibration Interval
Universal Radio Communication Tester	CMU200	108646	R&S	2023-01-17	25 months
Spectrum Analyzer	FSU	200030	R&S	2023-05-25	1 year
Climate chamber	SH-242	93008556	ESPEC	2023-12-23	3 years
Test Receiver	E4440A	MY48250642	Agilent	2023-03-10	1 year
Universal Radio Communication Tester	CMW500	143008	R&S	2022-12-01	1 year
EMI Antenna	VULB9163	9163-482	Schwarzbeck	2022-11-16	1 year
Signal Generator	SMF100A	101295	R&S	2022-12-23	1 year
EMI Antenna	LB-7180-NF	J203001300005	A-INFO	2023-02-23	1 year
EMI Antenna	3117	00058889	ETS-Lindgren	2022-11-07	1 year

©Copyright. All rights reserved by CTTL.

Annex A: Measurement Results

A.1 Output Power

A.1.1 Summary

During the process of testing, the EUT was controlled via communication tester to ensure max power transmission and proper modulation.

In all cases, output power is within the specified limits.

A.1.2 Conducted

A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

These measurements were done at 3 frequencies (bottom, middle and top of operational frequency range) for each bandwidth.

The results below include a correction factor for cable loss that is provided by the customer.

A.1.2.2 Measurement Result

GSM850

GSM(GMSK)

Frequency (MHz)	Power Step	Output power (dBm)
824.2	5	32.20
836.6	5	32.33
848.8	5	32.39

GPRS(GMSK,1Slot)

Frequency (MHz)	Power Step	Output power (dBm)
824.2	3	32.13
836.6	3	32.19
848.8	3	32.22

EGPRS(8PSK,1Slot)

Frequency (MHz)	Power Step	Output power (dBm)
824.2	6	25.80
836.6	6	25.81
848.8	6	26.14

©Copyright. All rights reserved by CTTL.

PCS1900

GSM(GMSK)

Frequency (MHz)	Power Step	Output power (dBm)
1850.2	0	29.44
1880.0	0	29.24
1909.8	0	29.11

GPRS(GMSK,1Slot)

Frequency (MHz)	Power Step	Output power (dBm)
1850.2	3	29.71
1880.0	3	29.58
1909.8	3	29.48

EGPRS(8PSK,1Slot)

Frequency (MHz)	Power Step	Output power (dBm)
1850.2	5	25.93
1880.0	5	25.68
1909.8	5	25.78

©Copyright. All rights reserved by CTTL.

A.1.3 Radiated

A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.

Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts".

Part 24.232(c) specifies "Mobile and portable stations are limited to 2 watts EIRP".

A.1.3.2 Method of Measurement

According to KDB 412172 D01 and ANSI C63.26 the relevant equation for determining the maximum ERP or EIRP from the measured RF output power is given in Equation as follows:

ERP or EIRP = $P_T + G_T – L_C$, ERP = EIRP -2.15, where

ERP or EIRP effective radiated power or equivalent isotropically radiated power, respectively (expressed in the same units as P_{Mea} , e.g., dBm or dBW)

P_T = transmitter output power in dBm;

G_T = gain of the transimitting antenna, in dBd(ERP) or dBi(EIRP);

1. L_C = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

The antenna gain provided by the client may affect the validity of the measurement results in this report, and the client shall bear the impact and consequences arising therefrom.

©Copyright. All rights reserved by CTTL.

GSM 850-ERP

Limits

	Power Step	Burst Peak ERP (dBm)
GSM	5	≤38.45dBm (7W)
GPRS	3	≤38.45dBm (7W)
EGPRS	6	≤38.45dBm (7W)

Measurement result

GSM(GMSK)

Frequency (MHz)	Power Step	Output power Conducted (dBm)	Output power Radiated(dBm) (G_T – L_C = -3.49)
824.2	5	32.20	26.56
836.6	5	32.33	26.69
848.8	5	32.39	26.75

GPRS(GMSK,1Slot)

Frequency (MHz)	Power Step	Output power Conducted (dBm)	Output power Radiated(dBm) (G_T – L_C = -3.49)
824.2	3	32.13	26.49
836.6	3	32.19	26.55
848.8	3	32.22	26.58

EGPRS(8PSK,1Slot)

Frequency (MHz)	Power Step	Output power Conducted (dBm)	Output power Radiated(dBm) (G_T – L_C = -3.49)
824.2	6	25.80	20.16
836.6	6	25.81	20.17
848.8	6	26.14	20.50

©Copyright. All rights reserved by CTTL.

PCS1900-EIRP

Limits

	Power Step	Burst Peak EIRP (dBm)
GSM	0	≤33dBm (2W)
GPRS	3	≤33dBm (2W)
EGPRS	5	≤33dBm (2W)

Measurement result

GSM

Frequency (MHz)	Power Step	Output power Conducted (dBm)	Output power Radiated(dBm) (G_T – L_C = -1.54)
1850.2	0	29.44	27.90
1880.0	0	29.24	27.70
1909.8	0	29.11	27.57

GPRS

Frequency (MHz)	Power Step	Output power Conducted (dBm)	Output power Radiated(dBm) (G_T – L_C = -1.54)
1850.2	3	29.71	28.17
1880.0	3	29.58	28.04
1909.8	3	29.48	27.94

EGPRS-8PSK

Frequency (MHz)	Power Step	Output power Conducted (dBm)	Output power Radiated(dBm) (G_T – L_C = -1.54)
1850.2	5	25.93	24.39
1880.0	5	25.68	24.14
1909.8	5	25.78	24.24

Note: Expanded measurement uncertainty is U = 0.578 dB, k = 2.

©Copyright. All rights reserved by CTTL.

A.2 Emission Limit

A.2.1 Measurement Method

The measurement procedures in TIA-603E-2016 are used.

The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set as outlined in Part 24.238 and Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of PCS1900 and GSM850.

The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5-meter-high non-conductive stand at a 3-meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna and adjusts the level of the signal generator output until the value of the

©Copyright. All rights reserved by CTTL.

receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P_{pl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.
   A amplifier should be connected in for the test.
   The Path loss (P_{pl}) is the summation of the cable loss and the gain of the amplifier.
   The measurement results are obtained as described below:
   Power (EIRP) = P_{Mea} - P_{pl} - G_a
5. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi.

A.2.2 Measurement Limit

Part 22.917 and Part 24.238 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS1900 band (1850.2MHz, 1880MHz and 1909.8MHz) and GSM850 band (824.2MHz, 836.6MHz and 848.8MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900, GSM850 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

©Copyright. All rights reserved by CTTL.

A.2.4 Measurement Results Table

Frequency	Channel	Frequency Range	Result
GSM 850MHz	Low	30MHz-10GHz	Pass
	Middle	30MHz-10GHz	Pass
	High	30MHz-10GHz	Pass
GSM 1900MHz	Low	30MHz-20GHz	Pass
	Middle	30MHz-20GHz	Pass
	High	30MHz-20GHz	Pass

A.2.5 Sweep Table

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
850MHz	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
1900MHz	0.03~1	100KHz	300KHz	10
	1-2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

©Copyright. All rights reserved by CTTL.

GSM Mode Channel 128/824.2MHz

Frequency (MHz)	P_{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1638.01	-54.56	3.56	5.25	2.15	-55.02	-13.00	42.00	H
2472.00	-43.95	4.59	6.02	2.15	-44.67	-13.00	31.70	H
3297.02	-55.32	5.29	7.71	2.15	-55.05	-13.00	42.10	V
4123.02	-52.89	6.04	9.02	2.15	-52.06	-13.00	39.10	V
4940.01	-56.89	6.71	9.84	2.15	-55.91	-13.00	42.90	V
5782.01	-56.69	7.22	10.54	2.15	-55.52	-13.00	42.50	V

GSM Mode Channel 190/836.6MHz

Frequency (MHz)	P_{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1674.01	-49.86	3.58	5.19	2.15	-50.40	-13.00	37.40	V
2524.00	-42.46	4.65	6.14	2.15	-43.12	-13.00	30.10	H
3347.02	-45.97	5.32	7.83	2.15	-45.61	-13.00	32.60	H
4182.02	-53.40	6.17	9.08	2.15	-52.64	-13.00	39.60	V
5034.01	-57.48	6.59	9.95	2.15	-56.27	-13.00	43.30	V
5854.01	-56.64	7.25	10.53	2.15	-55.51	-13.00	42.50	V

GSM Mode Channel 251/848.8MHz

Frequency (MHz)	P_{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1696.01	-53.85	3.60	5.15	2.15	-54.45	-13.00	41.40	H
2546.00	-42.61	4.66	6.18	2.15	-43.24	-13.00	30.20	H
3395.02	-50.19	5.36	7.95	2.15	-49.75	-13.00	36.80	H
4261.02	-57.56	6.23	9.16	2.15	-56.78	-13.00	43.80	V
5094.01	-55.74	6.76	10.03	2.15	-54.62	-13.00	41.60	H
5933.01	-56.61	7.47	10.51	2.15	-55.72	-13.00	42.70	V

©Copyright. All rights reserved by CTTL.

GSM Mode Channel 512/1850.2MHz

Frequency (MHz)	P_{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3700.02	-52.33	6.43	8.48	-50.28	-13.00	37.28	H
5551.02	-53.30	7.18	10.59	-49.89	-13.00	36.89	V
7401.01	-53.62	8.12	12.08	-49.66	-13.00	36.66	H
9254.01	-52.41	9.05	13.25	-48.21	-13.00	35.21	V
11106.01	-46.36	9.81	13.18	-42.99	-13.00	29.99	H
12956.01	-47.97	10.48	13.47	-44.98	-13.00	31.98	H

GSM Mode Channel 661/1880.0MHz

Frequency (MHz)	P_{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.02	-53.88	6.26	8.56	-51.58	-13.00	38.58	H
5640.02	-54.09	7.27	10.57	-50.79	-13.00	37.79	V
7505.01	-54.22	8.37	12.20	-50.39	-13.00	37.39	V
9404.01	-52.05	9.06	13.34	-47.77	-13.00	34.77	V
11280.01	-49.23	9.88	13.14	-45.97	-13.00	32.97	H
13165.01	-44.69	10.65	13.73	-41.61	-13.00	28.61	V

GSM Mode Channel 810/1909.8MHz

Frequency (MHz)	P_{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3820.02	-55.23	6.08	8.65	-52.66	-13.00	39.66	H
5729.02	-53.36	7.29	10.55	-50.10	-13.00	37.10	H
7637.01	-55.29	8.14	12.31	-51.12	-13.00	38.12	H
9554.01	-53.20	9.35	13.35	-49.20	-13.00	36.20	V
11452.01	-49.81	9.93	13.11	-46.63	-13.00	33.63	V
13365.01	-44.77	10.57	14.01	-41.33	-13.00	28.33	V

Note1: Expanded measurement uncertainty is U = 5.16 dB, k = 2.

Note2: The measurement results showed here are worst cases.

©Copyright. All rights reserved by CTTL.

A.3 Frequency Stability

A.3.1 Method of Measurement

Frequency stability is a measure of the frequency drift due to temperature and supply voltage variations, with reference to the frequency measured at +20 °C and rated supply voltage. Two reference points are established at the applicable unwanted emissions limit using a RBW equal to the RBW required by the unwanted emissions specification of the applicable regulatory standard. These reference points measured using the lowest and highest channel of operation shall be identified as F_L and F_H respectively.

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of CMU200.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30℃.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on mid channel of each band, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10℃ increments from -30℃ to +50℃. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50℃.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10℃ decrements from +50℃ to -30℃. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5℃ during the measurement procedure.

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of the lower, higher and nominal voltage. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress.

©Copyright. All rights reserved by CTTL.

A.3.2 Measurement results

GSM 850

Frequency Error vs Temperature

Temperature(℃)	Voltage(V)	F_L(MHz)	F_H(MHz)	Offset(Hz)	Frequency error(ppm)
20	3.85	824.030	848.971		
50				-0.45	0.0005
40				3.55	0.0042
30				4.46	0.0053
10				1.81	0.0022
0				0.71	0.0008
-10				-3.62	0.0043
-20				-2.97	0.0036
-30				-3.55	0.0042

Frequency Error vs Voltage

Voltage(V)	Temperature(℃)	F_L(MHz)	F_H(MHz)	Offset(Hz)	Frequency error(ppm)
3.5	20	824.030	848.971	0.52	0.0006
4.4				-2.20	0.0026

PCS 1900

Frequency Error vs Temperature

Temperature(℃)	Voltage(V)	F_L(MHz)	F_H(MHz)	Offset(Hz)	Frequency error(ppm)
20	3.85	1850.035	1909.962		
50				3.94	0.0021
40				2.65	0.0014
30				7.69	0.0041
10				3.75	0.0020
0				0.52	0.0003
-10				-7.10	0.0038
-20				-7.10	0.0038
-30				-24.21	0.0129

Frequency Error vs Voltage

Voltage(V)	Temperature(℃)	F_L(MHz)	F_H(MHz)	Offset(Hz)	Frequency error(ppm)
3.5	20	1850.035	1909.962	0.84	0.0004
4.4				4.84	0.0026

Note: Expanded measurement uncertainty is U = 0.01 PPM, k = 2.

©Copyright. All rights reserved by CTTL.

A.4 Occupied Bandwidth

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequency. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.
The measurement method is from ANSI C63.26:
a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts.
b) The nominal IF filter 3 dB bandwidth (RBW) shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set ≥ 3 × RBW.
c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation.
d) Set the detection mode to peak, and the trace mode to max-hold.

©Copyright. All rights reserved by CTTL.

GSM 850 (99%)

Frequency (MHz)	Occupied Bandwidth (99%)(kHz)
824.2	246.79
836.6	242.79
848.8	243.59

GSM 850 (99%)

Channel 128-Occupied Bandwidth (99% BW)



Date: 2.SEP.2022 13:21:28

©Copyright. All rights reserved by CTTL.

Channel 190-Occupied Bandwidth (99% BW)



Date: 2.SEP.2022 13:21:56

Channel 251-Occupied Bandwidth (99% BW)



Date: 2.SEP.2022 13:22:23

©Copyright. All rights reserved by CTTL.

GPRS 850 (99%)

Frequency (MHz)	Occupied Bandwidth (99%)(kHz)
824.2	244.39
836.6	244.39
848.8	244.39

GPRS 850 (99%)

Channel 128-Occupied Bandwidth (99% BW)



©Copyright. All rights reserved by CTTL.

Channel 190-Occupied Bandwidth (99% BW)



Date: 2.SEP.2022 14:00:35

Channel 251-Occupied Bandwidth (99% BW)



Date: 2.SEP.2022 14:01:02

©Copyright. All rights reserved by CTTL.

EGPRS 850-8PSK (99%)

Frequency (MHz)	Occupied Bandwidth (99%)(kHz)
824.2	250.80
836.6	247.60
848.8	250.00

EGPRS 850-8PSK (99%)

Channel 128-Occupied Bandwidth (99% BW)



©Copyright. All rights reserved by CTTL.

Channel 190-Occupied Bandwidth (99% BW)



Date: 2.SEP.2022 14:21:14

Channel 251-Occupied Bandwidth (99% BW)



Date: 2.SEP.2022 14:21:41

©Copyright. All rights reserved by CTTL.

PCS 1900 (99%)

Frequency (MHz)	Occupied Bandwidth (99%)(kHz)
1850.2	243.59
1880.0	242.79
1909.8	245.99

PCS 1900 (99%)

Channel 512-Occupied Bandwidth (99% BW)



Date: 2.SEP.2022 11:10:32

©Copyright. All rights reserved by CTTL.

Channel 661-Occupied Bandwidth (99% BW)



Date: 2.SEP.2022 11:10:59

Channel 810-Occupied Bandwidth (99% BW)



Date: 2.SEP.2022 11:11:26

©Copyright. All rights reserved by CTTL.

GPRS 1900 (99%)

Frequency (MHz)	Occupied Bandwidth (99%)(kHz)
1850.2	245.19
1880.0	242.79
1909.8	245.99

GPRS 1900 (99%)

Channel 512-Occupied Bandwidth (99% BW)



©Copyright. All rights reserved by CTTL.

Channel 661-Occupied Bandwidth (99% BW)



Date: 2.SEP.2022 11:49:38

Channel 810-Occupied Bandwidth (99% BW)



Date: 2.SEP.2022 11:50:05

©Copyright. All rights reserved by CTTL.

EGPRS 1900-8PSK (99%)

Frequency (MHz)	Occupied Bandwidth (99%)(kHz)
1850.2	254.01
1880.0	257.21
1909.8	255.61

EGPRS 1900-8PSK (99%)

Channel 512-Occupied Bandwidth (99% BW)



Date: 2.SEP.2022 12:09:49

©Copyright. All rights reserved by CTTL.

Channel 661-Occupied Bandwidth (99% BW)



Date: 2.SEP.2022 12:10:16

Channel 810-Occupied Bandwidth (99% BW)



Date: 2.SEP.2022 12:10:43

Note: Expanded measurement uncertainty is U = 3428 Hz, k = 2.

©Copyright. All rights reserved by CTTL.

A.5 Emission Bandwidth

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.
The measurement method is from ANSI C63.26:
a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be wide enough to see sufficient roll off of the signal to make the measurement.
b) The nominal RBW shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set ≥ 3 × RBW.
c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation.
d) The dynamic range of the spectrum analyzer at the selected RBW shall be more than 10 dB below the target "−X dB" requirement, i.e., if the requirement calls for measuring the −26 dB OBW, the spectrum analyzer noise floor at the selected RBW shall be at least 36 dB below the reference level.
e) Set spectrum analyzer detection mode to peak, and the trace mode to max hold.

©Copyright. All rights reserved by CTTL.

GSM 850 (-26dBc)

Frequency (MHz)	Emission Bandwidth (-26dBc)(kHz)
824.2	314.10
836.6	314.90
848.8	318.11

GSM 850 (-26dBc)

Channel 128-Emission Bandwidth (-26dBc BW)



©Copyright. All rights reserved by CTTL.

Channel 190-Emission Bandwidth (-26dBc BW)



Date: 2.SEP.2022 13:24:09

Channel 251-Emission Bandwidth (-26dBc BW)



Date: 2.SEP.2022 13:24:36

©Copyright. All rights reserved by CTTL.

GPRS 850 (-26dBc)

Frequency (MHz)	Emission Bandwidth (-26dBc)(kHz)
824.2	314.90
836.6	320.51
848.8	312.50

GPRS 850 (-26dBc)

Channel 128-Emission Bandwidth (-26dBc BW)



Date: 2.SEP.2022 14:02:20

©Copyright. All rights reserved by CTTL.

Channel 190-Emission Bandwidth (-26dBc BW)



Date: 2.SEP.2022 14:02:47

Channel 251-Emission Bandwidth (-26dBc BW)



Date: 2.SEP.2022 14:03:15

©Copyright. All rights reserved by CTTL.

EGPRS 850-8PSK (-26dBc)

Frequency (MHz)	Emission Bandwidth (-26dBc)(kHz)
824.2	314.10
836.6	311.70
848.8	310.10

EGPRS 850-8PSK (-26dBc)

Channel 128-Emission Bandwidth (-26dBc BW)



Date: 2.SEP.2022 14:22:59

©Copyright. All rights reserved by CTTL.

Channel 190-Emission Bandwidth (-26dBc BW)



Date: 2.SEP.2022 14:23:27

Channel 251-Emission Bandwidth (-26dBc BW)



Date: 2.SEP.2022 14:23:54

©Copyright. All rights reserved by CTTL.

PCS 1900 (-26dBc)

Frequency (MHz)	Emission Bandwidth (-26dBc)(kHz)
1850.2	314.90
1880.0	310.10
1909.8	320.51

PCS 1900 (-26dBc)

Channel 512-Emission Bandwidth (-26dBc BW)



Date: 2.SEP.2022 11:12:44

©Copyright. All rights reserved by CTTL.

Channel 661-Emission Bandwidth (-26dBc BW)



Date: 2.SEP.2022 11:13:12

Channel 810-Emission Bandwidth (-26dBc BW)



Date: 2.SEP.2022 11:13:40

©Copyright. All rights reserved by CTTL.

GPRS 1900 (-26dBc)

Frequency (MHz)	Emission Bandwidth (-26dBc)(kHz)
1850.2	312.50
1880.0	307.69
1909.8	314.10

GPRS 1900 (-26dBc)

Channel 512-Emission Bandwidth (-26dBc BW)



Date: 2.SEP.2022 11:51:23

©Copyright. All rights reserved by CTTL.

Channel 661-Emission Bandwidth (-26dBc BW)



Date: 2.SEP.2022 11:51:50

Channel 810-Emission Bandwidth (-26dBc BW)



Date: 2.SEP.2022 11:52:18

©Copyright. All rights reserved by CTTL.

EGPRS 1900-8PSK (-26dBc)

Frequency (MHz)	Emission Bandwidth (-26dBc)(kHz)
1850.2	319.71
1880.0	313.30
1909.8	323.72

EGPRS 1900-8PSK (-26dBc)

Channel 512-Emission Bandwidth (-26dBc BW)



Date: 2.SEP.2022 12:12:01

©Copyright. All rights reserved by CTTL.

Channel 661-Emission Bandwidth (-26dBc BW)



Channel 810-Emission Bandwidth (-26dBc BW)



Note: Expanded measurement uncertainty is U = 3428 Hz, k = 2.

©Copyright. All rights reserved by CTTL.

A.6 Band Edge Compliance

A.6.1 Measurement limit

Part 22.917 and Part 24.238 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

According to KDB 971168, a relaxation of the reference bandwidth is often provided for measurements within a specified frequency range at the edge of the authorized frequency block/band. This is often implemented by permitting the use of a narrower RBW (typically limited to a minimum RBW of 1% of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth.

The spectrum analyzer readings are corrected by [10 log (1/duty cycle)] for the non-continuous transmitting scenario.

©Copyright. All rights reserved by CTTL.

A.6.2 Measurement result

GSM 850

Channel 128



Date: 2.SEP.2022 13:32:37

Channel 251



Date: 2.SEP.2022 13:47:35

©Copyright. All rights reserved by CTTL.

GPRS 850

Channel 128



Date: 2.SEP.2022 14:11:15

Channel 251



Date: 2.SEP.2022 14:18:26

©Copyright. All rights reserved by CTTL.

PCS 1900

Channel 512



Date: 2.SEP.2022 11:21:41

Channel 810



Date: 2.SEP.2022 11:36:39

©Copyright. All rights reserved by CTTL.

GPRS 1900

Channel 512



Date: 2.SEP.2022 12:00:18

Channel 810



Date: 2.SEP.2022 12:07:29

Note: Expanded measurement uncertainty is U = 0.622 dB, k = 2.

©Copyright. All rights reserved by CTTL.

A.7 Conducted Spurious Emission

A.7.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. In measuring unwanted emissions, the spectrum shall be investigated from 30 MHz or the lowest radio frequency signal generated in the equipment, whichever is lower, without going below 9 kHz, up to at least the frequency given below:
   (a) If the equipment operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
   (b) If the equipment operates at or above 10 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.
3. The number of sweep points of spectrum analyzer is greater than 2×span/RBW.

A. 7.2 Measurement Limit

Part 22.917 and Part 24.238 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

©Copyright. All rights reserved by CTTL.

A.7.3 Measurement result

GSM850

Channel 128: 30MHz – 8.49GHz

NOTE: peak above the limit line is the carrier frequency.



Date: 2.SEP.2022 13:56:45

Channel 190: 30MHz – 8.49GHz

NOTE: peak above the limit line is the carrier frequency.



Date: 2.SEP.2022 13:57:16

©Copyright. All rights reserved by CTTL.

Channel 251: 30MHz – 8.49GMHz

NOTE: peak above the limit line is the carrier frequency.



Date: 2.SEP.2022 13:57:47

©Copyright. All rights reserved by CTTL.

PCS1900

Channel 512: 30MHz – 19.10GHz

NOTE: peak above the limit line is the carrier frequency.



Channel 661: 30MHz – 19.10GHz

NOTE: peak above the limit line is the carrier frequency.



©Copyright. All rights reserved by CTTL.

Channel 810: 30MHz – 19.10GHz

NOTE: peak above the limit line is the carrier frequency.



Note: Expanded measurement uncertainty is U = 0.622 dB, k = 2.

©Copyright. All rights reserved by CTTL.

A.8 Peak-to-Average Power Ratio

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB

a) Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;

b) Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;

c) Set the number of counts to a value that stabilizes the measured CCDF curve;

d) Record the maximum PAPR level associated with a probability of 0.1%.

Measurement results

	Frequency (MHz)	PAPR (dB)
PCS1900	1880.0	7.69
GPRS1900	1880.0	7.69
EGPRS1900(8PSK)	1880.0	10.03

Note: Expanded measurement uncertainty is U = 0.578 dB, k = 2.

©Copyright. All rights reserved by CTTL.

Annex B: Accreditation Certificate

United States Department of Commerce
National Institute of Standards and Technology

NVLAP®

ilac-MRA

Certificate of Accreditation to ISO/IEC 17025:2017

NVLAP LAB CODE: 600118-0

Telecommunication Technology Labs, CAICT
Beijing
China

is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:

Electromagnetic Compatibility & Telecommunications

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).

2022-10-01 through 2023-09-30
Effective Dates

DEPARTMENT OF COMMERCE · UNITED STATES OF AMERICA

For the National Voluntary Laboratory Accreditation Program

*****END OF REPORT*****

©Copyright. All rights reserved by CTTL.