

TEST REPORT

Application No.: SZCR2510004390WM
Applicant: TCL Communication Ltd.
Address of Applicant: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong
Manufacturer: TCL Communication Ltd.
Address of Manufacturer: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong
Equipment Under Test (EUT):
EUT Description: GSM/UMTS/LTE/NR Mobile phone
Model No.: T807W
Trade Mark: TCL
FCC ID: 2ACCJH194
Standard(s) : 47 CFR Part 15, Subpart E 15.407
Date of Receipt: 2025-10-10
Date of Test: 2025-10-15 to 2025-11-19
Date of Issue: 2025-11-20

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (EMC Laboratory)

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR251000439007
Page: 2 of 688

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2025-11-20		Original

Authorized for issue by:				
				
		Charlie Dai/Project Engineer		
				
		Eric Fu/Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart E 15.407	N/A	47 CFR Part 15, Subpart C 15.203	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart E 15.407	ANSI C63.10 (2020) Section 6.2	47 CFR Part 15, Subpart C 15.207 & Subpart E 15.407 b(9)	Pass
Radiated Emissions (Below 1GHz)		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions (Above 1GHz)		ANSI C63.10 (2020) Section 6.6	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2020) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
In-Band Emissions		ANSI C63.10 (2020) Section 12.6	47 CFR Part 15, Subpart E 15.407 (b)	Pass
Contention-based Protocol		KDB 987594 D02	47 CFR Part 15, Subpart E 15.407 (d)(6)	Pass
Duty Cycle		ANSI C63.10 (2020) Section 12.2	ANSI C63.10 (2013) Section 12.2	Pass
99% Bandwidth		ANSI C63.10 (2020) Section 12.5.3	ANSI C63.10 (2013) Section 12.4.2	Pass
26dB Emission bandwidth		ANSI C63.10 (2020) Section 12.5.2	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Maximum Conducted output power		ANSI C63.10 (2020) Section 12.4	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Peak Power spectrum density		ANSI C63.10 (2020) Section 12.6	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Frequency Stability		ANSI C63.10 (2020) Section 6.8	47 CFR Part 15, Subpart E 15.407 (g)	Pass

3 Contents

	Page
1 Cover Page	1
2 Test Summary.....	3
3 Contents	4
4 General Information.....	6
4.1 Details of E.U.T.	6
4.2 Environment Parameter.....	7
4.3 Description of Support Units.....	7
4.4 Measurement Uncertainty	7
4.5 Test Location	8
4.6 Test Facility.....	8
4.7 Deviation from Standards.....	8
4.8 Abnormalities from Standard Conditions	8
5 Equipment List	9
6 Radio Spectrum Technical Requirement.....	13
6.1 Antenna Requirement	13
6.1.1 Test Requirement:	13
7 Radio Spectrum Matter Test Results.....	15
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)	15
7.1.1 E.U.T. Operation	15
7.1.2 Test Mode Description	15
7.1.3 Test Setup Diagram	16
7.1.4 Measurement Procedure and Data.....	16
7.2 Radiated Emissions (Below 1GHz).....	19
7.2.1 E.U.T. Operation	19
7.2.2 Test Mode Description	19
7.2.3 Test Setup Diagram	20
7.2.4 Measurement Procedure and Data.....	20
7.3 Radiated Emissions (Above 1GHz).....	23
7.3.1 E.U.T. Operation	23
7.3.2 Test Mode Description	23
7.3.3 Test Setup Diagram	24
7.3.4 Measurement Procedure and Data.....	25
7.4 Radiated Emissions which fall in the restricted bands	74
7.4.1 E.U.T. Operation	74
7.4.2 Test Mode Description	74
7.4.3 Test Setup Diagram	75
7.4.4 Measurement Procedure and Data.....	76
7.5 In-Band Emissions	109
7.5.1 E.U.T. Operation	109



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR251000439007

Page: 5 of 688

7.5.2	Test Mode Description	109
7.5.3	Test Setup Diagram	110
7.5.4	Measurement Procedure and Data.....	110
7.6	Contention-based Protocol	111
7.6.1	E.U.T. Operation	111
7.6.2	Test Mode Description	111
7.6.3	Test Setup Diagram	111
7.6.4	Measurement Procedure and Data.....	111
7.7	Duty Cycle	112
7.7.1	E.U.T. Operation	112
7.7.2	Test Mode Description	112
7.7.3	Test Setup Diagram	112
7.7.4	Measurement Procedure and Data.....	112
7.8	99% Bandwidth	113
7.8.1	E.U.T. Operation	113
7.8.2	Test Mode Description	113
7.8.3	Test Setup Diagram	114
7.8.4	Measurement Procedure and Data.....	114
7.9	26dB Emission bandwidth	115
7.9.1	E.U.T. Operation	115
7.9.2	Test Mode Description	115
7.9.3	Test Setup Diagram	116
7.9.4	Measurement Procedure and Data.....	116
7.10	Maximum Conducted output power	117
7.10.1	E.U.T. Operation	117
7.10.2	Test Mode Description	117
7.10.3	Test Setup Diagram	118
7.10.4	Measurement Procedure and Data.....	118
7.11	Peak Power spectrum density	119
7.11.1	E.U.T. Operation	119
7.11.2	Test Mode Description	119
7.11.3	Test Setup Diagram	120
7.11.4	Measurement Procedure and Data.....	120
7.12	Frequency Stability.....	121
7.12.1	E.U.T. Operation	121
7.12.2	Test Mode Description	121
7.12.3	Test Setup Diagram	122
7.12.4	Measurement Procedure and Data.....	122
8	Test Setup Photo	123
9	EUT Constructional Details (EUT Photos).....	123
10	Appendix.....	124



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

EUT Description:	GSM/UMTS/LTE/NR Mobile phone	
Model No.:	T807W	
Trade Mark:	TCL	
Hardware Version:	03	
Software Version:	AX3V	
Power supply:	Powered by DC3.91V/5000mAh (Model: TLp050B7) by Rechargeable Li-ion Battery. Charged by USB port from adapter.	
IEEE 802.11 WLAN Mode Supported:	☒ 802.11a (20 MHz channel bandwidth) ☒ 802.11ax (20 MHz channel bandwidth) ☒ 802.11ax (40 MHz channel bandwidth) ☒ 802.11ax (80 MHz channel bandwidth)	
Operation Frequency:	IEEE 802.11 a/ax (HE20/40/80): 5925 MHz ~ 6425 MHz IEEE 802.11 a/ax (HE20/40/80): 6425 MHz ~ 6525 MHz IEEE 802.11 a/ax (HE20/40/80): 6525 MHz ~ 6875 MHz IEEE 802.11 a/ax (HE20/40/80): 6875 MHz ~ 7125 MHz	
Type of Modulation:	OFDM/OFDMA	
FCC Classification:	Dual Client (6XD), (Indoor client)	
Antenna Type:	Ant10: MDA Antenna Ant12: LDS Antenna	
Smart System:	☒ SISO	802.11a/ax
	☒ MIMO	802.11ax: 2Tx & 2Rx
	☒ Diversity	802.11a: 2Tx & 2Rx
Antenna Gain:	Ant10: UNII-5: -7.62dBi; UNII-6: -7.62dBi; UNII-7: -7.62dBi; UNII-8: -7.62dBi; Ant12: UNII-5: -5.93dBi; UNII-6: -5.93dBi; UNII-7: -5.93dBi; UNII-8: -5.93dBi;	
	Note: The antenna gain are derived from the gain information report provided by the manufacturer.	
RF Cable:	2.2dB	
Remark: As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.		



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR251000439007

Page: 7 of 688

4.2 Environment Parameter

Environment Parameter	1020 mbar Selected Values During Tests	
Relative Humidity	30.7-52.6 % RH Ambient	
Value	Temperature(°C)	Voltage(V)
NTNV	21.5~27.2	3.91
Note:		
NV:Normal Voltage	LV:Low Extreme Test Voltage	HV:High Extreme Test Voltage
NT:Normal Temperature	LT:Low Extreme Test Temperature	HT:High Extreme Test Temperature

4.3 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Adapter	HONOR	HN-200500CP0	N/A

4.4 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	± 3.1dB
Radiated Emissions (Below 1GHz)	± 6.0dB for 3m; ± 5.0dB for 10m
Radiated Emissions (Above 1GHz)	± 4.6dB (1-18GHz);± 4.8dB (18-40GHz)
Radiated Emissions which fall in the restricted bands	± 6.0dB (below 1GHz); ± 4.6dB (above 1GHz);
In-Band Emissions	± 2.84dB
Duty Cycle	± 0.37%
99% Bandwidth	± 3%
26dB Emission bandwidth	± 3%
Maximum Conducted output power	± 0.75dB
Peak Power spectrum density	± 2.84dB
Frequency Stability	± 7.25 x 10-8
Remark:	
The U _{lab} (lab Uncertainty) is less than U _{CISPR/ETSI} (CISPR/ETSI Uncertainty), so the test results	
– compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;	
– non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.	

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR251000439007

Page: 8 of 688

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2025-05-07	2028-05-06
EMI Test Receiver	Rohde&Schwarz	ESR	SZ-WRG-M-047	2025-01-08	2026-01-07
Matching Pad	N/A	N/A	SEM021-23	2025-03-19	2026-03-18
Matching Pad	N/A	N/A	SEM021-24	2025-03-19	2026-03-18
Measurement Software	AUDIX	e3 V8.2014-6-27a	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2025-07-05	2026-07-04
LISN	Rohde&Schwarz	ENV216	SEM007-01	2025-07-25	2026-07-24
LISN	ETS-LINDGREN	3816/2	SEM007-02	2025-03-03	2026-03-02

Radiated Emissions (Below 1GHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2023-11-20	2025-11-19
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2023-06-19	2026-06-18
MXE EMI Receiver	Agilent Technologies	N9038A	SEM004-15	2025-07-25	2026-07-24
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-01	2025-08-29	2027-08-28
Pre-Amplifier	Agilent Technologies	8447D	SEM005-01	2025-03-04	2026-03-03
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2025-07-05	2026-07-04

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR251000439007

Page: 10 of 688

Radiated Emissions (Above 1GHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Signal & Spectrum Analyzer	Rohde & Schwarz	FSV	SZ-WRG-M-048	2025-01-07	2026-01-06
Low Noise Amplifier 1G-18GHz	Tonscend	TAP01018050	SZ-WRG-M-051	2025-01-07	2026-01-06
Low Noise Amplifier 18G-40GHz	Tonscend	TAP18040048	SZ-WRG-M-052	2025-01-08	2026-01-07
Double Ridge Horn Antenna 1GHz-18GHz	SCHWARZBECK	BBHA 9120 D	SZ-WRG-M-055	2023-12-21	2025-12-20
SHF-EHF Horn 15GHz-40GHz	SCHWARZBECK	BBHA 9170	SZ-WRG-M-056	2023-12-25	2025-12-24
RSE Test Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Chamber	CRTSGSSAC966	N/A	SZ-WRG-C-063	2025-01-06	2028-01-05
Humidity and Temperature Indicator	deli	8838	SEM002-46	2025-07-23	2026-07-22

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Signal & Spectrum Analyzer	Rohde & Schwarz	FSV	SZ-WRG-M-048	2025-01-07	2026-01-06
Low Noise Amplifier 30M-8GHz	Tonscend	TAP30M8G30	SZ-WRG-M-050	2025-01-07	2026-01-06
Double Ridge Horn Antenna 1GHz-18GHz	SCHWARZBECK	BBHA 9120 D	SZ-WRG-M-055	2023-12-21	2025-12-20
SHF-EHF Horn 15GHz-40GHz	SCHWARZBECK	BBHA 9170	SZ-WRG-M-056	2023-12-25	2025-12-24
RSE Test Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Chamber	CRTSGSSAC966	N/A	SZ-WRG-C-063	2025-01-06	2028-01-05
Humidity and Temperature Indicator	deli	8838	SEM002-46	2025-07-23	2026-07-22



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch (SZEMC) Laboratory.
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR251000439007

Page: 11 of 688

In-Band Emissions					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2025-07-24	2026-07-23
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2025-03-04	2026-03-03
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2025-09-10	2026-09-09
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2025-07-05	2026-07-04
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2025-03-03	2026-03-02
Programmable Temperature & Humidity Chamber	Votsch Industrietechnik GmbH	VT 4002	SEM002-15	2025-02-26	2026-02-25

Contention-based Protocol					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Shielding Room	AUDIX	N/A	SEM001-08	2025-05-16	2028-05-15
EXA Signal Analyzer	KEYSIGHT	N9010A	SEM004-09	2025-03-03	2026-03-02
ESG Vector Signal Generator	KEYSIGHT	E4438C	SEM006-15	2025-07-24	2026-07-23
DC Power Supply	KEYSIGHT	E3642A	SEM011-07	2025-02-26	2026-02-25
Manual Step Attenuator	KEYSIGHT	8494B	SEM021-05	2025-03-03	2026-03-02
Manual Step Attenuator	KEYSIGHT	8496B	SEM021-06	2025-03-03	2026-03-02
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2025-03-04	2026-03-03
Power Sensor	TST PASS	TSPS2023R	SEM009-27	2025-03-04	2026-03-03
Power Sensor	TST PASS	TSPS2023R	SEM009-28	2025-03-04	2026-03-03
Power Sensor	TST PASS	TSPS2023R	SEM009-29	2025-03-04	2026-03-03
Programmable Temperature&Humidity Chamber	Votsch Industrietechnik GmbH	VT 4002	SEM002-15	2025-02-26	2026-02-25
Universal Radio Communication Tester	Rohde&Schwarz	CMW500	SEM010-08	2025-03-04	2026-03-03
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM028-01	2025-07-05	2026-07-04



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Testing Laboratory)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR251000439007

Page: 12 of 688

RF Conducted Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2025-07-24	2026-07-23
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2025-03-04	2026-03-03
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2025-09-10	2026-09-09
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2025-07-05	2026-07-04
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2025-03-03	2026-03-02
Programmable Temperature & Humidity Chamber	Votsch Industrietechnik GmbH	VT 4002	SEM002-15	2025-02-26	2026-02-25
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2025-03-04	2026-03-03
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2025-03-04	2026-03-03

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2025-07-23	2026-07-22
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2025-07-23	2026-07-22
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2025-03-03	2026-03-02



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is Ant10: MDA Antenna, Ant12: LDS Antenna, and no consideration of replacement.

The best case gain of the antenna is

Ant10: UNII-5: -7.62dBi; UNII-6: -7.62dBi; UNII-7: -7.62dBi; UNII-8: -7.62dBi;*

Ant12: UNII-5: -5.93dBi; UNII-6: -5.93dBi; UNII-7: -5.93dBi; UNII-8: -5.93dBi;*

**Note:*

The antenna gain are derived from the gain information report provided by the manufacturer.

Remark:

As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.



Cyclic Delay Diversity (CDD) System:

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

If all antennas have the same gain, G_{ANT} , Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

- For power spectral density (PSD) measurements on all devices,
Array Gain = $10 \log(N_{ANT}/N_{SS}=1)$ dB.
- For power measurements on IEEE 802.11 devices:
Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

For power, the directional gain may be calculated by using the formulas applicable to equal gain antennas with GANT set equal to the gain of the antenna having the highest gain.

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The Power and PSD limit should be modified if the directional gain of eut is over 6dbi.

The EUT supports CDD System.

Unequal antenna gain:

Operation Frequency	ANT Gain0 (dBi)	ANT Gain1 (dBi)	Directional gain For Power (dBi)	Directional gain For PSD (dBi)
5925 MHz to 6425 MHz	-7.62	-5.93	-5.93	-3.72
6425 MHz to 6525 MHz	-7.62	-5.93	-5.93	-3.72
6525 MHz to 6875 MHz	-7.62	-5.93	-5.93	-3.72
6875 MHz to 7125 MHz	-7.62	-5.93	-5.93	-3.72

5925 MHz to 6425 MHz:

Power Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

PSD Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

6425 MHz to 6525 MHz:

Power Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

PSD Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

6525 MHz to 6875 MHz:

Power Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

PSD Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

6875 MHz to 7125 MHz:

Power Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

PSD Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement: 47 CFR Part 15, Subpart C 15.207 & Subpart E 15.407 b(9)
 Test Method: ANSI C63.10 (2020) Section 6.2
 Test Engineer: Kaito Zeng

Limit:

Frequency of emission(MHz)	Conducted limit(dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

7.1.1 E.U.T. Operation


Operating Environment:

Temperature: 23.4 °C Humidity: 42.5 % RH Atmospheric Pressure: 1020 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	28	Charge + TX mode (U-NII-5) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.
Pre-scan	29	Charge + TX mode (U-NII-6) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.
Pre-scan	30	Charge + TX mode (U-NII-7) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.
Pre-scan	31	Charge + TX mode (U-NII-8) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.

7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark 1: Level=Read Level+ Cable Loss+ LISN Factor

Remark 2: Pre-test AC 120V/50-60Hz&AC 240V/50-60Hz then choose the AC 120/60Hz as worst case.


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR251000439007

Page: 17 of 688

Test Mode: 28; Line: Live line



Site : Shielding Room

Condition: Line

Job No. : 04390WM

Test mode: 28

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1668	0.06	10.17	22.64	32.87	65.12	-32.25	QP
2	0.1668	0.06	10.17	16.78	27.01	55.12	-28.11	Average
3 *	0.3872	0.09	9.70	19.90	29.69	58.12	-28.43	QP
4	0.3872	0.09	9.70	14.01	23.80	48.12	-24.32	Average
5	0.9431	0.11	9.59	17.09	26.79	56.00	-29.21	QP
6 *	0.9431	0.11	9.59	12.33	22.03	46.00	-23.97	Average
7	1.5518	0.12	9.58	12.55	22.25	56.00	-33.75	QP
8	1.5518	0.12	9.58	7.19	16.89	46.00	-29.11	Average
9	4.8997	0.14	9.66	10.91	20.71	56.00	-35.29	QP
10	4.8997	0.14	9.66	5.66	15.46	46.00	-30.54	Average
11	11.9962	0.16	9.79	14.32	24.27	60.00	-35.73	QP
12	11.9962	0.16	9.79	8.83	18.78	50.00	-31.22	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Services Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR251000439007

Page: 18 of 688

Test Mode: 28; Line: Neutral Line



Site : Shielding Room
Condition: Neutral
Job No. : 04390WM
Test mode: 28

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1650	0.06	10.13	21.04	31.23	65.21	-33.98	QP
2	0.1650	0.06	10.13	14.13	24.32	55.21	-30.89	Average
3 *	0.3914	0.09	9.74	19.97	29.80	58.03	-28.23	QP
4 *	0.3914	0.09	9.74	15.01	24.84	48.03	-23.19	Average
5	0.8944	0.11	9.57	16.61	26.29	56.00	-29.71	QP
6	0.8944	0.11	9.57	11.92	21.60	46.00	-24.40	Average
7	1.5767	0.12	9.55	11.52	21.19	56.00	-34.81	QP
8	1.5767	0.12	9.55	6.04	15.71	46.00	-30.29	Average
9	4.8224	0.14	9.56	10.24	19.94	56.00	-36.06	QP
10	4.8224	0.14	9.56	5.04	14.74	46.00	-31.26	Average
11	12.4495	0.16	9.73	17.14	27.03	60.00	-32.97	QP
12	12.4495	0.16	9.73	11.80	21.69	50.00	-28.31	Average



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.2 Radiated Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)
 Test Method: ANSI C63.10 (2020) Section 6.4,6.5
 Measurement Distance: 3m
 Test Engineer: Kaito Zeng

7.2.1 E.U.T. Operation

Operating Environment:
 Temperature: 23.5 °C Humidity: 46.8 % RH Atmospheric Pressure: 1020 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	24	TX mode (U-NII-5) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.
Pre-scan	25	TX mode (U-NII-6) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.
Pre-scan	26	TX mode (U-NII-7) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.
Pre-scan	27	TX mode (U-NII-8) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.
Final test	28	Charge + TX mode (U-NII-5) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.
Pre-scan	29	Charge + TX mode (U-NII-6) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.
Pre-scan	30	Charge + TX mode (U-NII-7) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.
Pre-scan	31	Charge + TX mode (U-NII-8) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
 Shenzhen Branch Inspection & Testing Services Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.2.3 Test Setup Diagram

7.2.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- For emission below 1GHz, through the pre-scan found the worst case is the lowest channel of 802.11a. Only the worst case is recorded in the report.
- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- The disturbance below 1GHz was very low and the below harmonics were the highest point could be found when testing, so only the below harmonics had been displayed.




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR251000439007

Page: 21 of 688


Test Mode: 28; Polarity: Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No. : 04390WM
Test Mode: 28

	Ant Freq	Cable Factor	Preamp Loss	Preamp Factor	Read Level	Read Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	30.105	21.15	0.74	27.65	24.88	19.12	40.00	-20.88	QP
2	53.693	12.18	0.91	27.63	29.21	14.67	40.00	-25.33	QP
3	92.139	11.92	1.19	27.60	34.14	19.65	43.50	-23.85	QP
4	225.308	15.77	1.82	27.71	34.59	24.47	46.00	-21.53	QP
5	549.020	23.81	2.96	28.02	26.52	25.27	46.00	-20.73	QP
6 q	948.761	28.23	4.08	26.68	24.62	30.25	46.00	-15.75	QP

Test Mode: 28; Polarity: Vertical



Site : chamber
Condition: 3m VERTICAL
Job No. : 04390WM
Test Mode: 28

	Ant	Cable	Preamp	Read		Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB
1	41.567	15.62	0.83	27.64	36.86	25.67	40.00	-14.33 QP
2	53.693	12.18	0.91	27.63	40.34	25.80	40.00	-14.20 QP
3 q	91.175	11.83	1.18	27.60	44.46	29.87	43.50	-13.63 QP
4	266.609	17.08	1.99	27.59	34.76	26.24	46.00	-19.76 QP
5	501.179	22.95	2.81	27.94	29.15	26.97	46.00	-19.03 QP
6	972.337	28.16	4.12	26.55	24.80	30.53	54.00	-23.47 QP



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR251000439007

Page: 23 of 688

7.3 Radiated Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)
 Test Method: ANSI C63.10 (2020) Section 6.6
 Measurement Distance: 3m
 Test Engineer: Xing Guo

7.3.1 E.U.T. Operation

Operating Environment:
 Temperature: 21.6 °C Humidity: 50.8 % RH Atmospheric Pressure: 1020 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	24	TX mode (U-NII-5) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.
Final test	25	TX mode (U-NII-6) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.
Final test	26	TX mode (U-NII-7) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.
Final test	27	TX mode (U-NII-8) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.
Pre-scan	28	Charge + TX mode (U-NII-5) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.
Pre-scan	29	Charge + TX mode (U-NII-6) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.
Pre-scan	30	Charge + TX mode (U-NII-7) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.
Pre-scan	31	Charge + TX mode (U-NII-8) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested and found the data rate @ MCS0 is the worst case of IEEE 802.11ax/be 20/40/80/160, Only the data of worst case is recorded in the report.




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
 Shenzhen Branch (Testing) EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.3.3 Test Setup Diagram



Above 1GHz



7.3.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on below plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The disturbance above 18GHz were very low and the below harmonics were the highest point could be found when testing, so only the below harmonics had been displayed.
5. For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s). Only the worst case mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum) is recorded in the test report.
6. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
7. For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle<98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch


SZEMC-TRF-01 Rev. A/1

Report No.: SZCR251000439007

Page: 26 of 688

Remark: Only retain the data of the worst-case 11a and 11ax(full RU) modes.

Test Mode: 24; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Condition: 3m HORIZONTAL

Job No : 04390WM

Mode : 5955 TX RSE

: Wi-Fi 6E 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7326.267	11.51	36.75	56.44	54.05	45.87	74.00	-28.13	peak
2	7966.832	11.55	37.73	55.93	53.58	46.93	88.20	-41.27	peak
3	8738.852	12.15	38.52	55.24	52.50	47.93	88.20	-40.27	peak
4	11910.000	14.87	39.71	53.77	47.40	48.21	74.00	-25.79	peak
5	15942.300	17.22	38.66	54.02	47.52	49.38	74.00	-24.62	peak
6	pp17865.000	18.22	42.89	54.47	45.88	52.52	74.00	-21.48	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 24; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Condition: 3m VERTICAL

Job No : 04390WM


Mode : 5955 TX RSE

: Wi-Fi 6E 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7096.999	11.97	36.39	56.62	52.86	44.60	88.20	-43.60	peak
2	7898.049	11.54	37.59	55.98	53.08	46.23	88.20	-41.97	peak
3	8588.607	12.00	38.45	55.37	52.82	47.90	88.20	-40.30	peak
4	11910.000	14.87	39.71	53.77	48.44	49.25	74.00	-24.75	peak
5	15988.450	17.16	38.61	54.00	47.68	49.45	74.00	-24.55	peak
6	pp17865.000	18.22	42.89	54.47	45.58	52.22	74.00	-21.78	peak



Test Mode: 24; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Condition: 3m HORIZONTAL

Job No : 04390WM

Mode : 6175 TX RSE

: Wi-Fi 6E 11A


		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6395.654	13.23	34.79	56.82	54.15	45.35	88.20	-42.85	peak
2	7966.832	11.55	37.73	55.93	53.94	47.29	88.20	-40.91	peak
3	8840.473	12.24	38.50	55.14	52.31	47.91	88.20	-40.29	peak
4	12350.000	15.08	39.85	54.04	46.96	47.85	74.00	-26.15	peak
5	15896.290	17.27	38.69	54.03	48.10	50.03	74.00	-23.97	peak
6	pp17793.090	18.18	42.45	54.46	46.36	52.53	74.00	-21.47	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 24; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Condition: 3m VERTICAL

Job No : 04390WM


Mode : 6175 TX RSE

: Wi-Fi 6E 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6954.852	11.37	36.11	56.71	53.98	44.75	88.20	-43.45	peak
2	7784.729	11.33	37.14	56.07	53.67	46.07	88.20	-42.13	peak
3	8840.473	12.24	38.50	55.14	52.48	48.08	88.20	-40.12	peak
4	12350.000	15.08	39.85	54.04	46.89	47.78	74.00	-26.22	peak
5	15759.050	17.13	38.54	54.07	47.56	49.16	74.00	-24.84	peak
6	pp17896.250	18.25	43.08	54.48	45.68	52.53	74.00	-21.47	peak



Test Mode: 24; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Condition: 3m HORIZONTAL

Job No : 04390WM


Mode : 6415 TX RSE

: Wi-Fi 6E 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7305.122	11.51	36.71	56.46	53.13	44.89	74.00	-29.11	peak
2	8764.146	12.19	38.50	55.21	52.71	48.19	88.20	-40.01	peak
3	11368.000	14.35	39.70	53.61	49.39	49.83	74.00	-24.17	peak
4	12830.000	15.53	40.33	54.38	47.32	48.80	88.20	-39.40	peak
5	15850.410	17.16	38.60	54.04	47.55	49.27	74.00	-24.73	peak
6	pp17844.590	18.21	42.77	54.47	45.93	52.44	74.00	-21.56	peak



Test Mode: 24; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Condition: 3m VERTICAL

Job No : 04390WM


Mode : 6415 TX RSE

: Wi-Fi 6E 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7096.999	11.97	36.39	56.62	53.39	45.13	88.20	-43.07	peak
2	8663.404	12.04	38.45	55.30	53.17	48.36	88.20	-39.84	peak
3	11172.560	14.73	39.57	53.55	49.56	50.31	74.00	-23.69	peak
4	12830.000	15.53	40.33	54.38	48.11	49.59	88.20	-38.61	peak
5	15850.410	17.16	38.60	54.04	47.75	49.47	74.00	-24.53	peak
6	pp17844.590	18.21	42.77	54.47	45.40	51.91	74.00	-22.09	peak



Test Mode: 24; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low



Condition: 3m HORIZONTAL

Job No : 04390WM


Mode : 5955 TX RSE

: Wi-Fi 6E 11AX20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6395.654	13.23	34.79	56.82	54.56	45.76	88.20	-42.44	peak
2	7920.911	11.54	37.64	55.96	53.50	46.72	88.20	-41.48	peak
3	8489.882	12.24	38.32	55.46	53.42	48.52	74.00	-25.48	peak
4	11910.000	14.87	39.71	53.77	47.92	48.73	74.00	-25.27	peak
5	15443.410	16.82	38.60	54.17	48.08	49.33	74.00	-24.67	peak
6	pp17865.000	18.22	42.89	54.47	45.33	51.97	74.00	-22.03	peak



Test Mode: 24; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low



Condition: 3m VERTICAL

Job No : 04390WM


Mode : 5955 TX RSE

: Wi-Fi 6E 11AX20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6395.654	13.23	34.79	56.82	53.45	44.65	88.20	-43.55	peak
2	7875.254	11.48	37.50	56.00	53.75	46.73	88.20	-41.47	peak
3	8995.123	12.15	38.59	55.00	52.25	47.99	88.20	-40.21	peak
4	11910.000	14.87	39.71	53.77	48.15	48.96	74.00	-25.04	peak
5	15896.290	17.27	38.69	54.03	47.54	49.47	74.00	-24.53	peak
6	pp17865.000	18.22	42.89	54.47	45.76	52.40	74.00	-21.60	peak



Test Mode: 24; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:middle



Condition: 3m HORIZONTAL

Job No : 04390WM

Mode : 6175 TX RSE

: Wi-Fi 6E 11AX20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7096.999	11.97	36.39	56.62	53.53	45.27	88.20	-42.93	peak
2	7943.838	11.55	37.69	55.94	53.39	46.69	88.20	-41.51	peak
3	8764.146	12.19	38.50	55.21	52.57	48.05	88.20	-40.15	peak
4	12350.000	15.08	39.85	54.04	47.61	48.50	74.00	-25.50	peak
5	15532.940	16.98	38.57	54.14	48.55	49.96	74.00	-24.04	peak
6	pp17896.250	18.25	43.08	54.48	45.26	52.11	74.00	-21.89	peak




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR251000439007

Page: 35 of 688

Test Mode: 24; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:middle



Condition: 3m VERTICAL

Job No : 04390WM

Mode : 6175 TX RSE

: Wi-Fi 6E 11AX20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6414.167	13.10	34.80	56.82	54.66	45.74	88.20	-42.46	peak
2	7966.832	11.55	37.73	55.93	52.99	46.34	88.20	-41.86	peak
3	8514.456	12.26	38.30	55.44	52.47	47.59	88.20	-40.61	peak
4	12350.000	15.08	39.85	54.04	47.22	48.11	74.00	-25.89	peak
5	15896.290	17.27	38.69	54.03	47.29	49.22	74.00	-24.78	peak
6	pp17844.590	18.21	42.77	54.47	45.43	51.94	74.00	-22.06	peak




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR251000439007

Page: 36 of 688

Test Mode: 24; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High



Condition: 3m HORIZONTAL

Job No : 04390WM

Mode : 6415 TX RSE

: Wi-Fi 6E 11AX20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7326.267	11.51	36.75	56.44	53.35	45.17	74.00	-28.83	peak
2	8995.123	12.15	38.59	55.00	52.56	48.30	88.20	-39.90	peak
3	10333.800	13.59	39.00	53.90	51.30	49.99	88.20	-38.21	peak
4	12830.000	15.53	40.33	54.38	49.02	50.50	88.20	-37.70	peak
5	15988.450	17.16	38.61	54.00	47.54	49.31	74.00	-24.69	peak
6	pp17844.590	18.21	42.77	54.47	45.94	52.45	74.00	-21.55	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 24; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High



Condition: 3m VERTICAL

Job No : 04390WM


Mode : 6415 TX RSE

: Wi-Fi 6E 11AX20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6414.167	13.10	34.80	56.82	53.96	45.04	88.20	-43.16	peak
2	8764.146	12.19	38.50	55.21	53.36	48.84	88.20	-39.36	peak
3	11204.900	14.75	39.60	53.56	50.70	51.49	74.00	-22.51	peak
4	12830.000	15.53	40.33	54.38	47.51	48.99	88.20	-39.21	peak
5	15988.450	17.16	38.61	54.00	47.26	49.03	74.00	-24.97	peak
6	pp17896.250	18.25	43.08	54.48	45.49	52.34	74.00	-21.66	peak



Test Mode: 25; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Condition: 3m HORIZONTAL

Job No : 04390WM

Mode : 6435 TX RSE

: Wi-Fi 6E 11A


		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7117.542	11.91	36.44	56.61	53.01	44.75	88.20	-43.45	peak
2	8489.882	12.24	38.32	55.46	54.26	49.36	74.00	-24.64	peak
3	9952.717	12.91	38.90	54.14	51.18	48.85	88.20	-39.35	peak
4	12870.000	15.69	40.37	54.41	47.43	49.08	88.20	-39.12	peak
5	15896.290	17.27	38.69	54.03	47.42	49.35	74.00	-24.65	peak
6	pp17896.250	18.25	43.08	54.48	45.27	52.12	74.00	-21.88	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 25; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Condition: 3m VERTICAL

Job No : 04390WM


Mode : 6435 TX RSE

: Wi-Fi 6E 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6934.778	11.37	36.13	56.71	53.88	44.67	88.20	-43.53	peak
2	8563.818	12.09	38.36	55.39	52.90	47.96	88.20	-40.24	peak
3	9923.991	12.85	38.90	54.17	50.34	47.92	88.20	-40.28	peak
4	12870.000	15.69	40.37	54.41	46.91	48.56	88.20	-39.64	peak
5	15942.300	17.22	38.66	54.02	47.72	49.58	74.00	-24.42	peak
6	pp17793.090	18.18	42.45	54.46	45.98	52.15	74.00	-21.85	peak



Test Mode: 25; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Condition: 3m HORIZONTAL

Job No : 04390WM


Mode : 6475 TX RSE

: Wi-Fi 6E 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6414.167	13.10	34.80	56.82	54.23	45.31	88.20	-42.89	peak
2	8738.852	12.15	38.52	55.24	53.54	48.97	88.20	-39.23	peak
3	11302.480	14.63	39.70	53.59	49.77	50.51	74.00	-23.49	peak
4	12950.000	15.85	40.35	54.47	47.62	49.35	88.20	-38.85	peak
5	15988.450	17.16	38.61	54.00	47.38	49.15	74.00	-24.85	peak
6	pp17844.590	18.21	42.77	54.47	46.60	53.11	74.00	-20.89	peak



Test Mode: 25; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Condition: 3m VERTICAL

Job No : 04390WM


Mode : 6475 TX RSE

: Wi-Fi 6E 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6874.906	11.37	36.10	56.73	54.87	45.61	88.20	-42.59	peak
2	8789.516	12.23	38.50	55.19	52.65	48.19	88.20	-40.01	peak
3	11044.130	14.39	39.44	53.51	50.09	50.41	74.00	-23.59	peak
4	12950.000	15.85	40.35	54.47	47.27	49.00	88.20	-39.20	peak
5	15988.450	17.16	38.61	54.00	48.16	49.93	74.00	-24.07	peak
6	pp17844.590	18.21	42.77	54.47	45.77	52.28	74.00	-21.72	peak



Test Mode: 25; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Condition: 3m HORIZONTAL

Job No : 04390WM


Mode : 6515 TX RSE

: Wi-Fi 6E 11A

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7179.527	11.62	36.56	56.56	53.16	44.78	88.20	-43.42	peak
2	8688.480	12.08	38.55	55.28	52.81	48.16	88.20	-40.04	peak
3	11335.190	14.49	39.70	53.60	48.98	49.57	74.00	-24.43	peak
4	13030.000	15.79	40.30	54.50	48.76	50.35	88.20	-37.85	peak
5	15046.850	16.65	38.75	54.29	48.62	49.73	88.20	-38.47	peak
6	pp17896.250	18.25	43.08	54.48	45.25	52.10	74.00	-21.90	peak



Test Mode: 25; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Condition: 3m VERTICAL

Job No : 04390WM


Mode : 6515 TX RSE

: Wi-Fi 6E 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6432.732	12.79	34.80	56.81	53.95	44.73	88.20	-43.47	peak
2	8840.473	12.24	38.50	55.14	52.43	48.03	88.20	-40.17	peak
3	11172.560	14.73	39.57	53.55	48.93	49.68	74.00	-24.32	peak
4	13030.000	15.79	40.30	54.50	47.86	49.45	88.20	-38.75	peak
5	15577.900	17.11	38.52	54.13	48.01	49.51	74.00	-24.49	peak
6	pp17844.590	18.21	42.77	54.47	45.71	52.22	74.00	-21.78	peak



Test Mode: 25; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low



Condition: 3m HORIZONTAL

Job No : 04390WM


Mode : 6435 TX RSE

: Wi-Fi 6E 11AX20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7263.015	11.51	36.63	56.49	53.81	45.46	74.00	-28.54	peak
2	8588.607	12.00	38.45	55.37	53.09	48.17	88.20	-40.03	peak
3	9781.603	13.02	38.60	54.30	51.05	48.37	88.20	-39.83	peak
4	12870.000	15.69	40.37	54.41	47.92	49.57	88.20	-38.63	peak
5	15942.300	17.22	38.66	54.02	47.91	49.77	74.00	-24.23	peak
6	pp17896.250	18.25	43.08	54.48	45.16	52.01	74.00	-21.99	peak



Test Mode: 25; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low



Condition: 3m VERTICAL

Job No : 04390WM

Mode : 6435 TX RSE

: Wi-Fi 6E 11AX20


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7284.038	11.51	36.67	56.47	53.44	45.15	74.00	-28.85	peak
2	8514.456	12.26	38.30	55.44	53.31	48.43	88.20	-39.77	peak
3	9981.525	12.97	38.90	54.12	51.81	49.56	88.20	-38.64	peak
4	12870.000	15.69	40.37	54.41	47.01	48.66	88.20	-39.54	peak
5	15942.300	17.22	38.66	54.02	47.48	49.34	74.00	-24.66	peak
6	pp17896.250	18.25	43.08	54.48	45.27	52.12	74.00	-21.88	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 25; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:middle



Condition: 3m HORIZONTAL

Job No : 04390WM


Mode : 6475 TX RSE

: Wi-Fi 6E 11AX20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7179.527	11.62	36.56	56.56	53.61	45.23	88.20	-42.97	peak
2	8489.882	12.24	38.32	55.46	53.34	48.44	74.00	-25.56	peak
3	11140.310	14.70	39.54	53.54	49.22	49.92	74.00	-24.08	peak
4	12950.000	15.85	40.35	54.47	47.65	49.38	88.20	-38.82	peak
5	15003.420	16.59	38.80	54.30	48.47	49.56	88.20	-38.64	peak
6	pp17793.090	18.18	42.45	54.46	46.46	52.63	74.00	-21.37	peak



Test Mode: 25; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:middle



Condition: 3m VERTICAL

Job No : 04390WM

Mode : 6475 TX RSE

: Wi-Fi 6E 11AX20


		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7179.527	11.62	36.56	56.56	55.19	46.81	88.20	-41.39	peak
2	8840.473	12.24	38.50	55.14	53.14	48.74	88.20	-39.46	peak
3	11269.860	14.68	39.67	53.58	49.02	49.79	74.00	-24.21	peak
4	12950.000	15.85	40.35	54.47	47.33	49.06	88.20	-39.14	peak
5	15988.450	17.16	38.61	54.00	47.73	49.50	74.00	-24.50	peak
6	pp17844.590	18.21	42.77	54.47	44.81	51.32	74.00	-22.68	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 25; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High



Condition: 3m HORIZONTAL

Job No : 04390WM

Mode : 6515 TX RSE

: Wi-Fi 6E 11AX20


		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6414.167	13.10	34.80	56.82	55.08	46.16	88.20	-42.04	peak
2	8688.480	12.08	38.55	55.28	52.56	47.91	88.20	-40.29	peak
3	11335.190	14.49	39.70	53.60	48.78	49.37	74.00	-24.63	peak
4	13030.000	15.79	40.30	54.50	47.83	49.42	88.20	-38.78	peak
5	15622.990	17.19	38.52	54.11	49.33	50.93	74.00	-23.07	peak
6	pp17844.590	18.21	42.77	54.47	46.13	52.64	74.00	-21.36	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 25; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High



Condition: 3m VERTICAL

Job No : 04390WM


Mode : 6515 TX RSE

: Wi-Fi 6E 11AX20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6432.732	12.79	34.80	56.81	54.16	44.94	88.20	-43.26	Peak
2	8440.945	11.91	38.44	55.50	52.91	47.76	74.00	-26.24	Peak
3	11237.330	14.72	39.64	53.57	49.26	50.05	74.00	-23.95	peak
4	13030.000	15.79	40.30	54.50	47.26	48.85	88.20	-39.35	peak
5	15942.300	17.22	38.66	54.02	47.37	49.23	74.00	-24.77	peak
6	pp17844.590	18.21	42.77	54.47	45.39	51.90	74.00	-22.10	peak



Test Mode: 26; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Condition: 3m HORIZONTAL

Job No : 04390WM


Mode : 6535 TX RSE

: Wi-Fi 6E 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6855.063	11.37	36.02	56.73	54.30	44.96	88.20	-43.24	peak
2	9393.689	12.29	38.80	54.65	52.16	48.60	74.00	-25.40	peak
3	11368.000	14.35	39.70	53.61	49.60	50.04	74.00	-23.96	peak
4	13070.000	15.67	40.30	54.49	48.04	49.52	88.20	-38.68	peak
5	15896.290	17.27	38.69	54.03	47.82	49.75	74.00	-24.25	peak
6	pp17844.590	18.21	42.77	54.47	45.81	52.32	74.00	-21.68	peak



Test Mode: 26; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Condition: 3m VERTICAL

Job No : 04390WM


Mode : 6535 TX RSE

: Wi-Fi 6E 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6414.167	13.10	34.80	56.82	54.76	45.84	88.20	-42.36	peak
2	8713.630	12.11	38.57	55.26	52.55	47.97	88.20	-40.23	peak
3	11368.000	14.35	39.70	53.61	48.95	49.39	74.00	-24.61	peak
4	13070.000	15.67	40.30	54.49	47.77	49.25	88.20	-38.95	peak
5	15850.410	17.16	38.60	54.04	47.80	49.52	74.00	-24.48	peak
6	pp17896.250	18.25	43.08	54.48	45.60	52.45	74.00	-21.55	peak



Test Mode: 26; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Condition: 3m HORIZONTAL

Job No : 04390WM


Mode : 6695 TX RSE

: Wi-Fi 6E 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6451.353	12.48	34.80	56.81	54.15	44.62	88.20	-43.58	Peak
2	8764.146	12.19	38.50	55.21	53.00	48.48	88.20	-39.72	peak
3	10126.820	13.22	39.10	54.02	51.11	49.41	88.20	-38.79	peak
4	13390.000	15.97	40.30	54.46	47.77	49.58	74.00	-24.42	peak
5	15896.290	17.27	38.69	54.03	47.31	49.24	74.00	-24.76	peak
6	pp17844.590	18.21	42.77	54.47	46.04	52.55	74.00	-21.45	peak



Test Mode: 26; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Condition: 3m VERTICAL

Job No : 04390WM

Mode : 6695 TX RSE

: Wi-Fi 6E 11A


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6737.207	11.40	35.62	56.75	54.52	44.79	88.20	-43.41	peak
2	8866.062	12.23	38.53	55.12	53.05	48.69	88.20	-39.51	peak
3	11302.480	14.63	39.70	53.59	49.91	50.65	74.00	-23.35	peak
4	13390.000	15.97	40.30	54.46	46.99	48.80	74.00	-25.20	peak
5	15988.450	17.16	38.61	54.00	47.39	49.16	74.00	-24.84	peak
6	pp17896.250	18.25	43.08	54.48	44.86	51.71	74.00	-22.29	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 26; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Condition: 3m HORIZONTAL

Job No : 04390WM


Mode : 6855 TX RSE

: Wi-Fi 6E 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6954.852	11.37	36.11	56.71	55.65	46.42	88.20	-41.78	peak
2	8738.852	12.15	38.52	55.24	52.54	47.97	88.20	-40.23	peak
3	11140.310	14.70	39.54	53.54	48.64	49.34	74.00	-24.66	peak
4	13710.000	16.36	39.99	54.43	48.50	50.42	88.20	-37.78	peak
5	15942.300	17.22	38.66	54.02	47.71	49.57	74.00	-24.43	peak
6	pp17896.250	18.25	43.08	54.48	45.31	52.16	74.00	-21.84	peak



Test Mode: 26; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Condition: 3m VERTICAL

Job No : 04390WM


Mode : 6855 TX RSE

: Wi-Fi 6E 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7263.015	11.51	36.63	56.49	54.08	45.73	74.00	-28.27	peak
2	9448.149	12.43	38.80	54.60	51.14	47.77	74.00	-26.23	peak
3	11172.560	14.73	39.57	53.55	49.02	49.77	74.00	-24.23	peak
4	13710.000	16.36	39.99	54.43	47.99	49.91	88.20	-38.29	peak
5	15988.450	17.16	38.61	54.00	47.51	49.28	74.00	-24.72	peak
6	pp17896.250	18.25	43.08	54.48	45.45	52.30	74.00	-21.70	peak



Test Mode: 26; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low



Condition: 3m HORIZONTAL

Job No : 04390WM


Mode : 6535 TX RSE

: Wi-Fi 6E 11AX20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6395.654	13.23	34.79	56.82	53.94	45.14	88.20	-43.06	peak
2	8840.473	12.24	38.50	55.14	53.39	48.99	88.20	-39.21	peak
3	10760.540	13.82	39.34	53.64	50.41	49.93	74.00	-24.07	peak
4	13070.000	15.67	40.30	54.49	47.93	49.41	88.20	-38.79	peak
5	15850.410	17.16	38.60	54.04	47.57	49.29	74.00	-24.71	peak
6	pp17844.590	18.21	42.77	54.47	46.24	52.75	74.00	-21.25	peak



Test Mode: 26; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:Low



Condition: 3m VERTICAL

Job No : 04390WM

Mode : 6535 TX RSE

: Wi-Fi 6E 11AX20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6974.982	11.37	36.15	56.71	54.58	45.39	88.20	-42.81	peak
2	8764.146	12.19	38.50	55.21	52.74	48.22	88.20	-39.98	peak
3	11012.250	14.23	39.41	53.50	49.46	49.60	74.00	-24.40	peak
4	13070.000	15.67	40.30	54.49	47.71	49.19	88.20	-39.01	peak
5	15942.300	17.22	38.66	54.02	48.44	50.30	74.00	-23.70	peak
6	pp17896.250	18.25	43.08	54.48	45.18	52.03	74.00	-21.97	peak




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR251000439007

Page: 58 of 688

Test Mode: 26; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:middle



Condition: 3m HORIZONTAL

Job No : 04390WM

Mode : 6695 TX RSE

: Wi-Fi 6E 11AX20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7117.542	11.91	36.44	56.61	53.57	45.31	88.20	-42.89	peak
2	8891.725	12.22	38.58	55.10	53.42	49.12	88.20	-39.08	peak
3	10636.850	13.76	39.34	53.72	50.35	49.73	74.00	-24.27	peak
4	13390.000	15.97	40.30	54.46	47.46	49.27	74.00	-24.73	peak
5	15896.290	17.27	38.69	54.03	47.93	49.86	74.00	-24.14	peak
6	pp17896.250	18.25	43.08	54.48	45.52	52.37	74.00	-21.63	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Shenzhen) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 26; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:middle



Condition: 3m VERTICAL

Job No : 04390WM

Mode : 6695 TX RSE

: Wi-Fi 6E 11AX20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7326.267	11.51	36.75	56.44	53.28	45.10	74.00	-28.90	peak
2	8514.456	12.26	38.30	55.44	53.11	48.23	88.20	-39.97	peak
3	11335.190	14.49	39.70	53.60	49.09	49.68	74.00	-24.32	peak
4	13390.000	15.97	40.30	54.46	46.86	48.67	74.00	-25.33	peak
5	15003.420	16.59	38.80	54.30	48.25	49.34	88.20	-38.86	peak
6	pp17896.250	18.25	43.08	54.48	45.49	52.34	74.00	-21.66	peak




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR251000439007

Page: 60 of 688

Test Mode: 26; Polarity: Horizontal; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High



Condition: 3m HORIZONTAL

Job No : 04390WM

Mode : 6855 TX RSE

: Wi-Fi 6E 11AX20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6414.167	13.10	34.80	56.82	54.02	45.10	88.20	-43.10	peak
2	8840.473	12.24	38.50	55.14	53.51	49.11	88.20	-39.09	peak
3	10393.710	13.62	39.00	53.86	51.38	50.14	88.20	-38.06	peak
4	13710.000	16.36	39.99	54.43	47.38	49.30	88.20	-38.90	peak
5	15896.290	17.27	38.69	54.03	47.45	49.38	74.00	-24.62	peak
6	pp17844.590	18.21	42.77	54.47	44.60	51.11	74.00	-22.89	peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 26; Polarity: Vertical; Modulation:802.11ax(Full RU0); Bandwidth:20MHz; Channel:High



Condition: 3m VERTICAL

Job No : 04390WM

Mode : 6855 TX RSE

: Wi-Fi 6E 11AX20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6602.265	11.60	35.21	56.78	54.78	44.81	88.20	-43.39	peak
2	8688.480	12.08	38.55	55.28	52.52	47.87	88.20	-40.33	peak
3	11302.480	14.63	39.70	53.59	49.14	49.88	74.00	-24.12	peak
4	13710.000	16.36	39.99	54.43	47.12	49.04	88.20	-39.16	peak
5	15577.900	17.11	38.52	54.13	47.92	49.42	74.00	-24.58	peak
6	pp17844.590	18.21	42.77	54.47	46.06	52.57	74.00	-21.43	peak

