FCC RF Test Report

APPLICANT	:	TCL Communication Ltd
EQUIPMENT	:	GSM Quad-band / UMTS Quad-band / LTE 6 band mobile phone
BRAND NAME	:	ALCATEL ONETOUCH
MODEL NAME	:	6045B
MARKETING NAME	:	ALCATEL ONETOUCH IDOL 3 (5.5)
FCC ID	:	2ACCJN001
STANDARD	:	FCC Part 15 Subpart C §15.247
CLASSIFICATION	:	(DTS) Digital Transmission System

The product was received on Jan. 13, 2015 and testing was completed on Feb. 27, 2015. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

Testing Laboratory 2627

SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification subjective to this standard 5
1.5 Modification of EUT 6
1.6 Testing Location 6
1.7 Applicable Standards 6

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **7**

2.1 Carrier Frequency Channel 7
2.2 Pre-Scanned RF Power 8
2.3 Test Mode 9
2.4 Connection Diagram of Test System 10
2.5 Support Unit used in test configuration and system 11
2.6 EUT Operation Test Setup 11
2.7 Measurement Results Explanation Example 11

3 TEST RESULT **12**

3.1 6dB Bandwidth Measurement 12
3.2 Output Power Measurement 14
3.3 Power Spectral Density Measurement 16
3.4 Conducted Band Edges and Spurious Emission Measurement 18
3.5 Radiated Band Edges and Spurious Emission Measurement 28
3.6 AC Conducted Emission Measurement 32
3.7 Antenna Requirements 36

4 LIST OF MEASURING EQUIPMENT **37**

5 UNCERTAINTY OF EVALUATION **38**

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. RADIATED SPURIOUS EMISSION

APPENDIX C. SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR511301C	Rev. 01	Initial issue of report	Apr. 06, 2015
FR511301C	Rev. 02	Revised the equipment to "GSM Quad-band / UMTS Quad-band / LTE 6 band mobile phone".	Apr. 14, 2015
FR511301C	Rev. 03	Update report for revising Brand Name to ALCATEL ONETOUCH	Apr. 20, 2015

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.2	15.247(b)	Power Output Measurement	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges	≤ 20dBc	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 8.46 dB at 2389.830 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 3.28 dB at 0.520 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

TCL Communication Ltd
FLAT/RM 1910-12A BLOCK 3 19/F CHINA HONG KONG CITY 33 CANTON ROAD TSIMSHATSUI KL

1.2 Manufacturer

TCL Communication Ltd
FLAT/RM 1910-12A BLOCK 3 19/F CHINA HONG KONG CITY 33 CANTON ROAD TSIMSHATSUI KL

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	GSM Quad-band / UMTS Quad-band / LTE 6 band mobile phone
Brand Name	ALCATEL ONETOUCH
Model Name	6045B
Marketing Name	ALCATEL ONETOUCH IDOL 3 (5.5)
FCC ID	2ACCJN001
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/ HSPA+(Downlink Only)/DC-HSDPA/LTE/NFC/ WLAN2.4GHz 802.11b/g/n HT20/ WLAN 5GHz 802.11a/n HT20/HT40/ Bluetooth v3.0+EDR/Bluetooth v4.1 LE
HW Version	PIO
SW Version	7S25
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to Antenna	802.11b : 20.54 dBm (0.1132 W) 802.11g : 22.15 dBm (0.1641 W) 802.11n HT20 : 20.96 dBm (0.1247 W)
Antenna Type / Gain	PIFA Antenna with gain -3.0 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.			
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
Test Site No.	**Sporton Site No.**			**FCC Registration No.**
	TH01-KS	03CH01-KS	CO01-KS	149928

Note: The test site complies with ANSI C63.4 2009 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. FCC permits the use of the 1.5 meter table as an alternative in C63.10-2013 through inquiry tracking number 961829.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

2.4GHz 802.11b RF Output Power (dBm)						
Power vs. Channel			Power vs. Data Rate			
Channel	Frequency (MHz)	Data Rate 1Mbps	Channel	2Mbps	5.5Mbps	11Mbps
CH 01	2412 MHz	20.05	CH 11	20.48	20.51	20.53
CH 06	2437 MHz	20.09				
CH 11	2462 MHz	**20.54**				

2.4GHz 802.11g RF Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	Data Rate 6Mbps	Channel	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
CH 01	2412 MHz	21.77	CH 11	21.97	22.02	22.10	22.08	22.05	22.07	22.12
CH 06	2437 MHz	21.96								
CH 11	2462 MHz	**22.15**								

2.4GHz 802.11n HT20 RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 01	2412 MHz	20.52	CH 06	20.82	20.87	20.79	20.93	20.85	20.89	20.91
CH 06	2437 MHz	20.69								
CH 11	2462 MHz	**20.96**								

2.3 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates from the power table described in section 2.2.

<2.4GHz>

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0

Test Cases	
AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + Battery 1 + USB Cable 1(Charging from Adapter 1)
Remark:	For Radiated TCs, the tests were performed with adapter 1, battery 1, earphone and USB cable 1.

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	G480	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A

2.6 EUT Operation Test Setup

For WLAN function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.5 dB.

Offset(dB) = RF cable loss(dB) = 5.5 (dB)

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A of this test report.

Minimum 6dB Bandwidth



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A of this test report.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A of this test report.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A of this test report.

Worst Case Power Density (dBm/3kHz)



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	**Temperature :**	24~25℃
Test Band :	2.4GHz Low	**Relative Humidity :**	49~51%
Test Channel :	01	**Test Engineer :**	Issac Song

WLAN 802.11b Channel 01

100kHz PSD reference Level



Date: 13.FEB.2015 10:12:56

Low Channel Plot



Date: 13.FEB.2015 10:13:21

Spurious Emission 30MHz~3GHz



Date: 13.FEB.2015 10:13:48

Spurious Emission 2GHz~25GHz



Date: 13.FEB.2015 10:14:06

Test Mode :	802.11b	**Temperature :**	24~25℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	49~51%
Test Channel :	06	**Test Engineer :**	Issac Song

WLAN 802.11b Channel 06

100kHz PSD reference Level



Date: 13.FEB.2015 10:20:21

Spurious Emission 30MHz~3GHz



Date: 13.FEB.2015 10:20:47

Spurious Emission 2GHz~25GHz



Date: 13.FEB.2015 10:21:05

Test Mode :	802.11b	**Temperature :**	24~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	49~51%
Test Channel :	11	**Test Engineer :**	Issac Song

WLAN 802.11b Channel 11

100kHz PSD reference Level



Date: 13.FEB.2015 10:25:35

High Channel Plot



Date: 13.FEB.2015 10:25:57

Spurious Emission 30MHz~3GHz



Date: 13.FEB.2015 10:26:23

Spurious Emission 2GHz~25GHz



Date: 13.FEB.2015 10:26:41

Test Mode :	802.11g	**Temperature :**	24~25℃
Test Band :	2.4GHz Low	**Relative Humidity :**	49~51%
Test Channel :	01	**Test Engineer :**	Issac Song

WLAN 802.11g Channel 01

100kHz PSD reference Level



Date: 13.FEB.2015 10:38:27

Low Channel Plot



Date: 13.FEB.2015 10:39:22

Spurious Emission 30MHz~3GHz



Date: 13.FEB.2015 10:42:00

Spurious Emission 2GHz~25GHz



Date: 13.FEB.2015 10:42:18

Test Mode :	802.11g	**Temperature :**	24~25℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	49~51%
Test Channel :	06	**Test Engineer :**	Issac Song

WLAN 802.11g Channel 06

100kHz PSD reference Level



Date: 13.FEB.2015 10:49:37

Spurious Emission 30MHz~3GHz



Date: 13.FEB.2015 10:50:13

Spurious Emission 2GHz~25GHz



Date: 13.FEB.2015 10:50:31

Test Mode :	802.11g	**Temperature :**	24~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	49~51%
Test Channel :	11	**Test Engineer :**	Issac Song

WLAN 802.11g Channel 11

100kHz PSD reference Level



Date: 13.FEB.2015 10:56:06

High Channel Plot



Date: 13.FEB.2015 10:57:22

Spurious Emission 30MHz~3GHz



Date: 13.FEB.2015 11:04:33

Spurious Emission 2GHz~25GHz



Date: 13.FEB.2015 11:04:51

Test Mode :	802.11n HT20	**Temperature :**	24~25℃
Test Band :	2.4GHz Low	**Relative Humidity :**	49~51%
Test Channel :	01	**Test Engineer :**	Issac Song

WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level



Date: 13.FEB.2015 11:10:00

Low Channel Plot



Date: 13.FEB.2015 11:10:25

Spurious Emission 30MHz~3GHz



Date: 13.FEB.2015 11:11:55

Spurious Emission 2GHz~25GHz



Date: 13.FEB.2015 11:12:13

Test Mode :	802.11n HT20	**Temperature :**	24~25℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	49~51%
Test Channel :	06	**Test Engineer :**	Issac Song

WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level



Date: 13.FEB.2015 11:16:10

Spurious Emission 30MHz~3GHz



Date: 13.FEB.2015 11:16:52

Spurious Emission 2GHz~25GHz



Date: 13.FEB.2015 11:17:10

Test Mode :	802.11n HT20	**Temperature :**	24~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	49~51%
Test Channel :	11	**Test Engineer :**	Issac Song

WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level



Date: 13.FEB.2015 11:22:14

High Channel Plot



Date: 13.FEB.2015 11:22:38

Spurious Emission 30MHz~3GHz



Date: 13.FEB.2015 11:26:55

Spurious Emission 2GHz~25GHz



Date: 13.FEB.2015 11:27:13

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. uThe EUT was placed on a turntable with 0.8 meter for freqency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW= 3MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	97.64	8.26	0.12	300Hz
802.11g	87.26	1.37	0.73	1kHz
802.11n HT20	86.49	1.28	0.78	1kHz

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	**Temperature :**	22~24℃
Test Engineer :	Eko Guan	**Relative Humidity :**	33~35%
Test Voltage :	120Vac / 60Hz	**Phase :**	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + Battery 1 + USB Cable 1(Charging from Adapter 1)		



Site : CO01-KS
Condition : FCC PART 15C LISN-L20140306 LINE

	Freq MHz	Level dBuV	Over Limit dB	Limit Line dBuV	Read Level dBuV	LISN Factor dB	Cable Loss dB	Remark
1	0.52	46.73	-9.27	56.00	35.90	0.20	10.63	QP
2 *	0.52	38.13	-7.87	46.00	27.30	0.20	10.63	Average
3	0.59	38.73	-17.27	56.00	27.90	0.20	10.63	QP
4	0.59	29.03	-16.97	46.00	18.20	0.20	10.63	Average
5	1.11	38.55	-17.45	56.00	27.80	0.10	10.65	QP
6	1.11	28.15	-17.85	46.00	17.40	0.10	10.65	Average
7	1.34	38.97	-17.03	56.00	28.20	0.10	10.67	QP
8	1.34	29.37	-16.63	46.00	18.60	0.10	10.67	Average
9	1.65	38.29	-17.71	56.00	27.50	0.10	10.69	QP
10	1.65	28.99	-17.01	46.00	18.20	0.10	10.69	Average
11	1.75	38.69	-17.31	56.00	27.90	0.10	10.69	QP
12	1.75	29.99	-16.01	46.00	19.20	0.10	10.69	Average

Test Mode :	Mode 1	**Temperature :**	22~24℃
Test Engineer :	Eko Guan	**Relative Humidity :**	33~35%
Test Voltage :	120Vac / 60Hz	**Phase :**	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + Battery 1 + USB Cable 1(Charging from Adapter 1)		



Site : CO01-KS
Condition : FCC PART 15C LISN-N20140306 NEUTRAL

		Freq MHz	Level dBuV	Over Limit dB	Limit Line dBuV	Read Level dBuV	LISN Factor dB	Cable Loss dB	Remark
1		0.52	48.52	-7.48	56.00	37.60	0.29	10.63	QP
2	*	0.52	42.72	-3.28	46.00	31.80	0.29	10.63	Average
3		0.59	41.68	-14.32	56.00	30.80	0.25	10.63	QP
4		0.59	36.78	-9.22	46.00	25.90	0.25	10.63	Average
5		1.09	40.95	-15.05	56.00	30.20	0.10	10.65	QP
6		1.09	35.45	-10.55	46.00	24.70	0.10	10.65	Average
7		1.22	39.56	-16.44	56.00	28.80	0.10	10.66	QP
8		1.22	35.06	-10.94	46.00	24.30	0.10	10.66	Average
9		1.34	41.07	-14.93	56.00	30.30	0.10	10.67	QP
10		1.34	35.67	-10.33	46.00	24.90	0.10	10.67	Average
11		1.71	41.29	-14.71	56.00	30.50	0.10	10.69	QP
12		1.71	35.39	-10.61	46.00	24.60	0.10	10.69	Average

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Oct. 28, 2014	Feb. 13, 2015	Oct. 27, 2015	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	30MHz~40GHz	Jan. 23, 2015	Feb. 13, 2015	Jan. 22, 2016	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 23, 2015	Feb. 13, 2015	Jan. 22, 2016	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Oct. 25, 2014	Feb. 19, 2015	Oct. 24, 2015	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	101399	9kHz~30GHz	May 04, 2014	Feb. 19, 2015	May 03, 2015	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 13, 2014	Feb. 19, 2015	Nov. 12, 2015	Radiation (03CH01-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	25Mhz-2Ghz	Jan. 17, 2015	Feb. 19, 2015	Jan. 16, 2016	Radiation (03CH01-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 17, 2015	Feb. 19, 2015	Jan. 16, 2016	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701030	1GHz~18GHz	Nov. 08, 2014	Feb. 19, 2015	Nov. 07, 2015	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Mar. 10, 2014	Feb. 19, 2015	Mar. 09, 2015	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1GHz /32dB	May 04, 2014	Feb. 19, 2015	May 03, 2015	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02371	1GHz~26.5GHz	Oct. 28, 2014	Feb. 19, 2015	Oct. 27, 2015	Radiation (03CH01-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Feb. 19, 2015	NCR	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Feb. 19, 2015	NCR	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Feb. 19, 2015	NCR	Radiation (03CH01-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	May 04, 2014	Feb. 27, 2015	May 03, 2015	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 25, 2014	Feb. 27, 2015	Oct. 24, 2015	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 25, 2014	Feb. 27, 2015	Oct. 24, 2015	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 25, 2014	Feb. 27, 2015	Oct. 24, 2015	Conduction (CO01-KS)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.3dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.5dB

Appendix A. Conducted Test Results

Test Engineer:	Len Li	Temperature:	21~25	°C
Test Date:	2015/2/13	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	13.70	8.52	0.50	Pass
11b	1Mbps	1	6	2437	13.95	8.52	0.50	Pass
11b	1Mbps	1	11	2462	13.85	8.56	0.50	Pass
11g	6Mbps	1	1	2412	18.15	16.32	0.50	Pass
11g	6Mbps	1	6	2437	18.35	16.34	0.50	Pass
11g	6Mbps	1	11	2462	18.30	16.36	0.50	Pass
HT20	MCS0	1	1	2412	19.00	17.52	0.50	Pass
HT20	MCS0	1	6	2437	19.00	17.56	0.50	Pass
HT20	MCS0	1	11	2462	19.00	17.56	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	20.05	30.00	-3.00	17.05	36.00	Pass
11b	1Mbps	1	6	2437	20.09	30.00	-3.00	17.09	36.00	Pass
11b	1Mbps	1	11	2462	20.54	30.00	-3.00	17.54	36.00	Pass
11g	6Mbps	1	1	2412	21.77	30.00	-3.00	18.77	36.00	Pass
11g	6Mbps	1	6	2437	21.96	30.00	-3.00	18.96	36.00	Pass
11g	6Mbps	1	11	2462	22.15	30.00	-3.00	19.15	36.00	Pass
HT20	MCS0	1	1	2412	20.52	30.00	-3.00	17.52	36.00	Pass
HT20	MCS0	1	6	2437	20.69	30.00	-3.00	17.69	36.00	Pass
HT20	MCS0	1	11	2462	20.96	30.00	-3.00	17.96	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.10	17.30
11b	1Mbps	1	6	2437	0.10	17.44
11b	1Mbps	1	11	2462	0.10	18.14
11g	6Mbps	1	1	2412	0.59	13.16
11g	6Mbps	1	6	2437	0.59	13.47
11g	6Mbps	1	11	2462	0.59	13.96
HT20	MCS0	1	1	2412	0.63	11.42
HT20	MCS0	1	6	2437	0.63	11.75
HT20	MCS0	1	11	2462	0.63	12.20

Report Number : FR511301C

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-5.48	-3.00	8.00	Pass
11b	1Mbps	1	6	2437	-4.81	-3.00	8.00	Pass
11b	1Mbps	1	11	2462	-5.45	-3.00	8.00	Pass
11g	6Mbps	1	1	2412	-12.42	-3.00	8.00	Pass
11g	6Mbps	1	6	2437	-11.83	-3.00	8.00	Pass
11g	6Mbps	1	11	2462	-11.24	-3.00	8.00	Pass
HT20	MCS0	1	1	2412	-13.35	-3.00	8.00	Pass
HT20	MCS0	1	6	2437	-12.90	-3.00	8.00	Pass
HT20	MCS0	1	11	2462	-14.56	-3.00	8.00	Pass

Appendix B. Radiated Spurious Emission

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz	*	2410.438	104.14	-	-	99.63	31.31	9.22	36.02	159	154	P	H
	*	2411.189	99.33	-	-	94.82	31.31	9.22	36.02	159	154	A	H
		2389.56	53.59	-20.41	74	49.2	31.3	9.17	36.08	159	154	P	H
		2387.49	41.01	-12.99	54	36.62	31.3	9.17	36.08	159	154	A	H
	*	2410.521	98.11	-	-	93.6	31.31	9.22	36.02	161	180	P	V
	*	2411.189	93.37	-	-	88.86	31.31	9.22	36.02	161	180	A	V
		2388.03	52.35	-21.65	74	47.96	31.3	9.17	36.08	161	180	P	V
		2387.67	40.12	-13.88	54	35.73	31.3	9.17	36.08	161	180	A	V
802.11b CH 06 2437MHz	*	2438.326	104.8	-	-	103.15	31.34	6.22	35.91	203	31	P	H
	*	2436.239	100.17	-	-	98.58	31.33	6.22	35.96	203	31	A	H
	*	2438.159	101.82	-	-	100.17	31.34	6.22	35.91	191	138	P	V
	*	2436.239	96.78	-	-	95.19	31.33	6.22	35.96	191	138	A	V
802.11b CH 11 2462MHz	*	2463.293	104.22	-	-	99.43	31.36	9.28	35.85	150	150	P	H
	*	2461.289	99.34	-	-	94.55	31.36	9.28	35.85	150	150	A	H
		2487.6	53.58	-20.42	74	48.6	31.39	9.33	35.74	150	150	P	H
		2487.28	42.1	-11.90	54	37.19	31.37	9.33	35.79	150	150	A	H
	*	2463.376	100.08	-	-	95.29	31.36	9.28	35.85	202	141	P	V
	*	2461.289	95.44	-	-	90.65	31.36	9.28	35.85	202	141	A	V
		2488.24	53.29	-20.71	74	48.31	31.39	9.33	35.74	202	141	P	V
		2487.4	40.63	-13.37	54	35.72	31.37	9.33	35.79	202	141	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		4824	44.64	-29.36	74	37.67	34.89	8.73	36.65	150	345	P	H
		4824	45.58	-28.42	74	38.61	34.89	8.73	36.65	150	32	P	V
802.11b CH 06 2437MHz		4875	43.57	-30.43	74	36.73	34.92	8.76	36.84	150	0	P	H
		7311	44.72	-29.28	74	37.18	35.56	10.84	38.86	150	91	P	H
		4875	44.36	-29.64	74	37.52	34.92	8.76	36.84	150	63	P	V
		7311	46.08	-27.92	74	38.54	35.56	10.84	38.86	150	98	P	V
802.11b CH 11 2462MHz		4923	45.24	-28.76	74	38.53	34.95	8.79	37.03	150	98	P	H
		7386	46.4	-27.60	74	39.12	35.58	10.89	39.19	150	96	P	H
		4923	44.93	-29.07	74	38.22	34.95	8.79	37.03	150	68	P	V
		7386	47.23	-26.77	74	39.95	35.58	10.89	39.19	150	256	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11g (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz	*	2408.35	103.64	-	-	99.13	31.31	9.22	36.02	155	140	P	H
	*	2405.26	92.42	-	-	87.91	31.31	9.22	36.02	155	140	A	H
		2389.83	65.54	-8.46	74	61.15	31.3	9.17	36.08	155	140	P	H
		2390	44.73	-9.27	54	40.34	31.3	9.17	36.08	155	140	A	H
	*	2406.012	100.06	-	-	95.55	31.31	9.22	36.02	214	111	P	V
	*	2405.594	89.65	-	-	85.14	31.31	9.22	36.02	214	111	A	V
		2389.92	59.82	-14.18	74	55.43	31.3	9.17	36.08	214	111	P	V
		2390	41.77	-12.23	54	37.38	31.3	9.17	36.08	214	111	A	V
802.11g CH 06 2437MHz	*	2439.329	103.05	-	-	101.34	31.34	6.28	35.91	159	157	P	H
	*	2440.498	91.57	-	-	89.86	31.34	6.28	35.91	159	157	A	H
	*	2442.084	98.12	-	-	96.41	31.34	6.28	35.91	162	144	P	V
	*	2441.667	86.95	-	-	85.24	31.34	6.28	35.91	162	144	A	V
802.11g CH 11 2462MHz	*	2469.054	100.04	-	-	95.25	31.36	9.28	35.85	150	148	P	H
	*	2468.804	89.28	-	-	84.49	31.36	9.28	35.85	150	148	A	H
		2483.76	64.53	-9.47	74	59.62	31.37	9.33	35.79	150	148	P	H
		2483.52	43.68	-10.32	54	38.77	31.37	9.33	35.79	150	148	A	H
	*	2466.049	98.39	-	-	93.6	31.36	9.28	35.85	221	127	P	V
	*	2468.136	87.45	-	-	82.66	31.36	9.28	35.85	221	127	A	V
		2483.52	61.16	-12.84	74	56.25	31.37	9.33	35.79	221	127	P	V
		2483.52	42.35	-11.65	54	37.44	31.37	9.33	35.79	221	127	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		4824	45.02	-28.98	74	38.05	34.89	8.73	36.65	150	120	P	H
		4824	45.95	-28.05	74	38.98	34.89	8.73	36.65	150	100	P	V
802.11g CH 06 2437MHz		4875	42.13	-31.87	74	35.29	34.92	8.76	36.84	150	120	P	H
		7311	44.38	-29.62	74	36.84	35.56	10.84	38.86	150	0	P	H
		4875	44.26	-29.74	74	37.42	34.92	8.76	36.84	150	10	P	V
		7311	44.35	-29.65	74	36.81	35.56	10.84	38.86	150	39	P	V
802.11g CH 11 2462MHz		4923	43.7	-30.30	74	36.99	34.95	8.79	37.03	150	98	P	H
		7386	46.68	-27.32	74	39.4	35.58	10.89	39.19	150	247	P	H
		4923	45.17	-28.83	74	38.46	34.95	8.79	37.03	150	68	P	V
		7386	46.04	-27.96	74	38.76	35.58	10.89	39.19	150	143	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz	*	2405.427	101.86	-	-	97.35	31.31	9.22	36.02	100	149	P	H
	*	2404.509	91.29	-	-	86.78	31.31	9.22	36.02	100	149	A	H
		2389.2	63.76	-10.24	74	59.37	31.3	9.17	36.08	100	149	P	H
		2390	43.96	-10.04	54	39.57	31.3	9.17	36.08	100	149	A	H
	*	2406.763	95.57	-	-	91.06	31.31	9.22	36.02	102	186	P	V
	*	2404.676	84.8	-	-	80.29	31.31	9.22	36.02	102	186	A	V
		2390	59.29	-14.71	74	54.9	31.3	9.17	36.08	102	186	P	V
		2390	41.01	-12.99	54	36.62	31.3	9.17	36.08	102	186	A	V
802.11n HT20 CH 06 2437MHz	*	2440.498	103.04	-	-	101.33	31.34	6.28	35.91	159	146	P	H
	*	2441.833	91.99	-	-	90.28	31.34	6.28	35.91	159	146	A	H
	*	2431.563	99.5	-	-	97.91	31.33	6.22	35.96	121	192	P	V
	*	2431.98	88.82	-	-	87.23	31.33	6.22	35.96	121	192	A	V
802.11n HT20 CH 11 2462MHz	*	2456.446	99.49	-	-	94.7	31.36	9.28	35.85	142	152	P	H
	*	2455.11	88.25	-	-	83.46	31.36	9.28	35.85	142	152	A	H
		2483.68	62.76	-11.24	74	57.85	31.37	9.33	35.79	142	152	P	H
		2483.52	43.91	-10.09	54	39	31.37	9.33	35.79	142	152	A	H
	*	2456.53	93.73	-	-	88.94	31.36	9.28	35.85	100	175	P	V
	*	2454.442	83	-	-	78.21	31.36	9.28	35.85	100	175	A	V
		2483.52	58.87	-15.13	74	53.96	31.37	9.33	35.79	100	175	P	V
		2483.76	40.69	-13.31	54	35.78	31.37	9.33	35.79	100	175	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		4824	44.74	-29.26	74	37.77	34.89	8.73	36.65	100	236	P	H
		4824	44.65	-29.35	74	37.68	34.89	8.73	36.65	110	20	P	V
802.11n HT20 CH 06 2437MHz		4875	45.45	-28.55	74	38.61	34.92	8.76	36.84	100	210	P	H
		7311	46.04	-27.96	74	38.5	35.56	10.84	38.86	120	0	P	H
		4875	45.14	-28.86	74	38.3	34.92	8.76	36.84	100	45	P	V
		7311	45.59	-28.41	74	38.05	35.56	10.84	38.86	100	97	P	V
802.11n HT20 CH 11 2462MHz		4923	44.3	-29.70	74	37.59	34.95	8.79	37.03	103	20	P	H
		7386	45.65	-28.35	74	38.37	35.58	10.89	39.19	100	67	P	H
		4923	46.09	-27.91	74	39.38	34.95	8.79	37.03	100	34	P	V
		7386	46.1	-27.90	74	38.82	35.58	10.89	39.19	100	164	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

15C Emission below 1GHz

2.4GHz WIFI 802.11b (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11b LF		30.97	18.78	-21.22	40	31.94	18.71	0.79	32.66	-	-	P	H
		56.19	19.86	-20.14	40	44.53	7.14	0.79	32.6	-	-	P	H
		89.17	24.32	-19.18	43.5	45.81	10.09	1.04	32.62	-	-	P	H
		149.31	29.27	-14.23	43.5	48.7	11.69	1.44	32.56	100	214	P	H
		173.56	27.59	-15.91	43.5	47.83	10.81	1.44	32.49	-	-	P	H
		467.47	25.53	-20.47	46	37.96	17.23	2.51	32.17	-	-	P	H
		30	24.54	-15.46	40	37.21	19.2	0.79	32.66	137	45	P	V
		40.67	22.23	-17.77	40	40.26	13.79	0.79	32.61	-	-	P	V
		89.17	21.65	-21.85	43.5	43.14	10.09	1.04	32.62	-	-	P	V
		146.4	25.28	-18.22	43.5	44.94	11.67	1.23	32.56	-	-	P	V
		173.56	26.54	-16.96	43.5	46.78	10.81	1.44	32.49	-	-	P	V
		211.39	23.39	-20.11	43.5	43.94	10.33	1.61	32.49	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

15C Emission below 1GHz

2.4GHz WIFI 802.11g (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		31.94	18.22	-21.78	40	31.86	18.22	0.79	32.65	-	-	P	H
		58.13	19.64	-20.36	40	44.83	6.62	0.79	32.6	-	-	P	H
		89.17	24.33	-19.17	43.5	45.82	10.09	1.04	32.62	-	-	P	H
		148.34	27.79	-15.71	43.5	47.23	11.68	1.44	32.56	127	45	P	H
		174.53	26.82	-16.68	43.5	47.1	10.77	1.44	32.49	-	-	P	H
		476.2	23.51	-22.49	46	35.97	17.2	2.51	32.17	-	-	P	H
		30	28.28	-11.72	40	40.95	19.2	0.79	32.66	100	215	P	V
		53.28	22.84	-17.16	40	46.74	7.92	0.79	32.61	-	-	P	V
		80.44	19.53	-20.47	40	42.04	9.1	1.04	32.65	-	-	P	V
		126.03	21.2	-22.30	43.5	41.08	11.51	1.23	32.62	-	-	P	V
		148.34	20.03	-23.47	43.5	39.47	11.68	1.44	32.56	-	-	P	V
		211.39	22.88	-20.62	43.5	43.43	10.33	1.61	32.49	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

15C Emission below 1GHz

2.4GHz WIFI 802.11n HT20 (LF)

WIFI	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT20 LF		30	19.15	-20.85	40	31.82	19.2	0.79	32.66	-	-	P	H
		58.13	18.86	-21.14	40	44.05	6.62	0.79	32.6	-	-	P	H
		89.17	23.76	-19.74	43.5	45.25	10.09	1.04	32.62	-	-	P	H
		148.34	26.71	-16.79	43.5	46.15	11.68	1.44	32.56	100	214	P	H
		174.53	26.16	-17.34	43.5	46.44	10.77	1.44	32.49	-	-	P	H
		213.33	23.74	-19.76	43.5	44.2	10.42	1.61	32.49	-	-	P	H
		30	25.41	-14.59	40	38.08	19.2	0.79	32.66	100	214	P	V
		52.31	22.27	-17.73	40	45.91	8.18	0.79	32.61	-	-	P	V
		86.26	16.6	-23.40	40	38.43	9.76	1.04	32.63	-	-	P	V
		149.31	18.27	-25.23	43.5	37.7	11.69	1.44	32.56	-	-	P	V
		209.45	23.59	-19.91	43.5	44.22	10.24	1.61	32.48	-	-	P	V
		445.16	22.01	-23.99	46	34.53	17.22	2.4	32.14	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.