


FCC RF Test Report


APPLICANT : TCL Communication Ltd
EQUIPMENT : GSM Quad-band / UMTS Quad-band / LTE 6 band
mobile phone
BRAND NAME : ALCATEL ONETOUCH
MODEL NAME : 6045I
MARKETING NAME : ALCATEL ONETOUCH IDOL 3 (5.5)
FCC ID : 2ACCJN002
STANDARD : FCC Part 15 Subpart C §15.225
CLASSIFICATION : (DXX) Low Power Communication Device Transmitter

The product testing was completed on Mar. 01, 2016. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



Prepared by: James Huang / Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.

No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



Table of Contents

SUMMARY OF THE TEST RESULT	4
1. GENERAL INFORMATION.....	5
1.1 Applicant	5
1.2 Manufacturer.....	5
1.3 Product Details.....	5
1.4 Modification of EUT.....	6
1.5 Accessories and Support Equipment	6
1.6 Testing Location	7
1.7 Applicable Standards	8
1.8 Test Modes.....	8
1.9 Test Configurations.....	9
1.10 Table for Supporting Units	10
2. CONDUCTED EMISSION TEST.....	11
2.1 Measuring Instruments	11
2.2 Test setup	11
2.3 Test Result of Conducted Emission Test.....	11
2.4 AC Power Line Conducted Emissions Measurement	12
3. CONDUCTED TEST ITEMS	13
3.1 Measuring Instruments	13
3.2 Test Setup	13
3.3 Test Result of Conducted Test Items.....	13
3.4 20dB Spectrum Bandwidth Measurement	14
3.5 Frequency Stability Measurement	14
4. RADIATED TEST ITEMS.....	15
4.1 Measuring Instruments	15
4.2 Test Setup	15
4.3 Test Result of Radiated Test Items	15
4.4 Field Strength of Fundamental Emissions and Mask Measurement	16
4.5 Radiated Emissions Measurement	17
5. LIST OF MEASURING EQUIPMENT	19
APPENDIX A. SETUP PHOTOGRAPHS OF EUT	
APPENDIX B. TEST RESULTS OF CONDUCTED EMISSION TEST	
APPENDIX C. TEST RESULTS OF CONDUCTED TEST ITEMS	
C.1. Test Result of 20dB Spectrum Bandwidth	
C.2 Test Result of Frequency Stability	
APPENDIX D. TEST RESULTS OF RADIATED TEST ITEMS	
D.1 Test Result of Field Strength of Fundamental Emissions	
D.2 Results of Radiated Emissions (9 kHz~30MHz)	
D.3 Results of Radiated Emissions (30MHz~1GHz)	
APPENDIX E. TEST RESULTS OF RADIATED TEST ITEMS FOR SPOT CHECK	
E.1 Test Result of Field Strength of Fundamental Emissions	
E.2 Results of Radiated Emissions (9 kHz~30MHz)	
E.3 Results of Radiated Emissions (30MHz~1GHz)	
APPENDIX F. PRODUCT EQUALITY DECLARATION	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR511301-30D	Rev. 01	This is a variant product of 6045I. Added a new battery, and only the worst case of Radiated spurious emission from original test report (Sporton Report Number FR511301D) were verified for the difference and the original test data were remain representative.	Mar. 07, 2016



SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	FCC Rule	Description of Test	Result	Under Limit
3.1	15.207	AC Power Line Conducted Emissions	Complies	3.08 dB at 0.520MHz
3.2	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Complies	66.750 dB at 13.560 MHz
3.3	2.1049	20dB Spectrum Bandwidth	Complies	-
3.4	15.225(d) 15.209	Radiated Emissions	Complies	5.10 dB at 33.880 MHz
3.5	15.225(e)	Frequency Stability	Complies	-
3.6	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	2.3 dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz) for 03CH01-KS	5.0 dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz) for 03CH02-KS	5.1 dB	Confidence levels of 95%



1. GENERAL INFORMATION

1.1 Applicant

TCL Communication Ltd

FLAT/RM 1910-12A BLOCK 3 19/F CHINA HONG KONG CITY 33 CANTON ROAD TSIMSHATSUI KL

1.2 Manufacturer

TCL Communication Ltd

FLAT/RM 1910-12A BLOCK 3 19/F CHINA HONG KONG CITY 33 CANTON ROAD TSIMSHATSUI KL

1.3 Product Details

Items	Description
Tx/Rx Frequency Range	13.553 ~ 13.567MHz
Channel Number	1
20dBW	2.64 kHz
99%OBW	2.24 kHz
Antenna Type	Loop Antenna
Type of Modulation	ASK

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Accessories and Support Equipment

Specification of Accessory				
AC Adapter	Brand Name	ALCATEL ONETOUCH	Model Name	UC13US
	Power Rating	I/P: 100-240Vac, 500mA, O/P: 5Vdc, 2000mA		
	P/N	CBA0059AG0C1		
Original Battery	Brand Name	ALCATEL ONETOUCH	Model Name	TLp029A2-S
	Power Rating	3.8Vdc, 2910mAh		
	S/N	C2910002C2Y0042G		
Added Battery	Brand Name	ALCATEL ONETOUCH	Model Name	TLp029AJ
	Power Rating	3.8Vdc, 2910mAh		
	S/N	C2910003CJY9411D		
USB Cable	Brand Name	ALCATEL ONETOUCH	Model Name	CDA0000043C2
	Signal Line Type	1.10m shielded without core		
Earphone 1	Brand Name	ALCATEL ONETOUCH	Model Name	CCA0001A10C9
	Signal Line Type	1.16m non-shielded without core		
Earphone 2	Brand Name	JBL	Model Name	CCB0029A10CC
	Signal Line Type	1.38m non-shielded without core		



1.6 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.			
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
Test Site No.	Sporton Site No.			FCC Registration No.
	TH01-KS	CO01-KS	03CH01-KS	149928
Test Engineer	Issac Song	Eko Guan	Nick Su	
Temperature	24~25℃	22~24℃	22~23℃	
Relative Humidity	49~51 %	33~35 %	40~41℃	

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.	FCC Registration No.	
	03CH02-KS	306251	
Test Engineer	Star Wei		
Temperature	22~23℃		
Relative Humidity	42~43℃		

Note: The test site complies with ANSI C63.4 2009 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.225
- ♦ ANSI C63.10-2013


1.8 Test Modes

Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.


Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
20dB Spectrum Bandwidth	Frequency Stability
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz
Note: 1. The EUT was programmed to be in continuously transmitting mode. 2. The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmit at 13.56MHz and is placed around 3 cm gap to the EUT.	

1.9 Test Configurations

<AC Conducted Emissions>



<For Fundamental Emissions and Mask and Radiated Emissions Measurement>



**1.10 Table for Supporting Units**


Support Unit	Manufacturer	Model	FCC ID
NFC Card	N/A	N/A	N/A
WLAN AP	D-Link	DIR-855	KA2DIR855A2
Notebook	Lenovo	G480	PRC4
Bluetooth Earphone	Nokia	BH-102	PYAHS-107W
DC Power Supply	GW INSTEK	GPD-2303S	N/A
System Simulator	R&S	CMU 200	N/A

2. CONDUCTED EMISSION TEST

2.1 Measuring Instruments

See list of measuring instruments of this test report.

2.2 Test setup



2.3 Test Result of Conducted Emission Test

Please refer to Appendix B.

2.4 AC Power Line Conducted Emissions Measurement

2.4.1 Limit

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

2.4.2 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3. CONDUCTED TEST ITEMS

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 20dB Spectrum Bandwidth



3.2.2 Frequency Stability



3.3 Test Result of Conducted Test Items

Please refer to Appendix C.

3.4 20dB Spectrum Bandwidth Measurement

3.4.1 Limit

Intentional radiators must be designed to ensure that the 20 dB bandwidth of the emissions in the specific band 13.553~13.567MHz

3.4.2 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak Max hold mode.
2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.

3.5 Frequency Stability Measurement

3.5.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

3.5.2 Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire emissions bandwidth.
4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
5. The f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 10^6$ ppm and the limit is less than ± 100 ppm.
6. Extreme temperature rule is -20°C~50°C.


4. RADIATED TEST ITEMS

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated emissions below 30MHz



4.2.2 For radiated emissions above 30MHz



4.3 Test Result of Radiated Test Items

Please refer to Appendix D.

4.4 Field Strength of Fundamental Emissions and Mask Measurement

4.4.1 Limit

Rules and specifications	CFR 47 Part 15 section 15.225(a)-(d)			
Description	Compliance with the spectrum mask is tested using a spectrum analyzer with RBW set to a 9kHz for the band 13.553~13.567MHz			
Freq. of Emission (MHz)	Field Strength (μV/m) at 30m	Field Strength (dBμV/m) at 30m	Field Strength (dBμV/m) at 10m	Field Strength (dBμV/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

4.4.2 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
4. For Fundamental emissions, use the receiver to measure QP reading.
5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. Compliance with the spectrum mask is tested using a spectrum analyzer with RBW set to a 9kHz for the band 13.553~13.567MHz.

Note: Emission level (dBμV/m) = 20 log Emission level (μV/m).

4.5 Radiated Emissions Measurement

4.5.1 Limit

The field strength of any emissions which appear outside of 13.553~13.567MHz band shall not exceed the general radiated emissions limits.

Frequencies (MHz)	Field Strength (μ V/m)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2 Measuring Instrument Setting

The following table is the setting of receiver.

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

4.5.3 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. Antenna Requirements.

4.5.4 Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

4.5.5 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.




5. LIST OF MEASURING EQUIPMENT

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Oct. 28, 2014	Feb. 13, 2015	Oct. 27, 2015	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 25, 2014	Feb. 13, 2015	Oct. 24, 2015	Conducted (TH01-KS)
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	May 04, 2014	Feb. 27, 2015	May 03, 2015	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 25, 2014	Feb. 27, 2015	Oct. 24, 2015	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 25, 2014	Feb. 27, 2015	Oct. 24, 2015	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 25, 2014	Feb. 27, 2015	Oct. 24, 2015	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESC1	100534	9kHz~3GHz	Oct. 25, 2014	Feb. 19, 2015	Oct. 24, 2015	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 13, 2014	Feb. 19, 2015	Nov. 12, 2015	Radiation (03CH01-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	25Mhz-2Ghz	Jan. 17, 2015	Feb. 19, 2015	Jan. 16, 2016	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1GHz /32dB	May 04, 2014	Feb. 19, 2015	May 03, 2015	Radiation (03CH01-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Feb. 19, 2015	NCR	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Feb. 19, 2015	NCR	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Feb. 19, 2015	NCR	Radiation (03CH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Max 30dBm	Sep. 10, 2015	Mar. 01, 2016	Sep. 09, 2016	Radiation (03CH02-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 07, 2015	Mar. 01, 2016	Nov. 06, 2016	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	37879	30MHz-2GHz	Sep. 12, 2015	Mar. 01, 2016	Sep. 11, 2016	Radiation (03CH02-KS)
Amplifier	com-power	PA-103A	161069	1kHz ~1000MHz	May 04, 2015	Mar. 01, 2016	May 03, 2016	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Mar. 01, 2016	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Mar. 01, 2016	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Mar. 01, 2016	NCR	Radiation (03CH02-KS)

Appendix B. Test Results of Conducted Emission Test

Test Mode :	NFC Tx	Test Voltage :	120Vac / 60Hz
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone 2 + Battery + NFC Tx		




Site : CO01-KS
Condition : FCC PART 15C LISN-L20140306 LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.53	44.73	-11.27	56.00	33.90	0.20	10.63	QP
2	0.53	36.43	-9.57	46.00	25.60	0.20	10.63	Average
3	0.59	38.53	-17.47	56.00	27.70	0.20	10.63	QP
4	0.59	29.73	-16.27	46.00	18.90	0.20	10.63	Average
5	1.36	39.57	-16.43	56.00	28.80	0.10	10.67	QP
6	1.36	29.57	-16.43	46.00	18.80	0.10	10.67	Average
7	1.50	39.58	-16.42	56.00	28.80	0.10	10.68	QP
8	1.50	29.88	-16.12	46.00	19.10	0.10	10.68	Average
9	1.66	39.49	-16.51	56.00	28.70	0.10	10.69	QP
10	1.66	29.89	-16.11	46.00	19.10	0.10	10.69	Average
11	3.33	37.17	-18.83	56.00	26.20	0.16	10.81	QP
12	3.33	27.57	-18.43	46.00	16.60	0.16	10.81	Average
13	13.56	58.38	-1.62	60.00	47.20	0.20	10.98	QP
14 *	13.56	54.48	4.48	50.00	43.30	0.20	10.98	Average

(1) The EUT is with NFC antenna during testing.



Test Mode :	NFC Tx	Test Voltage :	120Vac / 60Hz
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone 2 + Battery + NFC Tx		




Site : CO01-KS
Condition : FCC PART 15C LISN-N20140306 NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.52	47.92	-8.08	56.00	37.00	0.29	10.63	QP
2	0.52	42.92	-3.08	46.00	32.00	0.29	10.63	Average
3	0.59	41.58	-14.42	56.00	30.70	0.25	10.63	QP
4	0.59	36.78	-9.22	46.00	25.90	0.25	10.63	Average
5	1.12	40.66	-15.34	56.00	29.90	0.10	10.66	QP
6	1.12	34.96	-11.04	46.00	24.20	0.10	10.66	Average
7	1.35	41.07	-14.93	56.00	30.30	0.10	10.67	QP
8	1.35	35.47	-10.53	46.00	24.70	0.10	10.67	Average
9	1.52	41.28	-14.72	56.00	30.50	0.10	10.68	QP
10	1.52	35.48	-10.52	46.00	24.70	0.10	10.68	Average
11	3.45	37.48	-18.52	56.00	26.50	0.17	10.81	QP
12	3.45	32.48	-13.52	46.00	21.50	0.17	10.81	Average
13	13.56	52.57	-7.43	60.00	41.31	0.28	10.98	QP
14 *	13.56	50.07	0.07	50.00	38.81	0.28	10.98	Average

(1) The EUT is with NFC antenna during testing.



Test Mode :	NFC Tx	Test Voltage :	120Vac / 60Hz
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone 2 + Battery + NFC Tx		




Site : CO01-KS
Condition : FCC PART 15C LISN-L20140306 LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.52	45.03	-10.97	56.00	34.20	0.20	10.63	QP
2 *	0.52	35.13	-10.87	46.00	24.30	0.20	10.63	Average
3	0.59	38.23	-17.77	56.00	27.40	0.20	10.63	QP
4	0.59	28.53	-17.47	46.00	17.70	0.20	10.63	Average
5	1.12	38.35	-17.65	56.00	27.60	0.10	10.65	QP
6	1.12	29.05	-16.95	46.00	18.30	0.10	10.65	Average
7	1.37	37.97	-18.03	56.00	27.20	0.10	10.67	QP
8	1.37	28.27	-17.73	46.00	17.50	0.10	10.67	Average
9	1.56	38.29	-17.71	56.00	27.50	0.10	10.69	QP
10	1.56	28.59	-17.41	46.00	17.80	0.10	10.69	Average
11	1.71	38.69	-17.31	56.00	27.90	0.10	10.69	QP
12	1.71	29.09	-16.91	46.00	18.30	0.10	10.69	Average

(2) The NFC antenna is replaced by a dummy load during test.



Test Mode :	NFC Tx	Test Voltage :	120Vac / 60Hz
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone 2 + Battery + NFC Tx		



Site : CO01-KS
Condition : FCC PART 15C LISN-N20140306 NEUTRAL



	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.52	46.52	-9.48	56.00	35.60	0.29	10.63	QP
2 *	0.52	41.02	-4.98	46.00	30.10	0.29	10.63	Average
3	0.59	40.78	-15.22	56.00	29.90	0.25	10.63	QP
4	0.59	35.98	-10.02	46.00	25.10	0.25	10.63	Average
5	1.12	39.26	-16.74	56.00	28.50	0.10	10.66	QP
6	1.12	33.56	-12.44	46.00	22.80	0.10	10.66	Average
7	1.33	40.67	-15.33	56.00	29.90	0.10	10.67	QP
8	1.33	34.97	-11.03	46.00	24.20	0.10	10.67	Average
9	1.52	40.68	-15.32	56.00	29.90	0.10	10.68	QP
10	1.52	34.98	-11.02	46.00	24.20	0.10	10.68	Average
11	1.68	40.29	-15.71	56.00	29.50	0.10	10.69	QP
12	1.68	34.59	-11.41	46.00	23.80	0.10	10.69	Average

(2) The NFC antenna is replaced by a dummy load during test.



Appendix C. Test Results of Conducted Test Items

C.1 Test Result of 20dB Spectrum Bandwidth


Test mode		Test Frequency (MHz)	
NFC Tx		13.56	
			
20dB Bandwidth (kHz)	2.64	99% Occupied BW (kHz)	2.24
Frequency range (MHz)	$f_L > 13.553$	13.55860	Test Result
	$f_H < 13.567$	13.56124	Complies

C.2 Test Result of Frequency Stability

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability	
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (°C)	Measurement Frequency (MHz)
120	13.559940	-20	13.560000
102	13.559920	-10	13.560000
138	13.559940	0	13.559960
-	-	10	13.559960
-	-	20	13.559920
-	-	30	13.559900
-	-	40	13.559890
-	-	50	13.559920
Max.Deviation (MHz)	-0.000080	Max.Deviation (MHz)	-0.000110
Max.Deviation (ppm)	-5.8997	Max.Deviation (ppm)	-8.1121
Limit	FS < ±100 ppm	Limit	FS < ±100 ppm
Test Result	PASS	Test Result	PASS

Appendix D. Test Results of Radiated Test Items

D.1 Test Result of Field Strength of Fundamental Emissions



Note: All NFC's spurious emissions are below 20dB of limits.

D.2 Results of Radiated Emissions (9 kHz~30MHz)

Test Mode :		NFC Tx			Polarization :		Horizontal		
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.04	51.96	-64.74	116.70	31.95	20.00	0.01	-	-	Average
0.04	50.09	-65.55	115.64	30.08	20.00	0.01	-	-	Average
0.08	42.33	-67.67	110.00	22.32	20.00	0.01	-	-	Average
0.08	52.02	-57.67	109.69	32.01	20.00	0.01	-	-	Average
0.12	38.62	-67.69	106.31	18.61	20.00	0.01	-	-	Average
0.12	44.01	-62.18	106.19	24.00	20.00	0.01	-	-	Average
0.16	49.25	-54.40	103.65	29.24	20.00	0.01	-	-	Average
0.20	43.83	-57.90	101.73	23.82	20.00	0.01	-	-	Average
4.09	34.37	-35.17	69.54	14.21	20.00	0.16	-	-	QP
6.42	33.78	-35.76	69.54	13.59	20.00	0.19	-	-	QP
28.81	32.31	-37.23	69.54	11.96	20.00	0.35	-	-	QP

Test Mode :		NFC Tx			Polarization :		Vertical		
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.01	48.51	-78.40	126.91	28.45	20.00	0.06	-	-	Average
0.04	44.84	-71.86	116.70	24.83	20.00	0.01	-	-	Average
0.04	43.75	-71.96	115.71	23.74	20.00	0.01	-	-	Average
0.08	38.18	-71.51	109.69	18.17	20.00	0.01	-	-	Average
0.09	29.88	-78.80	108.68	9.87	20.00	0.01	-	-	Average
0.12	32.39	-73.81	106.20	12.38	20.00	0.01	-	-	Average
0.71	45.06	-25.56	70.62	25.03	20.00	0.03	-	-	QP
3.55	35.48	-34.06	69.54	15.37	20.00	0.11	-	-	QP
4.67	39.25	-30.29	69.54	19.09	20.00	0.16	-	-	QP
7.35	36.93	-32.61	69.54	16.73	20.00	0.20	-	-	QP
26.81	33.98	-35.56	69.54	13.64	20.00	0.34	-	-	QP

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);
3. Limit line = specific limits (dBμV) + distance extrapolation factor.

D.3 Results of Radiated Emissions (30MHz~1GHz)

Test Mode :		NFC Tx			Polarization :		Horizontal			
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.97	27.06	-12.94	40.00	40.22	18.71	0.79	32.66	-	-	Peak
88.20	24.67	-18.83	43.50	46.27	9.98	1.04	32.62	-	-	Peak
158.04	36.28	-7.22	43.50	55.99	11.40	1.44	32.55	100	325	Peak
189.08	29.13	-14.37	43.50	49.78	10.21	1.61	32.47	-	-	Peak
368.53	29.32	-16.68	46.00	43.95	15.56	2.15	32.34	-	-	Peak
465.53	29.73	-16.27	46.00	42.15	17.24	2.51	32.17	-	-	Peak

Test Mode :		NFC Tx			Polarization :		Vertical			
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.97	31.54	-8.46	40.00	44.70	18.71	0.79	32.66	100	0	Peak
45.52	27.12	-12.88	40.00	47.74	11.25	0.79	32.66	-	-	Peak
88.20	26.37	-17.13	43.50	47.97	9.98	1.04	32.62	-	-	Peak
156.10	30.86	-12.64	43.50	50.50	11.48	1.44	32.56	-	-	Peak
193.93	27.00	-16.50	43.50	47.84	10.02	1.61	32.47	-	-	Peak
462.62	32.30	-13.70	46.00	44.82	17.25	2.40	32.17	-	-	Peak


Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBμV/m) = 20 log Emission level (μV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.



Appendix E. Test Results of Radiated Test Items for Spot Check

E.1 Test Result of Field Strength of Fundamental Emissions



Note: All NFC's spurious emissions are below 20dB of limits.

E.2 Results of Radiated Emissions (9 kHz~30MHz)

Test Mode :		NFC Tx			Polarization :		Horizontal		
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.04002	49.73	-65.82	115.55	29.32	20.4	0.01	-	-	Average
0.0788	48.99	-60.67	109.66	28.63	20.35	0.01	-	-	Average
0.10164	43.95	-63.5	107.45	23.64	20.3	0.01	-	-	QP
0.15925	45.98	-57.57	103.55	25.58	20.39	0.01	-	-	Average
1.682	42.09	-20.99	63.08	22.29	19.77	0.03	-	-	QP
2.6	44.8	-24.74	69.54	24.96	19.8	0.04	-	-	QP
4.616	42.94	-26.6	69.54	23.17	19.71	0.06	-	-	QP
12.233	36.11	-33.43	69.54	16	19.97	0.14	-	-	QP

Test Mode :		NFC Tx			Polarization :		Vertical		
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.03946	41.89	-73.78	115.67	21.48	20.4	0.01	-	-	Average
0.07316	42.34	-67.97	110.31	21.98	20.35	0.01	-	-	Average
0.1015	36.61	-70.85	107.46	16.3	20.3	0.01	-	-	QP
0.70315	50.07	-20.58	70.65	30.43	19.62	0.02	-	-	QP
1.277	41.63	-23.84	65.47	21.88	19.73	0.02	-	-	QP
2.648	43.71	-25.83	69.54	23.87	19.8	0.04	-	-	QP
4.25	40.37	-29.17	69.54	20.55	19.76	0.06	-	-	QP
12.233	37.13	-32.41	69.54	17.02	19.97	0.14	-	-	QP

Note:

4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
5. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);
6. Limit line = specific limits (dBμV) + distance extrapolation factor.

E.3 Results of Radiated Emissions (30MHz~1GHz)

Test Mode :		NFC Tx			Polarization :		Horizontal			
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
98.87	19.5	-24	43.5	36.63	11.63	1.64	30.4	-	-	Peak
161.92	28.62	-14.88	43.5	45.82	11.11	2.09	30.4	-	-	Peak
262.8	34.77	-11.23	46	50.81	11.76	2.7	30.5	121	51	Peak
351.07	27.82	-18.18	46	39.64	15.72	3.06	30.6	-	-	Peak
450.98	25.9	-20.1	46	36.3	16.57	3.53	30.5	-	-	Peak
706.09	23.47	-22.53	46	28.91	20.29	4.68	30.41	-	-	Peak

Test Mode :		NFC Tx			Polarization :		Vertical			
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
33.88	34.9	-5.1	40	44.54	20.3	1	30.94	100	216	Peak
71.71	24.34	-15.66	40	46.24	7.23	1.45	30.58	-	-	Peak
160.95	27.17	-16.33	43.5	44.33	11.16	2.08	30.4	-	-	Peak
235.64	26.38	-19.62	46	43.33	11.03	2.49	30.47	-	-	Peak
343.31	25.2	-20.8	46	37.44	15.36	2.99	30.59	-	-	Peak
470.38	30.78	-15.22	46	41.36	16.26	3.62	30.46	-	-	Peak

Note:

- The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
- Emission level (dBμV/m) = 20 log Emission level (μV/m).
- Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.



APPENDIX F. PRODUCT EQUALITY DECLARATION

Declaration of changes from Initial (Idol 3 5.5 LATAM-6045B) to Variant (Idol 3 5.5 US – 6045I)

General: 6045I is a variant product of 6045B.

● SOFTWARE MODIFICATIONS:

- Protocol Stack changes: NO
- MMS/STK/USAT/USIM changes: NO
- DM/SUPL/VT/FUMO/SWP/HCI: NO
- Other changes detailed: NO

● HARDWARE MODIFICATIONS:

- Baseband changes: NO
- Band changes: YES

product	GSM	UMTS	LTE
6045B	850/900/1800/1900	FDD 850/900/1900/2100	B1/2/3/4/7/28
6045I	850/900/1800/1900	FDD 850/1900/1700/2100	B2/4/5/7/12/17

- Antenna changes: yes
- PCB Layout changes: no
- Main components changes:

	Base Band	Transceiver	ASM	Power Amplifier	Tx SAW Filter	Rx SAW Filter (SAW Duplexer)
GSM 850	NO	NO	NO	NO	N/A	NO
GSM 900	NO	NO	NO	NO	N/A	NO
GSM 1800	NO	NO	NO	NO	N/A	NO
GSM 1900	NO	NO	NO	NO	N/A	NO

	Base Band	Transceiver	ASM	Power Amplifier	Tx SAW Filter	Rx SAW Filter (SAW Duplexer)
UMTS FDD I	NO	NO	NO	NO	N/A	NO
UMTS FDD II	NO	NO	NO	NO	NA	NO
UMTS FDD IV	NO	NO	NO	No (SW activate)	N/A	No (share with LTE Band4)
UMTS FDD V	NO	NO	NO	NO	N/A	NO

LTE B12 and B17 with mFBI, that mean B12 and B17 share one RF path

	Base Band	Transceiver	ASM	Power Amplifier	Tx SAW Filter	Rx SAW Filter (SAW Duplexer)
LTE B2	NO	NO	NO	NO	N/A	NO
LTE B4	NO	NO	NO	NO	N/A	NO
LTE B5	NO	NO	NO	No (SW activate)	N/A	No (share with UMTS Band5)
LTE B7	NO	NO	NO	NO	N/A	NO
LTE B12	NO	NO	NO	No (SW activate)	N/A	YES
LTE B17	NO	NO	NO	No (SW activate, share with LTE Band12)	N/A	YES(share with LTE Band12)

- Bluetooth changes: NO
- WiFi changes: NO
- FM changes: NO
- Other components changes: NO

TP/LCD/ Camera changes: NO

- Other changes detailed: NO

➤ MECHANICAL MODIFICATIONS:

- Use new metal front/back cover or keypad: NO
- Mechanical shell changes: NO
- Whole size of EUT: NO
- Distance of Ear reference point to bottom of handset: NO
- Other trinkets to change the surface of handset: NO

➤ Other changes detailed

➤ **APPROVED BY:**

Project Manager:

Signature:

Date:

[Handwritten Signature] 3/2