FCC RF Test Report

APPLICANT	:	TCL Communication Ltd
EQUIPMENT	:	GSM Quad-band / UMTS Quad-band / LTE 4 band mobile phone
BRAND NAME	:	ALCATEL ONETOUCH
MODEL NAME	:	6045O
MARKETING NAME	:	ALCATEL ONETOUCH IDOL 3 (5.5)
FCC ID	:	2ACCJN005
STANDARD	:	FCC Part 15 Subpart E §15.407
CLASSIFICATION	:	(NII) Unlicensed National Information Infrastructure

The product testing was completed on Mar. 01, 2016. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

James Huang

Prepared by: James Huang / Manager

Jones Tsai

Approved by: Jones Tsai / Manager

Testing Laboratory 2627

SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 5
1.5 Modification of EUT 6
1.6 Accessories and Support Equipment 6
1.7 Testing Location 7
1.8 Applicable Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**

2.1 Carrier Frequency Channel 8
2.2 Pre-Scanned RF Power 9
2.3 Test Mode 10
2.4 Connection Diagram of Test System 11
2.5 Support Unit used in test configuration and system 12
2.6 EUT Operation Test Setup 12
2.7 Measurement Results Explanation Example 13

3 TEST RESULT **14**

3.1 26dB & 99% Occupied Bandwidth Measurement 14
3.2 Maximum Conducted Output Power Measurement 16
3.3 Power Spectral Density Measurement 17
3.4 Unwanted Radiated Emission Measurement 20
3.5 AC Conducted Emission Measurement 24
3.6 Frequency Stability Measurement 28
3.7 Automatically Discontinue Transmission 29
3.8 Antenna Requirements 30

4 LIST OF MEASURING EQUIPMENTS **31**

5 UNCERTAINTY OF EVALUATION **33**

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. RADIATED TEST RESULTS

APPENDIX C. SETUP PHOTOGRAPHS

APPENDIX D. PRODUCT EQUALITY DECLARATION

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR511301-29E	Rev. 01	This is a variant product of 6045O. Added a new battery, and only the worst case of Radiated spurious emission from original test report (Sporton Report Number FR511301-21E) were verified for the difference and the original test data were remain representative.	Mar. 07, 2016

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	2.1049 15.403(i)	99% Bandwidth	-	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 24 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 11 dBm	Pass	-
3.4	15.407(b)	Unwanted Emissions	≤ -17, -27 dBm (depend on band)&15.209(a)	Pass	Under limit 4.86 dB at 40.670 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 5.18 dB at 0.520 MHz
3.6	15.407(g)	Frequency Stability	Within Operation Band	Pass	-
3.7	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.8	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

TCL Communication Ltd
FLAT/RM 1910-12A BLOCK 3 19/F CHINA HONG KONG CITY 33 CANTON ROAD TSIMSHATSUI KL

1.2 Manufacturer

TCL Communication Ltd
FLAT/RM 1910-12A BLOCK 3 19/F CHINA HONG KONG CITY 33 CANTON ROAD TSIMSHATSUI KL

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	GSM Quad-band / UMTS Quad-band / LTE 4 band mobile phone
Brand Name	ALCATEL ONETOUCH
Model Name	6045O
Marketing Name	ALCATEL ONETOUCH IDOL 3 (5.5)
FCC ID	2ACCJN005
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/HSPA+(16QAM uplink is not supported)/DC-HSDPA/LTE/NFC/ WLAN 2.4GHz 802.11b/g/n HT20/ WLAN 5GHz 802.11a/HT20/HT40/ Bluetooth v3.0 + EDR/Bluetooth v4.1 LE
HW Version	03
SW Version	5A18
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx/Rx Frequency Range	5180 MHz ~ 5240 MHz
Maximum Output Power to Antenna	802.11a : 13.52 dBm / 0.0225 W 802.11n HT20 : 11.86 dBm / 0.0153 W 802.11n HT40 : 11.63 dBm / 0.0146 W
Antenna Type / Gain	PIFA Antenna with gain -3 dBi
Type of Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Accessories and Support Equipment

Specification of Accessory				
AC Adapter	**Brand Name**	ALCATEL ONETOUCH	**Model Name**	UC13US
	Power Rating	I/P: 100-240Vac, 500mA, O/P: 5Vdc, 2000mA		
	P/N	CBA0059AG0C1		
Original Battery	**Brand Name**	ALCATEL ONETOUCH	**Model Name**	TLp029A2-S
	Power Rating	3.8Vdc, 2910mAh		
	P/N	C2910002C2YHVOJE		
Added Battery	**Brand Name**	ALCATEL ONETOUCH	**Model Name**	TLp029AJ
	Power Rating	3.8Vdc, 2910mAh		
	P/N	C2910003CJY9411D		
USB Cable	**Brand Name**	ALCATEL ONETOUCH	**Model Name**	CDA0000043C2
	Signal Line Type	1.01m shielded without core		

1.7 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.			
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
Test Site No.	Sporton Site No.			FCC Registration No.
	TH01-KS	03CH01-KS	CO01-KS	149928

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.	
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958	
Test Site No.	Sporton Site No.	FCC Registration No.
	03CH03-KS	306251

Note: The test site complies with ANSI C63.4 2009 requirement.

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v01
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5150-5250 MHz Band 1 (U-NII-1)	36	5180	44	5220
	38	**5190**	**46**	**5230**
	40	5200	48	5240

Note: The above Frequency and Channel in boldface were 802.11n HT40.

2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test in the following tables. Final Output Power equals to Measured Output Power adds the duty factor.

5GHz 802.11a RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index 6Mbps	Channel	9M bps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
CH 36	5180	13.15	CH 48	13.35	13.34	13.39	13.47	13.44	13.51	13.50
CH 44	5220	12.73								
CH 48	5240	**13.52**								

5GHz 802.11n HT20 RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 36	5180	11.59	CH 48	11.84	11.81	11.72	11.80	11.83	11.84	11.83
CH 44	5220	11.26								
CH 48	5240	**11.86**								

5GHz 802.11n HT40 RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 38	5190	11.45	CH 46	11.40	11.42	11.55	11.53	11.45	11.53	11.54
CH 46	5230	**11.63**								

2.3 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates from the power table described in section 2.2.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0

AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN (5GHz) Link + USB Cable 1 (Charging from Adapter 1) + Earphone + Battery 1
Remark: For Radiated TCs, the tests were performed with adapter 1, USB cable 1, battery 1 and earphone.	

Ch. #		Band I：5150-5250 MHz		
		802.11a	802.11n HT20	802.11n HT40
L	Low	36	36	38
M	Middle	44	44	-
H	High	48	48	46

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritus	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	G480	PRC4	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A
5.	DC Power Supply	GW INSTEK	GPD-2303S	N/A	N/A	Unshielded, 1.8 m

2.6 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:
The spectrum analyzer offset is derived from RF cable loss.
Offset = RF cable loss.
Following shows an offset computation example with cable loss 7 dB.

Offset (dB) = RF cable loss (dB).
= 7 (dB)

3 Test Result

3.1 26dB & 99% Occupied Bandwidth Measurement

3.1.1 Description of 26dB & 99% Occupied Bandwidth

This section is for reporting purpose only.

There is no restriction limits for bandwidth.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01. Section C) Emission bandwidth
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW > RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
7. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1MHz and set the Video bandwidth (VBW) ≥ 3 * RBW.
8. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 26dB & 99% Occupied Bandwidth Plots

Please refer to Appendix A.

Maximum 26dB Bandwidth	Maximum 99% Occupied Bandwidth
	
Date: 13.FEB.2015 19:43:28	Date: 13.FEB.2015 19:43:01

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, 10 log(1/x), where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.
Section F) Maximum power spectral density.

 # Method SA-2 #

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

1. The testing follows Method SA-2 of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.
   - Measure the duty cycle.
   - Set span to encompass the entire emission bandwidth (EBW) of the signal.
   - Set RBW = 1 MHz.
   - Set VBW ≥ 3 MHz.
   - Number of points in sweep ≥ 2 Span / RBW.
   - Sweep time = auto.
   - Detector = RMS
   - Trace average at least 100 traces in power averaging mode.
   - Add 10 log(1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add 10 log(1/0.25) = 6 dB if the duty cycle is 25 percent.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

Worst Case Power Spectral Density(dBm/MHz)



Note: Average Power Density (dB) = Measured value+ Duty Factor

3.4 Unwanted Radiated Emission Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part15.205.

3.4.1 Limit of Unwanted Emissions

(1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of –27dBm/MHz.

(2) Unwanted spurious emissions fallen in restricted bands per FCC Part15.205 shall comply with the general field strength limits set forth in § 15.209 as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E=\frac{1000000\sqrt{30P}}{3}$$ μV/m, where P is the eirp (Watts)

EIRP (dBm)	Field Strength at 3m (dBμV/m)
-17	78.3
- 27	68.3

(3) KDB789033 v01 G)2)c) As specified in 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in 15.407(b)(4)). However, an out-of-band emission that complies with both the average and peak limits of 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz peak emission limit.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01. Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW ≥ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold

(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz

- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Band	Duty Cycle (%)	T(ms)	1/T(kHz)	VBW Setting
802.11a	87.26	1.37	0.73	1kHz
802.11n HT20	86.62	1.28	0.78	1kHz
802.11n HT40	76.30	0.64	1.55	3kHz

2. The EUT was placed on a turntable with 0.8 meter above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix B.

3.4.7 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	**Temperature :**	22~24℃
Test Engineer :	Eko Guan	**Relative Humidity :**	30~32%
Test Voltage :	120Vac / 60Hz	**Phase :**	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (5GHz) Link + USB Cable 1 (Charging from Adapter 1) + Earphone + Battery 1		



Site : CO01-KS
Condition : FCC PART 15E LISN-L20140306 LINE

	Freq MHz	Level dBuV	Over Limit dB	Limit Line dBuV	Read Level dBuV	LISN Factor dB	Cable Loss dB	Remark
1	0.52	44.63	-11.37	56.00	33.80	0.20	10.63	QP
2 *	0.52	35.53	-10.47	46.00	24.70	0.20	10.63	Average
3	0.59	37.73	-18.27	56.00	26.90	0.20	10.63	QP
4	0.59	28.13	-17.87	46.00	17.30	0.20	10.63	Average
5	1.35	38.67	-17.33	56.00	27.90	0.10	10.67	QP
6	1.35	29.17	-16.83	46.00	18.40	0.10	10.67	Average
7	1.55	38.29	-17.71	56.00	27.50	0.10	10.69	QP
8	1.55	28.69	-17.31	46.00	17.90	0.10	10.69	Average
9	1.69	38.39	-17.61	56.00	27.60	0.10	10.69	QP
10	1.69	28.69	-17.31	46.00	17.90	0.10	10.69	Average
11	3.26	35.76	-20.24	56.00	24.80	0.16	10.80	QP
12	3.26	26.16	-19.84	46.00	15.20	0.16	10.80	Average

Test Mode :	Mode 1	**Temperature :**	22~24℃
Test Engineer :	Eko Guan	**Relative Humidity :**	30~32%
Test Voltage :	120Vac / 60Hz	**Phase :**	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (5GHz) Link + USB Cable 1 (Charging from Adapter 1) + Earphone + Battery 1		



Site : CO01-KS
Condition : FCC PART 15E LISN-N20140306 NEUTRAL

		Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
		MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1		0.52	46.72	-9.28	56.00	35.80	0.29	10.63	QP
2	*	0.52	40.82	-5.18	46.00	29.90	0.29	10.63	Average
3		0.59	40.98	-15.02	56.00	30.10	0.25	10.63	QP
4		0.59	35.78	-10.22	46.00	24.90	0.25	10.63	Average
5		1.13	39.06	-16.94	56.00	28.30	0.10	10.66	QP
6		1.13	33.46	-12.54	46.00	22.70	0.10	10.66	Average
7		1.34	40.67	-15.33	56.00	29.90	0.10	10.67	QP
8		1.34	35.37	-10.63	46.00	24.60	0.10	10.67	Average
9		1.52	40.68	-15.32	56.00	29.90	0.10	10.68	QP
10		1.52	35.08	-10.92	46.00	24.30	0.10	10.68	Average
11		1.72	40.49	-15.51	56.00	29.70	0.10	10.69	QP
12		1.72	35.09	-10.91	46.00	24.30	0.10	10.69	Average

3.6 Frequency Stability Measurement

3.6.1 Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
2. The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10dB lower than the measured peak value.
3. The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

3.6.4 Test Setup



3.6.5 Test Result of Frequency Stability

Please refer to Appendix A.

3.7 Automatically Discontinue Transmission

3.7.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

3.8 Antenna Requirements

3.8.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2) ,if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.8.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.8.3 Antenna Gain

The antenna gain is less than 6 dBi. Therefore, it is not necessary to reduce maximum output power limit.

4 List of Measuring Equipments

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Oct. 28, 2014	Feb. 13, 2015	Oct. 27, 2015	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	30MHz~40GHz	Jan. 23, 2015	Feb. 13, 2015	Jan. 22, 2016	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 23, 2015	Feb. 13, 2015	Jan. 22, 2016	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 25, 2014	Feb. 13, 2015	Oct. 24, 2015	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Oct. 25, 2014	Feb. 20, 2015	Oct. 24, 2015	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Oct. 28, 2014	Feb. 20, 2015	Oct. 27, 2015	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 13, 2014	Feb. 20, 2015	Nov. 12, 2015	Radiation (03CH01-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	25Mhz-2Ghz	Jan. 17, 2015	Feb. 20, 2015	Jan. 16, 2016	Radiation (03CH01-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 17, 2015	Feb. 20, 2015	Jan. 16, 2016	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701030	1GHz~18GHz	Nov. 08, 2014	Feb. 20, 2015	Nov. 07, 2015	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Mar. 10, 2014	Feb. 20, 2015	Mar. 09, 2015	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1GHz /32dB	May 04, 2014	Feb. 20, 2015	May 03, 2015	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02371	1GHz~26.5GHz	Oct. 28, 2014	Feb. 20, 2015	Oct. 27, 2015	Radiation (03CH01-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Feb. 20, 2015	NCR	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Feb. 20, 2015	NCR	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Feb. 20, 2015	NCR	Radiation (03CH01-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	May 04, 2014	Feb. 11, 2015	May 03, 2015	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 25, 2014	Feb. 11, 2015	Oct. 24, 2015	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 25, 2014	Feb. 11, 2015	Oct. 24, 2015	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 25, 2014	Feb. 11, 2015	Oct. 24, 2015	Conduction (CO01-KS)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Max 30dBm	Sep. 10, 2015	Mar. 01, 2016	Sep. 09, 2016	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44GHz	Jun. 05, 2015	Mar. 01, 2016	Jun 04, 2016	Radiation (03CH03-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 07, 2015	Mar. 01, 2016	Nov. 06, 2016	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	35406	25MHz-2GHz	Jun. 25, 2015	Mar. 01, 2016	Jun. 24, 2016	Radiation (03CH03-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1356	1GHz~18GHz	Jun. 25, 2015	Mar. 01, 2016	Jun. 24, 2016	Radiation (03CH03-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz ~40GHz	Mar. 03, 2015	Mar. 01, 2016	Mar. 02, 2016	Radiation (03CH03-KS)
Amplifier	Burgeon	BPA-530	102212	0.01MHz-3000MHz	Aug.10,2015	Mar. 01, 2016	Aug.09,2016	Radiation (03CH03-KS)
Amplifier	MITEQ	TTA1840-35-HG	1887435	18~40GHz	Aug.27,2015	Mar. 01, 2016	Aug.26,2016	Radiation (03CH03-KS)
high gain Amplifier	MITEQ	AMF-7D-00101800-30-10P	1889560	1GHz-18GHz	Aug.10,2015	Mar. 01, 2016	Aug.09,2016	Radiation (03CH03-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Oct. 24, 2015	Mar. 01, 2016	Oct. 23, 2016	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Mar. 01, 2016	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Mar. 01, 2016	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Mar. 01, 2016	NCR	Radiation (03CH03-KS)

NCR: No Calibration Required

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.3 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz) for 03CH01-KS

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz) for 03CH03-KS

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.5 dB

Appendix A. Conducted Test Results

Test Engineer:	Issac Song	Temperature:	24~25	°C
Test Date:	2015/2/13	Relative Humidity:	49~51	%

TEST RESULTS DATA
26dB and 99% OBW

Band I								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	99% Bandwidth EIRP Limit (dBm)	Note
11a	6Mbps	1	36	5180	18.15	23.85	22.59	
11a	6Mbps	1	44	5220	18.05	24.05	22.56	
11a	6Mbps	1	48	5240	18.05	23.80	22.56	
HT20	MCS0	1	36	5180	19.00	24.10	22.79	
HT20	MCS0	1	44	5220	18.80	24.00	22.74	
HT20	MCS0	1	48	5240	18.90	24.00	22.76	
HT40	MCS0	1	38	5190	36.40	44.82	23.01	
HT40	MCS0	1	46	5230	36.40	45.36	23.01	

TEST RESULTS DATA
Average Power Table

FCC Band I										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail
11a	6Mbps	1	36	5180	0.59	13.15	24.00	-3.00		Pass
11a	6Mbps	1	44	5220	0.59	12.73	24.00	-3.00		Pass
11a	6Mbps	1	48	5240	0.59	13.52	24.00	-3.00		Pass
HT20	MCS0	1	36	5180	0.62	11.59	24.00	-3.00		Pass
HT20	MCS0	1	44	5220	0.62	11.26	24.00	-3.00		Pass
HT20	MCS0	1	48	5240	0.62	11.86	24.00	-3.00		Pass
HT40	MCS0	1	38	5190	1.17	11.45	24.00	-3.00		Pass
HT40	MCS0	1	46	5230	1.17	11.63	24.00	-3.00		Pass

TEST RESULTS DATA
Power Spectral Density

FCC Band I										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Power Density (dBm/MHz)	Average PSD Limit (dBm/MHz)	DG (dBi)	-	Pass/Fail
11a	6Mbps	1	36	5180	0.59	-0.41	11.00	-3.00		Pass
11a	6Mbps	1	44	5220	0.59	0.58	11.00	-3.00		Pass
11a	6Mbps	1	48	5240	0.59	0.64	11.00	-3.00		Pass
HT20	MCS0	1	36	5180	0.62	-2.02	11.00	-3.00		Pass
HT20	MCS0	1	44	5220	0.62	-1.62	11.00	-3.00		Pass
HT20	MCS0	1	48	5240	0.62	-2.56	11.00	-3.00		Pass
HT40	MCS0	1	38	5190	1.17	-4.23	11.00	-3.00		Pass
HT40	MCS0	1	46	5230	1.17	-5.14	11.00	-3.00		Pass

TEST RESULTS DATA
Frequency Stability

Band I										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stablility (ppm)	Temperature (˚C)	Voltage (V)	Note
11a	6Mbps	1	36	5180	5180.100	0.100	19.31	20	3.5	
11a	6Mbps	1	36	5180	5180.075	0.075	14.48	20	4.35	
11a	6Mbps	1	36	5180	5180.100	0.100	19.31	20	3.8	
11a	6Mbps	1	36	5180	5180.075	0.075	14.48	-30	3.8	
11a	6Mbps	1	36	5180	5180.100	0.100	19.31	55	3.8	

Appendix B. Radiated Spurious Emission

15E Band 1 - 5150~5250MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 36 5180MHz	*	5180	102.48	-	-	94.21	35.26	6.78	33.77	150	122	P	H
	*	5180	89.22	-	-	80.95	35.26	6.78	33.77	150	122	A	H
		5147.55	64.64	-9.36	74	56.39	35.25	6.77	33.77	150	122	P	H
		5149.15	43.25	-10.75	54	35	35.25	6.77	33.77	150	122	A	H
	*	5180	102.84	-	-	94.57	35.26	6.78	33.77	150	279	P	V
	*	5180	91.64	-	-	83.37	35.26	6.78	33.77	150	279	A	V
		5148.15	63.82	-10.18	74	55.57	35.25	6.77	33.77	150	280	P	V
		5149.55	43.7	-10.3	54	35.45	35.25	6.77	33.77	150	280	A	V
802.11a CH 44 5220MHz	*	5220	104.92	-	-	96.61	35.27	6.8	33.76	150	279	P	H
	*	5220	92.98	-	-	84.67	35.27	6.8	33.76	150	279	A	H
	*	5220	103.72	-	-	95.41	35.27	6.8	33.76	150	288	P	V
	*	5220	92.65	-	-	84.34	35.27	6.8	33.76	150	288	A	V
802.11a CH 48 5240MHz	*	5240	102.86	-	-	94.51	35.28	6.82	33.75	167	360	P	H
	*	5240	91.07	-	-	82.72	35.28	6.82	33.75	167	360	A	H
		5385.85	54.75	-19.25	74	46.18	35.34	6.95	33.72	150	108	P	H
		5380.1	40.95	-13.05	54	32.38	35.34	6.95	33.72	150	108	A	H
	*	5240	104.64	-	-	96.29	35.28	6.82	33.75	150	292	P	V
	*	5240	91.9	-	-	83.55	35.28	6.82	33.75	150	292	A	V
		5371.8	54.54	-19.46	74	46.01	35.33	6.92	33.72	150	292	P	V
		5378.75	41.11	-12.89	54	32.54	35.34	6.95	33.72	150	292	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

15E band 1 5150~5250MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 36 5180MHz		10359	33.78	-40.22	74	57.22	1.46	9.59	34.49	185	147	P	H
		10362	35.44	-38.56	74	58.88	1.46	9.59	34.49	150	185	P	V
802.11a CH 44 5220MHz		10440	31.89	-42.11	74	55.12	1.53	9.68	34.44	154	228	P	H
		10440	32.09	-41.91	74	55.32	1.53	9.68	34.44	158	88	P	V
802.11a CH 48 5240MHz		10479	31.43	-42.57	74	54.54	1.56	9.74	34.41	159	65	P	H
		10479	32.77	-41.23	74	55.88	1.56	9.74	34.41	198	285	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

15E band 1 5150~5250MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 36 5180MHz	*	5180	96.48	-	-	88.21	35.26	6.78	33.77	168	125	P	H
	*	5180	85.42	-	-	77.15	35.26	6.78	33.77	168	125	A	H
		5146.55	53.96	-20.04	74	45.71	35.25	6.77	33.77	168	125	P	H
		5127.85	39.96	-14.04	54	31.75	35.24	6.75	33.78	168	125	A	H
	*	5180	99.06	-	-	90.79	35.26	6.78	33.77	150	284	P	V
	*	5180	87.68	-	-	79.41	35.26	6.78	33.77	150	284	A	V
		5149.5	54.02	-19.98	74	45.77	35.25	6.77	33.77	150	284	P	V
		5127.7	40.18	-13.82	54	31.97	35.24	6.75	33.78	150	284	A	V
802.11n HT20 CH 44 5220MHz	*	5220	97.53	-	-	89.22	35.27	6.8	33.76	171	118	P	H
	*	5220	85.98	-	-	77.67	35.27	6.8	33.76	171	118	A	H
	*	5220	100.11	-	-	91.8	35.27	6.8	33.76	150	280	P	V
	*	5220	87.61	-	-	79.3	35.27	6.8	33.76	150	280	A	V
802.11n HT20 CH 48 5240MHz	*	5240	97.65	-	-	89.3	35.28	6.82	33.75	172	119	P	H
	*	5240	86.59	-	-	78.24	35.28	6.82	33.75	172	119	A	H
		5371.9	53.5	-20.5	74	44.97	35.33	6.92	33.72	172	119	P	H
		5355.3	39.97	-14.03	54	31.48	35.32	6.9	33.73	172	119	A	H
	*	5240	100.26	-	-	91.91	35.28	6.82	33.75	158	360	P	V
	*	5240	88.47	-	-	80.12	35.28	6.82	33.75	158	360	A	V
		5359.25	53.48	-20.52	74	44.99	35.32	6.9	33.73	158	288	P	V
		5357.5	40.05	-13.95	54	31.56	35.32	6.9	33.73	158	288	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

15E band 1 5150~5250MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 36 5180MHz		10360	33.75	-40.25	74	57.19	1.46	9.59	34.49	170	256	P	H
		10359	33.59	-40.41	74	57.03	1.46	9.59	34.49	165	229	P	V
802.11n HT20 CH 44 5220MHz		10440	31.95	-42.05	74	55.18	1.53	9.68	34.44	160	226	P	H
		10440	31.14	-42.86	74	54.37	1.53	9.68	34.44	195	56	P	V
802.11n HT20 CH 48 5240MHz		10480	31.87	-42.13	74	54.98	1.56	9.74	34.41	155	59	P	H
		10479	31.72	-42.28	74	54.83	1.56	9.74	34.41	174	85	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

15E band 1 5150~5250MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 38 5190MHz	*	5190	93.39	-	-	85.12	35.26	6.78	33.77	216	186	P	H
	*	5190	82.81	-	-	74.54	35.26	6.78	33.77	216	186	A	H
		5147.5	57.23	-16.77	74	48.98	35.25	6.77	33.77	216	187	P	H
		5149.8	43.2	-10.8	54	34.95	35.25	6.77	33.77	216	187	A	H
	*	5190	89.52	-	-	81.25	35.26	6.78	33.77	150	305	P	V
	*	5190	78.63	-	-	70.36	35.26	6.78	33.77	150	305	A	V
		5145.95	55.46	-18.54	74	47.21	35.25	6.77	33.77	150	305	P	V
		5149.2	40.94	-13.06	54	32.69	35.25	6.77	33.77	150	305	A	V
802.11n HT40 CH 46 5230MHz	*	5230	95.38	-	-	87.03	35.28	6.82	33.75	209	185	P	H
	*	5230	83.24	-	-	74.89	35.28	6.82	33.75	209	185	A	H
		5386.6	53.72	-20.28	74	45.15	35.34	6.95	33.72	209	186	P	H
		5387.2	40.55	-13.45	54	31.98	35.34	6.95	33.72	209	186	A	H
	*	5230	90.03	-	-	81.68	35.28	6.82	33.75	159	347	P	V
	*	5230	79.64	-	-	71.29	35.28	6.82	33.75	159	347	A	V
		5378.5	53.26	-20.74	74	44.69	35.34	6.95	33.72	159	348	P	V
		5392.65	40.47	-13.53	54	31.9	35.34	6.95	33.72	150	348	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

15E band 1 5150~5250MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 38 5190MHz		10380	34.55	-39.45	74	57.94	1.48	9.61	34.48	155	221	P	H
		10380	33.79	-40.21	74	57.18	1.48	9.61	34.48	165	225	P	V
802.11n HT40 CH 46 5230MHz		10461	31.74	-42.26	74	54.89	1.55	9.72	34.42	170	154	P	H
		10461	31.97	-42.03	74	55.12	1.55	9.72	34.42	187	225	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

15E Emission below 1GHz

WIFI 802.11a (LF @ 3m)

WIFI	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11a LF		172.59	28.9	-14.6	43.5	52.25	9.01	1.21	33.57	100	185	P	H
		320.03	20.8	-25.2	46	38.99	13.55	1.63	33.37	-	-	P	H
		449.04	19.85	-26.15	46	34.81	16.3	1.95	33.21	-	-	P	H
		520.82	21.19	-24.81	46	34.54	17.7	2.04	33.09	-	-	P	H
		700.27	21.9	-24.1	46	33.09	19.3	2.39	32.88	-	-	P	H
		896.21	24.4	-21.6	46	33.68	20.45	2.71	32.44	-	-	P	H
		79.47	28.68	-11.32	40	54.99	6.47	0.82	33.6	155	263	P	V
		214.3	26.31	-17.19	43.5	48.78	9.71	1.35	33.53	-	-	P	V
		378.23	24	-22	46	40.18	15.38	1.77	33.33	-	-	P	V
		457.77	26.08	-19.92	46	40.92	16.4	1.96	33.2	-	-	P	V
		605.21	23.49	-22.51	46	35.57	18.62	2.25	32.95	-	-	P	V
		875.84	24.95	-21.05	46	34.36	20.48	2.68	32.57	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Radiated Spurious Emission for Spot Check

15E Band 1 - 5150~5250MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 36 5180MHz		5149.15	49.31	-24.69	74	45.87	31.84	8.13	36.53	100	182	P	H
		5150	39.16	-14.84	54	35.72	31.84	8.13	36.53	100	182	A	H
	*	5174	96.43	-	-	92.92	31.85	8.17	36.51	100	182	P	H
	*	5174	89.05	-	-	85.54	31.85	8.17	36.51	100	182	A	H
		5147.85	48.78	-25.22	74	45.34	31.84	8.13	36.53	300	285	P	V
		5127.45	37.79	-16.21	54	34.38	31.84	8.11	36.54	300	285	A	V
	*	5184	93.15	-	-	89.64	31.85	8.17	36.51	300	285	P	V
	*	5184	85.72	-	-	82.21	31.85	8.17	36.51	300	285	A	V
802.11a CH 44 5220MHz	*	5226	95.64	-	-	92.06	31.87	8.21	36.5	100	181	P	H
	*	5226	88.27	-	-	84.69	31.87	8.21	36.5	100	181	A	H
	*	5224	93.83	-	-	90.27	31.86	8.2	36.5	300	338	P	V
	*	5226	86.33	-	-	82.75	31.87	8.21	36.5	300	338	A	V

802.11a CH 48 5240MHz	*	5236	95.31	-	-	91.73	31.87	8.21	36.5	106	202	P	H
	*	5244	88.24	-	-	84.64	31.88	8.22	36.5	106	202	A	H
		5380.35	45.87	-28.13	74	42.13	31.92	8.32	36.5	106	202	P	H
		5387.25	36.68	-17.32	54	32.94	31.92	8.32	36.5	106	202	A	H
	*	5236	93.53	-	-	89.95	31.87	8.21	36.5	270	339	P	V
	*	5234	86.68	-	-	83.1	31.87	8.21	36.5	270	339	A	V
		5370.05	46.37	-27.63	74	42.65	31.91	8.31	36.5	270	339	P	V
		5392.1	36.56	-17.44	54	32.82	31.92	8.32	36.5	270	339	A	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												

15E band 1 5150~5250MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 36 5180MHz		10359	46.53	-27.47	74	56.07	38.02	13.54	61.1	100	0	P	H
		10359	46.82	-27.18	74	56.36	38.02	13.54	61.1	100	360	P	V
802.11a CH 44 5220MHz		10440	45.02	-28.98	74	54.45	38.06	13.58	61.07	100	0	P	H
		10440	45.35	-28.65	74	54.78	38.06	13.58	61.07	100	360	P	V
802.11a CH 48 5240MHz		10479	45.74	-28.26	74	55.08	38.09	13.61	61.04	100	0	P	H
		10479	45.92	-28.08	74	55.26	38.09	13.61	61.04	100	360	P	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												

15E band 1 5150~5250MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 36 5180MHz		5143.9	49.45	-24.55	74	46.01	31.84	8.13	36.53	100	179	P	H
		5128.2	38.86	-15.14	54	35.45	31.84	8.11	36.54	100	179	A	H
	*	5174	94.55	-	-	91.04	31.85	8.17	36.51	100	179	P	H
	*	5172	87.43	-	-	83.95	31.85	8.15	36.52	100	179	A	H
		5113.55	47.86	-26.14	74	44.48	31.83	8.1	36.55	300	80	P	V
		5128.15	38.14	-15.86	54	34.73	31.84	8.11	36.54	300	80	A	V
	*	5184	92.85	-	-	89.34	31.85	8.17	36.51	300	80	P	V
	*	5186	84.83	-	-	81.32	31.85	8.17	36.51	300	80	A	V
802.11n HT20 CH 44 5220MHz	*	5226	93.92	-	-	90.34	31.87	8.21	36.5	100	183	P	H
	*	5226	86.5	-	-	82.92	31.87	8.21	36.5	100	183	A	H
	*	5218	92.04	-	-	88.48	31.86	8.2	36.5	305	345	P	V
	*	5216	84.3	-	-	80.74	31.86	8.2	36.5	305	345	A	V

802.11n HT20 CH 48 5240MHz	*	5244	94.45	-	-	90.85	31.88	8.22	36.5	313	187	P	H
	*	5248	86.86	-	-	83.26	31.88	8.22	36.5	313	187	A	H
		5385.55	46.22	-27.78	74	42.48	31.92	8.32	36.5	313	187	P	H
		5391.45	36.58	-17.42	54	32.84	31.92	8.32	36.5	313	187	A	H
	*	5244	92.1	-	-	88.5	31.88	8.22	36.5	342	339	P	V
	*	5246	84.87	-	-	81.27	31.88	8.22	36.5	342	339	A	V
		5399.3	46.04	-27.96	74	42.29	31.92	8.33	36.5	342	339	P	V
		5380.3	36.57	-17.43	54	32.83	31.92	8.32	36.5	342	339	A	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												

15E band 1 5150~5250MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 36 5180MHz		10359	45.59	-28.41	74	55.13	38.02	13.54	61.1	100	0	P	H
		10359	46.65	-27.35	74	56.19	38.02	13.54	61.1	100	360	P	V
802.11n HT20 CH 44 5220MHz		10440	45.2	-28.8	74	54.63	38.06	13.58	61.07	100	0	P	H
		10440	45.16	-28.84	74	54.59	38.06	13.58	61.07	100	360	P	V
802.11n HT20 CH 48 5240MHz		10479	44.7	-29.3	74	54.04	38.09	13.61	61.04	100	0	P	H
		10479	44.84	-29.16	74	54.18	38.09	13.61	61.04	100	360	P	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												

15E band 1 5150~5250MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 38 5190MHz		5149.25	56.56	-17.44	74	53.12	31.84	8.13	36.53	100	179	P	H
		5149.95	45.04	-8.96	54	41.6	31.84	8.13	36.53	100	179	A	H
	*	5202	91.37	-	-	87.82	31.86	8.19	36.5	100	179	P	H
	*	5200	84.16	-	-	80.61	31.86	8.19	36.5	100	179	A	H
		5147.15	53.86	-20.14	74	50.42	31.84	8.13	36.53	300	95	P	V
		5149.3	42.14	-11.86	54	38.7	31.84	8.13	36.53	300	95	A	V
	*	5182	89.39	-	-	85.88	31.85	8.17	36.51	300	95	P	V
	*	5188	81.95	-	-	78.44	31.85	8.17	36.51	300	95	A	V
802.11n HT40 CH 46 5230MHz	*	5228	90.87	-	-	87.29	31.87	8.21	36.5	100	182	P	H
	*	5228	83.84	-	-	80.26	31.87	8.21	36.5	100	182	A	H
		5370.55	46.96	-27.04	74	43.24	31.91	8.31	36.5	100	182	P	H
		5388.45	37.22	-16.78	54	33.48	31.92	8.32	36.5	100	182	A	H
	*	5238	88.58	-	-	85	31.87	8.21	36.5	311	99	P	V
	*	5232	81.62	-	-	78.04	31.87	8.21	36.5	311	99	A	V
		5366.15	46.13	-27.87	74	42.41	31.91	8.31	36.5	311	99	P	V
		5370.45	37.09	-16.91	54	33.37	31.91	8.31	36.5	311	99	A	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												

15E band 1 5150~5250MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 38 5190MHz		10380	45.82	-28.18	74	55.34	38.03	13.55	61.1	100	0	P	H
		10380	45.7	-28.3	74	55.22	38.03	13.55	61.1	100	360	P	V
802.11n HT40 CH 46 5230MHz		10461	45.31	-28.69	74	54.68	38.08	13.6	61.05	100	0	P	H
		10461	45.39	-28.61	74	54.76	38.08	13.6	61.05	100	360	P	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												

15E Emission below 1GHz

WIFI 802.11n HT40 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 LF		40.67	27.66	-12.34	40	43.85	13.92	0.77	30.88	-	-	P	H
		94.99	26.34	-17.16	43.5	42.97	12.6	1.17	30.4	-	-	P	H
		151.25	33.99	-9.51	43.5	49.16	13.74	1.49	30.4	216	187	P	H
		191.02	33.73	-9.77	43.5	51.2	11.25	1.68	30.4	-	-	P	H
		270.56	32.71	-13.29	46	47.42	13.9	1.89	30.5	-	-	P	H
		435.46	30.71	-15.29	46	41.4	17.28	2.59	30.56	-	-	P	H
		40.67	35.14	-4.86	40	51.33	13.92	0.77	30.88	100	0	P	V
		74.62	28.87	-11.13	40	49.24	9.1	1.05	30.52	-	-	P	V
		151.25	27.51	-15.99	43.5	42.68	13.74	1.49	30.4	-	-	P	V
		267.65	28.84	-17.16	46	43.67	13.8	1.87	30.5	-	-	P	V
		453.89	24.66	-21.34	46	35.03	17.47	2.65	30.49	-	-	P	V
		745.86	25.08	-20.92	46	31.34	20.77	3.46	30.49	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 36 5180MHz		5147.55	64.64	-9.36	74	56.39	35.25	6.77	33.77	150	122	P	H
		5149.15	43.25	-10.75	54	35	35.25	6.77	33.77	150	122	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 5147.55MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 35.25 (dB/m) + 6.77 (dB) + 56.39 (dBμV) –33.77 (dB)

= 64.64 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 64.64 (dBμV/m) – 74(dBμV/m)

= -9.36 (dB)

For Average Limit @ 5149.15MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 35.25 (dB/m) + 6.77 (dB) + 35 (dBμV) –33.77 (dB)

= 43.25 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.25 (dBμV/m) – 54(dBμV/m)

= -10.75 (dB)

Both peak and average measured complies with the limit line, so test result is "PASS".

Appendix D. Product Equality Declaration

TCT Mobile

5F, C building, No. 232, Liang Jing Road
ZhangJiang High-Tech Park, Pudong Area
Shanghai, P.R. China. 201203
TEL: +86(0)21 61460666
FAX: +86(0)21 61460602

Declaration of changes from Initial (Idol 3 5.5 LATAM-6045B) to Variant (Idol 3 5.5 cricket – 6045O)

General: 6045O is a variant product of 6045B.

SOFTWARE MODIFICATIONS:

- Protocol Stack changes: NO
- MMS/STK/USAT/USIM changes: NO
- DM/SUPL/VT/FUMO/SWP/HCI: NO
- Reversible Call: NO
- Other changes detailed: 6045O have no IMS,DTM, have TTY.

HARDWARE MODIFICATIONS:

- Baseband changes: NO
- Band changes: YES

product	GSM	UMTS	LTE
6045B	850/900/1800/1900	FDD 850/900/1900/2100	B1/2/3/4/7/28
6045O	850/900/1800/1900	FDD 850/1900/1700/2100	B2/4/5/12

- Antenna changes: yes
- PCB Layout changes: no
- Main components changes:

	Base Band	Transceiver	ASM	Power Amplifier	Tx SAW Filter	Rx SAW Filter（SAW Duplexer）
GSM 850	NO	NO	NO	NO	N/A	NO
GSM 900	NO	NO	NO	NO	N/A	NO
GSM 1800	NO	NO	NO	NO	N/A	NO
GSM 1900	NO	NO	NO	NO	N/A	NO

	Base Band	Transceiver	ASM	Power Amplifier	Tx SAW Filter	Rx SAW Filter（SAW Duplexer）
UMTS FDD I	NO	NO	NO	NO	N/A	NO
UMTS FDD II	NO	NO	NO	NO	NA	NO
UMTS FDD IV	NO	NO	NO	NO	N/A	NO
UMTS FDD V	NO	NO	NO	NO	N/A	NO

	Base Band	Transceiver	ASM	Power Amplifier	Tx SAW Filter	Rx SAW Filter（SAW Duplexer）
LTE B2	NO	NO	NO	NO	N/A	NO
LTE B4	NO	NO	NO	NO	N/A	NO
LTE B5	NO	NO	NO	NO	N/A	NO
LTE B12	NO	NO	NO	NO	N/A	YES

- Bluetooth changes: NO
- WiFi changes: NO
- FM changes: NO
- Other components changes:NO

TP/LCD/ Camera changes: NO

- Other changes detailed: 6045O support HSDPA Category 14 and GPRS/EDGE class 10. 6045B support HSDPA Category 24 and GPRS/EDGE class 12.

MECHANICAL MODIFICATIONS:

- Use new metal front/back cover or keypad: NO
- Mechanical shell changes: NO

  Whole size of EUT: NO

  Distance of Ear reference point to bottom of handset: NO

  Other trinkets to change the surface of handset: NO
- Other changes detailed

APPROVED BY:

Project Manager:
Signature: 李海光
Date: 2015.8.27