


Test Report No:
2590298R-RFUSV01S-A

TEST REPORT

FCC Rules&Regulations

Product Name	TS Electronic Lock & Trim
Brand Name	TownSteel
Model No.	e-Cronus 3000, e-Kestros 3000
FCC ID	2ACEY-TSM-3000
Applicant's Name / Address	TownSteel Inc. 17901 Railroad Street, City of Industry, CA, 91748, United States
Manufacturer's Name / Address	TownSteel Inc. 17901 Railroad Street, City of Industry, CA, 91748, United States
Test Method Requested, Standard	FCC CFR Title 47 Part 15 Subpart C Section 15.247 ANSI C63.10-2020, ANSI C63.10-2020+Cor.1-2023, ANSI C63.10a-2024
Verdict Summary	IN COMPLIANCE
Documented By	 Jennie She
Approved By	 Rueyyan Lin
Date of Receipt	Sep. 10, 2025
Date of Issue	Jan. 15, 2026
Report Version	V1.0

INDEX

	page
Competences and Guarantees.....	4
General Conditions	4
Revision History	5
Summary of Test Result.....	6
Comments and Remarks	6
1. General Information.....	7
1.1. EUT Description	7
1.2. EUT Information	7
1.3. Testing Applied Standards.....	7
1.4. Testing Location Information	8
1.5. Measurement Uncertainty	8
1.6. List of Test Equipment	9
2. Test Configuration of EUT	10
2.1. Test Condition.....	10
2.2. Test Frequency Mode	10
2.3. Duty Cycle	11
2.4. The Worst Case Measurement Configuration.....	12
2.5. Tested System Details	13
2.6. Configuration of Tested System	13
3. Occupied Bandwidth & DTS Bandwidth.....	14
3.1. Test Setup	14
3.2. Test Limit	14
3.3. Test Procedures	14
3.4. Test Result of Occupied Bandwidth & DTS Bandwidth.....	14
4. Maximum Conducted Output Power	15
4.1. Test Setup	15
4.2. Test Limit	15
4.3. Test Procedures	15
4.4. Test Result of Maximum Conducted Output Power	15
5. Maximum Power Spectral Density	16
5.1. Test Setup	16
5.2. Test Limit	16
5.3. Test Procedures	16
5.4. Test Result of Maximum Power Spectral Density	16
6. Antenna Port Conducted Emission	17
6.1. Test Setup	17
6.2. Test Limit	17
6.3. Test Procedure	17

6.4.	Test Result of Antenna Port Conducted Emission	17
7.	Transmitter Radiated Spurious Emission	18
7.1.	Test Setup	18
7.2.	Test Limit	19
7.3.	Test Procedure	19
7.4.	Test Result of Transmitter Radiated Spurious Emission (Below 30 MHz)	20
7.5.	Test Result of Transmitter Radiated Spurious Emission	20
Appendix A. Test Result of Occupied Bandwidth & DTS Bandwidth		
Appendix B. Test Result of Maximum Conducted Output Power		
Appendix C. Test Result of Maximum Power Spectral Density		
Appendix D. Test Result of Antenna Port Conducted Emission		
Appendix E. Test Result of Transmitter Radiated Spurious Emission		
Appendix F. Test Setup Photograph		

Competences and Guarantees

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

General Conditions

1. The test results relate only to the samples tested.
2. The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.
3. This report must not be used to claim product endorsement by TAF or any agency of the government.
4. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.
5. Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Revision History

Version	Description	Issued Date
V1.0	Initial issue of report	Jan. 15, 2026

Summary of Test Result

Report Clause	Test Items	Result (PASS/FAIL)	Remark
-	AC Power Line Conducted Emission	N/A	Note
3	Occupied Bandwidth & DTS Bandwidth	PASS	-
4	Maximum Conducted Output Power	PASS	-
5	Maximum Power Spectral Density	PASS	-
6	Antenna Port Conducted Emission	PASS	-
7	Transmitter Radiated Spurious Emission	PASS	-
Note: The EUT was powered by DC 6V (battery). It's not necessary to apply to AC Power Line Conducted Emission test.			

Comments and Explanations
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Comments and Remarks

The product specification and testing instructions for the EUT declared in the report are provided by the manufacturer who will take all responsibilities for the accuracy.

1. General Information

1.1. EUT Description

Frequency Range	2400 ~ 2483.5 MHz
Operating Frequency	1 Mbps: 2402 ~ 2480 MHz
Channel Number	1 Mbps: 40 Channels
Mode	Bluetooth LE
Type of Modulation	GFSK

Accessories Information		
No.	Equipment Name	Description
1	Key* 1	-

The difference for each model is shown as below:

Model No	Password Panel	keyhole	Internal handle
e-Cronus 3000	Independent panel	Independent	Different designs
e-Kestros 3000	Connected to the handle	Connected to the handle	

Note:

1. In addition to the above information, these devices are identical in RF hardware design and circuit.
2. From the above models, both e-Cronus 3000 and e-Kestros 3000 were tested for radiated measurements, while model e-Cronus 3000 was selected as the representative model and its data was recorded in this report.

Antenna Information				
Ant.	Brand Name	Model No.	Type	Gain (dBi)
1	Holtek	AN043	PCB	5.3

1.2. EUT Information

EUT Power Type	Form Battery (1.5V* 4)			
EUT Function	☒	Point-to-multipoint	☐	Point-to-point

1.3. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2020, ANSI C63.10-2020+Cor.1-2023, ANSI C63.10a-2024

The following reference test guidance is not within the scope of accreditation of TAF:

- ♦ KDB 558074 D01 v05r02

1.4. Testing Location Information

Testing Location Information		
Test Laboratory : DEKRA Testing and Certification Co., Ltd.		
1 (TAF: 3024)	ADD: No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C. TEL: +886-3-582-8001 FAX: +886-3-582-8958 Test site Designation No. TW3024 with FCC. Conformity Assessment Body Identifier (CABID) TW3024 with ISED.	
2 (TAF: 3024)	ADD: No.372, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C. TEL: +886-3-582-8001 FAX: +886-3-582-8958 Test site Designation No. TW3024 with FCC. Conformity Assessment Body Identifier (CABID) TW3024 with ISED.	
Test site number for address 1 includes HC-SR02 and HC-CB10. Test site number for address 2 includes HC-CB02, HC-CB03, HC-CB04, HC-SR10 and HC-SR12.		

Test Condition	Test Site No.	Test Engineer	Test Environment (°C / %)	Test Date
RF Conducted Emission	HC-SR12	Kevin Teng	24.5 / 51.7	2025/09/15
Radiated Emission	HC-CB02	Scott Chang	21~24 / 55~68	2025/09/15~2025/09/25

1.5. Measurement Uncertainty

Uncertainties have been calculated according to the DEKRA internal document with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Test item	Uncertainty
Occupied Bandwidth & DTS Bandwidth	± 282.55 Hz
Maximum Conducted Output Power	± 1.16 dB
Maximum Power Spectral Density	± 2.47 dB
Antenna Port Conducted Emission	± 2.47 dB
Transmitter Radiated Spurious Emission	± 3.52 dB below 1 GHz ± 3.56 dB above 1 GHz

1.6. List of Test Equipment

HC-SR12

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Cal. Date	Next Cal. Date
Signal & Spectrum Analyzer	R&S	FSV40	101869	10Hz-40GHz	2025/06/17	2026/06/16
High Speed Peak Power Meter Dual Input	Anritsu	ML2496A	1602004	0.3-40 GHz	2024/10/29	2025/10/28
Pulse Power Sensor	Anritsu	MA2411B	1531043	0.3-40 GHz	2024/10/29	2025/10/28
Power Supply	Agilent	E3645A	MY50030024	N/A	N/A	N/A

HC-CB02

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Cal. Date	Next Cal. Date
EXA Signal Analyzer	Keysight	N9010A	MY51440132	10 Hz-44 GHz	2024/12/10	2025/12/09
Trilog Broadband Antenna	Schwarzbeck	VULB 9168	1272	30 MHz-2 GHz	2025/05/13	2026/05/12
Double Ridged Horn Antenna	RF SPIN	DRH18-E	211211A18EN	1G-18GHz	2024/11/08	2025/11/07
Pre-Amplifier	EMCI	EMC01820I	980365	30M-8 GHz,20 dB	2025/03/20	2026/03/19
Pre-Amplifier	EMEC	EM01G18GA	060741	1G-18 GHz,50 dB	2025/04/14	2026/04/13

Note: All equipment upon which need to calibrated are with calibration period of 1 year.

2. Test Configuration of EUT

2.1. Test Condition

EUT Operational Condition	
Testing Voltage	DC 6V


2.2. Test Frequency Mode

Test Software Version	N/A
-----------------------	-----

Modulation	Frequency (MHz)	Power Setting
GFSK (1 Mbps)	2402	Default
	2440	Default
	2480	Default

2.3. Duty Cycle

Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
GFSK (1 Mbps)	--	--	100.00	0.00	0.010



2.4. The Worst Case Measurement Configuration

Tests Item	Occupied Bandwidth & DTS Bandwidth Maximum Conducted Output Power Maximum Power Spectral Density Antenna Port Conducted Emission
Test Condition	Conducted measurement at transmit chains

Tests Item	Transmitter Radiated Spurious Emission	
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.	
Operating Mode	Transmit	
Test Mode	1	e-Cronus 3000
	2	e-Kestros 3000


Note:

1. Determining compliance shall be based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. For radiated spurious emission below 1 GHz have performed all modes of operation were investigated and the worst-case emissions are reported.

2.5. Tested System Details


N/A

2.6. Configuration of Tested System



3. Occupied Bandwidth & DTS Bandwidth

3.1. Test Setup



3.2. Test Limit

The 6 dB bandwidth: ≥ 500 kHz.

Occupied Bandwidth: N/A

3.3. Test Procedures


The EUT was setup according to ANSI C63.10; tested according to DTS test procedure of KDB 558074.

3.4. Test Result of Occupied Bandwidth & DTS Bandwidth

Refer as Appendix A

4. Maximum Conducted Output Power

4.1. Test Setup



4.2. Test Limit

The Maximum Conducted Output Power shall be less 1 Watt.

4.3. Test Procedures


The EUT was setup according to ANSI C63.10; tested according to DTS test procedure of KDB 558074.

4.4. Test Result of Maximum Conducted Output Power

Refer as Appendix B

5. Maximum Power Spectral Density

5.1. Test Setup



5.2. Test Limit

The peak power spectral density conducted from the intentional radiated to the antenna shall not be greater than +8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.3. Test Procedures


The EUT was setup according to ANSI C63.10; tested according to DTS test procedure of KDB 558074.

5.4. Test Result of Maximum Power Spectral Density

Refer as Appendix C

6. Antenna Port Conducted Emission

6.1. Test Setup



6.2. Test Limit

RF output power procedure	Limit (dBc)
Peak output power procedure	20
Average output power procedure	30

Remarks:

1. In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limit.
2. If the transmitter complies with the conducted power limit based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

6.3. Test Procedure

The EUT was setup according to ANSI C63.10 and tested according to DTS test procedure of KDB 558074.


6.4. Test Result of Antenna Port Conducted Emission

Refer as Appendix D


7. Transmitter Radiated Spurious Emission

7.1. Test Setup


9 kHz ~ 30 MHz



30 MHz ~ 1 GHz



Above 1 GHz



7.2. Test Limit

Frequency (MHz)	Field strength (uV/m)	Field strength (dBuV/m)	Measurement distance (m)
0.009 – 0.490	2400/F(kHz)	20 log (2400/F(kHz))	300
0.490 – 1.705	24000/F(kHz)	20 log (24000/F(kHz))	30
1.705 - 30	30	29.5	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
Above 960	500	54	3

Remarks:

1. Field strength (dBuV/m) = 20 log Field strength (uV/m)
2. In the Above Table, the tighter limit applies at the band edges.
3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

7.3. Test Procedure

The EUT was setup according to ANSI C63.10 and tested according to DTS test procedure of KDB 558074.

The EUT and its simulators are placed on a turn table which is 0.8 or 1.5 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.10 on radiated measurement.

On any frequency or frequencies from 9 kHz(include The the lowest oscillator frequency generated within the device up to the 10th harmonic) to 1000 MHz, the limit shown are based on measuring equipment employing a quasi-peak detector function and on any frequency or frequencies above 1000 MHz the radiated limit shown are based upon the use of measurement instrumentation employing an average detector function. When average radiated emission measurement are included emission measurement below 1000 MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.

The bandwidth below 1 GHz setting on the field strength meter is 120 kHz and above 1 GHz is 1 MHz.

7.4. Test Result of Transmitter Radiated Spurious Emission (Below 30 MHz)


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

7.5. Test Result of Transmitter Radiated Spurious Emission

Refer as Appendix E


Appendix A.1 Test Result of Occupied Bandwidth

Modulation	Frequency (MHz)	Measure Level (MHz)	Limit (MHz)
GFSK (1 Mbps)	2402	1.01	-
	2440	1.00	-
	2480	1.00	-



Appendix A.2 Test Result of DTS Bandwidth

Modulation	Frequency (MHz)	Measure Level (MHz)	Limit (MHz)	Result
GFSK (1 Mbps)	2402	0.67	0.50	Pass
	2440	0.67	0.50	Pass
	2480	0.67	0.50	Pass




Appendix B. Test Result of Maximum Conducted Output Power

Modulation	Frequency (MHz)	Maximum Conducted Output Power (dBm)		Limit (dBm)	Result
		Average	Peak		
GFSK (1 Mbps)	2402	-3.090	-2.870	30.00	Pass
	2440	-3.620	-3.460	30.00	Pass
	2480	-4.260	-4.060	30.00	Pass



Appendix C. Test Result of Maximum Power Spectral Density

Modulation	Frequency (MHz)	Measure Value (dBm/3kHz)	Limit (dBm/3kHz)	Result
GFSK (1 Mbps)	2402	-3.27	8.00	Pass
	2440	-3.85	8.00	Pass
	2480	-4.52	8.00	Pass





Appendix D. Test Result of Antenna Port Conducted Emission



GFSK (1 Mbps) / 2402 MHz




GFSK (1 Mbps) / 2440 MHz



GFSK (1 Mbps) / 2480 MHz






Appendix E. Test Result of Transmitter Radiated Spurious Emission

30 MHz ~ 1 GHz

Test Mode: Mode 1

Site :HC-CB02
Condition :3m Horizontal
Mode :BLE_TX_LF
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	Limit	Level	dB	
1	32.716	29.26	40.00	-10.74	32.43	-3.17	QP
2	162.017	21.59	43.50	-21.91	24.26	-2.67	QP
3	243.109	21.94	46.00	-24.06	25.98	-4.04	QP
4	324.395	25.00	46.00	-20.20	27.10	-1.30	QP
5	490.459	24.75	46.00	-21.25	22.05	2.70	QP
6	845.964	31.27	46.00	-14.73	22.03	9.24	QP

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission under 30MHz was not included since the emission levels are very low against the limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m Vertical
Mode :BLE_TX_LF
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	Limit	Level	dB	
1	32.716	34.40	40.00	-5.60	37.57	-3.17	QP
2	162.017	28.78	43.50	-14.72	31.45	-2.67	QP
3	243.109	34.42	46.00	-11.58	38.46	-4.04	QP
4	324.201	41.02	46.00	-4.98	42.33	-1.31	QP
5	404.905	29.24	46.00	-16.76	28.54	0.70	QP
6	567.380	28.89	46.00	-17.11	24.68	4.21	QP

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission under 30MHz was not included since the emission levels are very low against the limit.
5. The other emission levels were very low against the limit.

Test Mode: Mode 2

Site :HC-CB02
Condition :3m Horizontal
Mode :BLE_TX_LF
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	Limit	Level	dB	
1	34.850	26.06	40.00	-13.94	28.86	-2.80	Peak
2	147.467	20.40	43.50	-23.10	22.98	-2.58	Peak
3	321.679	23.20	46.00	-22.80	24.57	-1.37	Peak
4	617.238	27.24	46.00	-18.76	21.57	5.67	Peak
5	863.715	30.69	46.00	-15.31	21.49	9.20	Peak
6	967.699	31.82	54.00	-22.18	21.21	10.61	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission under 30MHz was not included since the emission levels are very low against the limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m Vertical
Mode :BLE_TX_LF
Test by :Scott Chang



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	Limit	Level	dB	
1	32.813	32.66	40.00	-7.34	35.85	-3.19	QP
2	134.954	22.46	43.50	-21.04	26.08	-3.62	QP
3	321.679	36.79	46.00	-9.21	38.16	-1.37	QP
4	473.484	23.51	46.00	-22.49	21.07	2.44	QP
5	653.710	27.69	46.00	-18.31	21.42	6.27	QP
6	954.216	32.38	46.00	-13.62	21.61	10.77	QP


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission under 30MHz was not included since the emission levels are very low against the limit.
5. The other emission levels were very low against the limit.

Above 1 GHz

Test Mode: Mode 1

Site :HC-CB02
Condition :3m ,Horizontal
RB/VB(kHz):1000 / 3000
Mode :BLE_1M_TX_2402MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2378.495	40.47	74.00	-33.53	28.79	11.68	Peak
2	2401.979	81.68	-----	-----	69.91	11.77	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Vertical
RB/VB(kHz):1000 / 3000
Mode :BLE_1M_TX_2402MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2379.958	39.88	74.00	-34.12	28.19	11.69	Peak
2	2401.979	78.95	-----	-----	67.18	11.77	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Horizontal
RB/VB(kHz):1000 / 1
Mode :BLE_1M_TX_2402MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2320.906	30.89	54.00	-23.11	19.44	11.45	Average
2	2402.017	81.69	-----	-----	69.92	11.77	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Vertical
RB/VB(kHz):1000 / 1
Mode :BLE_1M_TX_2402MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2320.982	30.88	54.00	-23.12	19.43	11.45	Average
2	2402.017	78.89	-----	-----	67.12	11.77	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Horizontal
Mode :BLE_1M_TX_2402MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	4804.000	49.33	74.00	-24.67	64.31	-14.98	Peak
2	7206.000	47.10	74.00	-26.90	55.22	-8.12	Peak
3	9608.000	48.10	74.00	-25.90	53.07	-4.97	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Vertical
Mode :BLE_1M_TX_2402MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	4804.000	48.70	74.00	-25.30	63.68	-14.98	Peak
2	7206.000	47.91	74.00	-26.09	56.03	-8.12	Peak
3	9608.000	48.43	74.00	-25.57	53.40	-4.97	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Horizontal
RB/VB(kHz):1000 / 3000
Mode :BLE_1M_TX_2440MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2375.721	39.91	74.00	-34.09	28.24	11.67	Peak
2	2439.960	83.60	-----	-----	71.67	11.93	Peak
3	2494.604	39.96	74.00	-34.04	27.82	12.14	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Vertical
RB/VB(kHz):1000 / 3000
Mode :BLE_1M_TX_2440MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2358.830	40.73	74.00	-33.27	29.13	11.60	Peak
2	2439.732	79.84	-----	-----	67.91	11.93	Peak
3	2485.332	39.79	74.00	-34.21	27.68	12.11	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Horizontal
RB/VB(kHz):1000 / 1
Mode :BLE_1M_TX_2440MHz
Test by :Scott Chang




No.	Frequency MHz	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Read Level dBuV	Factor dB	Remark
1	2358.887	32.20	54.00	-21.80	20.60	11.60	Average
2	2440.017	83.63	54.00	-24.34	17.50	12.16	Average
3	2496.808	29.66	54.00	-24.34	17.50	12.16	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Vertical
RB/VB(kHz):1000 / 1
Mode :BLE_1M_TX_2440MHz
Test by :Scott Chang




No.	Frequency MHz	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Read Level dBuV	Factor dB	Remark
1	2359.001	32.15	54.00	-21.85	20.55	11.60	Average
2	2440.017	79.83	54.00	-24.53	17.30	12.17	Average
3	2498.936	29.47	54.00	-24.53	17.30	12.17	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Horizontal
Mode :BLE_1M_TX_2440MHz
Test by :Scott Chang




No.	Frequency MHz	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Read Level dBuV	Factor dB	Remark
1	4880.000	46.49	74.00	-27.51	61.17	-14.68	Peak
2	7320.000	47.18	74.00	-26.82	55.16	-7.98	Peak
3	9760.000	49.17	74.00	-24.83	53.85	-4.68	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Vertical
Mode :BLE_1M_TX_2440MHz
Test by :Scott Chang




No.	Frequency MHz	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Read Level dBuV	Factor dB	Remark
1	4880.000	46.92	74.00	-27.08	61.60	-14.68	Peak
2	7320.000	47.73	74.00	-26.27	55.71	-7.98	Peak
3	9760.000	49.79	74.00	-24.21	54.47	-4.68	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Horizontal
RB/VB(kHz):1000 / 3000
Mode :BLE_1M_TX_2480MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level		
1	2479.974	83.26	-----	-----	71.17	12.09	Peak
2	2484.439	39.61	74.00	-34.39	27.51	12.10	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Vertical
RB/VB(kHz):1000 / 3000
Mode :BLE_1M_TX_2480MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level		
1	2479.955	75.93	-----	-----	63.84	12.09	Peak
2	2484.458	40.12	74.00	-33.88	28.02	12.10	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Horizontal
RB/VB(kHz):1000 / 1
Mode :BLE_1M_TX_2480MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level		
1	2480.012	83.27	-----	-----	71.18	12.09	Average
2	2486.643	29.87	54.00	-24.13	17.75	12.12	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Vertical
RB/VB(kHz):1000 / 1
Mode :BLE_1M_TX_2480MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level		
1	2480.012	75.85	-----	-----	63.76	12.09	Average
2	2489.113	29.56	54.00	-24.44	17.43	12.13	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Horizontal
Mode :BLE_1M_TX_2480MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	4960.000	43.56	74.00	-30.44	57.93	-14.37	Peak
2	7440.000	47.22	74.00	-26.78	55.04	-7.82	Peak
3	9920.000	49.12	74.00	-24.88	53.51	-4.39	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Vertical
Mode :BLE_1M_TX_2480MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	4960.000	43.53	74.00	-30.47	57.90	-14.37	Peak
2	7440.000	47.51	74.00	-26.49	55.33	-7.82	Peak
3	9920.000	48.44	74.00	-25.56	52.83	-4.39	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Test Mode: Mode 2

Site :HC-CB02
Condition :3m ,Horizontal
RB/VB(kHz):1000 / 3000
Mode :BLE_TX_2402MHz
Test by :Scott Chang




No.	Frequency MHz	Level dBuV/m	Limit dBuV/m	Over Limit dB	Read Level dBuV	Factor dB	Remark
1	2357.880	39.47	74.00	-34.53	27.87	11.60	Peak
2	2401.979	77.88	-----	-----	66.11	11.77	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Vertical
RB/VB(kHz):1000 / 3000
Mode :BLE_TX_2402MHz
Test by :Scott Chang




No.	Frequency MHz	Level dBuV/m	Limit dBuV/m	Over Limit dB	Read Level dBuV	Factor dB	Remark
1	2317.030	40.05	74.00	-33.95	28.61	11.44	Peak
2	2401.979	80.16	-----	-----	68.39	11.77	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Horizontal
RB/VB(kHz):1000 / 1
Mode :BLE_TX_2402MHz
Test by :Scott Chang




No.	Frequency MHz	Level dBuV/m	Limit dBuV/m	Over Limit dB	Read Level dBuV	Factor dB	Remark
1	2387.102	28.70	54.00	-25.30	16.98	11.72	Average
2	2401.998	77.87	-----	-----	66.10	11.77	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Vertical
RB/VB(kHz):1000 / 1
Mode :BLE_TX_2402MHz
Test by :Scott Chang




No.	Frequency MHz	Level dBuV/m	Limit dBuV/m	Over Limit dB	Read Level dBuV	Factor dB	Remark
1	2321.514	31.12	54.00	-22.88	19.67	11.45	Average
2	2402.017	80.11	-----	-----	68.34	11.77	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Horizontal
Mode :BLE_TX_2402MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	4804.000	43.10	74.00	-30.90	58.08	-14.98	Peak
2	7206.000	47.29	74.00	-26.71	55.41	-8.12	Peak
3	9608.000	49.09	74.00	-24.91	54.06	-4.97	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Vertical
Mode :BLE_TX_2402MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	4804.000	46.02	74.00	-27.98	61.00	-14.98	Peak
2	7206.000	47.07	74.00	-26.93	55.19	-8.12	Peak
3	9608.000	48.54	74.00	-25.46	53.51	-4.97	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Horizontal
RB/VB(kHz):1000 / 3000
Mode :BLE_TX_2440MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2317.733	38.96	74.00	-35.04	27.52	11.44	Peak
2	2439.979	76.78	-----	-----	64.85	11.93	Peak
3	2484.116	39.72	74.00	-34.28	27.62	12.10	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Vertical
RB/VB(kHz):1000 / 3000
Mode :BLE_TX_2440MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2359.210	39.52	74.00	-34.48	27.92	11.60	Peak
2	2439.732	78.88	-----	-----	66.95	11.93	Peak
3	2493.711	39.91	74.00	-34.09	27.77	12.14	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Horizontal
RB/VB(kHz):1000 / 1
Mode :BLE_TX_2440MHz
Test by :Scott Chang




No.	Frequency MHz	Level dBuV/m	Limit dBuV/m	Over Limit dB	Read Level dBuV	Factor dB	Remark
1	2388.451	28.81	54.00	-25.19	17.08	11.73	Average
2	2440.017	76.78	54.00	22.78	64.85	11.93	Average
3	2497.397	29.33	54.00	-24.67	17.16	12.17	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Vertical
RB/VB(kHz):1000 / 1
Mode :BLE_TX_2440MHz
Test by :Scott Chang




No.	Frequency MHz	Level dBuV/m	Limit dBuV/m	Over Limit dB	Read Level dBuV	Factor dB	Remark
1	2359.552	30.37	54.00	-23.63	18.77	11.60	Average
2	2440.017	78.87	54.00	24.87	66.94	11.93	Average
3	2488.106	29.27	54.00	-24.73	17.14	12.13	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Horizontal
Mode :BLE_TX_2440MHz
Test by :Scott Chang




No.	Frequency MHz	Level dBuV/m	Limit dBuV/m	Over Limit dB	Read Level dBuV	Factor dB	Remark
1	4880.000	44.59	74.00	-29.41	59.27	-14.68	Peak
2	7320.000	48.01	74.00	-25.99	55.99	-7.98	Peak
3	9760.000	48.75	74.00	-25.25	53.43	-4.68	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Vertical
Mode :BLE_TX_2440MHz
Test by :Scott Chang




No.	Frequency MHz	Level dBuV/m	Limit dBuV/m	Over Limit dB	Read Level dBuV	Factor dB	Remark
1	4880.000	45.68	74.00	-28.32	60.36	-14.68	Peak
2	7320.000	47.28	74.00	-26.72	55.26	-7.98	Peak
3	9760.000	48.84	74.00	-25.16	53.52	-4.68	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Horizontal
RB/VB(kHz):1000 / 3000
Mode :BLE_TX_2480MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2479.993	76.57	-----	-----	64.48	12.09	Peak
2	2486.301	39.80	74.00	-34.20	27.69	12.11	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Vertical
RB/VB(kHz):1000 / 3000
Mode :BLE_TX_2480MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2479.974	78.34	-----	-----	66.25	12.09	Peak
2	2484.420	39.83	74.00	-34.17	27.73	12.10	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Horizontal
RB/VB(kHz):1000 / 1
Mode :BLE_TX_2480MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2480.012	76.55	-----	-----	64.46	12.09	Average
2	2487.156	29.23	54.00	-24.77	17.10	12.13	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Vertical
RB/VB(kHz):1000 / 1
Mode :BLE_TX_2480MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	2480.031	78.31	-----	-----	66.22	12.09	Average
2	2491.640	29.11	54.00	-24.89	16.98	12.13	Average

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Horizontal
Mode :BLE_TX_2480MHz
Test by :Scott Chang




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	4960.000	43.19	74.00	-30.81	57.56	-14.37	Peak
2	7440.000	48.24	74.00	-25.76	56.06	-7.82	Peak
3	9920.000	48.69	74.00	-25.31	53.08	-4.39	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.

Site :HC-CB02
Condition :3m ,Vertical
Mode :BLE_TX_2480MHz
Test by :Scott Chang



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	
1	4960.000	45.90	74.00	-28.10	60.27	-14.37	Peak
2	7440.000	47.33	74.00	-26.67	55.15	-7.82	Peak
3	9920.000	50.04	74.00	-23.96	54.43	-4.39	Peak

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The peak result complies with AVG limit, AVG result is deemed to comply with AVG limit.
5. The other emission levels were very low against the limit.