

FCC PART 15C TEST REPORT FOR CERTIFICATION
On Behalf of

Digilife Technologies Co., Ltd.

Car Camcorder

P70; SP20A; f940x; P75; P80; P85; f940g; f945x; f945g

FCC ID: 2ACFI20AWM

Prepared for : Digilife Technologies Co., Ltd.
13F., No.7, Dexing W. Rd., Shilin Dist., Taipei City 111, Taiwan
(R.O.C.)

Prepared By : Audix Technology (Shenzhen) Co., Ltd.
No. 6, Kefeng Road, Science & Technology Park,
Nanshan District , Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F25284
Date of Test : Nov.25~Dec.06, 2025
Date of Report : Dec.23, 2025

TABLE OF CONTENTS

Description	Page
1. SUMMARY OF STANDARDS AND RESULTS	5
1.1. Description of Standards and Results.....	5
2. GENERAL INFORMATION.....	6
2.1. Description of Equipment Under Test.....	6
2.2. Feature of Equipment Under Test	7
2.3. Tested Supporting System Details.....	8
2.4. Block diagram of connection between the EUT and simulators	8
2.5. Test Equipments	9
2.6. Test Information	10
2.7. Test Facility.....	11
2.8. Measurement Uncertainty (95% confidence levels, k=2)	11
3. POWER LINE CONDUCTED EMISSION TEST	12
3.1. Block Diagram of Test Setup	12
3.2. Power Line Conducted Emission Test Limits	12
3.3. Configuration of EUT on Test.....	12
3.4. Operating Condition of EUT	13
3.5. Test Procedure.....	13
3.6. Power Line Conducted Emission Test Results.....	13
4. RADIATED EMISSION TEST	14
4.1. Block Diagram of Test Setup	14
4.2. Radiated Emission Limits.....	15
4.3. EUT Configuration on Test.....	15
4.4. Operating Condition of EUT	16
4.5. Test Procedure.....	16
4.6. Radiated Emission Test Results	16
5. CONDUCTED SPURIOUS EMISSIONS	130
5.1. Limit.....	130
5.2. Test Procedure.....	130
5.3. Test result	130
6. BAND EDGE COMPLIANCE TEST.....	149
6.1. Limit.....	149
6.2. Test Procedure	149
6.3. Test Results	149
7. 6dB & 99% Bandwidth Test.....	198
7.1. Limit.....	198
7.2. Test Procedure.....	198
7.3. Test Results	199
8. OUTPUT POWER TEST	207
8.1. Limit (FCC Part 15C 15.247 b(3))	207
8.2. Test Procedure.....	207
8.3. Test Results	208
9. Power Spectral Density Test.....	212
9.1. Limit.....	212
9.2. Test Procedure	212
9.3. Test Results.....	213
10. Antenna REQUIREMENT	217
10.1. Standard Applicable	217
10.2. Antenna Connected Construction.....	217

11. DEVIATION TO TEST SPECIFICATIONS218

Appendix A. Photograph of Test
Appendix B. Photo of the EUT

TEST REPORT

Applicant : Digilife Technologies Co., Ltd.
Manufacturer : Digilife Technologies Co., Ltd.
Product : Car Camcorder
FCC ID : 2ACFI20AWM
(A) Model No. : P70; SP20A; f940x; P75; P80; P85; f940g; f945x; f945g
(B) Test Voltage : DC 5V From Adapter Input DC 12V

Tested for comply with:
FCC CFR 47 Part 15 Subpart C

Test procedure used:
ANSI C63.10:2020+Cor1:2023
KDB 558074 D01v05

The device described above is tested by Audix Technology (Shenzhen) Co., Ltd. to confirm comply with all the FCC Part 15 Subpart C requirements. The test results are contained in this test report and Audix Technology (Shenzhen) Co., Ltd. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC and IC requirements. This report contains data that are not covered by the NVLAP accreditation.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to single evaluation of one sample of above mentioned product and shall not be reproduced in part without written approval of Audix Technology (Shenzhen) Co., Ltd.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U. S. Government.

Date of Test: Nov.25~Dec.06, 2025 Date of Report: Dec.23, 2025

Prepared by: Olivia Liu Reviewed by: Thomas Chen
Olivia Liu / Assistant Thomas Chen / Assistant Manager

Approved & Authorized Signer:



1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT has been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	Standard	Results
Power Line Conducted Emission	FCC Part 15: 15.207	N/A
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.205	PASS
Band Edge Compliance	FCC Part 15: 15.247(d)	PASS
Conducted spurious emissions	FCC Part 15: 15.247(d)	PASS
6dB Bandwidth	FCC Part 15: 15.247(a)(2)	PASS
Peak Output Power	FCC Part 15: 15.247(b)(3)	PASS
Power Spectral Density	FCC Part 15: 15.247(e)	PASS
Antenna requirement	FCC Part 15: 15.203	PASS
Note: Measurement uncertainty affection to the result is not considered, the EUT is technically compliant with standard requirements.		

2. GENERAL INFORMATION

2.1. Description of Equipment Under Test

Applicant	Digilife Technologies Co., Ltd.
Applicant Address	13F., No.7, Dexing W. Rd., Shilin Dist., Taipei City 111, Taiwan (R.O.C.)
Manufacturer	Digilife Technologies Co., Ltd.
Manufacturer Address	13F., No.7, Dexing W. Rd., Shilin Dist., Taipei City 111, Taiwan (R.O.C.)
Product	Car Camcorder
Model No.	P70; SP20A; f940x; P75; P80; P85; f940g; f945x; f945g Model differences (Declared by the Applicant): Only the printed mode number is different.
FCC ID	2ACFI20AWM
Sample Type	Prototype production
Date of Receipt	Nov.17, 2025
Date of Test	Nov.25~Dec.06, 2025
Remark: This report only for WIFI 2.4GHz.	


2.2. Feature of Equipment Under Test

Product Feature & Specification		
Product	Car Camcorder	
Model No.	P70	
Power Source	☒ Commercial Power	AC 100-240V, 50/60Hz
	☒ External Power Source	DC 5V 2.5A; Max 12.5W
	☐ Lithium battery	DC V, mAh
	☐ UM battery	DC V
2.4GHz Wi-Fi		
Support Modes	802.11b/g/n20/n40/ax20/ax40	
Frequency Range	2412-2462MHz	
Type of Modulation	802.11b(DSSS): CCK, QPSK, BPSK 802.11g/n(OFDM): 64QAM,16QAM, QPSK, BPSK 802.11ax(OFDM): 64QAM,16QAM, QPSK, BPSK,1024QAM	
Data Rate	802.11b: 1/2/5.5/11Mbps; 802.11g: 6/9/12/18/24/36/48/54Mbps; 802.11n: up to 300Mbps; 802.11ax: up to 574Mbps	
Channel Separation	5MHz	
Antenna System		
Type of Antenna	FPC Antenna	
Antenna Number	1	
Antenna Peak Gain	WIFI 2.4GHz Peak Gain: 3.37dBi WIFI 5GHz: U-NII-1 Band (5150-5250) Peak Gain: 6.23dBi U-NII-3 Band (5725-5850) Peak Gain: 7.85dBi	
Remark: This report is for Wi-Fi 2.4GHz radio specification only. EUT also supports other radio specification as below listed: Wi-Fi 2.4GHz (Test report No. ACS-F25284) Wi-Fi 5GHz (Test report No. ACS- F25285) MPE (Test report No. ACS-F25292)		

2.3. Tested Supporting System Details

No.	Description	ACS No.	Manufacturer	Model	Serial Number
1.	Notebook	N/A	ACER	ZOW	N/A
Power Cord(3C): Unshielded, Detachable, 1.8m Power Adapter: Manufacturer: Lite-On, M/N: PA-1900-32 Data Cable: Shielded, Undetectable, 4.0m(Bond one ferrite core)					

2.4. Block diagram of connection between the EUT and simulators



(EUT: Car Camcorder)

2.5. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	1#Shielding Room(SE)	AUDIX	N/A	N/A	Nov.06,25	3 Year
2.	1#3m Chamber(NSA)	AUDIX	N/A	N/A	Aug.09,25	3Year
3.	1#3m Chamber(SE)	AUDIX	N/A	N/A	Sep.16,25	3 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR3	10383	Jul.10,25	1 Year
5.	Signal Analyzer	Rohde & Schwarz	FSV40	101608	Nov.06,25	1 Year
6.	L.I.S.N.#1	Rohde & Schwarz	ENV216	102160	Jun.09,25	1 Year
7.	Antenna Cable	Eastsheep	RG223	190424	Sep.13,24	2 Year
8.	Tri-log-Broadband Antenna	Schwarzbeck	VULB 9168	01856	Sep.23,25	1 Year
9.	NSA Cable	HUBER+SUHNER	CFD400NL-LW	No.3+190411	Sep.15,25	1 Year
10.	Coaxial Switch	Anritsu	MP59B	6201397222	Mar.10,25	1 Year
11.	RF Cable	TIMES MICROWAVE	SFT205-NMSM-10.00M	689241	Aug.07,25	1 Year
12.	EMI Test Receiver	Rohde & Schwarz	ESR3	101931	Mar.10,25	1 Year
13.	Amplifier	EMCI	EMC0518A45SE	980965	Aug.07,25	1 Year
14.	Amplifier	KEYSIGHT	83017A	39500711	Mar.10,25	1 Year
15.	PXA Signal Analyzer	Agilent	N9030A	MY51380221	Mar.10,25	1 Year
16.	RF Cable	EMCI	EMCCFD400-NM-NM-2500	No.4+190413	Mar.10,25	1 Year
17.	Attenuator(10dB)	eastsheep	2W-SMA-JK-6G-10dB	No. 4	Sep.15,25	1 Year
18.	Signal Analyzer	Rohde & Schwarz	FSV30	104050	Mar.10,25	1 Year
19.	Horn Antenna	EMCO	3115	9510-4580	Jan.21,25	3 Year

Note: N/A means Not applicable.

2.6. Test Information

A special test software (SSCOM5.13.1) was used to control EUT work in Continuous TX mode and select test channel, wireless mode and data rate.

Tested mode, channel, and data rate information			
Mode	data rate (Mbps)(see Note)	Channel	Frequency (MHz)
IEEE 802.11b	1	CH1	2412
	1	CH6	2437
	1	CH11	2462
IEEE 802.11g	6	CH1	2412
	6	CH6	2437
	6	CH11	2462
IEEE 802.11n HT20	MCS0	CH1	2412
	MCS0	CH6	2437
	MCS0	CH11	2462
IEEE 802.11n HT40	MCS0	CH3	2422
	MCS0	CH6	2437
	MCS0	CH9	2452
IEEE 802.11ax HE20	MCS0	CH1	2412
	MCS0	CH6	2437
	MCS0	CH11	2462
IEEE 802.11ax HE40	MCS0	CH3	2422
	MCS0	CH6	2437
	MCS0	CH9	2452
Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.			

2.7. Test Facility

Site Description

Name of Firm

: Audix Technology (Shenzhen) Co., Ltd.
No. 6, Kefeng Road, Science & Technology Park,
Nanshan District , Shenzhen, Guangdong, China

EMC Lab.

: Certificated by ISED, Canada
Company Number: 5183A
CAB identifier: CN0034
Valid Date: Mar.31, 2026

: Accredited by NVLAP, USA
NVLAP Code: 200372-0
Valid Date: Mar.31, 2026


: Certificated by FCC, USA
Designation No: CN5022
Valid Date: Mar.31, 2026

2.8. Measurement Uncertainty (95% confidence levels, k=2)

Test Item	Uncertainty
Uncertainty for Conduction emission test in No. 1 Conduction	2.6dB (150kHz to 30MHz)
Uncertainty for Radiation Emission test in 3m chamber	$\pm 3.8\text{dB}$ (30~200MHz, Polarization: H)
	$\pm 3.8\text{dB}$ (30~200MHz, Polarization: V)
	$\pm 4.0\text{dB}$ (200M~1GHz, Polarization: H)
	$\pm 4.0\text{dB}$ (200M~1GHz, Polarization: V)
Uncertainty for Radiation Emission test in 3m chamber(1GHz-25GHz)	$\pm 4.0\text{dB}$ (1~6GHz, Distance: 3m)
	$\pm 4.0\text{dB}$ (6~25GHz, Distance: 3m)
Uncertainty for S_{VSWR} in 3m chamber	$\pm 2.8\text{dB}$ (1~6GHz, Distance: 3m)
	$\pm 2.8\text{dB}$ (6~25GHz, Distance: 3m)
Uncertainty for Radiated Spurious Emission test in RF chamber	$\pm 3.7\text{dB}$ (30MHz~1000MHz)
	$\pm 3.3\text{dB}$ (1~26.5GHz)
Uncertainty for Conduction Spurious emission test	$\pm 2.0\text{dB}$
Uncertainty for Output power test	$\pm 0.8\text{dB}$
Uncertainty for Bandwidth test	$\pm 83\text{kHz}$
Uncertainty for DC power test	$\pm 1\%$
Uncertainty for test site temperature and humidity	$\pm 0.6^{\circ}\text{C}$
	$\pm 3\%$

3. POWER LINE CONDUCTED EMISSION TEST

3.1. Block Diagram of Test Setup



3.2. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limits shall apply at the transition frequencies.

3. Emission Level (dBμV) = Factor (L.I.S.N.) (dB) + Cable Loss (dB)+Reading (Receiver) (dBμV)

3.3. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

3.3.1. Car Camcorder (EUT)

Model No. : P70

Serial No. : N/A

3.3.2. Support Equipment: As Tested Supporting System Details, in Section 2.2.

3.4. Operating Condition of EUT

- 3.4.1. Setup the EUT as shown as Section 3.1.
- 3.4.2. Turn on the power of EUT.
- 3.4.3. PC run test software to control EUT work in Tx mode.

3.5. Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power Via Adapter unit connected to the power mains through a line impedance stabilization network (L.I.S.N. #1). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10 on Conducted Emission Test.

The bandwidth of test receiver (R & S ESCI) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.


3.6. Power Line Conducted Emission Test Results

N/A.


4. RADIATED EMISSION TEST

4.1. Block Diagram of Test Setup

For frequency range 30MHz-1000MHz



For frequency range 1GHz-25GHz



4.2. Radiated Emission Limits

4.2.1. 15.247&209 limits

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V/m}$	$\text{dB}(\mu\text{V})/\text{m}$
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

Remark: (1) Emission Level ($\text{dB}\mu\text{V}/\text{m}$) = Reading (Receiver) ($\text{dB}\mu\text{V}$) + Antenna Factor (dB/m) + Cable Loss (dB)
Emission Level ($\text{dB}\mu\text{V}/\text{m}$) = Reading (Spectrum) ($\text{dB}\mu\text{V}$) + Antenna Factor (dB/m) – Amp Factor (dB) + Cable Loss (dB)(above 1000MHz)
(2) The smaller limit shall apply at the cross point between two frequency bands.
(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

4.2.2. 15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

4.3. EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

4.3.1. Car Camcorder (EUT)

Model No. : P70
Serial No. : N/A

4.3.2. Support Equipment: As Tested Supporting System Details, in Section 2.3.

4.4. Operating Condition of EUT

4.4.1. Setup the EUT and simulator as shown as Section 4.1.

4.4.2. Turn on the power of all equipments.

4.4.3. Let EUT work in Tx(WiFi 2.4GHz) mode

4.5. Test Procedure

Frequency below 30MHz:

The EUT setup on the turn table which has 0.8 m height to the ground. The turn table rotated 360 degrees and antenna fixed to 1 m to find the maximum emission level. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10 regulation.

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground for frequency 30MHz~1000MHz, 1.5 meter high above ground for frequency above 1GHz and put the absorbing with 2.4m(L)*2.4m(W)*0.3m(H) on the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna for frequency 30MHz~1000MHz, and the Horn antenna is used as receiving antenna for frequency above 1GHz. Both horizontal and vertical polarization of the antenna are set on test.

This test was performed with EUT in X, Y, Z position, and the worse case was found when EUT in X position as test photo indicated.

The bandwidth of the EMI test receiver (R&S ESR7) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 3MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

The frequency range from 30MHz to 10th harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25GHz, So the radiated emissions from 18GHz to 25GHz were not record.

4.6. Radiated Emission Test Results

PASS.


All the emissions from 30MHz to 25 GHz were comply with 15.209 limits.

Note 1: For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

Note 2: The emissions (9kHz~30MHz) not reported for there is no emission be found.


Duty cycle

11 b




Note: The duty cycle is 92%.

11 g




Note: The duty cycle is 68%.

11n HT20




Note: The duty cycle is 66%.

11n HT40




Note: The duty cycle is 49%.

11ax HE20



Note: The duty cycle is 60%.

11ax HE 40




Note: The duty cycle is 43%.

Frequency: 30MHz~1GHz

Data: 1

File: C:\Users\hpl\Desktop\A1Z2510081.EM6 (4)


Date: 2025-12-01



Site no. : 3m Chamber Data no. : 1
 Dis. / Ant. : 3m 2025 VULB 9168-01856 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 C (3M)
 Env. / Ins. : Temp:23.5°C Humi:44% Engineer : Hongjie
 EUT :
 Power rating :
 Test Mode : WIFI 2.4G TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	165.800	18.02	0.80	15.21	34.03	43.50	9.47	QP
2	249.220	16.90	0.99	18.36	36.25	46.00	9.75	QP
3	332.640	19.50	1.14	17.24	37.88	46.00	8.12	QP
4	415.090	21.20	1.28	16.60	39.08	46.00	6.92	QP
5	498.510	23.00	1.40	12.66	37.06	46.00	8.94	QP
6	582.900	24.52	1.54	7.86	33.92	46.00	12.08	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.



Site no. : 3m Chamber Data no. : 2
 Dis. / Ant. : 3m 2025 VULB 9168-01856 Ant. pol. : VERTICAL
 Limit : FCC PART 15 C (3M)
 Env. / Ins. : Temp:23.5°C Humi:44% Engineer : Hongjie
 EUT :
 Power rating :
 Test Mode : WIFI 2.4G TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	34.850	17.16	0.41	15.58	33.15	40.00	6.85	QP
2	120.210	15.24	0.69	16.13	32.06	43.50	11.44	QP
3	163.860	18.30	0.79	12.75	31.84	43.50	11.66	QP
4	417.030	21.28	1.28	14.98	37.54	46.00	8.46	QP
5	500.450	23.01	1.40	10.89	35.30	46.00	10.70	QP
6	583.870	24.55	1.54	11.25	37.34	46.00	8.66	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.

Frequency: 1GHz~18GHz

Data: 49

File: F:\2025 Report\2025.12.8\WIFI2.4G.EM6 (156)


Date: 2025-12-05




Site no. : 3m Chamber Data no. : 49
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11b 2412MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2412.00	27.92	0.64	32.93	113.71	109.34	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 50
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11b 2412MHz TX Mode		



Site no. : 3m Chamber Data no. : 51
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11b 2412MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4824.00	32.59	0.98	31.19	35.19	37.57	54.00	16.43	Average
2	4824.00	32.59	0.98	31.19	48.18	50.56	74.00	23.44	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 52
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11b 2412MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2412.00	27.92	0.64	32.93	105.12	100.75	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 53
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11b 2412MHz TX Mode		



Site no. : 3m Chamber Data no. : 54
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11b 2412MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4824.00	32.59	0.98	31.19	35.47	37.85	54.00	16.15	Average
2	4824.00	32.59	0.98	31.19	48.46	50.84	74.00	23.16	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 55
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11b 2437MHz TX Mode		


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2437.00	27.97	0.64	32.91	115.34	111.04	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
- Amp factor(Peak)

2. The emission levels that are 20dB below the official
limit are not reported




Site no.	: 3m Chamber	Data no.	: 56
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11b 2437MHz TX Mode		



Site no. : 3m Chamber Data no. : 57
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11b 2437MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4874.00	32.90	0.99	31.16	36.84	39.57	54.00	14.43	Average
2	4874.00	32.90	0.99	31.16	49.85	52.58	74.00	21.42	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 58
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11b 2437MHz TX Mode		

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2437.00	27.97	0.64	32.91	108.77	104.47	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
- Amp factor(Peak)


2. The emission levels that are 20dB below the official
limit are not reported




Site no. : 3m Chamber Data no. : 59
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11b 2437MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4874.00	32.90	0.99	31.16	35.02	37.75	54.00	16.25	Average
2	4874.00	32.90	0.99	31.16	48.03	50.76	74.00	23.24	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 60
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11b 2437MHz TX Mode		




Site no. : 3m Chamber Data no. : 61
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11b 2462MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2462.00	28.10	0.65	32.88	115.80	111.67	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 62
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11b 2462MHz TX Mode		



Site no. : 3m Chamber Data no. : 63
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11b 2462MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4924.00	32.90	0.99	31.14	34.51	37.26	54.00	16.74	Average
2	4924.00	32.90	0.99	31.14	47.50	50.25	74.00	23.75	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 64
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11b 2462MHz TX Mode		


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2462.00	28.10	0.65	32.88	108.98	104.85	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
- Amp factor(Peak)

2. The emission levels that are 20dB below the official
limit are not reported




Site no.	: 3m Chamber	Data no.	: 65
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11b 2462MHz TX Mode		



Site no. : 3m Chamber Data no. : 66
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11b 2462MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4924.00	32.90	0.99	31.14	36.31	39.06	54.00	14.94	Average
2	4924.00	32.90	0.99	31.14	49.30	52.05	74.00	21.95	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 67
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11g 2412MHz TX Mode		

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin Limits (dB)	Remark
1	2412.00	27.92	0.64	32.93	111.34	106.97	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp factor(Peak)
 2. The emission levels that are 20dB below the official limit are not reported




Site no.	: 3m Chamber	Data no.	: 68
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11g 2412MHz TX Mode		



Site no. : 3m Chamber Data no. : 69
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11g 2412MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4824.00	32.59	0.98	31.19	36.63	39.01	54.00	14.99	Average
2	4824.00	32.59	0.98	31.19	49.62	52.00	74.00	22.00	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 70
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11g 2412MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2412.00	27.92	0.64	32.93	105.79	101.42	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 71
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11g 2412MHz TX Mode		



Site no. : 3m Chamber Data no. : 72
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11g 2412MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4824.00	32.59	0.98	31.19	37.21	39.59	54.00	14.41	Average
2	4824.00	32.59	0.98	31.19	49.20	51.58	74.00	22.42	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 73
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11g 2437MHz TX Mode		


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2437.00	27.97	0.64	32.91	112.64	108.34	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
- Amp factor(Peak)

2. The emission levels that are 20dB below the official
limit are not reported




Site no.	: 3m Chamber	Data no.	: 74
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11g 2437MHz TX Mode		



Site no. : 3m Chamber Data no. : 75
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11g 2437MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4874.00	32.90	0.99	31.16	35.46	38.19	54.00	15.81	Average
2	4874.00	32.90	0.99	31.16	47.47	50.20	74.00	23.80	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 76
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11g 2437MHz TX Mode		


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2437.00	27.97	0.64	32.91	113.71	109.41	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
- Amp factor(Peak)

2. The emission levels that are 20dB below the official
limit are not reported




Site no.	: 3m Chamber	Data no.	: 77
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11g 2437MHz TX Mode		



Site no. : 3m Chamber Data no. : 78
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11g 2437MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4874.00	32.90	0.99	31.16	35.91	38.64	54.00	15.36	Average
2	4874.00	32.90	0.99	31.16	48.92	51.65	74.00	22.35	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 79
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11g 2462MHz TX Mode		


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2462.00	28.10	0.65	32.88	115.60	111.47	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
- Amp factor(Peak)

2. The emission levels that are 20dB below the official
limit are not reported




Site no.	: 3m Chamber	Data no.	: 80
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11g 2462MHz TX Mode		



Site no. : 3m Chamber Data no. : 81
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11g 2462MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4924.00	32.90	0.99	31.14	34.44	37.19	54.00	16.81	Average
2	4924.00	32.90	0.99	31.14	47.43	50.18	74.00	23.82	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 82
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11g 2462MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin Limits (dB)	Remark
1	2462.00	28.10	0.65	32.88	112.39	108.26	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 83
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11g 2462MHz TX Mode		



Site no. : 3m Chamber Data no. : 84
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11g 2462MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4924.00	32.90	0.99	31.14	35.24	37.99	54.00	16.01	Average
2	4924.00	32.90	0.99	31.14	48.23	50.98	74.00	23.02	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 85
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n20 2412MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2412.00	27.92	0.64	32.93	110.09	105.72	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 86
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11n20 2412MHz TX Mode		



Site no. : 3m Chamber Data no. : 87
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n20 2412MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4824.00	32.59	0.98	31.19	37.18	39.56	54.00	14.44	Average
2	4824.00	32.59	0.98	31.19	49.17	51.55	74.00	22.45	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 88
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n20 2412MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2412.00	27.92	0.64	32.93	109.66	105.29	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 89
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11n20 2412MHz TX Mode		



Site no. : 3m Chamber Data no. : 90
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n20 2412MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4824.00	32.59	0.98	31.19	34.97	37.35	54.00	16.65	Average
2	4824.00	32.59	0.98	31.19	47.96	50.34	74.00	23.66	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 91
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11n20 2437MHz TX Mode		


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2437.00	27.97	0.64	32.91	113.64	109.34	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
- Amp factor(Peak)

2. The emission levels that are 20dB below the official
limit are not reported




Site no.	: 3m Chamber	Data no.	: 92
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11n20 2437MHz TX Mode		



Site no. : 3m Chamber Data no. : 93
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n20 2437MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4874.00	32.90	0.99	31.16	35.08	37.81	54.00	16.19	Average
2	4874.00	32.90	0.99	31.16	48.09	50.82	74.00	23.18	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 94
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11n20 2437MHz TX Mode		


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2437.00	27.97	0.64	32.91	111.83	107.53	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp factor(Peak)

2. The emission levels that are 20dB below the official limit are not reported




Site no.	: 3m Chamber	Data no.	: 95
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11n20 2437MHz TX Mode		



Site no. : 3m Chamber Data no. : 96
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n20 2437MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4874.00	32.90	0.99	31.16	34.46	37.19	54.00	16.81	Average
2	4874.00	32.90	0.99	31.16	47.47	50.20	74.00	23.80	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 97
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n20 2462MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2462.00	28.10	0.65	32.88	105.55	101.42	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 98
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11n20 2462MHz TX Mode		



Site no. : 3m Chamber Data no. : 99
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n20 2462MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4924.00	32.90	0.99	31.14	36.36	39.11	54.00	14.89	Average
2	4924.00	32.90	0.99	31.14	48.35	51.10	74.00	22.90	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 100
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n20 2462MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2462.00	28.10	0.65	32.88	111.99	107.86	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 101
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11n20 2462MHz TX Mode		



Site no. : 3m Chamber Data no. : 102
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n20 2462MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4924.00	32.90	0.99	31.14	35.65	38.40	54.00	15.60	Average
2	4924.00	32.90	0.99	31.14	48.64	51.39	74.00	22.61	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 103
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n40 2422MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2422.00	27.94	0.64	32.92	108.05	103.71	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 104
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11n40 2422MHz TX Mode		



Site no. : 3m Chamber Data no. : 105
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n40 2422MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4844.00	32.75	0.98	31.18	35.44	37.99	54.00	16.01	Average
2	4844.00	32.75	0.98	31.18	48.43	50.98	74.00	23.02	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 106
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n40 2422MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2422.00	27.94	0.64	32.92	107.10	102.76	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 107
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11n40 2422MHz TX Mode		



Site no. : 3m Chamber Data no. : 108
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n40 2422MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4844.00	32.75	0.98	31.18	33.64	36.19	54.00	17.81	Average
2	4844.00	32.75	0.98	31.18	46.83	49.38	74.00	24.62	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 109
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11n40 2437MHz TX Mode		


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin Limits (dB)	Remark
1	2437.00	27.97	0.64	32.91	110.02	105.72	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp factor(Peak)

2. The emission levels that are 20dB below the official limit are not reported




Site no.	: 3m Chamber	Data no.	: 110
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11n40 2437MHz TX Mode		



Site no. : 3m Chamber Data no. : 111
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n40 2437MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4874.00	32.90	0.99	31.16	35.93	38.66	54.00	15.34	Average
2	4874.00	32.90	0.99	31.16	47.94	50.67	74.00	23.33	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 112
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n40 2437MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2437.00	27.97	0.64	32.91	105.32	101.02	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 113
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11n40 2437MHz TX Mode		



Site no. : 3m Chamber Data no. : 114
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n40 2437MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4874.00	32.90	0.99	31.16	36.32	39.05	54.00	14.95	Average
2	4874.00	32.90	0.99	31.16	49.33	52.06	74.00	21.94	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 115
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n40 2452MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2452.00	28.02	0.65	32.89	104.20	99.98	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 116
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11n40 2452MHz TX Mode		



Site no. : 3m Chamber Data no. : 117
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n40 2452MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4904.00	32.98	0.99	31.15	36.48	39.30	54.00	14.70	Average
2	4904.00	32.98	0.99	31.15	49.47	52.29	74.00	21.71	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 118
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n40 2452MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2452.00	28.02	0.65	32.89	107.12	102.90	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 119
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11n40 2452MHz TX Mode		



Site no. : 3m Chamber Data no. : 120
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11n40 2452MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4904.00	32.98	0.99	31.15	35.02	37.84	54.00	16.16	Average
2	4904.00	32.98	0.99	31.15	47.40	50.22	74.00	23.78	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 121
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax20 2412MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2412.00	27.92	0.64	32.93	106.23	101.86	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 122
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11ax20 2412MHz TX Mode		



Site no. : 3m Chamber Data no. : 123
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax20 2412MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4824.00	32.59	0.98	31.19	34.72	37.10	54.00	16.90	Average
2	4824.00	32.59	0.98	31.19	47.71	50.09	74.00	23.91	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 124
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax20 2412MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2412.00	27.92	0.64	32.93	108.18	103.81	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 125
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11ax20 2412MHz TX Mode		



Site no. : 3m Chamber Data no. : 126
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax20 2412MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4824.00	32.59	0.98	31.19	36.05	38.43	54.00	15.57	Average
2	4824.00	32.59	0.98	31.19	49.04	51.42	74.00	22.58	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 127
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax20 2437MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2437.00	27.97	0.64	32.91	115.71	111.41	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 128
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11ax20 2437MHz TX Mode		



Site no. : 3m Chamber Data no. : 129
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax20 2437MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4874.00	32.90	0.99	31.16	36.50	39.23	54.00	14.77	Average
2	4874.00	32.90	0.99	31.16	48.51	51.24	74.00	22.76	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 130
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11ax20 2437MHz TX Mode		


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2437.00	27.97	0.64	32.91	110.37	106.07	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp factor(Peak)

2. The emission levels that are 20dB below the official limit are not reported




Site no.	: 3m Chamber	Data no.	: 131
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11ax20 2437MHz TX Mode		



Site no. : 3m Chamber Data no. : 132
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax20 2437MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4874.00	32.90	0.99	31.16	38.33	41.06	54.00	12.94	Average
2	4874.00	32.90	0.99	31.16	50.34	53.07	74.00	20.93	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 133
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax20 2462MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2462.00	28.10	0.65	32.88	106.89	102.76	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 134
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11ax20 2462MHz TX Mode		



Site no. : 3m Chamber Data no. : 135
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax20 2462MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4924.00	32.90	0.99	31.14	36.24	38.99	54.00	15.01	Average
2	4924.00	32.90	0.99	31.14	48.23	50.98	74.00	23.02	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported





Site no.	: 3m Chamber	Data no.	: 136
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11ax20 2462MHz TX Mode		

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2462.00	28.10	0.65	32.88	110.63	106.50	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
- Amp factor(Peak)

2. The emission levels that are 20dB below the official
limit are not reported






Site no. : 3m Chamber Data no. : 138
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax20 2462MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4924.00	32.90	0.99	31.14	34.39	37.14	54.00	16.86	Average
2	4924.00	32.90	0.99	31.14	47.38	50.13	74.00	23.87	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 139
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax40 2422MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin Limits (dB)	Remark
1	2422.00	27.94	0.64	32.92	108.39	104.05	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 140
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11ax40 2422MHz TX Mode		



Site no. : 3m Chamber Data no. : 141
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax40 2422MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4844.00	32.75	0.98	31.18	35.15	37.70	54.00	16.30	Average
2	4844.00	32.75	0.98	31.18	48.14	50.69	74.00	23.31	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 142
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax40 2422MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2422.00	27.94	0.64	32.92	105.25	100.91	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported






Site no. : 3m Chamber Data no. : 144
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax40 2422MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4844.00	32.75	0.98	31.18	36.16	38.71	54.00	15.29	Average
2	4844.00	32.75	0.98	31.18	49.15	51.70	74.00	22.30	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 145
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax40 2437MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2437.00	27.97	0.64	32.91	111.42	107.12	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 146
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11ax40 2437MHz TX Mode		



Site no. : 3m Chamber Data no. : 147
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax40 2437MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4874.00	32.90	0.99	31.16	34.08	36.81	54.00	17.19	Average
2	4874.00	32.90	0.99	31.16	47.09	49.82	74.00	24.18	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no. : 3m Chamber Data no. : 148
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax40 2437MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2437.00	27.97	0.64	32.91	106.66	102.36	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 149
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11ax40 2437MHz TX Mode		



Site no. : 3m Chamber Data no. : 150
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax40 2437MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4874.00	32.90	0.99	31.16	36.10	38.83	54.00	15.17	Average
2	4874.00	32.90	0.99	31.16	49.11	51.84	74.00	22.16	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 151
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11ax40 2452MHz TX Mode		


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin Limits (dB)	Remark
1	2452.00	28.02	0.65	32.89	103.58	99.36	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
-Amp factor(Peak)

2. The emission levels that are 20dB below the official
limit are not reported




Site no.	: 3m Chamber	Data no.	: 152
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11ax40 2452MHz TX Mode		



Site no. : 3m Chamber Data no. : 153
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax40 2452MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4924.00	32.90	0.99	31.14	35.74	38.49	54.00	15.51	Average
2	4924.00	32.90	0.99	31.14	48.73	51.48	74.00	22.52	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported




Site no.	: 3m Chamber	Data no.	: 154
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11ax40 2452MHz TX Mode		


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	2452.00	28.02	0.65	32.89	107.77	103.55	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
- Amp factor(Peak)

2. The emission levels that are 20dB below the official
limit are not reported



Site no.	: 3m Chamber	Data no.	: 155
Dis. / Ant.	: 3m 2025-3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: Epoch
Env. / Ins.	: 23.2°C/52.6%		
Test Mode	: WIFI2.4G 11ax40 2452MHz TX Mode		



Site no. : 3m Chamber Data no. : 156
 Dis. / Ant. : 3m 2025-3115-4580 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK Engineer : Epoch
 Env. / Ins. : 23.2°C/52.6%
 Test Mode : WIFI2.4G 11ax40 2452MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin Limits (dB)	Remark
1	4904.00	32.98	0.99	31.15	38.50	41.32	54.00	12.68	Average
2	4904.00	32.98	0.99	31.15	50.49	53.31	74.00	20.69	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp factor(Peak)
 2. The emission levels that are 20dB below the official
 limit are not reported

5. CONDUCTED SPURIOUS EMISSIONS

5.1. Limit

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30dB instead of 20dB.

5.2. Test Procedure






The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz and measure all the emissions with peak detector.

5.3. Test result




PASS (The testing data was attached in the next pages.)

EUT: Car Camcorder		
M/N: P70		
Test date: 2025-11-28	Pressure: 102.1±1.0 kpa	Humidity: 52.5±3.0%
Tested by: Lili	Test site: RF site	Temperature: 23.2±0.6°C





Test Mode: IEEE 802.11b
Test CH1: 2412MHz









Test CH6: 2437MHz







Test CH11: 2462MHz








Test Mode: IEEE 802.11g
Test CH1: 2412MHz



Test CH6: 2437MHz



Test CH11: 2462MHz



Test Mode: IEEE 802.11n HT20
Test CH1: 2412MHz

