



Report No.: PTC22102605005E-FC02

# FCC TEST REPORT

## FCC ID: 2ACFQ-GO95632G

|                                                                                |   |                      |
|--------------------------------------------------------------------------------|---|----------------------|
| Product                                                                        | : | DashCam              |
| Model Name                                                                     | : | GO95632G             |
| Brand                                                                          | : | Adesso/myGEKOgear    |
| Report No.                                                                     | : | PTC22102605005E-FC02 |
| <b>Prepared for</b>                                                            |   |                      |
| ADESSO INC.                                                                    |   |                      |
| 20659 Valley BLVD. Walnut, CA 91789, U.S.A.                                    |   |                      |
| <b>Prepared by</b>                                                             |   |                      |
| Precise Testing & Certification Co., Ltd.                                      |   |                      |
| Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China. |   |                      |



Report No.: PTC22102605005E-FC02

## TEST RESULT CERTIFICATION

Applicant's name : ADESSO INC.

Address : 20659 Valley BLVD. Walnut, CA 91789, U.S.A.

Manufacture's name : ADESSO ELECTRONICS INC.

Address : No.5, ChengDa East St., Xiangang Community, Changan, DongGuan, China

Product name : DashCam

Model name : GO95632G

Test procedure : FCC CFR47 Part 1.1307(b)(1)

Test Date : Dec. 07, 2022 to Dec. 23, 2022

Date of Issue : Dec. 30, 2022

Test Result : PASS

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink that reads "Simon Pu".

Simon Pu / Engineer

Technical Manager:

A handwritten signature in black ink that reads "Ronnie Liu".

Ronnie Liu / Manager



## Contents

|                                       | <b>Page</b> |
|---------------------------------------|-------------|
| <b>2 TEST SUMMARY .....</b>           | <b>4</b>    |
| <b>3 GENERAL INFORMATION .....</b>    | <b>5</b>    |
| 3.1 GENERAL DESCRIPTION OF E.U.T..... | 5           |
| <b>4 RF EXPOSURE .....</b>            | <b>6</b>    |
| 4.1 REQUIREMENTS.....                 | 6           |
| 4.2 THE PROCEDURES / LIMIT .....      | 6           |
| 4.3 MPE CALCULATION METHOD .....      | 7           |
| 4.4 TEST RESULT .....                 | 7           |



Report No.: PTC22102605005E-FC02

## 2 Test Summary

| Test Items                                                        | Test Requirement | Result |
|-------------------------------------------------------------------|------------------|--------|
| Maximum Permissible Exposure<br>(Exposure of Humans to RF Fields) | 15.247 (i)       | PASS   |
| Remark:                                                           |                  |        |
| N/A: Not Applicable                                               |                  |        |



### 3 General Information

#### 3.1 General Description of E.U.T.

|                      |   |                                                                                                                |
|----------------------|---|----------------------------------------------------------------------------------------------------------------|
| Product Name         | : | DashCam                                                                                                        |
| Model Name           | : | GO95632G                                                                                                       |
| Series model         | : | GO1180G, GO1288G, GO1328G, GO53016G, GO93016G, GO95016G, GO96016G, GO53532G, GO95132G, GOSP32G, GOMS32G, SBC01 |
| Specification        | : | 802.11b/g/n HT20/HT40                                                                                          |
| Operation Frequency  | : | 2412-2462MHz for 802.11b/g/ n(HT20/HT40)                                                                       |
| Number of Channel    | : | 11 channels for 802.11b/g/ n(HT20/HT40)                                                                        |
| Type of Modulation   | : | DSSS with DBPSK/DQPSK/CCK for 802.11b;<br>OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;                       |
| Antenna installation | : | Integral antenna                                                                                               |
| Antenna Gain         | : | 3.14 dBi                                                                                                       |
| Power supply         | : | Input: 5V $\pm$ 2.5A                                                                                           |
| Hardware Version     | : | N/A                                                                                                            |
| Software Version     | : | N/A                                                                                                            |

Model difference:

GO95632G, GO1180G, GO1288G, GO1328G, GO53016G, GO93016G, GO95016G, GO96016G, GO53532G, GO95132G, GOSP32G, GOMS32G, SBC01.  
Product appearance color is different, the test model is GO95632G.



## 4 RF Exposure

Test Requirement : 15.247 (i)

Evaluation Method : FCC Part 2.1091

### 4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

### 4.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

| Frequency Range | Electric Field | Magnetic Field | Power Density (S) | Averaging Time |
|-----------------|----------------|----------------|-------------------|----------------|
| 0.3-3.0         | 614            | 1.63           | (100)*            | 6              |
| 3.0-30          | 1842 / f       | 4.89 / f       | (900 / f)*        | 6              |
| 30-300          | 61.4           | 0.163          | 1.0               | 6              |
| 300-1500        |                |                | F/300             | 6              |
| 1500-100,000    |                |                | 5                 | 6              |

(B) Limits for General Population / Uncontrolled Exposure

| Frequency Range | Electric Field | Magnetic Field | Power Density (S) | Averaging Time |
|-----------------|----------------|----------------|-------------------|----------------|
| 0.3-1.34        | 614            | 1.63           | (100)*            | 30             |
| 1.34-30         | 824/f          | 2.19/f         | (180/f)*          | 30             |
| 30-300          | 27.5           | 0.073          | 0.2               | 30             |
| 300-1500        |                |                | F/1500            | 30             |
| 1500-100,000    |                |                | 1.0               | 30             |

Note: f = frequency in MHz ; \*Plane-wave equivalent power density



### 4.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

### 4.4 Test Result

| Item | Antenna Gain (numeric) | Max. Peak Output Power (dBm) | Tune up tolerance (dBm) | Max Tune Up Power (mW) | Power Density (mW/cm <sup>2</sup> ) | Limit of Power Density (mW/cm <sup>2</sup> ) | Result |
|------|------------------------|------------------------------|-------------------------|------------------------|-------------------------------------|----------------------------------------------|--------|
| 2462 | 2.06                   | 13.15                        | 13.15 ± 1               | 26.001596              | 0.010659                            | 1                                            | Pass   |

\*\*\*\*\*THE END REPORT\*\*\*\*\*