



FCC TEST REPORT

FCC ID: 2ACGT-C1

Product	:	Digital Calendar
Model Name	:	C1, C2, C3, C5, C6, C7, C8, C9, C10, S1, S2, S3, S5, S6, S7, S8, S9, S10
Brand	:	TECLAST
Report No.	:	PTC26050616701E-FC01
Prepared for		
Guangzhou Shangke Information Technology Co., Ltd.		
Room 1205-1212, R&F To-Win Building, No.30 Huaxia Road, Tianhe District, Guangzhou, Guangdong, China		
Prepared by		
Precise Testing & Certification Co., Ltd		
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China		



Report No.: PTC26050616701E-FC01

1 TEST RESULT CERTIFICATION

Applicant's name : Guangzhou Shangke Information Technology Co., Ltd.

Address : Room 1205-1212, R&F To-Win Building, No.30 Huaxia Road, Tianhe District, Guangzhou, Guangdong, China

Manufacture's name : Guangzhou Shangke Information Technology Co., Ltd.

Address : Room 1205-1212, R&F To-Win Building, No.30 Huaxia Road, Tianhe District, Guangzhou, Guangdong, China

Product name : Digital Calendar

Model name : C1, C2, C3, C5, C6, C7, C8, C9, C10, S1, S2, S3, S5, S6, S7, S8, S9, S10

Standards : FCC CFR47 Part 15 Section 15.247

Test procedure : ANSI C63.10-2020

Test Date : May 22, 2026 to June 19, 2026

Date of Issue : June 23, 2026

Test Result : Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink, appearing to read 'Jack Zhou'.

Jack Zhou / Engineer

Technical Manager:

A handwritten signature in black ink, appearing to read 'Simon Pu'.

Simon Pu / Manager



Contents

	Page
1 TEST RESULT CERTIFICATION	2
2 TEST SUMMARY	5
3 GENERAL INFORMATION	6
3.1 GENERAL DESCRIPTION OF E.U.T.	6
3.2 CHANNEL LIST	7
3.3 TEST SITE	7
4 EQUIPMENT DURING TEST	8
4.1 EQUIPMENTS LIST	8
4.2 MEASUREMENT UNCERTAINTY	10
4.3 DESCRIPTION OF SUPPORT UNITS	11
5 CONDUCTED EMISSION	12
5.1 E.U.T. OPERATION	12
5.2 EUT SETUP	12
5.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	13
5.4 MEASUREMENT PROCEDURE	13
5.5 CONDUCTED EMISSION LIMIT	13
5.6 MEASUREMENT DESCRIPTION	13
5.7 CONDUCTED EMISSION TEST RESULT	13
6 RADIATED SPURIOUS EMISSIONS	16
6.1 EUT OPERATION	16
6.2 TEST SETUP	17
6.3 SPECTRUM ANALYZER SETUP	18
6.4 TEST PROCEDURE	19
6.5 SUMMARY OF TEST RESULTS	20
7 CONDUCTED SPURIOUS EMISSION	27
7.1 TEST PROCEDURE	27
7.2 TEST SETUP	27
7.3 TEST RESULT	27
8 BAND EDGE MEASUREMENT	56



8.1 TEST PROCEDURE	56
8.2 TEST SETUP	56
8.3 TEST RESULT	56
9 6DB BANDWIDTH MEASUREMENT	63
9.1 TEST PROCEDURE	63
9.2 TEST SETUP	63
9.3 TEST RESULT	63
10 MAXIMUM CONDUCTED OUTPUT POWER	73
10.1 TEST PROCEDURE	73
10.2 TEST SETUP	73
10.3 TEST RESULT	73
11 POWER SPECTRAL DENSITY	74
11.1 TEST PROCEDURE	74
11.2 TEST SETUP	74
11.3 TEST RESULT	74
12 ANTENNA APPLICATION	84
12.1 ANTENNA REQUIREMENT	84
12.2 RESULT	84
13 TEST SETUP	85
14 EUT PHOTOS	87



2 Test Summary

Test Items	Test Requirement	Result
Conduct Emission	15.207	PASS
Radiated Spurious Emissions	15.205(a) 15.209 15.247(d)	PASS
Conducted Spurious Emission	15.247(d)	PASS
Band edge	15.247(d) 15.205(a)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Maximum conducted Output Power	15.247(b)(3)	PASS
Power Spectral Density	15.247(e)	PASS
Antenna Requirement	15.203	PASS
Remark: N/A: Not Applicable		



3 General Information

3.1 General Description of E.U.T.

Product Name	:	Digital Calendar
Model Name	:	C1, C2, C3, C5, C6, C7, C8, C9, C10, S1, S2, S3, S5, S6, S7, S8, S9, S10
Test Model	:	C1
Specification	:	802.11b/g/n HT20/HT40/ax20/ax40
Operating frequency	:	2412-2462MHz for 802.11b/g/ n(HT20)/ax20 2422-2452MHz for 802.11 n(HT40)/ax40
Numbers of Channel	:	11 channels for 802.11b/g/ n(HT20)/ax20 7 channels for 802.11n(HT40)/ax40
Antenna Type	:	FPC Antenna
Antenna Gain	:	1.89dbi
Type of Modulation	:	DSSS, OFDM, OFDMA
Power supply	:	12V ---2A from adapter
Hardware Version	:	BND-F915 V2.0
Software Version	:	N/A
Test sample No.	:	PTC26050616701E-1/2, PTC26050616701E-2/2
Model difference	:	All models are identical to each other except for the model name and appearance.



3.2 Channel List

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20)/ax20: MCS0;) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for 802.11 b/g/n (HT20/HT40)/ax20/ax40

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

The maximum duty cycle : see page 73 for details.

3.3 Test Site

Precise Testing & Certification Co., Ltd

Address: Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China

FCC Registration Number: 790290

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A

FCC Designation Number: CN1219



4 Equipment During Test

4.1 Equipments List

RF Conducted Test

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Last Calibration	Calibration Interval
MXG Signal Analyzer	Agilent	N9020A	SER MY5111038	10Hz-26.5GHz	Aug.15, 2025	1 Year
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	Aug.15, 2025	1 Year
Power Meter	Anritsu	ML2495A	0949003	300MHz-40GHz	Aug.15, 2025	1 Year
Power Sensor	Anritsu	MA2411B	0917017	300MHz-40GHz	Aug.15, 2025	1 Year
Test S/W	Tonscend	JS1120-3	/	/	/	/

Radiated Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Last Calibration	Calibration Interval
EMI Test Receiver	Rohde&Schwarz	ESPI7	101671	9KHz-7GHz	Aug.15, 2025	1 Year
Loop Antenna	Schwarzbeck	FMZB 1519	192	9 KHz -30MHz	Aug.15, 2025	1 Year
Bilog Antenna	SCHWARZBECK	VULB9160	9160-3355	25MHz-2GHz	Aug.15, 2025	1 Year
Preamplifier (low frequency)	SCHWARZBECK	BBV 9475	9745-0013	1MHz-1GHz	Aug.15, 2025	1 Year
Cable	IMRO	AK-9515E(9m)	Cable-L	9KHz-3GHz	Aug.15, 2025	1 Year
Spectrum Analyzer	Rohde&Schwarz	FSV40	6625-01-588-5515	9KHz-40GHz	Aug.15, 2025	1 Year
Horn Antenna	SCHWARZBECK	9120D	9120D-1246	1GHz-18GHz	Aug.15, 2025	1 Year
Power Amplifier	ZHINAN	ZN3380C	15002	1GHz-26.5GHz	Aug.15, 2025	1 Year



Report No.: PTC26050616701E-FC01

Horn Antenna	SCHWARZBEC K	BBHA 9170	9170-1066	15GHz- 40GHz	Jul. 19, 2025	1 Year
Amplifier	SCHWARZBEC K	BBV 9721	9721-205	18GHz- 40GHz	Jul. 19, 2025	1 Year
Cable	H+S	CBL-26	N/A	1GHz- 26.5GHz	Aug.15, 2025	1 Year
RF Cable	R&S	R204	R21X	1GHz-40GHz	Aug.15, 2025	1 Year
Test S/W	Tonscend	TS+	/	/	/	/

Conducted Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Date	Calibration Interval
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	9KHz-3GHz	Aug.15, 2025	1 Year
Artificial Mains Network	Rohde&Schwarz	ENV216	102453	9KHz- 300MHz	Aug.15, 2025	1 Year
Artificial Mains Network	Rohde&Schwarz	ENV216	101342	9KHz- 300MHz	Aug.15, 2025	1 Year
Limiter	R&S	ESH3-Z2	0357.8810.54- 102808-NB	0Hz-30MHz	Aug.15, 2025	1 Year
RF Switch	DIAMOND ANTENNA	CX-210	/	9kHz-6GHz	Mar. 21,2026	1 Year
Test S/W	Tonscend	JS32-CE	/	/	/	/



4.2 Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	$\pm 1.0\text{dB}$
Power Spectral Density, conducted	$\pm 2.2\text{dB}$
Radio Frequency	$\pm 1 \times 10^{-6}$
Bandwidth	$\pm 1.5 \times 10^{-6}$
Time	$\pm 2\%$
Duty Cycle	$\pm 2\%$
Temperature	$\pm 1^{\circ}\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 3\%$
Conducted Emissions (150kHz~30MHz)	$\pm 3.64\text{dB}$
Radiated Emission(9kHz~30MHz)	$\pm 3.15\text{dB}$
Radiated Emission(30MHz~1GHz)	$\pm 5.03\text{dB}$
Radiated Emission(1GHz~25GHz)	$\pm 4.74\text{dB}$



Report No.: PTC26050616701E-FC01

4.3Description of Support Units

Equipment	Model No.	Series No.
/	/	/

5 Conducted Emission

Test Requirement:	: FCC CFR 47 Part 15 Section 15.207
Test Method	: ANSI C63.10-2020
Test Result	: PASS
Frequency Range	: 150kHz to 30MHz
Class/Severity	: Class B


5.1E.U.T. Operation

Operating Environment :


Temperature	: 25°C
Humidity	: 60 % RH
Atmospheric Pressure	: 101.1 kPa

5.2EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2020.



5.3 Test SET-UP (Block Diagram of Configuration)



5.4 Measurement Procedure

1. The EUT was placed on a table, which is 0.1m above ground plane..
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

5.5 Conducted Emission Limit

Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.6 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

5.7 Conducted Emission Test Result


Pass.

During the test, the 120Vac/60Hz and 240Vac/60Hz power supplies were scanned in advance, and it was found that (120Vac/60Hz, TX 802.11b Low Channel) was a poor mode, and the report only reflected the poor mode.

Please refer to the following pages.



Line- AC 120V/60Hz




Final test data

NO.	Freq. [MHz]	Factor [dB]	QP Value	QP Limit	QP Margin	AV Value	AV Limit	AV Margin	Verdict
1	0.164	19.83	42.98	65.28	22.30	22.33	55.28	32.95	PASS
2	0.510	19.90	40.57	56.00	15.43	25.50	46.00	20.50	PASS
3	0.839	19.83	34.73	56.00	21.27	24.61	46.00	21.39	PASS
4	2.517	19.85	32.24	56.00	23.76	20.32	46.00	25.68	PASS
5	4.200	19.86	30.91	56.00	25.09	19.59	46.00	26.41	PASS
6	18.380	20.00	34.18	60.00	25.82	18.99	50.00	31.01	PASS



Neutral-AC 120V/60Hz



Final test data

NO.	Freq. [MHz]	Factor [dB]	QP Value	QP Limit	QP Margin	AV Value	AV Limit	AV Margin	Verdict
1	0.155	19.86	41.96	65.75	23.79	26.81	55.75	28.94	PASS
2	0.515	19.87	38.58	56.00	17.42	27.89	46.00	18.11	PASS
3	0.839	19.80	37.26	56.00	18.74	27.52	46.00	18.48	PASS
4	2.522	19.86	34.55	56.00	21.45	22.64	46.00	23.36	PASS
5	10.725	19.88	35.93	60.00	24.07	23.60	50.00	26.40	PASS
6	17.462	19.96	34.90	60.00	25.10	20.77	50.00	29.23	PASS

Note: QP Margin[dB]= QP Limit[dBμV]- QP Value[dBμV], AV Margin[dB]= AV Limit[dBμV]- AV Value[dBμV].



6 Radiated Spurious Emissions

Test Requirement : FCC CFR47 Part 15 Section 15.209 & 15.247
 Test Method : ANSI C63.10-2020
 Test Result : PASS
 Measurement Distance : 3m
 Limit : See the follow table

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

6.1EUT Operation


Operating Environment :

Temperature: : 25 °C
 Humidity: : 60 % RH
 Atmospheric Pressure: : 101.3kPa
 Test Voltage : AC 120V 60Hz


6.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site


The test setup for emission measurement below 30MHz



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz



6.3 Spectrum Analyzer Setup

	Frequency	Detector	RBW	VBW	Remark
Receiver Setup	Below 30MHz	--	10kHz	10kHz	--
	30MHz ~ 1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value



6.4 Test Procedure

1. Below 1000MHz, The EUT was placed on a turn table which is 0.1m above ground plane, And above 1000MHz, The EUT's ANT is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.
8. The test above 1GHz must be use the fully anechoic room, and the test below 1GHz use the half anechoic room



6.5 Summary of Test Results

Test Frequency: 9KHz-30MHz

Note:

The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance} / \text{test distance})$ (dB);

Limit line = Specific limits (dBuV) + distance extrapolation factor.


Test Frequency: 30MHz ~ 1GHz

All the modulation modes were tested the data of the worst mode (TX 802.11b Low Channel) are recorded in the following pages and the others modulation methods do not exceed the limits.

Please refer to the following test plots:




Antenna Polarization: Horizontal



Final Test Data								
NO.	Freq. [MHz]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity	Result
1	45.52	21.66	40.00	18.34	200	360	Horizontal	PASS
2	53.96	16.20	40.00	23.80	100	306	Horizontal	PASS
3	145.34	33.70	43.50	9.80	200	115	Horizontal	PASS
4	246.23	36.63	46.00	9.37	100	104	Horizontal	PASS
5	443.26	37.94	46.00	8.06	100	78	Horizontal	PASS
6	806.56	26.70	46.00	19.30	100	6	Horizontal	PASS



Antenna Polarization: Vertical



Final Test Data								
NO.	Freq. [MHz]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity	Result
1	45.52	21.34	40.00	18.66	100	360	Vertical	PASS
2	55.32	14.79	40.00	25.21	100	355	Vertical	PASS
3	145.15	31.61	43.50	11.89	100	116	Vertical	PASS
4	246.43	36.87	46.00	9.13	100	116	Vertical	PASS
5	442.49	37.40	46.00	8.60	100	72	Vertical	PASS
6	806.95	26.88	46.00	19.12	100	360	Vertical	PASS

Remark: Emission Level = Reading + Cable Loss + ANT Factor - AMP Factor



Test Frequency: From 1GHz to 18GHz

Worst case 802.11b

Test Mode: 2412					Test channel: Lowest			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4824	45.94	32.35	4.12	28.44	53.97	74	-20.03	V
7236	42.44	36.08	6.3	27.74	57.08	74	-16.92	V
9648	35.01	38.25	7.91	24.65	56.52	74	-17.48	V
4824	39.88	32.35	4.12	28.44	47.91	74	-26.09	H
7236	35.60	36.08	6.3	27.74	50.24	74	-23.76	H
9648	31.86	38.25	7.91	24.65	53.37	74	-20.63	H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4824	30.14	32.35	4.12	28.44	38.17	54	-15.83	V
7236	25.16	36.08	6.3	27.74	39.80	54	-14.20	V
9648	18.93	38.25	7.91	24.65	40.44	54	-13.56	V
4824	32.63	32.35	4.12	28.44	40.66	54	-13.34	H
7236	25.55	36.08	6.3	27.74	40.19	54	-13.81	H
9648	21.49	38.25	7.91	24.65	43.00	54	-11.00	H



Worst case 802.11b

Test Mode: 2437					Test channel: Middle			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4874	43.79	32.35	4.12	28.44	51.82	74	-22.18	V
7311	37.99	36.08	6.3	27.74	52.63	74	-21.37	V
9748	35.27	38.25	7.91	24.65	56.78	74	-17.22	V
4874	41.87	32.35	4.12	28.44	49.90	74	-24.10	H
7311	36.00	36.08	6.3	27.74	50.64	74	-23.36	H
9748	37.25	38.25	7.91	24.65	58.76	74	-15.24	H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4874	31.20	32.35	4.12	28.44	39.23	54	-14.77	V
7311	25.71	36.08	6.3	27.74	40.35	54	-13.65	V
9748	20.04	38.25	7.91	24.65	41.55	54	-12.45	V
4874	32.32	32.35	4.12	28.44	40.35	54	-13.65	H
7311	22.10	36.08	6.3	27.74	36.74	54	-17.26	H
9748	19.61	38.25	7.91	24.65	41.12	54	-12.88	H



Worst case 802.11b

Test Mode: 2462					Test channel: High			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4924	45.46	32.41	4.14	28.42	53.59	74	-20.41	V
7386	38.98	36.15	6.36	27.68	53.81	74	-20.19	V
9848	33.80	38.35	7.97	24.33	55.79	74	-18.21	V
4924	41.67	32.41	4.14	28.42	49.80	74	-24.20	H
7386	36.65	36.15	6.36	27.68	51.48	74	-22.52	H
9848	34.45	38.35	7.97	24.33	56.44	74	-17.56	H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4924	33.34	32.41	4.14	28.42	41.47	54	-12.53	V
7386	24.24	36.15	6.36	27.68	39.07	54	-14.93	V
9848	22.00	38.35	7.97	24.33	43.99	54	-10.01	V
4924	29.10	32.41	4.14	28.42	37.23	54	-16.77	H
7386	25.54	36.15	6.36	27.68	40.37	54	-13.63	H
9848	23.25	38.35	7.97	24.33	45.24	54	-8.76	H

Note:

1. The testing has been conformed to $10 \times 2462 \text{ MHz} = 24620 \text{ MHz}$.
2. All other emissions more than 30dB below the limit.
3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Emission Level = Reading + Factor
Margin=Emission Level-Limit
4. X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.



Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz
 2.4G WiFi (802.11b/g/n) mode have been tested, and the worst result(802.11g) was report as below
 Test Mode: Worst case 802.11g Low Channel 2412MHz

Test Mode: 802.11g Low Channel 2412MHz									Test Value
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Polarity H/V	
2390	45.06	28.67	6.72	37.26	43.19	74	-30.81	H	Peak
2400	58.48	28.08	6.81	37.12	56.25	74	-17.75	H	
2390	47.87	28.67	6.72	37.26	46.00	74	-28.00	V	
2400	48.67	28.08	6.81	37.12	46.44	74	-27.56	V	
2390	37.15	28.67	6.72	37.26	35.28	54	-18.72	H	Average
2400	46.11	28.08	6.81	37.12	43.88	54	-10.12	H	
2390	38.38	28.67	6.72	37.26	36.51	54	-17.49	V	
2400	42.45	28.08	6.81	37.12	40.22	54	-13.78	V	

Test Mode: Worst case 802.11g High Channel 2462MHz

Test Mode: 802.11g High Channel 2462MHz									Test Value
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Polarity H/V	
2483.5	63.26	27.38	6.15	36.29	60.50	74	-13.50	H	Peak
2500	44.62	27.43	6.68	36.79	41.94	74	-32.06	H	
2483.5	56.11	27.38	6.15	36.29	53.35	74	-20.65	V	
2500	43.42	27.43	6.68	36.79	40.74	74	-33.26	V	
2483.5	39.66	27.38	6.15	36.29	36.90	54	-17.10	H	Average
2500	44.04	27.43	6.68	36.79	41.36	54	-12.64	H	
2483.5	41.98	27.38	6.15	36.29	39.22	54	-14.78	V	
2500	39.25	27.43	6.68	36.79	36.57	54	-17.43	V	

Test Frequency: From 18GHz to 25GHz

The measurements were more than 20dB below the limit and not reported.




7 Conducted Spurious Emission

Test Requirement : FCC CFR47 Part 15 Section 15.247
Test Method : ANSI C63.10-2020
Test Limit : Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold

7.2 Test Setup



7.3 Test Result


TestMode	Antenna	Frequency[MHz]	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
11B	Ant1	2412	0~Reference	4.66	4.66	---	PASS
11B	Ant1	2412	30~1000	4.66	-59	≤-25.34	PASS
11B	Ant1	2412	1000~26500	4.66	-42.67	≤-25.34	PASS
11B	Ant1	2437	0~Reference	5.37	5.37	---	PASS
11B	Ant1	2437	30~1000	5.37	-59.26	≤-24.63	PASS
11B	Ant1	2437	1000~26500	5.37	-38.28	≤-24.63	PASS
11B	Ant1	2462	0~Reference	3.97	3.97	---	PASS
11B	Ant1	2462	30~1000	3.97	-59.04	≤-26.03	PASS
11B	Ant1	2462	1000~26500	3.97	-38.31	≤-26.03	PASS
11G	Ant1	2412	0~Reference	1.67	1.67	---	PASS
11G	Ant1	2412	30~1000	1.67	-58.64	≤-28.33	PASS
11G	Ant1	2412	1000~26500	1.67	-47.84	≤-28.33	PASS
11G	Ant1	2437	0~Reference	1.39	1.39	---	PASS
11G	Ant1	2437	30~1000	1.39	-58.89	≤-28.61	PASS
11G	Ant1	2437	1000~26500	1.39	-44.73	≤-28.61	PASS
11G	Ant1	2462	0~Reference	0.73	0.73	---	PASS
11G	Ant1	2462	30~1000	0.73	-59.19	≤-29.27	PASS




11G	Ant1	2462	1000~26500	0.73	-42.17	≤-29.27	PASS
11N20SISO	Ant1	2412	0~Reference	0.37	0.37	---	PASS
11N20SISO	Ant1	2412	30~1000	0.37	-58.27	≤-29.63	PASS
11N20SISO	Ant1	2412	1000~26500	0.37	-45.58	≤-29.63	PASS
11N20SISO	Ant1	2437	0~Reference	4.76	4.76	---	PASS
11N20SISO	Ant1	2437	30~1000	4.76	-59.27	≤-25.24	PASS
11N20SISO	Ant1	2437	1000~26500	4.76	-43.89	≤-25.24	PASS
11N20SISO	Ant1	2462	0~Reference	1.97	1.97	---	PASS
11N20SISO	Ant1	2462	30~1000	1.97	-58.98	≤-28.03	PASS
11N20SISO	Ant1	2462	1000~26500	1.97	-44.98	≤-28.03	PASS
11N40SISO	Ant1	2422	0~Reference	-1.27	-1.27	---	PASS
11N40SISO	Ant1	2422	30~1000	-1.27	-58.47	≤-31.27	PASS
11N40SISO	Ant1	2422	1000~26500	-1.27	-49.54	≤-31.27	PASS
11N40SISO	Ant1	2437	0~Reference	0.77	0.77	---	PASS
11N40SISO	Ant1	2437	30~1000	0.77	-59.12	≤-29.23	PASS
11N40SISO	Ant1	2437	1000~26500	0.77	-45.38	≤-29.23	PASS
11N40SISO	Ant1	2452	0~Reference	0.59	0.59	---	PASS
11N40SISO	Ant1	2452	30~1000	0.59	-58.91	≤-29.41	PASS
11N40SISO	Ant1	2452	1000~26500	0.59	-45.24	≤-29.41	PASS
11AX20SISO	Ant1	2412	0~Reference	2.92	2.92	---	PASS
11AX20SISO	Ant1	2412	30~1000	2.92	-58.74	≤-27.08	PASS
11AX20SISO	Ant1	2412	1000~26500	2.92	-44.83	≤-27.08	PASS
11AX20SISO	Ant1	2437	0~Reference	1.65	1.65	---	PASS
11AX20SISO	Ant1	2437	30~1000	1.65	-57.57	≤-28.35	PASS
11AX20SISO	Ant1	2437	1000~26500	1.65	-44.84	≤-28.35	PASS
11AX20SISO	Ant1	2462	0~Reference	3.19	3.19	---	PASS
11AX20SISO	Ant1	2462	30~1000	3.19	-58.6	≤-26.81	PASS
11AX20SISO	Ant1	2462	1000~26500	3.19	-44.39	≤-26.81	PASS
11AX40SISO	Ant1	2422	0~Reference	1.19	1.19	---	PASS
11AX40SISO	Ant1	2422	30~1000	1.19	-58.65	≤-28.81	PASS
11AX40SISO	Ant1	2422	1000~26500	1.19	-47.43	≤-28.81	PASS
11AX40SISO	Ant1	2437	0~Reference	1.51	1.51	---	PASS
11AX40SISO	Ant1	2437	30~1000	1.51	-58.93	≤-28.49	PASS
11AX40SISO	Ant1	2437	1000~26500	1.51	-43.03	≤-28.49	PASS
11AX40SISO	Ant1	2452	0~Reference	0.08	0.08	---	PASS
11AX40SISO	Ant1	2452	30~1000	0.08	-59.23	≤-29.92	PASS
11AX40SISO	Ant1	2452	1000~26500	0.08	-44.86	≤-29.92	PASS




Test Graphs:




11B-Ant1-2412-0~Reference-PASS




11B-Ant1-2412-30~1000-PASS




11B-Ant1-2412-1000~26500-PASS




11B-Ant1-2437-0~Reference-PASS




11B-Ant1-2437-30~1000-PASS




11B-Ant1-2437-1000~26500-PASS




11B-Ant1-2462-0~Reference-PASS




11B-Ant1-2462-30~1000-PASS




11B-Ant1-2462-1000~26500-PASS




11G-Ant1-2412-0~Reference-PASS




11G-Ant1-2412-30~1000-PASS




11G-Ant1-2412-1000~26500-PASS




11G-Ant1-2437-0~Reference-PASS




11G-Ant1-2437-30~1000-PASS




11G-Ant1-2437-1000~26500-PASS




11G-Ant1-2462-0~Reference-PASS




11G-Ant1-2462-30~1000-PASS




11G-Ant1-2462-1000~26500-PASS




11N20SISO-Ant1-2412-0~Reference-PASS




11N20SISO-Ant1-2412-30~1000-PASS




11N20SISO-Ant1-2412-1000~26500-PASS




11N20SISO-Ant1-2437-0~Reference-PASS




11N20SISO-Ant1-2437-30~1000-PASS




11N20SISO-Ant1-2437-1000~26500-PASS




11N20SISO-Ant1-2462-0~Reference-PASS






11N20SISO-Ant1-2462-30~1000-PASS




11N20SISO-Ant1-2462-1000~26500-PASS




11N40SISO-Ant1-2422-0~Reference-PASS







11N40SISO-Ant1-2437-0~Reference-PASS




11N40SISO-Ant1-2437-30~1000-PASS




11N40SISO-Ant1-2437-1000~26500-PASS




11N40SISO-Ant1-2452-0~Reference-PASS




11N40SISO-Ant1-2452-30~1000-PASS




11N40SISO-Ant1-2452-1000~26500-PASS




11AX20SISO-Ant1-2412-0~Reference-PASS




11AX20SISO-Ant1-2412-30~1000-PASS




11AX20SISO-Ant1-2412-1000~26500-PASS




11AX20SISO-Ant1-2437-0~Reference-PASS




11AX20SISO-Ant1-2437-30~1000-PASS




11AX20SISO-Ant1-2437-1000~26500-PASS




11AX20SISO-Ant1-2462-0~Reference-PASS




11AX20SISO-Ant1-2462-30~1000-PASS




11AX20SISO-Ant1-2462-1000~26500-PASS




11AX40SISO-Ant1-2422-0~Reference-PASS




11AX40SISO-Ant1-2422-30~1000-PASS




11AX40SISO-Ant1-2422-1000~26500-PASS




11AX40SISO-Ant1-2437-0~Reference-PASS




11AX40SISO-Ant1-2437-30~1000-PASS




11AX40SISO-Ant1-2437-1000~26500-PASS



11AX40SISO-Ant1-2452-0~Reference-PASS



11AX40SISO-Ant1-2452-30~1000-PASS



11AX40SISO-Ant1-2452-1000~26500-PASS


8 Band Edge Measurement

Test Requirement	:	Section 15.247(d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method	:	ANSI C63.10-2020
Test Limit	:	Regulation 15.247 (d),In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

8.1Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold

8.2Test Setup




8.3Test Result


TestMode	Antenna	ChName	Frequency[MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	Low	2412	4.64	-44.89	≤-25.36	PASS
11B	Ant1	High	2462	5.61	-47.23	≤-24.39	PASS
11G	Ant1	Low	2412	3.60	-36.67	≤-26.4	PASS
11G	Ant1	High	2462	3.64	-42.44	≤-26.36	PASS
11N20SISO	Ant1	Low	2412	4.38	-34.46	≤-25.62	PASS
11N20SISO	Ant1	High	2462	3.12	-39.84	≤-26.88	PASS
11N40SISO	Ant1	Low	2422	0.39	-31.58	≤-29.61	PASS
11N40SISO	Ant1	High	2452	2.40	-33.02	≤-27.6	PASS
11AX20SISO	Ant1	Low	2412	3.76	-35.23	≤-26.24	PASS
11AX20SISO	Ant1	High	2462	4.08	-38.19	≤-25.92	PASS
11AX40SISO	Ant1	Low	2422	1.52	-30.96	≤-28.48	PASS
11AX40SISO	Ant1	High	2452	2.12	-32.44	≤-27.88	PASS




Test Graphs:



11B-Ant1-2412-PASS




11B-Ant1-2462-PASS



11G-Ant1-2412-PASS



11G-Ant1-2462-PASS



11N20SISO-Ant1-2412-PASS



11N20SISO-Ant1-2462-PASS



11N40SISO-Ant1-2422-PASS



11N40SISO-Ant1-2452-PASS



11AX20SISO-Ant1-2412-PASS



11AX20SISO-Ant1-2462-PASS



11AX40SISO-Ant1-2422-PASS



11AX40SISO-Ant1-2452-PASS



9 6dB Bandwidth Measurement

Test Requirement : FCC CFR47 Part 15 Section 15.247


Test Method : ANSI C63.10-2020

Test Limit Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

9.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

9.2 Test Setup



9.3 Test Result

TestMode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	9.160	2407.480	2416.640	0.5	PASS
11B	Ant1	2437	9.120	2432.480	2441.600	0.5	PASS
11B	Ant1	2462	9.120	2457.480	2466.600	0.5	PASS
11G	Ant1	2412	16.320	2403.880	2420.200	0.5	PASS
11G	Ant1	2437	16.240	2428.920	2445.160	0.5	PASS
11G	Ant1	2462	16.280	2453.880	2470.160	0.5	PASS
11N20SISO	Ant1	2412	17.560	2403.240	2420.800	0.5	PASS
11N20SISO	Ant1	2437	17.480	2428.280	2445.760	0.5	PASS
11N20SISO	Ant1	2462	17.560	2453.240	2470.800	0.5	PASS
11N40SISO	Ant1	2422	36.160	2404.080	2440.240	0.5	PASS
11N40SISO	Ant1	2437	36.240	2419.000	2455.240	0.5	PASS
11N40SISO	Ant1	2452	36.160	2433.920	2470.080	0.5	PASS
11AX20SISO	Ant1	2412	18.920	2402.560	2421.480	0.5	PASS
11AX20SISO	Ant1	2437	18.920	2427.600	2446.520	0.5	PASS
11AX20SISO	Ant1	2462	18.960	2452.560	2471.520	0.5	PASS
11AX40SISO	Ant1	2422	37.760	2403.120	2440.880	0.5	PASS
11AX40SISO	Ant1	2437	37.840	2418.280	2456.120	0.5	PASS
11AX40SISO	Ant1	2452	38.000	2433.120	2471.120	0.5	PASS



Test Graphs:



11B-Ant1-2412-PASS



11B-Ant1-2437-PASS



11B-Ant1-2462-PASS



11G-Ant1-2412-PASS