



RF Exposure Evaluation Declaration

Report No.: S20250723677208

Issue Date: 2025-12-24

Applicant: Alps Alpine North America, Inc.
Address: 1500 Atlantic Blvd, Auburn Hills, Michigan, United States 48326
FCC ID: 2ACH3UTEMN801
Product: Marine Radio with Bluetooth
Model No.: UTE-MN801
Trade Mark: Alpine
FCC Rule Part(s): CFR 47, FCC Part 2.1091 Radio frequency radiation exposure evaluation: mobile devices.
Item Receipt date: Aug. 07, 2025
Test Date: Aug. 18, ~ Sep. 05, 2025



扫一扫 验真伪

Compiled By

Chuang Li

(Chuang Li)
Senior Test Engineer

Approved By

Line Chen

(Line Chen)
Engineer Manager

The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2020. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of Fangguang Inspection & Testing Co., Ltd.

The test report must not be used by the client to claim product certifications, approval, or endorsement by NVLAP, NIST or any agency of U.S. Government.

Revision History

Report No.	Version	Description	Issue Date
S20250723677208	Rev. 01	/	2025-12-24

1. PRODUCT INFORMATION

1.1. Equipment Description

Product Name:	Marine Radio with Bluetooth
Test Model:	UTE-MN801
Trade Mark:	Alpine
Input Voltage Range:	DC 14.4V
Bluetooth Version:	5.2
Software Version:	V1.07
Hardware Version:	V00
Note:	This information is provided by the Customer and its authenticity is the responsibility of the Customer.

1.2. Product Specification Subjective to this Report

Frequency Range:	BT: 2402~2480MHz
Channel Number:	BT: 79
Antenna Type:	PCB Antenna
Antenna Gain:	0dBi
Type of Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Data Rate:	1Mbps (GFSK), 2Mbps ($\pi/4$ DQPSK), 3Mbps (8DPSK)

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result of RF Exposure Evaluation

Product	Marine Radio with Bluetooth
Test Item	RF Exposure Evaluation

Mode	Frequency (MHz)	Maximum Conducted OutputPower (dBm)	Antenna Gain (dBi)	PG		MPE (mW/cm ²)	MPE Limits (mW/cm ²)
				(dBm)	(mW)		
BT	2402~2480	9.81	0	9.81	9.572	0.0019	1.00

Remark: 1. MPE use distance is 20cm from manufacturer declaration of user manual.

Remark: 2. Use the maximum gain of all bands when evaluating

CONCLUSION:

The Max Power Density at R (20 cm) = 0.0019mW/cm² < 1mW/cm².

So the EUT complies with the requirement.

Statement

1. This report is invalid for the following states: without the special inspection and testing stamp or the official stamp of our institution; without the signature of the report authorized officer; if the report is altered.
2. It is forbidden to copy partial contents of the report except in full without the approval of our institution.
3. The client shall provide the test sample(s) and commission information and be responsible for their authenticity.
4. The report content is only applicable to the tested sample(s) this time.
5. If there are any objections to the report content, please submit them to our company in writing within 15 days from the date of receiving the report.
6. If the reports include both Chinese and English versions, when there are any inconsistencies caused by language, the Chinese version shall prevail.
7. This report is issued by the following laboratory premises:
No.8 Ningyun Rd., Xinwu District Wuxi, Jiangsu 214000 China

——This page is blank below this line ——