FCC PART 15 SUBPART C TEST REPORT

FCC PART 15.247

Report Reference No.....:	**GTSR17032018-02**
FCC ID..... :	**2ACH9 ELL1201T**
Compiled by (position+printed name+signature)..:	File administrators Jimmy Wang
Supervised by (position+printed name+signature)..:	Test Engineer Peter Xiao
Approved by (position+printed name+signature)..:	Manager Sam Wang
Date of issue.....:	Mar. 25, 2017
Representative Laboratory Name.:	**Shenzhen Global Test Service Co.,Ltd.**
Address .....:	1F, Building No. 13A, Zhonghaixin Science and Technology City, No.12,6 Road, Ganli Industrial Park, Buji Street, Longgang District, Shenzhen, Guangdong
Applicant's name.....:	**WeiHeng Digital Company Limited**
Address .....:	Rm732, 3rd session, Build B, Mingyou Industrial Products Exhibition and Purchasing Center, Baoyuan Road, Bao'an District, Shenzhen, China
Test specification .....:	
Standard .....:	**FCC Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz**

Shenzhen Global Test Service Co.,Ltd. All rights reserved.
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description .....:	Laptop
Trade Mark .....:	TEQNIO
Manufacturer .....:	WeiHeng Digital Company Limited
Model/Type reference.....:	ELL1201T
Listed Models .....:	/
Operation Frequency.....:	From 2412MHz to 2462MHz
Hardware Version .....:	S16C Rev 1.1
Software Version .....:	V1.0
Rating .....:	DC 3.80V
Result.....:	**PASS**

T E S T R E P O R T

Test Report No. :	GTSR17032018-02	Mar. 25, 2017 Date of issue

Equipment under Test	:	Laptop
Model /Type	:	ELL1201T
Listed Models	:	/
Applicant	:	**WeiHeng Digital Company Limited**
Address	:	Rm732, 3rd session, Build B, Mingyou Industrial Products Exhibition and Purchasing Center, Baoyuan Road, Bao’an District, Shenzhen, China
Manufacturer	:	**WeiHeng Digital Company Limited**
Address	:	Rm732, 3rd session, Build B, Mingyou Industrial Products Exhibition and Purchasing Center, Baoyuan Road, Bao’an District, Shenzhen, China

Test Result:	**PASS**

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. TEST STANDARDS 4

2. SUMMARY 5

2.1. General Remarks 5
2.2. Product Description 5
2.3. Equipment Under Test 5
2.4. Short description of the Equipment under Test (EUT) 5
2.5. EUT operation mode 6
2.6. Block Diagram of Test Setup 6
2.7. Related Submittal(s) / Grant (s) 6
2.8. Modifications 6

3. TEST ENVIRONMENT 7

3.1. Address of the test laboratory 7
3.2. Test Facility 7
3.3. Environmental conditions 7
3.4. Test Description 8
3.5. Statement of the measurement uncertainty 9
3.6. Equipments Used during the Test 9

4. TEST CONDITIONS AND RESULTS..... 10

4.1. AC Power Conducted Emission 10
4.2. Radiated Emission.....13
4.3. Maximum Peak Output Power.....21
4.4. Power Spectral Density 22
4.5. 6dB Bandwidth 25
4.6. Band Edge Compliance of RF Emission 28
4.7. Spurious RF Conducted Emission 32
4.8. Antenna Requirement.....42

5. TEST SETUP PHOTOS OF THE EUT 43

6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT 44

1. TEST STANDARDS

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.
ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices
KDB558074 D01 V03r05: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247

2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	:	Mar. 01, 2017
Testing commenced on	:	Mar. 01, 2017
Testing concluded on	:	Mar. 25, 2017

2.2. Product Description

Name of EUT	Laptop
Trade Mark:	TEQNIO
Model Number	ELL1201T
Listed Models	/
FCC ID	2ACH9 ELL1201T
Power Supply	Battery DC 3.80V
Adapter Information	Model: B118-050300-AdU Input: 100-240V～50/60Hz 0.8A Output: DC5V/3A
Supported type:	802.11b/802.11g/802.11n HT20
Modulation:	802.11b: DSSS(CCK,DQPSK,DBPSK) 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK)
Operation frequency:	802.11b:2412-2462MHz 802.11g:2412-2462MHz 802.11n HT20:2412-2462MHz
Antenna Type	Internal Antenna
Antenna gain	-0.75dBi

2.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	○	230V / 50 Hz	○	120V / 60Hz
		○	12 V DC	○	24 V DC
		●	Other (specified in blank below)		

DC 5V From Adapter AC 120V/60Hz

2.4. Short description of the Equipment under Test (EUT)

This is a Laptop.

For more details, refer to the user's manual of the EUT.

2.5. EUT operation mode

The application provider specific test software to control sample in continuous TX and RX (Duty Cycle >98%)

for testing meet KDB558074 test requirement.

IEEE 802.11b/g/n: Thirteen channels are provided to the EUT.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	**2412**	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	**11**	**2462**
5	2432		
6	**2437**		
7	2442		

2.6. Block Diagram of Test Setup



2.7. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2ACH9 ELL1201T** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.8. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.
1F, Building No. 13A, Zhonghaixin Science and Technology City, No.12,6 Road, Ganli Industrial Park, Buji Street, Longgang District, Shenzhen, Guangdong

Shenzhen CTL Testing Technology Co.,Ltd.
1/F.-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, Guangdong, China

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 964637

Shenzhen Global Test Service Co.,Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 964637, Jul 24, 2015.

CNAS-Lab Code: L8169

Shenzhen Global Test Service Co.,Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories. Date of Registration: Dec. 11, 2015. Valid time is until Dec. 10, 2018.

FCC-Registration No.: 970318

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December 19, 2013.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4. Test Description

Test Specification clause	Test case	Test Mode	Test Channel	Recorded In Report		Pass	Fail	NA	NP	Remark
§15.247(b)(4)	Antenna gain	802.11b	☒ Lowest ☒ Middle ☒ Highest	802.11b	☒ Lowest ☒ Middle ☒ Highest	☒	☐	☐	☐	See remark 3
§15.247(e)	Power spectral density	802.11b 802.11g 802.11n HT20	☒ Lowest ☒ Middle ☒ Highest	802.11b 802.11g 802.11n HT20	☒ Lowest ☒ Middle ☒ Highest	☒	☐	☐	☐	See remark 3
§15.247(a)(2)	Spectrum bandwidth – 6 dB bandwidth	802.11b 802.11g 802.11n HT20	☒ Lowest ☒ Middle ☒ Highest	802.11b 802.11g 802.11n HT20	☒ Lowest ☒ Middle ☒ Highest	☒ ☒	☐	☐	☐	See remark 3
§15.247(b)(1)	Maximum output power	802.11b 802.11g 802.11n HT20	☒ Lowest ☒ Middle ☒ Highest	802.11b 802.11g 802.11n HT20	☒ Lowest ☒ Middle ☒ Highest	☒ ☒ ☒	☐	☐	☐	See remark 3
§15.247(d)	Band edge compliance conducted	802.11b 802.11g 802.11n HT20	☒ Lowest ☒ Highest	802.11b 802.11g 802.11n HT20	☒ Lowest ☒ Highest	☒ ☒	☐	☐	☐	See remark 3
§15.205	Band edge compliance radiated	802.11b 802.11g 802.11n HT20	☒ Lowest ☒ Highest	802.11b 802.11g 802.11n HT20	☒ Lowest ☒ Highest	☒	☐	☐	☐	See remark 4
§15.247(d)	TX spurious emissions conducted	802.11b 802.11g 802.11n HT20	☒ Lowest ☒ Middle ☒ Highest	802.11b 802.11g 802.11n HT20	☒ Lowest ☒ Middle ☒ Highest	☒ ☒	☐	☐	☐	See remark 3
§15.247(d)	TX spurious emissions radiated	802.11b 802.11g 802.11n HT20	☒ Lowest ☒ Middle ☒ Highest	802.11b 802.11g 802.11n HT20	☒ Lowest ☒ Middle ☒ Highest	☒	☐	☐	☐	See remark 4
§15.109	RX spurious emissions radiated	-/-	-/-	-/-	-/-	☐	☐	☒	☐	--
§15.209(a)	TX spurious Emissions radiated < 30 MHz	802.11b	-/-	802.11b	-/-	☒	☐	☐	☐	See remark 4
§15.107(a) §15.207	Conducted Emissions < 30 MHz	802.11b	-/-	802.11b	-/-	☒	☐	☐	☐	See remark 3

Remark:
1. The measurement uncertainty is not included in the test result.
2. NA = Not Applicable; NP = Not Performed
3. Test size: Shenzhen Global Test Service Co.,Ltd.
4. Test size: Shenzhen CTL Testing Technology Co., Ltd.

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
Maximum Peak Conducted Output Power Power Spectral Density 6dB Bandwidth Spurious RF conducted emission Radiated Emission 9kHz~1GHz& Radiated Emission 1GHz~10th Harmonic	11b/DSSS	1 Mbps	1/6/11
	11g/OFDM	6 Mbps	1/6/11
	11n(20MHz)/OFDM	6.5Mbps	1/6/11
Band Edge	11b/DSSS	1 Mbps	1/11
	11g/OFDM	6 Mbps	1/11
	11n(20MHz)/OFDM	6.5Mbps	1/11

3.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	3560.6550.08	2016/05/28	2017/05/27
LISN	R&S	ESH2-Z5	893606/008	2016/05/27	2017/05/26
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2016/06/02	2017/06/01
EMI Test Receiver	R&S	ESCI	101102	2016/06/26	2017/06/25
Spectrum Analyzer	Agilent	N9020A	MY48010425	2016/06/17	2017/06/16
Controller	EM Electronics	Controller EM 1000	N/A	2016/05/21	2017/05/20
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2016/05/19	2017/05/18
Active Loop Antenna	SCHWARZBECK	FMZB1519	1519-037	2016/05/19	2017/05/18
Amplifier	Agilent	8349B	3008A02306	2016/05/19	2017/05/18
Amplifier	Agilent	8447D	2944A10176	2016/05/19	2017/05/18
Temperature/Humidity Meter	Gangxing	CTH-608	02	2016/05/20	2017/05/19
High-Pass Filter	K&L	9SH10-2700/X12750-O/O	N/A	2016/05/20	2017/05/19
High-Pass Filter	K&L	41H10-1375/U12750-O/O	N/A	2016/05/20	2017/05/19
Data acquisition card	Agilent	U2531A	TW53323507	2016/05/20	2017/05/19
Power Sensor	Agilent	U2021XA	MY5365004	2016/05/20	2017/05/19
RF Cable	HUBER+SUHNER	RG214	N/A	2016/05/20	2017/05/19

Note: The Cal.Interval was one year.

4. TEST CONDITIONS AND RESULTS

4.1. AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
2 Support equipment, if needed, was placed as per ANSI C63.10-2013
3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
4 The EUT received DC 5V power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5 All support equipments received AC power from a second LISN, if any.
6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT.The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
* Decreases with the logarithm of the frequency.		

TEST RESULTS

Remark: We measured Conducted Emission at 802.11b/802.11g/802.11n HT20 mode in AC 120V/60Hz and 240V/60Hz, the worst case was recorded .

Power supply:	DC 5V from Adapter AC 120V/60Hz	Polarization	L

SCAN TABLE: "Voltage (9K-30M)FIN"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "GTS170313119_fin"

3/13/2017 11:27AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.190500	51.80	10.0	64	12.2	QP	L1	GND
0.649500	36.40	9.7	56	19.6	QP	L1	GND
1.576500	35.20	9.5	56	20.8	QP	L1	GND
2.247000	31.50	9.5	56	24.5	QP	L1	GND
5.293500	21.90	9.3	60	38.1	QP	L1	GND
22.884000	36.70	7.0	60	23.3	QP	L1	GND

MEASUREMENT RESULT: "GTS170313119_fin2"

3/13/2017 11:27AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.204000	34.80	10.0	53	18.6	AV	L1	GND
0.685500	28.40	9.7	46	17.6	AV	L1	GND
0.996000	26.90	9.6	46	19.1	AV	L1	GND
2.130000	24.20	9.5	46	21.8	AV	L1	GND
11.044500	18.90	8.7	50	31.1	AV	L1	GND
22.483500	31.50	7.0	50	18.5	AV	L1	GND

Power supply:	DC 5V from Adapter AC 120V/60Hz	Polarization	N

SCAN TABLE: "Voltage (9K-30M)FIN"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "GTS170313118_fin"

3/13/2017 11:24AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.190500	52.90	10.0	64	11.1	QP	N	GND
0.712500	36.40	9.7	56	19.6	QP	N	GND
1.248000	35.20	9.6	56	20.8	QP	N	GND
2.238000	31.90	9.5	56	24.1	QP	N	GND
5.122500	21.10	9.3	60	38.9	QP	N	GND
22.749000	40.50	7.0	60	19.5	QP	N	GND

MEASUREMENT RESULT: "GTS170313118_fin2"

3/13/2017 11:24AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.190500	37.90	10.0	54	16.1	AV	N	GND
0.685500	27.90	9.7	46	18.1	AV	N	GND
0.946500	26.70	9.6	46	19.3	AV	N	GND
2.121000	23.50	9.5	46	22.5	AV	N	GND
5.154000	16.30	9.3	50	33.7	AV	N	GND
22.429500	35.90	7.0	50	14.1	AV	N	GND

4.2. Radiated Emission

TEST CONFIGURATION

Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT minimum operation frequency was 32.768KHz and maximum operation frequency was 2480MHz.so radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Anternna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

Transd=AF +CL-AG

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark: We measured Radiated Emission at 802.11b/802.11g/802.11n HT20 mode from 9 KHz to 25GHz in AC 120V/60Hz and AC 240V/60Hz and recorded worst case at GFSK mode.
Test site: Shenzhen CTL Testing Technology Co., Ltd

For 9 KHz-30MHz

Frequency (MHz)	Corrected Reading (dBuV/m)@3m	FCC Limit (dBuV/m) @3m	Margin (dB)	Detector	Result
0.57	49.76	72.49	22.73	QP	PASS
3.44	43.17	69.54	26.37	QP	PASS
15.78	44.33	69.54	25.21	QP	PASS
20.16	43.63	69.54	25.91	QP	PASS

For 30MHz-1GHz

Horizontal



Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	24.40	20.8	40.0	15.6	PK	100	68.0	HORIZONTAL
130.880000	27.20	14.5	43.5	16.3	PK	100	82.0	HORIZONTAL
183.260000	24.30	13.1	43.5	19.2	PK	100	162.0	HORIZONTAL
198.780000	23.60	13.9	43.5	19.9	PK	100	158.0	HORIZONTAL
532.460000	26.10	20.5	46.0	19.9	PK	100	96.0	HORIZONTAL
600.360000	33.30	21.8	46.0	12.7	PK	100	172.0	HORIZONTAL

Vertical



Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	36.50	20.8	40.0	3.5	PK	100	128.0	VERTICAL
123.120000	31.00	14.6	43.5	12.5	PK	100	28.0	VERTICAL
177.440000	22.40	13.0	43.5	21.1	PK	100	97.0	VERTICAL
183.260000	21.90	13.1	43.5	21.6	PK	100	268.0	VERTICAL
385.020000	28.40	17.7	46.0	17.6	PK	100	172.0	VERTICAL
945.680000	30.10	26.5	46.0	15.9	PK	100	87.0	VERTICAL

For 1GHz to 25GHz

802.11b Mode (above 1GHz)

Frequency(MHz):				2412			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4824	53.95	PK	74	20.05	1.00	153	51.85	31.6	7.00	36.5	2.10
1	4824	39.77	AV	54	14.23	1.00	153	37.67	31.6	7.00	36.5	2.10
2	7236	51.90	PK	74	22.10	1.00	208	40.97	37.33	8.90	35.3	10.93
2	7236	38.98	AV	54	15.02	1.00	208	28.05	37.33	8.90	35.3	10.93

Frequency(MHz):				2412			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4824	55.94	PK	74	18.06	1.00	129	20.16	31.60	7.00	36.50	2.10
1	4824	41.82	AV	54	12.18	1.00	129	14.28	31.60	7.00	36.50	2.10
2	7236	51.43	PK	74	22.57	1.00	218	33.50	37.33	8.90	35.30	10.93
2	7236	41.38	AV	54	12.62	1.00	218	23.55	37.33	8.90	35.30	10.93

Frequency(MHz):				2437			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4874.00	57.72	PK	74.00	16.28	1.00	221	55.60	31.02	7.60	36.5	2.12
1	4874.00	39.13	AV	54.00	14.87	1.00	221	37.01	31.02	7.60	36.5	2.12
2	7311.00	54.75	PK	74.00	19.25	1.00	136	43.67	37.28	8.60	34.8	11.08
2	7311.00	39.12	AV	54.00	14.88	1.00	136	28.04	37.28	8.60	34.8	11.08

Frequency(MHz):				2437			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4874.00	58.00	PK	74.00	16.00	1.00	96	55.88	31.02	7.60	36.5	2.12
1	4874.00	40.74	AV	54.00	13.26	1.00	96	38.62	31.02	7.60	36.5	2.12
2	7311.00	53.13	PK	74.00	20.87	1.00	212	42.05	37.28	8.60	34.8	11.08
2	7311.00	40.93	AV	54.00	13.07	1.00	212	29.85	37.28	8.60	34.8	11.08

Frequency(MHz):				2462			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4924.00	59.82	PK	74.00	14.18	1.00	123	56.62	31.58	7.82	36.2	3.20
1	4924.00	40.78	AV	54.00	13.22	1.00	123	37.58	31.58	7.82	36.2	3.20
2	7386.00	55.59	PK	74.00	18.41	1.00	296	43.65	38.51	8.73	35.3	11.94
2	7386.00	39.81	AV	54.00	14.19	1.00	296	27.87	38.51	8.73	35.3	11.94

Frequency(MHz):				2462			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	4924.00	57.83	PK	74.00	16.17	1.00	86	54.63	31.58	7.82	36.2	3.20
1	4924.00	40.59	AV	54.00	13.41	1.00	86	37.39	31.58	7.82	36.2	3.20
2	7386.00	53.56	PK	74.00	20.44	1.00	257	41.62	38.51	8.73	35.3	11.94
2	7386.00	41.74	AV	54.00	12.26	1.00	257	29.80	38.51	8.73	35.3	11.94

802.11g Mode (above 1GHz)

Frequency(MHz):				2412			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4824	60.06	PK	74	13.94	1.00	56	57.96	31.6	7.00	36.5	2.10
1	4824	42.88	AV	54	11.12	1.00	56	40.78	31.6	7.00	36.5	2.10
2	7236	52.74	PK	74	21.26	1.00	189	41.81	37.33	8.90	35.3	10.93
2	7236	39.47	AV	54	14.53	1.00	189	28.54	37.33	8.90	35.3	10.93

Frequency(MHz):				2412			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4824	60.12	PK	74	13.88	1.00	116	58.02	31.60	7.00	36.50	2.10
1	4824	40.83	AV	54	13.17	1.00	116	38.73	31.60	7.00	36.50	2.10
2	7236	54.02	PK	74	19.98	1.00	175	43.09	37.33	8.90	35.30	10.93
2	7236	40.75	AV	54	13.25	1.00	175	29.82	37.33	8.90	35.30	10.93

Frequency(MHz):				2437			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4874.00	58.88	PK	74.00	15.12	1.00	118	56.76	31.02	7.60	36.5	2.12
1	4874.00	41.32	AV	54.00	12.68	1.00	118	39.20	31.02	7.60	36.5	2.12
2	7311.00	53.87	PK	74.00	20.13	1.00	256	42.79	37.28	8.60	34.8	11.08
2	7311.00	41.65	AV	54.00	12.35	1.00	256	30.57	37.28	8.60	34.8	11.08

Frequency(MHz):				2437			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4874.00	59.10	PK	74.00	14.90	1.00	78	56.98	31.02	7.60	36.5	2.12
1	4874.00	41.69	AV	54.00	12.31	1.00	78	39.57	31.02	7.60	36.5	2.12
2	7311.00	56.24	PK	74.00	17.76	1.00	221	45.16	37.28	8.60	34.8	11.08
2	7311.00	40.24	AV	54.00	13.76	1.00	221	29.16	37.28	8.60	34.8	11.08

Frequency(MHz):				2462			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4924.00	59.75	PK	74.00	14.25	1.00	148	56.55	31.58	7.82	36.2	3.20
1	4924.00	41.60	AV	54.00	12.40	1.00	148	38.40	31.58	7.82	36.2	3.20
2	7386.00	54.09	PK	74.00	19.91	1.00	218	42.15	38.51	8.73	35.3	11.94
2	7386.00	40.04	AV	54.00	13.96	1.00	218	28.10	38.51	8.73	35.3	11.94

Frequency(MHz):				2462			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4924.00	60.29	PK	74.00	13.71	1.00	116	57.09	31.58	7.82	36.2	3.20
1	4924.00	41.36	AV	54.00	12.64	1.00	116	38.16	31.58	7.82	36.2	3.20
2	7386.00	55.31	PK	74.00	18.69	1.00	229	43.37	38.51	8.73	35.3	11.94
2	7386.00	41.19	AV	54.00	12.81	1.00	229	29.25	38.51	8.73	35.3	11.94

802.11n HT20 Mode (above 1GHz)

Frequency(MHz):				2412			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4824	58.12	PK	74	15.88	1.00	118	56.02	31.6	7.00	36.5	2.10
1	4824	40.77	AV	54	13.23	1.00	118	38.67	31.6	7.00	36.5	2.10
2	7236	55.78	PK	74	18.22	1.00	183	44.85	37.33	8.90	35.3	10.93
2	7236	41.09	AV	54	12.91	1.00	186	30.16	37.33	8.90	35.3	10.93

Frequency(MHz):				2412			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4824	59.48	PK	74	14.52	1.00	107	57.38	31.60	7.00	36.50	2.10
1	4824	41.67	AV	54	12.33	1.00	107	39.57	31.60	7.00	36.50	2.10
2	7236	54.00	PK	74	20.00	1.00	292	43.07	37.33	8.90	35.30	10.93
2	7236	40.79	AV	54	13.21	1.00	292	29.86	37.33	8.90	35.30	10.93

Frequency(MHz):				2437			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4874.00	56.78	PK	74.00	17.22	1.00	118	54.66	31.02	7.60	36.5	2.12
1	4874.00	40.15	AV	54.00	13.85	1.00	118	38.03	31.02	7.60	36.5	2.12
2	7311.00	53.76	PK	74.00	20.24	1.00	261	42.68	37.28	8.60	34.8	11.08
2	7311.00	41.74	AV	54.00	12.26	1.00	261	30.66	37.28	8.60	34.8	11.08

Frequency(MHz):				2437			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4874.00	59.96	PK	74.00	14.04	1.00	96	57.84	31.02	7.60	36.5	2.12
1	4874.00	42.65	AV	54.00	11.35	1.00	96	40.53	31.02	7.60	36.5	2.12
2	7311.00	54.09	PK	74.00	19.91	1.00	182	43.01	37.28	8.60	34.8	11.08
2	7311.00	40.14	AV	54.00	13.86	1.00	182	29.06	37.28	8.60	34.8	11.08

Frequency(MHz):				2462			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4924.00	58.03	PK	74.00	15.97	1.00	137	54.83	31.58	7.82	36.2	3.20
1	4924.00	41.04	AV	54.00	12.96	1.00	137	37.84	31.58	7.82	36.2	3.20
2	7386.00	55.08	PK	74.00	18.92	1.00	218	43.14	38.51	8.73	35.3	11.94
2	7386.00	41.69	AV	54.00	12.31	1.00	218	29.75	38.51	8.73	35.3	11.94

Frequency(MHz):				2462			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4924.00	58.47	PK	74.00	15.53	1.00	169	55.27	31.58	7.82	36.2	3.20
1	4924.00	40.84	AV	54.00	13.16	1.00	169	37.64	31.58	7.82	36.2	3.20
2	7386.00	55.09	PK	74.00	18.91	1.00	228	43.15	38.51	8.73	35.3	11.94
2	7386.00	42.09	AV	54.00	11.91	1.00	228	30.15	38.51	8.73	35.3	11.94

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

4.3. Maximum Peak Output Power

TEST CONFIGURATION



TEST PROCEDURE

According to KDB558074 D01 DTS Measurement Guidance Section 9.1 Maximum peak conducted output power,9.1.2. and Average conducted output power, 9.2.3.1.

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

The maximum Average conducted output power may be measured using a wideband RF power meter with a thermocouple derector or equivalent. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

LIMIT

The Maximum Peak Output Power Measurement is 30dBm.

TEST RESULTS

Type	Channel	Output power PK (dBm)	Output power AV (dBm)	Limit (dBm)	Result
802.11b	01	9.55	6.57	30.00	Pass
	06	9.38	6.48		
	11	9.18	6.21		
802.11g	01	10.10	6.18	30.00	Pass
	06	10.08	6.11		
	11	9.89	5.96		
802.11n(HT20)	01	10.18	6.19	30.00	Pass
	06	10.01	6.05		
	11	9.98	5.99		

Note: 1.The test results including the cable lose.

Duty cycle used in all test items: 100%



4.4. Power Spectral Density

TEST CONFIGURATION



TEST PROCEDURE

According to KDB 558074 D01 Method PKPSD (peak PSD) This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.
1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
4. Set the VBW ≥ 3 RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

LIMIT

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST RESULTS

Type	Channel	Power Spectral Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
802.11b	01	-24.293	8.00	Pass
	06	-24.528		
	11	-24.457		
802.11g	01	-23.839	8.00	Pass
	06	-25.397		
	11	-25.998		
802.11n(HT20)	01	-24.682	8.00	Pass
	06	-25.003		
	11	-25.833		

802.11b

802.11g

CH01

CH01

CH06

CH06

CH11

CH11

802.11nHT20



CH01



CH06



CH11

4.5. 6dB Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=100 KHz and VBW=300KHz.
The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.
According to KDB558074 for one of the following procedures may be used to determine the modulated DTS device signal bandwidth.
1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

LIMIT

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

TEST RESULTS

Type	Channel	6dB Bandwidth (MHz)	Limit (KHz)	Result
802.11b	01	9.140	≥500	Pass
	06	9.154		
	11	9.156		
802.11g	01	16.43	≥500	Pass
	06	16.39		
	11	16.42		
802.11nHT20	01	17.63	≥500	Pass
	06	17.62		
	11	17.61		

802.11b



CH01

802.11g



CH01



CH06



CH06



CH11



CH11

802.11n HT20



CH01



CH06



CH11

4.6. Band Edge Compliance of RF Emission

TEST REQUIREMENT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE

According to KDB 558074 D01 for Antenna-port conducted measurement. Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz for peak detector and RBW=1MHz, VBW=10Hz for average detector.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.
6. Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 12.2.2, 12.2.3, and 12.2.4 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
7. Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see 12.2.5 for guidance on determining the applicable antenna gain)
8. Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
9. For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
10. Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:
    $E = EIRP - 20\log D + 104.8$

where:
E = electric field strength in dBμV/m,
EIRP = equivalent isotropic radiated power in dBm
D = specified measurement distance in meters.

11. Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.
12. Compare the resultant electric field strength level to the applicable regulatory limit.
13. Perform radiated spurious emission test dures until all measured frequencies were complete.

LIMIT

Below -20dB of the highest emission level in operating band.
Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a).

TEST RESULTS

Remark: Test site: Shenzhen CTL Testing Technology Co., Ltd.

4.6.1 For Radiated Bandedge Measurement

802.11b

Frequency(MHz):			**2412**			**Polarity:**			**HORIZONTAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2390.00	54.83	PK	74.00	19.17	1.00	79	60.14	27.49	3.32	36.12	-5.31
2390.00	41.78	AV	54.00	12.22	1.00	79	47.09	27.49	3.32	36.12	-5.31
Frequency(MHz):			**2412**			**Polarity:**			**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2390.00	56.88	PK	74.00	17.12	1.00	128	62.19	27.49	3.32	36.12	-5.31
2390.00	41.72	AV	54.00	12.28	1.00	128	47.03	27.49	3.32	36.12	-5.31
Frequency(MHz):			**2462**			**Polarity:**			**HORIZONTAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2483.50	57.36	PK	74.00	16.64	1.00	215	63.08	27.45	3.38	36.55	-5.72
2483.50	40.75	AV	54.00	13.25	1.00	215	46.47	27.45	3.38	36.55	-5.72
Frequency(MHz):			**2462**			**Polarity:**			**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2483.50	58.21	PK	74.00	15.79	1.00	162	63.93	27.45	3.38	36.55	-5.72
2483.50	40.48	AV	54.00	13.52	1.00	162	46.20	27.45	3.38	36.55	-5.72

802.11g

Frequency(MHz):			**2412**			**Polarity:**			**HORIZONTAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2390.00	58.21	PK	74.00	15.79	1.00	139	63.52	27.49	3.32	36.12	-5.31
2390.00	41.97	AV	54.00	12.03	1.00	139	47.28	27.49	3.32	36.12	-5.31
Frequency(MHz):			**2412**			**Polarity:**			**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2390.00	59.44	PK	74.00	14.56	1.00	227	64.75	27.49	3.32	36.12	-5.31
2390.00	40.60	AV	54.00	13.40	1.00	227	45.91	27.49	3.32	36.12	-5.31
Frequency(MHz):			**2462**			**Polarity:**			**HORIZONTAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2483.50	57.01	PK	74.00	16.99	1.00	165	62.73	27.45	3.38	36.55	-5.72
2483.50	42.22	AV	54.00	11.78	1.00	165	47.94	27.45	3.38	36.55	-5.72
Frequency(MHz):			**2462**			**Polarity:**			**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2483.50	55.51	PK	74.00	18.49	1.00	90	61.23	27.45	3.38	36.55	-5.72
2483.50	41.83	AV	54.00	12.17	1.00	90	47.55	27.45	3.38	36.55	-5.72

802.11n HT20

Frequency(MHz):			2412			Polarity:			HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2390.00	50.52	PK	74.00	23.48	1.00	168	55.83	27.49	3.32	36.12	-5.31
2390.00	41.79	AV	54.00	12.21	1.00	168	47.10	27.49	3.32	36.12	-5.31
Frequency(MHz):			**2412**			**Polarity:**			**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2390.00	51.34	PK	74.00	22.66	1.00	202	56.65	27.49	3.32	36.12	-5.31
2390.00	42.47	AV	54.00	11.53	1.00	202	47.78	27.49	3.32	36.12	-5.31
Frequency(MHz):			**2462**			**Polarity:**			**HORIZONTAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2483.50	50.39	PK	74.00	23.61	1.00	117	56.11	27.45	3.38	36.55	-5.72
2483.50	42.34	AV	54.00	11.66	1.00	117	48.06	27.45	3.38	36.55	-5.72
Frequency(MHz):			**2462**			**Polarity:**			**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2483.50	49.90	PK	74.00	24.10	1.00	146	55.62	27.45	3.38	36.55	-5.72
2483.50	43.09	AV	54.00	10.91	1.00	146	48.81	27.45	3.38	36.55	-5.72

4.6.2 For Conducted Bandedge Measurement

802.11b			
Frequency (MHz)	**Delta Peak to Band emission (dBc)**	**Limit (dBc)**	**Verdict**
2400.00	-37.83	-20	PASS
2483.50	-51.11	-20	PASS

2412



2462

802.11g			
Frequency (MHz)	**Delta Peak to Band emission (dBc)**	**Limit (dBc)**	**Verdict**
2400.00	-27.07	-20	PASS
2483.05	-35.67	-20	PASS

2412

2462

802.11n HT20			
Frequency (MHz)	**Delta Peak to Band emission (dBc)**	**Limit (dBc)**	**Verdict**
2400.00	-28.30	-20	PASS
2483.50	-33.56	-20	PASS

2412

2462

4.7. Spurious RF Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013, For 9KHz-150kHz, Set RBW=1kHz and VBW= 3KHz;For 150KHz-10MHz, Set RBW=10kHz and VBW= 30KHz:For 10MHz-25GHz ,Set RBW=100kHz and VBW= 300KHz in order to measure the peak field strength, and mwasure frequeny range from 9KHz to 25GHz.

LIMIT

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.
3.For below 30MHz,For 9KHz-150kHz,150K-10MHz,We use the RBW 1KHz,10KHz, So the limit need to calculated by “10lg(BW1/BW2)“. for example For9KHz-150kHz,RBW 1KHz, The Limit= the highest emission level-20-10log(100/1)= the highest emission level-40.

TEST RESULTS

Remark: The measurement frequency range is from 9KHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandege measurement data.