

FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency Range (MHz)	Antenna Gain		★Tune-up Output Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
BLE	2402~2480	1.98	1.58	1.0	1.26	20	0.0004	1.0
GSM 850	824-849	-0.47	0.90	25.81	381.07	20	0.0680	0.5493
GSM 1900	1850-1910	-0.57	0.88	22.81	190.99	20	0.0334	1.0
WCDMA II	1850-1910	-0.57	0.88	25	316.23	20	0.0554	1.0
WCDMA IV	1710-1755	-0.02	1.00	25	316.23	20	0.0629	1.0
WCDMA V	824-849	-0.47	0.90	25	316.23	20	0.0565	0.5493
LTE Band 2	1850-1910	-0.57	0.88	25	316.23	20	0.0554	1.0
LTE Band 4	1710-1755	-0.02	1.00	25	316.23	20	0.0629	1.0
LTE Band 5	824-849	-0.47	0.90	25	316.23	20	0.0565	0.5493
LTE Band 7	2500-2570	-0.90	0.81	25	316.23	20	0.0510	1.0
LTE Band 12	699-716	0.00	1.00	25	316.23	20	0.0629	0.466
LTE Band 13	777-787	-1.18	0.76	25	316.23	20	0.0429	0.518
LTE Band 25	1850-1915	-0.57	0.88	25	316.23	20	0.0554	1.0
LTE Band 26	814-824	-1.48	0.71	25	316.23	20	0.0447	0.5427
LTE Band 26	824-849	-0.47	0.09	25	316.23	20	0.0565	0.5493
LTE Band 38	2570-2620	0.76	1.19	25	316.23	20	0.0749	1.0
LTE Band 41	2496-2690	2.87	1.94	25	316.23	20	0.1220	1.0

Note:

1. For the above tune up power were declared by the manufacturer.
2. The EUT contains a certificated LTE module, FCC ID: XMR201903EG25G, Date of Grant: 2019/03/29

BLE, and 2G/3G/4G can transmit simultaneously, the worst case as below:

$$\sum_i \frac{S_i}{S_{Limit,i}} = 0.0004/1.0 + 0.0629/0.466 = 0.1354 < 1.0$$

Result: The device meet FCC MPE at 20 cm distance.