

APPLICATION CERTIFICATION
On Behalf of
IMC INTERNATIONAL INC.

5.5inch 3G TABLET
Model No.: FORCE XT55SP

FCC ID: 2ACI7-XT55SP

Prepared for : IMC INTERNATIONAL INC.
Address : 28E Jingang, Xixiang, Bao an District Shenzhen,
Guangdong Province,China
Prepared by : ACCURATE TECHNOLOGY CO. LTD
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report Number : ATE20141093
Date of Test : June 18-July 07,2014
Date of Report : July 07,2014

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	5
1.1. Description of Device (EUT).....	5
1.2. Description of Test Facility	5
1.3. Measurement Uncertainty	6
2. MEASURING DEVICE AND TEST EQUIPMENT	7
3. OPERATION OF EUT DURING TESTING	8
3.1. Operating Mode	8
3.2. Configuration and peripherals	8
4. TEST PROCEDURES AND RESULTS	9
5. 20DB BANDWIDTH TEST.....	10
5.1. Block Diagram of Test Setup.....	10
5.2. The Requirement For Section 15.247(a)(1).....	10
5.3. EUT Configuration on Measurement	10
5.4. Operating Condition of EUT	10
5.5. Test Procedure	11
5.6. Test Result	11
6. CARRIER FREQUENCY SEPARATION TEST.....	17
6.1. Block Diagram of Test Setup.....	17
6.2. The Requirement For Section 15.247(a)(1).....	17
6.3. EUT Configuration on Measurement	17
6.4. Operating Condition of EUT	17
6.5. Test Procedure	18
6.6. Test Result	18
7. NUMBER OF HOPPING FREQUENCY TEST	24
7.1. Block Diagram of Test Setup.....	24
7.2. The Requirement For Section 15.247(a)(1)(iii).....	24
7.3. EUT Configuration on Measurement	24
7.4. Operating Condition of EUT	24
7.5. Test Procedure	25
7.6. Test Result	25
8. DWELL TIME TEST	27
8.1. Block Diagram of Test Setup.....	27
8.2. The Requirement For Section 15.247(a)(1)(iii).....	27
8.3. EUT Configuration on Measurement	27
8.4. Operating Condition of EUT	27
8.5. Test Procedure	28
8.6. Test Result	28
9. MAXIMUM PEAK OUTPUT POWER TEST	44
9.1. Block Diagram of Test Setup.....	44
9.2. The Requirement For Section 15.247(b)(1).....	44
9.3. EUT Configuration on Measurement	44
9.4. Operating Condition of EUT	44
9.5. Test Procedure	45

9.6.	Test Result	45
10.	RADIATED EMISSION TEST	51
10.1.	Block Diagram of Test Setup.....	51
10.2.	The Limit For Section 15.247(d)	51
10.3.	Restricted bands of operation	52
10.4.	Configuration of EUT on Measurement	52
10.5.	est Procedure.....	53
10.6.	The Field Strength of Radiation Emission Measurement Results	53
11.	BAND EDGE COMPLIANCE TEST	66
11.1.	Block Diagram of Test Setup.....	66
11.2.	The Requirement For Section 15.247(d)	66
11.3.	EUT Configuration on Measurement	66
11.4.	Operating Condition of EUT	66
11.5.	Test Procedure	67
11.6.	Test Result	67
12.	AC POWER LINE CONDUCTED EMISSION FOR FCC PART 15 SECTION 15.207(A) ..	89
12.1.	Block Diagram of Test Setup.....	89
12.2.	The Emission Limit	89
12.3.	Configuration of EUT on Measurement	90
12.4.	Operating Condition of EUT	90
12.5.	Test Procedure	90
12.6.	Power Line Conducted Emission Measurement Results	90
13.	ANTENNA REQUIREMENT.....	93
13.1.	The Requirement	93
13.2.	Antenna Construction	93

Test Report Certification

Applicant : IMC INTERNATIONAL INC.
 Manufacturer : IMC INTERNATIONAL INC.
 EUT Description : 5.5inch 3G TABLET
 (A) MODEL NO.:FORCE XT55SP
 (B) Trade Name.: /
 (C) POWER SUPPLY: DC 3.7V (Battery) & DC 5V(USB Port)
 (D) Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247
 ANSI C63.4- 2009

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test : June 18-July 07,2014

Prepared by : 
 (Engineer)

Approved & Authorized Signer : 
 (Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	:	5.5inch 3G TABLET
Model Number	:	FORCE XT55SP
Frequency Range	:	GSM 850: 824.2-848.8 MHz 124 Channels GSM 1900 : 1850.2-1909.8 MHz 299 Channels FDD V: 826.4-846.6 MHz 277 Channels FDD II : 1852.4-1907.6 MHz 102 Channels 802.11b/g/n (20MHz): 2412-2462MHz 11 Channels 802.11n (40MHz): 2422-2452MHz 7 Channels Bluetooth 4.0 LE: 2402-2480MHz 40 Channels Bluetooth 2.1: 2402-2480MHz 79 Channels
Modulation	:	GSM GPRS: GMSK FDD: QPSK WLAN: CCK, OFDM BT: GFSK, Π/4-DQPSK, 8DPSK
Antenna Gain	:	0.5dBi(BT&WLAN) 1.5dBi(GSM & FDD)
Power Supply Adapter	:	DC 5V (USB Port) & DC 3.7V (Battery) Model number: UBP-A806-051000 Input: AC 100-240V; 50/60Hz Output: DC 5V/1000mA USB line: Non-shielded, Non-detachable, 1.5m
Applicant	:	IMC INTERNATIONAL INC.
Address	:	28E Jingang, Xixiang, Bao an District Shenzhen, Guangdong Province, China
Manufacturer	:	IMC INTERNATIONAL INC.
Address	:	28E Jingang, Xixiang, Bao an District Shenzhen, Guangdong Province, China
Date of sample received	:	June 18, 2014
Date of Test	:	June 18-July 07, 2014

1.2. Description of Test Facility

EMC Lab	:	Accredited by TUV Rheinland Shenzhen
		Listed by FCC
		The Registration Number is 752051
		Listed by Industry Canada
		The Registration Number is 5077A-2
		Accredited by China National Accreditation Committee for Laboratories
		The Certificate Registration Number is L3193
Name of Firm	:	ACCURATE TECHNOLOGY CO. LTD
Site Location	:	F1, Bldg. A, Changyuan New Material Port, Keyuan Rd. Science & Industry Park, Nanshan, Shenzhen, Guangdong P.R. China

1.3. Measurement Uncertainty

Conducted Emission Expanded Uncertainty	=	2.23dB, k=2
Radiated emission expanded uncertainty (9kHz-30MHz)	=	3.08dB, k=2
Radiated emission expanded uncertainty (30MHz-1000MHz)	=	4.42dB, k=2
Radiated emission expanded uncertainty (Above 1GHz)	=	4.06dB, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 11, 2014	Jan. 10, 2015
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 11, 2014	Jan. 10, 2015
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 11, 2014	Jan. 10, 2015
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 11, 2014	Jan. 10, 2015
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 15, 2014	Jan. 14, 2015
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 15, 2014	Jan. 14, 2015
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 15, 2014	Jan. 14, 2015
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1067	Jan. 15, 2014	Jan. 14, 2015
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 11, 2014	Jan. 10, 2015
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 11, 2014	Jan. 10, 2015

3. OPERATION OF EUT DURING TESTING

3.1.Operating Mode

The mode is used: Transmitting mode

Low Channel: 2402MHz

Middle Channel: 2441MHz

High Channel: 2480MHz

Hopping

3.2.Configuration and peripherals

EUT


(EUT: 5.5inch 3G TABLET)

4. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission Test	Compliant
Section 15.247(a)(1)	20dB Bandwidth Test	Compliant
Section 15.247(a)(1)	Carrier Frequency Separation Test	Compliant
Section 15.247(a)(1)(iii)	Number Of Hopping Frequency Test	Compliant
Section 15.247(a)(1)(iii)	Dwell Time Test	Compliant
Section 15.247(b)(1)	Maximum Peak Output Power Test	Compliant
Section 15.247(d) Section 15.209	Radiated Emission Test	Compliant
Section 15.247(d)	Band Edge Compliance Test	Compliant
Section 15.203	Antenna Requirement	Compliant

5. 20DB BANDWIDTH TEST

5.1. Block Diagram of Test Setup



(EUT: 5.5inch 3G TABLET)

5.2. The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

5.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.4. Operating Condition of EUT

5.4.1. Setup the EUT and simulator as shown as Section 5.1.

5.4.2. Turn on the power of all equipment.

5.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

5.5. Test Procedure

5.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

5.5.2. Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz.

5.5.3. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.


5.6. Test Result

Channel	Frequency (MHz)	GFSK 20dB Bandwidth (MHz)	$\Pi/4$ -DQPSK 20dB Bandwidth (MHz)	8DPSK 20dB Bandwidth (MHz)	Result
Low	2402	0.708	1.116	1.160	Pass
Middle	2441	0.704	1.116	1.164	Pass
High	2480	0.704	1.112	1.164	Pass


The spectrum analyzer plots are attached as below.

GFSK Mode


Low channel



Middle channel




High channel




$\Pi/4$ -DQPSK Mode


Low channel





Middle channel




High channel




8DPSK Mode





6. CARRIER FREQUENCY SEPARATION TEST

6.1. Block Diagram of Test Setup



(EUT: 5.5inch 3G TABLET)

6.2. The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

6.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

6.5. Test Procedure

- 6.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.
- 6.5.2. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz. Adjust Span to 3 MHz.
- 6.5.3. Set the adjacent channel of the EUT maxhold another trace.
- 6.5.4. Measurement the channel separation

6.6. Test Result

GFSK

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.002	25KHz or 20dB bandwidth	PASS
	2403			
Middle	2441	1.002	25KHz or 20dB bandwidth	PASS
	2442			
High	2479	1.158	25KHz or 20dB bandwidth	PASS
	2480			

Π/4-DQPSK

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.002	25KHz or 2/3*20dB bandwidth	PASS
	2403			
Middle	2441	1.002	25KHz or 2/3*20dB bandwidth	PASS
	2442			
High	2479	1.002	25KHz or 2/3*20dB bandwidth	PASS
	2480			


8QPSK

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.000	25KHz or 2/3*20dB bandwidth	PASS
	2403			
Middle	2441	1.004	25KHz or 2/3*20dB bandwidth	PASS
	2442			
High	2479	1.004	25KHz or 2/3*20dB bandwidth	PASS
	2480			


The spectrum analyzer plots are attached as below.

GFSK Mode


Low channel



Middle channel






High channel





$\Pi/4$ -DQPSK Mode


Low channel






8DPSK Mode





7. NUMBER OF HOPPING FREQUENCY TEST

7.1. Block Diagram of Test Setup



(EUT: 5.5inch 3G TABLET)

7.2. The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

7.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4. Operating Condition of EUT

7.4.1. Setup the EUT and simulator as shown as Section 7.1.

7.4.2. Turn on the power of all equipment.

7.4.3. Let the EUT work in TX (Hopping on) modes measure it.

7.5. Test Procedure


- 7.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.
- 7.5.2. Set the spectrum analyzer as Span=83.5MHz, RBW=100 kHz, VBW=300 kHz.
- 7.5.3. Max hold, view and count how many channel in the band.

7.6. Test Result


Total number of hopping channel	Measurement result(CH)	Limit(CH)
	79	≥ 15

The spectrum analyzer plots are attached as below.


Number of hopping channels(GFSK)



Number of hopping channels($\Pi/4$ -DQPSK)




Number of hopping channels(8QPSK)



8. DWELL TIME TEST

8.1. Block Diagram of Test Setup



(EUT: 5.5inch 3G TABLET)

8.2. The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

8.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

8.4. Operating Condition of EUT

8.4.1. Setup the EUT and simulator as shown as Section 8.1.

8.4.2. Turn on the power of all equipment.

8.4.3. Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

8.5. Test Procedure

- 8.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.
- 8.5.2. Set center frequency of spectrum analyzer = operating frequency.
- 8.5.3. Set the spectrum analyzer as RBW=100 kHz, VBW=300 kHz, Span=0Hz, Adjust Sweep=1s. Get the burst (in 1 sec.).
- 8.5.4. Set the spectrum analyzer as RBW=1MHz, VBW=3MHz, Span=0Hz, Adjust Sweep=2ms. Get the pulse time.
- 8.5.5. Repeat above procedures until all frequency measured were complete.

8.6. Test Result

GFSK Mode

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2402	0.440	140.80	400
	2441	0.430	137.60	400
	2480	0.425	136.00	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2 \times 79)) \times 31.6$				
DH3	2402	1.705	272.80	400
	2441	1.705	272.80	400
	2480	1.745	279.20	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4 \times 79)) \times 31.6$				
DH5	2402	3.085	329.07	400
	2441	3.085	329.07	400
	2480	3.025	322.67	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6 \times 79)) \times 31.6$				

Π/4-DQPSK



Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2402	0.415	132.80	400
	2441	0.420	134.40	400
	2480	0.420	134.40	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2 \times 79)) \times 31.6$				
DH3	2402	1.695	271.20	400
	2441	1.695	271.20	400
	2480	1.695	271.20	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4 \times 79)) \times 31.6$				
DH5	2402	2.960	315.73	400
	2441	2.960	315.73	400
	2480	2.960	315.73	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6 \times 79)) \times 31.6$				



8QPSK Mode



Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2402	0.420	134.40	400
	2441	0.420	134.40	400
	2480	0.420	134.40	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(2 \times 79)) \times 31.6$				
DH3	2402	1.680	268.80	400
	2441	1.680	268.80	400
	2480	1.695	271.20	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(4 \times 79)) \times 31.6$				
DH5	2402	3.010	321.07	400
	2441	3.010	321.07	400
	2480	3.040	324.27	400
A period transmit time = $0.4 \times 79 = 31.6$ Dwell time = pulse time $\times (1600/(6 \times 79)) \times 31.6$				



The spectrum analyzer plots are attached as below.


Mode 1: GFSK Link Mode




















Mode 2: $\pi/4$ DQPSK Link Mode
















Mode 3: 8DPSK Link Mode









3DH3 Middle channel



3DH3 High channel








9. MAXIMUM PEAK OUTPUT POWER TEST

9.1. Block Diagram of Test Setup



(EUT: 5.5inch 3G TABLET)

9.2. The Requirement For Section 15.247(b)(1)

Section 15.247(b)(1): For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

9.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

9.4. Operating Condition of EUT

9.4.1. Setup the EUT and simulator as shown as Section 9.1.

9.4.2. Turn on the power of all equipment.

9.4.3. Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

9.5. Test Procedure

9.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

9.5.2. Set RBW of spectrum analyzer to 1MHz and VBW to 3MHz for GFSK mode

9.5.3. Set RBW of spectrum analyzer to 3MHz and VBW to 10MHz for other mode

9.5.4. Measurement the maximum peak output power.

9.6. Test Result

GFSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm)	Limits dBm / W
Low	2402	4.28	30/1.0
Middle	2441	3.64	30/1.0
High	2480	1.79	30/1.0

Π/4-DQPSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm)	Limits dBm / W
Low	2402	4.35	21 / 0.125
Middle	2441	3.74	21 / 0.125
High	2480	1.87	21 / 0.125


8QPSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm)	Limits dBm / W
Low	2402	4.41	21 / 0.125
Middle	2441	3.74	21 / 0.125
High	2480	1.93	21 / 0.125


The spectrum analyzer plots are attached as below.

GFSK Mode


Low channel



Middle channel




High channel




II/4-DQPSK Mode


Low channel



Middle channel




High channel




8QPSK Mode


Low channel



Middle channel




High channel



10.RADIATED EMISSION TEST


10.1.Block Diagram of Test Setup

10.1.1.Block diagram of connection between the EUT and simulators



(EUT: 5.5inch 3G TABLET)

10.1.2.Anechoic Chamber Test Setup Diagram



10.2.The Limit For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

10.3.Restricted bands of operation

10.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

²Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

10.4.Configuration of EUT on Measurement

The equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

10.5. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4- 2009 on radiated emission measurement.

RBW (120 kHz), VBW (300 kHz) for QP detector below 1GHz

RBW (1 MHz), VBW (3MHz) for Peak detector above 1GHz

RBW (1 MHz), VBW (10Hz) for AV detector above 1GHz (duty cycle $\geq$ 98 percent)

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

10.6. The Field Strength of Radiation Emission Measurement Results

Note: 1. We tested GFSK mode, $\Pi/4$ -DQPSK Mode & 8QPSK mode and recorded the worst case data (GFSK mode) for all test mode.

2. The fundamental radiated emissions were reduced by 2.4G Band Reject Filter in the attached plots.

3. The 18-25GHz emissions are not reported, because the levels are too low against the limit.



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1855

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5"3G TABLET
5.5inch 3G TABLET

Mode: 1A 2402MHz

Model: Force XT55SP

Manufacturer: IMC

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 14/06/26/

Time: 16:03:21

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	39.7146	50.90	-20.08	30.82	40.00	-9.18	QP			
2	45.2165	51.29	-20.39	30.90	40.00	-9.10	QP			
3	114.9168	51.33	-22.35	28.98	43.50	-14.52	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1856

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2402MHz

Model: Force XT55SP

Manufacturer: IMC

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2014/06/26

Time: 16:07:01

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	34.7602	40.31	-19.42	20.89	40.00	-19.11	QP			
2	127.6645	47.73	-22.91	24.82	43.50	-18.68	QP			
3	259.2338	41.73	-19.18	22.55	46.00	-23.45	QP			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RICKY #1857
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 5.5inch 3G TABLET
Mode: TX 2441MHz
Model: Force XT55SP
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2014/06/26
Time: 16:07:55
Engineer Signature:
Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	35.3750	40.28	-19.56	20.72	40.00	-19.28	QP			
2	127.6645	48.54	-22.91	25.63	43.50	-17.87	QP			
3	259.2338	40.71	-19.18	21.53	46.00	-24.47	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1858

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2441MHz

Model: Force XT55SP

Manufacturer: IMC

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2014/06/26

Time: 16:09:16

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	39.8542	52.56	-20.08	32.48	40.00	-7.52	QP			
2	45.0583	52.11	-20.38	31.73	40.00	-8.27	QP			
3	126.3286	53.97	-22.86	31.11	43.50	-12.39	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1859

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2480MHz

Model: Force XT55SP

Manufacturer: IMC

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2014/06/26

Time: 16:10:13

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	39.5757	52.11	-20.06	32.05	40.00	-7.95	QP			
2	45.0583	51.86	-20.38	31.48	40.00	-8.52	QP			
3	127.2176	53.96	-22.90	31.06	43.50	-12.44	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1860

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2480MHz

Model: Force XT55SP

Manufacturer: IMC

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2014/06/26

Time: 16:11:01

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	34.5173	40.43	-19.34	21.09	40.00	-18.91	QP			
2	127.6645	47.29	-22.91	24.38	43.50	-19.12	QP			
3	258.3264	40.41	-19.25	21.16	46.00	-24.84	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1866

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2402MHz

Model: Force XT55SP

Manufacturer: IMC

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2014/06/26

Time: 16:28:51

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	6776.265	43.00	5.13	48.13	54.00	-5.87	peak			
2	11140.310	39.21	10.86	50.07	54.00	-3.93	peak			
3	16457.318	1.81	49.14	50.95	54.00	-3.05	peak			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1865

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2402MHz

Model: Force XT55SP

Manufacturer: IMC

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2014/06/26

Time: 16:27:33

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	3958.309	45.16	-1.49	43.67	54.00	-10.33	peak			
2	8514.456	40.34	8.87	49.21	54.00	-4.79	peak			
3	11837.445	37.62	13.08	50.70	54.00	-3.30	peak			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1864

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2441MHz

Model: Force XT55SP

Manufacturer: IMC

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2014/06/26

Time: 16:26:12

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	6776.265	43.00	5.13	48.13	54.00	-5.87	peak			
2	9420.880	37.96	10.51	48.47	54.00	-5.53	peak			
3	11140.310	39.21	10.86	50.07	54.00	-3.93	peak			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1863

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2441MHz

Model: Force XT55SP

Manufacturer: IMC

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 2014/06/26

Time: 16:24:28

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	5697.365	45.12	2.24	47.36	54.00	-6.64	peak			
2	9205.540	40.45	9.27	49.72	54.00	-4.28	peak			
3	11837.445	37.62	13.08	50.70	54.00	-3.30	peak			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1862

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2480MHz

Model: Force XT55SP

Manufacturer: IMC

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 2014/06/26

Time: 16:23:56

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	6776.265	43.00	5.13	48.13	54.00	-5.87	peak			
2	9420.880	37.96	10.51	48.47	54.00	-5.53	peak			
3	11140.310	39.21	10.86	50.07	54.00	-3.93	peak			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RICKY #1861
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: 5.5inch 3G TABLET
Mode: TX 2480MHz
Model: Force XT55SP
Manufacturer: IMC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 2014/06/26
Time: 16:16:14
Engineer Signature:
Distance: 3m


Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	8514.456	40.34	8.87	49.21	54.00	-4.79	peak			
2	11204.896	39.30	10.99	50.29	54.00	-3.71	peak			
3	14408.425	0.42	49.99	50.41	54.00	-3.59	peak			

11.BAND EDGE COMPLIANCE TEST

11.1.Block Diagram of Test Setup



(EUT: 5.5inch 3G TABLET)

11.2.The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

11.3.EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

11.4.Operating Condition of EUT

11.4.1.Setup the EUT and simulator as shown as Section 11.1.

11.4.2.Turn on the power of all equipment.

11.4.3.Let the EUT work in TX (Hopping off, Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2480MHz TX frequency to transmit.

11.5. Test Procedure

11.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.

11.5.2. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz with convenient frequency span including 100 kHz bandwidth from band edge.

11.5.3. For radiated band edge

The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.

The turntable was rotated for 360 degrees to determine the position of maximum emission level.

EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.



Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:



Set RBW (1 MHz), VBW (3MHz) for Peak detector, RBW (1 MHz), VBW (10Hz) for AV detector.



11.5.4. The band edges was measured and recorded.

11.6. Test Result

Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
GFSK		
2399.880	47.01	> 20dBc
2483.998	45.80	> 20dBc
Π/4-DQPSK Mode		
2399.802	46.36	> 20dBc
2484.838	44.24	> 20dBc
8QPSK		
2399.750	46.36	> 20dBc
2483.788	44.21	> 20dBc







Radiated Band Edge Result

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

3. Display the measurement of peak values.

Non-hopping mode



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1928

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2402MHz (GFSK)

Model: Force XT55SP

Manufacturer: IMC

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 14/06/27/

Time: 20/12/37

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2368.110	46.37	-7.72	38.65	74.00	-35.35	peak			
2	2368.110	41.38	-7.72	33.66	54.00	-20.34	AVG			
3	2390.000	44.19	-7.57	36.62	74.00	-37.38	peak			
4	2390.000	39.49	-7.57	31.92	54.00	-22.08	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1929

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2402MHz (GFSK)

Model: Force XT55SP

Manufacturer: IMC

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 14/06/27/

Time: 20/13/24

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2385.140	45.34	-7.61	37.73	74.00	-36.27	peak			
2	2385.140	40.18	-7.61	32.57	54.00	-21.43	AVG			
3	2390.000	43.73	-7.57	36.16	74.00	-37.84	peak			
4	2390.000	38.36	-7.57	30.79	54.00	-23.21	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1927

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2480MHz (GFSK)

Model: Force XT55SP

Manufacturer: IMC

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 14/06/27/

Time: 20/11/15

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	48.69	-7.38	41.31	74.00	-32.69	peak			
2	2483.500	43.30	-7.38	35.92	54.00	-18.08	AVG			
3	2484.220	49.31	-7.39	41.92	74.00	-32.08	peak			
4	2484.220	44.16	-7.39	36.77	54.00	-17.23	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1926

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2480MHz (GFSK)

Model: Force XT55SP

Manufacturer: IMC

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 14/06/27/

Time: 20/10/21

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	48.01	-7.38	40.63	74.00	-33.37	peak			
2	2483.500	42.53	-7.38	35.15	54.00	-18.85	AVG			
3	2484.400	49.55	-7.39	42.16	74.00	-31.84	peak			
4	2484.400	44.19	-7.39	36.80	54.00	-17.20	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1932

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2402MHz (PI/4DQPSK)

Model: Force XT55SP

Manufacturer: IMC

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 14/06/27/

Time: 20/16/41

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2368.110	46.21	-7.72	38.49	74.00	-35.51	peak			
2	2368.110	41.58	-7.72	33.86	54.00	-20.14	AVG			
3	2390.000	44.26	-7.57	36.69	74.00	-37.31	peak			
4	2390.000	39.61	-7.57	32.04	54.00	-21.96	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1933

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2402MHz (PI/4DQPSK)

Model: Force XT55SP

Manufacturer: IMC

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 14/06/27/

Time: 20/17/27

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2368.110	46.24	-7.72	38.52	74.00	-35.48	peak			
2	2368.110	41.22	-7.72	33.50	54.00	-20.50	AVG			
3	2390.000	44.24	-7.57	36.67	74.00	-37.33	peak			
4	2390.000	39.53	-7.57	31.96	54.00	-22.04	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1930

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2480MHz (PI/4DQPSK)

Model: Force XT55SP

Manufacturer: IMC

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 14/06/27/

Time: 20/14/38

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	48.05	-7.38	40.67	74.00	-33.33	peak			
2	2483.500	42.58	-7.38	35.20	54.00	-18.80	AVG			
3	2484.400	49.45	-7.39	42.06	74.00	-31.94	peak			
4	2484.400	44.09	-7.39	36.70	54.00	-17.30	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1931

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2480MHz (PI/4DQPSK)

Model: Force XT55SP

Manufacturer: IMC

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 14/06/27/

Time: 20/15/28

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	48.67	-7.38	41.29	74.00	-32.71	peak			
2	2483.500	43.35	-7.38	35.97	54.00	-18.03	AVG			
3	2484.220	49.29	-7.39	41.90	74.00	-32.10	peak			
4	2484.220	44.08	-7.39	36.69	54.00	-17.31	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1887

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2402MHz (8DPSK)

Model: Force XT55SP

Manufacturer: IMC

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 14/06/27/

Time: 9/27/57

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2385.140	45.01	-7.61	37.40	74.00	-36.60	peak			
2	2385.140	40.00	-7.61	32.39	54.00	-21.61	AVG			
3	2390.000	43.70	-7.57	36.13	74.00	-37.87	peak			
4	2390.000	38.27	-7.57	30.70	54.00	-23.30	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1886

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2402MHz (8DPSK)

Model: Force XT55SP

Manufacturer: IMC

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 14/06/27/

Time: 9/26/30

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2368.110	46.24	-7.72	38.52	74.00	-35.48	peak			
2	2368.110	41.22	-7.72	33.50	54.00	-20.50	AVG			
3	2390.000	44.24	-7.57	36.67	74.00	-37.33	peak			
4	2390.000	39.53	-7.57	31.96	54.00	-22.04	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1885

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2480MHz(8DPSK)

Model: Force XT55SP

Manufacturer: IMC

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 14/06/27/

Time: 9/23/29

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	48.71	-7.38	41.33	74.00	-32.67	peak			
2	2483.500	43.27	-7.38	35.89	54.00	-18.11	AVG			
3	2484.220	49.32	-7.39	41.93	74.00	-32.07	peak			
4	2484.220	44.18	-7.39	36.79	54.00	-17.21	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1884

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: TX 2480MHz (8DPSK)

Model: Force XT55SP

Manufacturer: IMC

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 14/06/27/

Time: 9/22/00

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	47.90	-7.38	40.52	74.00	-33.48	peak			
2	2483.500	42.61	-7.38	35.23	54.00	-18.77	AVG			
3	2484.400	49.45	-7.39	42.06	74.00	-31.94	peak			
4	2484.400	44.13	-7.39	36.74	54.00	-17.26	AVG			

Hopping mode



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1889

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: HOPPING(GFSK)

Model: Force XT55SP

Manufacturer: IMC

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 14/06/27/

Time: 9/40/50

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2364.200	46.29	-7.74	38.55	74.00	-35.45	peak			
2	2364.200	41.03	-7.74	33.29	54.00	-20.71	AVG			
3	2390.000	44.26	-7.57	36.69	74.00	-37.31	peak			
4	2390.000	38.67	-7.57	31.10	54.00	-22.90	AVG			
5	2483.500	46.34	-7.38	38.96	74.00	-35.04	peak			
6	2483.500	41.21	-7.38	33.83	54.00	-20.17	AVG			
7	2504.600	48.72	-7.37	41.35	74.00	-32.65	peak			
8	2504.600	43.38	-7.37	36.01	54.00	-17.99	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1888

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: HOPPING(GFSK)

Model: Force XT55SP

Manufacturer: IMC

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 14/06/27/

Time: 9/33/37

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2376.800	45.59	-7.66	37.93	74.00	-36.07	peak			
2	2376.800	40.21	-7.66	32.55	54.00	-21.45	AVG			
3	2390.000	44.48	-7.57	36.91	74.00	-37.09	peak			
4	2390.000	39.11	-7.57	31.54	54.00	-22.46	AVG			
5	2483.500	46.20	-7.38	38.82	74.00	-35.18	peak			
6	2483.500	41.02	-7.38	33.64	54.00	-20.36	AVG			
7	2491.700	47.05	-7.39	39.66	74.00	-34.34	peak			
8	2491.700	41.93	-7.39	34.54	54.00	-19.46	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1922

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: HOPPING(PI/4DQPSK)

Model: Force XT55SP

Manufacturer: IMC

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 14/06/27/

Time: 19/42/32

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2376.800	46.10	-7.66	38.44	74.00	-35.56	peak			
2	2376.800	40.19	-7.66	32.53	54.00	-21.47	AVG			
3	2390.000	44.85	-7.57	37.28	74.00	-36.72	peak			
4	2390.000	39.17	-7.57	31.60	54.00	-22.40	AVG			
5	2483.500	46.37	-7.38	38.99	74.00	-35.01	peak			
6	2483.500	40.97	-7.38	33.59	54.00	-20.41	AVG			
7	2491.700	47.23	-7.39	39.84	74.00	-34.16	peak			
8	2491.700	41.86	-7.39	34.47	54.00	-19.53	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1923

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: HOPPING(PI/4DQPSK)

Model: Force XT55SP

Manufacturer: IMC

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 14/06/27/

Time: 19/43/28

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2364.200	46.37	-7.74	38.63	74.00	-35.37	peak			
2	2364.200	41.10	-7.74	33.36	54.00	-20.64	AVG			
3	2390.000	44.31	-7.57	36.74	74.00	-37.26	peak			
4	2390.000	38.72	-7.57	31.15	54.00	-22.85	AVG			
5	2483.500	46.67	-7.38	39.29	74.00	-34.71	peak			
6	2483.500	41.30	-7.38	33.92	54.00	-20.08	AVG			
7	2504.600	48.62	-7.37	41.25	74.00	-32.75	peak			
8	2504.600	43.35	-7.37	35.98	54.00	-18.02	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1924

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: HOPPING(8DPSK)

Model: Force XT55SP

Manufacturer: IMC

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 14/06/27/

Time: 19/44/25

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2376.800	45.62	-7.66	37.96	74.00	-36.04	peak			
2	2376.800	40.30	-7.66	32.64	54.00	-21.36	AVG			
3	2390.000	44.51	-7.57	36.94	74.00	-37.06	peak			
4	2390.000	39.14	-7.57	31.57	54.00	-22.43	AVG			
5	2483.500	46.19	-7.38	38.81	74.00	-35.19	peak			
6	2483.500	41.00	-7.38	33.62	54.00	-20.38	AVG			
7	2491.700	47.12	-7.39	39.73	74.00	-34.27	peak			
8	2491.700	42.01	-7.39	34.62	54.00	-19.38	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: RICKY #1925

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: 5.5inch 3G TABLET

Mode: HOPPING(8DPSK)

Model: Force XT55SP

Manufacturer: IMC

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 14/06/27/

Time: 19/45/52

Engineer Signature:

Distance: 3m

Note: Report No:ATE20141093




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2364.200	46.68	-7.74	38.94	74.00	-35.06	peak			
2	2364.200	41.11	-7.74	33.37	54.00	-20.63	AVG			
3	2390.000	44.33	-7.57	36.76	74.00	-37.24	peak			
4	2390.000	38.72	-7.57	31.15	54.00	-22.85	AVG			
5	2483.500	46.38	-7.38	39.00	74.00	-35.00	peak			
6	2483.500	41.23	-7.38	33.85	54.00	-20.15	AVG			
7	2504.600	48.61	-7.37	41.24	74.00	-32.76	peak			
8	2504.600	43.35	-7.37	35.98	54.00	-18.02	AVG			

12.AC POWER LINE CONDUCTED EMISSION FOR FCC PART 15 SECTION 15.207(A)

12.1.Block Diagram of Test Setup

12.1.1.Block diagram of connection between the EUT and simulators

12.1.2.Shielding Room Test Setup Diagram



(EUT: 5.5inch 3G TABLET)

12.2.The Emission Limit

12.2.1.Conducted Emission Measurement Limits According to Section 15.207(a)

Frequency (MHz)	Limit dB(μ V)	
	Quasi-peak Level	Average Level
0.15 - 0.50	66.0 – 56.0 *	56.0 – 46.0 *
0.50 - 5.00	56.0	46.0
5.00 - 30.00	60.0	50.0

* Decreases with the logarithm of the frequency.

12.3.Configuration of EUT on Measurement

The equipment are installed on the Conducted Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

12.4.Operating Condition of EUT

12.4.1.Setup the EUT and simulator as shown as Section 11.1.

12.4.2.Turn on the power of all equipment.

12.4.3.Let the EUT work in TX (Operation) mode measure it.

12.5.Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.4- 2009 on Conducted Emission Measurement.

The bandwidth of test receiver (R & S ESCS30) is set at 9 kHz.

The frequency range from 150 kHz to 30MHz is checked.

12.6.Power Line Conducted Emission Measurement Results


ACCURATE TECHNOLOGY CO.,LTD
CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: 5.5inch 3G TABLET M/N:Force XT55SP
 Manufacturer: IMC
 Operating Condition: BT3.0/Charging
 Test Site: 1#Shielding Room
 Operator: Ricky
 Test Specification: N 120V/60Hz
 Comment:

Report No:ATE20141093

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average


MEASUREMENT RESULT: "RY0625-21_fin"

6/25/2014 4:22PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.151204	45.40	10.5	66	20.5	QP	N	GND
0.174947	39.70	10.5	65	25.0	QP	N	GND
1.247028	30.10	10.9	56	25.9	QP	N	GND

MEASUREMENT RESULT: "RY0625-21_fin2"

6/25/2014 4:22PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.207330	28.30	10.5	53	25.0	AV	N	GND
0.517701	30.00	10.7	46	16.0	AV	N	GND
1.350781	24.20	10.9	46	21.8	AV	N	GND

ACCURATE TECHNOLOGY CO.,LTD


CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: 5.5inch 3G TABLET/M/N:Force XT55SP
 Manufacturer: IMC
 Operating Condition: BT3.0/Charging
 Test Site: 1#Shielding Room
 Operator: Ricky
 Test Specification: L 120V/60Hz
 Comment:

Report No:ATE20141093

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 4.5 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "RY0625-22_fin"

6/25/2014 4:25PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.153333	44.20	10.5	66	21.6	QP	L1	GND
0.172517	42.20	10.5	65	22.6	QP	L1	GND
1.244539	29.00	10.9	56	27.0	QP	L1	GND

MEASUREMENT RESULT: "RY0625-22_fin2"

6/25/2014 4:25PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.206916	27.80	10.5	53	25.5	AV	L1	GND
0.517701	29.00	10.7	46	17.0	AV	L1	GND
1.448622	24.40	10.9	46	21.6	AV	L1	GND

13.ANTENNA REQUIREMENT

13.1.The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

13.2.Antenna Construction

The antenna is PCB Layout antenna, no consideration of replacement. Therefore, the equipment complies with the antenna requirement of Section 15.203.

