

Project No: TM-2606000400P
Report No.: TMTN2606000585NR

FCC ID: 2ACIA-TTBT021

Page: 1 / 105
Rev.: 00

FCC 47 CFR PART 15 SUBPART E: 2013 AND ANSI C63.10:2020 TEST REPORT

For

40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit

Model: A-1499WPT

Brand Name : N/A

Issued for

Ten Tronics Co., Ltd

No. 33, Lane 347, Chung-San S.Road Young-Kang District, Tainan, Taiwan

Issued by

Compliance Certification Services Inc.

Tainan Lab.

**No. 168, Ln. 523, Sec. 3, Zhongzheng Rd.,
Rende Dist., Tainan City, 717017, Taiwan**

Issued Date: August 20, 2026

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF or any government agencies. The test results of this report relate only to the tested sample identified in this report.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: TMTN2606000585NR

Page: 2 / 105
Rev.: 00

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	August 20, 2026	Initial Issue	ALL	Polly Wang

TABLE OF CONTENTS

TITLE	PAGE NO.
1. TEST REPORT CERTIFICATION	4
2. EUT DESCRIPTION	5
3. DESCRIPTION OF TEST MODES	6
4. TEST METHODOLOGY	6
5. FACILITIES AND ACCREDITATION	7
6. SETUP OF EQUIPMENT UNDER TEST	10
7. FCC PART 15.407 REQUIREMENTS	13
7.1 99% BANDWIDTH	13
7.2 26dB BANDWIDTH	19
7.3 6dB BANDWIDTH	24
7.4 MAXIMUM CONDUCTED OUTPUT POWER	28
7.5 PEAK POWER SPECTRAL DENSITY	34
7.6 DUTY CYCLE.....	41
7.7 CONDUCTED SPURIOUS EMISSION	46
7.8 RADIATED EMISSION.....	54
7.9 CONDUCTED EMISSION	82
7.10 FREQUENCY STABILITY	89
APPENDIX II SETUP PHOTOS	91

1. TEST REPORT CERTIFICATION

Applicant : **Ten Tronics Co., Ltd**
No. 33, Lane 347, Chung-San S.Road Young-Kang
District, Tainan, Taiwan

Manufacturer : **Ten Tronics Co., Ltd**
No. 33, Lane 347, Chung-San S.Road Young-Kang
District, Tainan, Taiwan

Equipment Under Test : 40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit

Model : A-1499WPT


Brand : N/A

Date of Test : July 04, 2026 ~ July 15, 2026

APPLICABLE STANDARD	
Standard	Test Result
FCC 47 CFR PART 15 SUBPART E AND ANSI C63.10:2020	PASS

WE HEREBY CERTIFY THAT: The above equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:



Vision Chang
Team Leader

2. EUT DESCRIPTION

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit
Model Number	A-1499WPT
Brand Name	N/A
Received Date	June 25, 2026
Reported Date	August 10, 2026
Frequency Range	Band 1: 5160~5240MHz, Band 4: 5730~5845MHz
Transmit Power	GFSK (5.2G) Mode: -6.71 dBm GFSK (5.8G) Mode: -2.47 dBm
Channel Spacing	2 MHz
Channel Number	GFSK (5.2G) Mode: 44 Channels GFSK (5.8G) Mode: 59 Channels
Transmit Data Rate	2 Mbps
Type of Modulation	GFSK
Antenna Type	5GHz Antenna (1TX1RX) Manufacture: Everestek Inc. Type: Wide-Band Antenna on Module Model: ETK52 Gain: 5.2G for 0.48 dBi, 5.8G for 0.26 dBi
Power Rating	24Vdc; 2.5A(Powered from Adapter)
Test Voltage	24Vdc
Firmware Version	V1.0
Software Version	V1.0

Remark :

1. Client consigns only one model sample to test (Model Number: A-1499WPT).
2. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.
3. For more details, please refer to the User's manual of the EUT.
4. This submittal(s) (test report) is intended for FCC ID: **2ACIA-TTBT021** filing to comply with Section 15.407, of the FCC Part 15, Subpart E Rules.
5. According to customer declaration 40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit (A-1499WPT / FCC ID: 2ACIA-TTBT021) and 40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit (A-1499WPR / FCC ID: 2ACIA-TTBT022) for sale.

3. DESCRIPTION OF TEST MODES

Conducted Emission / Radiated Emission Test (Below 1 GHz)

2. The following test modes were scanned during the preliminary test:

No.	Pre-Test Mode
1	TX Mode

2. After the preliminary scan, the following test mode was found to produce the highest emission level.

Final Test Mode		
Emission	Radiated Emission	TX Mode
	Conducted Emission	BT+5G LINK
		AUDIO IN

Remark : Then, the above highest emission mode of the configuration of the EUT and cable was chosen for all final test items.

Conducted / Radiated Emission Test (Above 1 GHz)

GFSK (5.2G) mode / 5160MHz ~ 5240MHz

The EUT had been tested under operating condition.

There are three channels have been tested as following :

Channel	Frequency (MHz)
Low	5160
Middle	5200
High	5240

GFSK (5.8G) mode / 5730MHz ~ 5845MHz

Channel	Frequency (MHz)
Low	5730
Middle	5785
High	5845

GFSK (5.2G) mode / GFSK (5.8G) mode:

2Mbps data rate (worst case) were chosen for full testing.

4. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10 and FCC CFR 47, 15.207, 15.209 and 15.407.

5. FACILITIES AND ACCREDITATION

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

- ☐ No.8, Jiucengling, Xinhua Dist., Tainan City 712, Taiwan (R.O.C.)
- ☒ No. 168, Ln. 523, Sec. 3, Zhongzheng Rd., Rende Dist., Tainan City 717, Taiwan

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 LABORATORY ACCREDITATIONS LISTINGS

The test facilities used to perform radiated and conducted emissions tests are accredited by Taiwan Accreditation Foundation for the specific scope of accreditation under Lab Code: 1109 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by TAF or any agency of the Government. In addition, the test facilities are listed with Federal Communications Commission (registration no: TW0035).



5.4 TABLE OF ACCREDITATIONS AND LISTINGS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

Taiwan	TAF
--------	-----

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada	Industry Canada (ISED#: 2324H)
Germany	TUV NORD
Taiwan	BSMI
USA	FCC

5.5 MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

5.6 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Measurement	Uncertainty
AC Powerline Conducted Emission	$\pm 2.21\text{dB}$
Channel Bandwidth	$\pm 2.87\%$
RF output power (Spectrum)	$\pm 2.88\text{dB}$
RF Output power (Power Meter & Power sensor)	$\pm 0.243\text{dB}$
Power Density	$\pm 2.87\text{dB}$
Conducted Badnedge	$\pm 2.87\text{dB}$
Conducted Spurious Emission	$\pm 2.88\text{dB}$
Channel Separation	$\pm 2.87\text{dB}$
In-Band Emission (Channel Mask)	$\pm 2.88\text{dB}$
Frequency Stability	$\pm 0.03\text{ ppm}$

Uncertainty figures are valid to a confidence level of 95%, K=2

6. SETUP OF EQUIPMENT UNDER TEST

SUPPORT EQUIPMENT

For RF test

No.	Product	Manufacturer	Model No.	Certify No.	Power cable
1	Note Book	ASUS	X515J	DOC	N/A
2	Adapter	N/A	GQ4Z-240250-AU	DOC	N/A
3	iPad nano	Apple	A1199	N/A	N/A
4	Speaker	logi	Z607	N/A	N/A

No.	Signal cable description	
A	Power	Unshielded, 1.5m 1 pcs.
B	Audio	Shielded, 1.5m 1 pcs.
C	Audio	Unshielded, 2.35m 1 pcs.
D	Command	Unshielded, 0.25m 1 pcs.
E	USB	Shielded, 1.5m 1 pcs.
F	Command	Unshielded, 0.2m 1 pcs.
G	USB	Shielded, 0.8m 1 pcs.


For EMI test

No.	Product	Manufacturer	Model No.	Certify No.	Signal cable
1	Adapter	Adapter	ATS060T-W240U	N/A	N/A
2	iPad nano	Apple	A1199	N/A	N/A
3	Speaker	logi	Z607	N/A	N/A
4	Multi-Zone BT Audio Amplifier Receiver	TEN-TRONICS	A-1499WPR	N/A	N/A
5	Cell Phone	SONY	XQ-DE72	N/A	N/A


No.	Signal cable description	
1	Power	Unshielded, 1.5m 1 pcs, with 1 core.
2	Audio	Shielded, 1.5m 1 pcs.
3	Audio	Unshielded, 2.35m 1 pcs.

SETUP DIAGRAM FOR TESTS

RF



EMI



EUT OPERATING CONDITION

RF Setup

1. Set up all computers like the setup diagram.
2. The "EMI_Tool_V27_Everestekinc_2023_0203.exe" software was used for testing.
3. Choose Control Interface Selection : I2C.

TX Mode :

- Select Module Type : 5.8GHz or 5.2GHz
- EMI Standard : FCC
- EMI RF Channel : 5160 ~ 5240 , 5730~5845
- EMI Mode : Tx PN-9 mode
- EMI power : 5
- OK Write EMI setting into flash

RX Mode :

- Select Module Type : 5.8GHz or 5.2GHz
- EMI Standard : FCC
- EMI RF Channel : 5160 ~ 5240 , 5730~5845
- EMI Mode : Rx moed
- EMI power : 5
- OK Write EMI setting into flash

4. All of the function are under run and power off and on again.
5. Start test.

7. FCC PART 15.407 REQUIREMENTS

7.1 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	07/24/2025	07/23/2026
SMA Cable+10dB Attenuator	CCS	SMA+10dB ATT	SMA/10dB	01/13/2026	01/12/2027
Software	Excel(ccs-o6-2020 v1.1)				

TEST RESULTS

TEST DATA

Model Name	A-1499WPT	Test By	Ted Huang
Temp & Humidity	25.8°C, 43%	Test Date	2026/07/15

Band 1



Channel	Channel Frequency (MHz)	99% Occupied Power Bandwidth (MHz)
Low	5160	2.97
Middle	5200	3.04
High	5240	3.03


Band 4

Channel	Channel Frequency (MHz)	99% Occupied Power Bandwidth (MHz)
Low	5730	3.42
Middle	5785	3.33
High	5845	3.15



99% BANDWIDTH


Test Mode: Band 1 / 5160 ~ 5240MHz





Test Mode: Band 4 / 5730 ~ 5845MHz





7.2 26dB BANDWIDTH

LIMITS

§ 15.303 (c) (2), For purposes of this subpart, the emission bandwidth shall be determined by measuring the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, that are 26 dB down relative to the maximum level of the modulated carrier. Determination of the emissions bandwidth is based on the use of measurement instrumentation employing a peak detector function with an instrument resolutions bandwidth approximately equal to 1.0 percent of the emission bandwidth of the device under measurement.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	07/24/2025	07/23/2026
SMA Cable+10dB Attenuator	CCS	SMA+10dB ATT	SMA/10dB	01/13/2026	01/12/2027
Software	Excel(ccs-o6-2020 v1.1)				

Remark: Each piece of equipment is scheduled for calibration once a year

TEST SETUP



TEST PROCEDURE

1. Set RBW = approximately 1% of the emission bandwidth.
2. Set the VBW > RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

TEST RESULTS

TEST DATA

Model Name	A-1499WPT	Test By	Ted Huang
Temp & Humidity	25.8°C, 43%	Test Date	2026/07/15

GFSK (5.2G) Mode / 5160 ~ 5240MHz



Channel	Channel Frequency (MHz)	26dB Bandwidth (MHz)	Pass / Fail
Low	5160	3.63	PASS
Middle	5200	3.66	PASS
High	5240	3.72	PASS


GFSK (5.8G) Mode / 5720 ~ 5845MHz

Channel	Channel Frequency (MHz)	26dB Bandwidth (MHz)	Pass / Fail
Low	5730	4.21	PASS
Middle	5785	4.29	PASS
High	5845	4.21	PASS


26dB BANDWIDTH



Test Mode: Band 1 / 5160 ~ 5240MHz





Test Mode: Band 4 / 5730 ~ 5845MHz





7.3 6dB BANDWIDTH


LIMIT

§ 15.407 (e) Within the 5.725-5.85 GHz band, the minimum 6dB bandwidth of U-NII devices shall be at least 500kHz.

TEST EQUIPMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	07/24/2025	07/23/2026
SMA Cable+10dB Attenuator	CCS	SMA+10dB ATT	SMA/10dB	01/13/2026	01/12/2027
Software	Excel(ccs-o6-2020 v1.1)				

TEST SETUP



TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 1-5 % of the emission bandwidth (EBW).
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. Compare the resultant bandwidth with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is 1-5 %.

TEST RESULTS

TEST DATA



Model Name	A-1499WPT	Test By	Ted Huang
Temp & Humidity	25.8°C, 43%	Test Date	2026/07/15


GFSK (5.8G) Mode / 5730 ~ 5845MHz

Channel	Channel Frequency (MHz)	6dB Bandwidth (kHz)	Minimum Limit (kHz)	Pass / Fail
Low	5745	1262	>500	PASS
Middle	5785	1212	>500	PASS
High	5825	1334	>500	PASS

6dB BANDWIDTH

Test Mode: Band 4 / 5730 ~ 58545Hz





Report No.: TMTN2606000585NR

7.4 MAXIMUM CONDUCTED OUTPUT POWER LIMITS

§ 15.407(a)

(1) For the band 5.15-5.25 GHz.

- (i) For an outdoor access point operating in the band 5.15 – 5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).
- (ii) For an indoor access point operating in the band 5.15 – 5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm $10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	07/24/2025	07/23/2026
SMA Cable+10dB Attenuator	CCS	SMA+10dB ATT	SMA/10dB	01/13/2026	01/12/2027
Software	Excel(ccs-o6-2020 v1.1)				

Remark: Each piece of equipment is scheduled for calibration once a year

TEST SETUP



TEST PROCEDURE

1. Set span to encompass the entire 26-dB emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.
2. Set RBW = 1 MHz.
3. Set VBW $\geq$ 3 MHz.
4. Number of points in sweep $\geq$ 2 Span / RBW. (This ensures that bin-to-bin spacing is $\leq$ RBW/2, so that narrowband signals are not lost between frequency bins.)
5. Sweep time = auto.
6. Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
7. If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq$ 98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".
8. Trace average at least 100 traces in power averaging (i.e., RMS) mode.
9. Compute power by integrating the spectrum across the 26 dB EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the 26 dB EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

TEST RESULTS

TEST DATA

Model Name	A-1499WPT	Test By	Ted Huang
Temp & Humidity	25.8°C, 43%	Test Date	2026/07/15

GFSK (5.2G) Mode / 5160 ~ 5240MHz

Channel	Channel Frequency (MHz)	Peak Power (dBm)	Peak Power Limit	Pass / Fail
			(dBm)	
Low	5160	-7.94	30.00	PASS
Middle	5200	-7.33	30.00	PASS
High	5240	-6.71	30.00	PASS

GFSK (5.8G) Mode / 5730 ~ 5845MHz



Channel	Channel Frequency (MHz)	Peak Power (dBm)	Peak Power Limit	Pass / Fail
			(dBm)	
Low	5745	-2.47	30.00	PASS
Middle	5785	-2.62	30.00	PASS
High	5825	-3.02	30.00	PASS


Remark:

1. At final test to get the worst-case emission at 6Mbps.
2. The cable assembly insertion loss of 11.7dB (including 10 dB pad and 1.7 dB cable) was Entered as an offset in the spectrum analyzer to allow for direct reading of power.


MAXIMUM CONDUCTED OUTPUT POWER



Test Mode: Band 1 / 5160 ~ 5240MHz





Test Mode: Band 4 / 5730 ~ 5845MHz





Report No.: TMTN2606000585NR

7.5 PEAK POWER SPECTRAL DENSITY LIMITS

§ 15.407 (a)

(1) For the band 5.15-5.25 GHz.

- (i) For an outdoor access point operating in the band 5.15 – 5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).
- (ii) For an indoor access point operating in the band 5.15 – 5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	07/24/2025	07/23/2026
SMA Cable+10dB Attenuator	CCS	SMA+10dB ATT	SMA/10dB	01/13/2026	01/12/2027
Software	Excel(ccs-o6-2020 v1.1)				

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE

1. Set span to encompass the entire 26-dB emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.
2. Set RBW = 1 MHz.
3. Set VBW ≥ 3 MHz.
4. Number of points in sweep ≥ 2 Span / RBW. (This ensures that bin-to-bin spacing is ≤ RBW/2, so that narrowband signals are not lost between frequency bins.)
5. Sweep time = auto.
6. Detector = RMS (*i.e.*, power averaging), if available. Otherwise, use sample detector mode.
7. If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (*i.e.*, with no off intervals) or at duty cycle ≥ 98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.
8. Trace average at least 100 traces in power averaging (*i.e.*, RMS) mode.
9. Use the peak search function on the instrument to find the peak of the spectrum.

TEST RESULTS

TEST DATA

Model Name	A-1499WPT	Test By	Ted Huang
Temp & Humidity	25.8°C, 43%	Test Date	2026/07/15

GFSK (5.2G) Mode / 5160 ~ 5240 MHz

Channel	Channel Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin (dB)	Pass / Fail
Low	5160	-8.19	17.00	-25.19	PASS
Middle	5200	-7.54		-24.54	PASS
High	5240	-6.94		-23.94	PASS

GFSK (5.8G) Mode / 5730 ~ 5845 MHz



Channel	Channel Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin (dB)	Pass / Fail
Low	5730	-2.79	30.00	-32.79	PASS
Middle	5785	-2.87		-32.87	PASS
High	5845	-3.32		-33.32	PASS


Remark:

1. At final test to get the worst-case emission at 117Mbps
2. The cable assembly insertion loss of 11.7dB (including 10 dB pad and 1.7 dB cable) was Entered as an offset in the spectrum analyzer to allow for direct reading of power.



PEAK POWER SPECTRAL DENSITY


Test Mode: Band 1 / 5160 ~ 5240MHz





Test Mode: Band 4 / 5730 ~ 5845MHz





7.6 DUTY CYCLE

LIMIT


Nil (No dedicated limit specified in the Rules)

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	07/24/2025	07/23/2026
SMA Cable+10dB Attenuator	CCS	SMA+10dB ATT	SMA/10dB	01/13/2026	01/12/2027
Software	Excel(ccs-o6-2020 v1.1)				

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE

- Place the EUT on the table and set it in transmitting mode.
- Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW $\geq$ OBW if possible; otherwise, set RBW to the largest available value. Set VBW $\geq$ RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

TEST RESULTS

No non-compliance noted.



Report No.: TMTN2606000585NR

Page: 42 / 105
Rev.: 00

TEST DATA

Model Name	A-1499WPT	Test By	Ted Huang
Temp & Humidity	25.8°C, 43%	Test Date	2026/07/15



	us	Times	Ton	Total Ton time(ms)
Ton1	100000.000	1	100000	
Ton2		0	0	
Ton3			0	100
Tp				100


Ton	100
Tp(Ton+Toff)	100
Duty Cycle	1
Duty Factor	0

TEST PLOT


Duty Cycle



Test Mode: Band 1 / 5160 ~ 5240MHz





Test Mode: Band 4 / 5730 ~ 5845MHz





7.7 CONDUCTED SPURIOUS EMISSION

LIMITS

§ 15.407 (b): Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: all emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.

The provisions of § 15.205 apply to intentional radiators operating under this section.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	07/24/2025	07/23/2026
SMA Cable+10dB Attenuator	CCS	SMA+10dB ATT	SMA/10dB	01/13/2026	01/12/2027
Software	Excel(ccs-o6-2020 v1.1)				

Remark: Each piece of equipment is scheduled for calibration once a year

TEST SETUP



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation of measurements on the radiated emissions site.


The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 1MHz. The video bandwidth is set to 1MHz. Peak detection measurements are compared to the average EIRP limit, adjusted for the maximum antenna gain. If necessary, additional average detection measurements are made.


Measurements are made over the 30 MHz to 40 GHz range with the transmitter set to the lowest, middle, and highest channels.


TEST RESULTS

OUT-OF-BAND SPURIOUS EMISSIONS-CONDUCTED MEASUREMENT

Test Mode: Band 1 / 5160 ~ 5240MHz










Test Mode: Band 4 / 5730 ~ 5845MHz

CH Low (GFSK (5.8G) Mode)







7.8 RADIATED EMISSION

LIMITS

(1) According to § 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3338	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

Remark:

1. ¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

2. ² Above 38.6

(2) According to § 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

- (3) According to § 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30.0	30	30
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

Remark: **Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

- (4) According to § 15.209 (b) In the emission table above, the tighter limit applies at the band edges.
- (5) § 15.407 (b): Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:
- (a) For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
 - (b) For transmitters operating in the 5.25-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
 - (c) For transmitters operating in the 5.47-5.725 GHz band: all emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
 - (d) For transmitters operating in the 5.725-5.85 GHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.

TEST EQUIPMENT

The following test equipments are utilized in making the measurements contained in this report.


Chamber Room # 1166					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Active Loop Antenna	ETS-LINDREN	6502	8905-2356	09/01/2025	08/31/2026
Attenuator	MCL	BW-S10W5	0605	01/13/2026	01/12/2027
Band Reject Filter	MICRO-TRONICS	HP50107-01	001	01/13/2026	01/12/2027
Bilog Antenna with 6dB Attenuator	SUNOL SCIENCES & EMCI	JB1 & N-6-06	A021306 & AT-N0682	10/08/2025	10/07/2026
Cable	EMCI	EM102-KMKM	CB1166-01	01/13/2026	01/12/2027
Double Ridged Guide Horn Antenna	ETS.LINDGREN	3117	00078733	04/24/2026	04/23/2027
EMI Test Receiver	R&S	ESCI 7	100856	06/29/2026	06/28/2027
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	07/24/2025	07/23/2026
Double Ridged Guide Horn Antenna	ETS-LINDGREN	3116	00078900	03/26/2026	03/25/2027
Pre-Amplifier	EMEC	EM01G40GA	060919/S02-130417-307	04/29/2026	04/28/2027
Software	Excel(ccs-o6-2020 v1.1) , e3(v6.101222)				

Remark: 1. Each piece of equipment is scheduled for calibration once a year.
 2. N.C.R = No Calibration Request.


TEST SETUP

The diagram below shows the test setup that is utilized to make the measurements for emission from below 1GHz.


9kHz ~ 30MHz



30MHz ~ 1GHz



The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.



TEST PROCEDURE

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. While measuring the radiated emission below 1GHz, the EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. While measuring the radiated emission above 1GHz, the EUT was set 3 meters away from the interference-receiving antenna.
3. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Remark :

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.


TEST RESULTS

Below 1 GHz (9kHz ~ 30MHz)

3m

Test Voltage: AC 120V, 60Hz

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/04
Model Name	A-1499WPT	Test By	Ted Huang
Test Mode	TX	Temp & Humidity	25.2°C, 44%




REMARK:

1. Test receiver setting QP(Quasi Peak) 、Average: RBW=200Hz
2. C.F=Antenna Factor+Cable Loss
3. The result basic equation calculation is as follow: Result = Reading + C.F, Margin = Result-Limit
4. The other emission levels were 10dB below the limit
5. The test distance is 3m.

Standard

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/04
Model Name	A-1499WPT	Test By	Ted Huang
Test Mode	TX	Temp & Humidity	25.2°C, 44%



REMARK:


1. Test receiver setting QP(Quasi Peak) 、Average: RBW=200Hz
2. C.F=Antenna Factor+Cable Loss
3. The result basic equation calculation is as follow: Result = Reading + C.F, Margin = Result-Limit
4. The other emission levels were 10dB below the limit
5. The test is standard distance.

150kHz~30MHz

3m

Test Voltage: AC 120V, 60Hz

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/04
Model Name	A-1499WPT	Test By	Ted Huang
Test Mode	TX	Temp & Humidity	25.2°C, 44%




REMARK:

- 1.Test receiver setting QP(Qusai Peak) 、Average : RBW=9kHz
- 2.C.F=Antenna Factor+Cable Loss
- 3.The result basic equation calculation is as follow:Result = Reading + C.F, Margin = Result-Limit
- 4.The other emission levels were 10dB below the limit
- 5.The test distance is 3m.

Standard

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/04
Model Name	A-1499WPT	Test By	Ted Huang
Test Mode	TX	Temp & Humidity	25.2°C, 44%



REMARK:


1. Test receiver setting QP(Qusai Peak) 、Average : RBW=9kHz
2. C.F=Antenna Factor+Cable Loss
3. The result basic equation calculation is as follow: Result = Reading + C.F, Margin = Result-Limit
4. The other emission levels were 10dB below the limit
5. The test is standard distance.

Below 1 GHz (30MHz ~ 1GHz)

Test Voltage: AC 120V, 60Hz

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/04
Model Name	A-1499WPT	Test By	Ted Huang
Test Mode	TX	Temp & Humidity	25.2°C, 44%

Vertical




REMARK:

1. Test receiver setting QP(Qusai Peak): RBW=120kHz
2. C.F=Antenna Factor+Cable Loss
3. The result basic equation calculation is as follow: Result = Reading + C.F, Margin = Result-Limit
4. The other emission levels were 10dB below the limit
5. The test distance is 3m.

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/04
Model Name	A-1499WPT	Test By	Ted Huang
Test Mode	TX	Temp & Humidity	25.2°C, 44%

Horizontal




REMARK:

1. Test receiver setting QP(Qusai Peak): RBW=120kHz
2. C.F=Antenna Factor+Cable Loss
3. The result basic equation calculation is as follow: Result = Reading + C.F, Margin = Result-Limit
4. The other emission levels were 10dB below the limit
5. The test distance is 3m.

Above 1 GHz

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/12
Model	A-1499WPT	Test By	Ted Huang
Test Mode	CH Low TX / Band 1	TEMP& Humidity	25.2°C, 44%

Vertical




REMARK:

1. Spectrum analyzer setting Peak: RBW=1MHz, VBW=3MHz, Average: RBW=1MHz, VBW $\geq$ 1/T
2. C.F=Antenna Factor+Cable Loss-Preamplifier gain+2.4GHz~2.5GHz Filter Insertion Loss
3. The result basic equation calculation is as follow: Result = Reading + C.F, Margin = Result-Limit
4. The other emission levels were 10dB below the limit
5. The test distance is 3m.

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/12
Model	A-1499WPT	Test By	Ted Huang
Test Mode	CH Low TX / Band 1	TEMP& Humidity	25.2°C, 44%

Horizontal




REMARK:

1. Spectrum analyzer setting Peak: RBW=1MHz, VBW=3MHz, Average: RBW=1MHz, VBW $\geq$ 1/T
2. C.F=Antenna Factor+Cable Loss-Preamplifier gain+2.4GHz~2.5GHz Filter Insertion Loss
3. The result basic equation calculation is as follow: Result = Reading + C.F, Margin = Result-Limit
4. The other emission levels were 10dB below the limit
5. The test distance is 3m.

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/12
Model	A-1499WPT	Test By	Ted Huang
Test Mode	CH Mid TX / Band 1	TEMP& Humidity	25.2°C, 44%

Vertical




REMARK:

1. Spectrum analyzer setting Peak: RBW=1MHz, VBW=3MHz, Average: RBW=1MHz, VBW $\geq$ 1/T
2. C.F=Antenna Factor+Cable Loss-Preamplifier gain+2.4GHz~2.5GHz Filter Insertion Loss
3. The result basic equation calculation is as follow: Result = Reading + C.F, Margin = Result-Limit
4. The other emission levels were 10dB below the limit
5. The test distance is 3m.

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/12
Model	A-1499WPT	Test By	Ted Huang
Test Mode	CH Mid TX / Band 1	TEMP& Humidity	25.2°C, 44%

Horizontal




REMARK:

1. Spectrum analyzer setting Peak: RBW=1MHz, VBW=3MHz, Average: RBW=1MHz, VBW $\geq$ 1/T
2. C.F=Antenna Factor+Cable Loss-Preamplifier gain+2.4GHz~2.5GHz Filter Insertion Loss
3. The result basic equation calculation is as follow: Result = Reading + C.F, Margin = Result-Limit
4. The other emission levels were 10dB below the limit
5. The test distance is 3m.

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/12
Model	A-1499WPT	Test By	Ted Huang
Test Mode	CH High TX / Band 1	TEMP& Humidity	25.2°C, 44%

Vertical




REMARK:

1. Spectrum analyzer setting Peak: RBW=1MHz, VBW=3MHz, Average: RBW=1MHz, VBW $\geq$ 1/T
2. C.F=Antenna Factor+Cable Loss-Preamplifier gain+2.4GHz~2.5GHz Filter Insertion Loss
3. The result basic equation calculation is as follow: Result = Reading + C.F, Margin = Result-Limit
4. The other emission levels were 10dB below the limit
5. The test distance is 3m.

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/12
Model	A-1499WPT	Test By	Ted Huang
Test Mode	CH High TX / Band 1	TEMP& Humidity	25.2°C, 44%

Horizontal




REMARK:

1. Spectrum analyzer setting Peak: RBW=1MHz, VBW=3MHz, Average: RBW=1MHz, VBW≥1/T
2. C.F=Antenna Factor+Cable Loss-Preamplifier gain+2.4GHz~2.5GHz Filter Insertion Loss
3. The result basic equation calculation is as follow: Result = Reading + C.F, Margin = Result-Limit
4. The other emission levels were 10dB below the limit
5. The test distance is 3m.

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/12
Model	A-1499WPT	Test By	Ted Huang
Test Mode	CH Low TX / Band 4	TEMP& Humidity	25.2°C, 44%

Vertical




REMARK:

1. Spectrum analyzer setting Peak: RBW=1MHz, VBW=3MHz, Average: RBW=1MHz, VBW $\geq$ 1/T
2. C.F=Antenna Factor+Cable Loss-Preamplifier gain+2.4GHz~2.5GHz Filter Insertion Loss
3. The result basic equation calculation is as follow: Result = Reading + C.F, Margin = Result-Limit
4. The other emission levels were 10dB below the limit
5. The test distance is 3m.

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/12
Model	A-1499WPT	Test By	Ted Huang
Test Mode	CH Low TX / Band 4	TEMP& Humidity	25.2°C, 44%

Horizontal




REMARK:

1. Spectrum analyzer setting Peak: RBW=1MHz, VBW=3MHz, Average: RBW=1MHz, VBW $\geq$ 1/T
2. C.F=Antenna Factor+Cable Loss-Preamplifier gain+2.4GHz~2.5GHz Filter Insertion Loss
3. The result basic equation calculation is as follow: Result = Reading + C.F, Margin = Result-Limit
4. The other emission levels were 10dB below the limit
5. The test distance is 3m.

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/12
Model	A-1499WPT	Test By	Ted Huang
Test Mode	CH Mid TX / Band 4	TEMP& Humidity	25.2°C, 44%

Vertical




REMARK:

1. Spectrum analyzer setting Peak: RBW=1MHz, VBW=3MHz, Average: RBW=1MHz, VBW $\geq$ 1/T
2. C.F=Antenna Factor+Cable Loss-Preamplifier gain+2.4GHz~2.5GHz Filter Insertion Loss
3. The result basic equation calculation is as follow: Result = Reading + C.F, Margin = Result-Limit
4. The other emission levels were 10dB below the limit
5. The test distance is 3m.

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/12
Model	A-1499WPT	Test By	Ted Huang
Test Mode	CH Mid TX / Band 4	TEMP& Humidity	25.2°C, 44%

Horizontal




REMARK:

1. Spectrum analyzer setting Peak: RBW=1MHz, VBW=3MHz, Average: RBW=1MHz, VBW $\geq$ 1/T
2. C.F=Antenna Factor+Cable Loss-Preamplifier gain+2.4GHz~2.5GHz Filter Insertion Loss
3. The result basic equation calculation is as follow: Result = Reading + C.F, Margin = Result-Limit
4. The other emission levels were 10dB below the limit
5. The test distance is 3m.

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/12
Model	A-1499WPT	Test By	Ted Huang
Test Mode	CH High TX / Band 4	TEMP& Humidity	25.2°C, 44%

Vertical




REMARK:

1. Spectrum analyzer setting Peak: RBW=1MHz, VBW=3MHz, Average: RBW=1MHz, VBW $\geq$ 1/T
2. C.F=Antenna Factor+Cable Loss-Preamplifier gain+2.4GHz~2.5GHz Filter Insertion Loss
3. The result basic equation calculation is as follow: Result = Reading + C.F, Margin = Result-Limit
4. The other emission levels were 10dB below the limit
5. The test distance is 3m.

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/12
Model	A-1499WPT	Test By	Ted Huang
Test Mode	CH High TX / Band 4	TEMP& Humidity	25.2°C, 44%

Horizontal




REMARK:

1. Spectrum analyzer setting Peak: RBW=1MHz, VBW=3MHz, Average: RBW=1MHz, VBW $\geq$ 1/T
2. C.F=Antenna Factor+Cable Loss-Preamplifier gain+2.4GHz~2.5GHz Filter Insertion Loss
3. The result basic equation calculation is as follow: Result = Reading + C.F, Margin = Result-Limit
4. The other emission levels were 10dB below the limit
5. The test distance is 3m.


Restricted Band Edges

Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/12
Model	A-1499WPT	Test By	Ted Huang
Test Mode	CH Low TX / Band 1	TEMP& Humidity	25.2°C, 44%

Horizontal




Vertical




Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/12
Model	A-1499WPT	Test By	Ted Huang
Test Mode	CH High TX / Band 1	TEMP& Humidity	25.2°C, 44%

Horizontal




Vertical




Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/12
Model	A-1499WPT	Test By	Ted Huang
Test Mode	CH Low TX / Band 4	TEMP& Humidity	25.2°C, 44%

Horizontal




Vertical




Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/12
Model	A-1499WPT	Test By	Ted Huang
Test Mode	CH Middle TX / Band 4	TEMP& Humidity	25.2°C, 44%

Horizontal




Vertical




Product Name	40W Wall Plate Multi-Zone Bluetooth Audio Amplifier Kit	Test Date	2026/07/12
Model	A-1499WPT	Test By	Ted Huang
Test Mode	CH High TX / Band 4	TEMP& Humidity	25.2°C, 44%

Horizontal



Vertical



7.9 CONDUCTED EMISSION

LIMITS

§ 15.207 (a) Except as shown in paragraph (b) and (c) this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.



Frequency Range (MHz)	Conducted Limit (dB μ v)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5.00	56	46
5.00 - 30.0	60	50

TEST EQUIPMENT

Conducted Emission room #1					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
BNC Coaxial Cable	CCS	BNC50	11	01/13/2026	01/12/2027
EMI Test Receiver	R&S	ESCI	101203	10/20/2025	10/19/2026
LISN	R&S	ENV216	101495	07/23/2026	07/22/2027
LISN	SCHWARZBECK	NNLK 8130	8130124	01/17/2026	01/16/2027
Pulse Limiter	SCHWARZBECK	VTSD 9561-F	797	01/13/2026	01/12/2027
Test S/W	e3(v6.101222)				

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE

The basic test procedure was in accordance with ANSI C63.4:2009.

The test procedure is performed in a 4m × 3m × 2.4m (L×W×H) shielded room.


The EUT along with its peripherals were placed on a 1.0m (W) × 1.5m (L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.

The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.

The EUT was located so that the distance between the boundary of the EUT and the closest surface of the LISN is 0.8 m. Where a mains flexible cord was provided by the manufacturer shall be 1 m long, or if in excess of 1 m, the excess cable was folded back and forth as far as possible so as to form a bundle not exceeding 0.4 m in length.

TEST RESULTS


Site: CON 1 Test Voltage: 120 Vac/ 60 Hz
M/N: A-1499WPT Mode: BT+5G LINK
POL: LINE Engineer: Tye.Lin Temp: 24.2 Humidity: 41%
Standard :



Freq MHz	Reading Level dBuV	C.F dB	Result dBuV	Limit dBuV	Over Limit dB	Detector
0.162	7.98	10.55	18.53	55.38	-36.85	Average
0.162	28.34	10.55	38.89	65.38	-26.49	QP
0.205	3.53	10.54	14.07	53.40	-39.33	Average
0.205	22.90	10.54	33.44	63.40	-29.96	QP
0.400	36.00	10.49	46.49	47.86	-1.37	Average
0.400	37.76	10.49	48.25	57.86	-9.61	QP
0.561	16.50	10.49	26.99	46.00	-19.01	Average
0.561	22.52	10.49	33.01	56.00	-22.99	QP
1.197	15.16	10.54	25.70	46.00	-20.30	Average
1.197	15.97	10.54	26.51	56.00	-29.49	QP
7.486	11.15	13.44	24.59	50.00	-25.41	Average
7.486	15.71	13.44	29.15	60.00	-30.85	QP

CON


Site: CON 1 Test Voltage: 120 Vac/ 60 Hz
M/N: A-1499WPT Mode: BT+5G LINK
POL: NEUTRAL Engineer: Tye.Lin Temp: 24.2 Humidity: 41%
Standard :



Freq MHz	Reading Level dBuV	C.F dB	Result dBuV	Limit dBuV	Over Limit dB	Detector
0.171	8.04	10.46	18.50	54.90	-36.40	Average
0.171	26.99	10.46	37.45	64.90	-27.45	QP
0.219	2.54	10.46	13.00	52.88	-39.88	Average
0.219	22.03	10.46	32.49	62.88	-30.39	QP
0.400	35.95	10.40	46.35	47.86	-1.51	Average
0.400	37.65	10.40	48.05	57.86	-9.81	QP
0.561	16.12	10.41	26.53	46.00	-19.47	Average
0.561	22.06	10.41	32.47	56.00	-23.53	QP
1.200	17.78	10.45	28.23	46.00	-17.77	Average
1.200	17.83	10.45	28.28	56.00	-27.72	QP
7.646	8.08	13.39	21.47	50.00	-28.53	Average
7.646	13.13	13.39	26.52	60.00	-33.48	QP


CON

Site: CON 1 Test Voltage: 120 Vac/ 60 Hz
M/N: A-1499WPT Mode: AUDIO IN
POL: LINE Engineer: Tye.Lin Temp: 24.2 Humidity: 41%
Standard :



CON

Site: CON 1 Test Voltage: 120 Vac/ 60 Hz
M/N: A-1499WPT Mode: AUDIO IN
POL: NEUTRAL Engineer: Tye.Lin Temp: 24.2 Humidity: 41%
Standard :



CON

7.10 FREQUENCY STABILITY

LIMITS


§ 15.407 (g) manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
-	-	-	-	-	-
-	-	-	-	-	-
Software	-				

Remark: Each piece of equipment is scheduled for calibration once a year

TEST SETUP



TEST PROCEDURE

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -20°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

Report No.: TMTN2606000585NR

Page: 90 / 105
Rev.: 00

TEST RESULTS

※ **Note: Not applicable**