

FCC/ISED - TEST REPORT

Report Number : **68.950.20.0654.02** Date of Issue: June 22, 2022

Model : PI7R, Pi7 S2R

Product Type : In-ear True Wireless Headphone

Applicant : B&W Group Ltd.

Address : Dale Road Worthing United Kingdom BN11 2BH

Factory : Charter Media (Dongguan) Co., Ltd.

Address : Dabandi Industrial Zone, Daning District, Humen Town,
523930 Dongguan City, Guangdong Province,
PEOPLE'S REPUBLIC OF CHINA

Test Result : **n Positive** **o Negative**

Total pages including Appendices : 70

Any use for advertising purposes must be granted in writing. This technical report may only be quoted in full. This report is the result of a single examination of the object in question and is not generally applicable evaluation of the quality of other products in regular production. For further details, please see testing and certification regulation, chapter A-3.4.

1 Table of Contents

1	Table of Contents	2
2	Details about the Test Laboratory.....	3
3	Description of the Equipment Under Test.....	4
4	Summary of Test Standards	5
5	Summary of Test Results	6
6	General Remarks	7
7	Test Setups.....	8
8	Systems test configuration	9
9	Technical Requirement	10
9.1	Conducted peak output power and e.i.r.p.....	10
9.2	20 dB bandwidth and 99% Occupied Bandwidth.....	23
9.3	Carrier Frequency Separation	33
9.4	Number of hopping frequencies.....	36
9.5	Dwell Time	38
9.6	Spurious RF conducted emissions.....	43
9.7	Band edge testing	54
9.8	Spurious radiated emissions for transmitter	59
10	Test Equipment List.....	69
11	System Measurement Uncertainty.....	70



2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12 & 13, Zhiheng Wisdomland Business Park, Nantou Checkpoint
Road 2, Nanshan District
Shenzhen 518052
P.R. China

Telephone: 86 755 8828 6998

Fax: 86 755 8288 5299

FCC Registration No.: 514049

ISED#: 10320A

3 Description of the Equipment Under Test

Product:	In-ear True Wireless Headphone
Model no/HVIN/PMN:	PI7R, Pi7 S2R
FVIN:	V.1.0.X
FCC ID	2ACIX-PI7R
IC:	11946B-PI7R
Options and accessories:	Type-C Cable, Charging Case, Aux in Cable
Rating:	PI7R: Earbud: 3.7VDC, 55mAh, 0.204Wh (Supplied by Built Li-ion battery) Pi7 S2R: Earbud: 3.85VDC, 70mAh, 0.270Wh (Supplied by Built Li-ion battery)
RF Transmission Frequency:	2402MHz-2480MHz
No. of Operated Channel:	79
Modulation:	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Antenna Type:	Mono pole antenna
Antenna Gain:	1.0dBi for PI7R, -3.0dBi for Pi7 S2R
Description of the EUT:	The Equipment Under Test (EUT) is an In-ear True Wireless Headphone support Bluetooth function.

4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2020 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators
RSS-Gen Issue 5, Amendment 1, March 2019	General Requirements for the Certification of Radio Apparatus
RSS-247 Issue 2 February 2017	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSS) and License-Exempt Local Area Network (LE-LAN) Devices

All the test methods were according to Public Notice DA 00-705 -Frequency Hopper Spread Spectrum Test Procedure, KDB558074 D01 v05r02 and ANSI C63.10-2013.

5 Summary of Test Results

Technical Requirements				
FCC Part 15 Subpart C/ RSS-247 Issue 2/RSS-Gen Issue 5				
Test Condition			Test Site	Test Result
§15.207	RSS-GEN 8.8	Conducted emission AC power port	--	N/A
§15.247(b)(1)	RSS-247 Clause 5.4(b)	Conducted peak output power and e.i.r.p.	Site 1	PASS
§15.247(e)	RSS-247 Clause 5.2(b)	Power spectral density*	--	N/A
§15.247(a)(2)	RSS-247 Clause 5.2(a)	6dB bandwidth	--	N/A
§15.247(a)(1)	RSS-247 Clause 5.1(a) & RSS-Gen 6.7	20dB bandwidth and 99% Occupied Bandwidth	Site 1	PASS
§15.247(a)(1)	RSS-247 Clause 5.1(b)	Carrier frequency separation	Site 1	PASS
§15.247(a)(1)(iii)	RSS-247 Clause 5.1(d)	Number of hopping frequencies	Site 1	PASS
§15.247(a)(1)(iii)	RSS-247 Clause 5.1(d)	Dwell Time	Site 1	PASS
§15.247(d)	RSS-247 Clause 5.5	Spurious RF conducted emissions	Site 1	PASS
§15.247(d)	RSS-247 Clause 5.5	Band edge	Site 1	PASS
§15.247(d) & §15.209 & §15.205	RSS-247 Clause 5.5 & RSS-GEN 6.13 RSS-GEN 8.9 RSS-GEN 8.10	Spurious radiated emissions for transmitter and receiver	Site 1	PASS
§15.203	RSS-GEN 6.8	Antenna requirement	See note 2	PASS

Note 1: N/A=Not Applicable.

Note 2: The EUT uses Mono pole antenna, which gain is 1.0dBi for PI7R, -3.0dBi for Pi7 S2R. In accordance to §15.203 and RSS-GEN 6.8, it is considered sufficiently to comply with the provisions of this section.



6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: 2ACIX-PI7R, IC: 11946B-PI7R complies with Section 15.205, 15.209, 15.247 of the FCC Part 15, Subpart and RSS-247 issue 2 and RSS-Gen issue 5 rules.

The report base 68.950.20.0654.01 additional a model Pi7 S2R, was identical with PI7R except for battery of earbuds, antenna of earbuds and appearance of earbuds. Additional Antenna Power tests. Other the test data in this report was referred from 68.950.20.0654.01

Note: The report is for BDR+EDR only.

SUMMARY:

All tests according to the regulations cited on page 6 were

n - Performed

o - **Not** Performed

The Equipment Under Test

n - **Fulfills** the general approval requirements.

o - **Does not** fulfill the general approval requirements.

Sample Received Date: August 27, 2020

Testing Start Date: August 27, 2020

Testing End Date: October 23, 2020

Updated test date: April 18, 2022-June 10, 2022

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch

Reviewed by:

Prepared by:

Tested by:

John Zhi
EMC Project Manager

Mark Chen
EMC Project Engineer




Tree Zhan
EMC Test Engineer


7 Test Setups

7.1 Radiated test setups


Below 1GHz



Above 1GHz



7.2 Conducted RF test setups



8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.	S/N
Notebook	Lenovo	X220	---

Test software: Bluetooth 3 Test Tool, which used to control the EUT in continues transmitting mode

The system was configured to hopping mode and non-hopping mode.

Hopping mode: typical working mode (normal hopping status)

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power .

9 Technical Requirement

9.1 Conducted peak output power and e.i.r.p.

Test Method

1. Use the following spectrum analyzer settings:
Span = approximately 5 times the 20dB bandwidth, centered on a hopping channel
RBW > the 20dB bandwidth of the emission being measured, VBW ≥ RBW,
Sweep = auto, Detector function = peak, Trace = max hold
2. Add a correction factor to the display.
3. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power

Limits

Conducted Peak Output Power:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤1	≤30

For e.i.r.p.:


Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤4	≤36

Conducted peak output power

PI7R Bluetooth Mode GFSK modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	e.i.r.p. dBm	Result
Low channel 2402MHz	7.2	8.2	Pass
Middle channel 2441MHz	6.89	7.89	Pass
High channel 2480MHz	6.83	7.83	Pass


Low channel 2402MHz



Date: 9.OCT.2020 14:50:17




Middle channel 2441MHz



Date: 9.OCT.2020 14:50:38

High channel 2480MHz




Date: 9.OCT.2020 14:50:58



Bluetooth Mode $\pi/4$ -DQPSK modulation Test Result

Frequency MHz	Conducted Peak Output		Result
	Power dBm	e.i.r.p. dBm	
Low channel 2402MHz	9.36	10.36	Pass
Middle channel 2441MHz	9.11	10.11	Pass
High channel 2480MHz	9.03	10.03	Pass


Low channel 2402MHz



Date: 9.OCT.2020 14:57:25




Middle channel 2441MHz



Date: 9.OCT.2020 14:57:44

High channel 2480MHz




Date: 9.OCT.2020 14:58:00



Bluetooth Mode 8DPSK modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	e.i.r.p. dBm	Result
Low channel 2402MHz	9.98	10.98	Pass
Middle channel 2441MHz	9.72	10.72	Pass
High channel 2480MHz	9.68	10.68	Pass


Low channel 2402MHz



Date: 9.OCT.2020 14:58:18




Middle channel 2441MHz



Date: 9.OCT.2020 14:58:37

High channel 2480MHz




Date: 9.OCT.2020 14:58:58

Pi7 S2R
Bluetooth Mode GFSK modulation Test Result

Frequency MHz	Power dBm	e.i.r.p. dBm	Result
Low channel 2402MHz	2.720	-0.28	Pass
Middle channel 2441MHz	2.210	-0.79	Pass
High channel 2480MHz	2.090	-0.91	Pass


Low channel 2402MHz



Date: 14.MAY.2022 14:27:37




Middle channel 2441MHz



Date: 14.MAY.2022 14:28:39

High channel 2480MHz




Date: 14.MAY.2022 14:29:19



Bluetooth Mode $\pi/4$ -DQPSK modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	e.i.r.p. dBm	Result
Low channel 2402MHz	4.880	1.880	Pass
Middle channel 2441MHz	4.630	1.630	Pass
High channel 2480MHz	4.610	1.610	Pass


Low channel 2402MHz



Date: 14.MAY.2022 14:31:35




Middle channel 2441MHz



Date: 14.MAY.2022 14:32:13

High channel 2480MHz




Date: 14.MAY.2022 14:32:47



Bluetooth Mode 8DPSK modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	e.i.r.p. dBm	Result
Low channel 2402MHz	5.480	2.480	Pass
Middle channel 2441MHz	5.340	2.340	Pass
High channel 2480MHz	5.440	2.440	Pass


Low channel 2402MHz



Date: 14.MAY.2022 14:34:05




Middle channel 2441MHz



Date: 14.MAY.2022 14:35:13

High channel 2480MHz



Date: 14.MAY.2022 14:35:55

9.2 20 dB bandwidth and 99% Occupied Bandwidth

Test Method

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Limit

Limit [kHz]


N/A

20 dB bandwidth and 99% Occupied Bandwidth

Bluetooth Mode GFSK Modulation test result

Frequency MHz	20 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz	Result
2402	1116	869	--	Pass
2441	1116	872	--	Pass
2480	1116	866	--	Pass

Low channel 2402MHz




Date: 9.OCT.2020 15:00:10




Date: 9.OCT.2020 15:00:21



Middle channel 2441MHz




Date: 9.OCT.2020 15:02:57




Date: 9.OCT.2020 15:03:08



High channel 2480MHz



Date: 9.OCT.2020 15:04:18




Date: 9.OCT.2020 15:04:28

20 dB bandwidth and 99% Occupied Bandwidth

Bluetooth Mode $\pi/4$ -DQPSK Modulation test result

Frequency MHz	20 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz	Result
2402	1431	1211	--	Pass
2441	1431	1214	--	Pass
2480	1431	1208	--	Pass

Low channel 2402MHz




Date: 9.OCT.2020 15:06:51




Date: 9.OCT.2020 15:07:02



Middle channel 2441MHz




Date: 9.OCT.2020 15:08:20




Date: 9.OCT.2020 15:08:31



High channel 2480MHz



Date: 9.OCT.2020 15:10:30




Date: 9.OCT.2020 15:10:40

20 dB bandwidth and 99% Occupied Bandwidth

Bluetooth Mode 8DPSK Modulation test result

Frequency MHz	20 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz	Result
2402	1416	1202	--	Pass
2441	1419	1202	--	Pass
2480	1422	1199	--	Pass

Low channel 2402MHz




Date: 9.OCT.2020 15:14:06




Date: 9.OCT.2020 15:14:17



Middle channel 2441MHz




Date: 9.OCT.2020 15:15:38




Date: 9.OCT.2020 15:15:49



High channel 2480MHz



Date: 9.OCT.2020 15:17:17



Date: 9.OCT.2020 15:17:28

9.3 Carrier Frequency Separation

Test Method

1. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels, RBW $\geq$ 1% of the span, VBW $\geq$ RBW, Sweep = auto, Detector function = peak
2. By using the Max-Hold function record the separation of two adjacent channels.
3. Measure the frequency difference of these two adjacent channels by spectrum analyzer marker function.
4. Repeat above procedures until all frequencies measured were complete.

Limit

Limit kHz	
$\geq 25\text{KHz}$ or $2/3$ of the 20 dB bandwidth which is greater	
GFSK Modulation Limit	
Test Mode	2/3 of 20 dB Bandwidth kHz
DH5	744
2DH5	954
3DH5	944




Carrier Frequency Separation

Test result: The measurement was performed with the typical configuration (normal hopping status), here GFSK modulation mode was used to show compliance.

GFSK Modulation test result


Test Mode	Carrier Frequency Separation kHz	Result
DH5	1000	Pass
2DH5	1009	Pass
3DH5	1000	Pass



Date: 9.OCT.2020 15:19:30




Middle channel 2441MHz



Date: 9.OCT.2020 15:21:00

High channel 2480MHz



Date: 9.OCT.2020 15:24:58

9.4 Number of hopping frequencies

Test Method

1. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels, $RBW \geq 1\%$ of the span, $VBW \geq RBW$, Sweep = auto, Detector function = peak
2. Set the spectrum analyzer on Max-Hold Mode, and then keep the EUT in hopping mode.
3. Record all the signals from each channel until each one has been recorded.
4. Repeat above procedures until all frequencies measured were complete.

Limit

Limit
number


≥ 15



Number of hopping frequencies

Test result: The measurement was performed with the typical configuration (normal hopping status), and the total hopping channels is constant for the all modulation mode according with the Bluetooth Core Specification. Here GFSK modulation mode was used to show compliance.

Number of hopping frequencies	Result
79	Pass



Date: 9.OCT.2020 15:19:45

9.5 Dwell Time

Test Method

1. Connect EUT antenna terminal to the spectrum analyzer with a low loss cable.
Equipment mode: Spectrum analyzer
2. RBW: 1MHz; VBW: 1MHz; SPAN: Zero Span
3. Adjust the center frequency of spectrum analyzer on any frequency be measured.
4. Measure the Dwell Time by spectrum analyzer Marker function.
5. Repeat above procedures until all frequencies measured were complete.

Limit

The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Dwell Time

Dwell time

The maximum dwell time shall be 0.4 s.

According to the Bluetooth Core Specification, the worse result (DH5 mode) was reported to show compliance.


The Dwell Time = Burst Width * Total Hops. The detailed calculations are showed as follows:

The duration for dwell time calculation: $0.4 \text{ [s]} * \text{hopping number} = 0.4 \text{ [s]} * 79 \text{ [ch]} = 31.6 \text{ [s*ch]}$;


Test Result

TestMode	Channel	BurstWidth(ms)	TotalHops	Result(s)	Limit(s)	Verdict
DH5	Hop	2.87	110	0.316	≤ 0.4	PASS
2DH5	Hop	2.88	110	0.317	≤ 0.4	PASS
3DH5	Hop	2.88	110	0.317	≤ 0.4	PASS

GFSK Modulation




Date: 9.OCT.2020 15:19:57




Date: 9.OCT.2020 15:20:03

DH5

$\pi/4$ -DQPSK Modulation




Date: 9.OCT.2020 15:21:23




Date: 9.OCT.2020 15:21:28

2DH5

8-DPSK Modulation



Date: 9.OCT.2020 15:25:22



Date: 9.OCT.2020 15:25:27

3DH5

9.6 Spurious RF conducted emissions

Test Method




1. Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz, VBW ≥ RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
3. The level displayed must comply with the limit specified in this Section. Submit these plots.
4. Repeat above procedures until all frequencies measured were complete.


Limit


Frequency Range MHz	Limit (dBc)
30-25000	-20


Spurious RF conducted emissions


TestMode	Antenna	Channel (MHz)	FreqRange(MHz)	RefLevel	Result(dBm)	Limit(dBm)	Verdict
DH5	Ant1	2402	Reference	7.24(dBm)	7.24	---	PASS
			30~1000	30~1000(MHz)	-68.63	<=-12.76	PASS
			1000~26500	1000~26500(MHz)	-44.28	<=-12.76	PASS
		2441	Reference	6.81(dBm)	6.81	---	PASS
			30~1000	30~1000(MHz)	-68.04	<=-13.19	PASS
			1000~26500	1000~26500(MHz)	-43.88	<=-13.19	PASS
		2480	Reference	6.88(dBm)	6.88	---	PASS
			30~1000	30~1000(MHz)	-68.33	<=-13.12	PASS
			1000~26500	1000~26500(MHz)	-43.99	<=-13.12	PASS
2DH5	Ant1	2402	Reference	7.18(dBm)	7.18	---	PASS
			30~1000	30~1000(MHz)	-67.78	<=-12.82	PASS
			1000~26500	1000~26500(MHz)	-28.29	<=-12.82	PASS
		2441	Reference	6.68(dBm)	6.68	---	PASS
			30~1000	30~1000(MHz)	-68.03	<=-13.32	PASS
			1000~26500	1000~26500(MHz)	-44.03	<=-13.32	PASS
		2480	Reference	6.72(dBm)	6.72	---	PASS
			30~1000	30~1000(MHz)	-67.96	<=-13.28	PASS
			1000~26500	1000~26500(MHz)	-43.15	<=-13.28	PASS
3DH5	Ant1	2402	Reference	7.29(dBm)	7.29	---	PASS
			30~1000	30~1000(MHz)	-67.43	<=-12.71	PASS
			1000~26500	1000~26500(MHz)	-28.9	<=-12.71	PASS
		2441	Reference	6.83(dBm)	6.83	---	PASS
			30~1000	30~1000(MHz)	-68.22	<=-13.17	PASS
			1000~26500	1000~26500(MHz)	-44.41	<=-13.17	PASS
		2480	Reference	6.84(dBm)	6.84	---	PASS
			30~1000	30~1000(MHz)	-66.74	<=-13.16	PASS
			1000~26500	1000~26500(MHz)	-44.5	<=-13.16	PASS























9.7 Band edge testing

Test Method



- 1 Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 kHz, VBW $\geq$ RBW, Sweep = auto, Detector function = peak, Trace = max hold
- 2 Allow the trace to stabilize, use the peak and delta measurement to record the result.
- 3 The level displayed must comply with the limit specified in this Section. .
- 4 Repeat the test at the hopping off and hopping on mode, submit all the plots.

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.





GFSK mode: Hopping off







GFSK mode: Hopping on






8DPSK mode: Hopping off






8DPSK mode: Hopping on



Date: 9.OCT.2020 15:25:58



Date: 9.OCT.2020 15:25:38

9.8 Spurious radiated emissions for transmitter

Test Method

- 1: The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2: The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
- 3: The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4: For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5: Use the following spectrum analyzer settings According to C63.10:

For Below 1GHz

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 KHz to 120KHz, VBW $\geq$ RBW for peak measurement, Sweep = auto,
Detector function = peak, Trace = max hold.

For Peak unwanted emissions Above 1GHz:

Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 1MHz, VBW $\geq$ RBW for peak measurement, Sweep = auto,
Detector function = peak, Trace = max hold.

Procedures for average unwanted emissions measurements above 1000 MHz:

Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 1MHz, VBW=10Hz, Sweep = auto, Detector function = peak, Trace = max hold.
If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit.

If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.

The setting method can refer to DA00-705.

Limit

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205, must comply with the radiated emission limits specified in section 15.209.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Frequency MHz	Field Strength uV/m	Field Strength dBμV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK


Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

The only worse case (which is subject to the maximum EIRP, GFSK mode) test result is listed in the report.


Transmitting spurious emission test result as below:

EUT: In-ear True Wireless Headphone
M/N: PI7R
Operating Condition: Tx 2402MHz, lowest Channel




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
53.583125	20.53	40.00	19.47	100.0	H	32.0	18
99.900625	18.51	43.50	24.99	100.0	H	356.0	16
196.476250	19.81	43.50	23.69	200.0	H	270.0	16
330.154375	22.43	46.00	23.57	100.0	H	104.0	20
473.229375	26.56	46.00	19.44	100.0	H	0.0	23
958.350625	35.53	46.00	10.47	200.0	H	53.0	30




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
35.577500	21.75	40.00	18.25	100.0	V	325.0	15
59.645625	20.26	40.00	19.74	100.0	V	0.0	17
104.326250	19.20	43.50	24.30	100.0	V	231.0	16
213.087500	20.18	43.50	23.32	100.0	V	116.0	17
452.798750	26.39	46.00	19.61	100.0	V	355.0	22
949.317500	34.87	46.00	11.13	100.0	V	148.0	30



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2558.000000	48.07	74.00	25.93	150.0	H	58.0	-2.7
5557.500000	49.50	74.00	24.50	150.0	H	134.0	4.3
8999.000000	46.29	74.00	27.71	150.0	H	219.0	6.7
16617.500000	49.45	74.00	24.55	150.0	H	31.0	15.8




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1593.000000	45.75	74.00	28.25	150.0	V	345.0	-7.4
2558.500000	42.90	74.00	31.10	150.0	V	219.0	-2.7
5898.000000	49.08	74.00	24.92	150.0	V	55.0	5.5
16706.500000	50.25	74.00	23.75	150.0	V	104.0	15.9




EUT: In-ear True Wireless Headphone
M/N: PI7R
Operating Condition: Tx 2441MHz, Middle Channel



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1841.000000	39.74	74.00	34.26	150.0	H	356.0	-5.4
2296.000000	43.02	74.00	30.98	150.0	H	86.0	-3.4
2597.000000	44.35	74.00	29.65	150.0	H	63.0	-2.6
5910.500000	49.79	74.00	24.21	150.0	H	345.0	5.4




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1596.500000	41.96	74.00	32.04	150.0	V	181.0	-7.3
2458.500000	49.21	74.00	24.79	150.0	V	0.0	-3.0
5549.000000	49.13	74.00	24.87	150.0	V	322.0	4.3
16913.000000	49.54	74.00	24.46	150.0	V	215.0	16.5




EUT: In-ear True Wireless Headphone
M/N: PI7R
Operating Condition: Tx 2480MHz, High Channel)



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1766.000000	46.83	74.00	27.17	150.0	H	220.0	-5.9
2458.500000	48.93	74.00	25.07	150.0	H	189.0	-3.0
4116.500000	45.94	74.00	28.06	150.0	H	236.0	1.6
5958.000000	49.79	74.00	24.21	150.0	H	166.0	5.4



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1598.500000	46.06	74.00	27.94	150.0	V	345.0	-7.3
2459.500000	50.88	74.00	23.12	150.0	V	251.0	-3.0
5829.000000	49.42	74.00	24.58	150.0	V	322.0	5.2
16081.500000	49.22	74.00	24.78	150.0	V	52.0	14.8

- Remark:
- (1) Data of measurement within frequency range18-26GHz are the noise floor or attenuated more than 20dB below the permissible limits or the field strength is too small to be measured, so test data does not present in this report.
 - (2) Level=Reading Level + Correction Factor
Above 1GHz: Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain
Below 1GHz: Corrector factor = Antenna Factor + Cable Loss
(The Reading Level is recorded by software which is not shown in the sheet)

10 Test Equipment List

List of Test Instruments

Radiated Emission Test

Description	Manufacturer	Model no.	Equipment ID	Serial no.	Calibration interval (year)	cal. due date
EMI Test Receiver	Rohde & Schwarz	ESR 26	68-4-74-14-002	101269	1	2021-6-29
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9162	68-4-80-19-003	284	1	2021-2-24
Wave Guide Antenna	ETS	3117	68-4-80-19-001	00218954	1	2021-6-15
Pre-amplifier	Rohde & Schwarz	SCU 18F	68-4-29-19-001	100745	1	2020-12-14
Pre-amplifier	Rohde & Schwarz	SCU 08F2	68-4-29-19-004	08400018	1	2020-12-14
Sideband Horn Antenna	Q-PAR	QWH-SL-18-40-K-SG	68-4-80-14-008	12827	1	2021-8-5
Pre-amplifier	Rohde & Schwarz	SCU 40A	68-4-29-14-002	100432	1	2021-7-30
3m Semi-anechoic chamber	TDK	9X6X6	68-4-90-19-006	----	3	2022-12-29
Test software	Rohde & Schwarz	EMC32	68-4-90-19-006-A01	Version10.3 5.02	N/A	N/A

RF Conducted Test

Description	Manufacturer	Model no.	Equipment ID	Serial no.	Calibration interval (year)	cal. due date
Signal Analyzer	Rohde & Schwarz	FSV40	68-4-74-14-004	101030	1	2023-5-27

11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Radiated Spurious Emission 30MHz-1000MHz	Horizontal: 4.70dB; Vertical: 4.67dB;
Radiated Spurious Emission 1000MHz-18000MHz	Horizontal: 4.65dB; Vertical: 4.63dB;
Conducted RF test with TS 8997	RF Power Conducted: 1.31dB Frequency test involved: 0.6×10 ⁻⁷ or 1%