

# TEST REPORT

**FCC ID: 2ACJAPLT76XXG**

**Product: TABLET PC**

**Model No.: PLT7650G**

**Additional Model No.: PLT7649G, PLT76XXG("XX" can be replaced by digital from "00" to "99")**

**Trade Mark: N/A**

**Report No.: TCT150721E013**

**Issued Date: July 31, 2015**

Issued for:

**ShenZhen Harmony Technology Co.,Ltd**  
**Block 2, Jiayuan Industrial Zone, Heping Community high-tech Park, No 2**  
**Fuyuan Road, Fuyong, Bao'an, Shenzhen, China**

Issued By:

**Shenzhen Tongce Testing Lab.**  
**1F, Leinuo Watch Building, Fuyong Town, Baoan Dist, Shenzhen, China**  
**TEL: +86-755-27673339**  
**FAX: +86-755-27673332**

**Note:** This report shall not be reproduced except in full, without the written approval of Shenzhen Tongce Testing Lab.

This document may be altered or revised by Shenzhen Tongce Testing Lab. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

## TABLE OF CONTENTS

|                                                                  |          |
|------------------------------------------------------------------|----------|
| <b>1. Test Certification.....</b>                                | <b>3</b> |
| <b>2. Test Result Summary .....</b>                              | <b>4</b> |
| <b>3. EUT Description .....</b>                                  | <b>5</b> |
| <b>4. Genera Information.....</b>                                | <b>6</b> |
| 4.1. Test environment and mode .....                             | 6        |
| 4.2. Description of Support Units .....                          | 7        |
| <b>5. Facilities and Accreditations .....</b>                    | <b>8</b> |
| 5.1. Facilities .....                                            | 8        |
| 5.2. Location .....                                              | 8        |
| 5.3. Measurement Uncertainty .....                               | 8        |
| <b>6. Test Results and Measurement Data .....</b>                | <b>9</b> |
| 6.1. Antenna requirement .....                                   | 9        |
| 6.2. Conducted Emission.....                                     | 10       |
| 6.3. Maximum Conducted (Average) Output Power .....              | 14       |
| 6.4. Emission Bandwidth .....                                    | 19       |
| 6.5. Power Spectral Density .....                                | 24       |
| 6.6. Test Specification.....                                     | 24       |
| 6.7. Conducted Band Edge and Spurious Emission Measurement ..... | 29       |
| 6.8. Radiated Spurious Emission Measurement .....                | 37       |

**Appendix A: Photographs of Test Setup**

**Appendix B: Photographs of EUT**

## 1. Test Certification

|                              |                                                                                                                      |
|------------------------------|----------------------------------------------------------------------------------------------------------------------|
| <b>Product:</b>              | TABLET PC                                                                                                            |
| <b>Model No.:</b>            | PLT7650G                                                                                                             |
| <b>Additional Model No.:</b> | PLT7649G, PLT76XXG("XX" can be replaced by digital from "00" to "99")                                                |
| <b>Applicant:</b>            | ShenZhen Harmony Technology Co.,Ltd                                                                                  |
| <b>Address:</b>              | Block 2, Jiayuan Industrial Zone, Heping Community high-tech Park, No 2 Fuyuan Road, Fuyong, Bao'an, Shenzhen, China |
| <b>Manufacturer:</b>         | ShenZhen Harmony Technology Co.,Ltd                                                                                  |
| <b>Address:</b>              | Block 2, Jiayuan Industrial Zone, Heping Community high-tech Park, No 2 Fuyuan Road, Fuyong, Bao'an, Shenzhen, China |
| <b>Date of Test:</b>         | July 21 - July 30, 2015                                                                                              |
| <b>Applicable Standards:</b> | FCC CFR Title 47 Part 15 Subpart C Section 15.247<br>KDB 558074 D01 DTS Meas Guidance v03r03                         |

The above equipment has been tested by Shenzhen Tongce Testing Lab. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:



Leon Chen

Date:

July 30, 2015

Reviewed By:



Joe Zhou

Date:

July 31, 2015

Approved By:



Tomsin

Date:

July 31, 2015

## 2. Test Result Summary

| Requirement                      | CFR 47 Section      | Result |
|----------------------------------|---------------------|--------|
| Antenna requirement              | §15.203/§15.247 (c) | PASS   |
| AC Power Line Conducted Emission | §15.207             | PASS   |
| Conducted Peak Output Power      | §15.247 (b)(3)      | PASS   |
| 6dB Emission Bandwidth           | §15.247 (a)(2)      | PASS   |
| Power Spectral Density           | §15.247 (e)         | PASS   |
| Band Edge                        | §15.247(d)          | PASS   |
| Spurious Emission                | §15.205/§15.209     | PASS   |

**Note:**

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

### 3. EUT Description

|                                                      |                                                                                                                                                             |
|------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Name:</b>                                 | TABLET PC                                                                                                                                                   |
| <b>Model :</b>                                       | PLT7650G                                                                                                                                                    |
| <b>Additional Model:</b>                             | PLT7649G, PLT76XXG("XX" can be replaced by digital from "00" to "99")                                                                                       |
| <b>Trade Mark:</b>                                   | N/A                                                                                                                                                         |
| <b>Operation Frequency:</b>                          | 2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20))                                                                                                             |
| <b>Channel Separation:</b>                           | 5MHz                                                                                                                                                        |
| <b>Number of Channel:</b>                            | 11 for 802.11b/802.11g/802.11n(HT20)                                                                                                                        |
| <b>Modulation Technology: (IEEE 802.11b)</b>         | Direct Sequence Spread Spectrum (DSSS)                                                                                                                      |
| <b>Modulation Technology: (IEEE 802.11g/802.11n)</b> | Orthogonal Frequency Division Multiplexing(OFDM)                                                                                                            |
| <b>Data speed (IEEE 802.11b):</b>                    | 1Mbps, 2Mbps, 5.5Mbps, 11Mbps                                                                                                                               |
| <b>Data speed (IEEE 802.11g):</b>                    | 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps,54Mbps                                                                                                 |
| <b>Data speed (IEEE 802.11n):</b>                    | Up to 135Mbps                                                                                                                                               |
| <b>Antenna Type:</b>                                 | Internal Antenna                                                                                                                                            |
| <b>Antenna Gain:</b>                                 | 2dBi                                                                                                                                                        |
| <b>Power Supply:</b>                                 | Rechargeable Li-ion Battery DC3.7V<br>Adapter Information:<br>Model: HJ-050200U<br>Input: AC 100-240V, 50/60Hz<br>Output: DC 5V, 2A                         |
| <b>Remark:</b>                                       | All models above are identical in interior structure, electrical circuits and components, and just model names are different for the marketing requirement. |

#### Operation Frequency each of channel For 802.11b/g/n(HT20)

| Channel | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|---------|-----------|---------|-----------|
| 1       | 2412MHz   | 4       | 2427MHz   | 7       | 2442MHz   | 10      | 2457MHz   |
| 2       | 2417MHz   | 5       | 2432MHz   | 8       | 2447MHz   | 11      | 2462MHz   |
| 3       | 2422MHz   | 6       | 2437MHz   | 9       | 2452MHz   |         |           |

**Note:**

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|---------|-----------|
| 1       | 2412MHz   | 6       | 2437MHz   | 11      | 2462MHz   |

## 4. Genera Information

### 4.1. Test environment and mode

#### Operating Environment:

|                       |           |
|-----------------------|-----------|
| Temperature:          | 25.0 °C   |
| Humidity:             | 56 % RH   |
| Atmospheric Pressure: | 1010 mbar |

#### Test Mode:

|                   |                                                                                                               |
|-------------------|---------------------------------------------------------------------------------------------------------------|
| Engineering mode: | Keep the EUT in continuous transmitting by select channel and modulations (The value of duty cycle is 98.50%) |
|-------------------|---------------------------------------------------------------------------------------------------------------|

The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

**Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.**

| Mode         | Data rate |
|--------------|-----------|
| 802.11b      | 1Mbps     |
| 802.11g      | 6Mbps     |
| 802.11n(H20) | 6.5Mbps   |

#### Final Test Mode:

|                 |                                                         |
|-----------------|---------------------------------------------------------|
| Operation mode: | Keep the EUT in continuous transmitting with modulation |
|-----------------|---------------------------------------------------------|

According to ANSI C63.4 standards, the test results are both the “worst case” and “worst setup” 1Mbps for 802.11b, 6Mbps for 802.11g and 6.5Mbps for 802.11n (H20) and Duty cycle setting during the transmission is 98.50% with maximum power setting for all modulations.

## 4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Equipment | Model No. | Serial No. | FCC ID | Trade Name |
|-----------|-----------|------------|--------|------------|
| /         | /         | /          | /      | /          |

**Note:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

## 5. Facilities and Accreditations

### 5.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 572331

Shenzhen Tongce Testing Lab

The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

- CNAS - Registration No.: CNAS L6165

Shenzhen TCT Testing Technology Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6165.

### 5.2. Location

Shenzhen Tongce Testing Lab

Address: 1F, Leinuo Watch Building, Fuyong Town, Baoan Dist, Shenzhen, China

Tel: 86-755-36638142

### 5.3. Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

| No. | Item                          | MU                        |
|-----|-------------------------------|---------------------------|
| 1   | Conducted Emission            | $\pm 2.56\text{dB}$       |
| 2   | RF power, conducted           | $\pm 0.12\text{dB}$       |
| 3   | Spurious emissions, conducted | $\pm 0.11\text{dB}$       |
| 4   | All emissions, radiated(<1G)  | $\pm 3.92\text{dB}$       |
| 5   | All emissions, radiated(>1G)  | $\pm 4.28\text{dB}$       |
| 6   | Temperature                   | $\pm 0.1^{\circ}\text{C}$ |
| 7   | Humidity                      | $\pm 1.0\%$               |

## 6. Test Results and Measurement Data

### 6.1. Antenna requirement

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| <b>Standard requirement:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | FCC Part15 C Section 15.203 /247(c) |
| <p>15.203 requirement:<br/>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(c) (1)(i) requirement:<br/>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p> |                                     |
| <b>E.U.T Antenna:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                     |
| <p>The Bluetooth antenna is an internal FPCB antenna which permanently attached, and the best case gain of the antenna is 2dBi.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                     |

## 6.2. Conducted Emission

### 6.2.1. Test Specification

| Test Requirement:     | FCC Part15 C Section 15.207                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|--------------|--|------------|---------|----------|-----------|-----------|-------|----|----|------|----|----|
| Test Method:          | ANSI C63.4:2014                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Frequency Range:      | 150 kHz to 30 MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Receiver setup:       | RBW=9 kHz, VBW=30 kHz, Sweep time=auto                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Limits:               | <table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table>                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Frequency range (MHz) | Limit (dBuV) |  | Quasi-peak | Average | 0.15-0.5 | 66 to 56* | 56 to 46* | 0.5-5 | 56 | 46 | 5-30 | 60 | 50 |
| Frequency range (MHz) | Limit (dBuV)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
|                       | Quasi-peak                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Average               |              |  |            |         |          |           |           |       |    |    |      |    |    |
| 0.15-0.5              | 66 to 56*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 56 to 46*             |              |  |            |         |          |           |           |       |    |    |      |    |    |
| 0.5-5                 | 56                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 46                    |              |  |            |         |          |           |           |       |    |    |      |    |    |
| 5-30                  | 60                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 50                    |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Test Setup:           | <div><p>Reference Plane</p><p>40cm 80cm</p><p>E.U.T AC power</p><p>Test table/Insulation plane</p><p>LISN Filter AC power</p><p>EMI Receiver</p><p>Remark:<br/>E.U.T: Equipment Under Test<br/>LISN: Line Impedance Stabilization Network<br/>Test table height=0.8m</p></div>                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Test Mode:            | Charging + transmitting with modulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Test Procedure:       | <ol style="list-style-type: none"><li>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li><li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li><li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.</li></ol> |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Test Result:          | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |

## 6.2.2. Test Instruments


| Conducted Emission Shielding Room Test Site (843) |                    |           |               |                 |
|---------------------------------------------------|--------------------|-----------|---------------|-----------------|
| Equipment                                         | Manufacturer       | Model     | Serial Number | Calibration Due |
| EMI Test Receiver                                 | R&S                | ESCS30    | 100139        | Sep. 16, 2015   |
| LISN                                              | Schwarzbeck        | NSLK 8126 | 8126453       | Sep. 29, 2015   |
| Coax cable                                        | TCT                | CE-05     | N/A           | Sep.15 , 2015   |
| EMI Test Software                                 | Shurple Technology | EZ-EMC    | N/A           | N/A             |

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

## 6.2.3. Test data

Please refer to following diagram for individual

### Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site Chamber #2 Phase: **L1** Temperature: 25 (C)  
Limit: FCC PART15 Conduction(QP) Power: AC 120V/60Hz Humidity: 56 %

| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1   |     | 0.1539       | 47.04                    | 11.49                   | 58.53                    | 65.78         | -7.25      | QP       |         |
| 2   |     | 0.1539       | 36.13                    | 11.49                   | 47.62                    | 55.78         | -8.16      | AVG      |         |
| 3   |     | 0.2084       | 42.11                    | 11.46                   | 53.57                    | 63.26         | -9.69      | QP       |         |
| 4   |     | 0.2084       | 29.42                    | 11.46                   | 40.88                    | 53.26         | -12.38     | AVG      |         |
| 5   |     | 0.3099       | 36.34                    | 11.40                   | 47.74                    | 59.97         | -12.23     | QP       |         |
| 6   | *   | 0.3099       | 33.09                    | 11.40                   | 44.49                    | 49.97         | -5.48      | AVG      |         |
| 7   |     | 0.4781       | 35.47                    | 11.31                   | 46.78                    | 56.37         | -9.59      | QP       |         |
| 8   |     | 0.4781       | 27.84                    | 11.31                   | 39.15                    | 46.37         | -7.22      | AVG      |         |
| 9   |     | 1.0881       | 26.35                    | 11.21                   | 37.56                    | 56.00         | -18.44     | QP       |         |
| 10  |     | 1.0881       | 22.81                    | 11.21                   | 34.02                    | 46.00         | -11.98     | AVG      |         |
| 11  |     | 4.4069       | 27.52                    | 10.83                   | 38.35                    | 56.00         | -17.65     | QP       |         |
| 12  |     | 4.4069       | 21.84                    | 10.83                   | 32.67                    | 46.00         | -13.33     | AVG      |         |

#### Note:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard


Margin (dB) = Measurement (dBuV) – Limits (dBuV)

Q.P. =Quasi-Peak

AVG =average

\* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

## Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site: Chamber #2  
Limit: FCC PART15 Conduction(QP)  
Phase: N  
Power: AC 120V/60Hz  
Temperature: 25 (C)  
Humidity: 56 %

| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1   |     | 0.1539       | 41.41                    | 11.49                   | 52.90                    | 65.78         | -12.88     | QP       |         |
| 2   |     | 0.1539       | 33.57                    | 11.49                   | 45.06                    | 55.78         | -10.72     | AVG      |         |
| 3   |     | 0.2006       | 38.89                    | 11.46                   | 50.35                    | 63.58         | -13.23     | QP       |         |
| 4   | *   | 0.2006       | 31.87                    | 11.46                   | 43.33                    | 53.58         | -10.25     | AVG      |         |
| 5   |     | 0.2553       | 32.42                    | 11.43                   | 43.85                    | 61.58         | -17.73     | QP       |         |
| 6   |     | 0.2553       | 28.13                    | 11.43                   | 39.56                    | 51.58         | -12.02     | AVG      |         |
| 7   |     | 0.4233       | 27.57                    | 11.34                   | 38.91                    | 57.38         | -18.47     | QP       |         |
| 8   |     | 0.4233       | 20.65                    | 11.34                   | 31.99                    | 47.38         | -15.39     | AVG      |         |
| 9   |     | 0.8296       | 34.45                    | 11.19                   | 45.64                    | 56.00         | -10.36     | QP       |         |
| 10  |     | 0.8296       | 17.27                    | 11.19                   | 28.46                    | 46.00         | -17.54     | AVG      |         |
| 11  |     | 4.2031       | 26.17                    | 10.89                   | 37.06                    | 56.00         | -18.94     | QP       |         |
| 12  |     | 4.2031       | 15.94                    | 10.89                   | 26.83                    | 46.00         | -19.17     | AVG      |         |

### Note:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) – Limits (dBuV)

Q.P. =Quasi-Peak

AVG =average

\* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

### 6.3. Maximum Conducted (Average) Output Power

#### 6.3.1. Test Specification

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (b)(3)                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Test Method:      | ANSI C63.10:2013 and KDB558074                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Limit:            | 30dBm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Test Setup:       |  <p style="text-align: center;">Spectrum Analyzer                      EUT</p>                                                                                                                                                                                                                                                                                                                                                |
| Test Mode:        | Transmitting mode with modulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Test Procedure:   | <ol style="list-style-type: none"> <li>1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r03.</li> <li>2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>3. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>4. Measure the conducted output power and record the results in the test report.</li> </ol> |
| Test Result:      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

#### 6.3.2. Test Instruments

| Equipment         | Manufacturer | Model  | Serial Number | Calibration Due |
|-------------------|--------------|--------|---------------|-----------------|
| Spectrum Analyzer | Agilent      | N9020A | MY49100060    | Oct. 21, 2015   |
| RF cable          | TCT          | RE-06  | N/A           | Sep.15 , 2015   |
| Antenna Connector | TCT          | RFC-01 | N/A           | Sep.15 , 2015   |

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

### 6.3.3. Test Data

| 802.11b mode |                                                      |             |        |
|--------------|------------------------------------------------------|-------------|--------|
| Test channel | Maximum Conducted<br>(Average) Output<br>Power (dBm) | Limit (dBm) | Result |
| Lowest       | 9.46                                                 | 30.00       | PASS   |
| Middle       | 9.64                                                 | 30.00       | PASS   |
| Highest      | 9.20                                                 | 30.00       | PASS   |

| 802.11g mode |                                                      |             |        |
|--------------|------------------------------------------------------|-------------|--------|
| Test channel | Maximum Conducted<br>(Average) Output<br>Power (dBm) | Limit (dBm) | Result |
| Lowest       | 9.18                                                 | 30.00       | PASS   |
| Middle       | 9.36                                                 | 30.00       | PASS   |
| Highest      | 9.37                                                 | 30.00       | PASS   |

| 802.11n(H20) mode |                                                      |             |        |
|-------------------|------------------------------------------------------|-------------|--------|
| Test channel      | Maximum Conducted<br>(Average) Output<br>Power (dBm) | Limit (dBm) | Result |
| Lowest            | 9.37                                                 | 30.00       | PASS   |
| Middle            | 9.46                                                 | 30.00       | PASS   |
| Highest           | 9.67                                                 | 30.00       | PASS   |

Test plots as follows:

## 802.11b Modulation

Lowest channel



Middle channel



Highest channel



## 802.11g Modulation


Lowest channel



Middle channel




Highest channel




## 802.11n (HT20) Modulation


### Lowest channel



### Middle channel



### Highest channel



## 6.4. Emission Bandwidth

### 6.4.1. Test Specification

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Requirement:</b> | FCC Part15 C Section 15.247 (a)(2)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Test Method:</b>      | ANSI C63.10:2013 and KDB558074                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Limit:</b>            | >500kHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Test Setup:</b>       |  <p style="text-align: center;">Spectrum Analyzer                      EUT</p>                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Test Mode:</b>        | Transmitting mode with modulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Test Procedure:</b>   | <ol style="list-style-type: none"> <li>1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r03.</li> <li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. Peak detector used</li> <li>4. Measure and record the results in the test report.</li> </ol> |
| <b>Test Result:</b>      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

### 6.4.2. Test Instruments

| RF Test Room      |              |        |               |                 |
|-------------------|--------------|--------|---------------|-----------------|
| Equipment         | Manufacturer | Model  | Serial Number | Calibration Due |
| Spectrum Analyzer | Agilent      | N9020A | MY49100060    | Oct. 21, 2015   |
| RF cable          | TCT          | RE-06  | N/A           | Sep.15 , 2015   |
| Antenna Connector | TCT          | RFC-01 | N/A           | Sep.15 , 2015   |

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).


### 6.4.3. Test data

| Test channel | 6dB Emission Bandwidth (MHz) |         |              |
|--------------|------------------------------|---------|--------------|
|              | 802.11b                      | 802.11g | 802.11n(H20) |
| Lowest       | 9.598                        | 16.62   | 17.83        |
| Middle       | 9.983                        | 16.62   | 17.84        |
| Highest      | 9.983                        | 16.63   | 17.84        |
| Limit:       | >500kHz                      |         |              |
| Test Result: | PASS                         |         |              |


Test plots as follows:

## 802.11b Modulation


### Lowest channel



### Middle channel




### Highest channel




## 802.11g Modulation


### Lowest channel



### Middle channel




### Highest channel




## 802.11n (HT20) Modulation


### Lowest channel



### Middle channel



### Highest channel



## 6.5. Power Spectral Density

## 6.6. Test Specification

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Requirement:</b> | FCC Part15 C Section 15.247 (e)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Test Method:</b>      | ANSI C63.10:2013 and KDB558074                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Limit:</b>            | The power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Test Setup:</b>       |  <p style="text-align: center;">Spectrum Analyzer                      EUT</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Test Mode:</b>        | Transmitting mode with modulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Test Procedure:</b>   | <ol style="list-style-type: none"> <li>1. The testing follows Measurement Procedure 10.3 Method AVGPDS of FCC KDB Publication No.558074 D01 DTS Meas. Guidance v03r03</li> <li>2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>3. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW): <math>3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}</math>. Video bandwidth VBW <math>\geq 3 \times \text{RBW}</math>. Set the span to at least 1.5 times the OBW.</li> <li>5. Detector = RMS, Sweep time = auto couple.</li> <li>6. Employ trace averaging (RMS) mode over a minimum of 100 traces. Use the peak marker function to determine the maximum power level.</li> <li>6. Measure and record the results in the test report.</li> </ol> |
| <b>Test Result:</b>      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

### 6.6.1. Test Instruments

| RF Test Room      |              |        |               |                 |
|-------------------|--------------|--------|---------------|-----------------|
| Equipment         | Manufacturer | Model  | Serial Number | Calibration Due |
| Spectrum Analyzer | Agilent      | N9020A | MY49100060    | Oct. 21, 2015   |
| RF cable          | TCT          | RE-06  | N/A           | Sep.15 , 2015   |
| Antenna Connector | TCT          | RFC-01 | N/A           | Sep.15 , 2015   |

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

### 6.6.2. Test data

| Test channel | Power Spectral Density (dBm/3kHz) |         |              |
|--------------|-----------------------------------|---------|--------------|
|              | 802.11b                           | 802.11g | 802.11n(H20) |
| Lowest       | -8.475                            | -11.198 | -11.302      |
| Middle       | -8.206                            | -11.114 | -11.211      |
| Highest      | -8.150                            | -11.053 | -11.427      |
| Limit:       | 8dBm/3kHz                         |         |              |
| Test Result: | PASS                              |         |              |

Test plots as follows:

## 802.11b Modulation

Lowest channel



Middle channel




Highest channel




## 802.11g Modulation


### Lowest channel



### Middle channel




### Highest channel




## 802.11n (HT20) Modulation


### Lowest channel



### Middle channel



### Highest channel



## 6.7. Conducted Band Edge and Spurious Emission Measurement

### 6.7.1. Test Specification

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Requirement:</b> | FCC Part15 C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Test Method:</b>      | ANSI C63.10:2013 and KDB558074                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Limit:</b>            | In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Test Setup:</b>       |  <p style="text-align: center;">Spectrum Analyzer                      EUT</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Test Mode:</b>        | Transmitting mode with modulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Test Procedure:</b>   | <ol style="list-style-type: none"> <li>1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03.</li> <li>2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>3. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).</li> <li>5. Measure and record the results in the test report.</li> <li>6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.</li> </ol> |
| <b>Test Result:</b>      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

## 6.7.2. Test Instruments

| RF Test Room      |              |        |               |                 |
|-------------------|--------------|--------|---------------|-----------------|
| Equipment         | Manufacturer | Model  | Serial Number | Calibration Due |
| Spectrum Analyzer | Agilent      | N9020A | MY49100060    | Oct. 21, 2015   |
| RF cable          | TCT          | RE-06  | N/A           | Sep.15 , 2015   |
| Antenna Connector | TCT          | RFC-01 | N/A           | Sep.15 , 2015   |

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

## 6.7.3. Test Data

### 802.11b Modulation




## 100kHz PSD reference Level



## Band Edge




## Spurious emission



## Highest Channel

## 802.11g Modulation



## 100kHz PSD reference Level



## Band Edge




## Spurious emission



## Highest Channel

## 802.11n (HT20) Modulation



## 100kHz PSD reference Level



## Band Edge




## Spurious emission




## Highest Channel


## 6.8. Radiated Spurious Emission Measurement

### 6.8.1. Test Specification

|                       |                                        |                                                                                      |                                      |                                     |                                  |  |
|-----------------------|----------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------|-------------------------------------|----------------------------------|--|
| Test Requirement:     | FCC Part15 C Section 15.209            |                                                                                      |                                      |                                     |                                  |  |
| Test Method:          | ANSI C63.4: 2014 and ANSI C63.10: 2013 |                                                                                      |                                      |                                     |                                  |  |
| Frequency Range:      | 9 kHz to 25 GHz                        |                                                                                      |                                      |                                     |                                  |  |
| Measurement Distance: | 3 m                                    |                                                                                      |                                      |                                     |                                  |  |
| Antenna Polarization: | Horizontal & Vertical                  |                                                                                      |                                      |                                     |                                  |  |
| Operation mode:       | Transmitting mode with modulation      |                                                                                      |                                      |                                     |                                  |  |
| Receiver Setup:       | Frequency                              | Detector                                                                             | RBW                                  | VBW                                 | Remark                           |  |
|                       | 9kHz- 150kHz                           | Quasi-peak                                                                           | 200Hz                                | 1kHz                                | Quasi-peak Value                 |  |
|                       | 150kHz- 30MHz                          | Quasi-peak                                                                           | 9kHz                                 | 30kHz                               | Quasi-peak Value                 |  |
|                       | 30MHz-1GHz                             | Quasi-peak                                                                           | 120KHz                               | 300KHz                              | Quasi-peak Value                 |  |
|                       | Above 1GHz                             | Peak                                                                                 | 1MHz                                 | 3MHz                                | Peak Value                       |  |
| RMS                   |                                        | 1MHz                                                                                 | 3MHz                                 | AV Value                            |                                  |  |
| Limit:                | Frequency                              |                                                                                      | Field Strength<br>(microvolts/meter) |                                     | Measurement<br>Distance (meters) |  |
|                       | 0.009-0.490                            |                                                                                      | 2400/F(KHz)                          |                                     | 300                              |  |
|                       | 0.490-1.705                            |                                                                                      | 24000/F(KHz)                         |                                     | 30                               |  |
|                       | 1.705-30                               |                                                                                      | 30                                   |                                     | 30                               |  |
|                       | 30-88                                  |                                                                                      | 100                                  |                                     | 3                                |  |
|                       | 88-216                                 |                                                                                      | 150                                  |                                     | 3                                |  |
|                       | 216-960                                |                                                                                      | 200                                  |                                     | 3                                |  |
|                       | Above 960                              |                                                                                      | 500                                  |                                     | 3                                |  |
|                       | Frequency                              |                                                                                      | Field Strength<br>(microvolts/meter) | Measurement<br>Distance<br>(meters) | Detector                         |  |
|                       | Above 1GHz                             |                                                                                      | 500                                  | 3                                   | Average                          |  |
|                       |                                        |                                                                                      | 5000                                 | 3                                   | Peak                             |  |
|                       | Test setup:                            | For radiated emissions below 30MHz                                                   |                                      |                                     |                                  |  |
|                       |                                        |  |                                      |                                     |                                  |  |
|                       |                                        | 30MHz to 1GHz                                                                        |                                      |                                     |                                  |  |



Above 1GHz



## Test Procedure:

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03.
2. For the radiated emission test below 1GHz:  
The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
- For the radiated emission test above 1GHz:  
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT,

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|               | <p>depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <p>3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level</p> <p>4. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.</p> <p>5. Use the following spectrum analyzer settings:</p> <ul style="list-style-type: none"> <li>(1) Span shall wide enough to fully capture the emission being measured;</li> <li>(2) Set RBW=100 kHz for <math>f &lt; 1</math> GHz; VBW <math>\geq</math> RBW; Sweep = auto; Detector function = peak; Trace = max hold;</li> <li>(3) Set RBW = 1 MHz, VBW= 3MHz for <math>f \geq 1</math> GHz for peak measurement.</li> </ul> <p>For average measurement: RBW = 1 MHz,VBW = 3 MHz,RMS detector</p> |
| Test results: | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

## 6.8.2. Test Instruments


| Radiated Emission Test Site (966) |                                    |            |               |                 |
|-----------------------------------|------------------------------------|------------|---------------|-----------------|
| Name of Equipment                 | Manufacturer                       | Model      | Serial Number | Calibration Due |
| ESPI Test Receiver                | ROHDE&SCHW ARZ                     | ESVD       | 100008        | Sep.16 , 2015   |
| Spectrum Analyzer                 | ROHDE&SCHW ARZ                     | FSEM       | 848597/001    | Sep.16 , 2015   |
| Spectrum Analyzer                 | Agilent                            | N9020A     | MY49100060    | Oct. 21, 2015   |
| Pre-amplifier                     | EM Electronics Corporation CO.,LTD | EM30265    | 07032613      | Sep.16 , 2015   |
| Pre-amplifier                     | HP                                 | 8447D      | 2727A05017    | Sep.16 , 2015   |
| Loop antenna                      | ZHINAN                             | ZN30900A   | 12024         | Dec.14 , 2015   |
| Broadband Antenna                 | Schwarzbeck                        | VULB9163   | 340           | Sep.16 , 2015   |
| Horn Antenna                      | Schwarzbeck                        | BBHA 9120D | 631           | Sep.16 , 2015   |
| Horn Antenna                      | Schwarzbeck                        | BBHA 9170  | 373           | Sep.16 , 2015   |
| Coax cable                        | TCT                                | RE-low-01  | N/A           | Sep.15 , 2015   |
| Coax cable                        | TCT                                | RE-high-02 | N/A           | Sep.15 , 2015   |
| Coax cable                        | TCT                                | RE-low-03  | N/A           | Sep.15 , 2015   |
| Coax cable                        | TCT                                | RE-High-04 | N/A           | Sep.15 , 2015   |
| Antenna Mast                      | CCS                                | CC-A-4M    | N/A           | Sep.15 , 2015   |
| EMI Test Software                 | Shurple Technology                 | EZ-EMC     | N/A           | N/A             |

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

## 6.8.3. Test Data

Please refer to following diagram for individual  
Below 1GHz


Horizontal:



Site: Polarization: **Horizontal** Temperature: 25  
Limit: FCC Part 15B Class B RE 3 m Power: Battery Humidity: 56 %

| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Antenna<br>Height<br>cm | Table<br>Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1   | *   | 45.4130      | 37.50                    | -12.24                  | 25.26                      | 40.00           | -14.74     | QP                      | 0               |         |
| 2   |     | 59.3133      | 27.90                    | -12.77                  | 15.13                      | 40.00           | -24.87     | QP                      | 0               |         |
| 3   |     | 108.5455     | 28.20                    | -11.91                  | 16.29                      | 43.50           | -27.21     | QP                      | 0               |         |
| 4   |     | 134.0194     | 35.30                    | -15.17                  | 20.13                      | 43.50           | -23.37     | QP                      | 0               |         |
| 5   |     | 156.4260     | 32.10                    | -14.71                  | 17.39                      | 43.50           | -26.11     | QP                      | 0               |         |
| 6   |     | 219.1785     | 28.30                    | -11.02                  | 17.28                      | 46.00           | -28.72     | QP                      | 0               |         |

Vertical:



Site: Polarization: **Vertical** Temperature: 25  
 Limit: FCC Part 15B Class B RE 3 m Power: Battery Humidity: 56 %

| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Antenna<br>Height<br>cm | Table<br>Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|-------------------------|-----------------|---------|
| 1   |     | 49.0626      | 43.40                    | -12.08                  | 31.32                      | 40.00           | -8.68      | QP       |                         | 0               |         |
| 2   |     | 60.5770      | 42.60                    | -13.02                  | 29.58                      | 40.00           | -10.42     | QP       |                         | 0               |         |
| 3   |     | 63.6311      | 42.20                    | -14.15                  | 28.05                      | 40.00           | -11.95     | QP       |                         | 0               |         |
| 4   | *   | 76.3868      | 53.00                    | -16.40                  | 36.60                      | 40.00           | -3.40      | QP       |                         | 0               |         |
| 5   |     | 133.0810     | 39.90                    | -15.14                  | 24.76                      | 43.50           | -18.74     | QP       |                         | 0               |         |
| 6   |     | 219.1785     | 33.70                    | -11.02                  | 22.68                      | 46.00           | -23.32     | QP       |                         | 0               |         |

**Note:** 1. The low frequency, which started from 9kHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported

2. Measurements were conducted in all three channels (high, middle, low) and all modulations (802.11b, 802.11g, 802.11n (HT20), and the worst case Mode (Highest channel and 802.11b) was submitted only.

## Test Result of Radiated Spurious at Band edges

Modulation Type: 802.11b

| Low channel: 2412 MHz |               |                     |                          |                           |                     |                   |
|-----------------------|---------------|---------------------|--------------------------|---------------------------|---------------------|-------------------|
| Frequency (MHz)       | Ant. Pol. H/V | Peak reading (dBμV) | Correction Factor (dB/m) | Peak Final Emission Level | Peak limit (dBμV/m) | AV limit (dBμV/m) |
| 2310                  | H             | 42.75               | -4.20                    | 38.55                     | 74                  | 54                |
| 2376.42               | H             | 45.84               | -4.10                    | 41.74                     | 74                  | 54                |
| 2390                  | H             | 51.75               | -3.94                    | 47.81                     | 74                  | 54                |
| 2310                  | V             | 40.27               | -4.20                    | 36.07                     | 74                  | 54                |
| 2376.42               | V             | 52.90               | -4.10                    | 48.80                     | 74                  | 54                |
| 2390                  | V             | 54.15               | -3.94                    | 50.21                     | 74                  | 54                |

Modulation Type: 802.11b

| Low channel: 2462 MHz |               |                     |                          |                           |                     |                   |
|-----------------------|---------------|---------------------|--------------------------|---------------------------|---------------------|-------------------|
| Frequency (MHz)       | Ant. Pol. H/V | Peak reading (dBμV) | Correction Factor (dB/m) | Peak Final Emission Level | Peak limit (dBμV/m) | AV limit (dBμV/m) |
| 2483.5                | H             | 47.42               | -3.60                    | 43.82                     | 74                  | 54                |
| 2490.11               | H             | 45.63               | -3.50                    | 42.13                     | 74                  | 54                |
| 2500                  | H             | 43.24               | -3.34                    | 39.90                     | 74                  | 54                |
| 2483.5                | V             | 51.69               | -3.60                    | 48.09                     | 74                  | 54                |
| 2490.11               | V             | 45.01               | -3.50                    | 41.51                     | 74                  | 54                |
| 2500                  | V             | 41.95               | -3.34                    | 38.61                     | 74                  | 54                |

Modulation Type: 802.11g

| Low channel: 2412 MHz |               |                     |                          |                           |                     |                   |
|-----------------------|---------------|---------------------|--------------------------|---------------------------|---------------------|-------------------|
| Frequency (MHz)       | Ant. Pol. H/V | Peak reading (dBμV) | Correction Factor (dB/m) | Peak Final Emission Level | Peak limit (dBμV/m) | AV limit (dBμV/m) |
| 2310                  | H             | 41.61               | -4.20                    | 37.41                     | 74                  | 54                |
| 2388.74               | H             | 50.12               | -4.12                    | 46.00                     | 74                  | 54                |
| 2390                  | H             | 51.37               | -3.94                    | 47.43                     | 74                  | 54                |
| 2310                  | V             | 42.94               | -4.20                    | 38.74                     | 74                  | 54                |
| 2388.74               | V             | 49.16               | -4.12                    | 45.04                     | 74                  | 54                |
| 2390                  | V             | 53.11               | -3.94                    | 49.17                     | 74                  | 54                |

Modulation Type: 802.11g

| Low channel: 2462 MHz |               |                     |                          |                           |                     |                   |
|-----------------------|---------------|---------------------|--------------------------|---------------------------|---------------------|-------------------|
| Frequency (MHz)       | Ant. Pol. H/V | Peak reading (dBμV) | Correction Factor (dB/m) | Peak Final Emission Level | Peak limit (dBμV/m) | AV limit (dBμV/m) |
| 2483.5                | H             | 50.82               | -3.6                     | 47.22                     | 74                  | 54                |
| 2486.39               | H             | 48.85               | -3.52                    | 45.33                     | 74                  | 54                |
| 2500                  | H             | 45.83               | -3.34                    | 42.49                     | 74                  | 54                |
| 2483.5                | V             | 49.49               | -3.60                    | 45.89                     | 74                  | 54                |
| 2486.39               | V             | 46.08               | -3.52                    | 42.56                     | 74                  | 54                |
| 2500                  | V             | 46.23               | -3.34                    | 42.89                     | 74                  | 54                |

## Modulation Type: 802.11n (20MHz)

| Low channel: 2412 MHz |               |                     |                          |                           |                     |                   |
|-----------------------|---------------|---------------------|--------------------------|---------------------------|---------------------|-------------------|
| Frequency (MHz)       | Ant. Pol. H/V | Peak reading (dBμV) | Correction Factor (dB/m) | Peak Final Emission Level | Peak limit (dBμV/m) | AV limit (dBμV/m) |
| 2310                  | H             | 44.70               | -4.20                    | 40.50                     | 74                  | 54                |
| 2387.84               | H             | 52.25               | -4.10                    | 48.15                     | 74                  | 54                |
| 2390                  | H             | 53.04               | -3.94                    | 49.10                     | 74                  | 54                |
| 2310                  | V             | 46.56               | -4.20                    | 42.36                     | 74                  | 54                |
| 2387.84               | V             | 56.67               | -4.10                    | 52.57                     | 74                  | 54                |
| 2390                  | V             | 56.82               | -3.94                    | 52.88                     | 74                  | 54                |

## Modulation Type: 802.11n(20MHz)

| Low channel: 2462 MHz |               |                     |                          |                           |                     |                   |
|-----------------------|---------------|---------------------|--------------------------|---------------------------|---------------------|-------------------|
| Frequency (MHz)       | Ant. Pol. H/V | Peak reading (dBμV) | Correction Factor (dB/m) | Peak Final Emission Level | Peak limit (dBμV/m) | AV limit (dBμV/m) |
| 2483.5                | H             | 48.57               | -3.60                    | 44.97                     | 74                  | 54                |
| 2492.41               | H             | 47.52               | -3.50                    | 44.02                     | 74                  | 54                |
| 2500                  | H             | 46.01               | -3.34                    | 42.67                     | 74                  | 54                |
| 2483.5                | V             | 49.09               | -3.60                    | 45.49                     | 74                  | 54                |
| 2492.41               | V             | 48.56               | -3.50                    | 45.06                     | 74                  | 54                |
| 2500                  | V             | 44.91               | -3.34                    | 41.57                     | 74                  | 54                |

### Note:

1. Peak Final Emission Level=Peak Reading + Correction Factor;
2. Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

### Above 1GHz

Modulation Type: 802.11b

| Low channel: 2412 MHz |               |                     |                   |                          |                |             |                     |                   |             |
|-----------------------|---------------|---------------------|-------------------|--------------------------|----------------|-------------|---------------------|-------------------|-------------|
| Frequency (MHz)       | Ant. Pol. H/V | Peak reading (dBμV) | AV reading (dBμV) | Correction Factor (dB/m) | Emission Level |             | Peak limit (dBμV/m) | AV limit (dBμV/m) | Margin (dB) |
|                       |               |                     |                   |                          | Peak (dBμV/m)  | AV (dBμV/m) |                     |                   |             |
| 4824                  | H             | 51.54               | ---               | 0.75                     | 52.29          | ---         | 74                  | 54                | -1.71       |
| 7236                  | H             | 42.45               | ---               | 9.87                     | 52.32          | ---         | 74                  | 54                | -1.68       |
| ---                   | H             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |
| 4824                  | V             | 49.68               | ---               | 0.75                     | 50.43          | ---         | 74                  | 54                | -3.57       |
| 7236                  | V             | 41.16               | ---               | 9.87                     | 51.03          | ---         | 74                  | 54                | -2.97       |
| ---                   | V             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |

| Middle channel: 2437MHz |               |                     |                   |                          |                |             |                     |                   |             |
|-------------------------|---------------|---------------------|-------------------|--------------------------|----------------|-------------|---------------------|-------------------|-------------|
| Frequency (MHz)         | Ant. Pol. H/V | Peak reading (dBμV) | AV reading (dBμV) | Correction Factor (dB/m) | Emission Level |             | Peak limit (dBμV/m) | AV limit (dBμV/m) | Margin (dB) |
|                         |               |                     |                   |                          | Peak (dBμV/m)  | AV (dBμV/m) |                     |                   |             |
| 4874                    | H             | 50.26               | ---               | 0.97                     | 51.23          | ---         | 74                  | 54                | -2.77       |
| 7311                    | H             | 42.06               | ---               | 9.83                     | 51.89          | ---         | 74                  | 54                | -2.11       |
| ---                     | H             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |
| 4874                    | V             | 48.98               | ---               | 0.97                     | 49.95          | ---         | 74                  | 54                | -4.05       |
| 7311                    | V             | 40.88               | ---               | 9.83                     | 50.71          | ---         | 74                  | 54                | -3.29       |
| ---                     | V             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |

| High channel: 2462 MHz |               |                     |                   |                          |                |             |                     |                   |             |
|------------------------|---------------|---------------------|-------------------|--------------------------|----------------|-------------|---------------------|-------------------|-------------|
| Frequency (MHz)        | Ant. Pol. H/V | Peak reading (dBμV) | AV reading (dBμV) | Correction Factor (dB/m) | Emission Level |             | Peak limit (dBμV/m) | AV limit (dBμV/m) | Margin (dB) |
|                        |               |                     |                   |                          | Peak (dBμV/m)  | AV (dBμV/m) |                     |                   |             |
| 4924                   | H             | 49.22               | ---               | 1.18                     | 50.40          | ---         | 74                  | 54                | -3.60       |
| 7386                   | H             | 40.43               | ---               | 10.07                    | 50.50          | ---         | 74                  | 54                | -3.50       |
| ---                    | H             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |
| 4924                   | V             | 50.22               | ---               | 1.18                     | 51.40          | ---         | 74                  | 54                | -2.60       |
| 7386                   | V             | 40.35               | ---               | 10.07                    | 50.42          | ---         | 74                  | 54                | -3.58       |
| ---                    | V             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |

**Note:**

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown "—" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

## Modulation Type: 802.11g

| Low channel: 2412 MHz |               |                     |                   |                          |                |             |                     |                   |             |
|-----------------------|---------------|---------------------|-------------------|--------------------------|----------------|-------------|---------------------|-------------------|-------------|
| Frequency (MHz)       | Ant. Pol. H/V | Peak reading (dBμV) | AV reading (dBμV) | Correction Factor (dB/m) | Emission Level |             | Peak limit (dBμV/m) | AV limit (dBμV/m) | Margin (dB) |
|                       |               |                     |                   |                          | Peak (dBμV/m)  | AV (dBμV/m) |                     |                   |             |
| 4824                  | H             | 50.37               | ---               | 0.75                     | 51.12          | ---         | 74                  | 54                | -2.88       |
| 7236                  | H             | 41                  | ---               | 9.87                     | 50.87          | ---         | 74                  | 54                | -3.13       |
| ---                   | H             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |
| 4824                  | V             | 46.34               | ---               | 0.75                     | 47.09          | ---         | 74                  | 54                | -6.91       |
| 7236                  | V             | 40.11               | ---               | 9.87                     | 49.98          | ---         | 74                  | 54                | -4.02       |
| ---                   | V             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |

| Middle channel: 2437MHz |               |                     |                   |                          |                |             |                     |                   |             |
|-------------------------|---------------|---------------------|-------------------|--------------------------|----------------|-------------|---------------------|-------------------|-------------|
| Frequency (MHz)         | Ant. Pol. H/V | Peak reading (dBμV) | AV reading (dBμV) | Correction Factor (dB/m) | Emission Level |             | Peak limit (dBμV/m) | AV limit (dBμV/m) | Margin (dB) |
|                         |               |                     |                   |                          | Peak (dBμV/m)  | AV (dBμV/m) |                     |                   |             |
| 4874                    | H             | 48.5                | ---               | 0.97                     | 49.47          | ---         | 74                  | 54                | -4.53       |
| 7311                    | H             | 40.55               | ---               | 9.83                     | 50.38          | ---         | 74                  | 54                | -3.62       |
| ---                     | H             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |
| 4874                    | V             | 45.24               | ---               | 0.97                     | 46.21          | ---         | 74                  | 54                | -7.79       |
| 7311                    | V             | 40.44               | ---               | 9.83                     | 50.27          | ---         | 74                  | 54                | -3.73       |
| ---                     | V             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |

| High channel: 2462 MHz |               |                     |                   |                          |                |             |                     |                   |             |
|------------------------|---------------|---------------------|-------------------|--------------------------|----------------|-------------|---------------------|-------------------|-------------|
| Frequency (MHz)        | Ant. Pol. H/V | Peak reading (dBμV) | AV reading (dBμV) | Correction Factor (dB/m) | Emission Level |             | Peak limit (dBμV/m) | AV limit (dBμV/m) | Margin (dB) |
|                        |               |                     |                   |                          | Peak (dBμV/m)  | AV (dBμV/m) |                     |                   |             |
| 4924                   | H             | 47.48               | ---               | 1.18                     | 48.66          | ---         | 74                  | 54                | -5.34       |
| 7386                   | H             | 40.27               | ---               | 10.07                    | 50.34          | ---         | 74                  | 54                | -3.66       |
| ---                    | H             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |
| 4924                   | V             | 45.15               | ---               | 1.18                     | 46.33          | ---         | 74                  | 54                | -7.67       |
| 7386                   | V             | 40.77               | ---               | 10.07                    | 50.84          | ---         | 74                  | 54                | -3.16       |
| ---                    | V             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |

### Note:

- Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
- Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
- The emission levels of other frequencies are very lower than the limit and not show in test report.
- Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
- Data of measurement shown "—" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

## Modulation Type: 802.11n (HT20)

| Low channel: 2412 MHz |               |                     |                   |                          |                |             |                     |                   |             |
|-----------------------|---------------|---------------------|-------------------|--------------------------|----------------|-------------|---------------------|-------------------|-------------|
| Frequency (MHz)       | Ant. Pol. H/V | Peak reading (dBμV) | AV reading (dBμV) | Correction Factor (dB/m) | Emission Level |             | Peak limit (dBμV/m) | AV limit (dBμV/m) | Margin (dB) |
|                       |               |                     |                   |                          | Peak (dBμV/m)  | AV (dBμV/m) |                     |                   |             |
| 4824                  | H             | 49.97               | ---               | 0.75                     | 50.72          | ---         | 74                  | 54                | -3.28       |
| 7236                  | H             | 40.23               | ---               | 9.87                     | 50.10          | ---         | 74                  | 54                | -3.90       |
| ---                   | H             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |
| 4824                  | V             | 45.67               | ---               | 0.75                     | 46.42          | ---         | 74                  | 54                | -7.58       |
| 7236                  | V             | 40.34               | ---               | 9.87                     | 50.21          | ---         | 74                  | 54                | -3.79       |
| ---                   | V             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |

| Middle channel: 2437MHz |               |                     |                   |                          |                |             |                     |                   |             |
|-------------------------|---------------|---------------------|-------------------|--------------------------|----------------|-------------|---------------------|-------------------|-------------|
| Frequency (MHz)         | Ant. Pol. H/V | Peak reading (dBμV) | AV reading (dBμV) | Correction Factor (dB/m) | Emission Level |             | Peak limit (dBμV/m) | AV limit (dBμV/m) | Margin (dB) |
|                         |               |                     |                   |                          | Peak (dBμV/m)  | AV (dBμV/m) |                     |                   |             |
| 4874                    | H             | 48.07               | ---               | 0.97                     | 49.04          | ---         | 74                  | 54                | -4.96       |
| 7311                    | H             | 40.39               | ---               | 9.83                     | 50.22          | ---         | 74                  | 54                | -3.78       |
| ---                     | H             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |
| 4874                    | V             | 45.16               | ---               | 0.97                     | 46.13          | ---         | 74                  | 54                | -7.87       |
| 7311                    | V             | 40.2                | ---               | 9.83                     | 50.03          | ---         | 74                  | 54                | -3.97       |
| ---                     | V             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |

| High channel: 2462 MHz |               |                     |                   |                          |                |             |                     |                   |             |
|------------------------|---------------|---------------------|-------------------|--------------------------|----------------|-------------|---------------------|-------------------|-------------|
| Frequency (MHz)        | Ant. Pol. H/V | Peak reading (dBμV) | AV reading (dBμV) | Correction Factor (dB/m) | Emission Level |             | Peak limit (dBμV/m) | AV limit (dBμV/m) | Margin (dB) |
|                        |               |                     |                   |                          | Peak (dBμV/m)  | AV (dBμV/m) |                     |                   |             |
| 4924                   | H             | 46.74               | ---               | 1.18                     | 47.92          | ---         | 74                  | 54                | -6.08       |
| 7386                   | H             | 40.35               | ---               | 10.07                    | 50.42          | ---         | 74                  | 54                | -3.58       |
| ---                    | H             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |
| 4924                   | V             | 45.03               | ---               | 1.18                     | 46.21          | ---         | 74                  | 54                | -7.79       |
| 7386                   | V             | 40.03               | ---               | 10.07                    | 50.10          | ---         | 74                  | 54                | -3.90       |
| ---                    | V             | ---                 | ---               | ---                      | ---            | ---         | ---                 | ---               | ---         |

### Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown "—" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

\*\*\*\*\*END OF REPORT\*\*\*\*\*