TEST REPORT

Report Number: 103224477MPK-003C
Project Number: G103224477
December 27, 2017

Testing performed on the
FIBERGATEWAY
Model Number: GR240BG
FCC ID: 2ACJF-FGW-GR240BG

to
FCC Part 15, Subpart E

For

Altice Labs, SA

Test Performed by:	Test Authorized by:
Intertek	Altice Labs, SA
1365 Adams Court	Rua Eng. Ferreira Pinto Basto
Menlo Park, CA 94025 USA	3810-106 Aveiro, Portugal

Prepared by: _____ **Date:** December 27, 2017
Minh Ly

Reviewed by: _____ **Date:** December 27, 2017
Krishna K Vemuri

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. This report must not be used to claim product endorsement by A2LA, NIST nor any other agency of the U.S. Government.

VERIFICATION OF COMPLIANCE
Report No. 103224477MPK-003C

Verification is hereby issued to the named APPLICANT and is VALID ONLY for the equipment identified hereon for use under the rules and regulations listed below.

Equipment Under Test:	FIBERGATEWAY
Trade Name:	Altice Labs, SA
Model No.:	GR240BG
Applicant:	Altice Labs, SA
Contact:	Ricardo Cunha
Address:	Rua Eng. Ferreira Pinto Basto 3810-106 Aveiro
Country	Portugal
Tel. Number:	351234403200
Email:	Rcunha@ptinovacao.pt
Applicable Regulation:	FCC Part 15, Subpart E
Date of Test:	December 04 to 13, 2017

We attest to the accuracy of this report:

Minh Ly EMC Project Engineer	Krishna K Vemuri Engineering Team Lead

intertek
Total Quality. Assured.

TABLE OF CONTENTS

1.0 Introduction 4
1.1 Summary of Tests 4

2.0 General Description 5
2.1 Product Description 5
2.2 Related Submittal(s) Grants 6
2.3 Test Methodology 6
2.4 Test Facility 6
2.5 Measurement Uncertainty 6

3.0 System Test Configuration 7
3.1 Support Equipment 7
3.2 Block Diagram of Test Setup 7
3.3 Justification 8
3.4 Mode of Operation During Test 8
3.5 Modifications required for Compliance 8
3.6 Additions, deviations and exclusions from standards 8

4.0 Measurement Results 9
4.1 Emission Bandwidth and 99% Occupied Bandwidth 9
4.1.1 Procedure 9
4.1.2 Test Result 10
4.2 Maximum Conducted Output Power 20
4.2.1 Requirement 20
4.2.2 Procedure 20
4.2.3 Test Results 21
4.3 Peak Power Spectral Density 59
4.3.1 Requirement 59
4.3.2 Procedure 59
4.3.3 Test Result 60
4.4 Frequency stability 62
4.4.1 Requirement 62
4.4.2 Procedure 62
4.4.3 Result 63
4.5 Transmitter Radiated Emissions 64
4.5.1 Requirement 64
4.5.2 Procedure 65
4.5.3 Field Strength Calculation 66
4.5.4 Test Results 66
4.5.5 Test setup photographs 93

5.0 List of Test Equipment 95

6.0 Document History 96

1.0 Introduction

1.1 Summary of Tests

Test	Reference FCC	Result
26 dB Emission Band width and 99% Occupied Bandwidth	15.407(a)(1)(2)(3)	Complies
Conducted Output Power	15.407(a)(1)(2)(3)	Complies
Peak Power Spectral Density	15.407(a)(1)(2)(3)	Complies
Undesirable Emissions	15.407(b)(1-8)	Complies
Transmitter Radiated Emissions	15.407(b)(1-8) 15.209, 15.205	Complies
Frequency stability	15.407(g)	Complies
Dynamic Frequency Selection (DFS)	15.407(h)	Complies*
Antenna Requirement	15.203	Complies. The EUT uses internal antenna.

*See test results in report #103224477MPK-006

EUT receive date: September 18, 2017

EUT receive condition: The pre-production version of the EUT was received in good condition with no apparent damage. As declared by the Applicant, it is identical to the production units.

Test start date: December 04, 2017

Test completion date: December 13, 2017

The test results in this report pertain only to the item tested.

2.0 General Description

2.1 Product Description

Altice Labs, SA supplied the following description of the EUT:

The FiberGateway GR240BG is an ONT (Optical Network Terminal) solution based on Rec. ITU-T G.984.x that supports triple play services (high speed internet, voice and video) which are deployed over Ethernet and Wi-Fi interfaces. GEM (GPON encapsulation method) is employed to adapt technologies. This system can be used in triple play service delivery network solutions. It includes Home Gateway functionalities, 4 GbE ports and Wi-Fi Dual-Band Concurrent (2.4 GHz bgn 4x4 + 5 GHz anac 4x4) for internet access and IPTV, 2 FXS ports for voice and 1 USB 2.0 port.

For more information, see user's manual provided by the manufacturer.

The information about the 5GHz radio, installed in the model GR240BG, is presented below.

Applicant	Altice Labs, SA
Model No.	GR240BG
FCC ID	2ACJF-FGW-GR240BG
Rated RF Output	802.11a: 21.48 dBm 802.11n 20MHz: 21.39 dBm 802.11n 40MHz: 22.34 dBm 802.11ac 80MHz: 20.99 dBm
Frequency Range	U-NII 2A: 5250 – 5350 MHz
Type of modulation	OFDM
Antenna(s) & Gain	Internal Antenna, 4.95 dBi calculated peak gain Ant 0 – DB1: 4.8dBi, Vertical Ant 1 – DB2: 3.4dBi, Horizontal Ant 2 – DB3: 4.0dBi, Horizontal Ant 3 – DB4: 5.1dBi, Vertical
Manufacturer Name & Address	Altice Labs, SA Rua Eng. Ferreira Pinto Basto 3810-106 Aveiro Portugal

The EUT supports a wide range of data rates in the U-NII-2A band:

IEEE 802.11a
IEEE 802.11n 20MHz
IEEE 802.11n 40MHz
IEEE 802.11ac 20MHz
IEEE 802.11ac 40MHz
IEEE 802.11ac 80MHz

2.2 Related Submittal(s) Grants

None.

2.3 Test Methodology

Antenna conducted measurements were performed according to the FCC documents "Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices Part 15, Subpart E" (789033 D02 General U-NII Test Procedures New Rules v01r04 & 905462 D02 UNII DFS Compliance Procedures New Rules v02).

Both AC mains line-conducted and radiated emissions measurements were performed according to the procedures in ANSI C63.4. Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the **"Data Sheet"** of this Application.

All other measurements were made in accordance with the procedures in part 2 of CFR 47.

2.4 Test Facility

The test site used to collect the radiated data is site 1 (10-m semi-anechoic chamber). This test facility and site measurement data have been fully placed on file with the FCC, IC and A2LA accredited.

2.5 Measurement Uncertainty

Compliance with the limits was based on the results of the measurements and doesn't take into account the measurement uncertainty.

Estimated Measurement Uncertainty

Measurement	Expanded Uncertainty (k=2)		
	0.15 MHz – 1 GHz	1 GHz – 6 GHz	> 6 GHz
RF Power and Power Density – antenna conducted	1.1 dB	1.5 dB	–
Unwanted emissions - antenna conducted	1.2 dB	1.7 dB	2.0 dB
Bandwidth – antenna conducted	50 Hz	100 Hz	–
Radiated emissions	4.2 dB	5.4 dB	
AC mains conducted emissions	2.4 dB	-	-

3.0 System Test Configuration

3.1 Support Equipment

Description	Manufacturer	Model No./ Part No.
Laptop	HP	EliteBook 8470p
Optical Line Termination	Cisco	Cisco ME 4600 Series
Flash Drive	Kingston	DT101G2 8GB
Telephone	TKT	1700137823
Telephone	Alcatel	N/A
Router	Linksys	BEFSR81

3.2 Block Diagram of Test Setup

Equipment Under Test			
Description	**Manufacturer**	**Model Number**	**Serial Number**
FiberGateway (Radiated Unit)	Altice Labs, SA	GR240BG	5054494E912154CF
AC/DC Power Adapter	Airline mechanical Co Ltd	EOSA+4B120-4000	AB1708240092570
FiberGateway (Conducted Unit)	Altice Labs, SA	GR240BG	5054494E9121874F



S = Shielded **U** = Unshielded	**F** = With Ferrite **m** = Meter

3.3 Justification

Preliminary testing was performed for all modulation/data rate modes. The following modes, in which the highest power was detected, were selected for final measurements:

OFDM, 6MB/s – for 802.11a (Power Setting on test firmware: 15)
OFDM, MCS0 – for 802.11n 20MHz (Power Setting on test firmware: 15)
OFDM, MCS0 – for 802.11n 40MHz (Power Setting on test firmware: 16)
OFDM, MCS0 – for 802.11ac 80MHz (Power Setting on test firmware: 15)

According to the manufacture, the FiberGateway utilizes cross-polarized antennas with two vertical (Ant 1 & Ant 4) and two Horizontal (Ant 2 & Ant 3). Per FCC KDB "662911 D01 Multiple Transmitter Output v02r01", the directional gain of the antenna is calculated as below:

Directional gain = $10 \log[(10^{G1/10} + 10^{G2/10} + \ldots + 10^{GN/10})/N_{ANT}]$ dBi
Vertical Gain = 10 log[(10^(4.8/10) + 10^(5.1/10))/2] = 4.9dBi
Horizontal Gain = 10 log[(10^(3.4/10) + 10^(4/10))/2] = 3.7dBi

3.4 Mode of Operation During Test

During transmitter testing, the transmitter was setup to transmit continuously using the maximum RF power setting. Their corresponding output power in dBm can be found in section 4.2 of this report.

3.5 Modifications required for Compliance

The following modification was made by the manufacturer to the EUT in order to bring the EUT into compliance:

Added a ferrite with double loop (Manufacture: Wurth Electronics, Part Number: 74271633S) at the DC input of the FiberGateway (See below).

3.6 Additions, deviations and exclusions from standards

No additions, deviations or exclusion have been made from standard.

4.0 Measurement Results

4.1 Emission Bandwidth and 99% Occupied Bandwidth

15.407(a)(1)(2)

4.1.1 Procedure

The Procedure, described in the FCC Publication 789033 D02 General U-NII Test Procedures New Rules v01r04, was used. Specifically Section C for Emission Bandwidth and Minimum Emission Bandwidth for the band 5.725-5.850 GHz. Section D was used for 99% Occupied Bandwidth.

The antenna port of the EUT was connected to the input of a spectrum analyzer (SA). For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier.

The Occupied bandwidth was measured using the build-in spectrum analyzer facility for 99% power bandwidth measurement.

Tested By:	Minh Ly
Test Date:	December 12, 2017

4.1.2 Test Result

Refer to the following plots for the test result:

Mode	Channel	Frequency, MHz	26-dB Bandwidth, MHz	Occupied Bandwidth, MHz	Plot #
802.11a	52	5260	21.923	17.371	1.1
	60	5300	21.794	17.243	1.2
	64	5320	21.948	17.243	1.3
802.11n 20MHz	52	5260	21.153	18.397	1.4
	60	5300	22.179	18.397	1.5
	64	5320	22.307	18.397	1.6
802.11n 40MHz	54	5270	40.769	36.666	1.7
	62	5310	40.897	36.666	1.8
802.11ac 80MHz	58	5290	82.692	76.153	1.9

Plot 1. 1

802.11a 5260MHz



Date: 11.DEC.2017 11:08:26

Plot 1. 2

802.11a 5300MHz



Date: 11.DEC.2017 11:11:53

Plot 1. 3

802.11a 5320MHz



Date: 11.DEC.2017 11:13:46

Plot 1. 4

802.11n 20MHz, 5260MHz



Date: 11.DEC.2017 11:45:40

Plot 1. 5

802.11n 20MHz, 5300MHz



Date: 11.DEC.2017 11:47:31

Plot 1. 6

802.11n 20MHz, 5320MHz



Date: 11.DEC.2017 11:49:15

Plot 1. 7

802.11n 40MHz, 5270MHz



Date: 11.DEC.2017 11:57:38

Plot 1. 8

802.11n 40MHz, 5310MHz



Date: 11.DEC.2017 12:02:00

Plot 1. 9

802.11AC 80MHz, 5290MHz



Date: 11.DEC.2017 12:10:03

4.2 Maximum Conducted Output Power
FCC Rule 15.407(a)(2)

4.2.1 Requirement

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.2.2 Procedure

The Procedure, described in the FCC Publication 789033 D02 General U-NII Test Procedures New Rules v01r04, was used. Specifically Section E (2) (b) Method SA-1 for Maximum Conducted Output Power

The antenna port output of the EUT was connected to the input of a spectrum analyzer to measure the Maximum Conducted Transmitter Output Power.

Tested By:	Minh Ly
Test Date:	December 12, 2017

4.2.3 Test Results

Refer to the following plots for the test result:

802.11a (6Mbps) – Conducted Average Power

CH	Frequency MHz	Ant 0 – DB1 (dBm)	Plot #	Ant 1 – DB2 (dBm)	Plot #	Ant 2 – DB3 (dBm)	Plot #	Ant 3 – DB4 (dBm)	Plot #
52	5260	15.17	2.1	15.39	2.4	14.80	2.7	15.26	2.10
60	5300	15.65	2.2	15.67	2.5	15.15	2.8	15.35	2.11
64	5320	15.43	2.3	15.70	2.6	15.07	2.9	15.40	2.12

802.11n 20MHz (MCS0) – Conducted Average Power

CH	Frequency MHz	Ant 0 – DB1 (dBm)	Plot #	Ant 1 – DB2 (dBm)	Plot #	Ant 2 – DB3 (dBm)	Plot #	Ant 3 – DB4 (dBm)	Plot #
52	5260	15.12	2.13	15.26	2.16	14.65	2.19	15.08	2.22
60	5300	15.45	2.14	15.60	2.17	15.01	2.20	15.35	2.23
64	5320	15.44	2.15	15.58	2.18	15.12	2.21	15.34	2.24

802.11n 40MHz (MCS0) – Conducted Average Power

CH	Frequency MHz	Ant 0 – DB1 (dBm)	Plot #	Ant 1 – DB2 (dBm)	Plot #	Ant 2 – DB3 (dBm)	Plot #	Ant 3 – DB4 (dBm)	Plot #
54	5270	16.15	2.25	16.22	2.27	15.66	2.29	16.21	2.31
62	5310	16.45	2.26	16.42	2.28	15.96	2.30	16.41	2.32

802.11ac 80MHz (MCS0) – Conducted Average Power

CH	Frequency MHz	Ant 0 – DB1 (dBm)	Plot #	Ant 1 – DB2 (dBm)	Plot #	Ant 2 – DB3 (dBm)	Plot #	Ant 3 – DB4 (dBm)	Plot #
58	5290	14.68	2.33	14.89	2.34	15.68	2.35	14.52	2.36

CH	Frequency (MHz)	Summed power (dBm)	Summed power (W)
802.11a			
52	5260	21.18	0.131
60	5300	21.48	0.141
64	5320	21.43	0.139
802.11n 20MHz			
52	5260	21.05	0.127
60	5300	21.38	0.137
64	5320	21.39	0.138
802.11n 40MHz			
54	5270	22.09	0.162
62	5310	22.34	0.171
802.11ac 80MHz			
58	5290	20.99	0.126

Plot 2. 1



Date: 12.DEC.2017 11:18:11

Plot 2. 2



Date: 12.DEC.2017 14:22:50

Plot 2. 3



Date: 12.DEC.2017 11:29:07

Plot 2. 4



Date: 12.DEC.2017 11:20:18

Plot 2. 5



Date: 12.DEC.2017 11:26:50

Plot 2. 6



Date: 12.DEC.2017 11:29:53

Plot 2. 7



Date: 12.DEC.2017 11:21:08

Plot 2. 8



Date: 12.DEC.2017 11:25:12

Plot 2. 9



Date: 12.DEC.2017 11:30:50

Plot 2. 10



Date: 12.DEC.2017 11:21:56

Plot 2. 11



Date: 12.DEC.2017 11:23:38

Plot 2. 12



Date: 12.DEC.2017 11:31:36

Plot 2. 13



Date: 12.DEC.2017 11:50:21

Plot 2. 14



Date: 12.DEC.2017 11:56:58

Plot 2. 15



Date: 12.DEC.2017 11:58:44

Plot 2. 16



Date: 12.DEC.2017 11:51:31

Plot 2. 17



Date: 12.DEC.2017 11:56:17

Plot 2. 18



Date: 12.DEC.2017 11:59:44

Plot 2. 19



Date: 12.DEC.2017 11:52:28

Plot 2. 20



Date: 12.DEC.2017 11:55:18

Plot 2. 21



Date: 12.DEC.2017 14:25:54

Plot 2. 22



Date: 12.DEC.2017 11:53:15

Plot 2. 23



Date: 12.DEC.2017 11:54:37

Plot 2.
24



Date: 12.DEC.2017 13:39:10

Plot 2. 25



Date: 12.DEC.2017 12:01:14

Plot 2. 26



Date: 12.DEC.2017 13:40:33

Plot 2. 27



Date: 12.DEC.2017 13:38:19

Plot 2. 28



Date: 12.DEC.2017 13:41:29

Plot 2. 29



Date: 12.DEC.2017 13:37:29

Plot 2. 30



Date: 12.DEC.2017 13:42:13

Plot 2. 31



Date: 12.DEC.2017 13:32:51

Plot 2. 32



Date: 12.DEC.2017 13:43:08

Plot 2. 93



Date: 12.DEC.2017 13:59:45

Plot 2. 104



Date: 12.DEC.2017 14:01:00

Plot 2. 115



Date: 12.DEC.2017 14:01:53

Plot 2. 126



Date: 12.DEC.2017 14:05:03

4.3 Peak Power Spectral Density
FCC Rule 15.407(a)(2)

4.3.1 Requirement

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.3.2 Procedure

Each antenna port of the EUT was connected to the input of a spectrum analyzer to measure the Peak Power Spectral Density (PPSD) and recorded.

The Procedure, described in the FCC Publication 789033 D02 General U-NII Test Procedures New Rules v01r04, was used. Specifically procedure from Section F was utilized for Maximum Power Spectral Density (PSD).

Tested By:	Minh Ly
Test Date:	December 12, 2017

4.3.3 Test Result

Refer to the following plots for the test result:

802.11a (6Mbps) – Peak Power Spectral Density

CH	Frequency MHz	Ant 0 – DB1 (dBm)	Plot #	Ant 1 – DB2 (dBm)	Plot #	Ant 2 – DB3 (dBm)	Plot #	Ant 3 – DB4 (dBm)	Plot #
52	5260	4.22	2.1	4.20	2.4	3.76	2.7	4.13	2.10
60	5300	4.64	2.2	4.51	2.5	4.07	2.8	4.17	2.11
64	5320	4.40	2.3	4.53	2.6	4.08	2.9	4.26	2.12

802.11n 20MHz (MCS0) –Power Spectral Density

CH	Frequency MHz	Ant 0 – DB1 (dBm)	Plot #	Ant 1 – DB2 (dBm)	Plot #	Ant 2 – DB3 (dBm)	Plot #	Ant 3 – DB4 (dBm)	Plot #
52	5260	3.82	2.13	3.90	2.16	3.36	2.19	3.70	2.22
60	5300	4.10	2.14	4.31	2.17	3.68	2.20	4.09	2.23
64	5320	4.04	2.15	4.25	2.18	3.73	2.21	4.09	2.24

802.11n 40MHz (MCS0) –Power Spectral Density

CH	Frequency MHz	Ant 0 – DB1 (dBm)	Plot #	Ant 1 – DB2 (dBm)	Plot #	Ant 2 – DB3 (dBm)	Plot #	Ant 3 – DB4 (dBm)	Plot #
54	5270	1.94	2.25	2.04	2.27	1.46	2.29	2.07	2.31
62	5310	2.25	2.26	2.02	2.28	1.52	2.30	2.13	2.32

802.11n 40MHz (MCS0) –Power Spectral Density

CH	Frequency MHz	Ant 0 – DB1 (dBm)	Plot #	Ant 1 – DB2 (dBm)	Plot #	Ant 2 – DB3 (dBm)	Plot #	Ant 3 – DB4 (dBm)	Plot #
58	5290	-2.56	2.33	-2.56	2.34	-1.57	2.35	-2.68	2.36

MIMO - Power Spectral Density

CH	Frequency (MHz)	Summed PSD (dBm)	Limit (dBm)	Margin (dB)
802.11a				
52	5260	10.10	11	-0.90
60	5300	10.37	11	-0.63
64	5320	10.34	11	-0.66
802.11n 20MHz				
52	5260	9.72	11	-1.28
60	5300	10.07	11	-0.93
64	5320	10.05	11	-0.95
802.11n 40MHz				
54	5270	7.90	11	-3.10
62	5310	8.01	11	-2.99
802.11ac 80MHz				
58	5290	3.70	11	-7.30

4.4 Frequency stability
FCC 15.407(g)

4.4.1 Requirement

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

4.4.2 Procedure

The EUT was placed in a temperature chamber and setup to transmit. Procedures for frequency stability in ANSIC63.10:2013 section 6.8 was utilized.

The carrier frequency was measured with the spectrum analyzer with resolution bandwidth of 1 kHz.
The temperature was varied from 0°C to 50°C, as stated in the user manual.

The EUT in this report is powered by 120.0VAC which was varied to 85% and 115% for testing. Testing was performed at a temperature of 20° C.
.

After the temperature stabilized for approximately 20 minutes, the transmitting frequency was measured.

Tested By:	Minh Ly
Test Date:	December 13, 2017

4.4.3 Result

Temperature, ^{0}C	**-26dB Band Edge at nominal voltage, (MHz)**	**Maximum deviation from frequency at 20°C, ppm**
Nominal Frequency: 5320 MHz		
50	5330.961538	12.025
40	5330.833333	12.025
30	5330.961538	12.025
20	5330.897436	0.000
10	5330.865438	6.002
0	5330.863442	6.377
Voltage at 20^{0}C	**-26dB Band Edge at nominal voltage, (MHz)**	**Maximum deviation from frequency at 20°C, ppm**
120V – 15%	5330.886445	6.377
120V + 15%	5330.882457	2.062

4.5 Transmitter Radiated Emissions
FCC Rule 15.407(b) (1-8) 15.209, 15.205

4.5.1 Requirement

(b) Undesirable emission limits. Except as shown in paragraph (b) (7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of −27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.

(6) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

(7) The provisions of §15.205 apply to intentional radiators operating under this section.

(8) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.

Emissions which fall in the restricted bands, as defined in §15.205(a), must comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

For transmitters operating in the 5.15–5.25 GHz band: all emissions outside of the 5.15–5.35 GHz band shall not exceed an EIRP of –27 dBm/MHz.

Note: An out-of-band emission that complies with both the average and peak limits of Section 15.209 is not required to satisfy the -27 dBm/MHz peak emission limit.

4.5.2 Procedure

Radiated emission measurements were performed from 30 MHz to 40 GHz according to the procedure described in ANSI C64.10. Spectrum Analyzer Resolution Bandwidth is 100 kHz or greater for frequencies 30 MHz to 1000 MHz, 1 MHz for frequencies above 1000 MHz. Above 1000 MHz Peak and Average measurements were performed.

The EUT is placed on a plastic turntable that is 80 cm in height for below 1000MHz and 1.5m in height for above 1GHz. If the EUT attaches to peripherals, they are connected and operational (as typical as possible). During testing, all cables were manipulated to produce worst-case emissions. The signal is maximized through rotation. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters.

Radiated emissions are taken at 1 meter for Band Edge measurements. Radiated spurious emissions are taken at 3 meters for frequencies above 1 GHz and at 10 meters for frequencies below 1 GHz.

The 2.4GHz and 5GHz radio can transmit simultaneously; both of the transmitters are turned on during spurious emission to investigate for inter-modulation emission. Measurements made from 1 GHz to 18 GHz had a 2.4-2.5GHz and 5GHz notch filter in place. A preamp was used from 30MHz to 40GHz.

All measurements were made with a Peak Detector and compared to QP limits for 30MHz – 1GHz and Average limits for 1GHz – 40 GHz.

Data is included of the worst-case configuration (the configuration which resulted in the highest emission levels).

4.5.3 Field Strength Calculation

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CF – AG; if measurement is performed at a distance other than specified in the rule, a Distance Correction Factor (DCF) shall be added.

Where FS = Field Strength in dB(μV/m)
RA = Receiver Amplitude (including preamplifier) in dB(μV); AF = Antenna Factor in dB(1/m)
CF = Cable Attenuation Factor in dB; AG = Amplifier Gain in dB

Assume a receiver reading of 52.0 dB(μV) is obtained. The antennas factor of 7.4 dB(1/m) and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted, giving field strength of 32 dB(μV/m). This value in dB(μV/m) was converted to its corresponding level in μV/m.
RA = 52.0 dB(μV)
AF = 7.4 dB(1/m)
CF = 1.6 dB
AG = 29.0 dB
FS = 52.0+7.4+1.6-29.0 = 32 dB(μV/m).
Level in μV/m = Common Antilogarithm [(32 dBμV/m)/20] = 39.8 μV/m.

4.5.4 Test Results

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance where emissions are within 3dB of the limit.

Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz.

Test Results: 15.209/15.205 Restricted Band Emissions

Tested By:	Minh Ly
Test Date:	December 05 - 08, 2017

Out-of-Band Spurious Emissions at the Band Edge @1m Distance
802.11a, 5320 MHz



Model: ; Client: ; Comments: ; Test Date: 12/05/2017 15:26



Model: ; Client: ; Comments: ; Test Date: 12/05/2017 13:58

Frequency (MHz)	Average (dBµV/m)	Lim. Avg (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
5350.002	49.0	54.0	-5.0	1.8	312	Horizontal	28.7
5350.622	49.3	54.0	-4.7	1.6	319	Vertical	28.7

Out-of-Band Spurious Emissions at the Band Edge @1m Distance
802.11 n 20MHz, 5320 MHz



Model: ; Client: ; Comments: ; Test Date: 12/05/2017 16:16

Frequency (MHz)	Peak (dBµV/m)	Lim. Peak (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
5350.000	69.1	74.0	-4.9	1.5	360	Horizontal	28.7
5350.021	69.8	74.0	-4.3	1.5	316	Vertical	28.7



Model: ; Client: ; Comments: ; Test Date: 12/05/2017 16:01

Frequency (MHz)	Average (dBµV/m)	Lim. Avg (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
5350.000	52.7	54.0	-1.4	1.7	309	Horizontal	28.7
5350.000	52.1	54.0	-1.9	1.6	0	Vertical	28.7

Out-of-Band Spurious Emissions at the Band Edge @1m Distance
802.11n 40MHz, 5310 MHz



Model: ; Client: ; Comments: ; Test Date: 12/05/2017 16:59

Frequency (MHz)	Peak (dBµV/m)	Lim. Peak (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
5350.000	67.7	74.0	-6.3	1.5	234	Horizontal	28.7
5350.021	69.6	74.0	-4.4	1.5	298	Vertical	28.7



Model: ; Client: ; Comments: ; Test Date: 12/05/2017 16:38

Frequency (MHz)	Average (dBµV/m)	Lim. Avg (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
5352.884	52.3	54.0	-1.7	1.7	312	Horizontal	28.7
5350.436	52.4	54.0	-1.6	1.6	360	Vertical	28.7

Out-of-Band Spurious Emissions at the Band Edge @1m Distance
802.11ac 80MHz, 5290 MHz



Model: ; Client: ; Comments: ; Test Date: 12/05/2017 18:15



Model: ; Client: ; Comments: ; Test Date: 12/05/2017 17:52

Frequency (MHz)	Average (dBµV/m)	Lim. Avg (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
5346.966	51.9	54.0	-2.1	1.5	324	Horizontal	28.7
5349.764	51.6	54.0	-2.4	1.6	309	Horizontal	28.7
5349.996	53.2	54.0	-0.8	1.6	360	Vertical	28.7
5352.480	52.4	54.0	-1.6	1.7	0	Vertical	28.7

Test Results: 15.209 Radiated Spurious Emissions Low Channel, Tx at 802.11b 2412MHz, and 802.11a 5260MHz

Radiated Spurious Emissions - 30 MHz to 1000 MHz



Model: ; Client: ; Comments: ; Test Date: 12/08/2017 10:08

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 11:50

Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 11:35

- 2412MHz peak is the fundamental frequency of the 2.4GHz band.

Frequency (MHz)	Average (dBµV/m)	Lim. Avg (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
4010.7	44.1	54.0	-9.9	2.5	134.3	Horizontal	4.25

Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz

Test Results: 15.209 Radiated Spurious Emissions Low Channel, Tx at 802.11b 2437MHz, and 802.11a 5300MHz

Radiated Spurious Emissions - 30 MHz to 1000 MHz



Model: ; Client: ; Comments: ; Test Date: 12/08/2017 10:22

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 12:06

Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 12:00

- 2437MHz peak is the fundamental frequency of the 2.4GHz band.

Frequency (MHz)	Average (dBµV/m)	Lim. Avg (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
1034.000	46.3	54.0	-7.7	1.5	0	Horizontal	-6.2

Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz

Test Results: 15.209 Radiated Spurious Emissions Low Channel, Tx at 802.11b 2462MHz, and 802.11a 5320MHz

Radiated Spurious Emissions - 30 MHz to 1000 MHz



Model: ; Client: ; Comments: ; Test Date: 12/08/2017 10:34

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 13:16

Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 12:16

- 5320MHz peak is the fundamental frequency.

Frequency (MHz)	Average (dBµV/m)	Lim. Avg (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
1034.000	47.9	54.0	-6.1	2.5	227	Vertical	-6.2

Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz

Test Results: 15.209 Radiated Spurious Emissions Low Channel, Tx at 802.11n 20MHz 2412MHz, and 802.11n 20MHz 5260MHz

Radiated Spurious Emissions - 30 MHz to 1000 MHz



Model: ; Client: ; Comments: ; Test Date: 12/08/2017 11:22

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 13:32

Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 13:25

- 2412MHz peak is the fundamental frequency of the 2.4GHz band.

Frequency (MHz)	Average (dBµV/m)	Lim. Avg (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
1033.433	44.3	54.0	-9.7	1.5	0	Horizontal	-6.2

Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz

Test Results: 15.209 Radiated Spurious Emissions Low Channel, Tx at 802.11n 20MHz 2437MHz, and 802.11n 20MHz 5300MHz

Radiated Spurious Emissions - 30 MHz to 1000 MHz

Model: ; Client: ; Comments: ; Test Date: 12/08/2017 11:33

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 13:56

Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 13:42

- 2437MHz peak is the fundamental frequency of the 2.4GHz band..

Frequency (MHz)	Average (dBµV/m)	Lim. Avg (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
5889.200	51.5	54.0	-2.5	1.5	111	Vertical	9.6

Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz

Test Results: 15.209 Radiated Spurious Emissions Low Channel, Tx at 802.11n 20MHz 2462MHz, and 802.11n 20MHz 5320MHz

Radiated Spurious Emissions - 30 MHz to 1000 MHz



Model: ; Client: ; Comments: ; Test Date: 12/08/2017 11:46

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 14:11

Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 14:05

- 2462MHz peak is the fundamental frequency of the 2.4GHz band.

Frequency (MHz)	Average (dBµV/m)	Lim. Avg (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
1005.667	47.0	54.0	-7.0	2.5	320	Vertical	-6.4

Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz

Test Results: 15.209 Radiated Spurious Emissions Low Channel, Tx at 802.11n 40MHz 2462MHz, and 802.11n 40MHz 5270MHz

Radiated Spurious Emissions - 30 MHz to 1000 MHz



Model: ; Client: ; Comments: ; Test Date: 12/08/2017 13:06

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 14:25

Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 14:18

- 2462MHz peak is the fundamental frequency of the 2.4GHz band.

Frequency (MHz)	Average (dBµV/m)	Lim. Avg (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
1019.833	46.5	54.0	-7.5	2.5	251	Vertical	-6.3

Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz

Test Results: 15.209 Radiated Spurious Emissions Low Channel, Tx at 802.11n 40MHz 2437MHz, and 802.11n 40MHz 5310MHz

Radiated Spurious Emissions - 30 MHz to 1000 MHz



Model: ; Client: ; Comments: ; Test Date: 12/08/2017 13:17

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 14:37

Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 14:30

- 2437MHz peak is the fundamental frequency of the 2.4GHz band.

Frequency (MHz)	Average (dBµV/m)	Lim. Avg (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
1034.000	49.6	54.0	-4.4	2.5	204	Vertical	-6.2

Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz

Test Results: 15.209 Radiated Spurious Emissions Low Channel, Tx at 802.11n 40MHz 2462MHz, and 802.11ac 80MHz 5290MHz

Radiated Spurious Emissions - 30 MHz to 1000 MHz



Model: ; Client: ; Comments: ; Test Date: 12/08/2017 14:04

Radiated Spurious Emissions 1000 - 18000 MHz, Peak Scan vs Peak Limit



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 14:50

Radiated Spurious Emissions 1000 - 18000 MHz, Avg Scan vs Avg Limit



Model: ; Client: ; Comments: ; Test Date: 12/07/2017 14:44

- 2462MHz peak is the fundamental frequency of the 2.4GHz band.

Frequency (MHz)	Average (dBµV/m)	Lim. Avg (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)
1034.000	44.3	54.0	-9.7	2.5	64	Vertical	-6.2

Note: Radiated emission measurements were performed up to 40GHz. No Emissions were identified when scanned from 18-40 GHz

4.5.5 Test setup photographs

The following photographs show the testing configurations used.





4.5.5 Test setup photographs (Continued)





5.0 List of Test Equipment

Measurement equipment used for emission compliance testing utilized the equipment on the following list:

Equipment	Manufacturer	Model/Type	Asset #	Cal Int	Cal Due
Spectrum Analyzer	Rohde and Schwarz	FSU	ITS 00913	12	01/12/18
EMI Receiver	Rohde and Schwarz	ESU	ITS 00961	12	07/10/18
Pyramidal Horn Antenna	EMCO	3160-09	ITS 00571	#	#
Pyramidal Horn Antenna	EMCO	3160-10	ITS 00572	#	#
Horn Antenna	ETS-Lindgren	3117	ITS 00982	12	02/03/18
BI-Log Antenna	Teseq	CBL 6111D	ITS 01058	12	08/11/18
Pre-Amplifier (18-40GHz)	Miteq	TTA1840-35-S-M	ITS 01393	12	04/18/18
Pre-Amplifier (1-18GHz)	Miteq	AMF-4D-001180-24-10P	ITS 00526	12	01/04/18
Pre-Amplifier	Sonoma Instrument	310	ITS 00942	12	01/19/18
Notch Filter	Micro-Tronics	BRM50702	ITS 01166	12	02/08/18
Notch Filter	Micro-Tronics	BRM50703	ITS 01167	12	01/19/18
Notch Filter	Micro-Tronics	BRM50705	ITS 01169	12	01/19/18
RF Cable	TRU Corporation	TRU CORE 300	ITS 01462	12	08/19/18
RF Cable	TRU Corporation	TRU CORE 300	ITS 01465	12	08/19/18
RF Cable	TRU Corporation	TRU CORE 300	ITS 01470	12	08/19/18
Attenuator	Mini Circuits	BW-N3W5+	ITS 01316	12	11/29/18
Attenuator	Narda	FSCM99899	ITS 01583	12	08/31/18
RF Cable	Megaphase	EMC1-K1K1-236	ITS 01538	12	06/13/18
RF Cable	Megaphase	TM40-K1K1-19	ITS 01154	12	01/26/18
RF Cable	Megaphase	TM40-K1K1-59 RF	ITS 01156	12	01/26/18

No Calibration required

Software used for emission compliance testing utilized the following:

Name	Manufacturer	Version	Template/Profile
BAT-EMC	Nexio	3.16.0.64	Altice, ML_12-08-2017.bpp Altice, ML_12-05-2017.bpp
RS Commander	Rohde Schwarz	1.6.4	Not Applicable (Screen grabber)

6.0 Document History

Revision/ Job Number	Writer Initials	Reviewer Initials	Date	Change
1.0 / G103224477	ML	KV	December 27, 2017	Original document