

FCC PART 15.407

TEST REPORT

For

MULTI-GOLD INDUSTRIAL LIMITED

Lasting Pear Industrial Section, No.2 Qianjin Road, Xixiang Town, Baoan District, Shenzhen,
China

FCC ID:2ACJSMGSC10

Report Type: Original Report	Product Name: Tablet PC
Report Number: RXM200715056-00C	
Report Date: 2020-08-06	
Ivan Cao 	
Reviewed By: Assistant Manager	
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
DECLARATIONS.....	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	9
SUPPORT CABLE LIST AND DETAILS	9
BLOCK DIAGRAM OF TEST SETUP	9
SUMMARY OF TEST RESULTS.....	10
FCC §15.407 (f) & §1.1310 & §2.1093- RF EXPOSURE	11
APPLICABLE STANDARD	11
TEST RESULT	11
FCC §15.203- ANTENNA REQUIREMENT	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.207(a)- CONDUCTED EMISSIONS.....	13
APPLICABLE STANDARD	13
EUT SETUP	13
EMI TEST RECEIVER SETUP.....	13
CORRECTED AMPLITUDE & MARGIN CALCULATION	14
TEST EQUIPMENT LIST AND DETAILS.....	14
TEST PROCEDURE	14
TEST DATA	15
FCC §15.209, §15.205 , §15.407(b) –UNWANTED EMISSION	17
APPLICABLE STANDARD	17
EUT SETUP	18
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	19
TEST PROCEDURE	19
CORRECTED AMPLITUDE & MARGIN CALCULATION	20
TEST EQUIPMENT LIST AND DETAILS.....	21
TEST DATA	21
FCC §15.407(a)(e)–EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH.....	30
APPLICABLE STANDARD	30
TEST EQUIPMENT LIST AND DETAILS.....	30
TEST PROCEDURE	30
TEST DATA	30
FCC §15.407(a) –MAXIMUM CONDUCTED OUTPUT POWER.....	41
APPLICABLE STANDARD	41

TEST EQUIPMENT LIST AND DETAILS.....	42
TEST PROCEDURE	42
TEST DATA	42
FCC §15.407(a) - POWER SPECTRAL DENSITY	44
APPLICABLE STANDARD	44
TEST PROCEDURE	45
TEST EQUIPMENT LIST AND DETAILS.....	45
TEST DATA	45

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:		Tablet PC
EUT Model:		MGSC10
Multiple Model:		MGSC30
Operation Frequency:		5180-5240MHz(802.11a/n ht20), 5190-5230 MHz(802.11n ht40) 5210 MHz(802.11ac vht80)
Maximum Output Power (Conducted):		14.69 dBm
Modulation Type:		OFDM
Rated Input Voltage:		DC 3.7V from battery or DC 5V from Adapter
Adapter Information	Model:	K-T100502000U
	Input:	100-240Vac 50-60Hz 0.35A Max
	Output:	5.0Vdc 2000mA
Serial Number:		RXM200715056-RF -S1
EUT Received Date:		2020.07.15
EUT Received Status:		Good

Notes: Model MGSC10 was selected for fully testing, the detailed information about the difference among MGSC30 and mode MGSC10 can be referred to the declaration letter which was stated and guaranteed by the manufacturer.

Objective

This type approval report is prepared on behalf of **MULTI-GOLD INDUSTRIAL LIMITED** in accordance with Part 2-Subpart J, Part 15-Subparts A, and E of the Federal Communications Commission's rules.

The tests were performed in order to determine compliance with FCC Rules Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

Related Submittal(s)/Grant(s)

FCC Part 15C DSS,DTS submissions with FCC ID: 2ACJSMGSC10.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And KDB 789033 D02 General U-NII Test Procedures New Rules v02r01.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “△”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the U.S. Government.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system supports 802.11a/n ht20/n ht40/ac vht20/ac vht40/ac vht80 modes the vht20/vht40 were reduced since the identical parameters with 802.11n ht20 and ht40.

For 5150~5250 MHz band, 7 channels are provided:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
38	5190	46	5230
40	5200	48	5240
42	5210	/	/

For 802.11a, 802.11n ht20 channel 36, 40 and 48 was tested, for 802.11n ht40 channel 38, 46 were tested. for 802.11ac vht80, channel 42 was tested.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.


EUT Exercise Software

The software “engineering mode” was used for testing, which was provided by manufacturer. The maximum power was configured as below table, that provided by the manufacturer:


Mode	Channel	Test Frequency (MHz)	Data rate	Power level Setting
802.11a	Low	5180	6 Mbps	11
	Middle	5200	6 Mbps	11
	High	5240	6 Mbps	11
802.11n ht20	Low	5180	MCS0	11
	Middle	5200	MCS0	11
	High	5240	MCS0	11
802.11n ht40	Low	5190	MCS0	15
	High	5230	MCS0	15
802.11ac vht80	Middle	5210	MCS0	15

The duty cycle as below:


Mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
802.11 a	1.392	1.656	84.06
802.11n ht20	1.200	1.452	82.64
802.11n ht40	0.600	0.870	68.97
802.11ac v ht80	0.315	0.590	53.39

802.11a


Date: 31.JUL.2020 21:32:03

802.11n ht20

Date: 31.JUL.2020 21:32:54

802.11n ht40

Date: 31.JUL.2020 21:34:43

802.11ac vht80

Date: 31.JUL.2020 21:36:11


Equipment Modifications

No modification was made to the EUT.

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	No	No	0.8	Adapter	EUT
Earphone Cable	No	No	1.2	EUT	Earphone

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

Rules	Description of Test	Result
FCC §15.407 (f) & §1.1310 & §2.1093	RF Exposure	Compliance
FCC§15.203,	Antenna Requirement	Compliance
FCC§15.407(b)(6)& §15.207(a)	Conducted Emissions	Compliance
FCC§15.205& §15.209 &§15.407(b)	Undesirable Emission& Restricted Bands	Compliance
FCC§15.407(b)	Out Of Band Emissions	Compliance
FCC§15.407(a) (e)	Emission Bandwidth	Compliance
FCC§15.407(a) RSS-247 Clause 6.2	Conducted Transmitter Output Power	Compliance
FCC§15.407 (a),	Power Spectral Density	Compliance

FCC §15.407 (f) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.407(f), §1.1310 and §2.1093.

Test Result

Compliant, please refer to the SAR report: RXM200715056-20.

FCC §15.203- ANTENNA REQUIREMENT**Applicable Standard**

According to FCC§ 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

Antenna Connector Construction

The EUT has one internal FPC antenna arrangement for BT/WLAN, fulfill the requirement of this section. Please refer to the EUT photos.

Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range
FPC	50	-1.2 dBi/2.4~2.5GHz -1.2 dBi/5.15-5.85GHz


Result: Compliance.

FCC §15.207(a)– CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a), §15.407(b) (6).

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main lisn with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV 216	101614	2019-09-12	2020-09-12
R&S	EMI Test Receiver	ESCI	101121	2020-05-09	2021-05-09
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-01	2019-09-05	2020-09-05
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.


Test Data**Environmental Conditions**

Temperature:	29.0 °C
Relative Humidity:	61 %
ATM Pressure:	100.3 kPa
Tester:	Leo Long
Test Date:	2020-07-27

Test Result: Compliance*Test Mode: Transmitting***AC120 V, 60 Hz, Line:****Final Result**

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.155329	51.51	---	65.71	14.20	9.000	L1	9.7
0.169074	49.80	---	65.01	15.21	9.000	L1	9.7
0.193446	46.21	---	63.89	17.68	9.000	L1	9.7
0.219135	44.89	---	62.85	17.96	9.000	L1	9.7
0.239718	43.93	---	62.11	18.18	9.000	L1	9.7
0.272910	39.93	---	61.03	21.10	9.000	L1	9.7
0.582452	---	25.51	46.00	20.49	9.000	L1	9.7
0.643549	---	37.76	46.00	8.24	9.000	L1	9.7
0.669745	---	32.46	46.00	13.54	9.000	L1	9.7

AC120 V, 60 Hz, Neutral:



Final Result

Frequency (MHz)	QuasiPeak (dB µ V)	Average (dB µ V)	Limit (dB µ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.150000	53.15	---	66.00	12.85	9.000	N	9.7
0.168233	51.28	---	65.05	13.77	9.000	N	9.7
0.185880	49.05	---	64.22	15.17	9.000	N	9.7
0.216960	46.63	---	62.93	16.30	9.000	N	9.7
0.232651	45.41	---	62.35	16.94	9.000	N	9.7
0.264864	42.48	---	61.28	18.80	9.000	N	9.7
0.646766	---	26.79	46.00	19.21	9.000	N	9.6

FCC §15.209, §15.205 , §15.407(b) –UNWANTED EMISSION

Applicable Standard

FCC §15.407; §15.209; §15.205;

(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in §15.247(d), but manufac vhturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in §15.247(d), but manufac vhturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.


(5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.

(6) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.


(7) The provisions of §15.205 apply to intentional radiators operating under this section.

EUT Setup


Below 1 GHz:



1-26.5 GHz:



26.5-40 GHz:



The radiated emission Below 1GHz tests were performed in the 10 meters chamber test site , above 1GHz tests were performed in the 3 meters chamber test site B, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 40GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz, peak and Average detection modes for frequencies above 1GHz.

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, emission shall be computed as: $E [dB\mu V/m] = EIRP[dBm] + 95.2$, for $d = 3$ meters.

According to C63.10, the above 1G test result shall be extrapolated to the specified distance using an extrapolation factor of 20dB/decade from 3m to 1.5m or 1m

Distance extrapolation factor = $20 \log (\text{specific distance } [3m] / \text{test distance } [1.5m])$ dB= 6.02 dB
or

Distance extrapolation factor = $20 \log (\text{specific distance } [3m] / \text{test distance } [1m])$ dB= 9.54 dB

All emissions under the average limit and under the noise floor have not recorded in the report.

Corrected Amplitude & Margin Calculation

For the range 30MHz-1GHz, the Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

For the range 1GHz-40GHz, Test performed at 1.5m or 1m, the Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading and the Distance extrapolation factor. The basic equation is as follows:

$$\begin{aligned} &\text{Corrected Amplitude} \\ &= \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain} - \text{Distance extrapolation factor} \end{aligned}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiation Below 1GHz					
Sunol Sciences	Antenna	JB3	A060611-2	2017-08-25	2020-08-25
R&S	EMI Test Receiver	ESCI	100224	2019-09-12	2020-09-12
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-02	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2019-09-24	2020-09-24
Sonoma	Amplifier	310N	185914	2019-10-13	2020-10-13
Radiation Above 1GHz					
ETS-Lindgren	Horn Antenna	3115	000 527 35	2018-10-12	2021-10-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2017-12-06	2020-12-05
Ducommun Technologies	Horn Antenna	ARH-2823-02	1007726-01 1302	2017-12-06	2020-12-05
R&S	Spectrum Analyzer	FSP 38	100478	2020-07-07	2021-07-07
Agilent	Spectrum Analyzer	E4440A	SG43360054	2020-07-07	2021-07-07
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-2.4J2.4J-50	C-0700-02	2020-06-27	2021-06-27
Mini-Circuit	Amplifier	ZVA-213-S+	54201245	2019-09-05	2020-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2020-06-27	2021-06-27
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Sinoscite	Bandstop Filters	BSF5150-5850MN-0899-003	899003	2020-05-06	2021-05-06
Micro-tronics	High Pass Filter	HPM50111	S/N-G217	2020-06-16	2021-06-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data**Environmental Conditions**

Test Items	Radiation Below 1GHz	Radiation Above 1GHz
Temperature:	21.9°C	29°C
Relative Humidity:	42%	45%
ATM Pressure:	100.4kPa	100.7kPa
Tester:	Joker Chen	Bond Qin
Test Date:	2020-08-03	2020-08-05


Test Mode: Transmitting

1) Below 1GHz (802.11a 5200 MHz was the worst):

Horizontal



Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Fac vhtor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
59.1000	47.29	peak	-16.64	30.65	40.00	9.35
88.2000	47.10	peak	-15.30	31.80	43.50	11.70
139.6100	45.83	peak	-9.37	36.46	43.50	7.04
169.6800	46.09	QP	-9.64	36.45	43.50	7.05
332.6400	37.44	peak	-7.00	30.44	46.00	15.56
691.5400	31.95	peak	0.19	32.14	46.00	13.86

Vertical:80.0 dB μ V/m

Frequency (MHz)	Receiver Reading (dB μ V)	Detector	Correction Fac vhtor (dB/m)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
51.3400	47.46	peak	-16.45	31.01	40.00	8.99
140.5800	44.29	peak	-9.36	34.93	43.50	8.57
164.8300	44.53	peak	-9.51	35.02	43.50	8.48
300.6300	37.75	peak	-7.45	30.30	46.00	15.70
362.7100	37.04	peak	-6.08	30.96	46.00	15.04
523.7300	34.38	peak	-2.52	31.86	46.00	14.14

**2) 1GHz-40GHz:
802.11a**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Extrapolation result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Fac vhtor (dB/m)						
Low Channel: 5180 MHz										
5180.00	68.90	PK	H	33.59	3.58	0.00	106.07	100.05	N/A	N/A
5180.00	59.54	AV	H	33.59	3.58	0.00	96.71	90.69	N/A	N/A
5180.00	69.23	PK	V	33.59	3.58	0.00	106.40	100.38	N/A	N/A
5180.00	57.90	AV	V	33.59	3.58	0.00	95.07	89.05	N/A	N/A
5150.00	27.68	PK	V	33.54	3.56	0.00	64.78	58.76	74.00	15.24
5150.00	17.63	AV	V	33.54	3.56	0.00	54.73	48.71	54.00	5.29
10360.00	35.69	PK	V	38.17	6.29	25.46	54.69	48.67	68.20	19.53
15540.00	35.63	PK	V	38.06	8.85	24.27	58.27	52.25	74.00	21.75
15540.00	24.51	AV	V	38.06	8.85	24.27	47.15	41.13	54.00	12.87
Middle Channel: 5200 MHz										
5200.00	70.79	PK	H	33.62	3.60	0.00	108.01	101.99	N/A	N/A
5200.00	62.25	AV	H	33.62	3.60	0.00	99.47	93.45	N/A	N/A
5200.00	71.11	PK	V	33.62	3.60	0.00	108.33	102.31	N/A	N/A
5200.00	63.69	AV	V	33.62	3.60	0.00	100.91	94.89	N/A	N/A
10400.00	34.69	PK	V	38.18	6.32	25.46	53.73	47.71	68.20	20.49
15600.00	37.61	PK	V	38.00	8.83	24.31	60.13	54.11	74.00	19.89
15600.00	25.97	AV	V	38.00	8.83	24.31	48.49	42.47	54.00	11.53
High Channel: 5240 MHz										
5240.00	69.78	PK	H	33.68	3.52	0.00	106.98	100.96	N/A	N/A
5240.00	61.75	AV	H	33.68	3.52	0.00	98.95	92.93	N/A	N/A
5240.00	70.05	PK	V	33.68	3.52	0.00	107.25	101.23	N/A	N/A
5240.00	62.05	AV	V	33.68	3.52	0.00	99.25	93.23	N/A	N/A
5350.00	27.60	PK	V	33.86	3.52	0.00	64.98	58.96	74.00	15.04
5350.00	17.50	AV	V	33.86	3.52	0.00	54.88	48.86	54.00	5.14
10480.00	36.01	PK	V	38.20	6.37	25.47	55.11	49.09	68.20	19.11
15720.00	37.56	PK	V	37.88	8.79	24.39	59.84	53.82	74.00	20.18
15720.00	25.98	AV	V	37.88	8.79	24.39	48.26	42.24	54.00	11.76

802.11n ht20

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Extrapolation result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Fac vhtor (dB/m)						
Low Channel: 5180 MHz										
5180.00	68.02	PK	H	33.59	3.58	0.00	105.19	99.17	N/A	N/A
5180.00	57.58	AV	H	33.59	3.58	0.00	94.75	88.73	N/A	N/A
5180.00	67.41	PK	V	33.59	3.58	0.00	104.58	98.56	N/A	N/A
5180.00	56.75	AV	V	33.59	3.58	0.00	93.92	87.9	N/A	N/A
5150.00	27.53	PK	V	33.54	3.56	0.00	64.63	58.61	74.00	15.39
5150.00	15.04	AV	V	33.54	3.56	0.00	52.14	46.12	54.00	7.88
10360.00	35.63	PK	V	38.17	6.29	25.46	54.63	48.61	68.20	19.59
15540.00	36.58	PK	V	38.06	8.85	24.27	59.22	53.2	74.00	20.80
15540.00	23.98	AV	V	38.06	8.85	24.27	46.62	40.6	54.00	13.40
Middle Channel: 5200 MHz										
5200.00	70.02	PK	H	33.62	3.60	0.00	107.24	101.22	N/A	N/A
5200.00	57.41	AV	H	33.62	3.60	0.00	94.63	88.61	N/A	N/A
5200.00	70.24	PK	V	33.62	3.60	0.00	107.46	101.44	N/A	N/A
5200.00	57.63	AV	V	33.62	3.60	0.00	94.85	88.83	N/A	N/A
10400.00	36.56	PK	V	38.18	6.32	25.46	55.60	49.58	68.20	18.62
15600.00	37.31	PK	V	38.00	8.83	24.31	59.83	53.81	74.00	20.19
15600.00	24.65	AV	V	38.00	8.83	24.31	47.17	41.15	54.00	12.85
High Channel: 5240 MHz										
5240.00	68.76	PK	H	33.68	3.52	0.00	105.96	99.94	N/A	N/A
5240.00	56.47	AV	H	33.68	3.52	0.00	93.67	87.65	N/A	N/A
5240.00	69.88	PK	V	33.68	3.52	0.00	107.08	101.06	N/A	N/A
5240.00	57.21	AV	V	33.68	3.52	0.00	94.41	88.39	N/A	N/A
5350.00	27.22	PK	V	33.86	3.52	0.00	64.60	58.58	74.00	15.42
5350.00	15.10	AV	V	33.86	3.52	0.00	52.48	46.46	54.00	7.54
10480.00	36.46	PK	V	38.20	6.37	25.47	55.56	49.54	68.20	18.66
15720.00	37.11	PK	V	37.88	8.79	24.39	59.39	53.37	74.00	20.63
15720.00	24.50	AV	V	37.88	8.79	24.39	46.78	40.76	54.00	13.24




802.11n ht40


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Extrapolation result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Fac vhtor (dB/m)						
Low Channel: 5190 MHz										
5190.00	67.10	PK	H	33.60	3.59	0.00	104.29	98.27	N/A	N/A
5190.00	53.58	AV	H	33.60	3.59	0.00	90.77	84.75	N/A	N/A
5190.00	68.11	PK	V	33.60	3.59	0.00	105.30	99.28	N/A	N/A
5190.00	54.62	AV	V	33.60	3.59	0.00	91.81	85.79	N/A	N/A
5150.00	27.30	PK	V	33.54	3.56	0.00	64.40	58.38	74.00	15.62
5150.00	15.02	AV	V	33.54	3.56	0.00	52.12	46.1	54.00	7.90
10380.00	35.62	PK	V	38.18	6.31	25.46	54.65	48.63	68.20	19.57
15570.00	35.87	PK	V	38.03	8.84	24.29	58.45	52.43	74.00	21.57
15570.00	23.41	AV	V	38.03	8.84	24.29	45.99	39.97	54.00	14.03
High Channel: 5230 MHz										
5230.00	66.56	PK	H	33.67	3.54	0.00	103.77	97.75	N/A	N/A
5230.00	53.21	AV	H	33.67	3.54	0.00	90.42	84.4	N/A	N/A
5230.00	67.26	PK	V	33.67	3.54	0.00	104.47	98.45	N/A	N/A
5230.00	53.75	AV	V	33.67	3.54	0.00	90.96	84.94	N/A	N/A
5350.00	27.19	PK	V	33.86	3.52	0.00	64.57	58.55	74.00	15.45
5350.00	15.09	AV	V	33.86	3.52	0.00	52.47	46.45	54.00	7.55
10460.00	36.06	PK	V	38.19	6.36	25.47	55.14	49.12	68.20	19.08
15690.00	37.53	PK	V	37.91	8.80	24.37	59.87	53.85	74.00	20.15
15690.00	25.41	AV	V	37.91	8.80	24.37	47.75	41.73	54.00	12.27

802.11ac vht80


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Extrapolation result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Fac vhtor (dB/m)						
Middle Channel: 5210 MHz										
5210.00	51.59	PK	H	33.64	3.58	0.00	88.81	82.79	N/A	N/A
5210.00	37.98	AV	H	33.64	3.58	0.00	75.20	69.18	N/A	N/A
5210.00	52.17	PK	V	33.64	3.58	0.00	89.39	83.37	N/A	N/A
5210.00	38.49	AV	V	33.64	3.58	0.00	75.71	69.69	N/A	N/A
5150.00	27.21	PK	V	33.54	3.56	0.00	64.31	58.29	74.00	15.71
5150.00	15.02	AV	V	33.54	3.56	0.00	52.12	46.1	54.00	7.90
5350.00	27.59	PK	V	33.86	3.52	0.00	64.97	58.95	74.00	15.05
5350.00	15.09	AV	V	33.86	3.52	0.00	52.47	46.45	54.00	7.55
10420.00	35.19	PK	V	38.18	6.33	25.47	54.23	48.21	68.20	19.99
15630.00	36.46	PK	V	37.97	8.82	24.33	58.92	52.9	74.00	21.10
15630.00	24.58	AV	V	37.97	8.82	24.33	47.04	41.02	54.00	12.98

Test Plots(For worst mode 802.11a 5200MHz)
Horizontal








Vertical



Fundamental
Test with Band
Rejection Filter





FCC §15.407(a)(e)–EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH**Applicable Standard**

15.407(a) (e).

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2020-01-04	2021-01-04
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

Test Data**Environmental Conditions**

Temperature:	26.7°C
Relative Humidity:	57 %
ATM Pressure:	100.5 kPa
Tester:	Rita Huang
Test Date:	2020-07-31

Test Result: Pass.

Please refer to the following tables and plots.


Test mode: Transmitting

Mode	Frequency (MHz)	26 dB Emission Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
802.11 a	5180	30.240	17.44
	5200	30.880	17.52
	5240	31.280	17.28
802.11n ht20	5180	31.440	18.24
	5200	31.840	18.32
	5240	30.400	18.24
802.11n ht40	5190	53.120	36.96
	5230	52.480	39.96
802.11ac vht80	5210	91.840	76.16

Note: the 99% Occupied Bandwidth have not fall into the band 5250-5350MHz, please refer to the test plots of 99% Occupied Bandwidth.


26dB Emission Bandwidth:

802.11a Low Channel




Date: 31.JUL.2020 21:28:24

802.11a Middle Channel




Date: 31.JUL.2020 21:26:11

802.11a High Channel




Date: 31.JUL.2020 21:24:07

802.11n ht20 Low Channel




Date: 31.JUL.2020 20:59:54

802.11n ht20 Middle Channel




Date: 31.JUL.2020 21:02:38

802.11n ht20 High Channel




Date: 31.JUL.2020 21:05:09

802.11n ht40 Low Channel




Date: 31.JUL.2020 21:07:12


802.11n ht40 High Channel



Date: 31.JUL.2020 21:08:36


802.11ac vht80 Middle Channel

Date: 31.JUL.2020 21:10:40

99% Occupied Bandwidth:**802.11a Low Channel**


Date: 31.JUL.2020 21:27:28

802.11a Middle Channel




Date: 31.JUL.2020 21:25:37

802.11a High Channel




Date: 31.JUL.2020 21:23:19

802.11n ht20 Low Channel




Date: 31.JUL.2020 21:01:30

802.11n ht20 Middle Channel




Date: 31.JUL.2020 21:02:50

802.11n ht20 High Channel




Date: 31.JUL.2020 21:05:47

802.11n ht40 Low Channel




Date: 31.JUL.2020 21:07:43

802.11n ht40 High Channel



Date: 31.JUL.2020 21:08:48

802.11ac vht80 Middle Channel



Date: 31.JUL.2020 21:10:01

FCC §15.407(a) –MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.407(a)

(a) Power limits:

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(4) The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
yzjingcheng	Coaxial Cable	KTRFBU-141-50	41005011	Each time	N/A
E-Microwave	Coaxial Attenuators	EMCA10-5RN-6	OE01203239	Each time	N/A
Agilent	USB Wideband Power Sensor	U2021XA	MY5425009	2020-05-09	2021-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

Test Data

Environmental Conditions

Temperature:	26.7°C
Relative Humidity:	57 %
ATM Pressure:	100.5 kPa
Tester:	Rita Huang
Test Date:	2020-07-31

Test Mode: Transmitting

Mode	Frequency (MHz)	Conducted Average Output Power (dBm)	Limit (dBm)
802.11a	5180	13.84	24
	5200	14.34	24
	5240	14.06	24
802.11n ht20	5180	14.69	24
	5200	14.46	24
	5240	14.25	24
802.11n ht40	5190	14.24	24
	5230	14.07	24
802.11ac vht80	5210	14.66	24

Note:

The device is a client device.

The duty cycle factor has been calculated into the test data.

FCC §15.407(a) - POWER SPECTRAL DENSITY

Applicable Standard

According to FCC §15.407(a)

(a) Power limits:

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 + 10 \log B$ dBm, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output

power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2020-01-04	2021-01-04
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.7°C
Relative Humidity:	57 %
ATM Pressure:	100.5 kPa
Tester:	Rita Huang
Test Date:	2020-07-31

Test Mode: Transmitting


Test Result: Compliance. Please refer to the following table and plot.

Mode	Frequency (MHz)	Maximum Power Spectral Density (dBm/MHz)	Limit (dBm/MHz)
802.11a	5180	-1.63	11
	5200	-1.74	11
	5240	-1.59	11
802.11n ht20	5180	-2.02	11
	5200	-2.25	11
	5240	-2.09	11
802.11n ht40	5190	-0.82	11
	5230	-0.24	11
802.11ac vht80	5210	-2.94	11

Note:


Method SA-3 in KDB 789033 D02 General UNII Test Procedures New Rules v02r01 was used for PSD test.

802.11a Low Channel




Date: 31.JUL.2020 21:27:39

802.11a Middle Channel




Date: 31.JUL.2020 21:25:48

802.11a High Channel




Date: 31.JUL.2020 21:23:30

802.11n ht20 Low Channel




Date: 31.JUL.2020 21:01:41

802.11n ht20 Middle Channel




Date: 31.JUL.2020 21:03:01

802.11n ht20 High Channel




Date: 31.JUL.2020 21:05:59

802.11n ht40 Low Channel




Date: 31.JUL.2020 21:07:54

802.11n ht40 High Channel



Date: 31.JUL.2020 21:09:00

802.11ac vht80 Middle Channel



Date: 31.JUL.2020 21:10:12

***** END OF REPORT *****