

# RF EXPOSURE REPORT



Report No.: 15070272-FCC-H2

Supersede Report No.: N/A

|                                                                                                                                      |                                                                                     |                                                                                       |
|--------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Applicant                                                                                                                            | Social Mobile Telecommunications                                                    |                                                                                       |
| Product Name                                                                                                                         | PHONE                                                                               |                                                                                       |
| Model No.                                                                                                                            | X301                                                                                |                                                                                       |
| Serial No.                                                                                                                           | Wind 3G                                                                             |                                                                                       |
| Test Standard                                                                                                                        | FCC 2.1093                                                                          |                                                                                       |
| Test Date                                                                                                                            | April 17 to April 27, 2015                                                          |                                                                                       |
| Issue Date                                                                                                                           | April 29, 2015                                                                      |                                                                                       |
| Test Result                                                                                                                          | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail              |                                                                                       |
| Equipment complied with the specification <input checked="" type="checkbox"/>                                                        |                                                                                     |                                                                                       |
| Equipment did not comply with the specification <input type="checkbox"/>                                                             |                                                                                     |                                                                                       |
|                                                   |  |  |
| Wiky.Jam<br>Test Engineer                                                                                                            | Chris You<br>Checked By                                                             |                                                                                       |
| This test report may be reproduced in full only<br>Test result presented in this test report is applicable to the tested sample only |                                                                                     |                                                                                       |

Issued by:

**SIEMIC (SHENZHEN-CHINA) LABORATORIES**

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

| Country/Region | Scope                              |
|----------------|------------------------------------|
| USA            | EMC, RF/Wireless, SAR, Telecom     |
| Canada         | EMC, RF/Wireless, SAR, Telecom     |
| Taiwan         | EMC, RF, Telecom, SAR, Safety      |
| Hong Kong      | RF/Wireless, SAR, Telecom          |
| Australia      | EMC, RF, Telecom, SAR, Safety      |
| Korea          | EMI, EMS, RF, SAR, Telecom, Safety |
| Japan          | EMI, RF/Wireless, SAR, Telecom     |
| Singapore      | EMC, RF, SAR, Telecom              |
| Europe         | EMC, RF, SAR, Telecom, Safety      |

|             |                 |
|-------------|-----------------|
| Test Report | 15070272-FCC-H2 |
| Page        | 3 of 10         |

This page has been left blank intentionally.

## CONTENTS

|                                                                                  |   |
|----------------------------------------------------------------------------------|---|
| 1. REPORT REVISION HISTORY .....                                                 | 5 |
| 2. CUSTOMER INFORMATION .....                                                    | 5 |
| 3. TEST SITE INFORMATION .....                                                   | 5 |
| 4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....                                  | 6 |
| 5. FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES. | 8 |
| 5.1 RF EXPOSURE.....                                                             | 8 |
| 5.2 TEST RESULT .....                                                            | 9 |

## 1. Report Revision History

| Report No.      | Report Version | Description | Issue Date     |
|-----------------|----------------|-------------|----------------|
| 15070272-FCC-H2 | NONE           | Original    | April 29, 2015 |
|                 |                |             |                |
|                 |                |             |                |
|                 |                |             |                |
|                 |                |             |                |
|                 |                |             |                |

## 2. Customer information

|                  |                                                 |
|------------------|-------------------------------------------------|
| Applicant Name   | Social Mobile Telecommunications                |
| Applicant Add    | 16400 NW 2nd Ave. #201 Miami, Florida 33169     |
| Manufacturer     | SMT TELECOMM HK LIMITED                         |
| Manufacturer Add | Unit C 8/F, CHARMHILL CTR 50 HILLWOOD RD TST KL |

## 3. Test site information

|                      |                                                                                                                                              |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Lab performing tests | SIEMIC (Shenzhen-China) LABORATORIES                                                                                                         |
| Lab Address          | Zone A, Floor 1, Building 2 Wan Ye Long Technology Park<br>South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong<br>China 518108 |
| FCC Test Site No.    | 718246                                                                                                                                       |
| IC Test Site No.     | 4842E-1                                                                                                                                      |
| Test Software        | Radiated Emission Program-To Shenzhen v2.0                                                                                                   |

#### 4. Equipment under Test (EUT) Information

Description of EUT: PHONE

Main Model: X301

Serial Model: Wind 3G

Date EUT received: April 15, 2015

Test Date(s): April 17 to April 27, 2015

Antenna Gain: GSM850: 0.8 dBi  
PCS1900: -1 dBi  
UMTS-FDD Band V: -0.7dBi  
UMTS-FDD Band II: -0.9dBi  
Bluetooth/BLE: -0.5dBi  
WIFI: -0.5 dBi

Type of Modulation: GSM / GPRS: GMSK  
EGPRS: GMSK, 8PSK  
UMTS-FDD: QPSK, 16QAM  
802.11b/g/n: DSSS, OFDM  
Bluetooth: GFSK,  $\pi$  /4DQPSK, 8DPSK  
BLE: GFSK

RF Operating Frequency (ies): GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz  
PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz  
UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz  
UMTS-FDD Band II TX: 1852.4 ~ 1907.6 MHz;  
RX: 1932.4 ~ 1987.6 MHz  
WIFI: 802.11b/g/n(20M): 2412-2462 MHz  
WIFI: 802.11n(40M): 2422-2452 MHz  
Bluetooth & BLE: 2402-2480 MHz

Number of Channels: GSM 850: 124CH  
PCS1900: 299CH  
UMTS-FDD Band V : 102CH

|             |                 |
|-------------|-----------------|
| Test Report | 15070272-FCC-H2 |
| Page        | 7 of 10         |

UMTS-FDD Band II : 277CH

WIFI :802.11b/g/n(20M): 11CH

WIFI :802.11n(40M): 7CH

Bluetooth: 79CH

BLE: 40CH

Port:

Power Port, Earphone Port, USB Port

Battery:

Model: BR1364AQ

Spec: 3.7V 1300mAh 4.81Wh

Input Power:

Adapter:

Model: PC X301

Input: AC 100-240V; 50/60Hz 0.15A Max

Output: DC 5.0V; 0.5A

Trade Name :

Wind

GPRS/EGPRS Multi-slot class

8/10/12

FCC ID:

2ACLMX301WB

## 5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

### 5.1 RF Exposure

#### Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR,<sup>16</sup> where

- $f_{\text{(GHz)}}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

$$\text{result} = P\sqrt{F} / D$$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm

## 5.2 Test Result

### Bluetooth Mode:

| Modulation    | CH   | Freq (MHz) | Conducted Power (dBm) | Tune Up Power (dBm) | Max Tune Up Power (dBm) | Max Tune Up Power (mW) | Result | Limit |
|---------------|------|------------|-----------------------|---------------------|-------------------------|------------------------|--------|-------|
| GFSK          | Low  | 2402       | -3.949                | -3.2±1              | -2.2                    | 0.603                  | 0.19   | 3     |
|               | Mid  | 2441       | -1.992                | -1.2±1              | -0.2                    | 0.955                  | 0.30   | 3     |
|               | High | 2480       | -0.858                | -1.2±1              | -0.2                    | 0.955                  | 0.30   | 3     |
| $\pi/4$ DQPSK | Low  | 2402       | -4.034                | -4.2±1              | -3.2                    | 0.479                  | 0.15   | 3     |
|               | Mid  | 2441       | -2.199                | -2.2±1              | -1.2                    | 0.759                  | 0.24   | 3     |
|               | High | 2480       | -1.053                | -1.2±1              | -0.2                    | 0.955                  | 0.30   | 3     |
| 8-DPSK        | Low  | 2402       | -4.108                | -4.2±1              | -3.2                    | 0.479                  | 0.15   | 3     |
|               | Mid  | 2441       | -2.045                | -2.2±1              | -1.2                    | 0.759                  | 0.24   | 3     |
|               | High | 2480       | -0.964                | -1.2±1              | -0.2                    | 0.955                  | 0.30   | 3     |

### WIFI Mode:

| Modulation    | CH   | Freq (MHz) | Conducted Power (dBm) | Tune Up Power (dBm) | Max Tune Up Power (dBm) | Max Tune Up Power (mW) | Result | Limit |
|---------------|------|------------|-----------------------|---------------------|-------------------------|------------------------|--------|-------|
| 802.11b       | Low  | 2412       | 9.32                  | 8.5±1               | 9.5                     | 8.91                   | 2.77   | 3     |
|               | Mid  | 2437       | 9.01                  | 8.5±1               | 9.5                     | 8.91                   | 2.78   | 3     |
|               | High | 2462       | 9.41                  | 8.5±1               | 9.5                     | 8.91                   | 2.80   | 3     |
| 802.11g       | Low  | 2412       | 9.28                  | 8.5±1               | 9.5                     | 8.91                   | 2.77   | 3     |
|               | Mid  | 2437       | 9.12                  | 8.5±1               | 9.5                     | 8.91                   | 2.78   | 3     |
|               | High | 2462       | 9.30                  | 8.5±1               | 9.5                     | 8.91                   | 2.80   | 3     |
| 802.11n (20M) | Low  | 2412       | 9.44                  | 8.5±1               | 9.5                     | 8.91                   | 2.77   | 3     |
|               | Mid  | 2437       | 9.15                  | 8.5±1               | 9.5                     | 8.91                   | 2.78   | 3     |
|               | High | 2462       | 9.33                  | 8.5±1               | 9.5                     | 8.91                   | 2.80   | 3     |
| 802.11n (40M) | Low  | 2422       | 8.16                  | 8.5±1               | 9.5                     | 8.91                   | 2.77   | 3     |
|               | Mid  | 2437       | 8.22                  | 8.5±1               | 9.5                     | 8.91                   | 2.78   | 3     |
|               | High | 2452       | 8.34                  | 8.5±1               | 9.5                     | 8.91                   | 2.80   | 3     |

### BLE Mode:

| Modulation | CH   | Freq (MHz) | Conducted Power (dBm) | Tune Up Power (dBm) | Max Tune Up Power (dBm) | Max Tune Up Power (mW) | Result | Limit |
|------------|------|------------|-----------------------|---------------------|-------------------------|------------------------|--------|-------|
| GFSK       | Low  | 2402       | -11.423               | -11±1               | -10                     | 0.100                  | 0.03   | 3     |
|            | Mid  | 2440       | -10.205               | -10±1               | -9                      | 0.126                  | 0.04   | 3     |
|            | High | 2480       | -9.435                | -9±1                | -8                      | 0.158                  | 0.05   | 3     |

**Result:** Compliance

No SAR measurement is required.