FCC RADIO TEST REPORT-WIFI
FCC ID:2ACMBLEARNI

Product：	Tablet PC &
Trade Name：	N/A
Model Name：	Learnit and Blast Tablet
Serial Model：	B for blast L for Learnit
Report No.：	NTEK-2015NT07012160F4

Prepared for

Caribbean eBook Ltd.

38 Oak Street, Hyde Park, Massachusetts,United States 02136

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street
Bao'an District, Shenzhen P.R. China
Tel.: +86-0755-61156588 Fax.: +86-0755-61156599
Website:www.ntek.org.cn

TEST RESULT CERTIFICATION

Applicant's name ..... Caribbean eBook Ltd.

Address..... 38 Oak Street, Hyde Park, Massachusetts,United States 02136

Manufacture's Name... DONGGUAN DIGI-IN DIGITAL TECHNOLOGY CO.,LTD.

Address..... Jiatian Industrial Park, Wulian, Fenggang Town, Dongguan, Guangdong Province,P.R.C

Product description

Product name..... Tablet PC &

Model and/or type reference ..... Learnit and Blast Tablet

Serial Model ..... B for blast L for Learnit

Standards ..... FCC Part15.247 01 Oct. 2014

Test procedure ..... ANSI C63.10-2013 and KDB 558074: June 5, 2014

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test .....

Date (s) of performance of tests..... 01 Jul. 2015 ~04 Aug. 2015

Date of Issue ..... 04 Aug. 2015

Test Result..... **Pass**

Testing Engineer : Allen Liu

(Allen Liu)

Technical Manager : Brown Lu

(Brown Lu)

Authorized Signatory : Sam Chen

(Sam Chen)

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	**5**
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	**7**
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	9
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	11
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
3 . EMC EMISSION TEST	**13**
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.1.2 TEST PROCEDURE	14
3.1.3 DEVIATION FROM TEST STANDARD	14
3.1.4 TEST SETUP	14
3.1.5 EUT OPERATING CONDITIONS	14
3.1.6 TEST RESULTS	15
3.2 RADIATED EMISSION MEASUREMENT	23
3.2.1 RADIATED EMISSION LIMITS	23
3.2.2 TEST PROCEDURE	24
3.2.3 DEVIATION FROM TEST STANDARD	24
3.2.4 TEST SETUP	25
3.2.5 EUT OPERATING CONDITIONS	26
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	27
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	28
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	30
4 . POWER SPECTRAL DENSITY TEST	**30**
4.1 APPLIED PROCEDURES / LIMIT	31
4.1.1 TEST PROCEDURE	31
4.1.2 DEVIATION FROM STANDARD	31
4.1.3 TEST SETUP	31
4.1.4 EUT OPERATION CONDITIONS	31
4.1.5 TEST RESULTS	32
5 . BANDWIDTH TEST	**40**
5.1 APPLIED PROCEDURES / LIMIT	40
5.1.1 TEST PROCEDURE	40

Table of Contents

Page

TEST SETUP 40
5.1.2 EUT OPERATION CONDITIONS 40
5.1.3 TEST RESULTS 41

6 . PEAK OUTPUT POWER TEST 49
6.1 APPLIED PROCEDURES / LIMIT 49
6.1.1 TEST PROCEDURE 49
6.1.2 DEVIATION FROM STANDARD 49
6.1.3 TEST SETUP 49
6.1.4 EUT OPERATION CONDITIONS 49
6.1.5 TEST RESULTS 50

7 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE 51
7.1 DEVIATION FROM STANDARD 51
7.2 TEST SETUP 51
7.3 EUT OPERATION CONDITIONS 51
7.4 TEST RESULTS 52

8 . ANTENNA REQUIREMENT 58
8.1 STANDARD REQUIREMENT 58
8.2 EUT ANTENNA 58

9 . EUT TEST PHOTO 59
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd
Add.:1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.
FCC Registration No.:238937; IC Registration No.:9270A-1
CNAS Registration No.:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement **y** ± **U**，where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**，providing a level of confidence of approximately **95** %。

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

<table>
<tr><td>Equipment</td><td>Tablet PC &</td></tr>
<tr><td>Trade Name</td><td>N/A</td></tr>
<tr><td>Model Name</td><td>Learnit and Blast Tablet</td></tr>
<tr><td>Serial Model</td><td>B for blast L for Learnit</td></tr>
<tr><td>Model Difference</td><td>All the model are the same circuit and RF module,
except the model name and colour.</td></tr>
<tr><td>Product Description</td><td>
<table>
<tr><td>Operation Frequency:</td><td>802.11b/g/n(20MHz): 2412~2462MHz
802.11n(40MHz):2422~2452MHz</td></tr>
<tr><td>Modulation Type:</td><td>IEEE 802.11b :
DSSS (CCK, QPSK, DBPSK)
IEEE 802.11g/n (HT20/HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)</td></tr>
<tr><td>Bit Rate of Transmitter</td><td>802.11b:11/5.5/2/1 Mbps
802.11g:54/48/36/24/18/12/9/6Mbps
802.11n(20MHz/40MHz):150/144.44/130/117/115.56/104/86.67/78/52/6.5Mbps</td></tr>
<tr><td>Number Of Channel</td><td>802.11b/g/n20MHz:11CH
802.11n40MHz:7CH</td></tr>
<tr><td>Antenna Designation:</td><td>Please see Note 3.</td></tr>
<tr><td>Antenna Gain (dBi)</td><td>1.0 dbi</td></tr>
</table>
</td></tr>
<tr><td>Channel List</td><td>Please refer to the Note 2.</td></tr>
<tr><td>Ratings</td><td>DC 3.7V</td></tr>
<tr><td>Adapter</td><td>Mode : XHY050200UUCH
Input: 100-240V~, 50/60Hz, 0.5A MAX
Output: 5.0V⎓, 2.0A</td></tr>
<tr><td>Battery</td><td>DC 3.7V, 2500mAh</td></tr>
<tr><td>Connecting I/O Port(s)</td><td>Please refer to the User's Manual</td></tr>
</table>

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2.

Channel List for 802.11b/g/n(20 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Channel List for 802.11n(40MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
03	2422	06	2437	09	2452		
04	2427	07	2442				
05	2432	08	2447				

3.

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
A	N/A	N/A	FPCB Antenna	N/A	1.0	Wifi Antenna

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n20 CH1/ CH6/ CH11
Mode 4	802.11n40 CH3/ CH6/ CH9
Mode 5	Link Mode

For Conducted Emission	
Final Test Mode	Description
Mode 5	Link Mode

Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n20 CH1/ CH6/ CH11
Mode 4	802.11n40 CH3/ CH6/ CH9
Mode 5	Link Mode

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.

(2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

(3) EUT configured to transmit continuously:

Operated Mode for Worst Duty Cycle	
Test Signal Duty Cycle (x)	Average correction factor (dB)
100% - IEEE 802.11b	0
100% - IEEE 802.11g	0
100% - IEEE 802.11n (HT20)	0
100% - IEEE 802.11n (HT40)	0

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission Test



Radiated Spurious Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	Tablet PC &	N/A	Learnit and Blast Tablet	N/A	EUT
E-2	Adapter	N/A	XHY050200UUCH	N/A	
E-3	Earphone	N/A	2688		

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	1.2m	
C-2	NO	NO	1.0m	

Note:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in『Length』column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2015.07.06	2016.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2015.06.06	2016.06.05	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2015.07.06	2016.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2015.06.06	2016.06.05	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2015.06.06	2016.06.05	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2015.07.06	2016.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2015.07.06	2016.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2014.12.22	2015.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2015.06.06	2016.06.05	1 year
10	Power Meter	R&S	NRVS	100696	2015.07.06	2016.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2015.07.06	2016.07.05	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2015.06.06	2016.06.05	1 year
2	LISN	R&S	ENV216	101313	2014.08.24	2015.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2015.06.06	2016.06.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2015.06.06	2016.06.05	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2015.06.06	2016.06.05	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2015.06.06	2016.06.05	1 year

1	Attenuation	MCE	24-10-34	BN9258	2015.07.06	2016.07.05	1 year

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

(1) The tighter limit applies at the band edges.

(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.1.6 TEST RESULTS

EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	26 ℃	Relative Humidity：	54%
Pressure：	1010hPa	Phase：	L
Test Voltage ：	DC 5.0V form Adapter AC 120V/60Hz	Test Mode：	Mode 5

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1700	40.53	9.61	50.14	64.96	-14.82	QP
0.1700	30.31	9.61	39.92	54.96	-15.04	AVG
0.2100	36.02	9.61	45.63	63.20	-17.57	QP
0.2100	25.58	9.61	35.19	53.20	-18.01	AVG
0.2940	29.47	9.61	39.08	60.41	-21.33	QP
0.2940	20.42	9.61	30.03	50.41	-20.38	AVG
0.3820	28.57	9.63	38.20	58.23	-20.03	QP
0.3820	21.41	9.63	31.04	48.23	-17.19	AVG
0.4660	26.93	9.66	36.59	56.58	-19.99	QP
0.4660	20.23	9.66	29.89	46.58	-16.69	AVG
2.2260	29.66	9.54	39.20	56.00	-16.80	QP
2.2260	19.68	9.54	29.22	46.00	-16.78	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	26 ℃	Relative Humidity：	54%
Pressure：	1010hPa	Phase：	N
Test Voltage ：	DC 5.0V form Adapter AC 120V/60Hz	Test Mode：	Mode 5

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1700	38.11	9.61	47.72	64.96	-17.24	QP
0.1700	28.63	9.61	38.24	54.96	-16.72	AVG
0.2100	34.31	9.61	43.92	63.20	-19.28	QP
0.2100	23.27	9.61	32.88	53.20	-20.32	AVG
0.2540	29.85	9.61	39.46	61.62	-22.16	QP
0.2540	20.92	9.61	30.53	51.62	-21.09	AVG
0.3420	25.64	9.62	35.26	59.15	-23.89	QP
0.3420	17.81	9.62	27.43	49.15	-21.72	AVG
0.4700	24.59	9.66	34.25	56.51	-22.26	QP
0.4700	20.09	9.66	29.75	46.51	-16.76	AVG
2.2580	27.20	9.53	36.73	56.00	-19.27	QP
2.2580	15.95	9.53	25.48	46.00	-20.52	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	26 ℃	Relative Humidity：	54%
Pressure：	1010hPa	Phase：	L
Test Voltage ：	DC 5.0V form Adapter AC 240V/60Hz	Test Mode：	Mode 5

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1700	40.18	9.62	49.80	64.96	-15.16	QP
0.1700	31.23	9.62	40.85	54.96	-14.11	AVG
0.2100	35.21	9.61	44.82	63.20	-18.38	QP
0.2100	22.95	9.61	32.56	53.20	-20.64	AVG
0.2540	31.77	9.67	41.44	61.62	-20.18	QP
0.2540	22.84	9.67	32.51	51.62	-19.11	AVG
0.2940	28.29	9.73	38.02	60.41	-22.39	QP
0.2940	20.73	9.73	30.46	50.41	-19.95	AVG
0.3420	27.88	9.58	37.46	59.15	-21.69	QP
0.3420	17.50	9.58	27.08	49.15	-22.07	AVG
0.4660	26.92	9.63	36.55	56.58	-20.03	QP
0.4660	20.00	9.63	29.63	46.58	-16.95	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	26 ℃	Relative Humidity：	54%
Pressure：	1010hPa	Phase：	N
Test Voltage ：	DC 5.0V form Adapter AC 240V/60Hz	Test Mode：	Mode 5

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1700	37.86	9.61	47.47	64.96	-17.49	QP
0.1700	29.17	9.61	38.78	54.96	-16.18	AVG
0.2100	34.07	9.61	43.68	63.20	-19.52	QP
0.2100	23.43	9.61	33.04	53.20	-20.16	AVG
0.2540	29.57	9.61	39.18	61.62	-22.44	QP
0.2540	19.96	9.61	29.57	51.62	-22.05	AVG
0.3020	26.69	9.62	36.31	60.19	-23.88	QP
0.3020	17.31	9.62	26.93	50.19	-23.26	AVG
0.3379	25.69	9.62	35.31	59.25	-23.94	QP
0.3379	17.36	9.62	26.98	49.25	-22.27	AVG
0.4660	25.35	9.66	35.01	56.58	-21.57	QP
0.4660	21.62	9.66	31.28	46.58	-15.30	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	26 ℃	Relative Humidity：	54%
Pressure：	1010hPa	Phase：	L
Test Voltage ：	DC 5.0V form PC AC 120V/60Hz	Test Mode：	Mode 5

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1660	38.38	9.62	48.00	65.15	-17.15	QP
0.1660	31.85	9.62	41.47	55.15	-13.68	AVG
0.2100	34.62	9.61	44.23	63.20	-18.97	QP
0.2100	24.85	9.61	34.46	53.20	-18.74	AVG
0.2580	30.04	9.69	39.73	61.49	-21.76	QP
0.2580	20.36	9.69	30.05	51.49	-21.44	AVG
0.3820	28.26	9.42	37.68	58.23	-20.55	QP
0.3820	21.15	9.42	30.57	48.23	-17.66	AVG
0.4620	27.56	9.61	37.17	56.66	-19.49	QP
0.4620	20.60	9.61	30.21	46.66	-16.45	AVG
2.2580	29.05	9.66	38.71	56.00	-17.29	QP
2.2580	16.21	9.66	25.87	46.00	-20.13	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	26 ℃	Relative Humidity：	54%
Pressure：	1010hPa	Phase：	N
Test Voltage ：	DC 5.0V form PC AC 120V/60Hz	Test Mode：	Mode 5

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1700	39.02	9.61	48.63	64.96	-16.33	QP
0.1700	30.11	9.61	39.72	54.96	-15.24	AVG
0.2140	33.10	9.62	42.72	63.04	-20.32	QP
0.2140	24.01	9.62	33.63	53.04	-19.41	AVG
0.2540	29.26	9.61	38.87	61.62	-22.75	QP
0.2540	17.90	9.61	27.51	51.62	-24.11	AVG
0.2980	27.34	9.61	36.95	60.30	-23.35	QP
0.2980	19.51	9.61	29.12	50.30	-21.18	AVG
0.3379	25.74	9.62	35.36	59.25	-23.89	QP
0.3379	18.52	9.62	28.14	49.25	-21.11	AVG
0.4700	25.04	9.66	34.70	56.51	-21.81	QP
0.4700	20.89	9.66	30.55	46.51	-15.96	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	26 ℃	Relative Humidity：	54%
Pressure：	1010hPa	Phase：	L
Test Voltage ：	DC 5.0V form PC AC 240V/60Hz	Test Mode：	Mode 5

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1700	40.04	9.62	49.66	64.96	-15.30	QP
0.1700	32.17	9.62	41.79	54.96	-13.17	AVG
0.2140	34.29	9.63	43.92	63.04	-19.12	QP
0.2140	22.97	9.63	32.60	53.04	-20.44	AVG
0.2580	29.53	9.69	39.22	61.49	-22.27	QP
0.2580	19.66	9.69	29.35	51.49	-22.14	AVG
0.2980	28.54	9.74	38.28	60.30	-22.02	QP
0.2980	22.61	9.74	32.35	50.30	-17.95	AVG
0.3420	27.62	9.58	37.20	59.15	-21.95	QP
0.3420	20.36	9.58	29.94	49.15	-19.21	AVG
0.3780	28.03	9.44	37.47	58.32	-20.85	QP
0.3780	22.30	9.44	31.74	48.32	-16.58	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	26 ℃	Relative Humidity：	54%
Pressure：	1010hPa	Phase：	N
Test Voltage ：	DC 5.0V form PC AC 240V/60Hz	Test Mode：	Mode 5

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1700	39.01	9.61	48.62	64.96	-16.34	QP
0.1700	30.76	9.61	40.37	54.96	-14.59	AVG
0.2140	32.94	9.62	42.56	63.04	-20.48	QP
0.2140	22.46	9.62	32.08	53.04	-20.96	AVG
0.2540	29.32	9.61	38.93	61.62	-22.69	QP
0.2540	19.75	9.61	29.36	51.62	-22.26	AVG
0.2980	27.61	9.61	37.22	60.30	-23.08	QP
0.2980	20.37	9.61	29.98	50.30	-20.32	AVG
0.3420	24.83	9.62	34.45	59.15	-24.70	QP
0.3420	15.70	9.62	25.32	49.15	-23.83	AVG
0.4660	25.00	9.66	34.66	56.58	-21.92	QP
0.4660	19.85	9.66	29.51	46.58	-17.07	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	dBuV/m@at 3M	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / *10Hz* for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	Peak	100 kHz	100 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

3.2.3 DEVIATION FROM TEST STANDARD

No deviation

3.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

EUT：	Tablet PC &	Model Name. ：	Learnit and Blast Tablet
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	N/A
--	--	--	--	N/A

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
Distance extrapolation factor =40 log (specific distance/test distance)(dB);
Limit line = specific limits(dBuv) + distance extrapolation factor.

3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	20 ℃	Relative Humidity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX		

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	35.8746	17.02	16.14	33.16	40.00	-6.84	QP
V	60.0690	26.49	7.81	34.30	40.00	-5.70	QP
V	157.5586	26.59	10.47	37.06	43.50	-6.44	QP
V	214.5141	20.68	11.76	32.44	43.50	-11.06	QP
V	432.5457	16.27	18.96	35.23	46.00	-10.77	QP
V	726.8052	13.22	25.50	38.72	46.00	-7.28	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
H	47.9938	21.27	11.18	32.45	40.00	-7.55	QP
H	160.9088	28.02	10.48	38.50	43.50	-5.00	QP
H	210.0482	28.55	11.46	40.01	43.50	-3.49	QP
H	336.035	22.14	15.66	37.80	46.00	-8.20	QP
H	432.5457	20.71	18.96	39.67	46.00	-6.33	QP
H	938.8324	14.11	27.25	41.36	46.00	-4.64	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	20 ℃	Relative Humidity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX		

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel (2412 MHz)-Above 1G							
Vertical	4826.332	51.6	10.44	61.25	74.00	-12.75	Pk
Vertical	4826.332	33.16	10.44	44.02	54.00	-9.98	Av
Vertical	7233.581	44.81	12.39	57.25	74.00	-16.75	Pk
Vertical	7233.581	29.09	12.39	40.36	54.00	-13.64	Av
Horizontal	4820.025	53.35	10.44	62.02	74.00	-11.98	Pk
Horizontal	4820.025	32.07	10.44	41.69	54.00	-12.31	Av
Horizontal	7230.221	45.51	12.39	56.69	74.00	-17.31	Pk
Horizontal	7230.221	30.65	12.39	42.58	54.00	-11.42	Av
Mid Channel (2437 MHz)-Above 1G							
Vertical	4875.363	51.01	10.40	62.03	74.00	-11.97	Pk
Vertical	4875.363	31.93	10.40	41.69	54.00	-12.31	Av
Vertical	7315.021	44.67	12.75	58.32	74.00	-15.68	Pk
Vertical	7315.021	27.66	12.75	39.25	54.00	-14.75	Av
Horizontal	4870.047	51.78	10.40	61.57	74.00	-12.43	Pk
Horizontal	4870.047	33.01	10.40	42.64	54.00	-11.36	Av
Horizontal	7312.25	47.89	12.75	59.02	74.00	-14.98	Pk
Horizontal	7312.25	28.58	12.75	40.78	54.00	-13.22	Av
High Channel (2462 MHz)- Above 1G							
Vertical	4925.363	50.95	10.39	60.32	74.00	-13.68	Pk
Vertical	4925.363	32.58	10.39	41.36	54.00	-12.64	Av
Vertical	7380.144	44.35	12.68	56.69	74.00	-17.31	Pk
Vertical	7380.144	27.99	12.68	39.58	54.00	-14.42	Av
Horizontal	4922.585	50.98	10.39	62.01	74.00	-11.99	Pk
Horizontal	4922.585	33.08	10.39	42.58	54.00	-11.42	Av
Horizontal	7388.125	47.37	12.68	59.66	74.00	-14.34	Pk
Horizontal	7388.125	28.67	12.68	40.73	54.00	-13.27	Av

Note:”802.11b” mode is the worst mode.

4. POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

4.1.1 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. 3 kHz ≤Set the RBW≤100 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP

4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

4.1.5 TEST RESULTS

EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	25 ℃	Relative Humidity：	56%
Pressure：	1015 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX b Mode /CH01, CH06, CH11		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-9.915	8	PASS
2437 MHz	-10.550	8	PASS
2462 MHz	-9.578	8	PASS

TX CH01



TX CH06



TX CH11



EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	25 ℃	Relative Humidity：	56%
Pressure：	1015 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX g Mode /CH01, CH06, CH11		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-11.72	8	PASS
2437 MHz	-14.45	8	PASS
2462 MHz	-14.60	8	PASS

TX CH01



TX CH06



TX CH11



EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	25 ℃	Relative Humidity：	56%
Pressure：	1015 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX n Mode (20MHz)/CH01, CH06, CH11		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-12.32	8	PASS
2437 MHz	-13.98	8	PASS
2462 MHz	-14.27	8	PASS

TX CH01



TX CH06



TX CH11



EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	25 ℃	Relative Humidity：	56%
Pressure：	1015 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX n Mode (40MHz)/CH03, CH06, CH09		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2422 MHz	-16.71	8	PASS
2437 MHz	-19.66	8	PASS
2452 MHz	-20.80	8	PASS

TX CH03



TX CH06



TX CH09



5. BANDWIDTH TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 x RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP



5.1.2 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.3 TEST RESULTS

EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	25 ℃	Relative Humidity：	56%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX b Mode /CH01, CH06, CH11		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	9.591	500	Pass
Middle	2437	9.552	500	Pass
High	2462	9.093	500	Pass

TX CH 01



TX CH 06



TX CH 11



EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX g Mode /CH01, CH06, CH11		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	15.234	500	Pass
Middle	2437	15.647	500	Pass
High	2462	15.106	500	Pass

TX CH 01



TX CH 06



TX CH 11



EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	25 ℃	Relative Humidity：	56%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX n Mode(20M) /CH01, CH06, CH11		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	16.738	500	Pass
Middle	2437	15.165	500	Pass
High	2462	15.351	500	Pass

TX CH 01



TX CH 06



TX CH 11



EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	25 ℃	Relative Humidity：	56%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX n Mode(40M) /CH03, CH06, CH09		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2422	35.232	500	Pass
Middle	2437	35.220	500	Pass
High	2452	35.039	500	Pass

TX CH 03



TX CH 06



TX CH 09



6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

a. The EUT was directly connected to the Power meter

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 TEST RESULTS

EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	TX b/g/n(20M/40M) Mode		

Test Channe	Frequency	Maximum Peak Conducted Output Power（PK）	Maximum Peak Conducted Output Power（AV）	LIMIT
	(MHz)	(dBm)	(dBm)	dBm
TX 802.11b Mode				
CH01	2412	12.21	9.36	30
CH06	2437	12.31	9.49	30
CH11	2462	12.02	9.26	30
TX 802.11g Mode				
CH01	2412	11.88	8.75	30
CH06	2437	11.69	8.56	30
CH11	2462	11.56	8.43	30
TX 802.11n(20) Mode				
CH01	2412	10.77	8.54	30
CH06	2437	10.89	8.66	30
CH11	2462	10.74	8.51	30
TX 802.11n(40) Mode				
CH03	2422	9.83	7.41	30
CH06	2437	9.54	7.12	30
CH09	2452	9.33	6.91	30

7. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE

a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
e) Repeat above procedures until all measured frequencies were complete.

7.1 DEVIATION FROM STANDARD

No deviation.

7.2 TEST SETUP



7.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.4 TEST RESULTS

EUT：	Tablet PC &	Model Name ：	Learnit and Blast Tablet
Temperature：	25 ℃	Relative Humidity：	56%
Pressure：	1012 hPa	Test Voltage ：	DC 3.7V

Frequency Band MHz	Delta Peak to band emission (dBc)	＞Limit (dBc)	Result
802.11b mode			
2400	51.10	20	Pass
2483.5	55.96	20	Pass
802.11g mode			
2400	34.90	20	Pass
2483.5	44.48	20	Pass
802.11n-HT20 mode			
2400	35.87	20	Pass
2483.5	38.77	20	Pass
802.11n-HT40 mode			
2400	36.66	20	Pass
2483.5	39.02	20	Pass

Radiated band edge:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
802.11b							
2390	58.67	-13.06	45.61	74	-28.39	peak	Vertical
2390	58.4	-13.06	45.34	74	-28.66	peak	Horizontal
2483.5	59.59	-12.78	46.81	74	-27.19	peak	Vertical
2483.5	59.61	-12.78	46.83	74	-27.17	peak	Horizontal
802.11g							
2390	58.25	-13.06	45.19	74	-28.81	peak	Vertical
2390	57.48	-13.06	44.42	74	-29.58	peak	Horizontal
2483.5	58.97	-12.78	46.19	74	-27.81	peak	Vertical
2483.5	59.36	-12.78	46.58	74	-27.42	peak	Horizontal
802.11n（20）							
2390	61.18	-13.06	48.12	74	-25.88	peak	Vertical
2390	60.96	-13.06	47.9	74	-26.10	peak	Horizontal
2483.5	61.1	-12.78	48.32	74	-25.68	peak	Vertical
2483.5	61.24	-12.78	48.46	74	-25.54	peak	Horizontal
802.11n（40）							
2390	61.94	-13.06	48.88	74	-25.12	peak	Vertical
2390	63.09	-13.06	50.03	74	-23.97	peak	Horizontal
2483.5	61.59	-12.78	48.81	74	-25.19	peak	Vertical
2483.5	61.56	-12.78	48.78	74	-25.22	peak	Horizontal

Note: Test method to see chapter 3.2 . When PK value is lower than the Average value limit, average not record.

802.11b: Band Edge, Right Side



802.11b: Band Edge, Left Side



802.11g: Band Edge, Right Side



802.11g: Band Edge, Left Side



802.11n-HT20: Band Edge, Right Side



802.11n-HT20: Band Edge, Left Side



802.11n-HT40: Band Edge, Right Side



802.11n-HT40: Band Edge, Left Side



8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2 EUT ANTENNA

The EUT antenna is permanent attached antenna. It comply with the standard requirement.

9. EUT TEST PHOTO

Radiated Measurement Photos





CONDUCTED EMISSION Photos