

RF Exposure Evaluation Report

Product : Remote Controller
Trade mark : 
Model/Type reference : WS26001, WSXXXXX (X=0-9)
Serial Number : N/A
Report Number : EED32S80594702
FCC ID : 2ACO2-GV-TX04
Date of Issue : Apr. 15, 2026
Test Standards : 47 CFR Part 1.1307
47 CFR Part 1.1310
47 CFR Part 2.1093
KDB 447498 D04 Interim General RF
Exposure Guidance v01
Test result : PASS

Prepared for:


Golden Vessel Electronic & Lighting, Inc
Industrial District, ZhongHan Town ChaoHu City, AnHui Province, China

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Park, Zone 70, Bao'an District,
Shenzhen, Guangdong, China

TEL: +86-755-3368 3668**FAX: +86-755-3368 3385**

Compiled by:



Win Wei

Reviewed by:



Keven Tan

Approved by:



Aaron Ma

Date:

Apr. 15, 2026



Check No.:4519240326

1 Contents

	Page
1 CONTENTS	2
2 GENERAL INFORMATION	3
2.1 CLIENT INFORMATION	3
2.2 GENERAL DESCRIPTION OF EUT	3
2.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	3
2.4 TEST LOCATION	4
2.5 DEVIATION FROM STANDARDS	4
2.6 ABNORMALITIES FROM STANDARD CONDITIONS	4
2.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	4
3 SAR EVALUATION	5
3.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
3.1.1 Limits	5
3.1.2 Test Procedure	5
3.1.3 EUT RF Exposure Evaluation	6

2 General Information

2.1 Client Information

Applicant:	Golden Vessel Electronic & Lighting, Inc
Address of Applicant:	Industrial District, ZhongHan Town ChaoHu City, AnHui Province,China
Manufacturer 1:	Golden Vessel Electronic & Lighting, Inc
Address of Manufacturer 1:	Industrial District, ZhongHan Town ChaoHu City, AnHui Province,China
Manufacturer 2:	WINKSTAR ELECTRONIC AND LIGHTING CO., LTD
Address of Manufacturer 2:	Kilometer number 69, National Road No. 2, Prey Prom Village, Roka Knong Commune, Daun keo City, Takeo Province,Cambodia

2.2 General Description of EUT

Product Name:	Remote Controller
Model No.:	WS26001, WSXXXXX (X=0-9)
Test Model No.:	WS26001
Trade mark:	

2.3 Product Specification subjective to this standard

Frequency Range:	2420MHz	
Modulation Type:	GFSK	
Test Power Grade:	Default	
Test Software of EUT:	N/A	
Antenna Type:	PCB Antenna	
Antenna Gain:	-3.89dBi	
Power Supply:	Battery:	DC3.0V
Sample Received Date:	Apr. 01, 2026	
Sample tested Date:	Apr. 01, 2026 to Apr. 10, 2026	
Remark: Model No.: WS26001, WSXXXXX (X=0-9) Only the model WS26001 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being model name.		

2.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Hongwei Industrial Park, Zone 70, Bao'an District, Shenzhen, Guangdong, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164, Test Firm Registration No.: 260439

2.5 Deviation from Standards

None.

2.6 Abnormalities from Standard Conditions

None.

2.7 Other Information Requested by the Customer

None.

3 SAR Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Limits

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold Pth (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). Pth is given by Formula

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and ERP20cm is per Formula (B.1).

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

3.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3.1.3 EUT RF Exposure Evaluation**For Stand alone:**

Band	Freq. (MHz)	Estimation distance (cm)	Max. Conducted Output power (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (mW)	Limit (mW)	MPE ratio	Result
GFSK	2420	0.5	-5.47	-3.89	-11.51	0.071	2.771	0.0256	Pass

Note:

- ① EIRP=conducted power+antenna gain;
- ② $ERP=EIRP-2.15$;
- ③ $EIRP(dBm) = \text{Field strength of the fundamental signal}(dBuV/m@3m) - 95.23$;
- ④ $ERP(mW) = 10^{(ERP(dBm)/10)}$;
- ⑤ The estimation distance is 0.5cm;
- ⑥ The test data please refer to the report of EED32S80594701 and only the worst case data was recorded in the report.

Statement

1. This report is considered invalid without approved signature, special seal and the seal on the perforation;
2. The Company Name shown on Report and Address, the sample(s) and sample information was/were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified;
3. The result(s) shown in this report refer(s) only to the sample(s) tested;
4. Unless otherwise stated, the decision rule for conformity reporting is based on Binary Statement for Simple Acceptance Rule stated in ILAC-G8:09/2019/CNAS-GL015:2022;
5. Without written approval of CTI, this report can't be reproduced except in full;

*** End of Report ***