

TEST REPORT

Product : Bluetooth in-ear headphones
Trade mark : **HEX**
Model/Type reference : HX-BTH3000
Serial number : N/A
Ratings : Charging input: 5V $\equiv$
lithium Battery: 3.7V $\equiv$ 200mAh, IPX0, Class III
FCC ID : 2ACQH-HXBTH3000
Report number : EESZG06180004-1
Date : Jul. 15, 2014
Regulations : See below

Test Standards	Results
☒ 47 CFR FCC Part 15 Subpart C 15.247: 2013	PASS

Prepared for:
Tassone Enterprises
Lafayette, CA 94549, United States

Prepared by:
Centre Testing International (Shenzhen) Corporation
Hongwei Industrial Zone, 70 Area, Bao'an District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Tested by: Chingy Chen Reviewed by: Louisa Lu
Approved by: Jimmy Li Date: Jul. 15, 2014



Check No.: 1843421051

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	5
2. TEST SUMMARY	5
3. PRODUCT INFORMATION.....	6
4. MEASUREMENT UNCERTAINTY	6
5. TEST EQUIPMENT LIST	6
6. SUPPORT EQUIPMENT LIST	6
7. 20DB BANDWIDTH MEASUREMENT	7
7.1. LIMITS.....	7
7.2. BLOCK DIAGRAM OF TEST SETUP.....	7
7.3. TEST PROCEDURE	7
7.4. TEST RESULT	7
8. CARRIER FREQUENCY SEPARATION	13
8.1. LIMITS.....	13
8.2. BLOCK DIAGRAM OF TEST SETUP.....	13
8.3. TEST PROCEDURE	13
8.4. TEST RESULT	13
9. NUMBER OF HOPPING FREQUENCY	19
9.1. LIMITS.....	19
9.2. BLOCK DIAGRAM OF TEST SETUP.....	19
9.3. TEST PROCEDURE	19
9.4. TEST RESULT	19
10. TIME OF OCCUPANCY (DWELL TIME).....	23
10.1. LIMITS.....	23
10.2. BLOCK DIAGRAM OF TEST SETUP.....	23
10.3. TEST PROCEDURE	23
10.4. TEST RESULT	23
11. MAXIMUM PEAK CONDUCTED OUTPUT POWER MEASUREMENT.....	29
11.1. LIMITS.....	29
11.2. BLOCK DIAGRAM OF TEST SETUP.....	29
11.3. TEST PROCEDURE	29

11.4. TEST RESULT	29
12. CONDUCTED BANDEDGE EMISSION MEASUREMENT	32
12.1. LIMITS.....	32
12.2. BLOCK DIAGRAM OF TEST SETUP	32
12.3. TEST PROCEDURE	32
12.4. TEST RESULT	32
13. CONDUCTED SPURIOUS EMISSION MEASUREMENT	39
13.1. LIMITS.....	39
13.2. BLOCK DIAGRAM OF TEST SETUP	39
13.3. TEST PROCEDURE	39
13.4. TEST RESULT	39
14. RADIATED BANDEDGE EMISSION / RADIATED SPURIOUS EMISSION MEASUREMENT.....	42
14.1. LIMITS.....	42
14.2. BLOCK DIAGRAM OF TEST SETUP	42
14.3. TEST PROCEDURE	43
14.4. TEST RESULT	44
15. AC CONDUCTED EMISSION TEST	48
15.1. LIMITS.....	48
15.2. BLOCK DIAGRAM OF TEST SETUP	48
15.3. PROCEDURE OF CONDUCTED EMISSION TEST	48
15.4. GRAPHS AND DATA	49
APPENDIX 1 PHOTOGRAPHS OF TEST SETUP	51
APPENDIX 2 EXTERNAL PHOTOGRAPHS OF PRODUCT.....	53
APPENDIX 3 INTERNAL PHOTOGRAPHS OF PRODUCT.....	53

N/A means not applicable.

1. GENERAL INFORMATION

Applicant: Tassone Enterprises
 Lafayette, CA 94549, United States

Manufacturer: Huizhou OVANN Industrial Co., Ltd
 Ovann Industrial Park, Longqiao Avenue, Longxi Town, Boluo
 Country, Huizhou City, Guangdong, China

FCC ID: 2ACQH-HXBTH3000

Product: Bluetooth in-ear headphones

Model/Type reference: HX-BTH3000

Trade Name: **HEX**

Serial Number: N/A

Report Number: EESZG06180004-1

Sample Received Date: Jun. 20, 2014

Sample tested Date: Jun. 20, 2014 to Jul. 15, 2014

The above equipment was tested by Centre Testing International (Shenzhen) Corporation for compliance with the requirements set forth in the FCC Rules and the measurement procedure according to ANSI C63.4:2009.

2. TEST SUMMARY

No.	Test Item	Rule	Test Result
1	20dB Bandwidth	FCC 15.247(a)(1)	PASS
2	Carrier Frequency Separation	FCC15.247(a)(1)	PASS
3	Number of Hopping Frequency	FCC 15.247(a)(iii)	PASS
4	Time of Occupancy (Dwell Time)	FCC 15.247(a)(iii)	PASS
5	Maximum Peak Conducted Output Power	FCC 15.247(b)(1)	PASS
6	Conducted Bandedge Emission / Conducted Spurious Emission	FCC PART15.247(d)	PASS
7	Radiated Bandedge Emission / Radiated Spurious Emission	FCC PART15.247(d)	PASS
8	AC Conducted Emission	FCC PART15.207	PASS
9	Antenna Requirements *	FCC PART15.203	PASS (See Notes)

*: According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The EUT has a built in antenna which is a short wire solder on the PCB, this is permanently attached antenna and meets the requirements of this section.

3. PRODUCT INFORMATION

Items	Description
Rating	Charging input: 5V $\equiv$ lithium Battery: 3,7V $\equiv$ 200mAh, IPX0, Class III
Type of Modulation	GFSK (1Mbps) , $\pi/4$ -DQPSK (2Mbps), 8DPSK (3Mbps)
Antenna Type	Integral antenna
Frequency Range	2402 ~ 2480 MHz
Gain	0dBi

4. MEASUREMENT UNCERTAINTY

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement items	Uncertainty
Conducted Emission Test	3.2 dB
Radiated Emissions / Bandedge Emission	4.5 dB

5. TEST EQUIPMENT LIST

Equipment	Manufacturer	Model	Serial No.	Due Date
3M Chamber & Accessory Equipment	ETS-LINDGREN	FACT-3	3510	07/12/2016
Spectrum Analyzer	Agilent	E4443A	MY45300910	01/15/2015
Receiver	R&S	ESCI	100435	07/19/2014
TRILOG Broadband Antenna	schwarzbeck	VULB 9163	618	06/25/2015
Multi device Controller	ETS-LINGREN	2090	00057230	N/A
Horn Antenna	ETS-LINGREN	3117	00057407	07/19/2014
Microwave Preamplifier	Agilent	8449B	3008A02425	03/19/2015
Spectrum Analyzer	R&S	FSP40	100416	07/06/2015
Receiver	R&S	ESCI	100009	07/19/2014
LISN	R&S	ENV216	100098	07/19/2014

6. SUPPORT EQUIPMENT LIST


Device Type	Brand	Model	Series No.	Data Cable	Remark
Notebook	DELL	Vostro 3400	GYQTVP1	N/A	FCC DOC
Mouse	L.Selectron	M004	02284699	Un-shielded 1.2M	FCC DOC

7. 20dB Bandwidth Measurement

7.1. LIMITS

None

7.2. BLOCK DIAGRAM OF TEST SETUP



7.3. TEST PROCEDURE

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings for 20dB Bandwidth measurement. Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel; RBW $\geq$ 1% of the 20 dB bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
4. Measure and record the results in the test report.

7.4. TEST RESULT

The test data of worst case are below:

GFSK:

Frequency (MHz)	20dB BW (MHz)
2402	1.07
2441	1.11
2480	1.09

$\pi/4$ -DQPSK:


Frequency (MHz)	20dB BW (MHz)
2402	1.37
2441	1.37
2480	1.38

8DPSK:


Frequency (MHz)	20dB BW (MHz)
2402	1.39
2441	1.37
2480	1.40

Please see the following plots (worst case):


GFSK (20dB BW):



2402 MHz




2441 MHz




2480 MHz


$\pi/4$ -DQPSK (20dB BW):



2402 MHz




2441 MHz




2480 MHz


8DPSK (20dB BW):



2402 MHz



2441 MHz




2480 MHz

8. CARRIER FREQUENCY SEPARATION

8.1. LIMITS

Frequency hopping systems operating in the 2400-2483.5MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

8.2. BLOCK DIAGRAM OF TEST SETUP



8.3. TEST PROCEDURE


1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Enable the EUT hopping function.
4. Use the following spectrum analyzer settings: Span = wide enough to capture the peaks of two adjacent channels; RBW $\geq$ 1% of the span; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
5. Measure and record the results in the test report.

8.4. TEST RESULT


Carrier Frequency Separation: 1 MHz

Please see the following plots (worst case):


GFSK:



2402 MHz




2441 MHz




2480 MHz


Π/4-DQPSK:



2402 MHz




2441 MHz




2480 MHz


8DPSK:



2402 MHz



2441 MHz




2480 MHz

9. NUMBER OF HOPPING FREQUENCY

9.1. LIMITS

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

9.2. BLOCK DIAGRAM OF TEST SETUP



9.3. TEST PROCEDURE


1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Enable the EUT hopping function.
4. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW $\geq$ 1% of the span; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
5. The number of hopping frequency used is defined as the number of total channel.
6. Record the measurement data derived from spectrum analyzer.

9.4. TEST RESULT



Number of Hopping Frequency is 79, with frequency space = 1MHz.

Please see the following plots (worst case):



GFSK:



$\pi/4$ -DQPSK:



8DPSK:




10. TIME OF OCCUPANCY (DWELL TIME)

10.1. LIMITS

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

10.2. BLOCK DIAGRAM OF TEST SETUP



10.3. TEST PROCEDURE

1. The RF output of EUT was connected to the spectrum analyzer by RF cable.
The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Enable the EUT hopping function.
4. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW ≥ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
5. Measure and record the results in the test report.

10.4. TEST RESULT

The test data of worst case (GFSK mode) are below:

Frequency (MHz)	Pulse Wide(ms)		Dwell Time (ms)	Limit (s)	Result (Pass / Fail)
2402	DH1	0.41	131.20	0.4	Pass
	DH3	1.68	268.80		
	DH5	2.94	313.61		
2441	DH1	0.41	131.20	0.4	Pass
	DH3	1.68	268.80		
	DH5	2.91	310.41		
2480	DH1	0.41	131.20	0.4	Pass
	DH3	1.68	268.80		
	DH5	2.94	313.61		


Remark:

DH1 Packet permit maximum $1600 / 79 / 2 = 10.12$ hops per second in each channel (1 time slot RX, 1 time slot TX). So, total hops is $10.12 \times 31.6 = 320$


DH3 Packet permit maximum $1600 / 79 / 4 = 5.06$ hops per second in each channel (3 time slots RX, 1 time slot TX). So, total hops is $5.06 \times 31.6 = 160$

DH5 Packet permit maximum $1600 / 79 / 6 = 3.37$ hops per second in each channel (5 time slots RX, 1 time slot TX). So, total hops is $3.37 \times 31.6 = 106.67$


Please see the following plots (worst case):




2402 MHz_DH1





2402 MHz_DH3






2402 MHz_DH5



2441 MHz_DH1








2480 MHz_DH5

11. MAXIMUM PEAK CONDUCTED OUTPUT POWER MEASUREMENT

11.1. LIMITS

The limit for peak output power is 1Watt (30 dBm).

11.2. BLOCK DIAGRAM OF TEST SETUP



11.3. TEST PROCEDURE


1. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Measure the conducted output power with cable loss and record the results in the test report.
4. Measure and record the results in the test report.

11.4. TEST RESULT


All the modes of GFSK, $\pi/4$ -DQPSK and 8DPSK have been tested. The worst case is GFSK mode, and the worst data of GFSK mode are below:

Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Result (Pass / Fail)
2402	-1.40	30	Pass
2441	-0.82	30	Pass
2480	-1.98	30	Pass


Please see the following plots (worst case):



2402MHz



2441MHz




2480MHz

12. CONDUCTED BANDEDGE EMISSION MEASUREMENT

12.1. LIMITS

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

12.2. BLOCK DIAGRAM OF TEST SETUP



12.3. TEST PROCEDURE

1. Set to the maximum power setting and enable the EUT transmit continuously.
2. Set RBW = 100 kHz, VBW = 300 kHz ($\geq$ RBW). Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
3. Enable hopping function of the EUT and then repeat step 1 and 2.
4. Measure and record the results in the test report.


12.4. TEST RESULT

Pass.


The test data of worst case are below:

GFSK:

Hopping off mode:




Low channel




High channel

Hopping mode:




Low channel




High channel

$\pi/4$ -DQPSK:
Hopping off mode:




Low channel




High channel

Hopping mode:




Low channel




High channel

8DPSK:

Hopping off mode:




Low channel




High channel

Hopping mode:



Low channel




High channel

13. CONDUCTED SPURIOUS EMISSION MEASUREMENT

13.1. LIMITS

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

13.2. BLOCK DIAGRAM OF TEST SETUP




13.3. TEST PROCEDURE

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100 kHz, VBW = 300 kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
4. Measure and record the results in the test report.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


13.4. TEST RESULT

Pass.


Please see the following plots (worst case, GFSK mode):



2402MHz



2441MHz



2480MHz

14. RADIATED BANDEDGE EMISSION / RADIATED SPURIOUS EMISSION MEASUREMENT

14.1. LIMITS


The field strength of any emissions, which appear outside of operating frequency band and restricted band specified on FCC 15.205(a), shall not exceed the general radiated emission limits as below.

Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Distance (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


Note: the tighter limit applies at the band edges.

14.2. BLOCK DIAGRAM OF TEST SETUP


For radiated emissions from 9kHz to 30MHz



For radiated emissions from 30 - 1000MHz



For radiated emissions from 1GHz to 25GHz



14.3. TEST PROCEDURE

Below 30MHz

- The Product is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The maximum values of the field strength are recorded by adjusting the polarizations of the test antenna and rotating the turntable.
- For each suspected emission, the Product was arranged to its worst case and then turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test frequency analyzer system was set to Peak Detect (300Hz RBW in 9kHz to 150kHz and 10kHz RBW in 150kHz to 30MHz) Function and Specified Bandwidth with Maximum Hold Mode.

30MHz ~ 1GHz:

- The Product was placed on the non-conductive turntable 0.8m above the ground at a chamber.
- Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 100 kHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied between 1~4 m in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
- For each frequency whose maximum record was higher or close to limit, measure its QP value (120 kHz RBW): vary the antenna's height and rotate the turntable from 0 to 360 degrees to find the height and degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to QP Detector and specified bandwidth with Maximum Hold Mode, and record the maximum value.

Above 1GHz:

- The EUT was placed on the non-conductive turntable 0.8 m above the ground at a chamber.
- Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 1MHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.

14.4. TEST RESULT

A. Below 30MHz:


No emissions were found higher than the background below 30MHz and background is lower than the limit, so it deems to compliance with the limit without recorded.

B. 30MHz ~ 1GHz:

The test data of low channel, middle channel and high channel are almost same in frequency bands 30MHz to 1GHz, and the data of middle channel (GFSK mode) are chosen as representative in below:

H:


76.9 dBuV/m



No.	Freq. MHz	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV/m)			Limit (dBuV/m)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		peak	QP	AVG	QP	AVG	QP	AVG		
1	47.7833	6.11			16.56	22.67			40.00		-17.33		P	
2	96.2833	7.71			13.57	21.28			43.50		-22.22		P	
3	306.4500	8.32			16.89	25.21			46.00		-20.79		P	

V:

76.9 dBuV/m



No.	Freq. MHz	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV/m)			Limit (dBuV/m)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		peak	QP	AVG	QP	AVG	QP	AVG		
1	52.6333	6.71			16.26	22.97			40.00		-17.03		P	
2	105.9833	7.58			13.76	21.34			43.50		-22.16		P	
3	337.1666	8.20			17.81	26.01			46.00		-19.99		P	

C. Above 1GHz:

Test Results-(Measurement Distance: 3m)_Channel low_2402MHz_GFSK mode							
Frequency (MHz)	Measurement value			Limit		Antenna	Result
	PK (dB μ V/m)	AV factor (dB)	AV (dB μ V/m)	PK (dB μ V/m)	AV (dB μ V/m)	(H/V)	(P/F)
2390.0	35.14	---	---	74	54	H	P
2402.0	97.81	---	---	---	---	H	P
2483.5	34.12	---	---	74	54	H	P
4804.0	47.23	---	---	74	54	H	P
2390.0	35.01	---	---	74	54	V	P
2402.0*	98.02	---	---	---	---	V	P
2483.5	35.12	---	---	74	54	V	P
4804.0	48.31	---	---	74	54	V	P

*: fundamental frequency

Test Results-(Measurement Distance: 3m)_Channel middle_2441MHz_GFSK mode							
Frequency (MHz)	Measurement value			Limit		Antenna	Result
	PK (dB μ V/m)	AV factor (dB)	AV (dB μ V/m)	PK (dB μ V/m)	AV (dB μ V/m)	(H/V)	(P/F)
2390.0	34.52	---	---	74	54	H	P
2441.0*	100.74	---	---	---	---	H	P
2483.5	35.82	---	---	74	54	H	P
4882.0	48.64	---	---	74	54	H	P
2390.0	35.14	---	---	74	54	V	P
2441.0*	104.42	---	---	---	---	V	P
2483.5	35.63	---	---	74	54	V	P
4882.0	50.41	---	---	74	54	V	P

*: fundamental frequency

Test Results-(Measurement Distance: 3m)_Channel high_2480MHz_GFSK mode							
Frequency (MHz)	Measurement value			Limit		Antenna	Result
	PK (dB μ V/m)	AV factor (dB)	AV (dB μ V/m)	PK (dB μ V/m)	AV (dB μ V/m)	(H/V)	(P/F)
2390.0	35.17	---	---	74	54	H	P
2480.0*	97.12	---	---	---	---	H	P
2483.5	38.21	---	---	74	54	H	P
4960.0	40.17	---	---	74	54	H	P
2390.0	35.41	---	---	74	54	V	P
2480.0*	99.25	---	---	---	---	V	P
2483.5	39.17	---	---	74	54	V	P
4960.0	42.64	---	---	74	54	V	P

*: fundamental frequency

Remark:

1. The above tables show that the frequencies peak data are all below the average limit, so the average data of these frequencies are deemed to fulfill the average limits and not reported.
2. All the modes of GFSK, $\pi/4$ -DQPSK and 8DPSK have been tested. The worst case is GFSK mode, and the worst data of GFSK mode are chosen as above.
3. No emissions found from 18GHz to 25GHz.
4. All outside of operating frequency band and restricted band specified are below 15.209.

15.AC CONDUCTED EMISSION TEST


15.1. LIMITS

Limits for Class B digital devices

Frequency range (MHz)	Limits dB(μV)	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

15.2. BLOCK DIAGRAM OF TEST SETUP




15.3. PROCEDURE OF CONDUCTED EMISSION TEST

- The Product was placed on a nonconductive table above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
- The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

15.4. GRAPHS AND DATA


Product : Bluetooth in-ear headphones **Model/Type reference** : HX-BTH3000
Power : DC 5V **Temperature** : 22℃
Mode : Keeping TX **Humidity** : 52%

L:



No.	Freq. MHz	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1860	31.32		27.04	9.79	41.11		36.83	64.21	54.21	-23.10	-17.38	P	
2	0.5299	32.63		27.58	9.80	42.43		37.38	56.00	46.00	-13.57	-8.62	P	
3	0.7180	29.50		25.00	9.80	39.30		34.80	56.00	46.00	-16.70	-11.20	P	
4	3.3740	34.49		29.26	9.95	44.44		39.21	56.00	46.00	-11.56	-6.79	P	
5	4.3740	30.55		24.74	9.98	40.53		34.72	56.00	46.00	-15.47	-11.28	P	
6	16.2300	28.54		25.46	10.17	38.71		35.63	60.00	50.00	-21.29	-14.37	P	

N:



No.	Freq. MHz	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1860	35.67		30.53	9.79	45.46		40.32	64.21	54.21	-18.75	-13.89	P	
2	0.2819	29.36		24.26	9.80	39.16		34.06	60.76	50.76	-21.60	-16.70	P	
3	0.5260	29.85		22.73	9.80	39.65		32.53	56.00	46.00	-16.35	-13.47	P	
4	1.4340	29.68		25.60	9.84	39.52		35.44	56.00	46.00	-16.48	-10.56	P	
5	3.2300	29.79		25.16	9.94	39.73		35.10	56.00	46.00	-16.27	-10.90	P	
6	16.2300	31.85		29.77	10.17	42.02		39.94	60.00	50.00	-17.98	-10.06	P	

APPENDIX 1 PHOTOGRAPHS OF TEST SETUP



TEST SETUP OF RADIATED EMISSION (30MHz-1GHz)



TEST SETUP OF RADIATED EMISSION (above 1GHz)



TEST SETUP OF CONDUCTED EMISSION

APPENDIX 2 EXTERNAL PHOTOGRAPHS OF PRODUCT



View of Product-1


APPENDIX 3 INTERNAL PHOTOGRAPHS OF PRODUCT




View of Product-1



View of Product-2



View of Product-3



View of Product-4



View of Product-5

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.