RF TEST REPORT

Report No.: 17071153-FCC-R2

Supersede Report No.: N/A

Applicant	MOVILTELCO TRADE, S.L
Product Name	Mobile phone
Model No.	M14D
Serial No.	N/A
Test Standard	FCC Part 15.247: 2016, ANSI C63.10: 2013
Test Date	November 10 to 23, 2017
Issue Date	November 24, 2017
Test Result	☑ Pass ☐ Fail
Equipment complied with the specification	☑
Equipment did not comply with the specification	☐

Loren Luo	David Huang	
Loren Luo Test Engineer	David Huang Checked By	

This test report may be reproduced in full only

Test result presented in this test report is applicable to the tested sample only

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.

In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY 5

2. CUSTOMER INFORMATION 5

3. TEST SITE INFORMATION 6

4. EQUIPMENT UNDER TEST (EUT) INFORMATION 7

5. TEST SUMMARY 9

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS 10

6.1 ANTENNA REQUIREMENT 10

6.2 CHANNEL SEPARATION 11

6.3 20DB BANDWIDTH 15

6.4 PEAK OUTPUT POWER 19

6.5 NUMBER OF HOPPING CHANNEL 23

6.6 TIME OF OCCUPANCY (DWELL TIME) 25

6.7 BAND EDGE & RESTRICTED BAND 29

6.8 AC POWER LINE CONDUCTED EMISSIONS 37

6.9 RADIATED EMISSIONS & RESTRICTED BAND 43

ANNEX A. TEST INSTRUMENT 50

ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS 51

ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT 62

ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST 66

ANNEX E. DECLARATION OF SIMILARITY 67

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17071153-FCC-R2	NONE	Original	November 24, 2017

2. Customer information

Applicant Name	MOVILTELCO TRADE, S.L
Applicant Add	Street: ABTAO,25-1Floor A-office MADRID-SPAIN
Manufacturer	MOVILTELCO TRADE, S.L
Manufacturer Add	Street: ABTAO,25-1Floor A-office MADRID-SPAIN

3. Test site information

Test Lab A:

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

Test Lab B:

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	694825
IC Test Site No.	4842B-1
Test Software	EZ_EMC(ver.lcp-03A1)

Note: We just perform Radiated Spurious Emission above 18GHz in the test Lab. B.

4. Equipment under Test (EUT) Information

Description of EUT:	Mobile phone
Main Model:	M14D
Serial Model:	N/A
Date EUT received:	November 09, 2017
Test Date(s):	November 10 to 23, 2017
Equipment Category :	DSS
Antenna Gain:	GSM850: 0.35dBi PCS1900: 0.65dBi Bluetooth: 0.35dBi
Antenna Type:	GSM: PIFA antenna BT: Monopole antenna
Type of Modulation:	GSM / GPRS: GMSK Bluetooth: GFSK, π /4DQPSK, 8DPSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz Bluetooth: 2402-2480 MHz
Max. Output Power:	-0.117dBm
Number of Channels:	GSM 850: 124CH PCS1900: 299CH Bluetooth: 79CH
Port:	USB Port, Earphone Port

Input Power:	Adapter: Model: M14D Input: AC100-240V~50/60Hz,0.20A Output: DC 5.0V,500mA Battery Model: M14D Spec: 3.7V, 600mAh Charging Voltage: 4.2V
Trade Name :	Mtt
FCC ID:	2ACQKTELCO014

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)	20 dB Bandwidth	Compliance
§15.247(b)(1)	Peak Output Power	Compliance
§15.247(a)(1)(iii)	Number of Hopping Channel	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(d)	Band Edge& Restricted Band	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions& Restricted Band	Compliance

Measurement Uncertainty

Emissions		
Test Item	**Description**	**Uncertainty**
Band Edge& Restricted Band and Radiated Emissions& Restricted Band	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited.
The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

a. Antenna must be permanently attached to the unit.
b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.
And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 2 antennas:
A permanently attached Monopole antenna for Bluetooth, the gain is 0.35dBi for Bluetooth.
A permanently attached PIFA antenna for GSM/PCS, the gain is 0.35dBi for GSM850, 0.65dBi for PCS1900.

The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 Channel Separation

Temperature	25℃
Relative Humidity	58%
Atmospheric Pressure	1016mbar
Test date :	November 16, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(a)(1)	a)	Channel Separation < 20dB BW and 20dB BW < 25KHz ; Channel Separation Limit=25KHz Chanel Separation < 20dB BW and 20dB BW > 25kHz ; Channel Separation Limit=2/3 20dB BW	☑
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - The EUT must have its hopping function enabled - Span = wide enough to capture the peaks of two adjacent channels - Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span - Video (or Average) Bandwidth (VBW) ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.		

Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Channel Separation measurement result

Type/ Modulation	CH	CH Frequency (MHz)	CH Separation (MHz)	Limit (MHz)	Result
CH Separation GFSK	Low Channel	2402	1.002	0.964	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.961	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.961	Pass
	Adjacency Channel	2479			
CH Separation π /4 DQPSK	Low Channel	2402	1.002	0.879	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.877	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.861	Pass
	Adjacency Channel	2479			
CH Separation 8DPSK	Low Channel	2402	1.002	0.863	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.865	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.864	Pass
	Adjacency Channel	2479			

Test Plots

Channel Separation measurement result

GFSK - Low Channel

GFSK - Middle Channel



GFSK - High Channel

π /4 DPSK - Low Channel

π /4 DQPSK - Middle Channel

π /4 DQPSK - High Channel

8DPSK - Low Channel

8DPSK - Middle Channel



8DPSK - High Channel

6.3 20dB Bandwidth

Temperature	25℃
Relative Humidity	58%
Atmospheric Pressure	1016mbar
Test date :	November 16, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a)(1)	a)	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	☑
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel - RBW ≥ 1% of the 20 dB bandwidth - VBW ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold. - The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference		

	marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Measurement result

Modulation	CH	CH Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GFSK	Low	2402	0.964	0.8860
	Mid	2441	0.961	0.8872
	High	2480	0.961	0.8808
π /4 DQPSK	Low	2402	1.318	1.1839
	Mid	2441	1.315	1.1891
	High	2480	1.292	1.1810
8-DPSK	Low	2402	1.294	1.1946
	Mid	2441	1.297	1.1953
	High	2480	1.296	1.1988

Test Plots

20dB Bandwidth measurement result



GFSK - Low Channel



GFSK - Middle Channel



GFSK - High Channel



π /4 DPSK - Low Channel



π /4 DQPSK - Middle Channel



π /4 DQPSK - High Channel



8DPSK - Low Channel



8DPSK - Middle Channel



8DPSK - High Channel

6.4 Peak Output Power

Temperature	25℃
Relative Humidity	58%
Atmospheric Pressure	1016mbar
Test date :	November 16, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b)(3)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	☑
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	☐
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	☑
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	☐
	e)	FHSS in 902-928MHz with ≥ 25 & <50 channels: ≤ 0.25 Watt	☐
	f)	DTS in 902-928MHz, 2400-2483.5MHz: ≤ 1 Watt	☐
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel - RBW > the 20 dB bandwidth of the emission being measured - VBW ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize.		

	- Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (see the note above regarding external attenuation and cable loss). The limit is specified in one of the subparagraphs of this Section. Submit this plot. A peak responding power meter may be used instead of a spectrum analyzer.
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Peak Output Power measurement result

Type	Modulation	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (mW)	Result
Output power	GFSK	Low	2402	-1.003	1000	Pass
		Mid	2441	-2.002	1000	Pass
		High	2480	-1.608	1000	Pass
	π /4 DQPSK	Low	2402	-0.386	125	Pass
		Mid	2441	-1.478	125	Pass
		High	2480	-1.247	125	Pass
	8-DPSK	Low	2402	-0.117	125	Pass
		Mid	2441	-1.228	125	Pass
		High	2480	-1.176	125	Pass

Test Plots

Output Power measurement result

GFSK Output power - Low CH 2402



GFSK Output power - Mid CH 2441



GFSK Output power - High CH 2480



π /4 DQPSK Output power - Low CH 2402



π /4 DQPSK Output power - Mid CH 2441



π /4 DQPSK Output power - High CH 2480



8DPSK Output power - Low CH 2402



8DPSK Output power - Mid CH 2441



8DPSK Output power - High CH 2480

6.5 Number of Hopping Channel

Temperature	25℃
Relative Humidity	58%
Atmospheric Pressure	1016mbar
Test date :	November 16, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a)(1)(iii)	a)	FHSS in 2400-2483.5MHz ≥ 15 channels	☑
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: The EUT must have its hopping function enabled. - Span = the frequency band of operation - RBW ≥ 1% of the span - VBW ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow trace to fully stabilize. - It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).		
Remark			
Result	☑ Pass ☐ Fail		

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Number of Hopping Channel measurement result

Type	Modulation	Frequency Range	Number of Hopping Channel	Limit
Number of Hopping Channel	GFSK	2400-2483.5	79	15
	π /4 DQPSK	2400-2483.5	79	15
	8-DPSK	2400-2483.5	79	15

Test Plots

Number of Hopping Channels measurement result



GFSK



π /4DQPSK



8DPSK

6.6 Time of Occupancy (Dwell Time)

Temperature	25℃
Relative Humidity	58%
Atmospheric Pressure	1016mbar
Test date :	November 16, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a)(1)(iii)	a)	Dwell Time < 0.4s	☑
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer - Span = zero span, centered on a hopping channel - RBW = 1 MHz - VBW ≥ RBW - Sweep = as necessary to capture the entire dwell time per hopping channel - Detector function = peak - Trace = max hold - use the marker-delta function to determine the dwell time		
Remark			
Result	☑ Pass ☐ Fail		

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Dwell Time measurement result

Type	Modulation	CH	Pulse Width (ms)	Dwell Time (ms)	Limit (ms)	Result
Dwell Time	GFSK	Low	2.920	311.467	400	Pass
		Mid	2.920	311.467	400	Pass
		High	2.920	311.467	400	Pass
	π /4 DQPSK	Low	2.910	310.400	400	Pass
		Mid	2.930	312.533	400	Pass
		High	2.900	309.333	400	Pass
	8-DPSK	Low	2.910	310.400	400	Pass
		Mid	2.910	310.400	400	Pass
		High	2.910	310.400	400	Pass
Note: Dwell time=Pulse Time (ms) × (1600 ÷ 6 ÷ 79) ×31.6						

Test Plots

Dwell Time measurement result



GFSK - Low CH 2402



GFSK - Mid CH 2441



GFDK - High CH 2480



π /4 DQPSK - Low CH 2402



π /4 DQPSK - Mid CH 2441



π /4 DQPSK - High CH 2480



8DPSK - Low CH 2402



8DPSK - Mid CH 2441



8DPSK - High CH 2480

6.7 Band Edge & Restricted Band

Temperature	25℃
Relative Humidity	57%
Atmospheric Pressure	1016mbar
Test date :	November 17, 2017
Tested By :	Evans He

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a)(1)(iii)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.☐	☑
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Radiated Method Only - 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. - 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range,		

	and make sure the instrument is operated in its linear range. - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	☑ Pass ☐ Fail

Test Data ☐ Yes ☑ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Plots

GFSK Mode:



GFSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz



GFSK-Hopping Right Side-PK

Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)

GFSK-Hopping Left Side-AV

Note: (no need if PK value less than the AV limit)

GFSK-Hopping Right Side-AV

Note: Both Horizontal and vertical polarities were investigated.



GFSK-Left Side-PK

Note: F1 is frequency 2400MHz



GFSK-Right Side-PK

Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)

GFSK-Left Side-AV

Note: (no need if PK value less than the AV limit)

GFSK-Right Side-AV

Note: Both Horizontal and vertical polarities were investigated.

π /4 DQPSK Mode:



π /4 DQPSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz



π /4 DQPSK-Hopping Right Side-PK

Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)

π /4 DQPSK-Hopping Left-AV

Note: (no need if PK value less than the AV limit)

π /4 DQPSK-Hopping Right-AV

Note: Both Horizontal and vertical polarities were investigated.



π /4 DQPSK-Left Side-PK

Note: F1 is frequency 2400MHz



π /4 DQPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)

π /4 DQPSK-Left Side-AV

Note: (no need if PK value less than the AV limit)

π /4 DQPSK-Right Side-AV

Note: Both Horizontal and vertical polarities were investigated.

8-DPSK Mode:



8DPSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz



8DPSK-Hopping Right Side-PK

Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)

8DPSK-Hopping Left-AV

Note: (no need if PK value less than the AV limit)

8DPSK-Hopping Right-AV

Note: Both Horizontal and vertical polarities were investigated.



8DPSK-Left Side-PK

Note: F1 is frequency 2400MHz



8DPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)

Note: (no need if PK value less than the AV limit)

8DPSK-Left Side-AV

8DPSK-Right Side-AV

Note: Both Horizontal and vertical polarities were investigated.

6.8 AC Power Line Conducted Emissions

Temperature	25℃
Relative Humidity	57%
Atmospheric Pressure	1016mbar
Test date :	November 17, 2017
Tested By :	Evans He

Requirement(s):

<table>
<tr><th>Spec</th><th>Item</th><th>Requirement</th><th>Applicable</th></tr>
<tr><td>47CFR§15.207, RSS210 (A8.1)</td><td>a)</td><td>For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.
<table>
<tr><th rowspan="2">Frequency ranges (MHz)</th><th colspan="2">Limit (dBμV)</th></tr>
<tr><th>QP</th><th>Average</th></tr>
<tr><td>0.15 ~ 0.5</td><td>66 – 56</td><td>56 – 46</td></tr>
<tr><td>0.5 ~ 5</td><td>56</td><td>46</td></tr>
<tr><td>5 ~ 30</td><td>60</td><td>50</td></tr>
</table></td><td>☑</td></tr>
<tr><td>Test Setup</td><td colspan="3"> 

Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</td></tr>
<tr><td>Procedure</td><td colspan="3">1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.
2. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains.
3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss</td></tr>
</table>

	coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Mode:	Bluetooth Mode



Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	L1	0.1734	36.62	QP	10.03	46.65	64.80	-18.15
2	L1	0.1734	23.34	AVG	10.03	33.37	54.80	-21.43
3	L1	0.2592	29.52	QP	10.03	39.55	61.46	-21.91
4	L1	0.2592	16.11	AVG	10.03	26.14	51.46	-25.32
5	L1	0.4698	25.44	QP	10.03	35.47	56.52	-21.05
6	L1	0.4698	12.08	AVG	10.03	22.11	46.52	-24.41
7	L1	1.5735	21.08	QP	10.04	31.12	56.00	-24.88
8	L1	1.5735	9.20	AVG	10.04	19.24	46.00	-26.76
9	L1	4.8174	23.98	QP	10.08	34.06	56.00	-21.94
10	L1	4.8174	9.38	AVG	10.08	19.46	46.00	-26.54
11	L1	12.3639	16.69	QP	10.19	26.88	60.00	-33.12
12	L1	12.3639	0.55	AVG	10.19	10.74	50.00	-39.26

Test Mode:	Bluetooth Mode



Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	N	0.1734	34.62	QP	10.03	44.65	64.80	-20.15
2	N	0.1734	18.68	AVG	10.03	28.71	54.80	-26.09
3	N	0.3801	34.13	QP	10.03	44.16	58.28	-14.12
4	N	0.3801	22.18	AVG	10.03	32.21	48.28	-16.07
5	N	0.8052	22.94	QP	10.03	32.97	56.00	-23.03
6	N	0.8052	10.22	AVG	10.03	20.25	46.00	-25.75
7	N	1.5657	20.71	QP	10.04	30.75	56.00	-25.25
8	N	1.5657	10.00	AVG	10.04	20.04	46.00	-25.96
9	N	4.7121	21.24	QP	10.08	31.32	56.00	-24.68
10	N	4.7121	7.31	AVG	10.08	17.39	46.00	-28.61
11	N	9.8328	14.44	QP	10.15	24.59	60.00	-35.41
12	N	9.8328	-0.63	AVG	10.15	9.52	50.00	-40.48

Test Mode:	Bluetooth Mode



Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	L1	0.1695	36.10	QP	10.03	46.13	64.98	-18.85
2	L1	0.1695	21.44	AVG	10.03	31.47	54.98	-23.51
3	L1	0.4269	30.24	QP	10.03	40.27	57.31	-17.04
4	L1	0.4269	25.41	AVG	10.03	35.44	47.31	-11.87
5	L1	0.7662	24.04	QP	10.03	34.07	56.00	-21.93
6	L1	0.7662	18.57	AVG	10.03	28.60	46.00	-17.40
7	L1	2.2989	26.36	QP	10.05	36.41	56.00	-19.59
8	L1	2.2989	17.22	AVG	10.05	27.27	46.00	-18.73
9	L1	3.8697	27.27	QP	10.07	37.34	56.00	-18.66
10	L1	3.8697	18.46	AVG	10.07	28.53	46.00	-17.47
11	L1	7.0131	20.24	QP	10.11	30.35	60.00	-29.65
12	L1	7.0131	7.44	AVG	10.11	17.55	50.00	-32.45

Test Mode:	Bluetooth Mode



Test Data

Phase Neutral Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	N	0.1812	29.05	QP	10.02	39.07	64.43	-25.36
2	N	0.1812	10.64	AVG	10.02	20.66	54.43	-33.77
3	N	0.4191	24.04	QP	10.02	34.06	57.47	-23.41
4	N	0.4191	12.58	AVG	10.02	22.60	47.47	-24.87
5	N	1.0392	24.14	QP	10.03	34.17	56.00	-21.83
6	N	1.0392	13.95	AVG	10.03	23.98	46.00	-22.02
7	N	2.5290	18.67	QP	10.05	28.72	56.00	-27.28
8	N	2.5290	14.62	AVG	10.05	24.67	46.00	-21.33
9	N	4.7238	19.66	QP	10.07	29.73	56.00	-26.27
10	N	4.7238	3.00	AVG	10.07	13.07	46.00	-32.93
11	N	22.4571	6.48	QP	10.30	16.78	60.00	-43.22
12	N	22.4571	1.41	AVG	10.30	11.71	50.00	-38.29

6.9 Radiated Emissions & Restricted Band

Temperature	25℃
Relative Humidity	57%
Atmospheric Pressure	1016mbar
Test date :	November 17, 2017
Tested By :	Evans He

Requirement(s):

<table>
<tr><th>Spec</th><th>Item</th><th>Requirement</th><th>Applicable</th></tr>
<tr><td>47CFR§15.205, §15.209, §15.247(d)</td><td>a)</td><td>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges
<table>
<tr><th>Frequency range (MHz)</th><th>Field Strength (μV/m)</th></tr>
<tr><td>0.009~0.490</td><td>2400/F(KHz)</td></tr>
<tr><td>0.490~1.705</td><td>24000/F(KHz)</td></tr>
<tr><td>1.705~30.0</td><td>30</td></tr>
<tr><td>30 – 88</td><td>100</td></tr>
<tr><td>88 – 216</td><td>150</td></tr>
<tr><td>216 960</td><td>200</td></tr>
<tr><td>Above 960</td><td>500</td></tr>
</table></td><td>☑</td></tr>
<tr><td>Test Setup</td><td colspan="3"> 
</td></tr>
</table>



Procedure

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:
   a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen.
   b. The EUT was then rotated to the direction that gave the maximum emission.
   c. Finally, the antenna height was adjusted to the height that gave the maximum emission.
3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.

   The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.
5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.

Remark

Result ☑ Pass ☐ Fail

Test Data ☑ Yes ☐ N/A

Test Plot ☑ Yes (See below) ☐ N/A

Test Result:

Test Mode:	Transmitting Mode

Frequency range: 9KHz - 30MHz

Freq. (MHz)	Detection value	Factor (dB/m)	Reading (dBuV/m)	Result (dBuV/m)	Limit@3m (dBuV/m)	Margin (dB)
--	--	--	--	--	--	>20
--	--	--	--	--	--	>20

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =40 log (specific distance/test distance)(dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

Test Mode:	Bluetooth Mode

30MHz -1GHz



Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	( )
1	H	45.2166	25.93	peak	10.50	22.29	0.75	14.89	40.00	-25.11	200	120
2	H	78.4134	30.48	peak	7.63	22.41	1.02	16.72	40.00	-23.28	100	335
3	H	98.8326	28.96	peak	10.12	22.32	1.09	17.85	43.50	-25.65	100	266
4	H	151.0666	25.93	peak	12.60	22.33	1.35	17.55	43.50	-25.95	100	93
5	H	255.6231	28.95	peak	11.65	22.29	1.71	20.02	46.00	-25.98	100	310
6	H	449.5558	25.37	peak	16.69	21.91	2.13	22.28	46.00	-23.72	100	16

30MHz -1GHz



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	V	31.8427	29.10	peak	19.98	22.27	0.67	27.48	40.00	-12.52	100	138
2	V	51.3005	39.69	peak	8.26	22.38	0.79	26.36	40.00	-13.64	100	282
3	V	78.4134	39.00	peak	7.63	22.41	1.02	25.24	40.00	-14.76	100	291
4	V	141.8262	29.13	peak	12.60	22.40	1.28	20.61	43.50	-22.89	100	37
5	V	304.6100	25.45	peak	13.70	22.28	1.81	18.68	46.00	-27.32	100	104
6	V	851.0353	32.66	peak	21.96	21.01	2.87	36.48	46.00	-9.52	100	184

Above 1GHz

Test Mode:	Transmitting Mode

Low Channel: 8-DPSK Mode (Worst Case) (2402 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4804	46.96	AV	V	33.39	7.22	48.46	39.11	54	-14.89
4804	47.51	AV	H	33.39	7.22	48.46	39.66	54	-14.34
4804	65.75	PK	V	33.39	7.22	48.46	57.9	74	-16.1
4804	64.89	PK	H	33.39	7.22	48.46	57.04	74	-16.96
9021	30.7	AV	V	38.15	9.18	48.68	29.35	54	-24.65
9021	28.64	AV	H	38.15	9.18	48.68	27.29	54	-26.71
9021	49.73	PK	V	38.15	9.18	48.68	48.38	74	-25.62
9021	51.95	PK	H	38.15	9.18	48.68	50.6	74	-23.4

Middle Channel: 8-DPSK Mode (Worst Case) (2441 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4882	46.06	AV	V	33.62	7.53	48.36	38.85	54	-15.15
4882	43.82	AV	H	33.62	7.53	48.36	36.61	54	-17.39
4882	66.85	PK	V	33.62	7.53	48.36	59.64	74	-14.36
4882	66.69	PK	H	33.62	7.53	48.36	59.48	74	-14.52
7050	39.8	AV	V	36.66	7.91	49.47	34.9	54	-19.1
7050	37.91	AV	H	36.66	7.91	49.47	33.01	54	-20.99
7050	56.78	PK	V	36.66	7.91	49.47	51.88	74	-22.12
7050	56.68	PK	H	36.66	7.91	49.47	51.78	74	-22.22

High Channel: 8-DPSK Mode (Worst Case) (2480 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4960	43.29	AV	V	33.89	7.86	48.31	36.73	54	-17.27
4960	48.96	AV	H	33.89	7.86	48.31	42.4	54	-11.6
4960	70.39	PK	V	33.89	7.86	48.31	63.83	74	-10.17
4960	66.78	PK	H	33.89	7.86	48.31	60.22	74	-13.78
17927	19.17	AV	V	42.85	19.37	43.87	37.52	54	-16.48
17927	18.32	AV	H	42.85	19.37	43.87	36.67	54	-17.33
17927	40.11	PK	V	42.85	19.37	43.87	58.46	74	-15.54
17927	42.11	PK	H	42.85	19.37	43.87	60.46	74	-13.54

Note:

*1, The testing has been conformed to 10*2480MHz=24,800MHz*
2, All other emissions more than 30 dB below the limit
3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.
4, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/15/2017	09/14/2018	☑
Line Impedance	LI-125A	191106	09/23/2017	09/22/2018	☑
Line Impedance	LI-125A	191107	09/23/2017	09/22/2018	☑
ISN	ISN T800	34373	09/23/2017	09/22/2018	☑
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/22/2017	09/21/2018	☑
Transient Limiter	LIT-153	531118	08/30/2017	08/29/2018	☑
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/15/2017	09/14/2018	☑
Power Splitter	1#	1#	08/30/2017	08/29/2018	☑
DC Power Supply	E3640A	MY40004013	09/15/2017	09/14/2018	☑
Radiated Emissions					
EMI test receiver	ESL6	100262	09/15/2017	09/14/2018	☑
Positioning Controller	UC3000	MF780208282	11/17/2017	11/16/2018	☑
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/30/2017	08/29/2018	☑
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	☑
Active Antenna (9kHz-30MHz)	AL-130	121031	10/12/2017	10/11/2018	☑
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/19/2017	09/18/2018	☑
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/22/2017	09/21/2018	☑
Universal Radio Communication Tester	CMU200	121393	09/23/2017	09/22/2018	☑