

MPE Calculations : (Bluetooth LE)

- Frequency range : 2402 MHz ~ 2480 MHz
- Measured RF output power : 2.79 dBm
- Target Power & Tolerance : 2.00 dBm $\pm$ 1 dB (Max. 3 dBm & Min. 1 dBm)
- Maximum antenna peak gain : 2.42 dBi
- **Maximum output power for the calculatio 3.00 dBm**

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the

The MPE calculation for this exposure is shown below.

▪ EIRP = P + G = 3.00 dBm + 2.42 dBi = 5.42 dBm = 3.484 mW	- Note - P = Power input to the antenna(dBm) - G = Power gain of the antenna(dBi)
---	--

- Power density at the specific separation

▪ S = EIRP / (4 R² π) = 3.484 / (4 X 20² X π) = 0.000694 mW/cm²	- Note - S = Maximum power dencity(mW/cm²) - EIRP = Equivalent Isotropic Radiated Power(mW) - R = Distance to the center of the radiation of the antenna(20cm)
---	---

Conclusion : The exposure condition of this device is compliant with FCC rules.

The maximum permissible exposure(MPE) of the general population/Uncontrolled for this device is 1.0 mW/cm².