



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5) Date : 15 Apr 2016

Application No. : LU011338(5)

Applicant : Zego Electronic Company Limited (Shenzhen Yangri Electronic Ltd)
Room 703, Kowloon Building,
555 Nathan Road, Kowloon, HK

Sample Description : One(1) item of submitted sample stated to be Copter of Flapper Bot
of Model No. 6910
Sample registration No. : RU013467-001
Radio Frequency : 2405MHz – 2475MHz Transceiver
Rating : 3.7V rechargeable battery
: USB 5V charging adaptor
No. of submitted sample : Three (3) set (s)

Date Received : 22 Mar 2016

Test Period : 24 Mar 2016 to 05 Apr 2016.

Test Requested : FCC Part 15 Certificate (15.249)

Test Method : 47 CFR Part 15 (10-1-15 Edition)
ANSI C63.4 – 2014, ANSI C63.10 - 2013

Test Engineer : Mr. LEUNG Shu-kan, Ken

Test Result : See attached sheet(s) from page 2 to 38.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15
Subpart B and C.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : _____


Mr. WONG Lap-pong, Andrew
Manager
Electrical Division

Page 1 of 38

FCC ID: 2ACS610RX



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

Table of Contents

1	General Information	3
1.1	General Description	3
1.2	Location of the test site	4
1.3	List of measuring equipment.....	5
1.4	Measurement Uncertainty.....	6
2	Description of the radiated emission test	7
2.1	Test Procedure	7
2.2	Test Result	8
2.3	Radiated Emission Measurement Data	9
3	Description of the Line-conducted Test	14
3.1	Test Procedure	14
3.2	Test Result	14
3.3	Graph and Table of Conducted Emission Measurement Data	14
4	Photograph	15
4.1	Photographs of the Test Setup for Radiated Emission and Conducted Emission.....	15
4.2	Photographs of the External and Internal Configurations of the EUT	15
5	Supplementary document.....	16
5.1	Bandwidth.....	16
5.2	EUT Antenna	16
6	Appendices.....	17



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

1 General Information

1.1 General Description

The equipment under test (EUT) is a copter for Flapper Bot. The EUT is power by 3.7V rechargeable battery. It operates at 2405MHz – 2475MHz. When the receiver receives radio signal from transmitter, it will take the corresponding actions.

The brief circuit description is listed as follows:

- | | |
|----------------------|---|
| - U1, U4 | and its associated circuit act as MCU |
| - U5 | and its associated circuit act as RF circuit |
| - Y1 | and its associated circuit act as oscillator |
| - DD1, DD3 | and its associated circuit act as LED |
| - M1, M2, M3, M4, M5 | and its associated circuit act as motor |
| - Q2 | and its associated circuit act as power circuit |



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

1.2 Location of the test site

FCC Registered Test Site Number: 552221

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.10 – 2013. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.10 – 2013. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date	Calibration Period
EMI Test Receiver	R&S	ESCI	100152	27 Sep 2016	1Year
Spectrum Analyzer	R&S	FSV40	100628	09 Feb 2017	1Year
Broadband Antenna	Schaffner	CBL6112B	2718	15 Mar 2017	2Years
Loop Antenna	EMCO	6502	00056620	25 Jan 2018	2Years
Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-531	24 Nov 2016	2Years
Broadband Pre-Amplifier	Schwarzbeck	BBV 9718	9718-119	24 Nov 2016	2Years
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170442	02 Aug 2017	2Years
Broadband Pre-Amplifier	Schwarzbeck	BBV 9719	9719-010	02 Aug 2017	2Years
Coaxial Cable	Schaffner	RG 213/U	N/A	18 May 2016	1Years
Coaxial Cable	Suhner	RG 214/U	N/A	18 May 2016	1Years
Coaxial Cable	Suhner	Sucoflex_104	N/A	13 Dec 2016	1Years
LISN	R&S	ENV216	101323	21 Oct 2016	1Year
Coaxial Cable	Tyco Electronics	RG 58C/U	N/A	01 Nov 2016	1Year

Support equipment:

Adaptor

Model: A1299

Supply by CMA



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

1.4 Measurement Uncertainty

The reported uncertainty is based on a standard uncertainty multiplied by a coverage factor $k=2$, providing a level of confidence of approximately 95%.

Radiated emissions

Frequency	Uncertainty (U_{lab})
30MHz ~ 200MHz (Horizontal)	4.83dB
30MHz ~ 200MHz (Vertical)	4.84dB
200MHz ~ 1000MHz (Horizontal)	4.87dB
200MHz ~ 1000MHz (Vertical)	5.94dB
1GHz ~ 6GHz	4.41dB
6GHz ~ 18GHz	4.64dB

Conducted emissions

Frequency	Uncertainty (U_{lab})
150kHz~30MHz	2.64dB



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.10 – 2013.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground for below 1GHz measurement and 1.5m high above the ground for above 1GHz measurement. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

For 30MHz to 1GHz, broadband antenna with its vertical and horizontal plane is placed 3m from the EUT and rotated about its vertical and horizontal axis for maximum response at each azimuth about the EUT. And the reference point of antenna shall be 1 m above the ground.

For above 1GHz, horn antenna with its vertical and horizontal plane is placed 3m from the EUT and rotated about its vertical and horizontal axis for maximum response at each azimuth about the EUT. Preamplifier and High Pass filter was used for measurements. The reference point of antenna shall be 1 m above the ground.

The device was placed flat to produce the highest emission during measurement for Radiated Emission measurement.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

2.2 Test Result

Subpart C:

Peak Detector data were measured unless otherwise stated.

“#” means emissions appear within the restricted bands shall follow the requirement of section 15.205.

The frequencies from fundamental up to that tenth harmonics were investigated, and emissions more 20dB below limit were not reported. Thus, those highest emissions were presented in next page (section 2.3).

It was found that the EUT not meet the FCC requirement

Subpart B:

Quasi-Peak Detector data were measured unless otherwise stated.

“#” means emissions appear within the restricted bands shall follow the requirement of section 15.205.

The emissions meet the requirement of section 15.109 are based on measurements employing the CISPR quasi-peak detector below 1000MHz and average detector for frequencies above 1000MHz.

The frequencies from 30MHz to 1000MHz were investigated, and emissions more 20dB below limit were not reported. Thus, those highest emissions were presented in next page (section 2.3).

It was found that the EUT meet the FCC requirement.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart C

Environmental conditions:

Parameter	Recorded value	
Ambient temperature:	23	° C
Relative humidity:	73	%

Measurement: Peak RBW: 1MHz VBW: 3MHz Operation mode: Transmission

Testing frequency range: 9kHz to 25GHz

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBμV)	Transducer Factor (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
2404.644	V	84.4	- 4.2	80.2	114.0	- 33.8
#4809.790	H	51.7	3.7	55.4	74.0	- 18.6
7213.961	H	38.6	11.5	50.1	74.0	- 23.9
7215.489	V	38.1	11.5	49.6	74.0	- 24.4

2433.137	V	82.9	- 4.2	78.7	114.0	- 35.3
#4863.807	H	50.6	3.7	54.3	74.0	- 19.7
#7297.956	H	39.9	11.5	51.4	74.0	- 22.6
#7299.394	V	41.0	11.5	52.5	74.0	- 21.5

2474.656	V	82.7	- 4.3	78.4	114.0	- 35.6
#4951.078	H	50.4	4.0	54.4	74.0	- 19.6
#7423.906	V	36.7	11.5	48.2	74.0	- 25.8
#7424.116	H	41.2	11.5	52.7	74.0	- 21.3

Remark: Other emissions more than 20dB below the limit are not reported.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

2.3 Radiated Emission Measurement Data (Con't)

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart C

Environmental conditions:

Parameter	Recorded value	
Ambient temperature:	23	° C
Relative humidity:	73	%

Measurement: Average Operation mode: Transmission

Testing frequency range: 9kHz to 25GHz

Frequency (MHz)	Polarity (H/V)	Peak Field Strength at 3m (dBμV/m)	Average Factor (dB/m)	Average Value at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
2404.644	V	80.2	- 10.2	70.0	94.0	- 24.0
#4809.790	H	55.4	- 10.2	45.2	54.0	- 8.8
7213.961	H	50.1	- 10.2	39.9	54.0	- 14.1
7215.489	V	49.6	- 10.2	39.4	54.0	- 14.6

2433.137	V	78.7	- 10.2	68.5	94.0	- 25.5
#4863.807	H	54.3	- 10.2	44.1	54.0	- 9.9
#7297.956	H	51.4	- 10.2	41.2	54.0	- 12.8
#7299.394	V	52.5	- 10.2	42.3	54.0	- 11.7

2474.656	V	78.4	- 10.2	68.2	94.0	- 25.8
#4951.078	H	54.4	- 10.2	44.2	54.0	- 9.8
#7423.906	V	48.2	- 10.2	38.0	54.0	- 16.0
#7424.116	H	52.7	- 10.2	42.5	54.0	- 11.5

Remark: Other emissions more than 20dB below the limit are not reported.

Average Value at 3m = Peak Field Strength at 3m + Average Factor.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

2.3 Radiated Emission Measurement Data (Con't)

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart C

Environmental conditions:

Parameter	Recorded value	
Ambient temperature:	21	° C
Relative humidity:	73	%

Detector: Quasi-peak

Mode; Transmission

RBW: 120kHz

VBW: 300kHz

Testing frequency range: 9kHz to 25GHz

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBμV)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
44.558	H	5.9	15.4	21.3	40.0	- 18.7
86.335	H	8.3	9.7	18.0	40.0	- 22.0
129.259	H	8.5	14.4	22.9	43.5	- 20.6
186.380	H	8.9	11.2	20.1	43.5	- 23.4
228.105	H	9.3	11.8	21.1	46.0	- 24.9
312.570	H	8.5	16.8	25.3	46.0	- 20.7
385.918	H	20.3	16.8	37.1	46.0	- 8.9

Remark: Other emissions more than 20dB below the limit are not reported.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

2.3 Radiated Emission Measurement Data (Con't)

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart B

Environmental conditions:

Parameter	Recorded value	
Ambient temperature:	21	° C
Relative humidity:	73	%

Detector: Quasi-peak

Mode: Receiving

RBW: 120kHz

VBW: 300kHz

Testing frequency range: 9kHz to 25GHz

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBμV)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
47.101	H	9.4	12.8	22.2	40.0	- 17.8
87.635	H	8.5	9.7	18.2	40.0	- 21.8
137.400	H	8.3	14.4	22.7	43.5	- 20.8
192.358	H	9.3	11.2	20.5	43.5	- 23.0
250.211	H	8.5	15.4	23.9	46.0	- 22.1
303.163	H	8.3	16.8	25.1	46.0	- 20.9
385.911	H	11.6	16.8	28.4	46.0	- 17.6

Remark: Other emissions more than 20dB below the limit are not reported.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

2.3 Radiated Emission Measurement Data (Con't)

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart B

Environmental conditions:

Parameter	Recorded value	
Ambient temperature:	21	° C
Relative humidity:	73	%

Detector: Quasi-peak

Mode; Charging

RBW: 120kHz

VBW: 300kHz

Testing frequency range: 9kHz to 25GHz

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBμV)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
67.857	H	3.3	7.6	16.1	40.0	- 23.9
118.551	H	13.0	12.2	22.7	43.5	- 20.8
164.456	H	5.7	11.9	20.1	43.5	- 23.4
203.380	H	9.4	12.0	20.6	43.5	- 22.9
251.904	H	8.6	15.4	24.0	46.0	- 22.0
279.830	H	7.7	15.4	24.5	46.0	- 21.5
321.315	H	8.9	16.8	25.7	46.0	- 20.3

Remark: Other emissions more than 20dB below the limit are not reported.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.10 – 2014. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

The EUT is connected to adaptor.

It was found that the EUT met the FCC requirement.

3.3 Graph and Table of Conducted Emission Measurement Data

For electronic filling, the document is saved with filename TestRpt2.pdf.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conducted Emission

For electronic filing, the photos are saved with filename 2ACS610RX TSup.pdf.

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename 2ACS610RX ExPho.pdf and 2ACS610RX InPho.pdf.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

The plot saved in TestRpt3.pdf shows the fundamental emission is confined in the specified band. It shows the 20dB bandwidth met the 15.215 requirement for frequency band 2400 to 2483.5 MHz. .

The plot saved in TestRpt4.pdf shows the band edge is fulfil 15.209 requirement.

5.2 EUT Antenna

Appendices A5 shows the antenna is permanently attached and cannot be changed. Therefore it fulfils the section 15.203 requirement

5.3 Duty cycle Calculation

Appendices A8 shows the plots of duty cycle

All channels are using the same data pattern

Time of one cycle: 558 μ s

Number of pulses in one cycle: 1

Time of one pulse: 172 μ s

Duty cycle = $170\mu\text{s} / 558\mu\text{s} = 0.308$

Average factor = $20 * \log(0.308) = -10.2$



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

6 Appendices

A1	Photos of the set-up of Radiated Emissions	4	pages
A2	Photos of the set-up of Conducted Emissions	2	pages
A3	Photos of External Configurations	3	pages
A4	Photos of Internal Configurations	2	pages
A5	EUT Antenna	1	page
A6	ID Label/Location	1	page
A7	Conducted Emission Measurement Data	3	pages
A8	Band Edge	2	pages
A9	20dB Bandwidth Plot	2	pages
A10	Duty Cycle Plot	1	page



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT


Report No. : AU0021373(5)

Date : 15 Apr 2016

A1. Photos of the set-up of Radiated Emissions



(Front view, 30MHz – 1GHz)



(Back view, 30MHz – 1GHz)

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AU0021373(5)

Date : 15 Apr 2016

A1. Photos of the set-up of Radiated Emissions



(Front view, 9KHz – 30MHz)



(Back view, 9KHz – 30MHz)

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

A1. Photos of the set-up of Radiated Emissions



(front view, 1GHz – 25GHz)



(rear view, 1GHz – 25GHz)

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT


Report No. : AU0021373(5)

Date : 15 Apr 2016

A1. Photos of the set-up of Radiated Emissions



(front view, charging)



(rear view, charging)

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT


Report No. : AU0021373(5)

Date : 15 Apr 2016

A2 Photos of the set-up of Conducted Emission



(front view)



(rear view)

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

A2 Photos of the set-up of Conducted Emission



(side view)

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew



**CMA Testing
and Certification
Laboratories**

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

A3. Photos of External Configuration



External Configuration 1



External Configuration 2

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

A3. Photos of External Configuration



External Configuration 3



External Configuration 4

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

A3. Photos of External Configuration



External Configuration 5

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT


Report No. : AU0021373(5)

Date : 15 Apr 2016

A4. Photos of Internal Configuration



Internal Configuration 1



Internal Configuration 2

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AU0021373(5)

Date : 15 Apr 2016

A4. Photos of Internal Configuration



Internal Configuration 3



Internal Configuration 4

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

A5. EUT Antenna



Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

A6. ID Label/Location



Label 1



Label 2

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016


A7 Conducted Emission Measurement Date



RBW 9 kHz

MT 1 s

Att 10 dB AUTO PREAMP OFF



Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

A7 Conducted Emission Measurement Date

EDIT PEAK LIST (Final Measurement Results)				
Trace1:	FCC-QP			
Trace2:	FCC-AV			
Trace3:	---			
TRACE	FREQUENCY	LEVEL dB μ V		DELTA LIMIT dB
1 Quasi Peak	199.5 kHz	26.48	L1 gnd	-37.14
1 Quasi Peak	235.5 kHz	47.77	N gnd	-14.48
2 Average	235.5 kHz	37.08	N gnd	-15.16
1 Quasi Peak	352.5 kHz	43.69	N gnd	-15.21
2 Average	352.5 kHz	35.79	N gnd	-13.11
1 Quasi Peak	469.5 kHz	39.66	N gnd	-16.85
2 Average	469.5 kHz	26.01	N gnd	-20.51
1 Quasi Peak	711.5 kHz	37.19	N gnd	-18.80
2 Average	711.5 kHz	28.13	N gnd	-17.86
1 Quasi Peak	828.5 kHz	35.59	L1 gnd	-20.40
2 Average	828.5 kHz	31.01	N gnd	-14.98
1 Quasi Peak	1.1885 MHz	32.28	L1 gnd	-23.71
2 Average	1.3055 MHz	25.52	N gnd	-20.47
1 Quasi Peak	1.544 MHz	32.80	N gnd	-23.19
2 Average	1.8905 MHz	23.42	N gnd	-22.57
1 Quasi Peak	2.129 MHz	30.79	N gnd	-25.20
2 Average	2.4935 MHz	22.00	N gnd	-24.00
1 Quasi Peak	3.0515 MHz	27.00	N gnd	-28.99
2 Average	3.0515 MHz	20.49	N gnd	-25.50
1 Quasi Peak	4.406 MHz	26.26	N gnd	-29.73

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

A7 Conducted Emission Measurement Date

EDIT PEAK LIST (Final Measurement Results)				
Trace1:	FCC-QP			
Trace2:	FCC-AV			
Trace3:	---			
TRACE	FREQUENCY	LEVEL dB μ V		DELTA LIMIT dB
2 Average	4.4195 MHz	20.73	N gnd	-25.26
2 Average	7.2635 MHz	19.19	N gnd	-30.80
1 Quasi Peak	7.8575 MHz	27.79	L1 gnd	-32.20
1 Quasi Peak	10.697 MHz	31.22	N gnd	-28.77
2 Average	10.697 MHz	18.85	L1 gnd	-31.14
2 Average	15.251 MHz	26.68	L1 gnd	-23.31
1 Quasi Peak	15.3005 MHz	39.48	N gnd	-20.51
1 Quasi Peak	17.6315 MHz	48.02	N gnd	-11.97
2 Average	17.843 MHz	36.25	N gnd	-13.74
2 Average	21.6095 MHz	23.93	N gnd	-26.06
1 Quasi Peak	21.839 MHz	33.20	N gnd	-26.79

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT


Report No. : AU0021373(5)

Date : 15 Apr 2016

A8. Band Edge



Lower edge (Peak measurement)



Lower edge (Average measurement)

Tested by:

Ken

Mr. LEUNG Shu-kan, Ken

Reviewed by:

PR

Mr. WONG Lap-pong, Andrew



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT


Report No. : AU0021373(5)

Date : 15 Apr 2016

A8. Band Edge



Upper edge (Peak measurement)



Upper edge (Average measurement)

Tested by:

Ken

Mr. LEUNG Shu-kan, Ken

Reviewed by:

PR

Mr. WONG Lap-pong, Andrew



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT


Report No. : AU0021373(5)

Date : 15 Apr 2016

A9. 20dB Bandwidth Plot



Bandwidth 1 (2405MHz)



Bandwidth 2 (2433MHz)

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

A9. 20dB Bandwidth Plot



Bandwidth 3 (2475MHz)

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew

FCC ID: 2ACS610RX

Page 37 of 38

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmatcl.com
This document shall not be reproduced except in full or with written approval by CMA Testing

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT

Report No. : AU0021373(5)

Date : 15 Apr 2016

A10. Duty cycle Plot



***** End of Report *****

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew

FCC ID: 2ACS610RX

Page 38 of 38

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmatcl.com
This document shall not be reproduced except in full or with written approval by CMA Testing

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>