

## INTERTEK TESTING SERVICES

---

### RF Exposure

The equipment under test (EUT) is a remote controller operating at 2.4G Band. The EUT can be powered by DC 3.0V (2 x 1.5V AAA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna

Modulation Type: GFSK

Antenna Gain: 0dBi

The normal radiated output power (e.i.r.p) is: -12.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -12.0dBm (tolerance: +/- 3dB).

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 83.5dBμV/m at 3m in the frequency 2402MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -11.73dBm  
which is within the production variation.

The Minimum peak radiated emission for the EUT is 81.0dBμV/m at 3m in the frequency 2478MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -14.23dBm  
which is within the production variation.

The maximum conducted output power specified is -9.0dBm = 0.126mW

The source- based time-averaging conducted output power  
= 0.126mW

The SAR Exclusion Threshold Level:

=  $3.0 \cdot (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$

=  $3.0 \cdot 5 / \sqrt{2.478}$  mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.