

TEST REPORT

Product : Spark Plug
Trade mark : Scalextric®
Model/Type reference : SA00528
Serial Number : N/A
Report Number : EED32L00061001
FCC ID : 2ACUF-SA00528
Date of Issue : Jun. 26, 2019
Test Standards : 47 CFR Part 15Subpart C
Test result : PASS

Prepared for:

Hornby Hobbies Ltd
Enterprise Road Westwood Industrial Estate, CT9 4JX,
United Kingdom

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Tested By:

Jay Zheng

Jay Zheng

Compiled by:

Kevin Lan

Kevin Lan

Reviewed by:

Ware Xin

Ware Xin

Approved by:

Kevin Yang

Kevin yang

Date:

Jun. 26, 2019

Check No.: 1022573910



2 Version

Version No.	Date	Description
00	Jun. 26, 2019	Original

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15Subpart C Section 15.203/15.247 (c)	ANSI C63.10-2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15Subpart C Section 15.207	ANSI C63.10-2013	PASS
Conducted Peak Output Power	47 CFR Part 15Subpart C Section 15.247 (b)(3)	ANSI C63.10-2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15Subpart C Section 15.247 (a)(2)	ANSI C63.10-2013	PASS
Power Spectral Density	47 CFR Part 15Subpart C Section 15.247 (e)	ANSI C63.10-2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15Subpart C Section 15.247(d)	ANSI C63.10-2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15Subpart C Section 15.247(d)	ANSI C63.10-2013	PASS
Radiated Spurious Emissions	47 CFR Part 15Subpart C Section 15.205/15.209	ANSI C63.10-2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15Subpart C Section 15.205/15.209	ANSI C63.10-2013	PASS

Remark:

Test according to ANSI C63.4-2014 & ANSI C63.10-2013.

The tested sample(s) and the sample information are provided by the client.


4 Content

1 COVER PAGE.....	1
2 VERSION.....	2
3 TEST SUMMARY.....	3
4 CONTENT.....	4
5 TEST REQUIREMENT.....	5
5.1 TEST SETUP.....	5
5.1.1 For Conducted test setup.....	5
5.1.2 For Radiated Emissions test setup.....	5
5.1.3 For Conducted Emissions test setup.....	6
5.2 TEST ENVIRONMENT.....	6
5.3 TEST CONDITION.....	6
6 GENERAL INFORMATION.....	7
6.1 CLIENT INFORMATION.....	7
6.2 GENERAL DESCRIPTION OF EUT.....	7
6.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	7
6.4 DESCRIPTION OF SUPPORT UNITS.....	8
6.5 TEST LOCATION.....	8
6.6 DEVIATION FROM STANDARDS.....	8
6.7 ABNORMALITIES FROM STANDARD CONDITIONS.....	8
6.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	8
6.9 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2).....	9
7 EQUIPMENT LIST.....	10
8 RADIO TECHNICAL REQUIREMENTS SPECIFICATION.....	14
Appendix A): 6dB Occupied Bandwidth.....	15
Appendix B): Conducted Peak Output Power.....	17
Appendix C): Band-edge for RF Conducted Emissions.....	19
Appendix D): RF Conducted Spurious Emissions.....	20
Appendix E): Power Spectral Density.....	24
Appendix F): Antenna Requirement.....	26
Appendix G): AC Power Line Conducted Emission.....	27
Appendix H): Restricted bands around fundamental frequency (Radiated).....	30
Appendix I): Radiated Spurious Emissions.....	35
PHOTOGRAPHS OF TEST SETUP.....	39
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....	41

5 Test Requirement

5.1 Test setup

5.1.1 For Conducted test setup



5.1.2 For Radiated Emissions test setup

Radiated Emissions setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz





Figure 3. Above 1GHz

5.1.3 For Conducted Emissions test setup

Conducted Emissions setup



5.2 Test Environment

Operating Environment for RF conducted test:	
Temperature:	24°C
Humidity:	54% RH
Atmospheric Pressure:	101kPa

5.3 Test Condition

Test channel:

Test Mode	Tx	RF Channel		
		Low(L)	Middle(M)	High(H)
GFSK	2402MHz ~2480 MHz	Channel 1	Channel 20	Channel 40
		2402MHz	2440MHz	2480MHz
TX mode:	The EUT transmitted the continuous signal at the specific channel(s).			

6 General Information

6.1 Client Information

Applicant:	Hornby Hobbies Ltd
Address of Applicant:	Enterprise Road Westwood Industrial Estate, CT9 4JX, United Kingdom
Manufacturer:	Hornby Hobbies Ltd
Address of Manufacturer:	Enterprise Road Westwood Industrial Estate, CT9 4JX, United Kingdom
Factory:	Jianhui Plastic & Electronic Industry (Shenzhen) Co. Ltd.
Address of Factory:	No. 127, Sili Road, Guanlan Zhen, Longhua District, Shenzhen, China

6.2 General Description of EUT

Product Name:	Spark Plug
Model No.:	SA00528
Trade mark:	Scalextric®
EUT Supports Radios application:	BT4.0 Single Mode; 2402-2480MHz
Power Supply:	AC Adapter MODEL No.: P9403W INPUT: 120V AC 60Hz 0.5A OUTPUT: 15V DC 1.2A
Hardware Version:	C(manufacturer declare)
Firmware Version:	1(manufacturer declare)
Sample Received Date:	Mar. 22, 2019
Sample tested Date:	Apr. 16, 2019 to Jun. 14, 2019

6.3 Product Specification subjective to this standard

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	4.0
Modulation Technique:	DSSS
Modulation Type:	GFSK
Number of Channel:	40
Test Power Grade:	P_m4dbm(manufacturer declare)
Test Software of EUT:	wtcdb
Antenna Type:	PCB antenna
Antenna Gain:	0dBi
Test Voltage:	AC 120V, 60Hz

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	11	2422MHz	21	2442MHz	31	2462MHz
2	2404MHz	12	2424MHz	22	2444MHz	32	2464MHz
3	2406MHz	13	2426MHz	23	2446MHz	33	2466MHz
4	2408MHz	14	2428MHz	24	2448MHz	34	2468MHz
5	2410MHz	15	2430MHz	25	2450MHz	35	2470MHz
6	2412MHz	16	2432MHz	26	2452MHz	36	2472MHz
7	2414MHz	17	2434MHz	27	2454MHz	37	2474MHz
8	2416MHz	18	2436MHz	28	2456MHz	38	2476MHz
9	2418MHz	19	2438MHz	29	2458MHz	39	2478MHz
10	2420MHz	20	2440MHz	30	2460MHz	40	2480MHz

6.4 Description of Support Units

The EUT has been tested independently.

6.5 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

6.6 Deviation from Standards

None.

6.7 Abnormalities from Standard Conditions

None.

6.8 Other Information Requested by the Customer

None.

6.9 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.9×10^{-8}
2	RF power, conducted	0.46dB (30MHz-1GHz)
		0.55dB (1GHz-18GHz)
3	Radiated Spurious emission test	4.3dB (30MHz-1GHz)
		4.5dB (1GHz-12.75GHz)
4	Conduction emission	3.5dB (9kHz to 150kHz)
		3.1dB (150kHz to 30MHz)
5	Temperature test	0.64°C
6	Humidity test	3.8%
7	DC power voltages	0.026%

7 Equipment List

RF test system					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Signal Generator	Keysight	E8257D	MY53401106	03-01-2019	02-28-2020
Spectrum Analyzer	Keysight	N9010A	MY54510339	03-01-2019	02-28-2020
Signal Generator	Keysight	N5182B	MY53051549	03-01-2019	02-28-2020
High-pass filter	Sinoscite	FL3CX03WG1 8NM12-0398-0 02	---	01-09-2019	01-08-2020
High-pass filter	MICRO-TRO NICS	SPA-F-63029-4	---	01-09-2019	01-08-2020
DC Power	Keysight	E3642A	MY54426035	03-01-2019	02-28-2020
PC-1	Lenovo	R4960d	---	03-01-2019	02-28-2020
BT&WI-FI Automatic control	R&S	OSP120	101374	03-01-2019	02-28-2020
RF control unit	JS Tonscend	JS0806-2	15860006	03-01-2019	02-28-2020
RF control unit	JS Tonscend	JS0806-1	15860004	03-01-2019	02-28-2020
RF control unit	JS Tonscend	JS0806-4	158060007	03-01-2019	02-28-2020
BT&WI-FI Automatic test software	JS Tonscend	JS1120-2	---	03-01-2019	02-28-2020
Temperature/ Humidity Indicator	biaozhi	HM10	1804186	10-12-2018	10-11-2019

Conducted disturbance Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Receiver	R&S	ESCI	100435	05-25-2018 05-20-2019	05-24-2019 05-18-2020
Temperature/ Humidity Indicator	Defu	TH128	/	07-02-2018	07-01-2019
Communication test set	Agilent	E5515C	GB47050 534	03-01-2019	02-28-2020
Communication test set	R&S	CMW500	102898	01-18-2019	01-17-2020
LISN	R&S	ENV216	100098	05-11-2018 05-08-2019	05-10-2019 05-06-2020
LISN	schwarzbeck	NNLK8121	8121-529	05-11-2018 05-08-2019	05-10-2019 05-06-2020
Voltage Probe	R&S	ESH2-Z3 0299.7810.56	100042	06-13-2017	06-11-2020
Current Probe	R&S	EZ-17 816.2063.03	100106	05-20-2019	05-18-2020
ISN	TESEQ	ISN T800	30297	01-06-2019	01-15-2020
Barometer	changchun	DYM3	1188	07-02-2018	07-01-2019

3M Semi/full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
3M Chamber & Accessory Equipment	TDK	SAC-3	---	06-04-2016 05-24-2019	06-03-2019 05-22-2022
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	9163-401	12-21-2018	12-20-2019
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	9163-618	07-30-2018	07-29-2019
Microwave Preamplifier	Agilent	8449B	3008A02425	08-21-2018	08-20-2019
Microwave Preamplifier	Tonscend	EMC051845S E	980380	01-16-2019	01-15-2020
Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-1869	04-25-2018	04-23-2021
Horn Antenna	ETS-LINDGREN	3117	00057410	06-05-2018	06-03-2021
Double ridge horn antenna	A.H.SYSTEMS	SAS-574	374	06-05-2018	06-04-2021
Pre-amplifier	A.H.SYSTEMS	PAP-1840-60	6041.6041	08-08-2018	08-07-2019
Loop Antenna	ETS	6502	00071730	06-22-2017	06-21-2019
Spectrum Analyzer	R&S	FSP40	100416	04-28-2019	04-26-2020
Receiver	R&S	ESCI	100435	05-20-2019	05-18-2020
Receiver	R&S	ESCI7	100938-003	11-23-2018	11-22-2019
Multi device Controller	matur	NCD/070/1071 1112	---	01-09-2019	01-08-2020
LISN	schwarzbeck	NNBM8125	81251547	05-11-2018 05-08-2019	05-10-2019 05-06-2020
LISN	schwarzbeck	NNBM8125	81251548	05-11-2018 05-08-2019	05-10-2019 05-06-2020
Signal Generator	Agilent	E4438C	MY45095744	03-01-2019	02-28-2020
Signal Generator	Keysight	E8257D	MY53401106	03-01-2019	02-28-2020
Temperature/ Humidity Indicator	Shanghai qixiang	HM10	1804298	10-12-2018	10-11-2019
Communication test set	Agilent	E5515C	GB47050534	03-01-2019	02-28-2020
Cable line	Fulai(7M)	SF106	5219/6A	01-09-2019	01-08-2020
Cable line	Fulai(6M)	SF106	5220/6A	01-09-2019	01-08-2020
Cable line	Fulai(3M)	SF106	5216/6A	01-09-2019	01-08-2020
Cable line	Fulai(3M)	SF106	5217/6A	01-09-2019	01-08-2020
Communication test set	R&S	CMW500	104466	01-18-2019	01-17-2020
High-pass filter	Sinoscite	FL3CX03WG1 8NM12-0398-002	---	01-09-2019	01-08-2020
High-pass filter	MICRO-TRONICS	SPA-F-63029-4	---	01-09-2019	01-08-2020
band rejection filter	Sinoscite	FL5CX01CA09 CL12-0395-001	---	01-09-2019	01-08-2020
band rejection filter	Sinoscite	FL5CX01CA08 CL12-0393-001	---	01-09-2019	01-08-2020
band rejection filter	Sinoscite	FL5CX02CA04 CL12-0396-002	---	01-09-2019	01-08-2020
band rejection filter	Sinoscite	FL5CX02CA03 CL12-0394-001	---	01-09-2019	01-08-2020

3M full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
RSE Automatic test software	JS Tonscend	JS36-RSE	10166	06-20-2018	06-19-2019
Receiver	Keysight	N9038A	MY57290136	03-27-2019	03-25-2020
Spectrum Analyzer	Keysight	N9020B	MY57111112	03-27-2019	03-25-2020
Spectrum Analyzer	Keysight	N9030B	MY57140871	03-27-2019	03-25-2020
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-075	04-25-2018	04-23-2021
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-076	04-25-2018	04-23-2021
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-1148	04-25-2018	04-23-2021
Horn Antenna	Schwarzbeck	BBHA 9170	9170-832	04-25-2018	04-23-2021
Horn Antenna	Schwarzbeck	BBHA 9170	9170-829	04-25-2018	04-23-2021
Communication Antenna	Schwarzbeck	CLSA 0110L	1014	02-15-2018 02-14-2019	02-14-2019 02-12-2020
Biconical antenna	Schwarzbeck	VUBA 9117	9117-381	04-25-2018	04-23-2021
Horn Antenna	ETS-LINDGR EN	3117	00057407	07-10-2018	07-08-2021
Preamplifier	EMCI	EMC184055SE	980596	06-20-2018	06-19-2019
Communication test set	R&S	CMW500	102898	01-18-2019	01-17-2020
Preamplifier	EMCI	EMC001330	980563	06-20-2018	06-19-2019
Preamplifier	Agilent	8449B	3008A02425	08-21-2018	08-20-2019
Temperature/Humidity Indicator	biaozhi	GM1360	EE1186631	05-02-2018 04-30-2019	05-01-2019 04-28-2020
Signal Generator	KEYSIGHT	E8257D	MY53401106	03-13-2018 03-01-2019	03-12-2019 02-28-2020
Fully Anechoic Chamber	TDK	FAC-3	---	01-17-2018	01-15-2021
Filter bank	JS Tonscend	JS0806-F	188060094	04-10-2018	04-08-2021
Cable line	Times	SFT205-NMSM-2.50M	394812-0001	01-09-2019	01-08-2020
Cable line	Times	SFT205-NMSM-2.50M	394812-0002	01-09-2019	01-08-2020
Cable line	Times	SFT205-NMSM-2.50M	394812-0003	01-09-2019	01-08-2020
Cable line	Times	SFT205-NMSM-2.50M	393495-0001	01-09-2019	01-08-2020
Cable line	Times	EMC104-NMNM-1000	SN160710	01-09-2019	01-08-2020
Cable line	Times	SFT205-NMSM-3.00M	394813-0001	01-09-2019	01-08-2020
Cable line	Times	SFT205-NMNM-1.50M	381964-0001	01-09-2019	01-08-2020
Cable line	Times	SFT205-NMSM-7.00M	394815-0001	01-09-2019	01-08-2020
Cable line	Times	HF160-KMKM-3.00M	393493-0001	01-09-2019	01-08-2020

8 Radio Technical Requirements Specification

Reference documents for testing:

No.	Identity	Document Title
1	FCC Part15C (2015)	Subpart C-Intentional Radiators
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

Test Results List:

Test Requirement	Test method	Test item	Verdict	Note
Part15C Section 15.247 (a)(2)	ANSI C63.10	6dB Occupied Bandwidth	PASS	Appendix A)
Part15C Section 15.247 (b)(3)	ANSI C63.10	Conducted Peak Output Power	PASS	Appendix B)
Part15C Section 15.247(d)	ANSI C63.10	Band-edge for RF Conducted Emissions	PASS	Appendix C)
Part15C Section 15.247(d)	ANSI C63.10	RF Conducted Spurious Emissions	PASS	Appendix D)
Part15C Section 15.247 (e)	ANSI C63.10	Power Spectral Density	PASS	Appendix E)
Part15C Section 15.203/15.247 (c)	ANSI C63.10	Antenna Requirement	PASS	Appendix F)
Part15C Section 15.207	ANSI C63.10	AC Power Line Conducted Emission	PASS	Appendix G)
Part15C Section 15.205/15.209	ANSI C63.10	Restricted bands around fundamental frequency (Radiated Emission)	PASS	Appendix H)
Part15C Section 15.205/15.209	ANSI C63.10	Radiated Spurious Emissions	PASS	Appendix I)

Appendix A): 6dB Occupied Bandwidth

Test Result

Mode	Channel	6dB Bandwidth [MHz]	99% OBW[MHz]	Verdict
BLE	LCH	0.6758	1.0554	PASS
BLE	MCH	0.7054	1.0680	PASS
BLE	HCH	0.7019	1.0687	PASS

Test Graphs

Graphs	
LCH	Center Freq 2.402000000 GHz Ref Offset 19.5 dB Ref 20.00 dBm Center 2.402 GHz #Res BW 100 kHz #VBW 300 kHz Span 3 MHz Sweep 1.057 ms Occupied Bandwidth 1.0554 MHz Total Power 6.30 dBm Transmit Freq Error -56.875 kHz OBW Power 99.90 % x dB Bandwidth 675.8 kHz x dB -6.00 dB
MCH	Center Freq 2.440000000 GHz Ref Offset 19.77 dB Ref 20.00 dBm Center 2.44 GHz #Res BW 100 kHz #VBW 300 kHz Span 3 MHz Sweep 1.057 ms Occupied Bandwidth 1.0680 MHz Total Power 7.13 dBm Transmit Freq Error -59.189 kHz OBW Power 99.90 % x dB Bandwidth 705.4 kHz x dB -6.00 dB
HCH	Center Freq 2.480000000 GHz Ref Offset 19.77 dB Ref 20.00 dBm Center 2.48 GHz #Res BW 100 kHz #VBW 300 kHz Span 3 MHz Sweep 1.057 ms Occupied Bandwidth 1.0687 MHz Total Power 7.18 dBm Transmit Freq Error -60.765 kHz OBW Power 99.90 % x dB Bandwidth 701.9 kHz x dB -6.00 dB

Appendix B): Conducted Peak Output Power

Test Result

Mode	Channel	Conduct Peak Power[dBm]	Verdict
BLE	LCH	-8.997	PASS
BLE	MCH	-7.884	PASS
BLE	HCH	-7.298	PASS

Test Graphs


Graphs	
LCH	Center Freq 2.402000000 GHz Ref Offset 19.6 dB Ref 13.50 dBm Mkr1 2.402 018 GHz -8.997 dBm Center 2.40200 GHz Res BW 2.0 MHz VBW 8.0 MHz Sweep 1.007 ms (8001 pos)
MCH	Center Freq 2.440000000 GHz Ref Offset 19.77 dB Ref 13.77 dBm Mkr1 2.440 203 GHz -7.884 dBm Center 2.44000 GHz Res BW 2.0 MHz VBW 8.0 MHz Sweep 1.007 ms (8001 pos)
HCH	Center Freq 2.480000000 GHz Ref Offset 19.77 dB Ref 13.77 dBm Mkr1 2.480 244 GHz -7.298 dBm Center 2.48000 GHz Res BW 2.0 MHz VBW 8.0 MHz Sweep 1.007 ms (8001 pos)

Appendix C): Band-edge for RF Conducted Emissions

Result Table

Mode	Channel	Carrier Power[dBm]	Max.Spurious Level [dBm]	Limit [dBm]	Verdict
BLE	LCH	-9.263	-59.424	-29.26	PASS
BLE	HCH	-7.789	-58.938	-27.79	PASS

Test Graphs





Appendix D): RF Conducted Spurious Emissions


Result Table

Mode	Channel	Pref [dBm]	Puw[dBm]	Verdict
BLE	LCH	-9.297	<Limit	PASS
BLE	MCH	-8.353	<Limit	PASS
BLE	HCH	-7.843	<Limit	PASS

Test Graphs







Appendix E): Power Spectral Density

Result Table

Mode	Channel	PSD [dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE	LCH	-21.202	8	PASS
BLE	MCH	-19.610	8	PASS
BLE	HCH	-19.391	8	PASS

Test Graphs

Graphs	
LCH	Center Freq 2.40200000 GHz Mkr1 2.401 079 84 GHz -21.202 dBm Center 2.4020000 GHz Res BW 3.0 kHz Span 1.503 MHz Sweep 158.4 ms [8001 pos]
MCH	Center Freq 2.44000000 GHz Mkr1 2.439 853 94 GHz -19.610 dBm Center 2.4400000 GHz Res BW 3.0 kHz Span 1.503 MHz Sweep 158.4 ms [8001 pos]
HCH	Center Freq 2.48000000 GHz Mkr1 2.479 946 94 GHz -19.391 dBm Center 2.4800000 GHz Res BW 3.0 kHz Span 1.503 MHz Sweep 158.4 ms [8001 pos]

Appendix F): Antenna Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is PCB antenna and no consideration of replacement. The best case gain of the antenna is 0dBi.



Appendix G): AC Power Line Conducted Emission

Test frequency range :150KHz-30MHz																	
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room.																
	2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.																
	3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,																
	4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment were at least 0.8 m from the LISN 2.																
	5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.																
Limit:	<table><tr><td rowspan="2">Frequency range (MHz)</td><td colspan="2">Limit (dBμV)</td></tr><tr><td>Quasi-peak</td><td>Average</td></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table>			Frequency range (MHz)	Limit (dBμV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
	Frequency range (MHz)	Limit (dBμV)															
		Quasi-peak	Average														
	0.15-0.5	66 to 56*	56 to 46*														
	0.5-5	56	46														
5-30	60	50															
	* The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.																
	NOTE : The lower limit is applicable at the transition frequency																
Charging mode:	Charging the EUT through charger.																
Test Ambient:	Temp.: 23°C	Humid.: 59%	Press.: 101kPa														


Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live line:


100.0 dBuV



No.	Freq. MHz	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		peak	QP	AVG	QP	AVG	QP	AVG		
1	0.3660	33.72	27.01	20.80	9.93	43.65	36.94	30.73	58.59	48.59	-21.65	-17.86	P	
2	0.5181	33.18	18.23	15.75	9.92	43.10	28.15	25.67	56.00	46.00	-27.85	-20.33	P	
3	0.5700	33.10	31.29	27.76	10.00	43.10	41.29	37.76	56.00	46.00	-14.71	-8.24	P	
4	1.4420	29.08	20.23	17.10	9.77	38.85	30.00	26.87	56.00	46.00	-26.00	-19.13	P	
5	5.0700	32.38	20.27	21.08	9.73	42.11	30.00	30.81	60.00	50.00	-30.00	-19.19	P	
6	7.7460	33.12	26.03	19.08	9.77	42.89	35.80	28.85	60.00	50.00	-24.20	-21.15	P	

Neutral line:

100.0 dBuV



No.	Freq. MHz	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		peak	QP	AVG	QP	AVG	QP	AVG		
1	0.2500	26.24	19.61	9.85	9.96	36.20	29.57	19.81	61.75	51.75	-32.18	-31.94	P	
2	0.5020	30.19	27.06	22.58	9.89	40.08	36.95	32.47	56.00	46.00	-19.05	-13.53	P	
3	0.5700	31.16	28.72	24.52	10.00	41.16	38.72	34.52	56.00	46.00	-17.28	-11.48	P	
4	2.2180	24.16	17.54	14.73	9.72	33.88	27.26	24.45	56.00	46.00	-28.74	-21.55	P	
5	5.7740	28.69	23.70	18.85	9.73	38.42	33.43	28.58	60.00	50.00	-26.57	-21.42	P	
6	18.9300	22.98	15.83	8.39	9.92	32.90	25.75	18.31	60.00	50.00	-34.25	-31.69	P	

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.


Appendix H): Restricted bands around fundamental frequency (Radiated)

Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Test Procedure:	Below 1GHz test procedure as below: - The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. - Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel Above 1GHz test procedure as below: - Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre). . Test the EUT in the lowest channel , the Highest channel - The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case. - Repeat above procedures until all frequencies measured was complete.				
Limit:	Frequency	Limit (dBμV/m @3m)		Remark	
	30MHz-88MHz	40.0		Quasi-peak Value	
	88MHz-216MHz	43.5		Quasi-peak Value	
	216MHz-960MHz	46.0		Quasi-peak Value	
	960MHz-1GHz	54.0		Quasi-peak Value	
	Above 1GHz	54.0		Average Value	
		74.0		Peak Value	
Test Ambient:	Temp.: 24°C	Humid.: 53%		Press.: 101kPa	

Test plot as follows:

Mode:	BLE GFSK Transmitting	Channel:	2402
Remark:	Peak		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-42.44	50.48	53.66	74.00	20.34	Pass	Horizontal
2	2401.9086	32.26	13.31	-42.43	66.86	70.00	74.00	4.00	Pass	Horizontal

Mode:	BLE GFSK Transmitting	Channel:	2402
Remark:	Peak		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-42.44	49.86	53.04	74.00	20.96	Pass	Vertical
2	2402.2653	32.26	13.31	-42.43	64.12	67.26	74.00	6.74	Pass	Vertical

Mode:	BLE GFSK Transmitting	Channel:	2402
Remark:	AV		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-42.44	38.47	41.65	54.00	12.35	Pass	Horizontal
2	2401.9086	32.26	13.31	-42.43	63.00	66.14	54.00	-12.14	Pass	Horizontal

Mode:	BLE GFSK Transmitting	Channel:	2402
Remark:	AV		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2390.0000	32.25	13.37	-42.44	38.79	41.97	54.00	12.03	Pass	Vertical
2	2401.9086	32.26	13.31	-42.43	60.36	63.50	54.00	-9.50	Pass	Vertical

Mode:	BLE GFSK Transmitting	Channel:	2480
Remark:	Peak		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2480.2128	32.37	13.39	-42.40	67.69	71.05	74.00	2.95	Pass	Horizontal
2	2483.5000	32.38	13.38	-42.40	49.31	52.67	74.00	21.33	Pass	Horizontal

Mode:	BLE GFSK Transmitting	Channel:	2480
Remark:	Peak		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2480.3004	32.37	13.39	-42.40	63.98	67.34	74.00	6.66	Pass	Vertical
2	2483.5000	32.38	13.38	-42.40	49.76	53.12	74.00	20.88	Pass	Vertical

Mode:	BLE GFSK Transmitting	Channel:	2480
Remark:	AV		


Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2479.9937	32.37	13.39	-42.39	66.14	69.51	54.00	-15.51	Pass	Horizontal
2	2483.5000	32.38	13.38	-42.40	36.79	40.15	54.00	13.85	Pass	Horizontal

Mode:	BLE GFSK Transmitting	Channel:	2480
Remark:	AV		

Test Graph



NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity
1	2479.9499	32.37	13.39	-42.39	61.29	64.66	54.00	-10.66	Pass	Vertical
2	2483.5000	32.38	13.38	-42.40	36.77	40.13	54.00	13.87	Pass	Vertical

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading - Correct Factor

Correct Factor = Preamplifier Factor - Antenna Factor - Cable Factor

Appendix I): Radiated Spurious Emissions

Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Test Procedure:					
Below 1GHz test procedure as below:					
a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.					
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.					
c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.					
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.					
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.					
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.					
Above 1GHz test procedure as below:					
g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).					
h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel					
i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case.					
j. Repeat above procedures until all frequencies measured was complete.					
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBµV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
5011.9		74.0	peak	3	
Test Ambient:	Temp.: 24°C		Humid.: 53%		Press.: 101kPa

Radiated Spurious Emissions test Data:

Radiated Emission below 1GHz

Mode: GFSK Transmitting						Channel: 2480				
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Magin [dB]	Result	Polarity
1	37.5668	11.52	0.69	-32.12	34.37	14.46	40.00	25.54	Pass	Horizontal
2	77.5348	7.57	1.03	-32.07	42.16	18.69	40.00	21.31	Pass	Horizontal
3	168.0448	8.34	1.52	-31.96	42.74	20.64	43.50	22.86	Pass	Horizontal
4	256.0326	12.32	1.90	-31.88	45.70	28.04	46.00	17.96	Pass	Horizontal
5	319.9620	13.64	2.12	-31.83	42.53	26.46	46.00	19.54	Pass	Horizontal
6	600.0290	19.00	2.96	-31.99	38.51	28.48	46.00	17.52	Pass	Horizontal

Mode: GFSK Transmitting						Channel: 2480				
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Magin [dB]	Result	Polarity
1	30.3880	10.52	0.63	-32.12	39.39	18.42	40.00	21.58	Pass	Vertical
2	55.2225	12.36	0.84	-32.07	39.28	20.41	40.00	19.59	Pass	Vertical
3	208.8859	11.13	1.71	-31.94	45.99	26.89	43.50	16.61	Pass	Vertical
4	319.9620	13.64	2.12	-31.83	39.01	22.94	46.00	23.06	Pass	Vertical
5	600.0290	19.00	2.96	-31.99	37.57	27.54	46.00	18.46	Pass	Vertical
6	897.9458	22.08	3.60	-31.60	37.25	31.33	46.00	14.67	Pass	Vertical

Remark : All the channels are tested, only the worst data were reported.

Transmitter Emission above 1GHz

Mode:		GFSK Transmitting					Channel:		2402		
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1399.0399	28.30	2.90	-42.68	53.01	41.53	74.00	32.47	Pass	H	PK
2	1793.8794	30.34	3.31	-42.71	61.17	52.11	74.00	21.89	Pass	H	PK
3	4803.1202	34.50	4.55	-40.66	54.66	53.05	74.00	20.95	Pass	H	PK
4	4803.4226	34.50	4.55	-40.66	48.81	47.20	54.00	6.80	Pass	H	AV
5	7206.0000	36.31	5.81	-41.02	54.54	55.64	74.00	18.36	Pass	H	PK
6	7205.4987	36.31	5.82	-41.02	49.05	50.16	54.00	3.84	Pass	H	AV
7	9608.0000	37.64	6.63	-40.76	39.54	43.05	74.00	30.95	Pass	H	PK
8	12010.0000	39.31	7.60	-41.21	38.91	44.61	74.00	29.39	Pass	H	PK
9	1598.4598	29.05	3.07	-42.90	59.19	48.41	74.00	25.59	Pass	V	PK
10	3197.0131	33.28	4.65	-42.01	53.98	49.90	74.00	24.10	Pass	V	PK
11	4804.0000	34.50	4.55	-40.66	51.91	50.30	74.00	23.70	Pass	V	PK
12	7206.2804	36.31	5.81	-41.02	50.17	51.27	74.00	22.73	Pass	V	PK
13	7205.4707	36.31	5.82	-41.02	43.47	44.58	54.00	9.42	Pass	V	AV
14	9608.0000	37.64	6.63	-40.76	38.98	42.49	74.00	31.51	Pass	V	PK
15	12010.0000	39.31	7.60	-41.21	38.38	44.08	74.00	29.92	Pass	V	PK

Mode:		GFSK Transmitting					Channel:		2440		
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1895.4895	31.01	3.42	-42.67	52.81	44.57	74.00	29.43	Pass	H	PK
2	3109.0073	33.24	4.69	-42.05	50.55	46.43	74.00	27.57	Pass	H	PK
3	4879.1253	34.50	4.80	-40.60	54.92	53.62	74.00	20.38	Pass	H	PK
4	4879.4023	34.50	4.80	-40.60	48.38	47.08	54.00	6.92	Pass	H	AV
5	7320.2880	36.42	5.85	-40.92	52.69	54.04	74.00	19.96	Pass	H	PK
6	7319.6203	36.42	5.85	-40.92	48.23	49.58	54.00	4.42	Pass	H	AV
7	9608.0000	37.64	6.63	-40.76	39.20	42.71	74.00	31.29	Pass	H	PK
8	12010.0000	39.31	7.60	-41.21	36.63	42.33	74.00	31.67	Pass	H	PK
9	1293.8294	28.19	2.74	-42.79	56.37	44.51	74.00	29.49	Pass	V	PK
10	1598.8599	29.05	3.07	-42.90	59.12	48.34	74.00	25.66	Pass	V	PK
11	4880.0000	34.50	4.80	-40.60	53.12	51.82	74.00	22.18	Pass	V	PK
12	4879.3589	34.50	4.80	-40.60	44.37	43.07	54.00	10.93	Pass	V	AV
13	7320.0000	36.42	5.85	-40.92	48.24	49.59	74.00	24.41	Pass	V	PK
14	9760.0000	37.70	6.73	-40.62	38.37	42.18	74.00	31.82	Pass	V	PK
15	12200.0000	39.42	7.67	-41.17	35.99	41.91	74.00	32.09	Pass	V	PK

Mode:		GFSK Transmitting					Channel:		2480		
NO	Freq. [MHz]	Ant Factor [dB]	Cable loss [dB]	Pream gain [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1599.8600	29.06	3.07	-42.90	52.63	41.86	74.00	32.14	Pass	H	PK
2	2004.9005	31.71	3.48	-42.61	51.07	43.65	74.00	30.35	Pass	H	PK
3	4960.0000	34.50	4.82	-40.53	54.06	52.85	74.00	21.15	Pass	H	PK
4	4959.4183	34.50	4.82	-40.53	47.90	46.69	54.00	7.31	Pass	H	AV
5	7440.0000	36.54	5.85	-40.82	52.09	53.66	74.00	20.34	Pass	H	PK
6	7439.5096	36.54	5.85	-40.82	46.76	48.33	54.00	5.67	Pass	H	AV
7	9920.0000	37.77	6.79	-40.48	38.67	42.75	74.00	31.25	Pass	H	PK
8	12400.0000	39.54	7.86	-41.12	38.74	45.02	74.00	28.98	Pass	H	PK
9	1596.8597	29.04	3.07	-42.90	58.92	48.13	74.00	25.87	Pass	V	PK
10	3191.0127	33.28	4.64	-42.01	51.70	47.61	74.00	26.39	Pass	V	PK
11	4959.1306	34.50	4.82	-40.53	51.81	50.60	74.00	23.40	Pass	V	PK
12	7440.0000	36.54	5.85	-40.82	49.32	50.89	74.00	23.11	Pass	V	PK
13	9920.0000	37.77	6.79	-40.48	37.86	41.94	74.00	32.06	Pass	V	PK
14	12400.0000	39.54	7.86	-41.12	37.66	43.94	74.00	30.06	Pass	V	PK

Note:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading - Correct Factor

Correct Factor = Preamplifier Factor - Antenna Factor - Cable Factor

2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

PHOTOGRAPHS OF TEST SETUP

Test model No.: SA00528



Radiated spurious emission Test Setup-1(Below 30MHz)



Radiated spurious emission Test Setup-2(30MHz-1GHz)



Radiated spurious emission Test Setup-3(Above 1GHz)




Conducted Emissions Test Setup

PHOTOGRAPHS OF EUT Constructional Details

Test model No.: SA00528



View of Product-1



View of Product-2



View of Product-3



View of Product-4



View of Product-5



View of Product-6




View of Product-7




View of Product-8



View of Product-9



View of Product-10



View of Product-11



View of Product-12



View of Product-13



View of Product-14

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.