



REPORT No. : SZ15090025S14

RF EXPOSURE EVALUATION REPORT

APPLICANT : Testo Instruments (Shenzhen) Co., Ltd

PRODUCT NAME : testo 115i

MODEL NAME : testo 115i

TRADE NAME : testo

BRAND NAME : testo

FCC ID : 2ACVD-1115

STANDARD(S) : 47CFR 2.1093
KDB 447498 D01 General RF Exposure
Guidance v05r02

ISSUE DATE : 2019-11-17



SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB GROUP

FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555
Http://www.morlab.com

Fax: 86-755-36698525
E-mail: service@morlab.cn



DIRECTORY

TEST REPORT DECLARATION	3
1. TECHNICAL INFORMATION	4
1.1. IDENTIFICATION OF APPLICANT	4
1.2. IDENTIFICATION OF MANUFACTURER	4
1.3. EQUIPMENT UNDER TEST (EUT)	4
1.3.1. PHOTOGRAPHS OF THE EUT	5
1.3.2. IDENTIFICATION OF ALL USED EUT	6
1.4. APPLIED REFERENCE DOCUMENTS	6
2.DEVICE CATEGORY AND RF EXPOSURE LIMIT	7
3.MEASUREMENT OF CONDUCTED PEAK OUTPUT POWER	8
4. RF EXPOSURE EVALUATION	8
ANNEX A GENERAL INFORMATION	9

Change History		
Issue	Date	Reason for change
1.0	2015-11-17	First edition



REPORT No. : SZ15090025S14

TEST REPORT DECLARATION

Applicant	Testo Instruments (Shenzhen) Co., Ltd
Applicant Address	Block A, B4 Building, China Merchants Guangming Sci&Tech Park, No.3009 Guan Guang Road, Guangming New District, Shenzhen City
Manufacturer	Testo Instruments (Shenzhen) Co., Ltd
Manufacturer Address	Block A, B4 Building, China Merchants Guangming Sci&Tech Park, No.3009 Guan Guang Road, Guangming New District, Shenzhen City
Product Name	testo 115i
Model Name	testo 115i
Brand Name	testo
HW Version	V1.1
SW Version	V1.0
Test Standards	47CFR 2.1093; KDB 447498 D01 General RF Exposure Guidance v05r02
Issue Date	2015-11-17
SAR Evaluation	Not Required

Tested by : Liu Jun

Liu Jun

Reviewed by : Zhu Zhan

Zhu Zhan

Approved by : Zeng Dexin

Zeng Dexin



1. TECHNICAL INFORMATION

Note: the following data is based on the information by the applicant.

1.1. Identification of Applicant

Company Name:	Testo Instruments (Shenzhen) Co., Ltd
Address:	Block A, B4 Building, China Merchants Guangming Sci&Tech Park, No.3009 Guan Guang Road, Guangming New District, Shenzhen City

1.2. Identification of Manufacturer

Company Name:	Testo Instruments (Shenzhen) Co., Ltd
Address:	Block A, B4 Building, China Merchants Guangming Sci&Tech Park, No.3009 Guan Guang Road, Guangming New District, Shenzhen City

1.3. Equipment Under Test (EUT)

Model Name:	testo 115i
Serial Number	49400761
Trade Name:	testo
Brand Name:	testo
Hardware Version:	V1.1
Software Version:	V1.0
Frequency Bands:	Bluetooth 4.0:2402-2480MHz;
Modulation Mode:	Bluetooth 4.0: GFSK;
Antenna type:	Fixed Internal Antenna
Development Stage:	Identical prototype



REPORT No. : SZ15090025S14

1.3.1. Photographs of the EUT

1. EUT front view



2. EUT rear view





1.3.2. Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
1#	V1.1	V1.0

1.4. Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1	47 CFR§2.1093	Radiofrequency Radiation Exposure Evaluation: portable devices
2	KDB 447498 D01v05r02	General RF Exposure Guidance



2. DEVICE CATEGORY AND RF EXPOSURE LIMIT

Per user manual, this device is a Bluetooth device. Based on 47CFR 2.1093, this device belongs to portable device category with General Population/Uncontrolled exposure.

Portable Devices:

47CFR 2.1093(b)

For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

GENERAL POPULATION / UNCONTROLLED EXPOSURE

47CFR 2.1093(d) (2)

Limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 1.6 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 4 W/kg, as averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). General Population/Uncontrolled limits apply when the general public may be exposed, or when persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or do not exercise control over their exposure. Warning labels placed on consumer devices such as cellular telephones will not be sufficient reason to allow these devices to be evaluated subject to limits for occupational/controlled exposure in paragraph (d)(1) of this section.



3. MEASUREMENT OF CONDUCTED PEAK OUTPUT POWER

1. Bluetooth Average output power

Band	Channel	Frequency (MHz)	Output Power(dBm)
			GFSK
BT	0	2402	-0.73
	19	2440	-1.16
	39	2480	-1.58

4. RF EXPOSURE EVALUATION

The device only incorporates a Bluetooth transmitter, so standalone SAR evaluation is required for Bluetooth and simultaneous SAR is not required.

Standalone transmission SAR evaluation

According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation

Distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

The maximum tune-up limit power is **0.89mW @ 2.402GHz**

use **5mm** as the most conservative minimum test separation distance,

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] = 0.28 \leq 3.0$$

So SAR evaluation is not required for this device.



REPORT No. : SZ15090025S14

ANNEX A GENERAL INFORMATION

1. Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

***** END OF REPORT *****