

FCC PART 15 CLASS B
EMI MEASUREMENT AND TEST REPORT
For

Shuanghe Electron instrument Co.,Ltd.
Dayin Industrial Park Yuanqu Rd. 11#,Yuyao,Zhejiang,China

FCC ID:2ACVG-BXOBA

KN128BXOBA

This Report Concerns: Original Report	Equipment Type: KA GMT DIGITAL REMOTE THERMOMETER BLACK
Test Engineer:	Lisa Chen <i>Lisa Chen</i>
Report No.:	BSL20141230-2
Receive EUT Date/Test Date:	December 20, 2014 / December 20- December 30, 2014
Reviewed By:	<i>Sky Zhang</i> Sky Zhang
Prepared By:	BSL Testing Co.,LTD. NO. 24, ZH Park, Nantou, Shenzhen, 518000 China Tel: 86- 755-26508703 Fax: 86- 755-26508703

Note: The test report is specially limited to the above company and this particular sample only.
It may not be duplicated without prior written consent of BSL Testing Co.,LTD.
This report must not be used by the client to claim product certification,
approval,or endorsement by NVLAP, NIST or any agency of the US Government.

TABLE OF CONTENTS

1.	GENERAL INFORMATION	3
1.1.	Report information.....	3
2.	PRODUCT DESCRIPTION	4
2.1.	EUT Description	4
2.2.	Block Diagram of EUT Configuration	4
2.3.	Figure 1 EUT Setup Support Equipment List.....	4
2.4.	Test Conditions	5
2.5.	TEST Results SUMmary	5
3.	TEST EQUIPMENT USED	6
4.	CONDUCTED EMISSION TEST	7
4.1.	Block Diagram of Test Setup.....	7
4.2.	Test Standard	7
4.3.	Conducted Emission Limit(Class B)	8
4.4.	EUT Configuration on Test	8
4.5.	Operating Condition of EUT	8
4.6.	Test Procedure	8
4.7.	Test Result	8
5.	RADIATED EMISSION MEASUREMENT	9
5.1.	Block Diagram of EUT Configuration	9
5.2.	Test Standard	9
5.3.	Radiated Emission Limit(Class B)	10
5.4.	EUT Configuration on Test	10
5.5.	Operating Condition of EUT	10
5.6.	Test Procedure	11
5.7.	Test Result	11

1. GENERAL INFORMATION

1.1. Report information

- 1.1.1.This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that BSL approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that BSL in any way guarantees the later performance of the product/equipment.
- 1.1.2.The sample/s mentioned in this report is/are supplied by Applicant, BSL therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.
- 1.1.3.Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through BSL, unless the applicant has authorized BSL in writing to do so.

Test Facility -

The test site used to collect the radiated data is located on the address of BSL Testing Co.,LTD.

(FCC Registered Test Site Number: 191509) on

NO. 24, ZH Park, Nantou, Shenzhen, 518000 China

The Test Site is constructed and calibrated to meet the FCC requirements.

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	+/-1.25dB
2	RF Power, Conducted	+/-0.20dB
3	Spurious emissions, conducted	+/-0.33dB
4	All emissions, radiated (<1G)	+/-3.47dB
5	All emissions, radiated (>1G)	+/-3.82dB
6	Temperature	+/-0.5°CdB
7	Humidity	+/-2%

2. PRODUCT DESCRIPTION

2.1. EUT Description

Applicant : Shuanghe Electron instrument Co.,Ltd.
 Address : Dayin Industrial Park Yuanqu Rd. 11#,Yuyao,Zhejiang,China


 Manufacturer : Shuanghe Electron instrument Co.,Ltd.
 Address : Dayin Industrial Park Yuanqu Rd. 11#,Yuyao,Zhejiang,China

 EUT Description : KA GMT DIGITAL REMOTE THERMOMETER BLACK
 Trade Name : KitchenAid
 Model Number : KN128BXOBA
 Power Supply : DC 3V battery
 (The new battery is used during the measurement)
 the RX frequency : 434MHz

 modulation type : ASK

 the antenna type : Welding antenna

2.2. Block Diagram of EUT Configuration



2.3. Figure 1 EUT Setup Support Equipment List

Name	Model No	S/N	Manufacturer	Used (Y/N)
--	--	--	--	--

2.4. Test Conditions

Temperature: 23~27°C

Relative Humidity: 50~63 %

2.5. TEST Results Summary

Table 1 Test Results Summary

FCC Part 15B:2013	
Test Items	Test Results
Conducted disturbance	N/A
Radiated disturbance	Pass

Remark: “N/A” means “Not applicable.”

Note: It is powered by the battery, Conduction emission test is not applicable.


3. TEST EQUIPMENT USED

EQUIPMENT/FACILITIES	MANUFACTURER	MODEL	SERIAL NO.	DATE OF CAL.	CAL. INTERVAL
3m Semi-Anechoic Chamber	Chengyu Electron	9 (L)*6 (W)* 6 (H)	BSL086	Aug. 23 2014	1 Year
EMI Test Receiver	Rohde & Schwarz	ESCI3	BSL001	Sep. 28 2014	1 Year
BiConiLog Antenna	Rohde & Schwarz	HL562	BSL009	Sep. 28 2014	1 Year
Double -ridged waveguide horn	Rohde & Schwarz	9120D	BSL008	Aug. 27 2014	1 Year
Horn Antenna	ETS-LINDGREN	3160	BSL072	Dec. 28 2014	1 Year
Cable	Rohde & Schwarz	N/A	BSL045	Aug. 27 2014	1 Year
Cable	Rohde & Schwarz	N/A	BSL046	Aug. 27 2014	1 Year
Cable	Rohde & Schwarz	N/A	BSL047	Aug. 27 2014	1 Year
Amplifier(100kHz-40G Hz)	R&S	SMR40	BSL007	Sep. 28 2014	1 Year
Band filter	Amindeon	82346	BSL049	Aug. 27 2014	1 Year
Active Loop Antenna	EMTES	EM15	BSL011	Sep. 28 2014	1 Year
Power Meter	R&S	NRVS	BSL052	Aug. 3, 2014	1 Year
Power Sensor	R&S	NRV-Z33	BSL053	Aug. 3, 2014	1 Year


4. CONDUCTED EMISSION TEST

4.1. Block Diagram of Test Setup

4.1.1. Block Diagram of connection between the EUT and the simulators



4.1.2. Test Setup Diagram



4.2. Test Standard

FCC Part 15 CLASS B:2013

ANSI C63.4 2003

4.3. Conducted Emission Limit(Class B)

Frequency MHz	Limits dB(μ V)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*
0.50 ~ 5.00	56	46
5.00 ~ 30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.

4.4. EUT Configuration on Test

The following equipments are installed on conducted emission test to meet FCC Part 15 requirement and operating in a manner, which tends to maximize its emission characteristics in a normal application.

4.5. Operating Condition of EUT

4.5.1. Setup the EUT RX Mode.

4.6. Test Procedure

The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI test receiver is used to test the emissions form both sides of AC line. The bandwidth of EMI test receiver is set at 9kHz.

4.7. Test Result

Note: It is powered by the battery, Conduction emission test is not applicable.


5. RADIATED EMISSION MEASUREMENT

5.1. Block Diagram of EUT Configuration

5.1.1. Block Diagram of connection between the EUT and the simulators



5.1.2. Semi-anechoic Chamber Test Setup Diagram



5.2. Test Standard

FCC Part 15CLASS B: 2013
ANSI C63.4 2003

5.3. Radiated Emission Limit(Class B)

FREQUENCY (MHz)	DISTANCE (Meters)	FIELD STRENGTHS LIMITS (dB μ V/m)
30 ~ 88	3	40.0
88 ~ 216	3	43.5
216 ~ 960	3	46.0
Above 1000	3	54.0

Note:(1) The smaller limit shall apply at the edge between two frequency bands.

(2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the EUT or system.

5.4. EUT Configuration on Test

The following equipment are installed on Radiated Emission Measurement to meet the Commission requirements and operating regulations in a manner which tends to maximize Its emission characteristics in normal application.

5.5. Operating Condition of EUT

5.5.1.Setup the EUT RX Mode.

5.6. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Calibrated Loop antenna is used as receiving antenna for frequencies below 30MHz, Calibrated Bilog antenna is used as receiving antenna for frequencies between 30 MHz and 1 GHz, Calibrated Horn antenna is used as receiving antenna for frequencies above 1000MHz. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated emission measurement.

The bandwidth of test receiver is set at 9kHz in below 30MHz. and set at 120kHz in 30-1000MHz.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Peak detector and Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

5.7. Test Result

PASS

Test mode:receiving


For below 9kHz-30MHz Spurious

Freq. (MHz)	Emission(dBuV/m) AV/PK	Limits(dBuV/m) AV/PK	Margin (dB)
-	-	-	-
-	-	-	-

Note:

Emissions attenuated more than 20 dB below the permissible value are not reported.


Horizontal



Condition : FCC CLASS-B 3m HORIZONTAL
 : RBW:120.000KHz VBW:300.000KHz SWT:Auto

		Limit	Over		
	Freq	Line	Level	Limit	Remark
	MHz	dBuV/m	dBuV/m	dB	Pol/Phase
1	max	30.638	40.0	29.6	-10.4 QP
2		34.882	40.0	28.7	-11.3 QP
3		43.506	40.0	26.1	-13.9 QP
4		305.680	46.0	23.0	-23.0 QP
5		399.030	46.0	24.3	-21.7 QP
6		470.523	46.0	24.7	-21.3 QP
7		560.693	46.0	26.2	-19.8 QP
8		726.805	46.0	29.1	-16.9 QP
9		893.857	46.0	32.1	-13.9 QP
10		952.094	46.0	31.9	-14.1 QP

Vertical



Condition : FCC CLASS-B 3m VERTICAL
 : RBW:120.000KHz VBW:300.000KHz SWT:Auto

	Freq	Limit	Level	Over	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB		
1 max	30.853	40.0	29.3	-10.7	QP	VERTICAL
2	34.037	40.0	29.0	-11.0	QP	VERTICAL
3	36.127	40.0	27.9	-12.1	QP	VERTICAL
4	41.860	40.0	26.8	-13.2	QP	VERTICAL
5	51.301	40.0	23.4	-16.6	QP	VERTICAL
6	640.611	46.0	28.0	-18.0	QP	VERTICAL
7	721.726	46.0	28.2	-17.8	QP	VERTICAL
8	836.244	46.0	30.2	-15.8	QP	VERTICAL
9	968.934	54.0	30.6	-23.4	QP	VERTICAL

Above 1GHz

Frequency (MHz)	Receiver		Turn table Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBuV/m)	FCC Part 15.109	
	Reading (dBuV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H / V)			Limit (dBuV/m)	Margin (dB)
1350	22.86	Ave.	166	2.47	V	9.19	32.05	54	21.95
2136	24.42	Ave.	100	2.32	V	1.88	26.3	54	27.7
2759	26.86	Ave.	23	3.14	V	3.8	30.66	54	23.34
3963	25.63	Ave.	27	3.38	V	10.46	36.09	54	17.91
4676	23.77	Ave.	123	3.45	V	15.87	39.64	54	14.36
5358	25.12	Ave.	13	3.57	V	17.24	42.36	54	11.64
1350	40.56	PK	166	2.47	V	9.19	49.75	74	24.25
2136	39.62	PK	23	2.32	V	1.88	41.5	74	32.5
2759	43.6	PK	100	3.4	V	3.8	47.4	74	26.6
3963	42.66	PK	27	3.38	V	10.46	53.12	74	20.88
4676	41.23	PK	123	3.45	V	15.87	57.1	74	16.9
5358	41.13	PK	13	3.57	V	17.24	58.37	74	15.63
1350	25.11	Ave.	166	2.49	H	9.21	34.32	54	19.68
2136	26.72	Ave.	100	2.76	H	2.49	29.21	54	24.79
2759	26.99	Ave.	23	3.24	H	6.25	33.24	54	20.76
3963	25.73	Ave.	27	3.69	H	11.58	37.31	54	16.69
4676	26.93	Ave.	123	3.82	H	17.01	43.94	54	10.06
5358	24.84	Ave.	13	3.3	H	18.45	43.29	54	10.71
1350	41.66	PK	166	2.4	H	9.21	50.87	74	23.13
2136	44.73	PK	23	2.7	H	2.49	47.22	74	26.78
2759	46.84	PK	100	3.4	H	6.25	53.09	74	20.91
3963	44.77	PK	27	3.9	H	11.58	56.35	74	17.65
4676	43.58	PK	123	3.2	H	17.01	60.59	74	13.41
5358	44.66	PK	13	34.3	H	18.45	63.11	74	10.89

***** END OF REPORT *****