

FCC 47 CFR MPE REPORT

Shenyang Tongfang Multimedia Technology Co., Limited

LED TV, 40inch 1080P Smart TV, 40inch WIDESCREEN LED TV

Model Number: NP4P0

Additional Model: WD40FBR101, E2SW3918, T395TAA4BFT,

T39*****, WD*****, NP*****, EL*****

maybe followed by 9 character, * can be A-Z, 0-9 or “-“ or blank

FCC ID: 2ACWIT395TAA4

Prepared for:	Shenyang Tongfang Multimedia Technology Co., Limited
	No. 10 Nanping East Road HunNan New District Shenyang, LiaoNing
	Province P.R. China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R1906087
Date of Test:	Jun. 21~24, 2019
Date of Report:	Jun. 25, 2019



Maximum Permissible Exposure

1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)、Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3、Conducted Power Result

3.1 Antenna a

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	15.92	39.084	15 ± 2	1.21	1.321
	2437	15.69	37.068	15 ± 2	1.21	1.321
	2462	16.50	44.668	16 ± 2	1.21	1.321
IEEE 802.11g	2412	12.16	16.444	12 ± 2	1.21	1.321
	2437	12.19	16.558	12 ± 2	1.21	1.321
	2462	12.11	16.255	12 ± 2	1.21	1.321
IEEE 802.11n HT20	2412	12.34	17.140	12 ± 2	1.21	1.321
	2437	11.43	13.900	11 ± 2	1.21	1.321
	2462	11.85	15.311	11 ± 2	1.21	1.321
IEEE 802.11n HT40	2422	9.74	9.419	9 ± 2	1.21	1.321
	2437	9.38	8.670	9 ± 2	1.21	1.321
	2452	9.74	9.419	9 ± 2	1.21	1.321

3.2 Antenna b

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	16.58	45.499	16 ± 2	1.21	1.321
	2437	16.56	45.290	16 ± 2	1.21	1.321
	2462	16.63	46.026	16 ± 2	1.21	1.321
IEEE 802.11g	2412	12.66	18.450	12 ± 2	1.21	1.321
	2437	13.08	20.324	13 ± 2	1.21	1.321
	2462	12.22	16.672	12 ± 2	1.21	1.321
IEEE 802.11n HT20	2412	13.14	20.606	13 ± 2	1.21	1.321
	2437	12.76	18.880	12 ± 2	1.21	1.321
	2462	12.21	16.634	12 ± 2	1.21	1.321
IEEE 802.11n HT40	2422	10.48	11.169	10 ± 2	1.21	1.321
	2437	9.95	9.886	9 ± 2	1.21	1.321
	2452	10.37	10.889	10 ± 2	1.21	1.321

4、Calculated Result and Limit

4.1 Antenna a

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
IEEE 802.11b	18	1.21	1.321	0.01659	1	Compiles
IEEE 802.11g	14	1.21	1.321	0.00660	1	Compiles
IEEE 802.11n HT20	14	1.21	1.321	0.00660	1	Compiles
IEEE 802.11n HT40	11	1.21	1.321	0.00331	1	Compiles

4.2 Antenna b

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
IEEE 802.11b	18	1.21	1.321	0.01659	1	Compiles
IEEE 802.11g	15	1.21	1.321	0.00831	1	Compiles
IEEE 802.11n HT20	15	1.21	1.321	0.00831	1	Compiles
IEEE 802.11n HT40	12	1.21	1.321	0.00417	1	Compiles

4.3 Antenna a+b

Mode	Power Density (S) (mW/cm ²) Antenna a	Power Density (S) (mW/cm ²) Antenna b	Power Density (S) (mW/cm ²) Total	Limited of Power Density (S) (mW/cm ²)	Test Result
2.4G Band					
IEEE 802.11n HT20	0.00660	0.00831	0.01491	1	Compiles
IEEE 802.11n HT40	0.00331	0.00417	0.00748	1	Compiles