

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

LED TV

Model No.: WD50FBE1001, 8502811, EL, WD50

FCC ID: 2ACWIWD50FBE10

Trademark: THTF, Fluid, Westinghouse, Seiki, Element, ONN

Report No.: ED170511031E

Issue Date: May 18, 2017

Prepared for

**Shenyang Tongfang Multimedia Technology Co., Limited
No.10 Nanping East Road HunNan New District Shenyang, LiaoNing
Province P.R .China**

Prepared by

**EMTEK(DONGGUAN) CO., LTD.
No.281, Guantai Road, Nancheng District,
Dongguan, Guangdong, China
TEL: 86-769-22807078
FAX: 86-769-22807079**

**This report shall not be reproduced, except in full, without the written approval of
EMTEK(DONGGUAN) CO., LTD.**

VERIFICATION OF COMPLIANCE

Applicant:	Shenyang Tongfang Multimedia Technology Co., Limited No.10 Nanping East Road Hunnan New District Shenyang, Liaoning Province P.R .China
Manufacturer:	Shenyang Tongfang Multimedia Technology Co., Limited No.10 Nanping East Road Hunnan New District Shenyang, Liaoning Province P.R .China
Product Description:	LED TV
Model Number:	WD50FBE1001, 8502811, EL, WD50

We hereby certify that:

The above equipment was tested by EMTEK(DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247(2016).

Date of Test :

May 11, 2017 to May 15, 2017

Abby Li

Prepared by :

Abby Li/Editor

Tomas Yang

Reviewer :

Tomas Yang/Supervisor

Sam Lv

Approved & Authorized
Signer :

Sam Lv/Manager

Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Report	/	ED170511031E

Table of Contents

1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION	6
2. SYSTEM TEST CONFIGURATION	7
2.1 EUT CONFIGURATION	7
2.2 EUT EXERCISE	7
2.3 TEST PROCEDURE	7
2.4 CONFIGURATION OF TESTED SYSTEM	7
3. DESCRIPTION OF TEST MODES.....	9
4. SUMMARY OF TEST RESULTS.....	10
5. TEST FACILITY.....	11
6. CONDUCTED EMISSIONS TEST	12
6.1 MEASUREMENT PROCEDURE	12
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	12
6.3 MEASUREMENT EQUIPMENT USED	12
6.4 CONDUCTED EMISSION LIMIT	12
6.5 MEASUREMENT RESULT	12
7. RADIATED EMISSION TEST.....	19
7.1 MEASUREMENT PROCEDURE	19
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	20
7.3 MEASUREMENT EQUIPMENT USED	21
7.4 RADIATED EMISSION LIMIT	22
7.5 MEASUREMENT RESULT	23
8. 6DB BANDWIDTH TEST	32
8.1 MEASUREMENT PROCEDURE	32
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	32
8.3 MEASUREMENT EQUIPMENT USED	32
8.4 MEASUREMENT RESULTS	32
9. MAXIMUM PEAK OUTPUT POWER TEST	41
9.1 MEASUREMENT PROCEDURE	41
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	41
9.3 MEASUREMENT EQUIPMENT USED	41
9.4 PEAK POWER OUTPUT LIMIT	41
9.5 MEASUREMENT RESULTS	41
10. BAND EDGE TEST	42
10.1 MEASUREMENT PROCEDURE	42
10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	43
10.3 MEASUREMENT EQUIPMENT USED	43
10.4 MEASUREMENT RESULTS	43
11. POWER DENSITY	49
11.1 TEST EQUIPMENT	49
11.2 MEASURING INSTRUMENTS AND SETTING.....	49
11.3 TEST PROCEDURES	49
11.4 BLOCK DIAGRAM OF TEST SETUP	49
11.5 LIMIT.....	49
11.6 TEST RESULT	50

12.	ANTENNA PORT EMISSION.....	58
12.1	TEST EQUIPMENT	58
12.2	MEASURING INSTRUMENTS AND SETTING.....	58
12.3	TEST PROCEDURES.....	58
12.4	BLOCK DIAGRAM OF TEST SETUP	58
12.5	TEST RESULT	58
13.	ANTENNA APPLICATION	65
13.1	ANTENNA REQUIREMENT	65
13.2	RESULT.....	65

APPENDIX I (PHOTOS OF EUT)(3 PAGES)

1. General Information

1.1 Product Description

Characteristics	Description
Product Name	LED TV
Model number	WD50FBE1001
Power Supply	AC 100V-240V, 50/60Hz, 80W
Modulation	802.11b: DSSS(DBPSK/DQPSK/CCK) 802.11g/n: OFDM(BPSK/QPSK/16QAM/64QAM)
Operating Frequency Range	2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11n(HT40)
Number of Channels	11 for 20MHz bandwidth; 7 for 40MHz bandwidth
Transmit Power Max	802.11b: 13.96dBm 802.11g: 9.92dBm 802.11n(HT20): 9.06dBm 802.11n(HT40): 6.12dBm
Antenna Type	Internal antenna
Antenna Gain	2.0dBi

Note: for more details, please refer to the User's manual of the EUT.

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. Emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Item	Equipment	Trademark	Model No.	FCC ID	Note
1.	LED TV	THTF, Fluid, Westinghouse, Seiki, Element, ONN	WD50FBE1001	2ACWIWD50FBE10	EUT

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column, device(s) used in tested system is a support equipment.

3. Description of Test Modes

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; 802.11n (HT40): MCS8) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for 802.11 b/g/n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Frequency and Channel list for 802.11 n (HT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	8	2447
4	2427	6	2437	9	2452
		7	2442		

Test Frequency and Channel for 802.11 b/g/n (HT20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462

Test Frequency and channel for 802.11 n (HT40):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	6	2437	9	2452

4. Summary of Test Results

FCC Rules	Description Of Test	Result
§15.247(a)(2)	6dB bandwidth	Pass
§15.247(b)(3)	Max Peak output Power test	Pass
§15.247(e)	Power density	Pass
§15.247(d)	Band edge test	Pass
§15.207	AC Power Conducted Emission	Pass
§15.247(d), §15.209	Radiated Emission	Pass
§15.247(d)	Antenna Port Emission	Pass
§15.247(b)&§15.203	Antenna Application	Pass

5. Test Facility

Site Description

EMC Lab : Registered on FCC, July 06, 2016
The Certificate Number is 247565.

Registered on Industry Canada, January 13, 2017
The Certificate Number is 9444A


Name of Firm : EMTEK(DONGGUAN) CO., LTD.
Site Location : No.281, Guantai Road, Nancheng District,
Dongguan, Guangdong, China

6. Conducted Emissions Test

6.1 Measurement Procedure

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 Measurement Equipment Used

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Last Cal.	Due date
Test Receiver	Rohde & Schwarz	ESCS30	100018	05/16/2017	05/15/2018
L.I.S.N	Rohde & Schwarz	ENV216	100017	05/16/2017	05/15/2018
RF Switching Unit	CDS	RSU-M2	38401	05/16/2017	05/15/2018
Coaxial Cable	CDS	79254	46107086	05/16/2017	05/15/2018

6.4 Conducted Emission Limit


Conducted Emission Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

6.5 Measurement Result

Conducted emission at both 120V & 240V is assessed, and emission at 120V represents


the worst case. All the modulation modes were tested the data of the worst mode (TX 802.11b) are recorded in the following pages and the others modulation methods do not exceed the limits. Please refer to following pages.



Site site #1 Phase: **L1** Temperature: 24
 Limit: (CE)FCC PART 15C_QP Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX2412
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1900	48.35	10.02	58.37	64.04	-5.67	QP	
2		0.1900	30.60	10.02	40.62	54.04	-13.42	AVG	
3		0.3060	37.93	10.05	47.98	60.08	-12.10	QP	
4		0.3060	29.09	10.05	39.14	50.08	-10.94	AVG	
5		0.6020	25.59	10.10	35.69	56.00	-20.31	QP	
6		0.6020	22.85	10.10	32.95	46.00	-13.05	AVG	
7		0.9220	24.49	10.10	34.59	56.00	-21.41	QP	
8		0.9220	19.52	10.10	29.62	46.00	-16.38	AVG	
9		1.5380	25.31	10.10	35.41	56.00	-20.59	QP	
10		1.5380	16.06	10.10	26.16	46.00	-19.84	AVG	
11		23.2420	23.44	10.45	33.89	60.00	-26.11	QP	
12		23.2420	15.42	10.45	25.87	50.00	-24.13	AVG	


*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Aspen



Site site #1 Phase: **N** Temperature: 24
 Limit: (CE)FCC PART 15C_QP Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX2412
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1900	47.51	10.02	57.53	64.04	-6.51	QP	
2		0.1900	32.07	10.02	42.09	54.04	-11.95	AVG	
3		0.3100	37.90	10.05	47.95	59.97	-12.02	QP	
4		0.3100	29.43	10.05	39.48	49.97	-10.49	AVG	
5		0.6020	27.92	10.10	38.02	56.00	-17.98	QP	
6		0.6020	22.53	10.10	32.63	46.00	-13.37	AVG	
7		0.9260	28.25	10.10	38.35	56.00	-17.65	QP	
8		0.9260	19.60	10.10	29.70	46.00	-16.30	AVG	
9		4.8180	22.34	10.10	32.44	56.00	-23.56	QP	
10		4.8180	12.71	10.10	22.81	46.00	-23.19	AVG	
11		23.2740	23.68	10.45	34.13	60.00	-25.87	QP	
12		23.2740	14.48	10.45	24.93	50.00	-25.07	AVG	

*:Maximum data x:Over limit l:over margin Comment: Factor build in receiver. Operator: Aspen




Site site #1
 Limit: (CE)FCC PART 15C_QP
 Mode: TX2437
 Note:

Phase: **L1**
 Power: AC 120V/60Hz
 Temperature: 24
 Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1900	46.80	10.02	56.82	64.04	-7.22	QP	
2		0.1900	30.89	10.02	40.91	54.04	-13.13	AVG	
3		0.3100	37.09	10.05	47.14	59.97	-12.83	QP	
4		0.3100	29.35	10.05	39.40	49.97	-10.57	AVG	
5		0.6020	26.22	10.10	36.32	56.00	-19.68	QP	
6		0.6020	22.61	10.10	32.71	46.00	-13.29	AVG	
7		0.9260	25.88	10.10	35.98	56.00	-20.02	QP	
8		0.9260	19.69	10.10	29.79	46.00	-16.21	AVG	
9		4.9020	22.49	10.10	32.59	56.00	-23.41	QP	
10		4.9020	12.33	10.10	22.43	46.00	-23.57	AVG	
11		24.3940	24.34	10.47	34.81	60.00	-25.19	QP	
12		24.3940	15.61	10.47	26.08	50.00	-23.92	AVG	


*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Aspen



Site site #1 Phase: **N** Temperature: 24
 Limit: (CE)FCC PART 15C_QP Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX2437
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1900	47.72	10.02	57.74	64.04	-6.30	QP	
2		0.1900	32.03	10.02	42.05	54.04	-11.99	AVG	
3		0.3100	37.65	10.05	47.70	59.97	-12.27	QP	
4		0.3100	29.18	10.05	39.23	49.97	-10.74	AVG	
5		0.6060	28.89	10.10	38.99	56.00	-17.01	QP	
6		0.6060	22.35	10.10	32.45	46.00	-13.55	AVG	
7		0.9260	28.81	10.10	38.91	56.00	-17.09	QP	
8		0.9260	20.06	10.10	30.16	46.00	-15.84	AVG	
9		4.6260	21.91	10.10	32.01	56.00	-23.99	QP	
10		4.6260	12.97	10.10	23.07	46.00	-22.93	AVG	
11		22.9580	24.11	10.44	34.55	60.00	-25.45	QP	
12		22.9580	15.20	10.44	25.64	50.00	-24.36	AVG	


*:Maximum data x:Over limit l:over margin Comment: Factor build in receiver. Operator: Aspen



Site site #1 Phase: **L1** Temperature: 24
 Limit: (CE)FCC PART 15C_QP Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX2462
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1900	47.82	10.02	57.84	64.04	-6.20	QP	
2		0.1900	30.38	10.02	40.40	54.04	-13.64	AVG	
3		0.3100	36.86	10.05	46.91	59.97	-13.06	QP	
4		0.3100	29.38	10.05	39.43	49.97	-10.54	AVG	
5		0.6060	27.59	10.10	37.69	56.00	-18.31	QP	
6		0.6060	22.40	10.10	32.50	46.00	-13.50	AVG	
7		0.9300	25.46	10.10	35.56	56.00	-20.44	QP	
8		0.9300	19.75	10.10	29.85	46.00	-16.15	AVG	
9		4.9460	22.65	10.10	32.75	56.00	-23.25	QP	
10		4.9460	12.46	10.10	22.56	46.00	-23.44	AVG	
11		23.0020	25.16	10.45	35.61	60.00	-24.39	QP	
12		23.0020	15.94	10.45	26.39	50.00	-23.61	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Aspen



Site site #1
 Limit: (CE)FCC PART 15C_QP
 Mode: TX2462
 Note:

Phase: **N**
 Power: AC 120V/60Hz

Temperature: 24
 Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1900	46.91	10.02	56.93	64.04	-7.11	QP	
2		0.1900	30.53	10.02	40.55	54.04	-13.49	AVG	
3		0.3100	37.37	10.05	47.42	59.97	-12.55	QP	
4		0.3100	30.13	10.05	40.18	49.97	-9.79	AVG	
5		0.6020	28.72	10.10	38.82	56.00	-17.18	QP	
6		0.6020	22.10	10.10	32.20	46.00	-13.80	AVG	
7		0.9260	28.17	10.10	38.27	56.00	-17.73	QP	
8		0.9260	19.85	10.10	29.95	46.00	-16.05	AVG	
9		4.8300	21.20	10.10	31.30	56.00	-24.70	QP	
10		4.8300	13.13	10.10	23.23	46.00	-22.77	AVG	
11		24.3940	24.00	10.47	34.47	60.00	-25.53	QP	
12		24.3940	15.46	10.47	25.93	50.00	-24.07	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Aspen

7. Radiated Emission Test

7.1 Measurement Procedure

1. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane, And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured was complete.

When spectrum scanned from 30MHz to 1GHz setting resolution bandwidth 120KHz and video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	120KHz
VB	300KHz
Detector	QP
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	AVG
Trace	Max hold

7.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



7.3 Measurement Equipment Used

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCI	1166.5950.03	05/16/2017	1 Year
2.	Bilog Antenna	Schwarzbeck	VULB9163	000141	05/16/2017	1 Year
3.	Power Amplifier	CDS	RSU-M352	818	05/16/2017	1 Year
4.	Power Amplifier	HP	8447F	OPT H64	05/16/2017	1 Year
5.	Color Monitor	SUNSPO	SP-140A	N/A	05/16/2017	1 Year
6.	Single Line Filter	JIANLI	XL-3	N/A	05/16/2017	1 Year
7.	Single Phase Power Line Filter	JIANLI	DL-2X100B	N/A	05/16/2017	1 Year
8.	3 Phase Power Line Filter	JIANLI	DL-4X100B	N/A	05/16/2017	1 Year
9.	DC Power Filter	JIANLI	DL-2X50B	N/A	05/16/2017	1 Year
10.	Cable	Schwarzbeck	PLF-100	549489	05/16/2017	1 Year
11.	Cable	Rosenberger	CIL02	A0783566	05/16/2017	1 Year
12.	Cable	Rosenberger	RG 233/U	525178	05/16/2017	1 Year
13.	Signal Analyzer	Rohde & Schwarz	FSV30	103040	05/16/2017	1 Year
14.	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1272	05/16/2017	1 Year
15.	Power Amplifier	LUNAR EM	LNA1G18-40	J10100000081	05/16/2017	1 Year
16.	Cable	H+S	CBL-26	N/A	05/16/2017	1 Year
17.	Cable	H+S	CBL-26	N/A	05/16/2017	1 Year
18.	Cable	H+S	CBL-26	N/A	05/16/2017	1 Year

7.4 Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

Remark 1. Emission level in dBuV/m=20 log (uV/m)

- :
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
 3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of § 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

7.5 Measurement Result

Below 30MHz:

All the modulation modes were tested the data of the test mode are recorded in the following pages.

Operation Mode:	TX Mode	Test Date :	May 15, 2017
Frequency Range:	9KHz~30MHz	Temperature :	28°C
Test Result:	PASS	Humidity :	60 %
Measured Distance:	3m	Test By:	WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.


Distance extrapolation factor = $40 \log(\text{Specific distance} / \text{test distance})$ (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor.

Below 1000MHz:

Radiated emission at both 120V & 240V is assessed, and emission at 120V represents the worst case. All the modulation modes were tested the data of the worst mode (TX 802.11b) are recorded in the following pages and the others modulation methods do not exceed the limits.


Please refer to the following test plots:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		73.6500	48.15	-22.16	25.99	40.00	-14.01	QP		
2	*	151.2500	56.35	-18.70	37.65	43.50	-5.85	QP		
3		291.9000	47.56	-15.79	31.77	46.00	-14.23	QP		
4		528.5800	48.13	-9.73	38.40	46.00	-7.60	QP		
5		729.3700	39.50	-5.80	33.70	46.00	-12.30	QP		
6		832.1900	36.58	-4.58	32.00	46.00	-14.00	QP		

*:Maximum data x:Over limit !:over margin


Operator: washington



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		33.8800	43.65	-14.18	29.47	40.00	-10.53	QP		
2		151.2500	52.16	-18.70	33.46	43.50	-10.04	QP		
3		242.4300	47.35	-16.71	30.64	46.00	-15.36	QP		
4		304.5100	49.35	-15.12	34.23	46.00	-11.77	QP		
5	*	528.5800	48.60	-9.73	38.87	46.00	-7.13	QP		
6		806.9700	37.52	-4.79	32.73	46.00	-13.27	QP		

*:Maximum data x:Over limit !:over margin


Operator: washington



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		73.6500	47.85	-22.16	25.69	40.00	-14.31	QP		
2	*	151.2500	54.25	-18.70	35.55	43.50	-7.95	QP		
3		290.9300	45.35	-15.81	29.54	46.00	-16.46	QP		
4		530.5200	47.35	-9.66	37.69	46.00	-8.31	QP		
5		729.3700	38.23	-5.80	32.43	46.00	-13.57	QP		
6		832.1900	35.16	-4.58	30.58	46.00	-15.42	QP		

*:Maximum data x:Over limit !:over margin


Operator: washington



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		33.8800	43.58	-14.18	29.40	40.00	-10.60	QP		
2		150.2800	51.89	-18.62	33.27	43.50	-10.23	QP		
3		241.4600	47.55	-16.72	30.83	46.00	-15.17	QP		
4		321.0000	45.13	-14.05	31.08	46.00	-14.92	QP		
5	*	528.5800	46.87	-9.73	37.14	46.00	-8.86	QP		
6		833.1600	36.55	-4.47	32.08	46.00	-13.92	QP		

*:Maximum data x:Over limit !:over margin


Operator: washington



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		73.6500	49.65	-22.16	27.49	40.00	-12.51	QP		
2	*	151.2500	54.56	-18.70	35.86	43.50	-7.64	QP		
3		292.8700	45.85	-15.79	30.06	46.00	-15.94	QP		
4		541.1900	45.33	-9.27	36.06	46.00	-9.94	QP		
5		671.1700	38.16	-7.41	30.75	46.00	-15.25	QP		
6		802.1200	37.58	-4.46	33.12	46.00	-12.88	QP		

*:Maximum data x:Over limit !:over margin

Operator: washington



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		33.8800	42.35	-14.18	28.17	40.00	-11.83	QP		
2		93.0500	48.11	-21.07	27.04	43.50	-16.46	QP		
3		151.2500	51.59	-18.70	32.89	43.50	-10.61	QP		
4		322.9400	45.12	-14.04	31.08	46.00	-14.92	QP		
5	*	528.5800	47.65	-9.73	37.92	46.00	-8.08	QP		
6		832.1900	36.85	-4.46	32.39	46.00	-13.61	QP		

*:Maximum data x:Over limit !:over margin

Operator: washington

Above 1GHz:

Operation Mode: 802.11b Lowest
Test Voltage: AC 120V/60Hz

Test Date : May 15, 2017
Test by: Andy

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4824	V	64.06	44.06	74	54	-9.94	-9.94
7236	V	63.21	43.12	74	54	-10.79	-10.88
9648	V	62.95	42.94	74	54	-11.05	-11.06
12060	V	61.25	41.85	74	54	-12.75	-12.15
14472	V	60.28	40.36	74	54	-13.72	-13.64
16884	V	59.42	39.42	74	54	-14.58	-14.58
4824	H	63.22	43.12	74	54	-10.78	-10.88
7236	H	62.94	42.65	74	54	-11.06	-11.35
9648	H	61.41	41.95	74	54	-12.59	-12.05
12060	H	60.62	40.21	74	54	-13.38	-13.79
14472	H	59.42	39.12	74	54	-14.58	-14.88
16884	H	58.62	38.65	74	54	-15.38	-15.35

Operation Mode: 802.11b Middle
Test Voltage: AC 120V/60Hz

Test Date : May 15, 2017
Test by: Andy

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4824	V	63.06	43.15	74	54	-10.94	-10.85
7236	V	62.14	42.65	74	54	-11.86	-11.35
9648	V	61.39	41.95	74	54	-12.61	-12.05
12060	V	60.53	40.18	74	54	-13.47	-13.82
14472	V	59.42	39.62	74	54	-14.58	-14.38
16884	V	58.41	38.42	74	54	-15.59	-15.58
4824	H	64.28	44.69	74	54	-9.72	-9.31
7236	H	63.41	43.25	74	54	-10.59	-10.75
9648	H	62.95	42.65	74	54	-11.05	-11.35
12060	H	61.42	41.24	74	54	-12.58	-12.76
14472	H	60.36	40.32	74	54	-13.64	-13.68
16884	H	59.42	39.42	74	54	-14.58	-14.58

Operation Mode: 802.11b Highest

Test Date : May 15, 2017

Test Voltage: AC 120V/60Hz

Test by: Andy

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4824	V	65.06	45.95	74	54	-8.94	-8.05
7236	V	64.12	44.18	74	54	-9.88	-9.82
9648	V	63.25	43.62	74	54	-10.75	-10.38
12060	V	62.95	42.65	74	54	-11.05	-11.35
14472	V	61.48	41.29	74	54	-12.52	-12.71
16884	V	60.29	40.29	74	54	-13.71	-13.71
4824	H	64.12	44.65	74	54	-9.88	-9.35
7236	H	63.95	43.18	74	54	-10.05	-10.82
9648	H	62.19	42.15	74	54	-11.81	-11.85
12060	H	61.42	41.66	74	54	-12.58	-12.34
14472	H	60.62	40.28	74	54	-13.38	-13.72
16884	H	59.42	39.45	74	54	-14.58	-14.55

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

No others harmonics emissions are higher than 20 dB below the limits of 47 CFR Part 15.247.

Note: (1) All Readings are Peak Value and AV.
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 (3) Data of measurement within this frequency range shown “ – ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


8. 6dB Bandwidth Test

8.1 Measurement Procedure

The EUT was operating in IEEE 802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40) mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

1. Set resolution bandwidth (RBW) = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequency) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	FSV30	1321.3008K	05/16/2017	05/15/2018

8.4 Measurement Results


6 Bandwidth Test Data Chart:



Refer to attached data chart.

Spectrum Detector: PK
Test By: Andy
Humidity : 60%


Test Date : May 16, 2017
Temperature : 28°C



IEEE 802.11b			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
2412	10059	>500	Pass
2437	10058	>500	
2462	10067	>500	








IEEE 802.11g			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
2412	16481	>500	Pass
2437	16462	>500	
2462	16459	>500	








IEEE 802.11n(HT20)			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
2412	17609	>500	Pass
2437	17593	>500	
2462	17623	>500	





IEEE 802.11n (HT40)			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
2422	36423	>500	Pass
2437	36376	>500	
2452	36361	>500	





9. Maximum Peak Output Power Test

9.1 Measurement Procedure

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

9.2 Test SET-UP (Block Diagram of Configuration)



9.3 Measurement Equipment Used

EQUIPMENT TYPE	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Power meter	ML2495A	0824006	05/16/2017	05/15/2018
Power sensor	MA2411B	0738172	05/16/2017	05/15/2018

9.4 Peak Power output limit

The maximum peak power shall be less 1Watt.

9.5 Measurement Results

Spectrum Detector:	PK	Test Date :	May 16, 2017
Test By:	Andy	Temperature :	28°C
Test Result:	PASS	Humidity :	60%

Test Channel	Peak Output Power (dBm)				Limit(dBm)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	13.96	9.92	9.06	6.12	30	Pass
Middle	13.81	9.84	8.64	5.86		
Highest	12.12	9.14	8.32	5.64		

10. Band Edge Test

10.1 Measurement Procedure

For Conducted Test

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. Measure and record the results in the test report.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

For Radiated emission Test

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Repeat above procedures until all frequency measured were complete.


When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz.

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz.

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	AVG
Trace	Max hold

10.2 Test SET-UP (Block Diagram of Configuration)



10.3 Measurement Equipment Used



EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	FSV30	1321.3008K	05/16/2017	05/15/2018

10.4 Measurement Results



1. Conducted Test

Please refer to the following pages.



Test mode: 802.11b





Test mode: 802.11g



Test mode: 802.11n(HT20)



Test mode: 802.11n(HT40)



2. Radiated emission Test

Spectrum Detector: PK/AV Test Date : May 15, 2017
Test By: Andy Temperature : 28 °C
Humidity : 65 %

IEEE 802.11b							
Frequency (MHz)	Antenna polarization	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
	(H/V)	PK	AV	PK	AV	PK	AV
<2400	H	63.05	43.66	74	54	-10.95	-10.34
<2400	V	59.21	39.2	74	54	-14.79	-14.8
>2483.5	H	64.29	44.12	74	54	-9.71	-9.88
>2483.5	V	60.25	40.29	74	54	-13.75	-13.71

IEEE 802.11g							
Frequency (MHz)	Antenna polarization	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
	(H/V)	PK	AV	PK	AV	PK	AV
<2400	H	65.21	45.12	74	54	-8.79	-8.88
<2400	V	60.23	40.2	74	54	-13.77	-13.8
>2483.5	H	64.12	44.12	74	54	-9.88	-9.88
>2483.5	V	60.29	40.36	74	54	-13.71	-13.64

IEEE 802.11n(HT20)							
Frequency (MHz)	Antenna polarization	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
	(H/V)	PK	AV	PK	AV	PK	AV
<2400	H	63.12	43.62	74	54	-10.88	-10.38
<2400	V	60.95	40.95	74	54	-13.05	-13.05
>2483.5	H	64.12	44.18	74	54	-9.88	-9.82
>2483.5	V	59.21	39.52	74	54	-14.79	-14.48

IEEE 802.11n(HT40)							
Frequency (MHz)	Antenna polarization	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
	(H/V)	PK	AV	PK	AV	PK	AV
<2400	H	63.59	43.12	74	54	-10.41	-10.88
<2400	V	60.25	40.26	74	54	-13.75	-13.74
>2483.5	H	62.36	43.01	74	54	-11.64	-10.99
>2483.5	V	58.69	38.14	74	54	-15.31	-15.86

11. Power Density

11.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	FSV30	1321.3008K	05/16/2017	05/15/2018

11.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS bandwidth.
RB	3kHz
VB	10KHz
Detector	Peak
Trace	Max hold
Sweep Time	Automatic

11.3 Test Procedures

- The transmitter output (antenna port) was connected to the spectrum analyzer.
- Set analyzer center frequency to DTS channel center frequency.
- Set the analyzer span to a minimum of 1.5 times the DTS bandwidth.
- Set the RBW ≥ 3 kHz. Set the VBW $\geq 3 \times$ RBW.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

11.4 Block Diagram of Test Setup




11.5 Limit



The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3 kHz bandwidth.

11.6 Test Result


Spectrum Detector:	PK	Test Date :	May 15, 2017
Test By:	Andy	Temperature :	28°C
Test Result:	PASS	Humidity :	60%



IEEE 802.11b			
Channel frequency (MHz)	Measurement level (dBm)	Limit(dBm)	Result
2412	-4.08	8	Pass
2437	-4.35		
2462	-5.08		








IEEE 802.11g			
Channel frequency (MHz)	Measurement level (dBm)	Limit(dBm)	Result
2412	-7.62	8	Pass
2437	-7.99		
2462	-8.27		








IEEE 802.11n(HT20)			
Channel frequency (MHz)	Measurement level (dBm)	Limit(dBm)	Result
2412	-8.66	8	Pass
2437	-9.9		
2462	-9.76		





IEEE 802.11n(HT40)			
Channel frequency (MHz)	Measurement level (dBm)	Limit(dBm)	Result
2422	-13.47	8	Pass
2437	-13.20		
2452	-13.81		





12. Antenna Port Emission

12.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	FSV30	1321.3008K	05/16/2017	05/15/2018

12.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
RB	100kHz
VB	300kHz
Detector	Peak
Trace	Max hold

12.3 Test Procedures

The conducted spurious emissions were measured conducted using a spectrum analyzer at low, Middle, and high channels, the limit was determined by attenuation 20dB of the RF peak power output.

12.4 Block Diagram of Test setup




12.5 Test Result


PASS.

Please refer to following pages.


Test Mode: 802.11b



Lowest Channel




Middel Channel




Highest Channel


Test Mode: 802.11g



Lowest Channel




Middle Channel




Highest Channel


Test Mode: 802.11n(HT20)



Lowest Channel




Middle Channel




Highest Channel


Test Mode: 802.11n(HT40)



Lowest Channel



Middle Channel



Highest Channel

13. Antenna Application

13.1 Antenna Requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

13.2 Result

The EUT'S antenna is an internal PCB antenna. The antenna's gain is 2 dBi and meets the requirement.

APPENDIX I (PHOTOS OF EUT)





