

FCC 47 CFR MPE REPORT

Shenyang Tongfang Multimedia Technology Co., Limited
LED TV

Model Number: WD55UT4490

FCC ID: 2ACWIWD55UT4490

Prepared for : Shenyang Tongfang Multimedia Technology Co., Limited
No. 10 Nanping East Road HunNan New District Shenyang,
LiaoNing Province P.R. China

Prepared By :EST Technology Co., Ltd.
Santun(guantai Road), Houjie Town, DongGuan City,GuangDong,
China.

Tel: 86-769-83081888-808

Report Number: ESTE-R1610036

Date of Test : September19~ October 20, 2016

Date of Report : October 22, 2016



Maximum Permissible Exposure

1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)、Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3、Calculated Result and Limit

Mode	Frequency (MHz)	output power (dBm)	output power (mW)	Target power (dBm)	Antenna gain		Power Density (S) (mW /cm2)	Limited of Power Density (S) (mW /cm2)	Test Result
					(dBi)	(Linear)			
Antenna a									
IEEE 802.11b	2412	18.86	76.91	18 ± 1	1.8	1.51	0.02392	1	Compiles
	2437	19.15	82.22	19 ± 1	1.8	1.51	0.03011	1	Compiles
	2462	18.92	77.98	18 ± 1	1.8	1.51	0.02392	1	Compiles
IEEE 802.11g	2412	14.74	29.79	14 ± 1	1.8	1.51	0.00952	1	Compiles
	2437	15.13	32.58	15 ± 1	1.8	1.51	0.01199	1	Compiles
	2462	16.08	40.55	16 ± 1	1.8	1.51	0.01509	1	Compiles
IEEE 802.11n HT20	2412	14.94	31.19	14 ± 1	1.8	1.51	0.00952	1	Compiles
	2437	15.29	33.81	15 ± 1	1.8	1.51	0.01199	1	Compiles
	2462	15.41	34.75	15 ± 1	1.8	1.51	0.01199	1	Compiles
IEEE 802.11n HT40	2422	13.37	21.73	13 ± 1	1.8	1.51	0.00756	1	Compiles
	2437	13.29	21.33	13 ± 1	1.8	1.51	0.00756	1	Compiles
	2452	13.99	25.06	13 ± 1	1.8	1.51	0.00756	1	Compiles
Antenna b									
IEEE 802.11b	2412	18.98	79.07	18 ± 1	1.8	1.51	0.02392	1	Compiles
	2437	19.03	79.98	19 ± 1	1.8	1.51	0.03011	1	Compiles
	2462	18.78	75.51	18 ± 1	1.8	1.51	0.02392	1	Compiles
IEEE 802.11g	2412	14.53	28.38	14 ± 1	1.8	1.51	0.00952	1	Compiles
	2437	14.84	30.48	14 ± 1	1.8	1.51	0.00952	1	Compiles
	2462	15.13	32.58	15 ± 1	1.8	1.51	0.01199	1	Compiles
IEEE 802.11n HT20	2412	14.58	28.71	14 ± 1	1.8	1.51	0.00952	1	Compiles
	2437	15.16	32.81	15 ± 1	1.8	1.51	0.01199	1	Compiles
	2462	15.40	34.67	15 ± 1	1.8	1.51	0.01199	1	Compiles
IEEE 802.11n HT40	2422	13.47	22.23	13 ± 1	1.8	1.51	0.00756	1	Compiles
	2437	14.19	26.24	13 ± 1	1.8	1.51	0.00756	1	Compiles
	2452	13.11	20.46	13 ± 1	1.8	1.51	0.00756	1	Compiles

Mode	Frequency (MHz)	Power (W)			Limited (W)	Test Result
		Ant		Total		
		a	b			
IEEE 802.11n HT20	2412	0.00952	0.00952	0.01904	1	Compiles
	2437	0.01199	0.01199	0.02398	1	Compiles
	2462	0.01199	0.01199	0.02398	1	Compiles
IEEE 802.11n HT40	2412	0.00756	0.00756	0.01512	1	Compiles
	2437	0.00756	0.00756	0.01512	1	Compiles
	2462	0.00756	0.00756	0.01512	1	Compiles