

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

LED TV

**Model No.: LE-55GDH, WE55UC4200, WE55UT4200, WE55XXXXXXXXXX,
SEXXXXXXXXXX, ELXXXXXXXXXX, LE-55GXXXXXXXXXX
(where X would be any Arabian number or English letter or blank)**

FCC ID: 2ACWIWE55UC420

Trademark: THTF, Fluid, Westinghouse, Seiki, Element

Report No.: ED151105018E

Issue Date: November 20, 2015

Prepared for

**Shenyang Tongfang Multimedia Technology Co., Limited
No.10 Nanping East Road HunNan New District Shenyang, LiaoNing
Province P.R .China**

Prepared by

**EMTEK(Dongguan) Co., Ltd.
No.281, Guantai Road, Nancheng District,
Dongguan, Guangdong, China
TEL: 86-769-22807078
FAX: 86-769-22807079**

**This report shall not be reproduced, except in full, without the written approval of
EMTEK(Dongguan) Co., Ltd.**

VERIFICATION OF COMPLIANCE

Applicant:	Shenyang Tongfang Multimedia Technology Co., Limited No.10 Nanping East Road Hunnan New District Shenyang, Liaoning Province P.R .China
Manufacturer:	Shenyang Tongfang Multimedia Technology Co., Limited No.10 Nanping East Road Hunnan New District Shenyang, Liaoning Province P.R .China
Product Description:	LED TV
Model Number:	LE-55GDH, WE55UC4200, WE55UT4200, WE55XXXXXXXXXX, SEXXXXXXXXXX, ELXXXXXXXXXX, LE-55GXXXXXXXXXX (where X would be any Arabian number or English letter or blank) (Notes: these models are identical except for decorative parts in front panels, color of enclosures and design of signal input/output terminals in secondary circuits.)
Input Rating:	AC 100-240V, 50/60Hz, 165W

We hereby certify that:

The above equipment was tested by EMTEK(Dongguan) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247(2015).

Date of Test : November 05, 2015 to November 17, 2015

Prepared by : 

Mary Jiang/Editor

Reviewer : 

Alan He/Supervisor

Approved & Authorized Signer : 

Sam Lv/Manager

Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Report	/	KAD150616050E
Ver.1.0	Changed the LED panel	2015-11-20	ED151105018E

Table of Contents

1. GENERAL INFORMATION.....	5
1.1 PRODUCT DESCRIPTION	5
2. SYSTEM TEST CONFIGURATION	6
2.1 EUT CONFIGURATION	6
2.2 EUT EXERCISE	6
2.3 TEST PROCEDURE	6
2.4 CONFIGURATION OF TESTED SYSTEM.....	6
3. DESCRIPTION OF TEST MODES	7
4. SUMMARY OF TEST RESULTS	8
5. TEST METHODOLOGY.....	8
6. TEST FACILITY	8
7. TEST SYSTEM UNCERTAINTY.....	9
8. CONDUCTED EMISSIONS TEST	10
8.1 MEASUREMENT PROCEDURE	10
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	10
8.3 MEASUREMENT EQUIPMENT USED	10
8.4 CONDUCTED EMISSION LIMIT	10
8.5 MEASUREMENT RESULT	10
9. RADIATED EMISSION TEST	15
9.1 MEASUREMENT PROCEDURE	15
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	16
9.3 MEASUREMENT EQUIPMENT USED	17
9.4 RADIATED EMISSION LIMIT	18
9.5 MEASUREMENT RESULT	19
10. ANTENNA APPLICATION.....	28
10.1 ANTENNA REQUIREMENT	28
10.2 RESULT	28

APPENDIX I (PHOTOS OF EUT)(6 PAGES)

1. General Information

1.1 Product Description

Characteristics	Description
IEEE 802.11 WLAN Mode Supported	☒ 802.11b(20MHz channel bandwidth) ☒ 802.11g(20MHz channel bandwidth) ☒ 802.11n(20MHz channel bandwidth) ☒ 802.11n(40MHz channel bandwidth)
Data Rate	802.11 b:1,2,5.5,11Mbps; 802.11 g:6,9,12,18,24,36,48,54Mbps; 802.11n(HT20):MCS0-MCS7; 802.11n(HT40):MCS0-MCS7; 802.11n(HT40):MCS8-MCS15;
MIMO Mode	802.11n(HT20), 802.11n(HT40)
Modulation	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Operating Frequency Range	2412-2462MHz for 802.11b/g; 2412-2462MHz for 802.11n(HT20); 2422-2452MHz for 802.11n(HT40);
Number of Channels	11 channels for 802.11b/g; 11 channels for 802.11n(HT20); 7 channels for 802.11n(HT40);
Transmit Power Max	14.85dBm for 802.11b; 13.69dBm for 802.11g; 12.71dBm for 802.11n(HT20); 12.32dBm for 802.11n(HT40);
Antenna Type	2TX2RX
Antenna Port	☒ Ant1; ☒ Ant2;
Smart system	☒ SISO for 802.11b/g ☒ MIMO for 802.11n
Antenna Gain	2.0dBi (for per antenna port Max) 5.01dBi for MIMO(Ant1+Ant2 Directional Gain)

Note: for more details, please refer to the User's manual of the EUT.

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, the EUT was placed on a styrofoam table which is 1.5m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. Emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Item	Equipment	Trademark	Model No.	FCC ID	Note
1.	LED TV	Westinghouse	WE55UC4200	2ACWIWE55UC420	EUT

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column, device(s) used in tested system is a support equipment.

3. Description of Test Modes

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; 802.11n (HT40): MCS8) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for 802.11 b/g/n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Frequency and Channel list for 802.11 n (HT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	8	2447
4	2427	6	2437	9	2452
		7	2442		

Test Frequency and Channel for 802.11 b/g/n (HT20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462

Test Frequency and channel for 802.11 n (HT40):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	6	2437	9	2452

4. Summary of Test Results

FCC Rules	Description Of Test	Result
§15.207	AC Power Conducted Emission	Pass
§15.247(d), §15.209	Radiated Emission	Pass
§15.247(b)&§15.203	Antenna Application	Pass

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2ACWIWE55UC420 filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

The system is compliance with Subpart B is authorized under a DOC procedure

5. Test Methodology

According to its specifications, the EUT must comply with the requirements of the following standards:

FCC 47 CFR Part 2, Subpart J

FCC 47 CFR Part 15, Subpart C

FCC KDB 558074 D01 DTS Meas Guidance v03r03

FCC KDB 662911 D01 Multiple Transmitter Output v01

FCC KDB 662911 D02 MIMO With Cross Polarized Antenna V01

6. Test Facility

Site Description

EMC Lab : Registered on FCC, June 18, 2014
The Certificate Number is 247565.

Registered on Industry Canada, February 19, 2014
The Certificate Number is 9444A

Name of Firm : EMTEK(Dongguan) Co., Ltd.
Site Location : No.281, Guantai Road, Nancheng District,
Dongguan, Guangdong, China

7. TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0\text{dB}$
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Power Density	$\pm 2.0\text{dB}$
Occupied Bandwidth Test	$\pm 1.0\text{dB}$
Band Edge Test	$\pm 3\text{dB}$
All emission, radiated	$\pm 3\text{dB}$
Antenna Port Emission	$\pm 3\text{dB}$
Temperature	$\pm 0.5^\circ\text{C}$
Humidity	$\pm 3\%$


Measurement Uncertainty for a level of Confidence of 95%

8. Conducted Emissions Test

8.1 Measurement Procedure

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Last Cal.	Due date
Test Receiver	Rohde & Schwarz	ESCS30	100018	03/16/2015	03/15/2016
L.I.S.N	Rohde & Schwarz	ENV216	100017	03/16/2015	03/15/2016
RF Switching Unit	CDS	RSU-M2	38401	03/16/2015	03/15/2016
Coaxial Cable	CDS	79254	46107086	03/16/2015	03/15/2016


8.4 Conducted Emission Limit

Conducted Emission Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.5 Measurement Result


Please refer to following pages.



Site site #1 Phase: **L1** Temperature: 24
 Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX2412
 Note:

No.	Mk.	Freq. MHz	Reading Level dBpW	Correct Factor dB	Measure- ment dBpW	Limit dBpW	Over dB	Detector	Comment
1		0.1660	41.10	10.11	51.21	65.16	-13.95	QP	
2		0.1660	33.25	10.11	43.36	55.16	-11.80	AVG	
3		0.1940	38.99	10.12	49.11	63.86	-14.75	QP	
4		0.1940	34.20	10.12	44.32	53.86	-9.54	AVG	
5		0.3900	34.59	10.16	44.75	58.06	-13.31	QP	
6	*	0.3900	29.78	10.16	39.94	48.06	-8.12	AVG	
7		0.4540	33.49	10.18	43.67	56.80	-13.13	QP	
8		0.4540	27.51	10.18	37.69	46.80	-9.11	AVG	
9		0.5220	32.32	10.19	42.51	56.00	-13.49	QP	
10		0.5220	24.06	10.19	34.25	46.00	-11.75	AVG	
11		0.7820	29.67	10.18	39.85	56.00	-16.15	QP	
12		0.7820	22.48	10.18	32.66	46.00	-13.34	AVG	


*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator:



Site site #1 Phase: **N** Temperature: 24
 Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX2412
 Note:

No.	Mk.	Freq. MHz	Reading Level dBpW	Correct Factor dB	Measure- ment dBpW	Limit dBpW	Over dB	Detector	Comment
1		0.1580	41.31	10.11	51.42	65.57	-14.15	QP	
2		0.1580	29.82	10.11	39.93	55.57	-15.64	AVG	
3		0.1940	38.49	10.12	48.61	63.86	-15.25	QP	
4		0.1940	31.38	10.12	41.50	53.86	-12.36	AVG	
5		0.3900	32.21	10.16	42.37	58.06	-15.69	QP	
6		0.3900	27.89	10.16	38.05	48.06	-10.01	AVG	
7		0.4540	34.06	10.18	44.24	56.80	-12.56	QP	
8	*	0.4540	27.56	10.18	37.74	46.80	-9.06	AVG	
9		0.5220	31.06	10.19	41.25	56.00	-14.75	QP	
10		0.5220	23.22	10.19	33.41	46.00	-12.59	AVG	
11		0.8460	30.06	10.18	40.24	56.00	-15.76	QP	
12		0.8460	20.14	10.18	30.32	46.00	-15.68	AVG	


*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator:



Site site #1 Phase: **L1** Temperature: 24
 Limit: (CE)FCC PART 15 class B_QP Power: AC 240V/50Hz Humidity: 55 %
 Mode: TX2412
 Note:

No.	Mk.	Freq. MHz	Reading Level dBpW	Correct Factor dB	Measure- ment dBpW	Limit dBpW	Over dB	Detector	Comment
1		0.1500	42.75	10.11	52.86	66.00	-13.14	QP	
2		0.1500	28.28	10.11	38.39	56.00	-17.61	AVG	
3		0.1940	39.36	10.12	49.48	63.86	-14.38	QP	
4		0.1940	33.26	10.12	43.38	53.86	-10.48	AVG	
5		0.3260	35.13	10.15	45.28	59.55	-14.27	QP	
6		0.3260	27.06	10.15	37.21	49.55	-12.34	AVG	
7		0.3900	34.19	10.16	44.35	58.06	-13.71	QP	
8		0.3900	26.65	10.16	36.81	48.06	-11.25	AVG	
9		0.4540	33.55	10.18	43.73	56.80	-13.07	QP	
10		0.4540	25.92	10.18	36.10	46.80	-10.70	AVG	
11		0.5220	37.21	10.19	47.40	56.00	-8.60	QP	
12	*	0.5220	29.79	10.19	39.98	46.00	-6.02	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator:



Site site #1

Phase: **N**

Temperature: 24

Limit: (CE)FCC PART 15 class B_QP

Power: AC 240V/50Hz

Humidity: 55 %

Mode: TX2412

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBpW	dB	dBpW	dBpW	dB	Detector	Comment
1		0.1580	41.26	10.11	51.37	65.57	-14.20	QP	
2		0.1580	26.99	10.11	37.10	55.57	-18.47	AVG	
3		0.1940	36.80	10.12	46.92	63.86	-16.94	QP	
4		0.1940	30.29	10.12	40.41	53.86	-13.45	AVG	
5		0.3900	33.91	10.16	44.07	58.06	-13.99	QP	
6		0.3900	24.82	10.16	34.98	48.06	-13.08	AVG	
7		0.4540	34.46	10.18	44.64	56.80	-12.16	QP	
8		0.4540	24.89	10.18	35.07	46.80	-11.73	AVG	
9		0.5220	36.51	10.19	46.70	56.00	-9.30	QP	
10	*	0.5220	28.72	10.19	38.91	46.00	-7.09	AVG	
11		4.5660	33.31	10.11	43.42	56.00	-12.58	QP	
12		4.5860	20.13	10.11	30.24	46.00	-15.76	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator:

9. Radiated Emission Test

9.1 Measurement Procedure

1. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane, And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured was complete.

When spectrum scanned from 30MHz to 1GHz setting resolution bandwidth 120KHz and video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RBW	120KHz
VBW	300KHz
Detector	QP
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:


EMI Test Receiver	Setting
Attenuation	Auto
RBW	1MHz
VBW	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz:


EMI Test Receiver	Setting
Attenuation	Auto
RBW	1MHz
VBW	10Hz
Detector	Peak
Trace	Max hold

9.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



9.3 Measurement Equipment Used

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCI	1166.5950.03	03/16/2015	1 Year
2.	Bilog Antenna	Schwarzbeck	VULB9163	000141	03/16/2015	1 Year
3.	Power Amplifier	CDS	RSU-M352	818	03/16/2015	1 Year
4.	Power Amplifier	HP	8447F	OPT H64	03/16/2015	1 Year
5.	Color Monitor	SUNSPO	SP-140A	N/A	03/16/2015	1 Year
6.	Single Line Filter	JIANLI	XL-3	N/A	03/16/2015	1 Year
7.	Single Phase Power Line Filter	JIANLI	DL-2X100B	N/A	03/16/2015	1 Year
8.	3 Phase Power Line Filter	JIANLI	DL-4X100B	N/A	03/16/2015	1 Year
9.	DC Power Filter	JIANLI	DL-2X50B	N/A	03/16/2015	1 Year
10.	Cable	Schwarzbeck	PLF-100	549489	03/16/2015	1 Year
11.	Cable	Rosenberger	CIL02	A0783566	03/16/2015	1 Year
12.	Cable	Rosenberger	RG 233/U	525178	03/16/2015	1 Year
13.	Signal Analyzer	Rohde & Schwarz	FSV30	103040	12/29/2014	1 Year
14.	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1272	12/29/2014	1 Year
15.	Power Amplifier	LUNAR EM	LNA1G18-40	J10100000081	12/29/2014	1 Year
16.	Cable	H+S	CBL-26	N/A	12/29/2014	1 Year
17.	Cable	H+S	CBL-26	N/A	12/29/2014	1 Year
18.	Cable	H+S	CBL-26	N/A	12/29/2014	1 Year

9.4 Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

Remark 1. Emission level in dBuV/m=20 log (uV/m)

: 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of § 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

9.5 Measurement Result

Below 30MHz:

All the modulation modes were tested the data of the test mode are recorded in the following pages.

Operation Mode:	TX Mode	Test Date :	November 09, 2015
Frequency Range:	9KHz~30MHz	Temperature :	28°C
Test Result:	PASS	Humidity :	60 %
Measured Distance:	3m	Test By:	Andy

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.


Distance extrapolation factor = $40\log(\text{Specific distance/ test distance})$ (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor.

Below 1000MHz:

All the modulation modes were tested the data of the worst mode (ANT 1: TX 802.11b) are recorded in the following pages and the others modulation methods do not exceed the limits.


Please refer to the following test plots:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		107.6000	46.93	-17.87	29.06	43.50	-14.44	QP		
2		146.4000	48.02	-17.48	30.54	43.50	-12.96	QP		
3		412.1800	43.45	-11.34	32.11	46.00	-13.89	QP		
4		596.4800	42.67	-8.45	34.22	46.00	-11.78	QP		
5		662.4400	42.94	-7.79	35.15	46.00	-10.85	QP		
6	*	918.5200	39.42	-2.85	36.57	46.00	-9.43	QP		

*:Maximum data x:Over limit !:over margin

Operator: John




Site Chamber #1 Polarization: **Vertical** Temperature: 24
 Limit: (RE)FCC PART 15 class B 3m Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX 2412
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		35.8200	47.08	-14.08	33.00	40.00	-7.00	QP		
2	*	40.6700	47.51	-13.64	33.87	40.00	-6.13	QP		
3		111.4800	53.15	-17.48	35.67	43.50	-7.83	QP		
4		136.7000	53.27	-16.68	36.59	43.50	-6.91	QP		
5		413.1500	46.52	-11.36	35.16	46.00	-10.84	QP		
6		918.5200	38.87	-2.85	36.02	46.00	-9.98	QP		

*:Maximum data x:Over limit !:over margin


Operator: John



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		110.5100	45.90	-17.53	28.37	43.50	-15.13	QP		
2		137.6700	46.88	-16.79	30.09	43.50	-13.41	QP		
3		147.3700	49.50	-17.56	31.94	43.50	-11.56	QP		
4		595.5100	41.55	-8.46	33.09	46.00	-12.91	QP		
5		675.0500	43.27	-7.62	35.65	46.00	-10.35	QP		
6	*	917.5500	39.10	-2.90	36.20	46.00	-9.80	QP		

*:Maximum data x:Over limit !:over margin

Operator: John



Site: Chamber #1
 Limit: (RE)FCC PART 15 class B 3m
 Mode: TX 2437
 Note:


Polarization: **Vertical**
 Power: AC 120V/60Hz

Temperature: 24
 Humidity: 55 %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		37.7600	44.60	-13.84	30.76	40.00	-9.24	QP		
2		41.6400	43.41	-13.58	29.83	40.00	-10.17	QP		
3	*	110.5100	51.80	-17.53	34.27	43.50	-9.23	QP		
4		147.3700	50.66	-17.56	33.10	43.50	-10.40	QP		
5		482.0200	47.01	-10.52	36.49	46.00	-9.51	QP		
6		917.5500	39.33	-2.90	36.43	46.00	-9.57	QP		

*:Maximum data x:Over limit !:over margin

Operator: John




Site Chamber #1 Polarization: **Horizontal** Temperature: 24
 Limit: (RE)FCC PART 15 class B 3m Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX 2462
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		110.5100	46.85	-17.53	29.32	43.50	-14.18	QP		
2		129.9100	46.48	-16.25	30.23	43.50	-13.27	QP		
3		136.7000	48.02	-16.68	31.34	43.50	-12.16	QP		
4		590.6600	41.62	-8.52	33.10	46.00	-12.90	QP		
5	*	666.3200	44.54	-7.73	36.81	46.00	-9.19	QP		
6		916.5800	38.07	-2.94	35.13	46.00	-10.87	QP		

*:Maximum data x:Over limit !:over margin

Operator: John



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		41.7130	43.97	-13.57	30.40	40.00	-9.60	QP		
2		44.5500	43.64	-13.47	30.17	40.00	-9.83	QP		
3	*	110.5100	52.14	-17.53	34.61	43.50	-8.89	QP		
4		410.2400	46.48	-11.33	35.15	46.00	-10.85	QP		
5		478.1400	45.22	-10.59	34.63	46.00	-11.37	QP		
6		917.5500	39.23	-2.90	36.33	46.00	-9.67	QP		

*:Maximum data x:Over limit !:over margin

Operator: John

Above 1000MHz:

Operation Mode: 802.11b Lowest
Test Voltage: AC 120V/60Hz

Test Date : November 09, 2015
Test by: Andy

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4824	V	60.19	42.1	74	54	-13.81	-11.9
7236	V	59.09	40.9	74	54	-14.91	-13.1
9648	V	60.13	43.5	74	54	-13.87	-10.5
12060	V	59.44	41.8	74	54	-14.56	-12.2
14472	V	56.91	39.6	74	54	-17.09	-14.4
16884	V	56.62	38.4	74	54	-17.38	-15.6
4824	H	62.89	44.7	74	54	-11.11	-9.3
7236	H	61.89	42.3	74	54	-12.11	-11.7
9648	H	60.34	43.1	74	54	-13.66	-10.9
12060	H	59.79	41.9	74	54	-14.21	-12.1
14472	H	58.2	40.4	74	54	-15.8	-13.6
16884	H	57.93	39.6	74	54	-16.07	-14.4

Operation Mode: 802.11b Middle
Test Voltage: AC 120V/60Hz

Test Date : November 09, 2015
Test by: Andy

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4874	V	61.17	42.8	74	54	-12.83	-11.2
7311	V	60.26	41.6	74	54	-13.74	-12.4
9688	V	59.98	40.9	74	54	-14.02	-13.1
12185	V	60.18	42.7	74	54	-13.82	-11.3
14622	V	57.67	0.3	74	54	-16.33	-53.7
17059	V	56.55	38.6	74	54	-17.45	-15.4
4874	H	61.09	42.4	74	54	-12.91	-11.6
7311	H	60.94	41.8	74	54	-13.06	-12.2
9688	H	58.87	40.9	74	54	-15.13	-13.1
12185	H	58.19	41.3	74	54	-15.81	-12.7
14622	H	57.43	39.8	74	54	-16.57	-14.2
17059	H	59.96	38.5	74	54	-14.04	-15.5

Operation Mode: 802.11b Highest

Test Date : November 09, 2015

Test Voltage: AC 120V/60Hz

Test by: Andy

Freq. (MHz)	Ant. Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4924	V	60.42	42.9	74	54	-13.58	-11.1
7386	V	60.59	41.6	74	54	-13.41	-12.4
9848	V	59.8	40.3	74	54	-14.2	-13.7
12310	V	58.94	42.4	74	54	-15.06	-11.6
14772	V	56.22	38.6	74	54	-17.78	-15.4
17234	V	55.17	37.5	74	54	-18.83	-16.5
4924	H	59.63	41.9	74	54	-14.37	-12.1
7386	H	59.61	40.3	74	54	-14.39	-13.7
9848	H	59.93	41.7	74	54	-14.07	-12.3
12310	H	59.62	42.4	74	54	-14.38	-11.6
14772	H	58.83	39.6	74	54	-15.17	-14.4
17234	H	56.46	38.5	74	54	-17.54	-15.5

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ – ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

10. Antenna Application

10.1 Antenna Requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

10.2 Result

The EUT'S antenna, permanent attached antenna, is internal antenna. The antenna's gain is 2dBi and meets the requirement.

APPENDIX I (PHOTOS OF EUT)





