



No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan
District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM140900484302
Page: 1 of 49

FCC REPORT

Application No: SZEM1409004843RF(SGS SH No.:SHEM1408001950RF)
Applicant: Shanghai IGoo Smartlamp Technology Co.,Ltd
Manufacturer: Shanghai Grandar Light Art& Technology Co.,Ltd
Factory: Shanghai Grandar Light Art& Technology Co.,Ltd
Product Name: Smartlamp Control
Model No.(EUT): IGoo 1
FCC ID: 2ACWVIGOO1SC
Standards: 47 CFR Part 15, Subpart C (2013)
Date of Receipt: 2014-09-03
Date of Test: 2014-09-10 to 2014-09-18
Date of Issue: 2014-10-11

Test Result:	PASS *
---------------------	---------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager


The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2014-10-11		Original

Authorized for issue by:				
Tested By		 		2014-09-18
				Date
Prepared By		 		2014-10-11
				Date
Checked By		 		2014-10-14
				Date
		(Chris Zhong)/Project Engineer		
		(Sade Luo) /Clerk		
		(Emen Li) /Reviewer		



3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2009	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2009	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	KDB558074 D01 v03r02	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	KDB558074 D01 v03r02	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	KDB558074 D01 v03r02	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	KDB558074 D01 v03r02	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	KDB558074 D01 v03r02	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS



4 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 TEST SUMMARY	3
4 CONTENTS	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST ENVIRONMENT	7
5.4 DESCRIPTION OF SUPPORT UNITS	7
5.5 TEST LOCATION.....	7
5.6 TEST FACILITY	8
5.7 DEVIATION FROM STANDARDS	8
5.8 ABNORMALITIES FROM STANDARD CONDITIONS.....	8
5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	8
5.10 EQUIPMENT LIST.....	9
6 TEST RESULTS AND MEASUREMENT DATA.....	11
6.1 ANTENNA REQUIREMENT.....	11
6.2 CONDUCTED EMISSIONS	12
6.3 CONDUCTED PEAK OUTPUT POWER	16
6.4 6dB OCCUPY BANDWIDTH.....	19
6.5 POWER SPECTRAL DENSITY.....	22
6.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS.....	25
6.7 SPURIOUS RF CONDUCTED EMISSIONS	27
6.8 RADIATED SPURIOUS EMISSION.....	34
6.8.1 Radiated Emission below 1GHz	36
6.8.2 Transmitter Emission above 1GHz.....	38
6.9 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	40-49

5 General Information

5.1 Client Information

Applicant:	Shanghai IGOO Smartlamp Technology Co.,Ltd
Address of Applicant:	Floor 11, Building 90, #1122 North Qinzhou Rd., Shanghai, P.R.China 200233
Manufacturer:	Shanghai Grandar Light Art& Technology Co.,Ltd
Address of Manufacturer:	Floor 11, Building 90, #1122 North Qinzhou Rd., Shanghai, P.R.China 200233
Factory:	Shanghai Grandar Light Art& Technology Co.,Ltd
Address of Factory:	Factory 6, No.466 Chengjian Road, Minhang District, Shanghai P.R.China

5.2 General Description of EUT

Product Name:	Smartlamp Control
Model No.:	IGOO 1
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	4.0
	This test report is for BLE mode
Modulation Type:	GFSK
Number of Channel:	40
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	Portable production
EUT Function:	IGOO Smartlamp
Test Power Grade:	7 (manufacturer declare)
Test Software of EUT:	*##*3646633#* (manufacturer declare)
Antenna Type:	Integral
Antenna Gain:	-4dBi
AC Adapter:	MODEL:C-P17 INPUT: 100-240V 50/60Hz 0.3A OUTPUT:DC 5.0V 1000mA
Battery:	MODEL:I01C01Ba01 Maximum Charging Voltage:4.2V---3.7V 2500mAh 9.25Wh Rechargeable Lithium-polaymer Battery
USB Cable:	100cm(Unshielded)



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	11	2422MHz	21	2442MHz	31	2462MHz
2	2404MHz	12	2424MHz	22	2444MHz	32	2464MHz
3	2406MHz	13	2426MHz	23	2446MHz	33	2466MHz
4	2408MHz	14	2428MHz	24	2448MHz	34	2468MHz
5	2410MHz	15	2430MHz	25	2450MHz	35	2470MHz
6	2412MHz	16	2432MHz	26	2452MHz	36	2472MHz
7	2414MHz	17	2434MHz	27	2454MHz	37	2474MHz
8	2416MHz	18	2436MHz	28	2456MHz	38	2476MHz
9	2418MHz	19	2438MHz	29	2458MHz	39	2478MHz
10	2420MHz	20	2440MHz	30	2460MHz	40	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2440MHz
The Highest channel	2480MHz



5.3 Test Environment

Operating Environment:	
Temperature:	25.0 °C
Humidity:	53 % RH
Atmospheric Pressure:	1005mbar

5.4 Description of Support Units

The EUT has been tested independent unit.

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,
No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **VCCI**

The 3m Semi-anechoic chamber, Full-anechoic Chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197, G-416, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.

5.10 Equipment List

RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2015-06-10
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	2015-05-16
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2014-10-24
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2014-10-24
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2014-10-24
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2015-05-16
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2014-10-24
9	Coaxial cable	SGS	N/A	SEL0027	2015-05-29
10	Coaxial cable	SGS	N/A	SEL0189	2015-05-29
11	Coaxial cable	SGS	N/A	SEL0121	2015-05-29
12	Coaxial cable	SGS	N/A	SEL0178	2015-05-29
13	Band filter	Amindeon	82346	SEL0094	2015-05-16
14	Barometer	Chang Chun	DYM3	SEL0088	2015-05-16
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2014-10-24
16	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2014-10-24
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2015-05-16
18	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2014-10-24
19	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2015-06-04


RF connected test					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2014-10-24
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2014-10-24
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2014-10-24
4	Coaxial cable	SGS	N/A	SEL0178	2015-05-29
5	Coaxial cable	SGS	N/A	SEL0179	2015-05-29
6	Barometer	ChangChun	DYM3	SEL0088	2015-05-16
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2015-05-16
8	Band filter	amideon	82346	SEL0094	2015-05-16
9	POWER METER	R & S	NRVS	SEL0144	2014-10-24
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2015-05-16
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2014-10-24

Note: The calibration interval is one year, all the instruments are valid.




6 Test results and Measurement Data

6.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	
The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is -4dBi.	

6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2009		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2009 on conducted measurement.		

Test Setup:	
Test Mode:	AC Charge+Transmitting mode
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass


Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live line:

Data: 862
Level (dBuV)



Site : Shielding Room
Condition : 47 CFR PART15C QP CE LINE
Job No. : 4843RF
Mode : BLE TX mode


	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.18249	0.02	9.70	22.08	31.80	54.37	-22.57	Average
2	0.18249	0.02	9.70	29.03	38.75	64.37	-25.62	QP
3	0.24293	0.02	9.70	32.80	42.52	62.00	-19.48	QP
4	0.24293	0.02	9.70	22.14	31.86	52.00	-20.14	Average
5 @	0.53782	0.01	9.80	20.86	30.67	46.00	-15.33	Average
6	0.53782	0.01	9.80	28.67	38.48	56.00	-17.52	QP
7	1.396	0.02	9.80	17.45	27.27	46.00	-18.73	Average
8	1.396	0.02	9.80	24.53	34.35	56.00	-21.65	QP
9	5.867	0.01	9.90	25.82	35.73	60.00	-24.27	QP
10	5.867	0.01	9.90	17.45	27.36	50.00	-22.64	Average
11	16.486	0.02	10.10	27.54	37.66	60.00	-22.34	QP
12	16.486	0.02	10.10	16.89	27.01	50.00	-22.99	Average



Neutral line:

Data: 861


Level (dBuV)



Site : Shielding Room
Condition : 47 CFR PART15C QP CE NEUTRAL
Job No. : 4843RF
Mode : BLE TX mode

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.17961	0.02	9.70	34.64	44.36	64.50	-20.15	QP
2	0.17961	0.02	9.70	22.21	31.93	54.50	-22.57	Average
3	0.30348	0.01	9.71	18.92	28.64	50.15	-21.51	Average
4	0.30348	0.01	9.71	31.50	41.22	60.15	-18.93	QP
5	0.54355	0.01	9.80	17.43	27.24	46.00	-18.76	Average
6	0.54355	0.01	9.80	26.80	36.61	56.00	-19.39	QP
7	1.456	0.02	9.80	26.13	35.95	56.00	-20.05	QP
8	1.456	0.02	9.80	16.94	26.76	46.00	-19.24	Average
9	11.870	0.01	10.00	28.91	38.92	60.00	-21.08	QP
10	11.870	0.01	10.00	20.66	30.67	50.00	-19.33	Average
11	17.661	0.02	10.06	31.88	41.95	60.00	-18.05	QP
12	17.661	0.02	10.06	20.35	30.43	50.00	-19.57	Average

6.3 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)
Test Method:	KDB558074 D01 v03r02
Test Setup:	 <i>Remark:</i> Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.
Limit:	30dBm
Test Mode:	Non-hopping transmitting with GFSK modulation
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass


Measurement Data

GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	1.39	30.00	Pass
Middle	1.85	30.00	Pass
Highest	1.90	30.00	Pass




Test plot as follows:

Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------






Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------



6.4 6dB Occupy Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	KDB558074 D01 v03r02
Test Setup:	
Limit:	≥ 500 kHz
Test Mode:	Non-hopping transmitting with GFSK modulation
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass


Measurement Data

Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	0.688	≥ 500	Pass
Middle	0.697	≥ 500	Pass
Highest	0.697	≥ 500	Pass




Test plot as follows:

Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------






Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------



6.5 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	KDB558074 D01 v03r02
Test Setup:	
Limit:	$\leq 8.00 \text{ dBm/3kHz}$
Exploratory Test Mode:	Non-hopping transmitting with GFSK modulation
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass


Measurement Data

GFSK mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-0.28	≤ 8.00	Pass
Middle	0.18	≤ 8.00	Pass
Highest	0.25	≤ 8.00	Pass




Test plot as follows:

Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------






Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------




6.6 Band-edge for RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	KDB558074 D01 v03r02
Test Setup:	 Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Non-hopping and hopping transmitting with GFSK modulation
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Test plot as follows:

Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------





"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



6.7 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	KDB558074 D01 v03r02
Test Setup:	 Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Non-hopping transmitting with GFSK modulation
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass





Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------











Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------









Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------






Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report.

6.8 Radiated Spurious Emission

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2009				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					
Test Setup:					
Figure 1. Above 1 GHz					
Test Procedure:	a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.				




	b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel (2402MHz),the middle channel (2440MHz),the Highest channel (2480MHz) h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode,And found the X axis positioning which it is worse case. i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type Transmitting mode,Charge +Transmitting mode.
Final Test Mode:	Pretest the EUT at Transmitting mode and Charge +Transmitting mode, found the Charge +Transmitting mode which it is worse case Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

6.8.1 Radiated Emission below 1GHz

30MHz~1GHz (QP)

Test mode: AC Charge+Transmitting Vertical

Data: 30



Condition: FCC PART 15C 3m 3142C Vertical


Job No. : 4843RF

Mode : BLE AC charge TX mode

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.00	0.60	15.20	27.36	45.35	33.79	40.00	-6.21
2	47.66	0.76	9.22	27.30	50.55	33.23	40.00	-6.77
3	93.77	1.14	8.85	27.21	52.06	34.84	43.50	-8.66
4	285.98	1.84	13.30	26.44	51.46	40.16	46.00	-5.84
5	689.56	2.88	21.52	27.43	43.23	40.20	46.00	-5.80
6	755.39	3.07	21.77	27.35	43.23	40.72	46.00	-5.28

Test mode:	AC Charge+Transmitting	Horizontal
------------	------------------------	------------

Data: 31



Condition: FCC PART 15C 3m 3142C Horizontal

Job No. : 4843RF

Mode : BLE AC charge TX mode

	Freq	Cable Loss	Ant Factor	Preamplifier	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	88.03	1.10	8.51	27.22	52.23	34.62	43.50	-8.88
2	230.10	1.57	11.67	26.59	49.15	35.80	46.00	-10.20
3	419.11	2.28	16.38	27.25	49.28	40.69	46.00	-5.31
4	719.20	2.96	21.60	27.39	38.61	35.78	46.00	-10.22
5	842.13	3.38	22.40	27.06	40.69	39.41	46.00	-6.59
6	948.76	3.65	23.30	26.54	38.03	38.44	46.00	-7.56

6.8.2 Transmitter Emission above 1GHz

Test mode:		GFSK		Test channel:		Lowest		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization		
3316.617	4.66	32.56	38.66	43.51	42.07	74	-31.93	Vertical		
4804.000	5.63	34.70	39.24	43.82	44.91	74	-29.09	Vertical		
5986.509	6.63	36.27	39.19	44.15	47.86	74	-26.14	Vertical		
7206.000	6.80	35.63	39.07	43.18	46.54	74	-27.46	Vertical		
9608.000	8.94	37.33	37.93	43.00	51.34	74	-22.66	Vertical		
12148.020	9.06	38.89	38.83	43.66	52.78	74	-21.22	Vertical		
3249.760	4.69	32.38	38.63	44.54	42.98	74	-31.02	Horizontal		
4804.000	5.63	34.70	39.24	44.27	45.36	74	-28.64	Horizontal		
5895.771	6.09	36.10	39.19	44.31	47.31	74	-26.69	Horizontal		
7206.000	6.80	35.63	39.07	43.73	47.09	74	-26.91	Horizontal		
9608.000	8.94	37.33	37.93	42.07	50.41	74	-23.59	Horizontal		
11994.380	9.31	38.69	38.70	43.53	52.83	74	-21.17	Horizontal		

Test mode:		GFSK		Test channel:	Middle		Remark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3333.545	4.66	32.61	38.67	43.80	42.40	74	-31.60	Vertical
4880.000	5.61	34.78	39.26	43.20	44.33	74	-29.67	Vertical
5986.509	6.63	36.27	39.19	45.31	49.02	74	-24.98	Vertical
7320.000	6.73	35.51	39.06	44.06	47.24	74	-26.76	Vertical
9760.000	8.84	37.80	37.84	42.78	51.58	74	-22.42	Vertical
11842.690	9.38	38.54	38.63	42.74	52.03	74	-21.97	Vertical
3291.385	4.67	32.50	38.65	44.00	42.52	74	-31.48	Horizontal
4880.000	5.61	34.78	39.26	43.88	45.01	74	-28.99	Horizontal
6109.670	6.51	36.18	39.17	44.56	48.08	74	-25.92	Horizontal
7320.000	6.73	35.51	39.06	44.80	47.98	74	-26.02	Horizontal
9760.000	8.84	37.80	37.84	41.96	50.76	74	-23.24	Horizontal
11963.890	9.33	38.66	38.68	44.31	53.62	74	-20.38	Horizontal



Test mode:		GFSK		Test channel:		Highest		Remark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamplifier Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3402.126	4.64	32.78	38.70	43.36	42.08	74	-31.92	Vertical	
4960.000	5.60	34.86	39.29	43.42	44.59	74	-29.41	Vertical	
6032.401	6.65	36.26	39.18	43.58	47.31	74	-26.69	Vertical	
7440.000	6.72	35.43	39.05	43.30	46.40	74	-27.60	Vertical	
9920.000	9.19	38.27	37.75	42.46	52.17	74	-21.83	Vertical	
12086.330	9.17	38.81	38.77	43.43	52.64	74	-21.36	Vertical	
3112.129	4.67	32.06	38.56	43.93	42.10	74	-31.90	Horizontal	
4960.000	5.60	34.86	39.29	45.05	46.22	74	-27.78	Horizontal	
6063.190	6.59	36.23	39.18	44.49	48.13	74	-25.87	Horizontal	
7440.000	6.72	35.43	39.05	44.60	47.70	74	-26.30	Horizontal	
9920.000	9.19	38.27	37.75	43.06	52.77	74	-21.23	Horizontal	
11663.190	9.45	38.36	38.54	42.82	52.09	74	-21.91	Horizontal	

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported .
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

6.9 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205																						
Test Method:	ANSI C63.10 2009																						
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																						
Limit:	<table><tr><td>Frequency</td><td>Limit (dBuV/m @3m)</td><td>Remark</td></tr><tr><td>30MHz-88MHz</td><td>40.0</td><td>Quasi-peak Value</td></tr><tr><td>88MHz-216MHz</td><td>43.5</td><td>Quasi-peak Value</td></tr><tr><td>216MHz-960MHz</td><td>46.0</td><td>Quasi-peak Value</td></tr><tr><td>960MHz-1GHz</td><td>54.0</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>54.0</td><td>Average Value</td></tr><tr><td>74.0</td><td>Peak Value</td></tr></table>			Frequency	Limit (dBuV/m @3m)	Remark	30MHz-88MHz	40.0	Quasi-peak Value	88MHz-216MHz	43.5	Quasi-peak Value	216MHz-960MHz	46.0	Quasi-peak Value	960MHz-1GHz	54.0	Quasi-peak Value	Above 1GHz	54.0	Average Value	74.0	Peak Value
	Frequency	Limit (dBuV/m @3m)	Remark																				
	30MHz-88MHz	40.0	Quasi-peak Value																				
	88MHz-216MHz	43.5	Quasi-peak Value																				
	216MHz-960MHz	46.0	Quasi-peak Value																				
	960MHz-1GHz	54.0	Quasi-peak Value																				
	Above 1GHz	54.0	Average Value																				
		74.0	Peak Value																				
Test Setup:																							




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz

Test Procedure:	- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. - Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel
-----------------	---



	g. Test the EUT in the lowest channel , the Highest channel h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode,And found the X axis positioning which it is worse case. i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type Transmitting mode,Charge +Transmitting mode
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worse case of GFSK modulation type. Pretest the EUT at Transmitting mode and Charge +Transmitting mode, found the Charge +Transmitting mode which it is worse case Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass




Test plot as follows:

Restricted bands around fundamental frequency

Test mode:	GFSK	Test channel:	Lowest	Remark:	Peak	Vertical
------------	------	---------------	--------	---------	------	----------

Data: 98




Site : chamber
Condition: FCC PART C 247 PK 3m Vertical
Job No: : 4843RF
Mode: : 2402 BLE Bandedge

		Aux	Cable	Ant	Preamp	Read	Limit	Over
	Freq	Factor	Loss	Factor	Factor	Level	Level	Line
	MHz	dB	dB	dB/m	dB	dBuV	dBuV/m	dB
1	2390.00	0.00	3.36	32.35	38.46	45.38	42.63	74.00
2 pp	2401.80	0.00	3.37	32.41	38.46	96.85	94.17	74.00



Test mode:	GFSK	Test channel:	Lowest	Remark:	Peak	Horizontal
------------	------	---------------	--------	---------	------	------------

Data: 99




Site : chamber
Condition: FCC PART C 247 PK 3m Horizontal
Job No: : 4843RF
Mode: : 2402 BLE Bandedge

		Aux	Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Factor	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	0.00	3.36	32.35	38.46	45.41	42.66	74.00	-31.34
2 pp	2401.90	0.00	3.37	32.41	38.46	95.00	92.32	74.00	18.32



Test mode:	GFSK	Test channel:	Lowest	Remark:	Average	Vertical
------------	------	---------------	--------	---------	---------	----------

Data: 100




Site : chamber
Condition: FCC PART C 247 AV 3m Vertical
Job No: : 4843RF
Mode: : 2402 BLE Bandedge

		Aux	Cable	Ant	Preamp	Read	Limit	Over
	Freq	Factor	Loss	Factor	Factor	Level	Line	Limit
	MHz	dB	dB	dB/m	dB	dBuV	dBuV/m	dB
1	2390.00	0.00	3.36	32.35	38.46	32.27	29.52	54.00 -24.48
2 pp	2402.09	0.00	3.37	32.41	38.46	81.15	78.47	54.00 24.47



Test mode:	GFSK	Test channel:	Lowest	Remark:	Average	Horizontal
------------	------	---------------	--------	---------	---------	------------

Data: 101




Site : chamber
Condition: FCC PART C 247 AV 3m Horizontal
Job No: : 4843RF
Mode: : 2402 BLE Bandedge

		Aux	Cable	Ant	Preamp	Read	Limit	Over
	Freq	Factor	Loss	Factor	Factor	Level	Line	Limit
	MHz	dB	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m
1	2390.00	0.00	3.36	32.35	38.46	32.83	30.08	54.00
2 pp	2402.09	0.00	3.37	32.41	38.46	89.40	86.72	54.00



Test mode:	GFSK	Test channel:	Highest	Remark:	Peak	Vertical
------------	------	---------------	---------	---------	------	----------

Data: 103




Site : chamber
Condition: FCC PART C 247 PK 3m Vertical
Job No: : 4843RF
Mode: : 2480 BLE Bandedge

		Aux	Cable	Ant	Preamp	Read	Limit	Over
	Freq	Factor	Loss	Factor	Factor	Level	Level	Line
	MHz	dB	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m
1	pp 2480.25	0.00	3.46	32.44	38.47	95.59	93.02	74.00
2	2483.50	0.00	3.47	32.44	38.47	46.23	43.67	74.00



Test mode:	GFSK	Test channel:	Highest	Remark:	Peak	Horizontal
------------	------	---------------	---------	---------	------	------------

Data: 102




Site : chamber
Condition: FCC PART C 247 PK 3m Horizontal
Job No: : 4843RF
Mode: : 2480 BLE Bandedge

		Aux	Cable	Ant	Preamp	Read	Limit	Over
	Freq	Factor	Loss	Factor	Factor	Level	Level	Line
	MHz	dB	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m
1 pp	2479.76	0.00	3.46	32.44	38.47	93.96	91.39	74.00
2	2483.50	0.00	3.47	32.44	38.47	46.75	44.19	74.00



Test mode:	GFSK	Test channel:	Highest	Remark:	Average	Vertical
------------	------	---------------	---------	---------	---------	----------

Data: 104




Site : chamber
Condition: FCC PART C 247 AV 3m Vertical
Job No: : 4843RF
Mode: : 2480 BLE Bandedge

		Aux	Cable	Ant	Preamp	Read	Limit	Over
	Freq	Factor	Loss	Factor	Factor	Level	Line	Limit
	MHz	dB	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m
1 pp	2480.03	0.00	3.46	32.44	38.47	89.20	86.63	54.00
2	2483.50	0.00	3.47	32.44	38.47	36.12	33.56	54.00



Test mode:	GFSK	Test channel:	Highest	Remark:	Average	Horizontal
------------	------	---------------	---------	---------	---------	------------

Data: 105



Site : chamber
Condition: FCC PART C 247 AV 3m Horizontal
Job No: : 4843RF
Mode: : 2480 BLE Bandedge

		Aux	Cable	Ant	Preamp	Read	Limit	Over
	Freq	Factor	Loss	Factor	Factor	Level	Level	Line
	MHz	dB	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m
1 pp	2480.01	0.00	3.46	32.44	38.47	78.47	75.90	54.00
2	2483.50	0.00	3.47	32.44	38.47	32.27	29.71	54.00

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor