

# FCC ID: 2ACWX-NH380

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

BT DSS:

| Transmit Frequency (GHz) | Mode             | Max Conducted Power (dBm) | Result calculation | 1-g SAR |
|--------------------------|------------------|---------------------------|--------------------|---------|
| 2.402                    | GFSK             | 3.116                     | 0.64               | 3.0     |
| 2.441                    | GFSK             | 5.276                     | 1.05               | 3.0     |
| 2.480                    | GFSK             | 4.874                     | 0.97               | 3.0     |
| 2.402                    | 1/4 $\Pi$ -DQPSK | 3.227                     | 0.66               | 3.0     |
| 2.441                    | 1/4 $\Pi$ -DQPSK | 3.078                     | 0.63               | 3.0     |
| 2.480                    | 1/4 $\Pi$ -DQPSK | 2.612                     | 0.57               | 3.0     |
| 2.402                    | 8DPSK            | 1.607                     | 0.45               | 3.0     |
| 2.441                    | 8DPSK            | 3.326                     | 0.67               | 3.0     |
| 2.480                    | 8DPSK            | 2.931                     | 0.61               | 3.0     |

BT DTS:

| Transmit Frequency (GHz) | Mode | Max Conducted Power (dBm) | Result calculation | 1-g SAR |
|--------------------------|------|---------------------------|--------------------|---------|
| 2.402                    | GFSK | 5.280                     | 1.04               | 3.0     |
| 2.441                    | GFSK | 6.160                     | 1.29               | 3.0     |
| 2.480                    | GFSK | 5.868                     | 1.22               | 3.0     |

Conclusion:

For the max result :  $1.29 \leq 3.0$  for 1-g SAR extremity SAR, No SAR is required.

Sincerely,



---

Signature

Company Name: SHENZHEN EMTEK CO., LTD.

Address: Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen, China

David Lee/ Manager