

FCC ID TEST REPORT

for

TABLET PC

Model: H8336

FCC ID: 2ACXAH8336

Prepared for: KIMUS TRADING, INC
6436 Shadow CT. Douglasville, GA 30134 USA

Prepared by: Shenzhen TCT Testing Technology Co.,Ltd
1F, Building 1, Yibaolai Industrial Park, Qiaotou Village, Fuyong Town,
Baoan District, Shenzhen, Guangdong, China

TEL: +86-0755-27673339

FAX: +86-0755-27673332

Report Number: TCT140807E011F2

Date of Test: Aug. 08-Aug. 15, 2014

Date of Report: Aug. 15, 2014

The results detailed in this test report relate only to the specific sample(s) tested. It is the Application's responsibility to ensure that all production units are manufactured with equivalent EMC characteristics. This report is not to be reproduced except in full, without written approval from TCT Testing Technology

Table of Contents

1.0 General Details	3
1.1 Test Lab Details	3
1.2 Applicant Details	3
1.4 Statement	4
1.5 Test Engineer	4
2.0 Test equipments and Associated Equipment used during the test.	5
2.1 Test Equipments.....	5
2.2 AE used during the test.....	5
3.0 Technical Details	6
3.1 Summary of test results	6
3.2 Test Standards	6
4.0 EUT Modification	6
5.0 Measurement Uncertainty (95% confidence levels, k=2)	6
6.0 Power Line Conducted Emission Test	7
7.0 Maximum Peak Output Power	11
8.0 6dB Bandwidth Measurement	13
9.0 Power Spectral Density Measurement	21
10.0 Band-edge Measurement	29
11.0 Spurious Emission Test	34
12.0 Antenna Requirement	59

1.0 General Details

1.1 Test Lab Details

Name :	Shenzhen Tongce Testing Lab
Address:	1F, Leinuo Watch Building, Fuyong Town, Baoan Dist, Shenzhen, China
Telephone:	13410377511
Fax:	--

The test facility is recognized, certified, or accredited by the following organizations:

FCC Registration Number: 572331

Shenzhen TCT Testing Technology Co., Ltd., Shenzhen EMC Laboratory: Shenzhen Tongce Testing Lab
The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.
Registration Number: 572331

Industry Canada (IC)

The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing
Registration Number IC: 10668A-1

1.2 Applicant Details

Applicant:	KIMUS TRADING, INC
Address:	6436 Shadow CT. Douglasville, GA 30134 USA
Telephone:	678.793.2046 / 404-200-2236 (USA)
Fax:	678.348.7525

Manufacturer:	Hengdi Digital Technology (ShenZhen) Co., Ltd.
Address:	Guanjie Industrial Park, Xinshiqiao, Guihua Village, Guanlan Street, Bao'an Dist, Shenzhen City, China, PRC
Telephone:	--
Fax:	--

1.3 Description of EUT

Product:	TABLET PC
Model No.:	H8336
Additional Model No.:	N.A.
Brand Name:	
Operation Frequency:	WCDMA 850/GSM850: 824-849(TX): 869-894 MHz(RX) PCS1900: 1850-1910MHz(TX), 1930-1990MHz(RX) WCDMA 1700:1710-1750(TX), 2110-2150(RX) BT 3.0+EDR , GFSK, Pi/4DQPSK, 8DPSK, 2402-2480 MHz BLE, GFSK, 2402-2480MHz WIFI:IEEE 802.11b: 2412-2462 MHz IEEE 802.11g: 2412-2462 MHz IEEE 802.11n: 2412-2462 MHz(HT 20), 2422-2452 MHz(HT 40)
Antenna Designation:	internal antennas BT WIFI antenna gain is 1.0dBi. WWAN antenna gain is -0.8dbi
Power supply:	DC 3.7V (Li-lion battery), DC 5V from adapter Adapter information: Model: SJ-0520-U Input: AC 100-240V, 50/60Hz, 0.3A Output: DC 5V, 2.0A

1.4 Statement

N.A.

1.5 Test Engineer

The sample tested by



Printed name: Jack Kang

2.0 Test equipments and Associated Equipment used during the test.

2.1 Test Equipments

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	July 3, 2014	July 2, 2015
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	July 3, 2014	July 2, 2015
Power Meter	Agilent	E4416A	MY45101555	July 3, 2014	July 2, 2015
Power Sensor	Agilent	E9327A	MY44421198	July 3, 2014	July 2, 2015
System Controller	CT	SC100	-	July 3, 2014	July 2, 2015
Spectrum Analyzer	ROHDE&SCHWARZ	FSEM	848597/001	July 3, 2014	July 2, 2015
Pre-amplifier	Teseq	LAN6900	--	July 3, 2014	July 2, 2015
Pre-amplifier	Agilent	8447D	83153007374	July 3, 2014	July 2, 2015
Pre-amplifier	Agilent	8449B	3008A01738	July 3, 2014	July 2, 2015
Loop antenna	A.R.A.	PLA-1030/B	1029	July 3, 2014	July 2, 2015
Horn Antenna	ETS LINDGREN	3117	--	July 3, 2014	July 2, 2015
Horn Antenna	ETS LINDGREN	3160	--	July 3, 2014	July 2, 2015
EMI Test Receiver	R&S	ESCS30	100139	July 2, 2014	July 1, 2015
LISN	AFJ	LS16C	16010222119	July 2, 2014	July 1, 2015
Coaxial Cable	TCT	N/A	N/A	July 2, 2014	July 1, 2015
Coaxial Cable	TCT	N/A	N/A	July 2, 2014	July 1, 2015
Coaxial cable	TCT	N/A	N/A	July 2, 2014	July 1, 2015
Coaxial Cable	TCT	N/A	N/A	July 2, 2014	July 1, 2015

2.2 AE used during the test

Equipment type	Manufacturer	Model
Notebook	Lenovo	G480

3.0 Technical Details

3.1 Summary of test results

The EUT has been tested according to the following specifications:		
Test Item	CFR 47 Section	Result
AC Power Line Conducted Emission	15.207(a)	Complies
Maximum Peak Output Power	15.247(b)(3)	Complies
6 dB bandwidth	15.247 (a)(2)	Complies
Maximum Power Density	15.247(e)	Complies
Band age Measurement	15.247 (d), 15.205 (a), 15.209 (a)	Complies
Radiated Emission	15.209	Complies
Antenna Requirement	15.203,15.247(c)	Complies
RF Exposure	15.247(b), 1.1307(b)	Complies

3.2 Test Standards

FCC Part 15:2013 Subpart C, Paragraph 15.247

KDB 558074 D01 DTS Meas Guidance v03r02

According to ANSI C63.4 standards, the test results are both the “worst case” and “worst setup” 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n(H20) and 13.5 Mbps for 802.11n(H40). Duty cycle setting during the transmission is 98.5% with maximum power setting for all modulations.

4.0 EUT Modification

No modification by Shenzhen TCT Testing Technology Co., Ltd.


5.0 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	MU
1.	Radio Frequency	$\pm 1 \times 10^{-9}$
2.	Temperature	$\pm 0.1^{\circ}\text{C}$
3.	Humidity	$\pm 1.0\%$
4.	RF power, conducted	$\pm 0.34\text{dB}$
5.	RF power density, conducted	$\pm 1.45\text{dB}$
6.	Spurious emissions, conducted	$\pm 3.70\text{dB}$
7.	All emissions, radiated	$\pm 4.50\text{dB}$

Note: 1) For IEEE 802.11b/g/n (HT 20): Low channel: 2412MHz, Middle channel: 2437MHz,
High channel: 2462MHz
For IEEE 802.11n (HT 40): Low channel: 2422MHz, Middle channel: 2437MHz,
High channel: 2452MHz

6.0 Power Line Conducted Emission Test

6.1 Schematics of the test




EUT: Equipment Under Test

6.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2009. The Frequency spectrum From 0.15MHz to 30MHz was investigated.

Test Voltage: 120V~, 60Hz EUT

Block diagram of Test setup



6.3 EUT Operating Condition

Operating condition is according to ANSI C63.10 -2009

- A Setup the EUT and simulators as shown on the following
- B Enable AF signal and confirm EUT active to normal condition

6.4 Test Equipment

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
EMI Test Receiver	R&S	ESCS30	100139	July 2, 2014	July 1, 2015
LISN	AFJ	LS16C	16010222119	July 2, 2014	July 1, 2015

6.5 Conducted Emission Limit

Frequency(MHz)	Class A Limits (dB μ V)		Class B Limits (dB μ V)	
	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level
0.15 ~ 0.50	79.0	66.0	66.0~56.0*	56.0~46.0*
0.50 ~ 5.00	73.0	60.0	56.0	46.0
5.00 ~ 30.00	73.0	60.0	60.0	50.0

Notes: 1. *Decreasing linearly with logarithm of frequency.
2. The tighter limit shall apply at the transition frequencies

6.6 Test specification:

Environmental conditions: Temperature: 23° C Humidity: 51% Atmospheric pressure: 103kPa

Frequency range: 0.15 MHz – 30 MHz

The test was carried out in the following operation mode(s):

- Tx mode

6.7 Test result

Min. limit margin >10 dB from 0.15MHz to 30MHz


The requirements are FULFILLED

Remarks: According to FCC part 15.207.

A Conducted Emission on Line Terminal of the power line (150kHz to 30MHz)

EUT Description:	TABLET PC
Operation Mode:	Charging+Tx mode
Tested By:	SKY
Test date:	Aug. 10, 2014

Start Frequency	Stop Frequency	Step	IF BW	Detector	Final M-Time
0.15MHz	30MHz	4.5KHz	10KHz	QP+AV	1s




Frequency (MHz)	Reading(dB μ V)				Limit (dB μ V)	
	Live		Neutral			
	Quasi-peak	Average	Quasi-peak	Average		
0.1655	46.81	25.97	--	--	65.18	55.18
0.2359	41.71	26.51	--	--	62.24	52.24
0.5757	36.87	28.77	--	--	56.00	46.00
1.3375	34.06	27.70	--	--	56.00	46.00
4.6953	31.08	26.35	--	--	56.00	46.00
27.7422	23.14	17.22	--	--	60.00	50.00

B Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT Description:	TABLET PC
Operation Mode:	Charging+Tx mode
Tested By:	SKY
Test Date:	Aug. 10, 2014

Start Frequency	Stop Frequency	Step	IF BW	Detector	Final M-Time
0.15MHz	30MHz	4.5KHz	10KHz	QP+AV	1s


80.0 dB μ V



Frequency (MHz)	Reading(dB μ V)				Limit (dB μ V)	
	Live		Neutral		(dB μ V)	
	Quasi-peak	Average	Quasi-peak	Average		
0.1500	--	--	47.71	39.71	65.99	55.99
0.1695	--	--	46.42	32.06	64.98	54.98
0.1969	--	--	41.32	23.54	63.74	53.74
0.7632	--	--	36.65	28.01	56.00	46.00
1.7320	--	--	30.23	19.36	56.00	46.00
4.0586	--	--	32.86	22.65	56.00	46.00

7.0 Maximum Peak Output Power

7.1 Test Setup



7.2 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.

7.3 Test Procedure

1. The testing follows FCC KDB Publication NO558074 (Measurement Guidance of DTS)
2. The RF output of EUT was connected to the power meter by a low loss cable
3. Measure the power by power meter
4. Use the data rate as follows in maximum transmit power: 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n(H20) and 13.5 Mbps for 802.11n(H40)

7.4 Test Equipment:

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
Power Meter	Agilent	E4416A	MY45101555	July 3, 2014	July 2, 2015
Power Sensor	Agilent	U2021XA	MY53480008	July 3, 2014	July 2, 2015

7.5 Test Result

Configuration IEEE 802.11b

Test channel	Conducted Power (dBm)	Limit (dBm)	Result
Lowest	17.98	30	Pass
Middle	18.04	30	
Highest	18.45	30	

Configuration IEEE 802.11g

Test channel	Conducted Power (dBm)	Limit (dBm)	Result
Lowest	19.04	30	Pass
Middle	20.63	30	
Highest	19.58	30	

Configuration IEEE 802.11n


Test channel	Conducted Power (dBm)	Limit (dBm)	Result
Lowest	19.07	30	Pass
Middle	20.35	30	
Highest	19.76	30	

Configuration IEEE 802.11n(40MHz)

Test channel	Conducted Power (dBm)	Limit (dBm)	Result
Lowest	16.95	30	Pass
Middle	19.14	30	
Highest	17.19	30	

8.0 6dB Bandwidth Measurement

8.1 Test Setup



8.2 Limits of 6dB Bandwidth Measurement

The minimum of 6 dB Bandwidth is >500 kHz

8.3 Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02, the transmitter output was connected to the spectrum analyzer through an attenuator. The spectrum analyzer is setting as follows: RBW=100 kHz, VBW=300 kHz, Detector=Peak, Trace mode=max hold, Sweep=auto couple. The 6dB bandwidth is defined as the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

8.4 Test Equipment:

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
Spectrum Analyzer	ROHDE&SCHWARZ	FSU	1166.1660.03	July 3, 2014	July 2, 2015

8.5 Test Result


Antenna 1:

IEEE 802.11b mode			
Test channel	6 dB occupied bandwidth (MHz)	Limit (kHz)	Result
Lowest	10.048	500	Pass
Middle	10.048	500	Pass
Highest	10.096	500	Pass
IEEE 802.11g mode			
Test channel	6 dB occupied bandwidth (MHz)	Limit (kHz)	Result
Lowest	15.962	500	Pass
Middle	16.010	500	Pass
Highest	15.865	500	Pass
IEEE 802.11n(HT 20) mode			
Test channel	6 dB occupied bandwidth (MHz)	Limit (kHz)	Result
Lowest	16.923	500	Pass
Middle	16.923	500	Pass
Highest	16.827	500	Pass
IEEE 802.11n(HT 40) mode			
Test channel	6 dB occupied bandwidth (MHz)	Limit (kHz)	Result
Lowest	35.256	500	Pass
Middle	35.497	500	Pass
Highest	35.497	500	Pass


Test plot :

Test Mode: IEEE 802.11b mode


Low channel



Middle channel




High channel




Test Mode: IEEE 802.11g mode


Low channel



Middle channel




High channel




Test Mode: IEEE 802.11n (HT 20) mode


Low channel



Middle channel




High channel




Test Mode: IEEE 802.11n(HT 40) mode


Low channel



Middle channel




High channel



9.0 Power Spectral Density Measurement

9.1 Test Setup



9.2 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density is 8 dBm in any 3 kHz.

9.3 Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02, the transmitter output was connected to the spectrum analyzer through an attenuator.

The spectrum analyzer is setting as follows:

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the *DTS bandwidth*.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

9.4 Test Equipment:

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
Spectrum Analyzer	ROHDE&SCHWARZ	FSU	1166.1660.03	July 3, 2014	July 2, 2015


9.5 Test Result

IEEE 802.11b	Peak Power Spectral Density (dBm)	Limit (dBm)	Result
Test channel			
Lowest	-7.70	8	Pass
Middle	-7.96	8	Pass
Highest	-8.39	8	Pass
IEEE 802.11g	Peak Power Spectral Density (dBm)	Limit (dBm)	Result
Test channel			
Lowest	-13.34	8	Pass
Middle	-12.44	8	Pass
Highest	-12.56	8	Pass
IEEE 802.11n	Peak Power Spectral Density (dBm)	Limit (dBm)	Result
Test channel			
Lowest	-14.53	8	Pass
Middle	-11.61	8	Pass
Highest	-12.27	8	Pass
IEEE 802.11n(40M)	Peak Power Spectral Density (dBm)	Limit (dBm)	Result
Test channel			
Lowest	-19.39	8	Pass
Middle	-18.25	8	Pass
Highest	-19.69	8	Pass


Test plots:

Test Mode: IEEE 802.11b mode


Low channel



Middle channel




High channel




Test Mode: IEEE 802.11g mode


Low channel



Middle channel




High channel




Test Mode: IEEE 802.11n (HT 20) mode


Low channel



Middle channel




High channel




Test Mode: IEEE 802.11n(HT 40) mode


Low channel



Middle channel



High channel



10.0 Band-edge Measurement

10.1 Test Equipment

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
Spectrum Analyzer	ROHDE&SCHWARZ	FSU	1166.1660.03	July 3, 2014	July 2, 2015
Pre-amplifier	Agilent	8449B	3008A01738	July 2, 2014	July 1, 2015
Horn Antenna	ETS LINDGREN	3117	--	July 1, 2014	July 1, 2015

10.2 Test specification:

Environmental conditions: Temperature 23° C Humidity: 54% Atmospheric pressure: 102kPa

10.3 Limit:

Radiated emissions which fall in the restricted bands, as defined in section 15.205(a), must also comply with The radiated emission limits specified in 15.209(a)

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (*i.e.*, 20 dBc).
- If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (*i.e.*, 30 dBc).
- In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

10.4 Test Procedure

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW $\geq 3 \times$ RBW.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.


10.5 Test Result:

Conducted Emission Method

Test plots:

Test Mode: IEEE 802.11b mode

Low channel




High channel




Test Mode: IEEE 802.11g mode

Low channel




High channel




Test Mode: IEEE 802.11n (HT 20) mode

Low channel




High channel




Test Mode: IEEE 802.11n (HT 40) mode

Low channel




High channel



11.0 Spurious Emission Test

11.1 Conducted emissions Measurement

11.1.1 Test configuration



11.1.2 Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

11.1.3 Test procedure:

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site. The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz. Measurements are made over the 30MHz to 25 GHz range with the transmitter set to the lowest, middle, and highest channels.

11.1.4 Test Equipment

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
Spectrum Analyzer	ROHDE&SCHWARZ	FSEM	848597/001	July 3, 2014	July 2, 2015

11.1.5 Test Result:


Test plots please refer to next pages.

Note: 1. Conducted emissions measurements below 30 MHz were made, and the maximum peak was detected, which is much less the limit. So it is not submitted in the report.

Test plots:


Test Mode: IEEE 802.11b mode

Low channel




Note: Sweep points=1001pts

Middle channel



Note: Sweep points=1001pts


High channel



Note: Sweep points=1001pts


Test Mode: IEEE 802.11g mode

Low channel




Note: Sweep points=1001pts

Middle channel



Note: Sweep points=1001pts


High channel



Note: Sweep points=1001pts


Test Mode: IEEE 802.11n(HT 20) mode

Low channel




Note: Sweep points=1001pts

Middle channel



Note: Sweep points=1001pts


High channel



Note: Sweep points=1001pts


Test Mode: IEEE 802.11n(HT 40) mode

Low channel




Note: Sweep points=1001pts

Middle channel



Note: Sweep points=1001pts

High channel




Note: Sweep points=1001pts

11.2 Radiated emissions Measurement


11.2.1 Test Method and test Procedure:

- 1) The EUT was tested according to ANSI C63.10 –2009.
- 2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2009.
- 3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz quasi-peak values with a resolution bandwidth of 120 kHz.
All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz . Measurements were made at 3 meters.
Set the spectrum as follows:
 - 1): Peak: RBW=1MHz, VBW=1MHz, Sweep=Auto
 - 2): Average: RBW=1MHz, VBW=10Hz, Sweep=Auto
- 4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- 5) The antenna polarization: Vertical polarization and Horizontal polarization.


Block diagram of Test setup



Block diagram of Test setup for frequency below 30MHz



Block diagram of Test setup for frequency above 1GHz



11.2.2 EUT Operating Condition

Operating condition is according to ANSI C63.10 -2009

11.2.3 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.209.

Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/m)
0.009-0.490	3	$20\log 2400/F$ (kHz) + 80
0.490-1.705	3	$20\log 24000/F$ (kHz) + 40
1.705-30	3	$20\log 30$ + 40
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

- Note:
- 1) RF Voltage (dBuV) = 20 log RF Voltage (uV)
 - 2) In the Above Table, the tighter limit applies at the band edges.
 - 3) Distance refers to the distance in meters between the measuring instrument antenna and the EUT
 - 4) This is a handheld device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.
 - 5) All scanning using PK detector. And the final emission level was get using QP detector for frequency range from 30-1000MHz. As to 1G-25G, the final emission level got using PK and AV detector.
 - 6) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula $Ld1 = Ld2 * (d2/d1)$
 - 7) The DTS rules specify that emissions which fall into restricted frequency bands shall comply with the general radiated emission limits.9

11.2.4 Test Equipment:

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	July 3, 2014	July 2, 2015
Spectrum Analyzer	ROHDE&SCHWARZ	FSEM	848597/001	July 3, 2014	July 2, 2015
Pre-amplifier	Teseq	LNA6900	--	July 3, 2014	July 2, 2015
Pre-amplifier	Agilent	8447D	83153007374	July 3, 2014	July 2, 2015
Pre-amplifier	Agilent	8449B	3008A01738	July 3, 2014	July 2, 2015
Loop antenna	A.R.A.	PLA-1030/B	1029	July 3, 2014	July 2, 2015
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	July 3, 2014	July 2, 2015
Horn Antenna	ETS LINDGREN	3117	--	July 3, 2014	July 2, 2015
Horn Antenna	ETS LINDGREN	3160	--	July 3, 2014	July 2, 2015

11.2.5 Test specification:

Environmental conditions: Temperature 22° C Humidity: 51% Atmospheric pressure: 103kPa

11.2.6 Test result

A Radiated Emission (9 kHz---30 MHz)

Note: 1) Emission Level=Reading+ Cable loss+ Antenna factor-Amp factor
2) The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement


Result: Pass

Frequency (MHz)	Level@3m (dB μ V/m)	Limit@3m (dB μ V/m)
--	--	--
--	--	--
--	--	--
--	--	--

B General Radiated Emissions Data


Please refer to following diagram for individual

Radiated Emission In Horizontal (30MHz----1000MHz)



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1	*	30.0000	32.73	-12.50	20.23	40.00	-19.77	peak	0	
2		46.7077	31.02	-11.30	19.72	40.00	-20.28	peak	0	
3		74.7934	30.08	-16.41	13.67	40.00	-26.33	peak	0	
4		100.4712	29.09	-10.88	18.21	43.50	-25.29	peak	0	
5		138.8120	32.36	-14.93	17.43	43.50	-26.07	peak	0	
6		531.2910	26.83	-1.70	25.13	46.00	-20.87	peak	0	

Radiated Emission In Vertical (30MHz----1000MHz)



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	dBuV	Factor	ment	dBuV/m	dB	Height	Degree	Comment
1		37.5648	37.99	-13.29	24.70	40.00	-15.30	peak	0	
2		50.8172	38.22	-13.04	25.18	40.00	-14.82	peak	0	
3	*	83.1076	44.36	-16.62	27.74	40.00	-12.26	peak	0	
4		124.9250	40.00	-16.44	23.56	43.50	-19.94	peak	0	
5		371.2680	34.91	-9.98	24.93	46.00	-21.07	peak	0	
6		827.1795	30.58	-3.68	26.90	46.00	-19.10	peak	0	

Note: Measurements were conducted in all three channels (high, middle, low) with IEEE 802.11b mode, IEEE 802.11g mode, IEEE 802.11n(HT20), IEEE 802.11n(HT40), and the worst case (high channel in IEEE 802.11b mode) was submitted only.

C Fundamental & Harmonics Radiated Emission Data (1000MHz-25000MHz)

IEEE 802.11b mode: Low channel: 2412 MHz									
Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emission Level		Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2389.78	H	74.20	---	-4.20	70.00	---	74.00	54.00	-4.00
2389.01	H	---	54.51	-4.20	---	50.31	74.00	54.00	-3.69
4824.00	H	51.20	---	-3.94	47.26	---	74.00	54.00	-6.74
7236.00	H	49.35	---	0.52	49.87	---	74.00	54.00	-4.13
---	---	---	---	---	---	---	---	---	---
2389.45	V	72.62	---	-4.20	68.42	---	74.00	54.00	-5.58
2388.36	V	---	54.71	-4.20	---	50.51	74.00	54.00	-3.49
4824.00	V	49.53	---	-3.94	45.59	---	74.00	54.00	-8.41
7236.00	V	44.00	---	0.52	44.52	---	74.00	54.00	-9.48
---	---	---	---	---	---	---	---	---	---

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak readings were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

IEEE 802.11b mode: Middle channel: 2437 MHz

Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emission Level		Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
4874.00	H	50.20	---	-3.98	46.22	---	74.00	54.00	-7.78
7311.00	H	48.31	---	0.57	48.88	---	74.00	54.00	-5.12
---	---	---	---	---	---	---	---	---	---
4874.00	V	51.42	---	-3.98	47.44	---	74.00	54.00	-6.56
7311.00	V	42.63	---	0.57	43.20	---	74.00	54.00	-10.8
---	---	---	---	---	---	---	---	---	---

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak readings were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

IEEE 802.11b mode: High channel: 2462 MHz

Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emission Level		Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2483.82	H	72.42	---	-2.38	70.04	---	74.00	54.00	-3.96
2483.24	H	---	51.79	-2.38	---	49.41	74.00	54.00	-4.59
4924.00	H	72.03	---	-3.98	68.36	---	74.00	54.00	-5.64
7386.00	H	47.29	---	0.57	47.86	---	74.00	54.00	-6.14
---	---	---	---	---	---	---	---	---	---
2493.51	H	73.10	---	-2.38	70.72	---	74.00	54.00	-3.28
2493.51	H	---	52.51	-2.38	---	50.13	74.00	54.00	-3.87
4924.00	V	52.70	---	-3.98	48.72	---	74.00	54.00	-5.28
7386.00	V	48.32	---	0.57	48.89	---	74.00	54.00	-5.11
---	---	---	---	---	---	---	---	---	---

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak readings were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

IEEE 802.11g mode: Low channel: 2412 MHz

Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emission Level		Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2379.35	H	70.15	---	-4.20	65.95	---	74.00	54.00	-8.05
2379.35	H	---	54.51	-4.20	---	50.31	74.00	54.00	-3.69
4824.00	H	50.32	---	-3.94	46.38	---	74.00	54.00	-7.62
7236.00	H	46.57	---	0.52	47.09	---	74.00	54.00	-6.91
---	---	---	---	---	---	---	---	---	---
2388.00	V	73.97	---	-4.20	69.77	---	74.00	54.00	-4.23
2388.00	V	---	53.10	-4.20	---	48.9	74.00	54.00	-5.10
4824.00	V	48.82	---	-3.94	44.88	---	74.00	54.00	-9.12
7236.00	V	44.31	---	0.52	44.83	---	74.00	54.00	-9.17
---	---	---	---	---	---	---	---	---	---

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak readings were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

IEEE 802.11g mode: Middle channel: 2437 MHz									
Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emission Level		Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
4874.00	H	51.33	---	-3.98	47.35	---	74.00	54.00	-6.65
7311.00	H	47.21	---	0.57	47.78	---	74.00	54.00	-6.22
---	---	---	---	---	---	---	---	---	---
4874.00	V	51.16	---	-3.98	47.18	---	74.00	54.00	-6.82
7311.00	V	44.21	---	0.57	44.78	---	74.00	54.00	-9.22
---	---	---	---	---	---	---	---	---	---

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak readings were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

IEEE 802.11g mode: High channel: 2462 MHz

Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emission Level		Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2489.55	H	71.32	---	-2.38	68.94	---	74.00	54.00	-5.06
2489.55	H	---	50.31	-2.38	---	47.93	74.00	54.00	-6.07
4924.00	H	72.67	---	-3.98	68.69	---	74.00	54.00	14.69
7386.00	H	47.28	---	0.57	47.85	---	74.00	54.00	-6.15
---	---	---	---	---	---	---	---	---	---
2493.51	H	71.03	---	-2.38	68.65	---	74.00	54.00	-5.35
2493.51	H	---	49.32	-2.38	---	46.94	74.00	54.00	-7.06
4924.00	V	51.29	---	-3.98	47.31	---	74.00	54.00	-6.69
7386.00	V	44.32	---	0.57	44.89	---	74.00	54.00	-9.11
---	---	---	---	---	---	---	---	---	---

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak readings were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

IEEE 802.11n(20MHz) mode: Low channel: 2412 MHz

Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emission Level		Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2386.08	H	71.00	---	-4.20	66.8	---	74.00	54.00	-7.2
2386.08	H	---	50.28	-4.20	---	46.08	74.00	54.00	-7.92
4824.00	H	51.28	---	-3.94	47.34	---	74.00	54.00	-6.66
7236.00	H	47.20	---	0.52	47.72	---	74.00	54.00	-6.28
---	---	---	---	---	---	---	---	---	---
2379.35	V	73.42	---	-4.20	69.22	---	74.00	54.00	-4.78
2379.35	V	---	50.28	-4.20	---	46.08	74.00	54.00	-7.92
4824.00	V	46.11	---	-3.94	42.17	---	74.00	54.00	-11.83
7236.00	V	43.37	---	0.52	43.89	---	74.00	54.00	-10.11
---	---	---	---	---	---	---	---	---	---

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak readings were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

IEEE 802.11n(20MHz) mode: Middle channel: 2437 MHz									
Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emission Level		Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
4874.00	H	51.32	---	-3.98	47.34	---	74.00	54.00	-6.66
7311.00	H	47.62	---	0.57	48.19	---	74.00	54.00	-5.81
---	---	---	---	---	---	---	---	---	---
4874.00	V	54.02	---	-3.98	50.04	---	74.00	54.00	-3.96
7311.00	V	41.82	---	0.57	42.39	---	74.00	54.00	-11.61
---	---	---	---	---	---	---	---	---	---

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak readings were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

IEEE 802.11n(20MHz) mode: High channel: 2462 MHz									
Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emission Level		Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2480.05	H	70.10	---	-2.38	67.72	---	74.00	54.00	-6.28
2480.05	H	---	50.09	-2.38	---	47.71	74.00	54.00	-6.29
4924.00	H	52.03	---	-3.98	48.05	---	74.00	54.00	-5.95
7386.00	H	47.29	---	0.57	47.86	---	74.00	54.00	-6.14
---	---	---	---	---	---	---	---	---	---
2493.51	H	72.30	---	-2.38	69.92	---	74.00	54.00	-4.08
2493.51	H	---	50.37	-2.38	---	47.99	74.00	54.00	-6.01
4924.00	V	50.42	---	-3.98	46.44	---	74.00	54.00	-7.56
7386.00	V	47.28	---	0.57	47.85	---	74.00	54.00	-6.15
---	---	---	---	---	---	---	---	---	---

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak readings were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

IEEE 802.11n(40MHz) mode: Low channel: 2422 MHz

Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emission Level		Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2380.65	H	74.20	---	-4.20	70.00	---	74.00	54.00	-4.00
2380.65	H	---	54.51	-4.20	---	50.31	74.00	54.00	-3.69
4844.00	H	51.20	---	-3.94	47.26	---	74.00	54.00	-6.74
7266.00	H	49.35	---	0.52	49.87	---	74.00	54.00	-4.13
---	---	---	---	---	---	---	---	---	---
2389.45	V	72.62	---	-4.20	68.42	---	74.00	54.00	-5.58
2389.45	V	---	54.71	-4.20	---	50.51	74.00	54.00	-3.49
4844.00	V	49.53	---	-3.94	45.59	---	74.00	54.00	-8.41
7266.00	V	44.00	---	0.52	44.52	---	74.00	54.00	-9.48
---	---	---	---	---	---	---	---	---	---

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak readings were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

IEEE 802.11n(40MHz) mode: Middle channel: 2437 MHz									
Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emission Level		Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
4874.00	H	51.30	---	-3.98	46.22	---	74.00	54.00	-7.78
7311.00	H	48.31	---	0.57	48.88	---	74.00	54.00	-5.12
---	---	---	---	---	---	---	---	---	---
4874.00	V	50.32	---	-3.98	46.34	---	74.00	54.00	-7.66
7311.00	V	41.63	---	0.57	42.20	---	74.00	54.00	-11.8
---	---	---	---	---	---	---	---	---	---

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak readings were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

IEEE 802.11n(40MHz): High channel: 2452 MHz									
Freq. (MHz)	Ant. Pol. H/V	Peak reading (dBuV)	AV reading (dBuV)	Correction Factor (dB)	Emission Level		Peak limit (dBuV/m)	AV limit (dBuV/m)	Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)			
2486.08	H	71.52	---	-2.38	69.14	---	74.00	54.00	-4.86
2486.08	H	---	50.66	-2.38	---	48.28	74.00	54.00	-5.72
4904.00	H	53.09	---	-3.98	49.11	---	74.00	54.00	-4.89
7356.00	H	47.14	---	0.57	47.71	---	74.00	54.00	-6.29
---	---	---	---	---	---	---	---	---	---
2498.40	H	73.25	---	-2.38	70.87	---	74.00	54.00	-3.13
2498.40	H	---	51.00	-2.38	---	48.62	74.00	54.00	-5.38
4904.00	V	52.17	---	-3.98	48.19	---	74.00	54.00	-5.81
7356.00	V	46.39	---	0.57	46.96	---	74.00	54.00	-7.04
---	---	---	---	---	---	---	---	---	---

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak readings were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

12.0 Antenna Requirement

12.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

12.2 Antenna Specification

According to the manufacturer declared, the EUT has internal antennas; the directional gain of BT WIFI antenna is 1.0dBi, the WWAN antenna is -0.8dBi, and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.



****END OF REPORT****