

RF Exposure evaluation

FCCID:2ACXFRB-T11C

According to 447498 D01 General RF Exposure Guidance v06

4.3. General SAR test exclusion guidance

4.3.1. Standalone SAR test exclusion considerations

- a) For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following: $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR,³⁰ where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation³¹
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

³⁰ This is equivalent to the formula written as: $[(\text{max. power of channel, including tune-up tolerance, mW}) / (60 / \sqrt{f(\text{GHz})} \text{ mW})] \cdot [20 \text{ mm} / (\text{min. test separation distance, mm})] \leq 1.0$ for 1-g SAR; also see Appendix A for approximate exclusion threshold numerical values at selected frequencies and distances.

$$\text{eirp} = \text{pt} \times \text{gt} = (\text{EXd})^2 / 30$$

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- $10((\text{dBuV/m})/20)/10^6$

d = measurement distance in meters (m)---3m

$$\text{So pt} = (\text{EXd})^2 / 30 \times \text{gt}$$

RF Exposure evaluation

Copied from the FCC test report: 9.4 Summary of Test Results/Plots

Test Result:

For GFSK

Channel	Frequency MHz	Measured Value dBm	Output Power mW	Limit mW
Low Channel	2402	0.78	1.20	1000
Middle Channel	2441	1.51	1.41	1000
High Channel	2480	-1.14	0.77	1000

For Pi/4 QDPSK

Channel	Frequency MHz	Measured Value dBm	Output Power mW	Limit mW
Low Channel	2402	-1.60	0.69	1000
Middle Channel	2441	-0.61	0.87	1000
High Channel	2480	-3.58	0.44	1000

For 8DPSK

Channel	Frequency MHz	Measured Value dBm	Output Power mW	Limit mW
Low Channel	2402	-1.36	0.73	1000
Middle Channel	2441	-0.18	0.96	1000
High Channel	2480	-3.17	0.48	1000

Note: the antenna gain of 1dBi less than 6dBi maximum permission antenna gain value based on

1 watt peak output power limit.

Then we choose Normal mode channel as the worst case of Maximum Peak Output Power:

Channel	Frequency MHz	Measured Value dBm	Output Power mW	Limit mW
Low Channel	2402	0.78	1.20	1000
Middle Channel	2441	1.51	1.41	1000
High Channel	2480	-1.14	0.77	1000

EIRP/ dBm= Conducted Max Output Power/ dBm+ Antenna gain /dBi.

Since the distance from the internal BT-antenna to the outer is more than 10mm, we choose the min. test separation distance = 5mm

General RF Exposure:

$$(1.20 \text{ mW })/5.0\text{mm}) \times \sqrt{2.402 \text{ GHz}} = 0.372$$

$$(1.41\text{mW })/5.0\text{mm}) \times \sqrt{2.441 \text{ GHz}} = 0.441$$

$$(0.77 \text{ mW })/5.0\text{mm}) \times \sqrt{2.480 \text{ GHz}} = 0.243$$

SAR requirement: S=3.0

General RF Exposure<3

Then SAR evaluation is not required