



Certificate of Acknowledgment

Customer : 茂傑

Product : 5G External Antenna Black Plastic
Housing 1.13 Black Cable L=75mm IPEX 1

Model :

Part Number : NF2-2Z0083-RS

Written By :

Issued Date : 2026/01/08

CUSTOMER

ENGINEER R&D DEPT	QUALITY DEPT	APPROVED

Free Walk

WRITTEN BY	ENGINEER R&D DEPT	APPROVED
shali.Chen	Bing. Yang	zhiyang. Tan

address:

221 No. 179, Section 1, Datong Road, Xizhi District, New Taipei City

.....

File Change History

Model							
Index	Change Type	Change Type	Change Date	Description of Changes	Revision	Version	Remarks

Number:QR-NF-001

Version : A1



Index

One、	Cover	• • • • •	1
Two、	Document change history	• • • • •	2
Three、	Index	• • • • •	3
Four、	Antenna basic parameters	• • • • •	4
Five、	Test Equipment & Conditions	• • • • •	5-7
Six、	Test Data	• • • • •	8-10
Seven、	Product Drawing	• • • • •	11-14
Eight、	Reliability Test Report	• • • • •	15-20
Nine、	Material Report List	• • • • •	21
Ten、	Manner of packing	• • • • •	22



Specification Sheet

Main teclmical specification	
Frequency Range (MHz)	5150-5850
Impedance	50
Peak Gain(dBi)	5±1
VSWR	≦2.0
Polarization	Linear, polarization
Average efficiency (%)	84%
Connector Type	IPXE 1
Physica Properties	
Cable	black
Packaging	PE bag
Storage Temp	-40℃~+70℃
Operating Temp	-10℃~+60℃



Test Equipment & Conditions


1. Network Analyzers :

Agilent 5071C

2. Communications Test Set:

Rohde & Schwarz CWM500

3. 3D Chamber Test System






宏信科技股份有限公司
HT-TECH CORPORATION

HT-TECH CORPORATION

Laboratory





CMW500






Test the darkroom





5.8G S Parameter



Test: *bing Yang*

Review: *zhi Yung. Tan*



5.8G Efficiency&Gain







Frequency/Mhz	Efficiency / %	MaxGain/dBi
5150	82.72	5.48
5200	85.21	5.33
5250	84.2	5.4
5300	85.6	5.37
5350	86.1	5.49
5400	84.57	5.4
5450	85.34	5.32
5500	84.33	5.66
5550	82.95	5.45
5600	85.23	5.39
5650	83.7	5.49
5700	81.29	5.39
5750	82.09	5.43
5800	85.34	5.5
5850	85.46	5.49

Test: *peng Yang*

Review: *zhiyung. Tan*




5.8G Directional map

Channel(MHz) 5 1 5 0	Channel(MHz) 5 5 0 0	Channel(MHz) 5 8 5 0
ZX-Plane Total	ZX-Plane Total	ZX-Plane Total
		
Phi 02D	Phi 90 2D	Theta 90 2D
		

Test: *heng Yang*

Review: *zhi Yung. Tan*




NOTE:


- . DIMENSIONS MARKED WITH * ARE THE KEY INSPECTION DIMENSIONS;
- . DIMENSIONS WITHOUT SPECIFIED TOLERANCES ARE INSPECTED WITH ± 0.15 .
- . UNMARKED DIMENSIONS SHOULD REFER TO THE DRAWING;
- . OTHER DIMENSIONS SHOULD BE BASED ON ACTUAL FIT.
- . WIRES SHOULD NOT HAVE SOLDER SLAG, SCRATCHES, ETC.;
- . WIRES WITH TERMINALS SHOULD PASS TESTING.
- . FINISHED PRODUCT SOLDER PADS SHOULD HAVE NO COLD SOLDER, SOLDER BRIDGES, ETC. ; FINISHED PRODUCTS SHOULD PASS CONTINUITY TESTING.
- . MATERIALS MUST COMPLY WITH ROHS 2.0 AND REACH AND OTHER ENVIRONMENTAL REGULATIONS.

SERIAL NUMBER	PRODUCT NAME	MATERIALS/SPECIFICATIONS	COLOR	QUANTITY	REMARKS
⑤	IPEX	IPEX-1	GOLDEN	1	
④	ROD SLEEVE	ABS	BLACK	1	
③	UPPER SOLID	ABS	BLACK	1	
②	LOWER SOLID	PC	BLACK	1	
①	RF CABLE	φ1.13 LINE	BLACK	1	

HT-TECH CORPORATION					
THIRD ANGLE PROJECTION		PROJECT	茂傑	DATE	2025-05-10
10以下	±0.10	NAME	5.8G - EXTERNAL ANTENNA	DESIGN	bing.Yang
10~20	±0.12	PART NUMBER	NF2-220083-RS	RADIO FREQUENCY	bing.Yang
20~40	±0.15	CUSTOMER PART NUMBER		REVIEW	zhiyang.Tan
40以上	±0.20				
REFER TO THE STANDARD FOR THE TOLERANCE OF THE ULTIMATE NOTE			單位	比例	FIT 版本 T:A



• • • • •



THIS DRAWING IS A CONTROLLED DOCUMENT FOR DUOYA ELECTRONICS CORPORATION